Diseño de Compiladores Luis Enrique Güitrón Leal A01018616 Profesor Victor de la Cueva

Proyecto 2 Parser

Gramática en EBNF

```
1. program \rightarrow declaration-list
2. declaration-list → declaration {declaration}
3. declaration \rightarrow var-declaration | fun-declaration
4. var-declaration → type-specifier ID [¥[NUM ¥]];
5. type-specifier → int | void
6. fun-declaration \rightarrow type-specifier ID \pm( params \pm) compound-stmt
7. params \rightarrow param-list | void
8. param-list \rightarrow param \{, param\}
9. param \rightarrow type-specifier ID [ Y[Y]]
10. compound-stmt \rightarrow  { local-declarations statement-list  }
11. local-declarations \rightarrow {var declaration}
12. statement-list \rightarrow {statement}
13. statement \rightarrow expression-stmt
                     | compound-stmt
                     | selection-stmt
                     | iteration-stmt
                     | return-stmt
14. expression-stmt → [expression];
15. selection-stmt \rightarrow if \forall (expression \forall) compound stmt [else compound stmt]
16. iteration-stmt \rightarrow while Y (expression Y) compound stmt
17. return-stmt → return [ expression ];
18. expression \rightarrow {var =} simple-expression
19. var \rightarrow ID [ \[ \] [ expression \[ \] ]
20. simple-expression \rightarrow additive-expression [ relop additive-expression ]
21. relop \rightarrow \langle = | \langle | \rangle | \rangle = | = | ! =
22. additive-expression \rightarrow term {addop term}
23. addop \rightarrow + | -
24. term \rightarrow factor {mulop factor}
25. mulop \rightarrow * |/
26. factor \rightarrow NUM | ( expression ) | call | var
```

```
27. call \rightarrow ID ( args )
```

28. args
$$\rightarrow$$
 arg-list | ϵ

29.
$$arg$$
-list \rightarrow expression $\{$, expression $\}$