

How to generate custom wordlists with HASHCAT / MASK PROCESSOR

Command 1:

```
mp64 -1 <charset> <pattern ?1 ?1> --output-file=custom_wordlist.txt
```

```
mp64 -1 0123456789ABCDEF 48BDCE?1?15314 --output-file=custom_wordlist.txt
```

Explanation:

- mp64: This tool generates wordlists based on mask patterns.
- -1 0123456789ABCDEF: Defines the custom character set for ?1 as 0123456789ABCDEF.
- 48BDCE?1?15314: The mask pattern where ?1 is replaced by characters from the defined custom set.
- --output-file=custom_wordlist.txt: Specifies the output file where the generated wordlist is saved.

Command 2:

```
hashcat --stdout -a 3 -1 <charset> <pattern ?1 ?1> > custom_wordlist.txt
```

```
hashcat --stdout -a 3 -1 0123456789ABCDEF 48BDCE?1?15314 > custom_wordlist.txt
```

Explanation:

- hashcat: A password recovery tool.
- --stdout: Outputs the generated wordlist directly to the console.
- -a 3: Specifies the attack mode as mask attack.
- -1 0123456789ABCDEF: Defines the custom character set for ?1 as 0123456789ABCDEF.
- 48BDCE?1?15314: The mask pattern where ?1 is replaced by characters from the defined custom set.
- > custom_wordlist.txt: Redirects the output to the file custom_wordlist.txt.

Both commands are used to generate wordlists based on specific mask patterns. The first command directly saves the output to a file using mp64, while the second uses hashcat and redirects the

output to a file.

The -1 option in both commands is not hardcoded; it is used to define a custom character set for a placeholder (e.g., ?1). Similarly, you can use other options like -2, -3, and -4 to define additional custom character sets for ?2, ?3, and ?4 respectively.

For your example:

```
mp64 -4 0123456789ABCDEF 48BDCE?4?45314 --output-file=custom_wordlist.txt
```

```
hashcat --stdout -a 3 -4 0123456789ABCDEF 48BDCE?4?45314 > custom_wordlist.txt
```