



GSC+ API

v 2.0.4

Version information.....	3
1. Summary.....	4
2.Single wallet.....	4
2.1 Balance.....	4
batch_requests.....	5
Data.....	6
2.2 Withdraw.....	7
Batch_Requests.....	8
Data.....	9
2.3 Deposit.....	10
Batch_Requests.....	11
Data.....	12
2.4 Push Bet Data.....	13
3.Operator (Operator).....	16
3.1 Launch Game (Launch Game)	16
3.2 Wager List (Wager List).....	18
3.3 Wager (Wager).....	20
3.4 Game List (Game List).....	21
3.5 Game History (Game History).....	24
3.6 Product List (Product List).....	24
3.7 Turn on Super Lobby.....	26
3.8 Create Free Round for Player.....	28
3.9 Cancel Free Round (CancelFreeRound).....	30
3.10 Get Player Free Round Bonus (GetPlayerFRB).....	32
3.11 Get Game Bet Scales(GetGamesBetScales).....	34
Appendix.....	37
Seamless wallet code.....	37
Carrier Code.....	37
Pagination.....	38
Game Type.....	38
Product Code.....	39
Transaction (Transaction).....	44
Wagers (Wagers)for Push Bet Data.....	45
Wager (Wager).....	46
Wager Status (Wager Status).....	47
Language Code (Language Code).....	48
Currency Code (Currency Code).....	50
Transaction Action Type (Transaction Action Type)	56
Games.....	58

Version information

Date	Version	Content
2024/10/20	v2.0.0	First version released
2024/11/25	v2.0.1	3.4 and 3.6 without size, the default is full display without paging.
2024/12/27	v2.0.1	Modify the request_time format for 2.1, 2.2, 2.3, and 2.4 .
2025/1/23	v2.0.2	A new round_id parameter has been added to the Transaction .
2025/4/21	v2.0.3	There has been an adjustment in API 2.4 Push Bet Data. The previously documented parameter "transactions" has been updated to "wagers" .
2025/7/14	v2.0.4	Added Operator FreeRound Feature.
2025/7/23	v2.0.4	Added Launch Game SABA quick betting component widget ID parameter

1. Summary

- Contact the GSC+ window and provide the following information when requesting a proxy connection
 - The currency the agent wishes to connect to (multiple currencies supported)
 - Platform server IP: API, BO
 - Agent name
 - callback URL
- After creating relevant information, provide the following information to the platform:
 - Operator code - A 4-character alphanumeric operator identification code (not case sensitive). (Agent code is a unique value for GSC+)
 - secret_key
 - operator_url
 - GSC+: <https://staging.gsimw.com>
 - Aurora Gaming: <https://staging-idr.pglsucs.com>

2. Single wallet

- All API requests will use the content-type header of application/json
- The time format for all requests will be a second timestamp with time zone GMT+8

2.1 Balance

Describe

Providers wishing to obtain the balance of a specific player will obtain it through this API. Operator-side API for Seamless Wallet to retrieve a specific player's balance for the provider

EndPoint

- POST `{{callback_url}}/v1/api/seamless/balance`

Parameter

Parameter	Type	Introduce
batch_requests	[]batch_requests	request information
operator_code	string	The unique identifier of the operator as the username to log in to the backend.
currency	string	refer to Currency Code
sign	string	md5(operator_code + request_time + "getbalance" + secret_key) Example: MD5(ABCD + 1698219740 + getbalance + XXXX) * Signature verification tool https://testcase.gscplusmd.com/
request_time	string	timestamp of request time(Second)。

batch_requests

Parameter	Type	Introduce
member_account	string	The unique identifier of the member in the operator(Limit 50 characters)
product_code	int	Product's unique identifier. refer to Currency Code

Example

```
{
  "batch_requests": [
    {
      "member_account": "user1",
      "product_code": 1002
    },
    {
      "member_account": "user2",
      "product_code": 1020
    },
    {
      "member_account": "user3",
      "product_code": 1009
    }
  ],
  "operator_code": "ABCD",
  "currency": "CNY",
  "sign": "369af7416deef76a9cc4f019b8559f99",
}
```

```
}
  "request_time": "1694617425"
}
```

Response

Parameter	Type	Introduce
data	[]data	data

Data

Parameter	Type	Introduce
member_account	string	The unique identifier of the member in the operator(Limit 50 characters)
product_code	int	The unique identifier of the product. See Product Code
balance	float64	player balance (Support up to the fourth decimal place)
code	int	See Seamless wallet code
message	string	response message

Example

```
{
  "data": [
    {
      "member_account": "user1",
      "product_code": 1002,
      "balance": 12345,
      "code": 0,
      "message": ""
    },
    {
      "member_account": "user2",
      "product_code": 1020,
      "balance": 1000,
      "code": 0,

```

```

        "message":""
    },
    {
        "member_account":"user3",
        "product_code":1009,
        "balance":1000,
        "code":0,
        "message":""
    }
]

```

2.2 Withdraw

Describe

The API is used by Seamless Wallet on the operator side for players to place bets or similar deduction operations such as tips.

EndPoint

- POST `{{callback_url}}/v1/api/seamless/withdraw`

Parameter

Parameter	Type	Introduce
batch_requests	[]batch_requests	request information
operator_code	string	The unique identifier of the operator logged in as username bo
game_type	optional	Most values are empty (used in some cases).
currency	string	See Currency Code
sign	string	md5(operator_code + request_time + "withdraw" + secret_key) Example: md5(ABCD+ 1698219740 +withdraw+XXXX) * Signature verification tool https://testcase.gscplusmd.com/

request_time	string	timestamp of request time(Second)。
--------------	--------	------------------------------------

Batch_Requests

Parameter	Type	Introduce
member_account	string	The unique identifier of the member in the operator(Limit 50 characters)
product_code	int	The unique identifier of the product. See Product Code
game_type	string	See Game Type
transactions	[]Transaction	transactions

Example

```
{
  "batch_requests": [
    {
      "member_account": "user1",
      "Product_code": 1002,
      "game_type": "POKER",
      "transactions": [
        {
          "id": "23746",
          "action": "bet",
          "wager_code": "tZDwLV3ayzBeP4Nvwxhcti",
          "wager_status": "BET",
          "round_id": "95978",
          "channel_code": "gscp",
          "amount": 10,
          "bet_amount": 10,
          "valid_bet_amount": 10,
          "prize_amount": 0,
          "tip_amount": 0,
          "settled_at": 0,
          "game_code": "moreturkeyv10000",
          "round_id": "95978",
          "Channel_code": "gscp",
          "wager_type": "NORMAL"
        }
      ]
    }
  ],
  "operator_code": "ABCD",
}
```

```
"game_type": "",
"currency": "CNY",
"sign": "369af7416deef76a9cc4f019b8559f99",
"request_time": "1694617425"
}
```

Response

Parameter	Type	Introduce
data	[]data	data

Data

Parameter	Type	Introduce
member_account	string	The unique identifier of the member in the operator(Limit 50 characters)
product_code	int	The unique identifier of the product.See Product Code
before_balance	float64	Player balance before operation (Support up to the fourth decimal place)
balance	float64	Player balance after operation (Support up to the fourth decimal place)
code	int	See Seamless wallet code
message	string	response message

 **Does the transaction ID exist? If the tx_id exists in the carrier system and has been refunded before, please return the duplicate transaction**

Example

```
{
  "data": [
    {
      "member_account": "user1",
      "product_code": 1002,
      "before_balance": 12345,
      "Balance": 12340,
      "code": 0,
      "message": ""
    }
  ]
}
```

```
}  
    ]  
}
```

2.3 Deposit

Describe

The API is used by Seamless Wallet on the operator side for players to receive bonuses or similar incremental actions, such as giving credits based on the activities the player participates in.

Note:

1. You must accept settled deposits even if there are no bets, as some providers issue additional promotional bonuses. Rejecting settlements due to a lack of bets will result in players not receiving their bonus payouts.
2. The WBET product uses a special mechanism where winnings are not distributed via the /deposit API. Instead, the operator must handle the payout manually after receiving the /push-bet-data notification.

EndPoint

- POST `{{callback_url}}/v1/api/seamless/deposit`

Parameter

Parameter	Type	Introduce
batch_requests	[]batch_requests	request information
operator_code	string	The unique identifier of the operator logged in as username bo
currency	string	See Product Code
sign	string	md5(operator_code + request_time + "deposit" + secret_key) Example: md5(ABCD+ 1698219740 +deposit+XXXX) * Signature verification tool https://testcase.gscplusmd.com/

request_time	string	timestamp of request time(Second)。
--------------	--------	------------------------------------

Batch_Requests

Parameter	Type	Introduce
member_account	string	The unique identifier of the member in the operator(Limit 50 characters)
product_code	int	The unique identifier of the product. See Product Code
game_type	string	See Game Type
transactions	[]Transaction	trade

Example

```
{
  "batch_requests": [
    {
      "member_account": "user1",
      "Product_code": 1002,
      "game_type": "POKER",
      "transactions": [
        {
          "id": "23746",
          "action": "settled",
          "wager_code": "tZDwLV3ayzBeP4Nvwxhcti",
          "wager_status": "SETTLED",
          "amount": 10,
          "bet_amount": 10,
          "valid_bet_amount": 10,
          "prize_amount": 10,
          "tip_amount": 0,
          "settled_at": 1729134752372,
          "game_code": "moreturkeyv10000",
          "round_id": "95978",
          "Channel_code": "gscp",
          "wager_type": "NORMAL"
        }
      ]
    }
  ],
  "operator_code": "ABCD",
}
```

```
"currency": "CNY",
"sign": "369af7416deef76a9cc4f019b8559f99",
"request_time": "1694617425"
}
```

Response

Parameter	Type	Introduce
data	[]data	data

Data

Parameter	Type	Introduce
member_account	string	The unique identifier of the member in the operator(Limit 50 characters)
product_code	int	The unique identifier of the product. See Product Code
before_balance	float64	Player balance before operation (Support up to the fourth decimal place)
balance	float64	Player balance after operation (Support up to the fourth decimal place)
code	int	See Seamless wallet code
message	string	response message

💡 Does the transaction ID exist? If the id exists in the carrier system and has been refunded before, please return the duplicate transaction

Example

```
{
  "data": [
    {
      "member_account": "user1",
      "product_code": 1002,
      "before_balance": 12345,

```

```
    "balance":12340,
    "code":0,
    "message":""
  }
}
```

2.4 Push Bet Data

Describe

It is a seamless wallet API on the operator side, used to synchronize all data and status of bets.

EndPoint

- **POST** `{{callback_url}}/v1/api/seamless/pushbetdata`

Parameter

Parameter	Type	Introduce
operator_code	string	The unique identifier of the operator, used as the background login username.
wagers	wagers	wagers for this operation.
sign	string	md5(operator_code + request_time + “pushbetdata” + secret_key) Example: md5(ABCD+ 1698219740+pushbetdata+XXXX) * Signature verification tool https://testcase.gscplusmd.com/
request_time	string	timestamp of request time(Second)。

Example

```
String parseJS eval fails
```

```

{
  "operator_code": "CMUT_V2",
  "wagers": [
    {
      "member_account": "s0350",
      "bet_amount": "10",
      "valid_bet_amount": "10",
      "prize_amount": "10",
      "tip_amount": "0",
      "wager_type": "NORMAL",
      "wager_code": "tZDwLV3ayzBeP4Nvwxxhti",
      "wager_status": "SETTLED",
      "round_id": "95978",
      "channel_code": "gscp",
      "game_type": "POKER",
      "settled_at": 1697439181000,
      "created_at": 1697435181000,
      "payload": {
      },
      "product_code": "1001",
      "game_code": "1001",
      "currency": "CNY"
    },
    {
      "member_account": "s0351",
      "bet_amount": "100",
      "valid_bet_amount": "100",
      "prize_amount": "10",
      "tip_amount": "0",
      "wager_type": "NORMAL",
      "wager_code": "txDwLV5aazBeP4evwxhti",
      "wager_status": "SETTLED",
      "round_id": "95785",
      "game_type": "POKER",
      "settled_at": 1697439181000,
      "created_at": 1697438182000,
      "payload": {
      },
      "product_code": "1001",
      "game_code": "1001",
      "currency": "CNY"
    }
  ],
  "sign": "369af7416deef76a9cc4f019b8559f99",
  "request_time": "1694617425"
}

```

Response

Parameter	Type	Introduce
-----------	------	-----------

code	int	See Seamless wallet code
message	string	response message

Example

```
{
  "code": 0,
  "message": "",
}
```


3.Operator (Operator)

3.1 Launch Game (Launch Game)

EndPoint

- POST `{{operator_url}}/api/operators/launch-game`

Parameter

Parameter	Type	Introduce	Must
operator_code	String	The unique identifier of the operator, used as the background login user name.	Must
member_account	String	The unique identifier of the member in the operator.(Limit 50 characters)	Must
password	String	The member's password in the operator's system, used to verify identity.	Must
nickname	String	The member's nickname displayed in the game.	No
currency	String	The currency used by members in the game. Make sure the currency is supported by the provider. See Currency code	Must
game_code	String	A unique identifier within the game list API given by the provider. Required if the provider supports direct play, no otherwise.	Optional, depending on provider
product_code	int	The unique identifier of the product. See Product code	Must
game_type	String	See Game type	Must

language_code	String	The member's language code. See Language code .	No, default is 0
ip	String	The member's IP address.	Must
platform	String	platform type (SABA Sports Match Link Please select Widget)	Must. Enum includes WEB, DESKTOP, and MOBILE, Widget
widget_id	String	SABA Sports Quick Bet Widget ID. If a value is passed, the default card widget is obtained (staging environment classic widget ID: 1lx2FADe) Reference Documentation	No
is_widget_login	bool	SABA Sports Quick Bet Widget ID Login Status true = Login mode false or not provided = Non-login mode	No
sign	String	md5(request_time + secret_key + "launchgame" + operator_code) Example: md5(1694617425XXXXlaunchgameCMUT_V2) * Signature verification tool https://testcase.gscplusmd.com/	Must
request_time	int	timestamp of request time(Second) .	Must
operator_lobby_url	string	Client site URL	Must

Example

```
{
  "operator_code": "CMUT_V2",
  "member_account": "s0350",
  "password": "e10adc3949ba59abbe56e057f20f883e",
  "nickname": "test123",
  "currency": "IDR",
```

```

    "game_code":null,
    "product_code":1001,
    "game_type":"Slot",
    "language_code":0,
    "ip":"127.0.0.1",
    "platform":"WEB",
    "sign":"977e0ad6dd5c9f953a5b7681d2fa9fb8",
    "request_time":1694617425,
    "operator_lobby_url":"https://URL"
}

```

Response

Parameter	Type	Introduce
Code	int	See Carrier code
Message	string	error message
URL	string	The URL used to launch the game or provider's lobby.
Content	string	HTML content for displaying games from a specific provider

Example

```

{
    "code":200,
    "message":"",
    "url":"https://dev-test.spribe.io/games/launch/aviator?currency=USD&lang=EN&user=test9&operator=efinity&token=NCVKnX2cTPDDfLUfQ7UtXB"
}

```

3.2 Wager List (Wager List)

EndPoint

- GET `{{operator_url}}/api/operators/wagers`

Parameter

Parameter	Type	Introduce	Must
operator_code	string	The unique identifier of the operator, used as the background login username.	Must
start	int	The start time of the settlement time search range (Timestamp millisecond)。	Must
end	int	The end time of the settlement time search range (Timestamp millisecond)。	Must
offset	int	The starting record number for this capture.	No
size	int	The number of records fetched this time.	No (default=100)
sign	String	md5(request_time + secret_key + "getwagers" + operator_code) Example: md5(1694617425XXXXgetwagersCMUT_V2) * Signature verification tool https://testcase.gscplusmd.com/	Must
request_time	int64	Timestamp of request time.	Must

Example

https://example.com/api/operators/wagers?operator_code=E004&sign=xxxxxx&request_time=169155100?start=169155100000&end=169155100000

Response

Name	Type
wagers	Wager
pagination	Pagination

Example

```
{
  "wagers": [
    {
      "id": 3,
      "code": "e8bf16ae-07c8-4663-a22e-4e441f12e65e",
      "member_account": "test3",
      "round_id": "95978",
      "currency": "USD",
      "provider_id": 0,
      "provider_line_id": 0,
      "provider_product_id": 0,
      "provider_product_oid": 1138,
      "game_type": "poker",
      "game_code": "dice",
      "valid_bet_amount": 0.10,
      "bet_amount": 0.10,
      "prize_amount": 0,
      "status": "BET",
      "payload": null,
      "settled_at": 0,
      "created_at": 1691149098011,
      "updated_at": 1691149098011
    }
  ],
  "pagination": {
    "size": 1000,
    "total": 1234
  }
}
```

3.3 Wager (Wager)

EndPoint

- GET `{{opeartor_url}}/api/operators/wagers/{{id/code}}`

Parameter

Parameter	Type	Introduce	Must
operator_code	string	The unique identifier of the operator, used as the background login username.	Must
sign	String	md5(request_time + secret_key + "getwager" + operator_code)	Must

		Example: md5(1694617425XXXXgetwagerCMUT_V2) * Signature verification tool https://testcase.gscplusmd.com/	
request_time	int64	Timestamp of request time.	Must

Request

https://staging.effinitymd.com/api/operators/wagers/3?operator_code=E004&sign=xxxxxx&request_time=169155100

Response

Name	Type
wager	Wager

Example

```
{
  "wager": {
    "id": 3,
    "code": "e8bf16ae-07c8-4663-a22e-4e441f12e65e",
    "member_account": "test3",
    "round_id": "95978",
    "currency": "USD",
    "provider_id": 0,
    "provider_line_id": 0,
    "provider_product_id": 0,
    "provider_product_oid": 1138,
    "game_type": "poker",
    "game_code": "dice",
    "valid_bet_amount": 0.10,
    "bet_amount": 0.10,
    "prize_amount": 0,
    "status": "BET",
    "payload": null,
    "settled_at": 0,
    "created_at": 1691149098011,
    "updated_at": 1691149098011
  }
}
```

3.4 Game List (Game List)

Used to obtain all games that the operator has signed with GSC+. Only games with signed contracts will be displayed.

EndPoint

- GET `{{operator_url}}/api/operators/provider-games`

Parameter

Parameter	Type	Introduce	Must
product_code	int	The unique identifier of the product.	Must
operator_code	string	The unique identifier of the operator, used as the background login username.	Must
game_type	String	See Game Type	No
sign	String	md5(request_time + secret_key + "gamelist" + operator_code) Example: md5(1694617425XXXXgamelistCMUT_V2) * Signature verification tool https://testcase.gscplusmd.com/	Must
request_time	int64	Timestamp of request time.	Must
offset	int	The starting record number for this search.	No
size	int	The number of records retrieved this time.	No (if not included, all will be displayed)

Response

Scope	Type	Introduce
code	int	See operator code Operator Code
message	string	error message

provider_games	array	Reference game Games
pagination	object	Pagination

Response

```
{
  "code": 0,
  "message": "",
  "provider_games": [
    {
      "game_code": "aviator",
      "game_name": "Aviator",
      "game_type": "POKER",
      "image_url": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER/aviator.png",
      "product_id": 1,
      "product_code": 1138,
      "support_currency": "USD",
      "status": "ACTIVAT",
      "allow_free_round": true
      "lang_name": {
        "0": "Aviator",
        "1": "Aviator",
        "12": "Aviator",
        "2": "Aviator",
        "3": "Aviator",
        "33": "Aviator",
        "39": "Aviator",
        "4": "Aviator",
        "5": "Aviator",
        "6": "Aviator",
        "7": "Aviator",
        "9": "Aviator"},
      "lang_icon": {
        "0": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER/aviator.png",
        "1": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER/aviator.png",
        "12": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER/aviator.png",
        "2": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER/aviator.png",
        "3": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER/aviator.png",
        "33": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER/aviator.png",
        "39": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER/aviator.png",
      }
    }
  ]
}
```



```

"4": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER
/aviator.png",
"5": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER
/aviator.png",
"6": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER
/aviator.png",
"7": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER
/aviator.png",
"9": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER
/aviator.png"}},
{
  "game_code": "aviator",
  "game_name": "Aviator",
  "game_type": "POKER",
  "image_url": "https://images.gscplusmd.com/statics/staging/images/games
/1/POKER/aviator.png",
  "product_id": 1,
  "product_code": 1138,
  "support_currency": "IDR",
  "status": "ACTIVATED"
  "allow_free_round": true
  "lang_name": {
    "0": "Aviator",
    "1": "Aviator",
    "12": "Aviator",
    "2": "Aviator",
    "3": "Aviator",
    "33": "Aviator",
    "39": "Aviator",
    "4": "Aviator",
    "5": "Aviator",
    "6": "Aviator",
    "7": "Aviator",
    "9": "Aviator"}},
  "lang_icon": {
    "0": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER
/aviator.png",
    "1": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER
/aviator.png",
    "12": "https://images.gscplusmd.com/statics/staging/images/games/1/POKE
R/aviator.png",
    "2": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER
/aviator.png",
    "3": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER
/aviator.png",
    "33": "https://images.gscplusmd.com/statics/staging/images/games/1/POKE
R/aviator.png",
    "39": "https://images.gscplusmd.com/statics/staging/images/games/1/POKE
R/aviator.png",
    "4": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER
/aviator.png",
    "5": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER
/aviator.png",
    "6": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER
/aviator.png",
    "7": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER
/aviator.png",

```

```

        "9": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER/aviator.png"},
    },
    {
        "game_code": "dice",
        "game_name": "Dice",
        "game_type": "POKER",
        "image_url": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER/dice.png",
        "product_id": 1,
        "product_code": 1138,
        "support_currency": "USD",
        "status": "ACTIVATED"
        "allow_free_round": true
        "lang_name": {
            "0": "Dice",
            "1": "Dice",
            "12": "Dice",
            "2": "Dice",
            "3": "Dice",
            "33": "Dice",
            "39": "Dice",
            "4": "Dice",
            "5": "Dice",
            "6": "Dice",
            "7": "Dice",
            "9": "Dice"},
        "lang_icon": {
            "0": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER/Dice.png",
            "1": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER/Dice.png",
            "12": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER/Dice.png",
            "2": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER/Dice.png",
            "3": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER/Dice.png",
            "33": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER/Dice.png",
            "39": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER/Dice.png",
            "4": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER/Dice.png",
            "5": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER/Dice.png",
            "6": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER/Dice.png",
            "7": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER/Dice.png",
            "9": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER/Dice.png"},
        },
    },
    {
        "game_code": "dice",
        "game_name": "Dice",
        "game_type": "POKER",

```

```

        "image_url": "https://images.gscplusmd.com/statics/staging/images/games
        /1/POKER/dice.png",
        "product_id": 1,
        "product_code": 1138,
        "support_currency": "IDR",
        "status": "ACTIVATED"
        "allow_free_round": true
        "lang_name": {
            "0": "Dice",
            "1": "Dice",
            "12": "Dice",
            "2": "Dice",
            "3": "Dice",
            "33": "Dice",
            "39": "Dice",
            "4": "Dice",
            "5": "Dice",
            "6": "Dice",
            "7": "Dice",
            "9": "Dice"},

        "lang_icon": {
            "0": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER
            /Dice.png",
            "1": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER
            /Dice.png",
            "12": "https://images.gscplusmd.com/statics/staging/images/games/1/POKE
            R/Dice.png",
            "2": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER
            /Dice.png",
            "3": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER
            /Dice.png",
            "33": "https://images.gscplusmd.com/statics/staging/images/games/1/POKE
            R/Dice.png",
            "39": "https://images.gscplusmd.com/statics/staging/images/games/1/POKE
            R/Dice.png",
            "4": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER
            /Dice.png",
            "5": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER
            /Dice.png",
            "6": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER
            /Dice.png",
            "7": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER
            /Dice.png",
            "9": "https://images.gscplusmd.com/statics/staging/images/games/1/POKER
            /Dice.png"},

        }
    },
    "pagination": {
        "size": 10,
        "offset": 0,
        "total": "2000"
    }
}

```

3.5 Game History (Game History)

EndPoint

- GET `{{operator_url}}/api/operators/{wager_code}/game-history`

Parameter

Parameter	Type	Introduce	Must
operator_code	string	The operator's unique identifier, used as the backend login username.	Must
sign	String	md5(request time + secret_key + "gamehistory" + operator code) example : md5(1694617425XXXXproductlistCMUT_V2) * Signature verification tool https://testcase.gscplusmd.com/	Must
request_time	int64	Timestamp of request time.	Must

Response

<pre>{ "content": "https://" }</pre>
--

* The PG Soft product returns content in HTML format, and you will need to handle the display adjustment on your end.

3.6 Product List (Product List)

EndPoint

- GET `{{operator_url}}/api/operators/available-products`

Parameter

Parameter	Type	Introduce	Must
-----------	------	-----------	------

operator_code	string	The unique identifier of the operator, used as the background login username.	Must
sign	String	md5(request time + secret_key + "product list" + operator code) example : md5(1694617425XXXXproductlistCMUT_V2) * Signature verification tool https://testcase.gscplusmd.com/	No
request_time	int64	Timestamp of request time.	Must
offset	int	The starting record number obtained this time	No
size	int	The number of records obtained this time	No (if not included, all will be displayed)

Response

Parameter	Type	Introduce
provider	string	Provider's name
currency	string	currency code, see Currency code
status	string	product status
provider_id	int	Provider's unique identifier
product_id	int	product unique identifier
product_code	int	OID unique identifier of the product, see Product code
game_type	string	Game types in Seamless Games, see Game type
product_name	string	Provider's product name

Example

```

{
  "code":0,
  "message":"",
  "details":[
    {
      "provider":"SBO",
      "currency":"IDR2",
      "status":"MAINTAINED",
      "provider_id":2,
      "product_id":1190,
      "product_code":1012,
      "game_type":"POKER",
      "product_name":"sbo"
    },
    {
      "provider":"SBO",
      "currency":"IDR2",
      "status":"ACTIVATED",
      "provider_id":2,
      "product_id":1189,
      "product_code":1012,
      "game_type":"SPORT_BOOK",
      "product_name":"sbo"
    }
  ]
}

```

3.7 Turn on Super Lobby

**Please first ensure that you have completed the integration and docking of the single wallet API. Once completed, please contact us if you would like to connect with Super Lobby.*

EndPoint

- POST `{{operator_url}}/superlobby/launch`

Parameter

Parameter	Type	Introduce	Must
operator_code	String	The unique identifier of the operator, used as the background login username.	Must
member_account	String	The unique identifier of the member in the operator.	Must

nickname	String	The member's nickname displayed in the game.	Must
currency	String	The currency used by members in the game. Make sure the currency is supported by the provider. See Currency Code .	Must
language_code	String	The member's language code. See Language Code .	No, default is 0
platform	String	Platform Type	Must. Enum includes WEB, DESKTOP, and MOBILE.
sign	String	md5(request_time + secret_key + "launchsuperlobby" + operator_code) Example: md5(1694617425XXXXlaunchsuperlobbyCMUT_V2) * Signature verification tool https://testcase.gscplusmd.com/	Must
request_time	int	timestamp of request time (Second).	Must
type	int	Open lobby type	No, default 0: SUPER LOBBY 1: AURORA LIVE
operator_lobby_url	string	Client site URL	Must

Example

```
{
  "operator_code": "CMUT_V2",
  "member_account": "s0350",
  "currency": "IDR",
  "language_code": 0,
  "platform": "WEB",
  "sign": "fc607f037e87fbf9cfac419423e43144",
  "request_time": 1694617425,
  "type": 0,
```

```
}
  "operator_lobby_url": "https://test.com"
}
```

Respond

Parameter	Type	Introduce
url	string	The URL used to launch Super Lobby/Aurora LIVE.

Example

```
{
  "url": "https://lobby.gsimw.com/#/home?t=iQhpYErFQBm6Wqu8WL5abc"
}
```

3.8 Create Free Round for Player

Please ensure the Single Wallet API integration has been completed. If you wish to integrate the FreeRound feature, please contact us.

Endpoint

- POST `{{operator_url}}/api/operators/create-free-round`

Parameters

Parameter	Type	Description	Required
operator_code	String	Unique identifier of the operator (same as backend login username)	Yes
member_account	String	Unique member account identifier in the operator system (max 50 characters)	Yes
currency	String	Player's in-game currency. Make sure it is supported by the provider. See currency codes .	Yes
product_code	Integer	Product unique ID. See product code list .	Yes

game_type	String	See game types.	Yes
start_at	Integer	Free round start time (Unix timestamp)	Yes
end_at	Integer	Free round end time (Unix timestamp)	Yes
rounds	Integer	Number of free rounds	Yes
sign	String	Signature: md5(request_time + secret_key + "createfreeround" + operator_code) * Signature verification tool https://testcase.gscplusmd.com	Yes
request_time	Integer	Request timestamp (in seconds)	Yes
channel_code	String	Channel code, e.g., gscp	Yes
game_list	Array	List of games and corresponding bet values	Yes
game_list[].gameId	String	Unique game identifier	Yes
game_list[].betValues	Array	List of betting values. Refer to section 3.11 GetGamesBetScales	Yes
betValues.betPerLine	Float	Bet per line amount	Yes
betValues.currency	String	Currency used in the game	Yes

Example

```
{
  "operator_code": "CMUT_V2",
  "member_account": "s1023",
  "currency": "IDR",
  "product_code": 1006,
  "game_type": "SLOT",
  "start_at": 1752105600,
  "end_at": 1752940800,
  "rounds": 10,
  "game_list": [
    {
      "gameId": "vs20sugarrush",
      "betValues": [
        {
          "betPerLine": 0.05,
          "currency": "IDR"
        }
      ]
    }
  ]
}
```

```
],
"sign": "36227604e220ea0e2c8e806736f58401",
"request_time": 1752054762,
"channel_code": "gscp"
}
```

Response

Parameter	Type	SS
bonus_code	String	Unique FreeRound ID, can be referenced in wallet transaction via <code>Payload.bonus_code</code>

Example

```
{
  "bonus_code": "7dfc41a2-960e-4fd8-b812-6ebe9b194777"
}
```

3.9 Cancel Free Round (CancelFreeRound)

lease ensure the Single Wallet API integration has been completed. If you wish to integrate the FreeRound feature, please contact us.

Use this API to cancel a previously created FreeRound campaign by specifying the bonus_code.

EndPoint

- **POST** `{{operator_url}}/api/operators/cancel-free-round`

Parameters

Parameter	Type	Description	Required
operator_code	String	Operator's unique ID (backend login username)	Yes

currency	String	Player's game currency. Ensure it is supported by the provider	Yes
product_code	Integer	Product unique ID	Yes
bonus_code	String	Unique FreeRound ID (from section 3.8)	Yes
sign	String	Signature: md5(request_time + secret_key + "cancelfreeround" + operator_code) * Signature verification tool https://testcase.gscplusmd.com	Yes
request_time	Integer	Request timestamp (in seconds)	Yes
channel_code	String	VVVVVChannel code, e.g., gscp	Yes

Example

```
{
  "operator_code": "CMUT_V2",
  "currency": "IDR",
  "product_code": 1006,
  "game_type": "SLOT",
  "bonus_code": "10868087-1ef9-4b9d-bd62-7226cb26e7f4",
  "sign": "01ee0b21e2e127fa6df08ef4fc5129c5",
  "request_time": 1752054762,
  "channel_code": "gscp"
}
```

Response

Parameter	type	Description
bonus_code	string	FreeRound unique order number

例子

```
{
  "bonus_code": "7dfc41a2-960e-4fd8-b812-6ebe9b194777"
}
```

3.10 Get Player Free Round Bonus (GetPlayerFRB)

Please ensure the Single Wallet API integration has been completed. If you wish to integrate the FreeRound feature, please contact us.

This API retrieves a player's current FreeRound bonus information using their account and related identifiers.

EndPoint

- GET `{{operator_url}}/api/operators/get-player-frb`

Parameter

Parameter	Type	Description	Required
operator_code	String	Operator's unique identifier	Yes
member_account	String	Member's unique identifier (max 50 characters)	Yes
currency	String	Player's currency	Yes
product_code	Integer	Product ID	Yes
game_type	String	Game type	Yes

sign	String	Signature: md5(request_time + secret_key + "getplayersfrb" + operator_code) * Signature verification tool https://testcase.gscplusmd.com	Yes
request_time	Integer	Timestamp in seconds	Yes
channel_code	String	Channel code, e.g., gscp	Yes

Example

https://example.com/api/operators/get-player-frb?operator_code=CMUT_V2&member_account=s1023¤cy=IDR&product_code=1006&sign=22711668739a77102f4a5b54cd64d233&request_time=1752054762&channel_code=gscp&game_type=SLOT

回应

Parameter	Type	Description
bonuses	Array	List of Free Round bonus entries
bonuses.currency	String	Currency used by the player in-game. Ensure it is supported by the provider. See currency codes .
bonuses.gameIDList	String	List of unique game identifiers
bonuses.rounds	int	Total number of Free Rounds granted
bonuses.roundsPlayed	int	Number of Free Rounds that have been used
bonuses.bonus_code	String	Unique FreeRound order ID. Refer to section 3.8 Create Free Round
bonuses.expirationDate	String	The time when the free round expires (format: YYYY-MM-DD HH:mm).

Response

```

{
  "code": 0,
  "message": "",
  "bonuses": [
    {
      "currency": "IDR",
      "gameIDList": [
        "vs20sugarrush",
      ],
      "rounds": 10,
      "roundsPlayed": 0,
      "bonus_code": "7dfc41a2-960e-4fd8-b812-6ebe9b194777",
      "expirationDate": "2025-07-19 16:00"
    }
  ]
}

```

3.11 Get Game Bet Scales(GetGamesBetScales)

Please ensure the Single Wallet API integration has been completed. If you wish to integrate the FreeRound feature, please contact us.

Use this API to query supported bet configurations per game and currency.

EndPoint

- GET `{{operator_url}}/api/operators/get-bet-scales`

Parameters

Parameter	Type	Description	Required
operator_code	String	Operator's unique identifier	Yes
currency	String	Currency used in game. Must be supported by provider	Yes
product_code	Integer	Product unique ID	Yes
game_type	String	Game type	Yes
bet_game_list	String	Comma-separated game IDs (max 50). Commas must be URL encoded (%2C)	Yes

sign	String	Signature: md5(request_time + secret_key + "getbetscales" + operator_code) * Signature verification tool https://testcase.gscplusmd.com	Yes
request_time	Integer	Timestamp in seconds	Yes
channel_code	String	Channel code, e.g., gscp	Yes

Example

https://example.com/api/operators/get-bet-scales?operator_code=CMUT_V2¤cy=IDR&product_code=1006&bet_game_list=vs20olympgold&sign=0b98fd6db161704c6a476fbd1ac7d0fe&request_time=1752054762&channel_code=gscp&game_type=SLOT

Response

Parameter	Type	Description
betScales	Array	List of game bet scale configurations
betScales.gameID	String	Unique identifier of the game
betScales.betScaleList	Array	Currency-based bet scale configurations for the game
betScaleList.currency	String	Currency used by the player in-game. Ensure it is supported by the provider. See currency codes.
betScaleList.betPerLineScales	float	Array of bet amounts per line, sorted in ascending order
betScaleList.totalBetScales	float	Array of total bet amount options (currently empty)

Response

```
{
  "code": 0,
  "message": "",
  "betScales": [
```

```
{
  "gameID": "vs20olympgold",
  "betScaleList": [
    {
      "currency": "IDR",
      "betPerLineScales": [
        10,
        20,
        30,
        40,
        50,
        60,
        80,
        100,
        150,
        200,
        250,
        300,
        350,
        400,
        450,
        500,
        750,
        1000,
        1500,
        2000,
        2500,
        3000,
        4000,
        4500,
        5000,
        7500,
        10000,
        15000,
        20000,
        25000,
        30000,
        35000,
        40000,
        45000,
        50000,
        60000
      ],
      "totalBetScales": []
    },
  ],
}
```


Appendix

Seamless wallet code

Code	Describe
0	success
999	Internal Server Error
1000	API member does not exist
1001	API member balance is insufficient
1002	API proxy key error
1003	Duplicate API transactions
1004	API signature is invalid
1005	API not getting game list
1006	API bet does not exist
2000	API product is under maintenance

Carrier Code

Code	Describe
200	success
999	Internal Server Error
10002	Invalid parameter

Pagination

Name	Type	Describe
size	integer	The number of records you get
total	integer	Total number of records in a given time interval
offset	Integer	Start record number of this retrieval.

Game Type

Code	Describe
SLOT	Slot
LIVE_CASINO	Live Casino
SPORT_BOOK	Sport Book
VIRTUAL_SPORT	Virtual Sport
LOTTERY	Lottery
QIPAI	Qipai
P2P	P2P
FISHING	Fishing
COCK_FIGHTING	Cock Fighting
BONUS	Bonus

ESPORT	ESport
POKER	Poker
OTHERS	Others
LIVE_CASINO_PRE MIUM	Live Casino Premium

Product Code

ID	Code
1009	CQ9
1020	WM Casino
1022	Sexy_gaming
1033	SV388cockfighting
1050	PlayStar
1055	MrSlotty
1056	TrueLab
1058	BGaming
1060	Volt Entertainment
1062	Fazi
1064	Netgame
1065	Kiron
1067	RedRake

1070	Booongo
1080	Venus
1097	FuntaGaming
1098	Felix
1101	ZeusPlay
1102	KAGaming
1138	Spribe
1139	Fastspin
1149	AI Live Casino
1148	WOW Gaming
1006	Pragmatic Play
1011	Play Tech
1016	YeeBet
1091	Jili tcg
1018	live_22
1012	SBO
1052	DreamGaming
1085	JDB
1049	Evoplay
1153	Hacksaw
1154	Bigpot
1157	IMoon

1161	TADA
1166	NO LIMIT CITY (ASIA)
1167	BIG TIME GAMING (ASIA)
1172	WORLD ENTERTAINMENT
1183	FB SPORT
1152	1XBET
1168	Netent(ASIA)
1169	Red Tiger(ASIA)
1040	WBET
1184	RICH88
1079	Fachai
1046	IBC-SABA
1185	SA Gaming
1002	Evolution Gaming(ASIA)
1038	King855/CT855
1191	King855/CT855
1007	PG Soft
1156	Betfair
1158	Pascal Gaming
1004	BigGaming
1160	EPICWIN
1163	NOVOMATIC

1162	Octoplay
1165	aviatrix
1164	DIGITAIN
1170	smartsoft
1171	FIABLE GAMES
1173	Evolution (LATAM)
1174	Netent (LATAM)
1175	Red Tiger (LATAM)
1176	no limit city (LATAM)
1177	big time gaming(LATAM)
1115	BOOMING GAMES
1186	ENDORPHINA
1187	WINFINITY
1192	AMIGO GAMING
1193	FB Games
1197	Habanero
1194	PRETTY GAMING
1203	PlayAce
1221	SPADE GAMING
1204	ADVANTPLAY
1222	TF Gaming
1220	ASTAR

1205	AMBPOKER
1206	SlotXO(AMB)
1207	PG SOFT (AMB)
1225	JOKER
1229	PANDA SPORTS
1223	ALLBET
1224	GEMINI
1230	BETSOLUTIONS
1231	SIMPLE PLAY
1232	QQKENO
1233	NEX4D
1227	UG
1237	KAIYUANGAMING
1239	Hotdog
1228	CMD
1238	KA Gaming (Direct Line)
1007	PG Soft (THB)
1091	JE:JILI
1240	TCG SEA LOTTO
1241	TCG LOTTO
1244	BETBY
1242	PLAYTECH(Q6)

Transaction (Transaction)

Parameter	Type	Describe
id	string	Transaction ID
action	string	Transaction action type, Withdraw: Supported action types include BET,TIP,ROLLBACK,ADJUSTMEN T, etc. Deposit: Supported action types include SETTLED, JACKPOT, BONUS, PROMO, LEADERBOARD, ROLLBACK, CANCEL ,ADJUSTMENT, etc. Push Bet Data: Does not involve balance changes, only used for synchronizing bet data and status. referenceTransaction Action Type
amount	string	The amount needs to be changed to the player's wallet. Positive value indicates recharge, negative value indicates deduction.
currency	string	See Currency Code 。
valid_bet_amount	string	Effective bet amount
bet_amount	string	Bet amount
prize_amount	string	Payout amount
tip_amount	string	Tip amount
wager_code	string	Bet ID in Seamless
wager_status	string	bet status,reference bet status

round_id	string	Provider's turn ID in the game
payload	JSON	Provider transaction details
settled_at	int64	Reward time(timestamp)
product_code	int	Unique identifier for the product, see product code (Appears only with 2.4 PushBet)
game_code	string	Game Code (Required if the provider supports direct game entry; otherwise, null.)

Wagers (Wagers)for Push Bet Data

Parameter	Type	Describe
member_account	string	The account number of the member in the operator
bet_amount	decimal	Total bet amount.
valid_bet_amount	decimal	The effective bet amount actually deducted. May differ from bet amount
prize_amount	decimal	The player's winning amount. If the player lost, it is 0.
tip_amount	string	Tip amount
wager_type	string	Bet mark (bet=NORMALI , manual free spin=FREEROUND)
wager_code	string	Code for bet (for checking)
wager_status	string	bet status, see bet status
round_id	string	Provider's turn ID in the game
channel_code	string	Channel code, such as gscp
game_type	string	Game types in Seamless, see Game Type
settled_at	int64	Time when bets are settled

created_at	int64	The time the bet was created
payload	json	Some information about the provider
product_code	int	The OID unique identification of the product, see Product Code
game_code	string	Provider's game code (Required if the provider supports direct game entry; otherwise, null.)
currency	string	Currency code, see Currency Code

Wager (Wager)

Parameter	Type	Describe
id	id	ID of the bet (used for association)
wager_code	string	Code for bet (is wager_code for checking)
agent_code	string	The code for the agent in the operator
member_account	string	The account number of the member in the operator
round_id	string	Provider's turn ID in the game
currency	string	Currency code, see Currency Code
provider_id	int	Provider's unique identifier
provider_line_id	int	Product line unique identifier
povider_product_id	int	Product unique identifier
product_code	int	The OID unique identification of the product, see Product Code
product_name	int	Product Name
wager_type	string	Bet mark (bet=NORMALI , manual free spin=FREEROUND)
game_type	string	Game types in Seamless, see Game Type

game_code	string	Provider's game code (Required if the provider supports direct game entry; otherwise, null.)
valid_bet_amount	decimal	The effective bet amount actually deducted. May differ from bet amount
bet_amount	decimal	Total bet amount.
prize_amount	decimal	The player's winning amount. If the player lost, it is 0.
status	string	bet status, see bet statu
payload	json	Some information about the provider
settled_at	int64	Time when bets are settled
created_at	int64	The time the bet was created
updated_at	int64	When bets are updated

Wager Status (Wager Status)

State	Describe
BET	The bet is in the betting stage
BONUS	Multiple prizes are distributed in the same round
SETTLED	Bet settled
RESETTLED	Bets have been resettled
VOID	Bets are void

 **NOTE:** In some edge cases, transfer requests fitaction type “**RESETTLED**” , It is possible to cause a player's balance to become negative, such as a fractional change, which often occurs in sports betting games.

Language Code (Language Code)

State	Describe
0	English
1	Traditional Chinese
2	Simplify Chinese
3	Thai
4	Indonesia
5	Japanese
6	Korea
7	Vietnamese
8	Deutsch
9	Espanol
10	Francais
11	Russia
12	Portuguese
13	Burmese
14	Danish
15	Finnish
16	Italian
17	Dutch

18	Norwegian
19	Polish
20	Romanian
21	Swedish
22	Turkish
23	Bulgarian
24	Czech
25	Greek
26	Hungarian
27	Brazilian Portugese
28	Slovak
29	Georgian
30	Latvian
31	Ukrainian
32	Estonian
33	Filipino
34	Cambodian
35	Lao
36	Malay
37	Cantonese
38	Tamil
39	Hindi

40	European Spanish
41	Azerbaijani
42	Brunei Darussalam
43	Croatian

Currency Code (Currency Code)

Note: When the currency ratio is 1:1000, operators are required to perform the conversion themselves before responding with the balances. This is due to certain provider requirements, as the currency value is too small.

幣別 (Currency)	比例
AED	1:1
AFN	1:1
ALL	1:1
AMD	1:1
ANG	1:1
AOA	1:1
ARS	1:1
AUD	1:1
AWG	1:1
AZN	1:1
BAM	1:1
BBD	1:1
BDT	1:1
BDT2	1:1000
BGN	1:1
BHD	1:1
BIF	1:1
BMD	1:1
BND	1:1
BOB	1:1
BRL	1:1

BRL2	1:1000
BSD	1:1
BTC	1:1
BTN	1:1
BWP	1:1
BYN	1:1
BZD	1:1
CAD	1:1
CDF	1:1
CDF2	1:1000
CHF	1:1
CLF	1:1
CLP	1:1
CNY	1:1
CNY2	1:1000
COP	1:1
COP2	1:1000
CRC	1:1
CSD	1:1
CUC	1:1
CUP	1:1
CVE	1:1
CZK	1:1
DJF	1:1
DKK	1:1
DOGE	1:1
DOP	1:1
DZD	1:1
EGP	1:1
ERN	1:1
ETB	1:1
ETH	1:1
EUR	1:1
EUR2	1:1000
FJD	1:1

FKP	1:1
FRF	1:1
FTN	1:1
GBP	1:1
GC	1:1
GEL	1:1
GGP	1:1
GHS	1:1
GIP	1:1
GMD	1:1
GNF	1:1
GTQ	1:1
GYD	1:1
HKD	1:1
HKD2	1:1000
HNL	1:1
HRK	1:1
HTG	1:1
HUF	1:1
IDR	1:1
IDR2	1:1000
ILS	1:1
IMP	1:1
INR	1:1
INR2	1:1000
IQD	1:1
IRR	1:1
IRR2	1:1000
ISK	1:1
JEP	1:1
JMD	1:1
JOD	1:1
JPY	1:1
JPY2	1:1000
KES	1:1

KGS	1:1
KHR	1:1
KHR2	1:1000
KRW	1:1
KRW2	1:1000
KSH	1:1
KWD	1:1
KZT	1:1
LAK	1:1
LAK2	1:1000
LBP	1:1
LBP2	1:1000
LKR	1:1
LRD	1:1
LSL	1:1
LTC	1:1
LYD	1:1
MAD	1:1
MAD2	1:1000
MBTC	1:1
MDL	1:1
METH	1:1
MGA	1:1
MKD	1:1
MMK	1:1
MMK2	1:1000
MMK3	1:100
MNT	1:1
MNT2	1:1000
MOP	1:1
MRU	1:1
MVR	1:1
MWK	1:1
MXBT	1:1
MXN	1:1

MXN2	1:1000
MYR	1:1
MYR2	1:1000
MZN	1:1
NAD	1:1
NGN	1:1
NGN2	1:1000
NIO	1:1
NOK	1:1
NOT	1:1
NPR	1:1
NPR2	1:1000
NTD	1:1
NZD	1:1
OMR	1:1
PAB	1:1
PEN	1:1
PGK	1:1
PHP	1:1
PHP2	1:1000
PKR	1:1
PKR2	1:1000
PLN	1:1
PTI	1:1
PTV	1:1
PYG	1:1
PYG	1:1
PYG2	1:1000
QAR	1:1
RON	1:1
RSD	1:1
RUB	1:1
RWF	1:1
SAR	1:1
SBD	1:1

SC	1:1
SCR	1:1
SDG	1:1
SEK	1:1
SGD	1:1
SGD2	1:1000
SHP	1:1
SLL	1:1
SOS	1:1
SRD	1:1
SSP	1:1
STD	1:1
STN	1:1
SVC	1:1
SYP	1:1
SZL	1:1
THB	1:1
THB2	1:1000
TJS	1:1
TMT	1:1
TND	1:1
TON	1:1
TOP	1:1
TRY	1:1
TRY2	1:1000
TTD	1:1
TWD	1:1
TWD2	1:1000
TZS	1:1
TZS2	1:1000
UBTC	1:1
UGX	1:1
UGX2	1:1000
USD	1:1
USD2	1:1000

USDC	1:1
USDT	1:1
USDT2	1:1000
UXBT	1:1
UYU	1:1
UZS	1:1
UZS2	1:1000
VES	1:1
VND	1:1
VND2	1:1000
VUV	1:1
WST	1:1
XAF	1:1
XCD	1:1
XDR	1:1
XOF	1:1
XPF	1:1
YER	1:1
ZAR	1:1
ZMW	1:1
ZWL	1:1

Transaction Action Type (Transaction Action Type)

Action Code	Describe
BET	The transaction type for placing bets. The operator shall deduct the amount from the player's wallet.
FREEBET	Bonus deal type for free bets. Operators should increase the amount of players' wallets.

SETTLED	Bonus transaction type for win or draw. Operators should increase the amount of players' wallets.
ROLLBACK	Type of transaction to cancel bets and/or wins. When the amount is positive, the operator should increase the amount in the player's wallet, otherwise it should be deducted.
CANCEL	Cancel bet transaction type. Operators should increase the amount of players' wallets.
ADJUSTMENT	The type of transaction that adjusts the bet amount. When the amount is positive, the operator should increase the amount in the player's wallet, otherwise it should be deducted.
JACKPOT	Bonus transaction type for the jackpot. Operators should increase the amount of players' wallets.
BONUS	The type of transaction on which the bonus is placed. Operators should increase the amount of players' wallets.
TIP	The type of transaction in which the tip is placed. The operator shall deduct the amount from the player's wallet.
PROMO	The transaction type of event reward. Operators should increase the amount of players' wallets.
LEADERBOARD	The transaction type rewarded by the leaderboard event. Operators should increase the amount of players' wallets.
BET_PRESERVE	A type of transaction that reserves an amount of money before placing a bet, in case the player's balance is insufficient for subsequent bets. The operator shall deduct the amount from the player's wallet.
PRESERVE_REFUND	The transaction type that refunds the reserved amount. Operators should increase the amount of players' wallets.

Games

Description	Type	Description
game_code	string	Game code, used for launch game
game_name	string	Game name
game_type	string	Game type, see Game Type
product_id	int32	
product_code	int32	Id for each provider product, see Product Code
status	string	Current game status DEACTIVATED: Game is deactivated. Unable to launch ACTIVATED: Game is valid to launch MAINTAINED: game is under maintained.
support_currency	string	Support currency, related to currency that operator signed with GSC+.
allow_free_round	int	Whether manual Free Round are supported
lang_name	string	Display game names in multiple languages (default to English). Language Code
lang_icon	string	Display localized game entry image URL (default to English image) Language Code