

Existential quantification and closed vs. open worlds

Dave Dubin

March 2019

Inference rule from last week

```
needstool(Recipe,Tool,Property) :-  
    stepin(Step,Recipe),  
    utool(Step,Tool),  
    realizes(Tool, Property).
```

- If a step in a recipe uses a tool that realizes a property, then the recipe needs that tool for the property.

```
needstool(Recipe,Tool,Property) :-  
    stepin(Step,Recipe),  
    utool(Step,Tool),  
    realizes(Tool, Property).
```

- If a step in a recipe uses a tool that realizes a property, then the recipe needs that tool for the property.
- $\forall w \forall x \forall y \forall z (((Swx \wedge Uwy) \wedge Ryz) \rightarrow Nxyz)$

Inference rule from last week

```
needstool(Recipe,Tool,Property) :-  
    stepin(Step,Recipe),  
    utool(Step,Tool),  
    realizes(Tool, Property).
```

- If a step in a recipe uses a tool that realizes a property, then the recipe needs that tool for the property.
- $\forall w \forall x \forall y \forall z (((Swx \wedge Uwy) \wedge Ryz) \rightarrow Nxyz)$
- However, our data usually doesn't specify both the tool and the property. One or the other is mentioned alone.

Using existential quantification

- With predicate logic we could deduce the existence of a needed tool from a property that it should realize.

Using existential quantification

- With predicate logic we could deduce the existence of a needed tool from a property that it should realize.
- $\forall x \forall y \forall z ((R_{xy} \wedge S_{yz}) \rightarrow \exists w N_{xwz})$

Using existential quantification

- With predicate logic we could deduce the existence of a needed tool from a property that it should realize.
- $\forall x \forall y \forall z ((R_{xy} \wedge S_{yz}) \rightarrow \exists w N_{xwz})$
- This is a powerful inference, since it lets us reason about one or more individuals that aren't specified.

Using existential quantification

- With predicate logic we could deduce the existence of a needed tool from a property that it should realize.
- $\forall x \forall y \forall z ((R_{xy} \wedge S_{yz}) \rightarrow \exists w N_{xwz})$
- This is a powerful inference, since it lets us reason about one or more individuals that aren't specified.
- But Datalog doesn't give us full existential quantification for reasoning.

Our approximation using constants

- Datalog doesn't support $\forall x \forall y \forall z ((R_{xy} \wedge S_{yz}) \rightarrow \exists w N_{xwz})$

Our approximation using constants

- Datalog doesn't support $\forall x \forall y \forall z ((Rxy \wedge Syz) \rightarrow \exists w N_{xwz})$
- Our work around is $\forall x \forall y \forall z ((Rxy \wedge Syz) \rightarrow N_{xaz})$

Our approximation using constants

- Datalog doesn't support $\forall x \forall y \forall z ((Rxy \wedge Syz) \rightarrow \exists w Nxwz)$
- Our work around is $\forall x \forall y \forall z ((Rxy \wedge Syz) \rightarrow Nxaz)$
- That is to say, if a recipe requires an ingredient and that ingredient satisfies a property, then the recipe needs a tool we call 'something.'

Our approximation using constants

- Datalog doesn't support $\forall x \forall y \forall z ((Rxy \wedge Syz) \rightarrow \exists w Nxwz)$
- Our work around is $\forall x \forall y \forall z ((Rxy \wedge Syz) \rightarrow Nxaz)$
- That is to say, if a recipe requires an ingredient and that ingredient satisfies a property, then the recipe needs a tool we call 'something.'
- But on this account, 'something' is some particular tool that we're calling 'something.'

Our approximation using constants

- Datalog doesn't support $\forall x \forall y \forall z ((Rxy \wedge Syz) \rightarrow \exists w Nxwz)$
- Our work around is $\forall x \forall y \forall z ((Rxy \wedge Syz) \rightarrow Nxaz)$
- That is to say, if a recipe requires an ingredient and that ingredient satisfies a property, then the recipe needs a tool we call 'something.'
- But on this account, 'something' is some particular tool that we're calling 'something.'
- And 'something' is always the same something, no matter how many different qualifying properties it's matched with.

Our approximation using constants

- Datalog doesn't support $\forall x \forall y \forall z ((Rxy \wedge Syz) \rightarrow \exists w Nxwz)$
- Our work around is $\forall x \forall y \forall z ((Rxy \wedge Syz) \rightarrow Nxaz)$
- That is to say, if a recipe requires an ingredient and that ingredient satisfies a property, then the recipe needs a tool we call 'something.'
- But on this account, 'something' is some particular tool that we're calling 'something.'
- And 'something' is always the same something, no matter how many different qualifying properties it's matched with.
- That's not consistent with the semantics of predicate logic.

Our approximation using constants

- Datalog doesn't support $\forall x \forall y \forall z ((Rxy \wedge Syz) \rightarrow \exists w Nxwz)$
- Our work around is $\forall x \forall y \forall z ((Rxy \wedge Syz) \rightarrow Nxaz)$
- That is to say, if a recipe requires an ingredient and that ingredient satisfies a property, then the recipe needs a tool we call 'something.'
- But on this account, 'something' is some particular tool that we're calling 'something.'
- And 'something' is always the same something, no matter how many different qualifying properties it's matched with.
- That's not consistent with the semantics of predicate logic.

Our approximation using constants

- Datalog doesn't support $\forall x \forall y \forall z ((Rxy \wedge Syz) \rightarrow \exists w Nxwz)$
- Our work around is $\forall x \forall y \forall z ((Rxy \wedge Syz) \rightarrow Nxaz)$
- That is to say, if a recipe requires an ingredient and that ingredient satisfies a property, then the recipe needs a tool we call 'something.'
- But on this account, 'something' is some particular tool that we're calling 'something.'
- And 'something' is always the same something, no matter how many different qualifying properties it's matched with.
- That's not consistent with the semantics of predicate logic.

```
needstool(Recipe,something,Property) :-  
    requires(Recipe,Ingredient),  
    satisfies(Ingredient, Property).
```


The closed world assumption

- Many deductive applications are based on a 'closed world assumption.'

The closed world assumption

- Many deductive applications are based on a 'closed world assumption.'
- This means that if a statement is not deduced to be true, then that statement should be treated as false.

The closed world assumption

- Many deductive applications are based on a 'closed world assumption.'
- This means that if a statement is not deduced to be true, then that statement should be treated as false.
- For example, our assertions do not directly state that the chicken soup recipe needs a slow cooker.

The closed world assumption

- Many deductive applications are based on a 'closed world assumption.'
- This means that if a statement is not deduced to be true, then that statement should be treated as false.
- For example, our assertions do not directly state that the chicken soup recipe needs a slow cooker.
- But a substep of a step included in the recipe uses a slow cooker, so the need for the tool can be deduced.

The closed world assumption

- Many deductive applications are based on a 'closed world assumption.'
- This means that if a statement is not deduced to be true, then that statement should be treated as false.
- For example, our assertions do not directly state that the chicken soup recipe needs a slow cooker.
- But a substep of a step included in the recipe uses a slow cooker, so the need for the tool can be deduced.
- We deduce that some tool is needed for dicing, skinning, and trimming.

The closed world assumption

- Many deductive applications are based on a 'closed world assumption.'
- This means that if a statement is not deduced to be true, then that statement should be treated as false.
- For example, our assertions do not directly state that the chicken soup recipe needs a slow cooker.
- But a substep of a step included in the recipe uses a slow cooker, so the need for the tool can be deduced.
- We deduce that some tool is needed for dicing, skinning, and trimming.
- But we can't deduce that we need a knife for those actions.

The closed world assumption

- Many deductive applications are based on a 'closed world assumption.'
- This means that if a statement is not deduced to be true, then that statement should be treated as false.
- For example, our assertions do not directly state that the chicken soup recipe needs a slow cooker.
- But a substep of a step included in the recipe uses a slow cooker, so the need for the tool can be deduced.
- We deduce that some tool is needed for dicing, skinning, and trimming.
- But we can't deduce that we need a knife for those actions.
- Under a closed world assumption we would take it as false that a knife is needed for this recipe.

The closed world assumption

- The closed world assumption is reasonable in applications where all relevant facts and rules of inference are available.

The closed world assumption

- The closed world assumption is reasonable in applications where all relevant facts and rules of inference are available.
- Systems under the stewardship of one organization with limited use cases and all information stored together are good candidates for the closed world assumption.

The closed world assumption

- The closed world assumption is reasonable in applications where all relevant facts and rules of inference are available.
- Systems under the stewardship of one organization with limited use cases and all information stored together are good candidates for the closed world assumption.
- But these days many information systems rely on loosely coupled, widely distributed data.

The closed world assumption

- The closed world assumption is reasonable in applications where all relevant facts and rules of inference are available.
- Systems under the stewardship of one organization with limited use cases and all information stored together are good candidates for the closed world assumption.
- But these days many information systems rely on loosely coupled, widely distributed data.
- Systems are designed for uses across institutional boundaries.

The closed world assumption

- The closed world assumption is reasonable in applications where all relevant facts and rules of inference are available.
- Systems under the stewardship of one organization with limited use cases and all information stored together are good candidates for the closed world assumption.
- But these days many information systems rely on loosely coupled, widely distributed data.
- Systems are designed for uses across institutional boundaries.
- Stakeholders cooperate on maintaining and integrating machine readable data.

The open world assumption

- With an open world assumption, we can't conclude that failure to deduce a proposition means that the proposition is false.

The open world assumption

- With an open world assumption, we can't conclude that failure to deduce a proposition means that the proposition is false.
- Reasoning must be based on what might be true, consistent with what we know.


The open world assumption

- With an open world assumption, we can't conclude that failure to deduce a proposition means that the proposition is false.
- Reasoning must be based on what might be true, consistent with what we know.
- Understanding how this works requires the concept of an *interpretation*.


- 1 The structure of language can each be described using formal systems.

- ① The structure of language can each be described using formal systems.
- ② Language has meaning.

- ① The structure of language can each be described using formal systems.
- ② Language has meaning.
- ③ Meanings are things that aren't language.



Language and the world



Syntax of Bach's logic subset

$\langle var \rangle ::= w|x|y|z$

$\langle con \rangle ::= a|b|c|d$

$\langle ter \rangle ::= \langle var \rangle|\langle con \rangle$

$\langle 1pp \rangle ::= Run|Walk|Happy|Calm$

$\langle 2pp \rangle ::= Love|Kiss|Like|See$

$\langle wff \rangle ::= \langle 1pp \rangle(\langle ter \rangle)$

$\langle wff \rangle ::= \langle 2pp \rangle(\langle ter \rangle, \langle ter \rangle)$

$\langle wff \rangle ::= \neg \langle wff \rangle$

$\langle wff \rangle ::= (\langle wff \rangle \vee \langle wff \rangle)$

$\langle wff \rangle ::= (\langle wff \rangle \& \langle wff \rangle)$

$\langle wff \rangle ::= \forall \langle var \rangle \langle wff \rangle$

$\langle wff \rangle ::= \exists \langle var \rangle \langle wff \rangle$

Notational differences between readings

- The $\&$ and \wedge symbols both mean conjunction (“and”).

Notational differences between readings

- The $\&$ and \wedge symbols both mean conjunction (“and”).
- The \neg , \sim , and $-$ all mean negation (“not”).

Notational differences between readings

- The $\&$ and \wedge symbols both mean conjunction (“and”).
- The \neg , \sim , and $-$ all mean negation (“not”).
- Sometimes predicates are written with parentheses ($P(x, y)$), sometimes not (P_{xy}).

Notational differences between readings

- The $\&$ and \wedge symbols both mean conjunction (“and”).
- The \neg , \sim , and $-$ all mean negation (“not”).
- Sometimes predicates are written with parentheses ($P(x, y)$), sometimes not (Pxy).
- In other words, $(Pab \wedge \neg Qbc)$ is the same as $(P(a, b) \& -Q(b, c))$.

Notational differences between readings

- The $\&$ and \wedge symbols both mean conjunction (“and”).
- The \neg , \sim , and $-$ all mean negation (“not”).
- Sometimes predicates are written with parentheses ($P(x, y)$), sometimes not (Pxy).
- In other words, $(Pab \wedge \neg Qbc)$ is the same as $(P(a, b) \& -Q(b, c))$.
- Some authors use D for the domain set and I for the interpretation function.

Notational differences between readings

- The $\&$ and \wedge symbols both mean conjunction (“and”).
- The \neg , \sim , and $-$ all mean negation (“not”).
- Sometimes predicates are written with parentheses ($P(x, y)$), sometimes not (Pxy).
- In other words, $(Pab \wedge \neg Qbc)$ is the same as $(P(a, b) \& -Q(b, c))$.
- Some authors use D for the domain set and I for the interpretation function.
- But Bach calls the domain set E (entities) and the interpretation function D (denotes).


Notational differences between readings

- The $\&$ and \wedge symbols both mean conjunction (“and”).
- The \neg , \sim , and $-$ all mean negation (“not”).
- Sometimes predicates are written with parentheses ($P(x, y)$), sometimes not (Pxy).
- In other words, $(Pab \wedge \neg Qbc)$ is the same as $(P(a, b) \& -Q(b, c))$.
- Some authors use D for the domain set and I for the interpretation function.
- But Bach calls the domain set E (entities) and the interpretation function D (denotes).
- I will bring in some details from other readings, but use Bach’s notation in this presentation.


Notational differences between readings

- The $\&$ and \wedge symbols both mean conjunction (“and”).
- The \neg , \sim , and $-$ all mean negation (“not”).
- Sometimes predicates are written with parentheses ($P(x, y)$), sometimes not (Pxy).
- In other words, $(Pab \wedge \neg Qbc)$ is the same as $(P(a, b) \& -Q(b, c))$.
- Some authors use D for the domain set and I for the interpretation function.
- But Bach calls the domain set E (entities) and the interpretation function D (denotes).
- I will bring in some details from other readings, but use Bach’s notation in this presentation.
- Bach calls his structure an interpretation, so I’ll use I for that.

Language and the world



Language and the world




Language and the world


Language

(denotes)

World




Language and the world



Language and the world

Language (denotes under assignment g_1) World



Models and interpretations

Bach writes:

An interpretation is a way of assigning denotations in a certain model structure to expressions in a language.

- Bach's formalization gives us: $I = \langle M1, D, G \rangle$ where:

Models and interpretations

Bach writes:

An interpretation is a way of assigning denotations in a certain model structure to expressions in a language.

- Bach's formalization gives us: $I = \langle M1, D, G \rangle$ where:
 - $M1$ is the first model structure he proposes;

Bach writes:

An interpretation is a way of assigning denotations in a certain model structure to expressions in a language.

- Bach's formalization gives us: $I = \langle M1, D, G \rangle$ where:
 - $M1$ is the first model structure he proposes;
 - G is a set of assignments of values to variables;

Bach writes:

An interpretation is a way of assigning denotations in a certain model structure to expressions in a language.

- Bach's formalization gives us: $I = \langle M1, D, G \rangle$ where:
 - $M1$ is the first model structure he proposes;
 - G is a set of assignments of values to variables;
 - D is the denoting evaluation function.

Bach writes:

An interpretation is a way of assigning denotations in a certain model structure to expressions in a language.

- Bach's formalization gives us: $I = \langle M1, D, G \rangle$ where:
 - $M1$ is the first model structure he proposes;
 - G is a set of assignments of values to variables;
 - D is the denoting evaluation function.
- Bach's $M1$ is itself a two-place tuple consisting of:

Bach writes:

An interpretation is a way of assigning denotations in a certain model structure to expressions in a language.

- Bach's formalization gives us: $I = \langle M1, D, G \rangle$ where:
 - $M1$ is the first model structure he proposes;
 - G is a set of assignments of values to variables;
 - D is the denoting evaluation function.
- Bach's $M1$ is itself a two-place tuple consisting of:
 - Set E of individuals;

Bach writes:

An interpretation is a way of assigning denotations in a certain model structure to expressions in a language.

- Bach's formalization gives us: $I = \langle M1, D, G \rangle$ where:
 - $M1$ is the first model structure he proposes;
 - G is a set of assignments of values to variables;
 - D is the denoting evaluation function.
- Bach's $M1$ is itself a two-place tuple consisting of:
 - Set E of individuals;
 - The set of truth values $\{1, 0\}$.

Bach writes:

An interpretation is a way of assigning denotations in a certain model structure to expressions in a language.

- Bach's formalization gives us: $I = \langle M1, D, G \rangle$ where:
 - $M1$ is the first model structure he proposes;
 - G is a set of assignments of values to variables;
 - D is the denoting evaluation function.
- Bach's $M1$ is itself a two-place tuple consisting of:
 - Set E of individuals;
 - The set of truth values $\{1, 0\}$.
- Toward the end of the reading he suggests adding a set of times and a set of possible worlds for more expressive languages.

Simple denotations

Individual constants (like a and b) will denote individuals in the domain, so they'll be elements of Bach's set E . The one-place predicates (classes) will denote their extensions (i.e., subsets of the domain). The two-place predicates (binary relations) will denote sets of ordered pairs.

$$D(\langle con \rangle) \in E$$

$$D(\langle 1pp \rangle) \subseteq E$$

$$D(\langle 2pp \rangle) \subseteq E \times E$$

Following a common convention, we adopt the notation φ_D for $D(\varphi)$. So, for example, a_D would be some individual in the Domain set E , and $Love_D$ would be a set of ordered pairs $\langle x, y \rangle$, in each of which x loves y .

Variable assignments

- Let V be the set of variables in the language. Bach's G is a set of variable assignments, and each $g \in G$ is a function from variables ($v \in V$) to individuals in E , i.e.: $g \subseteq V \times E$.

Variable assignments

- Let V be the set of variables in the language. Bach's G is a set of variable assignments, and each $g \in G$ is a function from variables ($v \in V$) to individuals in E , i.e.: $g \subseteq V \times E$.
- For example, suppose $g_1 = \{\langle w, a_D \rangle, \langle x, b_D \rangle, \langle y, c_D \rangle, \langle z, d_D \rangle\}$, but $g_2 = \{\langle w, b_D \rangle, \langle x, c_D \rangle, \langle y, d_D \rangle, \langle z, a_D \rangle\}$.

Variable assignments

- Let V be the set of variables in the language. Bach's G is a set of variable assignments, and each $g \in G$ is a function from variables ($v \in V$) to individuals in E , i.e.: $g \subseteq V \times E$.
- For example, suppose $g_1 = \{\langle w, a_D \rangle, \langle x, b_D \rangle, \langle y, c_D \rangle, \langle z, d_D \rangle\}$, but $g_2 = \{\langle w, b_D \rangle, \langle x, c_D \rangle, \langle y, d_D \rangle, \langle z, a_D \rangle\}$.
- Because our functions are cartesian product subsets, two or more different variables can be mapped to the same individual. For example, maybe $g_3 = \{\langle w, a_D \rangle, \langle x, a_D \rangle, \langle y, b_D \rangle, \langle z, a_D \rangle\}$ and $g_4 = \{\langle w, c_D \rangle, \langle x, c_D \rangle, \langle y, c_D \rangle, \langle z, c_D \rangle\}$. But they're functions, so every variable in the domain will be included.

Variable assignments

- Let V be the set of variables in the language. Bach's G is a set of variable assignments, and each $g \in G$ is a function from variables ($v \in V$) to individuals in E , i.e.: $g \subseteq V \times E$.
- For example, suppose $g_1 = \{\langle w, a_D \rangle, \langle x, b_D \rangle, \langle y, c_D \rangle, \langle z, d_D \rangle\}$, but $g_2 = \{\langle w, b_D \rangle, \langle x, c_D \rangle, \langle y, d_D \rangle, \langle z, a_D \rangle\}$.
- Because our functions are cartesian product subsets, two or more different variables can be mapped to the same individual. For example, maybe $g_3 = \{\langle w, a_D \rangle, \langle x, a_D \rangle, \langle y, b_D \rangle, \langle z, a_D \rangle\}$ and $g_4 = \{\langle w, c_D \rangle, \langle x, c_D \rangle, \langle y, c_D \rangle, \langle z, c_D \rangle\}$. But they're functions, so every variable in the domain will be included.
- The expression $g[v:=e]$ is understood to mean "the variable assignment that is completely like g except that v now gets the value e (where g might have assigned a different value)."

Variable assignments

- Let V be the set of variables in the language. Bach's G is a set of variable assignments, and each $g \in G$ is a function from variables ($v \in V$) to individuals in E , i.e.: $g \subseteq V \times E$.
- For example, suppose $g_1 = \{\langle w, a_D \rangle, \langle x, b_D \rangle, \langle y, c_D \rangle, \langle z, d_D \rangle\}$, but $g_2 = \{\langle w, b_D \rangle, \langle x, c_D \rangle, \langle y, d_D \rangle, \langle z, a_D \rangle\}$.
- Because our functions are cartesian product subsets, two or more different variables can be mapped to the same individual. For example, maybe $g_3 = \{\langle w, a_D \rangle, \langle x, a_D \rangle, \langle y, b_D \rangle, \langle z, a_D \rangle\}$ and $g_4 = \{\langle w, c_D \rangle, \langle x, c_D \rangle, \langle y, c_D \rangle, \langle z, c_D \rangle\}$. But they're functions, so every variable in the domain will be included.
- The expression $g[v:=e]$ is understood to mean "the variable assignment that is completely like g except that v now gets the value e (where g might have assigned a different value)."
- For example, $g_1[x:=d_D] = \{\langle w, a_D \rangle, \langle x, d_D \rangle, \langle y, c_D \rangle, \langle z, d_D \rangle\}$

Denotation, support, and truth

An expression in our language will be true or false in an interpretation, relative to a particular assignment of individuals to variables. So we write $I \models_g \varphi$ to mean that assignment g *satisfies* expression φ in interpretation I (or, in other words, φ is true in interpretation I under assignment g).

- $\llbracket v \rrbracket_D^g = g(v)$

Denotation, support, and truth

An expression in our language will be true or false in an interpretation, relative to a particular assignment of individuals to variables. So we write $I \models_g \varphi$ to mean that assignment g *satisfies* expression φ in interpretation I (or, in other words, φ is true in interpretation I under assignment g).

- $\llbracket v \rrbracket_D^g = g(v)$
- $\llbracket c \rrbracket_D^g = c_D$

Denotation, support, and truth

An expression in our language will be true or false in an interpretation, relative to a particular assignment of individuals to variables. So we write $I \models_g \varphi$ to mean that assignment g *satisfies* expression φ in interpretation I (or, in other words, φ is true in interpretation I under assignment g).

- $\llbracket v \rrbracket_D^g = g(v)$
- $\llbracket c \rrbracket_D^g = c_D$
- $I \models_g P(t)$ iff $\llbracket t \rrbracket_D^g \in P_D$

Denotation, support, and truth

An expression in our language will be true or false in an interpretation, relative to a particular assignment of individuals to variables. So we write $I \models_g \varphi$ to mean that assignment g *satisfies* expression φ in interpretation I (or, in other words, φ is true in interpretation I under assignment g).

- $\llbracket v \rrbracket_D^g = g(v)$
- $\llbracket c \rrbracket_D^g = c_D$
- $I \models_g P(t)$ iff $\llbracket t \rrbracket_D^g \in P_D$
- $I \models_g R(s, t)$ iff $\langle \llbracket s \rrbracket_D^g, \llbracket t \rrbracket_D^g \rangle \in R_D$

Denotation, support, and truth

An expression in our language will be true or false in an interpretation, relative to a particular assignment of individuals to variables. So we write $I \models_g \varphi$ to mean that assignment g *satisfies* expression φ in interpretation I (or, in other words, φ is true in interpretation I under assignment g).

- $\llbracket v \rrbracket_D^g = g(v)$
- $\llbracket c \rrbracket_D^g = c_D$
- $I \models_g P(t)$ iff $\llbracket t \rrbracket_D^g \in P_D$
- $I \models_g R(s, t)$ iff $\langle \llbracket s \rrbracket_D^g, \llbracket t \rrbracket_D^g \rangle \in R_D$
- $I \models_g \neg \varphi$ iff it is not the case that $I \models_g \varphi$

Denotation, support, and truth

An expression in our language will be true or false in an interpretation, relative to a particular assignment of individuals to variables. So we write $I \models_g \varphi$ to mean that assignment g *satisfies* expression φ in interpretation I (or, in other words, φ is true in interpretation I under assignment g).

- $\llbracket v \rrbracket_D^g = g(v)$
- $\llbracket c \rrbracket_D^g = c_D$
- $I \models_g P(t)$ iff $\llbracket t \rrbracket_D^g \in P_D$
- $I \models_g R(s, t)$ iff $\langle \llbracket s \rrbracket_D^g, \llbracket t \rrbracket_D^g \rangle \in R_D$
- $I \models_g \neg \varphi$ iff it is not the case that $I \models_g \varphi$
- $I \models_g (\varphi_1 \ \& \ \varphi_2)$ iff $I \models_g \varphi_1$ and $I \models_g \varphi_2$

Denotation, support, and truth

An expression in our language will be true or false in an interpretation, relative to a particular assignment of individuals to variables. So we write $I \models_g \varphi$ to mean that assignment g *satisfies* expression φ in interpretation I (or, in other words, φ is true in interpretation I under assignment g).

- $\llbracket v \rrbracket_D^g = g(v)$
- $\llbracket c \rrbracket_D^g = c_D$
- $I \models_g P(t)$ iff $\llbracket t \rrbracket_D^g \in P_D$
- $I \models_g R(s, t)$ iff $\langle \llbracket s \rrbracket_D^g, \llbracket t \rrbracket_D^g \rangle \in R_D$
- $I \models_g \neg \varphi$ iff it is not the case that $I \models_g \varphi$
- $I \models_g (\varphi_1 \ \& \ \varphi_2)$ iff $I \models_g \varphi_1$ and $I \models_g \varphi_2$
- $I \models_g (\varphi_1 \vee \varphi_2)$ iff $I \models_g \varphi_1$ or $I \models_g \varphi_2$

Denotation, support, and truth

An expression in our language will be true or false in an interpretation, relative to a particular assignment of individuals to variables. So we write $I \models_g \varphi$ to mean that assignment g *satisfies* expression φ in interpretation I (or, in other words, φ is true in interpretation I under assignment g).

- $\llbracket v \rrbracket_D^g = g(v)$
- $\llbracket c \rrbracket_D^g = c_D$
- $I \models_g P(t)$ iff $\llbracket t \rrbracket_D^g \in P_D$
- $I \models_g R(s, t)$ iff $\langle \llbracket s \rrbracket_D^g, \llbracket t \rrbracket_D^g \rangle \in R_D$
- $I \models_g \neg \varphi$ iff it is not the case that $I \models_g \varphi$
- $I \models_g (\varphi_1 \ \& \ \varphi_2)$ iff $I \models_g \varphi_1$ and $I \models_g \varphi_2$
- $I \models_g (\varphi_1 \vee \varphi_2)$ iff $I \models_g \varphi_1$ or $I \models_g \varphi_2$
- $I \models_g \forall v \varphi$ iff for all $e \in E$ it holds that $I \models_{g[v:=e]} \varphi$

Denotation, support, and truth

An expression in our language will be true or false in an interpretation, relative to a particular assignment of individuals to variables. So we write $I \models_g \varphi$ to mean that assignment g *satisfies* expression φ in interpretation I (or, in other words, φ is true in interpretation I under assignment g).

- $\llbracket v \rrbracket_D^g = g(v)$
- $\llbracket c \rrbracket_D^g = c_D$
- $I \models_g P(t)$ iff $\llbracket t \rrbracket_D^g \in P_D$
- $I \models_g R(s, t)$ iff $\langle \llbracket s \rrbracket_D^g, \llbracket t \rrbracket_D^g \rangle \in R_D$
- $I \models_g \neg \varphi$ iff it is not the case that $I \models_g \varphi$
- $I \models_g (\varphi_1 \ \& \ \varphi_2)$ iff $I \models_g \varphi_1$ and $I \models_g \varphi_2$
- $I \models_g (\varphi_1 \vee \varphi_2)$ iff $I \models_g \varphi_1$ or $I \models_g \varphi_2$
- $I \models_g \forall v \varphi$ iff for all $e \in E$ it holds that $I \models_{g[v:=e]} \varphi$
- $I \models_g \exists v \varphi$ iff for at least one $e \in E$ it holds that $I \models_{g[v:=e]} \varphi$