

# Artificial Languages, Part 1 (Syntax)

Dave Dubin

March 27, 2017

# Key concepts for language topics

- 1 Syntax governs the *form* expressions of a language may take.

# Key concepts for language topics

- 1 Syntax governs the *form* expressions of a language may take.
- 2 Semantics governs the *relationship* between language expressions and the *domain* we're modeling.

# Key concepts for language topics

- ① Syntax governs the *form* expressions of a language may take.
- ② Semantics governs the *relationship* between language expressions and the *domain* we're modeling.
- ③ We have the usual formalist agenda of reducing our accounts of language to simple mathematical objects.

# Key concepts for language topics

- ① Syntax governs the *form* expressions of a language may take.
- ② Semantics governs the *relationship* between language expressions and the *domain* we're modeling.
- ③ We have the usual formalist agenda of reducing our accounts of language to simple mathematical objects.
- ④ That agenda is partly in the service of understanding, but also our aim to process language expressions using software.

# Key concepts for language topics

- ① Syntax governs the *form* expressions of a language may take.
- ② Semantics governs the *relationship* between language expressions and the *domain* we're modeling.
- ③ We have the usual formalist agenda of reducing our accounts of language to simple mathematical objects.
- ④ That agenda is partly in the service of understanding, but also our aim to process language expressions using software.
- ⑤ The cost of processing language is measured in processing time and memory.

# Key concepts for language topics

- 1 Syntax governs the *form* expressions of a language may take.
- 2 Semantics governs the *relationship* between language expressions and the *domain* we're modeling.
- 3 We have the usual formalist agenda of reducing our accounts of language to simple mathematical objects.
- 4 That agenda is partly in the service of understanding, but also our aim to process language expressions using software.
- 5 The cost of processing language is measured in processing time and memory.
- 6 The more expressive our language, the more expensive it will be to run our software over it.

# Key concepts for language topics

- 1 Syntax governs the *form* expressions of a language may take.
- 2 Semantics governs the *relationship* between language expressions and the *domain* we're modeling.
- 3 We have the usual formalist agenda of reducing our accounts of language to simple mathematical objects.
- 4 That agenda is partly in the service of understanding, but also our aim to process language expressions using software.
- 5 The cost of processing language is measured in processing time and memory.
- 6 The more expressive our language, the more expensive it will be to run our software over it.
- 7 Classifications of languages (like the Chomsky hierarchy) help us recognize what kind of software we need to accomplish our processing goals.



# Grammars for artificial languages

- We've seen grammars in earlier presentations.

# Grammars for artificial languages

- We've seen grammars in earlier presentations.
- Propositional logic:

# Grammars for artificial languages

- We've seen grammars in earlier presentations.
- Propositional logic:
  - Let  $P$  be a set of proposition letters and let  $p \in P$ .

# Grammars for artificial languages

- We've seen grammars in earlier presentations.
- Propositional logic:
  - Let  $P$  be a set of proposition letters and let  $p \in P$ .
  - $\varphi ::= p \mid \neg\varphi \mid (\varphi \wedge \varphi) \mid (\varphi \vee \varphi) \mid (\varphi \rightarrow \varphi) \mid (\varphi \leftrightarrow \varphi)$

# Grammars for artificial languages

- We've seen grammars in earlier presentations.
- Propositional logic:
  - Let  $P$  be a set of proposition letters and let  $p \in P$ .
  - $\varphi ::= p | \neg\varphi | (\varphi \wedge \varphi) | (\varphi \vee \varphi) | (\varphi \rightarrow \varphi) | (\varphi \leftrightarrow \varphi)$
- Predicate logic:

# Grammars for artificial languages

- We've seen grammars in earlier presentations.
- Propositional logic:
  - Let  $P$  be a set of proposition letters and let  $p \in P$ .
  - $\varphi ::= p | \neg\varphi | (\varphi \wedge \varphi) | (\varphi \vee \varphi) | (\varphi \rightarrow \varphi) | (\varphi \leftrightarrow \varphi)$
- Predicate logic:
  - $\mathbf{v} ::= x | y | z | \dots$

# Grammars for artificial languages

- We've seen grammars in earlier presentations.
- Propositional logic:
  - Let  $P$  be a set of proposition letters and let  $p \in P$ .
  - $\varphi ::= p \mid \neg\varphi \mid (\varphi \wedge \varphi) \mid (\varphi \vee \varphi) \mid (\varphi \rightarrow \varphi) \mid (\varphi \leftrightarrow \varphi)$
- Predicate logic:
  - $\mathbf{v} ::= x \mid y \mid z \mid \dots$
  - $\mathbf{c} ::= a \mid b \mid c \mid \dots$

# Grammars for artificial languages

- We've seen grammars in earlier presentations.
- Propositional logic:
  - Let  $P$  be a set of proposition letters and let  $p \in P$ .
  - $\varphi ::= p \mid \neg\varphi \mid (\varphi \wedge \varphi) \mid (\varphi \vee \varphi) \mid (\varphi \rightarrow \varphi) \mid (\varphi \leftrightarrow \varphi)$
- Predicate logic:
  - $\mathbf{v} ::= x \mid y \mid z \mid \dots$
  - $\mathbf{c} ::= a \mid b \mid c \mid \dots$
  - $\mathbf{t} ::= \mathbf{v} \mid \mathbf{c}$



# Grammars for artificial languages

- We've seen grammars in earlier presentations.
- Propositional logic:
  - Let  $P$  be a set of proposition letters and let  $p \in P$ .
  - $\varphi ::= p | \neg\varphi | (\varphi \wedge \varphi) | (\varphi \vee \varphi) | (\varphi \rightarrow \varphi) | (\varphi \leftrightarrow \varphi)$
- Predicate logic:
  - $\mathbf{v} ::= x | y | z | \dots$
  - $\mathbf{c} ::= a | b | c | \dots$
  - $\mathbf{t} ::= \mathbf{v} | \mathbf{c}$
  - $\mathbf{P} ::= P | Q | R | \dots$

# Grammars for artificial languages

- We've seen grammars in earlier presentations.
- Propositional logic:
  - Let  $P$  be a set of proposition letters and let  $p \in P$ .
  - $\varphi ::= p \mid \neg\varphi \mid (\varphi \wedge \varphi) \mid (\varphi \vee \varphi) \mid (\varphi \rightarrow \varphi) \mid (\varphi \leftrightarrow \varphi)$
- Predicate logic:
  - $\mathbf{v} ::= x \mid y \mid z \mid \dots$
  - $\mathbf{c} ::= a \mid b \mid c \mid \dots$
  - $\mathbf{t} ::= \mathbf{v} \mid \mathbf{c}$
  - $\mathbf{P} ::= P \mid Q \mid R \mid \dots$
  - **Atom**  $::= \mathbf{P} \mathbf{t}_1 \dots \mathbf{t}_n$  where  $n$  is the arity of  $\mathbf{P}$

# Grammars for artificial languages

- We've seen grammars in earlier presentations.
- Propositional logic:
  - Let  $P$  be a set of proposition letters and let  $p \in P$ .
  - $\varphi ::= p \mid \neg\varphi \mid (\varphi \wedge \varphi) \mid (\varphi \vee \varphi) \mid (\varphi \rightarrow \varphi) \mid (\varphi \leftrightarrow \varphi)$
- Predicate logic:
  - $\mathbf{v} ::= x \mid y \mid z \mid \dots$
  - $\mathbf{c} ::= a \mid b \mid c \mid \dots$
  - $\mathbf{t} ::= \mathbf{v} \mid \mathbf{c}$
  - $\mathbf{P} ::= P \mid Q \mid R \mid \dots$
  - **Atom** ::=  $\mathbf{P}\mathbf{t}_1 \dots \mathbf{t}_n$  where  $n$  is the arity of  $\mathbf{P}$
  - $\varphi ::= \mathbf{Atom} \mid \neg\varphi \mid (\varphi \wedge \varphi) \mid (\varphi \vee \varphi) \mid (\varphi \rightarrow \varphi) \mid (\varphi \leftrightarrow \varphi) \mid \forall \mathbf{v}\varphi \mid \exists \mathbf{v}\varphi$

- $\forall wx((F_xw \wedge Aw) \rightarrow \exists yz((P_{xy} \wedge Ay) \wedge (F_{xz} \wedge Dz)))$

- $\forall wx((F_xw \wedge Aw) \rightarrow \exists yz((P_{xy} \wedge Ay) \wedge (F_{xz} \wedge Dz)))$
- $\forall \mathbf{vv}((F_{\mathbf{vv}} \wedge A\mathbf{v}) \rightarrow \exists \mathbf{vv}((P_{\mathbf{vv}} \wedge A\mathbf{v}) \wedge (F_{\mathbf{vv}} \wedge D\mathbf{v})))$

# Bottom-up parse

- $\forall wx((F_xw \wedge Aw) \rightarrow \exists yz((P_{xy} \wedge Ay) \wedge (F_{xz} \wedge Dz)))$
- $\forall vv((F_{vv} \wedge Av) \rightarrow \exists vv((P_{vv} \wedge Av) \wedge (F_{vv} \wedge Dv)))$
- $\forall vv((P_{vv} \wedge Pv) \rightarrow \exists vv((P_{vv} \wedge Pv) \wedge (P_{vv} \wedge Pv)))$

# Bottom-up parse

- $\forall wx((F_xw \wedge Aw) \rightarrow \exists yz((P_{xy} \wedge Ay) \wedge (F_{xz} \wedge Dz)))$
- $\forall vv((F_{vv} \wedge Av) \rightarrow \exists vv((P_{vv} \wedge Av) \wedge (F_{vv} \wedge Dv)))$
- $\forall vv((P_{vv} \wedge Pv) \rightarrow \exists vv((P_{vv} \wedge Pv) \wedge (P_{vv} \wedge Pv)))$
- $\forall vv((P_{tt} \wedge Pt) \rightarrow \exists vv((P_{tt} \wedge Pt) \wedge (P_{tt} \wedge Pt)))$

# Bottom-up parse

- $\forall wx((F_{xw} \wedge A_w) \rightarrow \exists yz((P_{xy} \wedge A_y) \wedge (F_{xz} \wedge D_z)))$
- $\forall vv((F_{vv} \wedge A_v) \rightarrow \exists vv((P_{vv} \wedge A_v) \wedge (F_{vv} \wedge D_v)))$
- $\forall vv((P_{vv} \wedge P_v) \rightarrow \exists vv((P_{vv} \wedge P_v) \wedge (P_{vv} \wedge P_v)))$
- $\forall vv((P_{tt} \wedge P_t) \rightarrow \exists vv((P_{tt} \wedge P_t) \wedge (P_{tt} \wedge P_t)))$
- $\forall vv((\mathbf{Atom} \wedge \mathbf{Atom}) \rightarrow \exists vv((\mathbf{Atom} \wedge \mathbf{Atom}) \wedge (\mathbf{Atom} \wedge \mathbf{Atom})))$



# Bottom-up parse

- $\forall wx((F_{xw} \wedge A_w) \rightarrow \exists yz((P_{xy} \wedge A_y) \wedge (F_{xz} \wedge D_z)))$
- $\forall vv((F_{vv} \wedge A_v) \rightarrow \exists vv((P_{vv} \wedge A_v) \wedge (F_{vv} \wedge D_v)))$
- $\forall vv((P_{vv} \wedge P_v) \rightarrow \exists vv((P_{vv} \wedge P_v) \wedge (P_{vv} \wedge P_v)))$
- $\forall vv((P_{tt} \wedge P_t) \rightarrow \exists vv((P_{tt} \wedge P_t) \wedge (P_{tt} \wedge P_t)))$
- $\forall vv((\mathbf{Atom} \wedge \mathbf{Atom}) \rightarrow \exists vv((\mathbf{Atom} \wedge \mathbf{Atom}) \wedge (\mathbf{Atom} \wedge \mathbf{Atom})))$
- $\forall vv((\varphi \wedge \varphi) \rightarrow \exists vv((\varphi \wedge \varphi) \wedge (\varphi \wedge \varphi)))$

# Bottom-up parse

- $\forall wx((F_xw \wedge Aw) \rightarrow \exists yz((P_{xy} \wedge Ay) \wedge (F_{xz} \wedge Dz)))$
- $\forall vv((F_{vv} \wedge Av) \rightarrow \exists vv((P_{vv} \wedge Av) \wedge (F_{vv} \wedge Dv)))$
- $\forall vv((P_{vv} \wedge Pv) \rightarrow \exists vv((P_{vv} \wedge Pv) \wedge (P_{vv} \wedge Pv)))$
- $\forall vv((P_{tt} \wedge Pt) \rightarrow \exists vv((P_{tt} \wedge Pt) \wedge (P_{tt} \wedge Pt)))$
- $\forall vv((\mathbf{Atom} \wedge \mathbf{Atom}) \rightarrow \exists vv((\mathbf{Atom} \wedge \mathbf{Atom}) \wedge (\mathbf{Atom} \wedge \mathbf{Atom})))$
- $\forall vv((\varphi \wedge \varphi) \rightarrow \exists vv((\varphi \wedge \varphi) \wedge (\varphi \wedge \varphi)))$
- $\forall vv((\varphi \wedge \varphi) \rightarrow \exists vv((\varphi \wedge \varphi) \wedge \varphi))$

# Bottom-up parse

- $\forall wx((F_xw \wedge Aw) \rightarrow \exists yz((P_{xy} \wedge Ay) \wedge (F_{xz} \wedge Dz)))$
- $\forall vv((F_{vv} \wedge Av) \rightarrow \exists vv((P_{vv} \wedge Av) \wedge (F_{vv} \wedge Dv)))$
- $\forall vv((P_{vv} \wedge Pv) \rightarrow \exists vv((P_{vv} \wedge Pv) \wedge (P_{vv} \wedge Pv)))$
- $\forall vv((P_{tt} \wedge Pt) \rightarrow \exists vv((P_{tt} \wedge Pt) \wedge (P_{tt} \wedge Pt)))$
- $\forall vv((\mathbf{Atom} \wedge \mathbf{Atom}) \rightarrow \exists vv((\mathbf{Atom} \wedge \mathbf{Atom}) \wedge (\mathbf{Atom} \wedge \mathbf{Atom})))$
- $\forall vv((\varphi \wedge \varphi) \rightarrow \exists vv((\varphi \wedge \varphi) \wedge (\varphi \wedge \varphi)))$
- $\forall vv((\varphi \wedge \varphi) \rightarrow \exists vv((\varphi \wedge \varphi) \wedge \varphi))$
- $\forall vv((\varphi \wedge \varphi) \rightarrow \exists vv(\varphi \wedge \varphi))$

# Bottom-up parse

- $\forall wx((F_xw \wedge Aw) \rightarrow \exists yz((P_{xy} \wedge Ay) \wedge (F_{xz} \wedge Dz)))$
- $\forall vv((F_{vv} \wedge Av) \rightarrow \exists vv((P_{vv} \wedge Av) \wedge (F_{vv} \wedge Dv)))$
- $\forall vv((P_{vv} \wedge Pv) \rightarrow \exists vv((P_{vv} \wedge Pv) \wedge (P_{vv} \wedge Pv)))$
- $\forall vv((P_{tt} \wedge Pt) \rightarrow \exists vv((P_{tt} \wedge Pt) \wedge (P_{tt} \wedge Pt)))$
- $\forall vv((\mathbf{Atom} \wedge \mathbf{Atom}) \rightarrow \exists vv((\mathbf{Atom} \wedge \mathbf{Atom}) \wedge (\mathbf{Atom} \wedge \mathbf{Atom})))$
- $\forall vv((\varphi \wedge \varphi) \rightarrow \exists vv((\varphi \wedge \varphi) \wedge (\varphi \wedge \varphi)))$
- $\forall vv((\varphi \wedge \varphi) \rightarrow \exists vv((\varphi \wedge \varphi) \wedge \varphi))$
- $\forall vv((\varphi \wedge \varphi) \rightarrow \exists vv(\varphi \wedge \varphi))$
- $\forall vv(\varphi \rightarrow \exists vv(\varphi \wedge \varphi))$

# Bottom-up parse

- $\forall wx((F_xw \wedge Aw) \rightarrow \exists yz((P_{xy} \wedge Ay) \wedge (F_{xz} \wedge Dz)))$
- $\forall vv((F_{vv} \wedge Av) \rightarrow \exists vv((P_{vv} \wedge Av) \wedge (F_{vv} \wedge Dv)))$
- $\forall vv((P_{vv} \wedge Pv) \rightarrow \exists vv((P_{vv} \wedge Pv) \wedge (P_{vv} \wedge Pv)))$
- $\forall vv((P_{tt} \wedge Pt) \rightarrow \exists vv((P_{tt} \wedge Pt) \wedge (P_{tt} \wedge Pt)))$
- $\forall vv((\mathbf{Atom} \wedge \mathbf{Atom}) \rightarrow \exists vv((\mathbf{Atom} \wedge \mathbf{Atom}) \wedge (\mathbf{Atom} \wedge \mathbf{Atom})))$
- $\forall vv((\varphi \wedge \varphi) \rightarrow \exists vv((\varphi \wedge \varphi) \wedge (\varphi \wedge \varphi)))$
- $\forall vv((\varphi \wedge \varphi) \rightarrow \exists vv((\varphi \wedge \varphi) \wedge \varphi))$
- $\forall vv((\varphi \wedge \varphi) \rightarrow \exists vv(\varphi \wedge \varphi))$
- $\forall vv(\varphi \rightarrow \exists vv(\varphi \wedge \varphi))$
- $\forall vv(\varphi \rightarrow \exists vv\varphi)$

# Bottom-up parse

- $\forall wx((Fwx \wedge Aw) \rightarrow \exists yz((Pxy \wedge Ay) \wedge (Fxz \wedge Dz)))$
- $\forall vv((Fvv \wedge Av) \rightarrow \exists vv((Pvv \wedge Av) \wedge (Fvv \wedge Dv)))$
- $\forall vv((Pvv \wedge Pv) \rightarrow \exists vv((Pvv \wedge Pv) \wedge (Pvv \wedge Pv)))$
- $\forall vv((Ptt \wedge Pt) \rightarrow \exists vv((Ptt \wedge Pt) \wedge (Ptt \wedge Pt)))$
- $\forall vv((\mathbf{Atom} \wedge \mathbf{Atom}) \rightarrow \exists vv((\mathbf{Atom} \wedge \mathbf{Atom}) \wedge (\mathbf{Atom} \wedge \mathbf{Atom})))$
- $\forall vv((\varphi \wedge \varphi) \rightarrow \exists vv((\varphi \wedge \varphi) \wedge (\varphi \wedge \varphi)))$
- $\forall vv((\varphi \wedge \varphi) \rightarrow \exists vv((\varphi \wedge \varphi) \wedge \varphi))$
- $\forall vv((\varphi \wedge \varphi) \rightarrow \exists vv(\varphi \wedge \varphi))$
- $\forall vv(\varphi \rightarrow \exists vv(\varphi \wedge \varphi))$
- $\forall vv(\varphi \rightarrow \exists vv\varphi)$
- $\forall vv(\varphi \rightarrow \varphi)$

# Bottom-up parse

- $\forall wx((Fwx \wedge Aw) \rightarrow \exists yz((Pxy \wedge Ay) \wedge (Fxz \wedge Dz)))$
- $\forall vv((Fvv \wedge Av) \rightarrow \exists vv((Pvv \wedge Av) \wedge (Fvv \wedge Dv)))$
- $\forall vv((Pvv \wedge Pv) \rightarrow \exists vv((Pvv \wedge Pv) \wedge (Pvv \wedge Pv)))$
- $\forall vv((Ptt \wedge Pt) \rightarrow \exists vv((Ptt \wedge Pt) \wedge (Ptt \wedge Pt)))$
- $\forall vv((\mathbf{Atom} \wedge \mathbf{Atom}) \rightarrow \exists vv((\mathbf{Atom} \wedge \mathbf{Atom}) \wedge (\mathbf{Atom} \wedge \mathbf{Atom})))$
- $\forall vv((\varphi \wedge \varphi) \rightarrow \exists vv((\varphi \wedge \varphi) \wedge (\varphi \wedge \varphi)))$
- $\forall vv((\varphi \wedge \varphi) \rightarrow \exists vv((\varphi \wedge \varphi) \wedge \varphi))$
- $\forall vv((\varphi \wedge \varphi) \rightarrow \exists vv(\varphi \wedge \varphi))$
- $\forall vv(\varphi \rightarrow \exists vv(\varphi \wedge \varphi))$
- $\forall vv(\varphi \rightarrow \exists vv\varphi)$
- $\forall vv(\varphi \rightarrow \varphi)$
- $\forall vv\varphi$

# Bottom-up parse

- $\forall wx((Fwx \wedge Aw) \rightarrow \exists yz((Pxy \wedge Ay) \wedge (Fxz \wedge Dz)))$
- $\forall vv((Fvv \wedge Av) \rightarrow \exists vv((Pvv \wedge Av) \wedge (Fvv \wedge Dv)))$
- $\forall vv((Pvv \wedge Pv) \rightarrow \exists vv((Pvv \wedge Pv) \wedge (Pvv \wedge Pv)))$
- $\forall vv((Ptt \wedge Pt) \rightarrow \exists vv((Ptt \wedge Pt) \wedge (Ptt \wedge Pt)))$
- $\forall vv((\mathbf{Atom} \wedge \mathbf{Atom}) \rightarrow \exists vv((\mathbf{Atom} \wedge \mathbf{Atom}) \wedge (\mathbf{Atom} \wedge \mathbf{Atom})))$
- $\forall vv((\varphi \wedge \varphi) \rightarrow \exists vv((\varphi \wedge \varphi) \wedge (\varphi \wedge \varphi)))$
- $\forall vv((\varphi \wedge \varphi) \rightarrow \exists vv((\varphi \wedge \varphi) \wedge \varphi))$
- $\forall vv((\varphi \wedge \varphi) \rightarrow \exists vv(\varphi \wedge \varphi))$
- $\forall vv(\varphi \rightarrow \exists vv(\varphi \wedge \varphi))$
- $\forall vv(\varphi \rightarrow \exists vv\varphi)$
- $\forall vv(\varphi \rightarrow \varphi)$
- $\forall vv\varphi$
- $\varphi$



# Parsing is a search through a space of possible solutions

We can go wrong!

- $\forall wx((F_xw \wedge Aw) \rightarrow \exists yz((P_{xy} \wedge Ay) \wedge (F_{xz} \wedge Dz)))$

# Parsing is a search through a space of possible solutions

We can go wrong!

- $\forall wx((F_{xw} \wedge Aw) \rightarrow \exists yz((P_{xy} \wedge Ay) \wedge (F_{xz} \wedge Dz)))$
- $\forall \mathbf{vv}((F_{\mathbf{vv}} \wedge A\mathbf{v}) \rightarrow \exists \mathbf{vv}((P_{\mathbf{vv}} \wedge A\mathbf{v}) \wedge (F_{\mathbf{vv}} \wedge D\mathbf{v})))$

# Parsing is a search through a space of possible solutions

We can go wrong!

- $\forall wx((F_{xw} \wedge Aw) \rightarrow \exists yz((P_{xy} \wedge Ay) \wedge (F_{xz} \wedge Dz)))$
- $\forall vv((F_{vv} \wedge Av) \rightarrow \exists vv((P_{vv} \wedge Av) \wedge (F_{vv} \wedge Dv)))$
- $\forall vv((P_{vv} \wedge Pv) \rightarrow \exists vv((P_{vv} \wedge Pv) \wedge (P_{vv} \wedge Pv)))$

# Parsing is a search through a space of possible solutions

We can go wrong!

- $\forall wx((F_{xw} \wedge Aw) \rightarrow \exists yz((P_{xy} \wedge Ay) \wedge (F_{xz} \wedge Dz)))$
- $\forall vv((F_{vv} \wedge Av) \rightarrow \exists vv((P_{vv} \wedge Av) \wedge (F_{vv} \wedge Dv)))$
- $\forall vv((P_{vv} \wedge Pv) \rightarrow \exists vv((P_{vv} \wedge Pv) \wedge (P_{vv} \wedge Pv)))$
- $\forall tt((P_{tt} \wedge Pt) \rightarrow \exists tt((P_{tt} \wedge Pt) \wedge (P_{tt} \wedge Pt)))$

# Parsing is a search through a space of possible solutions

We can go wrong!

- $\forall wx((F_{xw} \wedge Aw) \rightarrow \exists yz((P_{xy} \wedge Ay) \wedge (F_{xz} \wedge Dz)))$
- $\forall vv((F_{vv} \wedge Av) \rightarrow \exists vv((P_{vv} \wedge Av) \wedge (F_{vv} \wedge Dv)))$
- $\forall vv((P_{vv} \wedge Pv) \rightarrow \exists vv((P_{vv} \wedge Pv) \wedge (P_{vv} \wedge Pv)))$
- $\forall tt((P_{tt} \wedge Pt) \rightarrow \exists tt((P_{tt} \wedge Pt) \wedge (P_{tt} \wedge Pt)))$
- $\forall tt((\mathbf{Atom} \wedge \mathbf{Atom}) \rightarrow \exists tt((\mathbf{Atom} \wedge \mathbf{Atom}) \wedge (\mathbf{Atom} \wedge \mathbf{Atom})))$

# Parsing is a search through a space of possible solutions

We can go wrong!

- $\forall wx((F_{xw} \wedge Aw) \rightarrow \exists yz((P_{xy} \wedge Ay) \wedge (F_{xz} \wedge Dz)))$
- $\forall vv((F_{vv} \wedge Av) \rightarrow \exists vv((P_{vv} \wedge Av) \wedge (F_{vv} \wedge Dv)))$
- $\forall vv((P_{vv} \wedge Pv) \rightarrow \exists vv((P_{vv} \wedge Pv) \wedge (P_{vv} \wedge Pv)))$
- $\forall tt((P_{tt} \wedge Pt) \rightarrow \exists tt((P_{tt} \wedge Pt) \wedge (P_{tt} \wedge Pt)))$
- $\forall tt((\mathbf{Atom} \wedge \mathbf{Atom}) \rightarrow \exists tt((\mathbf{Atom} \wedge \mathbf{Atom}) \wedge (\mathbf{Atom} \wedge \mathbf{Atom})))$
- $\forall tt((\varphi \wedge \varphi) \rightarrow \exists tt((\varphi \wedge \varphi) \wedge (\varphi \wedge \varphi)))$

# Parsing is a search through a space of possible solutions

We can go wrong!

- $\forall wx((F_{xw} \wedge Aw) \rightarrow \exists yz((P_{xy} \wedge Ay) \wedge (F_{xz} \wedge Dz)))$
- $\forall vv((F_{vv} \wedge Av) \rightarrow \exists vv((P_{vv} \wedge Av) \wedge (F_{vv} \wedge Dv)))$
- $\forall vv((P_{vv} \wedge Pv) \rightarrow \exists vv((P_{vv} \wedge Pv) \wedge (P_{vv} \wedge Pv)))$
- $\forall tt((P_{tt} \wedge Pt) \rightarrow \exists tt((P_{tt} \wedge Pt) \wedge (P_{tt} \wedge Pt)))$
- $\forall tt((\mathbf{Atom} \wedge \mathbf{Atom}) \rightarrow \exists tt((\mathbf{Atom} \wedge \mathbf{Atom}) \wedge (\mathbf{Atom} \wedge \mathbf{Atom})))$
- $\forall tt((\varphi \wedge \varphi) \rightarrow \exists tt((\varphi \wedge \varphi) \wedge (\varphi \wedge \varphi)))$
- $\forall tt((\varphi \wedge \varphi) \rightarrow \exists tt((\varphi \wedge \varphi) \wedge \varphi))$

# Parsing is a search through a space of possible solutions

We can go wrong!

- $\forall wx((F_xw \wedge Aw) \rightarrow \exists yz((P_{xy} \wedge Ay) \wedge (F_{xz} \wedge Dz)))$
- $\forall vv((F_{vv} \wedge Av) \rightarrow \exists vv((P_{vv} \wedge Av) \wedge (F_{vv} \wedge Dv)))$
- $\forall vv((P_{vv} \wedge Pv) \rightarrow \exists vv((P_{vv} \wedge Pv) \wedge (P_{vv} \wedge Pv)))$
- $\forall tt((P_{tt} \wedge Pt) \rightarrow \exists tt((P_{tt} \wedge Pt) \wedge (P_{tt} \wedge Pt)))$
- $\forall tt((\mathbf{Atom} \wedge \mathbf{Atom}) \rightarrow \exists tt((\mathbf{Atom} \wedge \mathbf{Atom}) \wedge (\mathbf{Atom} \wedge \mathbf{Atom})))$
- $\forall tt((\varphi \wedge \varphi) \rightarrow \exists tt((\varphi \wedge \varphi) \wedge (\varphi \wedge \varphi)))$
- $\forall tt((\varphi \wedge \varphi) \rightarrow \exists tt((\varphi \wedge \varphi) \wedge \varphi))$
- $\forall tt((\varphi \wedge \varphi) \rightarrow \exists tt(\varphi \wedge \varphi))$



# Parsing is a search through a space of possible solutions

We can go wrong!

- $\forall wx((F_{xw} \wedge Aw) \rightarrow \exists yz((P_{xy} \wedge Ay) \wedge (F_{xz} \wedge Dz)))$
- $\forall vv((F_{vv} \wedge Av) \rightarrow \exists vv((P_{vv} \wedge Av) \wedge (F_{vv} \wedge Dv)))$
- $\forall vv((P_{vv} \wedge Pv) \rightarrow \exists vv((P_{vv} \wedge Pv) \wedge (P_{vv} \wedge Pv)))$
- $\forall tt((P_{tt} \wedge Pt) \rightarrow \exists tt((P_{tt} \wedge Pt) \wedge (P_{tt} \wedge Pt)))$
- $\forall tt((\mathbf{Atom} \wedge \mathbf{Atom}) \rightarrow \exists tt((\mathbf{Atom} \wedge \mathbf{Atom}) \wedge (\mathbf{Atom} \wedge \mathbf{Atom})))$
- $\forall tt((\varphi \wedge \varphi) \rightarrow \exists tt((\varphi \wedge \varphi) \wedge (\varphi \wedge \varphi)))$
- $\forall tt((\varphi \wedge \varphi) \rightarrow \exists tt((\varphi \wedge \varphi) \wedge \varphi))$
- $\forall tt((\varphi \wedge \varphi) \rightarrow \exists tt(\varphi \wedge \varphi))$
- $\forall tt(\varphi \rightarrow \exists tt(\varphi \wedge \varphi))$

# Parsing is a search through a space of possible solutions

We can go wrong!

- $\forall wx((F_{xw} \wedge Aw) \rightarrow \exists yz((P_{xy} \wedge Ay) \wedge (F_{xz} \wedge Dz)))$
- $\forall vv((F_{vv} \wedge Av) \rightarrow \exists vv((P_{vv} \wedge Av) \wedge (F_{vv} \wedge Dv)))$
- $\forall vv((P_{vv} \wedge Pv) \rightarrow \exists vv((P_{vv} \wedge Pv) \wedge (P_{vv} \wedge Pv)))$
- $\forall tt((P_{tt} \wedge Pt) \rightarrow \exists tt((P_{tt} \wedge Pt) \wedge (P_{tt} \wedge Pt)))$
- $\forall tt((\mathbf{Atom} \wedge \mathbf{Atom}) \rightarrow \exists tt((\mathbf{Atom} \wedge \mathbf{Atom}) \wedge (\mathbf{Atom} \wedge \mathbf{Atom})))$
- $\forall tt((\varphi \wedge \varphi) \rightarrow \exists tt((\varphi \wedge \varphi) \wedge (\varphi \wedge \varphi)))$
- $\forall tt((\varphi \wedge \varphi) \rightarrow \exists tt((\varphi \wedge \varphi) \wedge \varphi))$
- $\forall tt((\varphi \wedge \varphi) \rightarrow \exists tt(\varphi \wedge \varphi))$
- $\forall tt(\varphi \rightarrow \exists tt(\varphi \wedge \varphi))$
- $\forall tt(\varphi \rightarrow \exists tt \varphi)$

# Parsing is a search through a space of possible solutions

We can go wrong!

- $\forall wx((F_xw \wedge Aw) \rightarrow \exists yz((P_{xy} \wedge Ay) \wedge (F_{xz} \wedge Dz)))$
- $\forall vv((F_{vv} \wedge Av) \rightarrow \exists vv((P_{vv} \wedge Av) \wedge (F_{vv} \wedge Dv)))$
- $\forall vv((P_{vv} \wedge Pv) \rightarrow \exists vv((P_{vv} \wedge Pv) \wedge (P_{vv} \wedge Pv)))$
- $\forall tt((P_{tt} \wedge Pt) \rightarrow \exists tt((P_{tt} \wedge Pt) \wedge (P_{tt} \wedge Pt)))$
- $\forall tt((\mathbf{Atom} \wedge \mathbf{Atom}) \rightarrow \exists tt((\mathbf{Atom} \wedge \mathbf{Atom}) \wedge (\mathbf{Atom} \wedge \mathbf{Atom})))$
- $\forall tt((\varphi \wedge \varphi) \rightarrow \exists tt((\varphi \wedge \varphi) \wedge (\varphi \wedge \varphi)))$
- $\forall tt((\varphi \wedge \varphi) \rightarrow \exists tt((\varphi \wedge \varphi) \wedge \varphi))$
- $\forall tt((\varphi \wedge \varphi) \rightarrow \exists tt(\varphi \wedge \varphi))$
- $\forall tt(\varphi \rightarrow \exists tt(\varphi \wedge \varphi))$
- $\forall tt(\varphi \rightarrow \exists tt \varphi)$
- Stuck! No rule applies, so we must backtrack.

# Parsing is a search through a space of possible solutions

We can go wrong!

- $\forall wx((F_{xw} \wedge A_w) \rightarrow \exists yz((P_{xy} \wedge A_y) \wedge (F_{xz} \wedge D_z)))$
- $\forall vv((F_{vv} \wedge A_v) \rightarrow \exists vv((P_{vv} \wedge A_v) \wedge (F_{vv} \wedge D_v)))$
- $\forall vv((P_{vv} \wedge P_v) \rightarrow \exists vv((P_{vv} \wedge P_v) \wedge (P_{vv} \wedge P_v)))$
- $\forall tt((P_{tt} \wedge P_t) \rightarrow \exists tt((P_{tt} \wedge P_t) \wedge (P_{tt} \wedge P_t)))$
- $\forall tt((\mathbf{Atom} \wedge \mathbf{Atom}) \rightarrow \exists tt((\mathbf{Atom} \wedge \mathbf{Atom}) \wedge (\mathbf{Atom} \wedge \mathbf{Atom})))$
- $\forall tt((\varphi \wedge \varphi) \rightarrow \exists tt((\varphi \wedge \varphi) \wedge (\varphi \wedge \varphi)))$
- $\forall tt((\varphi \wedge \varphi) \rightarrow \exists tt((\varphi \wedge \varphi) \wedge \varphi))$
- $\forall tt((\varphi \wedge \varphi) \rightarrow \exists tt(\varphi \wedge \varphi))$
- $\forall tt(\varphi \rightarrow \exists tt(\varphi \wedge \varphi))$
- $\forall tt(\varphi \rightarrow \exists tt \varphi)$
- Stuck! No rule applies, so we must backtrack.
- A conforming expression should have *some* path to our start symbol, but how do we program software to make the right choices?

# Parsing as search

- Grammars like the ones we've seen typically have the parsing problem of which rules to apply in which order.

# Parsing as search

- Grammars like the ones we've seen typically have the parsing problem of which rules to apply in which order.
- Nondeterministic parsing software explores one path of choices, and if no rule applies will back up and try a different path.

# Parsing as search

- Grammars like the ones we've seen typically have the parsing problem of which rules to apply in which order.
- Nondeterministic parsing software explores one path of choices, and if no rule applies will back up and try a different path.
- If all possible paths are exhausted for an expression, then the parse fails because the expression doesn't conform to the grammar.

# Parsing as search

- Grammars like the ones we've seen typically have the parsing problem of which rules to apply in which order.
- Nondeterministic parsing software explores one path of choices, and if no rule applies will back up and try a different path.
- If all possible paths are exhausted for an expression, then the parse fails because the expression doesn't conform to the grammar.
- The time required to explore all those possibilities is expensive, even for very fast computers.



# Parsing as search

- Grammars like the ones we've seen typically have the parsing problem of which rules to apply in which order.
- Nondeterministic parsing software explores one path of choices, and if no rule applies will back up and try a different path.
- If all possible paths are exhausted for an expression, then the parse fails because the expression doesn't conform to the grammar.
- The time required to explore all those possibilities is expensive, even for very fast computers.
- Rules of thumb (heuristics) for ordering the productions can save time, but only on average.

# Parsing as search

- Grammars like the ones we've seen typically have the parsing problem of which rules to apply in which order.
- Nondeterministic parsing software explores one path of choices, and if no rule applies will back up and try a different path.
- If all possible paths are exhausted for an expression, then the parse fails because the expression doesn't conform to the grammar.
- The time required to explore all those possibilities is expensive, even for very fast computers.
- Rules of thumb (heuristics) for ordering the productions can save time, but only on average.
- Ideally we'd like an efficient and deterministic path through the search space that allows us to quit early if the expression doesn't conform.

# Parsing as search

- Grammars like the ones we've seen typically have the parsing problem of which rules to apply in which order.
- Nondeterministic parsing software explores one path of choices, and if no rule applies will back up and try a different path.
- If all possible paths are exhausted for an expression, then the parse fails because the expression doesn't conform to the grammar.
- The time required to explore all those possibilities is expensive, even for very fast computers.
- Rules of thumb (heuristics) for ordering the productions can save time, but only on average.
- Ideally we'd like an efficient and deterministic path through the search space that allows us to quit early if the expression doesn't conform.
- It turns out that some languages are easy to parse: consider, for example, the set of strings consisting of the letter 'b'.

# An easy URL subset grammar

Consider this simple syntax for a subset of URL web addresses:

- Conforming expressions will all begin with `http://`

# An easy URL subset grammar

Consider this simple syntax for a subset of URL web addresses:

- Conforming expressions will all begin with `http://`
- followed by strings of one or more lower case letters that are separated by periods,

# An easy URL subset grammar

Consider this simple syntax for a subset of URL web addresses:

- Conforming expressions will all begin with `http://`
- followed by strings of one or more lower case letters that are separated by periods,
- the last such string will be one of `com`, `org`, or `edu`,

# An easy URL subset grammar

Consider this simple syntax for a subset of URL web addresses:

- Conforming expressions will all begin with `http://`
- followed by strings of one or more lower case letters that are separated by periods,
- the last such string will be one of `com`, `org`, or `edu`,
- then there's a slash,

# An easy URL subset grammar

Consider this simple syntax for a subset of URL web addresses:

- Conforming expressions will all begin with `http://`
- followed by strings of one or more lower case letters that are separated by periods,
- the last such string will be one of `com`, `org`, or `edu`,
- then there's a slash,
- then zero or more strings of lower case letters that are separated by slashes



# An easy URL subset grammar

Consider this simple syntax for a subset of URL web addresses:

- Conforming expressions will all begin with `http://`
- followed by strings of one or more lower case letters that are separated by periods,
- the last such string will be one of `com`, `org`, or `edu`,
- then there's a slash,
- then zero or more strings of lower case letters that are separated by slashes
- with one of those slashes being the rightmost character.

# An easy URL subset grammar

Consider this simple syntax for a subset of URL web addresses:

- Conforming expressions will all begin with `http://`
- followed by strings of one or more lower case letters that are separated by periods,
- the last such string will be one of `com`, `org`, or `edu`,
- then there's a slash,
- then zero or more strings of lower case letters that are separated by slashes
- with one of those slashes being the rightmost character.
- We can easily parse this from left to right, and quit right away if one of the rules is broken.

# Parsing a URL

- `http://www.whatever.something.com/abc/cba/wxy/qrs/`

# Parsing a URL

- `http://www.whatever.something.com/abc/cba/wxy/qrs/`
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**

# Parsing a URL

- `http://www.whatever.something.com/abc/cba/wxy/qrs/`
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**

# Parsing a URL

- `http://www.whatever.something.com/abc/cba/wxy/qrs/`
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**

# Parsing a URL

- `http://www.whatever.something.com/abc/cba/wxy/qrs/`
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**

# Parsing a URL

- `http://www.whatever.something.com/abc/cba/wxy/qrs/`
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**



# Parsing a URL

- `http://www.whatever.something.com/abc/cba/wxy/qrs/`
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**

# Parsing a URL

- `http://www.whatever.something.com/abc/cba/wxy/qrs/`
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**

# Parsing a URL

- `http://www.whatever.something.com/abc/cba/wxy/qrs/`
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**

# Parsing a URL

- `http://www.whatever.something.com/abc/cba/wxy/qrs/`
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**

# Parsing a URL

- `http://www.whatever.something.com/abc/cba/wxy/qrs/`
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **`http://www.whatever.something.com/abc/cba/wxy/qrs/`**
- **Success!**

# Regular expressions

- We can summarize the URL subset grammar using *regular expression* notation.

# Regular expressions

- We can summarize the URL subset grammar using *regular expression* notation.
- Not all grammars can be encoded this way, but those that can will admit the kind of efficient, left-to-right parsing shown on the previous slide.

# Regular expressions

- We can summarize the URL subset grammar using *regular expression* notation.
- Not all grammars can be encoded this way, but those that can will admit the kind of efficient, left-to-right parsing shown on the previous slide.
- Most popular programming languages, and many text editors include support for regular expressions.



# Regular expressions

- We can summarize the URL subset grammar using *regular expression* notation.
- Not all grammars can be encoded this way, but those that can will admit the kind of efficient, left-to-right parsing shown on the previous slide.
- Most popular programming languages, and many text editors include support for regular expressions.
- The full grammar is expressed as  
`(http://)(([a-z]+)\.)+(com|org|edu)/(([a-z]+)/)*`

# Regular expressions

- We can summarize the URL subset grammar using *regular expression* notation.
- Not all grammars can be encoded this way, but those that can will admit the kind of efficient, left-to-right parsing shown on the previous slide.
- Most popular programming languages, and many text editors include support for regular expressions.
- The full grammar is expressed as  
`(http://)(([a-z]+)\.)+(com|org|edu)/((([a-z]+))/)*`
- `[a-z]` means any single lower case letter.

# Regular expressions

- We can summarize the URL subset grammar using *regular expression* notation.
- Not all grammars can be encoded this way, but those that can will admit the kind of efficient, left-to-right parsing shown on the previous slide.
- Most popular programming languages, and many text editors include support for regular expressions.
- The full grammar is expressed as  
`(http://)(([a-z]+)\.)+(com|org|edu)/((([a-z]+))/)*`
- `[a-z]` means any single lower case letter.
- `[a-z]+` means a string of one or more lower case letters.

# Regular expressions

- We can summarize the URL subset grammar using *regular expression* notation.
- Not all grammars can be encoded this way, but those that can will admit the kind of efficient, left-to-right parsing shown on the previous slide.
- Most popular programming languages, and many text editors include support for regular expressions.
- The full grammar is expressed as  
`(http://)(([a-z]+)\.)+(com|org|edu)/((([a-z]+))/)*`
- `[a-z]` means any single lower case letter.
- `[a-z]+` means a string of one or more lower case letters.
- `\.` means a literal period.

# Regular expressions

- We can summarize the URL subset grammar using *regular expression* notation.
- Not all grammars can be encoded this way, but those that can will admit the kind of efficient, left-to-right parsing shown on the previous slide.
- Most popular programming languages, and many text editors include support for regular expressions.
- The full grammar is expressed as  
`(http://)(([a-z]+)\.)+(com|org|edu)/((([a-z]+))/)*`
- `[a-z]` means any single lower case letter.
- `[a-z]+` means a string of one or more lower case letters.
- `\.` means a literal period.
- `(([a-z]+)\.)+(com|org|edu)` means one or more sequences of lower case letter strings separated by periods.

# Regular expressions

`(http://)(([a-z]+\.)+(com|org|edu)/)(([a-z]+)/)*`

- `(com|org|edu)` means one of either `com`, `org`, or `edu`.

# Regular expressions

`(http://)(([a-z]+\.)+(com|org|edu)/([a-z]+)/)*`

- `(com|org|edu)` means one of either `com`, `org`, or `edu`.
- `(([a-z]+)/)*` means zero or more lower case letter strings separated by slashes.

# Regular expressions

`(http://)(([a-z]+\.)+(com|org|edu)/)(([a-z]+)/)*`

- `(com|org|edu)` means one of either `com`, `org`, or `edu`.
- `(([a-z]+)/)*` means zero or more lower case letter strings separated by slashes.
- So `(http://)(([a-z]+\.)+(com|org|edu)/)(([a-z]+)/)*` means:



`(http://)(([a-z]+\.)+(com|org|edu)/)(([a-z]+)/)*`

- `(com|org|edu)` means one of either `com`, `org`, or `edu`.
- `(([a-z]+)/)*` means zero or more lower case letter strings separated by slashes.
- So `(http://)(([a-z]+\.)+(com|org|edu)/)(([a-z]+)/)*` means:
  - `http://` followed by

`(http://)(([a-z]+\.)+(com|org|edu)/)(([a-z]+)/)*`

- `(com|org|edu)` means one of either `com`, `org`, or `edu`.
- `(([a-z]+)/)*` means zero or more lower case letter strings separated by slashes.
- So `(http://)(([a-z]+\.)+(com|org|edu)/)(([a-z]+)/)*` means:
  - `http://` followed by
  - one or more strings of lower case letters, separated by periods, followed by

`(http://)(([a-z]+\.)+(com|org|edu)/([a-z]+)/)*`

- `(com|org|edu)` means one of either `com`, `org`, or `edu`.
- `(([a-z]+)/)*` means zero or more lower case letter strings separated by slashes.
- So `(http://)(([a-z]+\.)+(com|org|edu)/([a-z]+)/)*` means:
  - `http://` followed by
  - one or more strings of lower case letters, separated by periods, followed by
  - one of either `com`, `org`, or `edu`,

# Regular expressions

`(http://)(([a-z]+\.)+(com|org|edu)/)(([a-z]+)/)*`

- `(com|org|edu)` means one of either `com`, `org`, or `edu`.
- `(([a-z]+)/)*` means zero or more lower case letter strings separated by slashes.
- So `(http://)(([a-z]+\.)+(com|org|edu)/)(([a-z]+)/)*` means:
  - `http://` followed by
  - one or more strings of lower case letters, separated by periods, followed by
  - one of either `com`, `org`, or `edu`,
  - followed by a slash, followed by

`(http://)(([a-z]+\.)+(com|org|edu)/)(([a-z]+)/)*`

- `(com|org|edu)` means one of either `com`, `org`, or `edu`.
- `(([a-z]+)/)*` means zero or more lower case letter strings separated by slashes.
- So `(http://)(([a-z]+\.)+(com|org|edu)/)(([a-z]+)/)*` means:
  - `http://` followed by
  - one or more strings of lower case letters, separated by periods, followed by
  - one of either `com`, `org`, or `edu`,
  - followed by a slash, followed by
  - zero or more lower case letter strings separated by slashes.

# Abstract state machines

- We can diagram the rules for the URL subset grammar as a state transition diagram.

# Abstract state machines

- We can diagram the rules for the URL subset grammar as a state transition diagram.
- States (circles) are situations or configurations of the parser.

# Abstract state machines

- We can diagram the rules for the URL subset grammar as a state transition diagram.
- States (circles) are situations or configurations of the parser.
- As we parse the string from left to right, we try to move from the start state (circle number 1) to the goal state (circle 7).



# Abstract state machines

- We can diagram the rules for the URL subset grammar as a state transition diagram.
- States (circles) are situations or configurations of the parser.
- As we parse the string from left to right, we try to move from the start state (circle number 1) to the goal state (circle 7).
- If our input matches the label on an arc, we can follow that arrow.

# Abstract state machines

- We can diagram the rules for the URL subset grammar as a state transition diagram.
- States (circles) are situations or configurations of the parser.
- As we parse the string from left to right, we try to move from the start state (circle number 1) to the goal state (circle 7).
- If our input matches the label on an arc, we can follow that arrow.
- Otherwise we look for a default arc labeled with an asterisk.

# Abstract state machines

- We can diagram the rules for the URL subset grammar as a state transition diagram.
- States (circles) are situations or configurations of the parser.
- As we parse the string from left to right, we try to move from the start state (circle number 1) to the goal state (circle 7).
- If our input matches the label on an arc, we can follow that arrow.
- Otherwise we look for a default arc labeled with an asterisk.
- Our first diagram is almost deterministic, but may still require some backtracking.

# Abstract state machines

- We can diagram the rules for the URL subset grammar as a state transition diagram.
- States (circles) are situations or configurations of the parser.
- As we parse the string from left to right, we try to move from the start state (circle number 1) to the goal state (circle 7).
- If our input matches the label on an arc, we can follow that arrow.
- Otherwise we look for a default arc labeled with an asterisk.
- Our first diagram is almost deterministic, but may still require some backtracking.
- The second diagram adds some additional states and arcs, but is completely deterministic.

# Nondeterministic Finite State Automaton




Figure 1: NFA Parser for URL grammar

# Deterministic Finite State Automaton




Figure 2: DFA Parser for URL grammar

# Top-down derivation

Derivation (a term you read in Rosen) is parsing in reverse.

- $\varphi$

# Top-down derivation

Derivation (a term you read in Rosen) is parsing in reverse.

- $\varphi$
- $\forall v \varphi$



# Top-down derivation

Derivation (a term you read in Rosen) is parsing in reverse.

- $\varphi$
- $\forall \mathbf{v} \varphi$
- $\forall \mathbf{v} (\varphi \leftrightarrow \varphi)$

# Top-down derivation

Derivation (a term you read in Rosen) is parsing in reverse.

- $\varphi$
- $\forall \mathbf{v} \varphi$
- $\forall \mathbf{v}(\varphi \leftrightarrow \varphi)$
- $\forall \mathbf{v}(\varphi \leftrightarrow \exists \mathbf{v} \varphi)$

# Top-down derivation

Derivation (a term you read in Rosen) is parsing in reverse.

- $\varphi$
- $\forall \mathbf{v} \varphi$
- $\forall \mathbf{v}(\varphi \leftrightarrow \varphi)$
- $\forall \mathbf{v}(\varphi \leftrightarrow \exists \mathbf{v} \varphi)$
- $\forall \mathbf{v}(\mathbf{Atom} \leftrightarrow \exists \mathbf{v} \varphi)$

# Top-down derivation

Derivation (a term you read in Rosen) is parsing in reverse.

- $\varphi$
- $\forall \mathbf{v} \varphi$
- $\forall \mathbf{v}(\varphi \leftrightarrow \varphi)$
- $\forall \mathbf{v}(\varphi \leftrightarrow \exists \mathbf{v} \varphi)$
- $\forall \mathbf{v}(\mathbf{Atom} \leftrightarrow \exists \mathbf{v} \varphi)$
- $\forall \mathbf{v}(\mathbf{Atom} \leftrightarrow \exists \mathbf{v} \mathbf{Atom})$

# Top-down derivation

Derivation (a term you read in Rosen) is parsing in reverse.

- $\varphi$
- $\forall \mathbf{v} \varphi$
- $\forall \mathbf{v}(\varphi \leftrightarrow \varphi)$
- $\forall \mathbf{v}(\varphi \leftrightarrow \exists \mathbf{v} \varphi)$
- $\forall \mathbf{v}(\mathbf{Atom} \leftrightarrow \exists \mathbf{v} \varphi)$
- $\forall \mathbf{v}(\mathbf{Atom} \leftrightarrow \exists \mathbf{v} \mathbf{Atom})$
- $\forall \mathbf{v}(\mathbf{Pt} \leftrightarrow \exists \mathbf{v} \mathbf{Atom})$

# Top-down derivation

Derivation (a term you read in Rosen) is parsing in reverse.

- $\varphi$
- $\forall \mathbf{v} \varphi$
- $\forall \mathbf{v}(\varphi \leftrightarrow \varphi)$
- $\forall \mathbf{v}(\varphi \leftrightarrow \exists \mathbf{v} \varphi)$
- $\forall \mathbf{v}(\mathbf{Atom} \leftrightarrow \exists \mathbf{v} \varphi)$
- $\forall \mathbf{v}(\mathbf{Atom} \leftrightarrow \exists \mathbf{v} \mathbf{Atom})$
- $\forall \mathbf{v}(\mathbf{Pt} \leftrightarrow \exists \mathbf{v} \mathbf{Atom})$
- $\forall \mathbf{v}(\mathbf{Pt} \leftrightarrow \exists \mathbf{v} \mathbf{Ptt})$

# Top-down derivation

Derivation (a term you read in Rosen) is parsing in reverse.

- $\varphi$
- $\forall \mathbf{v} \varphi$
- $\forall \mathbf{v} (\varphi \leftrightarrow \varphi)$
- $\forall \mathbf{v} (\varphi \leftrightarrow \exists \mathbf{v} \varphi)$
- $\forall \mathbf{v} (\mathbf{Atom} \leftrightarrow \exists \mathbf{v} \varphi)$
- $\forall \mathbf{v} (\mathbf{Atom} \leftrightarrow \exists \mathbf{v} \mathbf{Atom})$
- $\forall \mathbf{v} (\mathbf{Pt} \leftrightarrow \exists \mathbf{v} \mathbf{Atom})$
- $\forall \mathbf{v} (\mathbf{Pt} \leftrightarrow \exists \mathbf{v} \mathbf{Ptt})$
- $\forall \mathbf{v} (\mathbf{Pv} \leftrightarrow \exists \mathbf{v} \mathbf{Pvv})$

# Top-down derivation

Derivation (a term you read in Rosen) is parsing in reverse.

- $\varphi$
- $\forall \mathbf{v} \varphi$
- $\forall \mathbf{v} (\varphi \leftrightarrow \varphi)$
- $\forall \mathbf{v} (\varphi \leftrightarrow \exists \mathbf{v} \varphi)$
- $\forall \mathbf{v} (\mathbf{Atom} \leftrightarrow \exists \mathbf{v} \varphi)$
- $\forall \mathbf{v} (\mathbf{Atom} \leftrightarrow \exists \mathbf{v} \mathbf{Atom})$
- $\forall \mathbf{v} (\mathbf{Pt} \leftrightarrow \exists \mathbf{v} \mathbf{Atom})$
- $\forall \mathbf{v} (\mathbf{Pt} \leftrightarrow \exists \mathbf{v} \mathbf{Ptt})$
- $\forall \mathbf{v} (\mathbf{Pv} \leftrightarrow \exists \mathbf{v} \mathbf{Pvv})$
- $\forall \mathbf{v} (\mathbf{Pv} \leftrightarrow \exists \mathbf{v} \mathbf{Lv v})$



# Top-down derivation

Derivation (a term you read in Rosen) is parsing in reverse.

- $\varphi$
- $\forall \mathbf{v} \varphi$
- $\forall \mathbf{v} (\varphi \leftrightarrow \varphi)$
- $\forall \mathbf{v} (\varphi \leftrightarrow \exists \mathbf{v} \varphi)$
- $\forall \mathbf{v} (\mathbf{Atom} \leftrightarrow \exists \mathbf{v} \varphi)$
- $\forall \mathbf{v} (\mathbf{Atom} \leftrightarrow \exists \mathbf{v} \mathbf{Atom})$
- $\forall \mathbf{v} (\mathbf{Pt} \leftrightarrow \exists \mathbf{v} \mathbf{Atom})$
- $\forall \mathbf{v} (\mathbf{Pt} \leftrightarrow \exists \mathbf{v} \mathbf{Ptt})$
- $\forall \mathbf{v} (\mathbf{Pv} \leftrightarrow \exists \mathbf{v} \mathbf{Pvv})$
- $\forall \mathbf{v} (\mathbf{Pv} \leftrightarrow \exists \mathbf{v} \mathbf{Lv v})$
- $\forall \mathbf{v} (\mathbf{Vv} \leftrightarrow \exists \mathbf{v} \mathbf{Lv v})$

# Top-down derivation

Derivation (a term you read in Rosen) is parsing in reverse.

- $\varphi$
- $\forall \mathbf{v} \varphi$
- $\forall \mathbf{v} (\varphi \leftrightarrow \varphi)$
- $\forall \mathbf{v} (\varphi \leftrightarrow \exists \mathbf{v} \varphi)$
- $\forall \mathbf{v} (\mathbf{Atom} \leftrightarrow \exists \mathbf{v} \varphi)$
- $\forall \mathbf{v} (\mathbf{Atom} \leftrightarrow \exists \mathbf{v} \mathbf{Atom})$
- $\forall \mathbf{v} (\mathbf{Pt} \leftrightarrow \exists \mathbf{v} \mathbf{Atom})$
- $\forall \mathbf{v} (\mathbf{Pt} \leftrightarrow \exists \mathbf{v} \mathbf{Ptt})$
- $\forall \mathbf{v} (\mathbf{Pv} \leftrightarrow \exists \mathbf{v} \mathbf{Pvv})$
- $\forall \mathbf{v} (\mathbf{Pv} \leftrightarrow \exists \mathbf{v} \mathbf{Lv v})$
- $\forall \mathbf{v} (\mathbf{Vv} \leftrightarrow \exists \mathbf{v} \mathbf{Lv v})$
- $\forall \mathbf{v} (\mathbf{Vv} \leftrightarrow \exists \mathbf{z} \mathbf{Lv z})$

# Top-down derivation

Derivation (a term you read in Rosen) is parsing in reverse.

- $\varphi$
- $\forall \mathbf{v} \varphi$
- $\forall \mathbf{v}(\varphi \leftrightarrow \varphi)$
- $\forall \mathbf{v}(\varphi \leftrightarrow \exists \mathbf{v} \varphi)$
- $\forall \mathbf{v}(\mathbf{Atom} \leftrightarrow \exists \mathbf{v} \varphi)$
- $\forall \mathbf{v}(\mathbf{Atom} \leftrightarrow \exists \mathbf{v} \mathbf{Atom})$
- $\forall \mathbf{v}(\mathbf{Pt} \leftrightarrow \exists \mathbf{v} \mathbf{Atom})$
- $\forall \mathbf{v}(\mathbf{Pt} \leftrightarrow \exists \mathbf{v} \mathbf{Ptt})$
- $\forall \mathbf{v}(\mathbf{Pv} \leftrightarrow \exists \mathbf{v} \mathbf{Pvv})$
- $\forall \mathbf{v}(\mathbf{Pv} \leftrightarrow \exists \mathbf{v} \mathbf{Lv v})$
- $\forall \mathbf{v}(\mathbf{Vv} \leftrightarrow \exists \mathbf{v} \mathbf{Lv v})$
- $\forall \mathbf{v}(\mathbf{Vv} \leftrightarrow \exists \mathbf{z} \mathbf{Lv z})$
- $\forall \mathbf{x}(\mathbf{Vx} \leftrightarrow \exists \mathbf{z} \mathbf{Lxz})$

*A vocabulary (or alphabet)  $V$  is a finite nonempty set of elements, called symbols. A word (or sentence) over  $V$  is a string of finite length of elements of  $V$ . The empty string or null string, denoted by  $\lambda$ , is the string containing no symbols. The set of all words over  $V$  is denoted by  $V^*$ . A language over  $V$  is a subset of  $V^*$ .*

*A phrase-structure grammar  $G = \langle V, T, S, P \rangle$  consists of a vocabulary  $V$ , a subset  $T$  of  $V$  consisting of terminal elements, a start symbol  $S$  from  $V$ , and a set of productions  $P$ . The set  $V - T$  is denoted by  $N$ . Elements of  $N$  are called nonterminal symbols. Every production in  $P$  must contain at least one nonterminal on its left side.*

# Phrase-structure grammar

```
<protocol> ::= http://  
<letter>   ::= a|b|c|d|e|f|g|h|i|j|k|l|m  
<letter>   ::= n|o|p|q|r|s|t|u|v|w|x|y|z  
<slash>    ::= /  
<dot>      ::= .  
<string>   ::= <letter><string>|<letter>  
<host>     ::= <string><dot><host>|<string><dot>  
<domain>   ::= com|org|edu  
<site>     ::= <host><domain><slash>  
<dir>      ::= <string><slash>  
<body>     ::= <dir><body>|<dir>  
<url>      ::= <protocol><site><body>|<protocol><site>
```

# Rosen on languages and derivability

*Let  $G = \langle V, T, S, P \rangle$  be a phrase-structure grammar. Let  $w_0 = lz_0r$  (that is, the concatenation of  $l$ ,  $z_0$ , and  $r$ ) and  $w_1 = lz_1r$  be strings over  $V$ . If  $z_0 \rightarrow z_1$  is a production of  $G$ , we say that  $w_1$  is directly derivable from  $w_0$  and we write  $w_0 \Rightarrow w_1$ . If  $w_0, w_1, \dots, w_n, n \geq 0$ , are strings over  $V$  such that  $w_0 \Rightarrow w_1, w_1 \Rightarrow w_2, \dots, w_{n-1} \Rightarrow w_n$ , then we say that  $w_n$  is derivable from  $w_0$ , and we write  $w_0 \xRightarrow{*} w_n$ . The sequence of steps used to obtain  $w_n$  from  $w_0$  is called a derivation.*

*Let  $G = \langle V, T, S, P \rangle$  be a phrase-structure grammar. Let  $w_0 = lz_0r$  (that is, the concatenation of  $l$ ,  $z_0$ , and  $r$ ) and  $w_1 = lz_1r$  be strings over  $V$ . If  $z_0 \rightarrow z_1$  is a production of  $G$ , we say that  $w_1$  is directly derivable from  $w_0$  and we write  $w_0 \Rightarrow w_1$ . If  $w_0, w_1, \dots, w_n, n \geq 0$ , are strings over  $V$  such that  $w_0 \Rightarrow w_1, w_1 \Rightarrow w_2, \dots, w_{n-1} \Rightarrow w_n$ , then we say that  $w_n$  is derivable from  $w_0$ , and we write  $w_0 \xRightarrow{*} w_n$ . The sequence of steps used to obtain  $w_n$  from  $w_0$  is called a derivation.*

*Let  $G = \langle V, T, S, P \rangle$  be a phrase-structure grammar. The language generated by  $G$  (or the language of  $G$ ), denoted by  $L(G)$ , is the set of all strings of terminals that are derivable from the starting state  $S$ . In other words,  $L(G) = \{w \in T^* \mid S \xRightarrow{*} w\}$ .*



# Production type determines grammar classification

Per Rosen, section 10.1:

- A *type 0* grammar has no restriction on its productions.

# Production type determines grammar classification

Per Rosen, section 10.1:

- A *type 0* grammar has no restriction on its productions.
- A *type 1* grammar can have productions only of the form  $w_1 \rightarrow w_2$ , where the length of  $w_2$  is greater than or equal to the length of  $w_1$ , or of the form  $w_1 \rightarrow \lambda$ .

# Production type determines grammar classification

Per Rosen, section 10.1:

- A *type 0* grammar has no restriction on its productions.
- A *type 1* grammar can have productions only of the form  $w_1 \rightarrow w_2$ , where the length of  $w_2$  is greater than or equal to the length of  $w_1$ , or of the form  $w_1 \rightarrow \lambda$ .
- A *type 2* (context free) grammar can have productions only of the form  $w_1 \rightarrow w_2$ , where  $w_1$  is a single symbol that is not a terminal symbol.

# Production type determines grammar classification

Per Rosen, section 10.1:

- A *type 0* grammar has no restriction on its productions.
- A *type 1* grammar can have productions only of the form  $w_1 \rightarrow w_2$ , where the length of  $w_2$  is greater than or equal to the length of  $w_1$ , or of the form  $w_1 \rightarrow \lambda$ .
- A *type 2* (context free) grammar can have productions only of the form  $w_1 \rightarrow w_2$ , where  $w_1$  is a single symbol that is not a terminal symbol.
- A *type 3* (regular) grammar can have productions only of the form  $w_1 \rightarrow w_2$  with  $w_1 = A$ , and either  $w_2 = aB$  or  $w_2 = a$ , where  $A$  and  $B$  are nonterminal symbols and  $a$  is a terminal symbol, or with  $w_1 = S$  and  $w_2 = \lambda$ .

# Chomsky hierarchy implications

- Regular languages (like our URL subset) can be summarized using DFAs, NFAs, and regular expressions.

# Chomsky hierarchy implications

- Regular languages (like our URL subset) can be summarized using DFAs, NFAs, and regular expressions.
- Therefore, their expressions can be parsed in very little time, using little memory.

# Chomsky hierarchy implications

- Regular languages (like our URL subset) can be summarized using DFAs, NFAs, and regular expressions.
- Therefore, their expressions can be parsed in very little time, using little memory.
- Our grammars for propositional and predicate logic are *not* regular, but they are context free.

# Chomsky hierarchy implications

- Regular languages (like our URL subset) can be summarized using DFAs, NFAs, and regular expressions.
- Therefore, their expressions can be parsed in very little time, using little memory.
- Our grammars for propositional and predicate logic are *not* regular, but they are context free.
- No regular expression is powerful enough to recognize any arbitrary logic expression, because logics admit arbitrarily deep levels of nesting: we can always open up a new set of parentheses, just as with Boolean search languages.



# Chomsky hierarchy implications

- Regular languages (like our URL subset) can be summarized using DFAs, NFAs, and regular expressions.
- Therefore, their expressions can be parsed in very little time, using little memory.
- Our grammars for propositional and predicate logic are *not* regular, but they are context free.
- No regular expression is powerful enough to recognize any arbitrary logic expression, because logics admit arbitrarily deep levels of nesting: we can always open up a new set of parentheses, just as with Boolean search languages.
- Parsing non-regular, context free languages like our logic grammar always requires a stack memory, and often requires backtracking.

# Chomsky hierarchy implications

- Regular languages (like our URL subset) can be summarized using DFAs, NFAs, and regular expressions.
- Therefore, their expressions can be parsed in very little time, using little memory.
- Our grammars for propositional and predicate logic are *not* regular, but they are context free.
- No regular expression is powerful enough to recognize any arbitrary logic expression, because logics admit arbitrarily deep levels of nesting: we can always open up a new set of parentheses, just as with Boolean search languages.
- Parsing non-regular, context free languages like our logic grammar always requires a stack memory, and often requires backtracking.
- We can usually tell that a language is not regular by seeing whether its productions meet Rosen's constraints.

# Context free, non-regular grammars

- $\mathbf{v} ::= x|y|z|\dots$

# Context free, non-regular grammars

- $\mathbf{v} ::= x|y|z|\dots$
- $\mathbf{c} ::= a|b|c|\dots$

# Context free, non-regular grammars

- $\mathbf{v} ::= x|y|z|\dots$
- $\mathbf{c} ::= a|b|c|\dots$
- $\mathbf{t} ::= \mathbf{v}|\mathbf{c}$

# Context free, non-regular grammars

- $\mathbf{v} ::= x|y|z|\dots$
- $\mathbf{c} ::= a|b|c|\dots$
- $\mathbf{t} ::= \mathbf{v}|\mathbf{c}$
- $\mathbf{P} ::= P|Q|R|\dots$

# Context free, non-regular grammars

- $\mathbf{v} ::= x|y|z|\dots$
- $\mathbf{c} ::= a|b|c|\dots$
- $\mathbf{t} ::= \mathbf{v}|\mathbf{c}$
- $\mathbf{P} ::= P|Q|R|\dots$
- $\mathbf{Atom} ::= \mathbf{P}t_1\dots t_n$  where  $n$  is the arity of  $\mathbf{P}$

# Context free, non-regular grammars

- $\mathbf{v} ::= x|y|z|\dots$
- $\mathbf{c} ::= a|b|c|\dots$
- $\mathbf{t} ::= \mathbf{v}|\mathbf{c}$
- $\mathbf{P} ::= P|Q|R|\dots$
- $\mathbf{Atom} ::= \mathbf{P}t_1\dots t_n$  where  $n$  is the arity of  $\mathbf{P}$
- $\varphi ::= \mathbf{Atom}|\neg\varphi|(\varphi \wedge \varphi)|(\varphi \vee \varphi)|(\varphi \rightarrow \varphi)|(\varphi \leftrightarrow \varphi)|\forall \mathbf{v}\varphi|\exists \mathbf{v}\varphi$



# Caveats for the Rosen definitions

- Being regular and being context-free are really properties of languages, not grammars.

# Caveats for the Rosen definitions

- Being regular and being context-free are really properties of languages, not grammars.
- Some grammars that don't satisfy Rosen's type 3 definition still summarize regular languages.

# Caveats for the Rosen definitions

- Being regular and being context-free are really properties of languages, not grammars.
- Some grammars that don't satisfy Rosen's type 3 definition still summarize regular languages.
- It can be challenging to verify whether a language is regular just by looking at the productions.

# The URL subset is a regular language

```
<protocol> ::= http://  
<letter>   ::= a|b|c|d|e|f|g|h|i|j|k|l|m  
<letter>   ::= n|o|p|q|r|s|t|u|v|w|x|y|z  
<slash>    ::= /  
<dot>      ::= .  
<string>   ::= <letter><string>|<letter>  
<host>     ::= <string><dot><host>|<string><dot>  
<domain>   ::= com|org|edu  
<site>     ::= <host><domain><slash>  
<dir>      ::= <string><slash>  
<body>     ::= <dir><body>|<dir>  
<url>      ::= <protocol><site><body>|<protocol><site>
```

# Context free, non-regular grammars

- $\langle \text{const} \rangle ::= a|b|c|d|e|f|g|h|i|j|k|l|m|n|o|p$

# Context free, non-regular grammars

- $\langle \text{const} \rangle ::= a|b|c|d|e|f|g|h|i|j|k|l|m|n|o|p$
- $\langle \text{var} \rangle ::= q|r|s|t|u|v|w|x|y|z$

# Context free, non-regular grammars

- $\langle \text{const} \rangle ::= a|b|c|d|e|f|g|h|i|j|k|l|m|n|o|p$
- $\langle \text{var} \rangle ::= q|r|s|t|u|v|w|x|y|z$
- $\langle \text{pred} \rangle ::= A|B|C|D|E|F|G|H|I|J|K|L|M$

# Context free, non-regular grammars

- $\langle \text{const} \rangle ::= a|b|c|d|e|f|g|h|i|j|k|l|m|n|o|p$
- $\langle \text{var} \rangle ::= q|r|s|t|u|v|w|x|y|z$
- $\langle \text{pred} \rangle ::= A|B|C|D|E|F|G|H|I|J|K|L|M$
- $\langle \text{pred} \rangle ::= N|O|P|Q|R|S|T|U|V|W|X|Y|Z$



# Context free, non-regular grammars

- $\langle \text{const} \rangle ::= a|b|c|d|e|f|g|h|i|j|k|l|m|n|o|p$
- $\langle \text{var} \rangle ::= q|r|s|t|u|v|w|x|y|z$
- $\langle \text{pred} \rangle ::= A|B|C|D|E|F|G|H|I|J|K|L|M$
- $\langle \text{pred} \rangle ::= N|O|P|Q|R|S|T|U|V|W|X|Y|Z$
- $\langle \text{lp} \rangle ::= ($

# Context free, non-regular grammars

- $\langle \text{const} \rangle ::= a|b|c|d|e|f|g|h|i|j|k|l|m|n|o|p$
- $\langle \text{var} \rangle ::= q|r|s|t|u|v|w|x|y|z$
- $\langle \text{pred} \rangle ::= A|B|C|D|E|F|G|H|I|J|K|L|M$
- $\langle \text{pred} \rangle ::= N|O|P|Q|R|S|T|U|V|W|X|Y|Z$
- $\langle \text{lp} \rangle ::= ($
- $\langle \text{rp} \rangle ::= )$

# Context free, non-regular grammars

- $\langle \text{const} \rangle ::= a|b|c|d|e|f|g|h|i|j|k|l|m|n|o|p$
- $\langle \text{var} \rangle ::= q|r|s|t|u|v|w|x|y|z$
- $\langle \text{pred} \rangle ::= A|B|C|D|E|F|G|H|I|J|K|L|M$
- $\langle \text{pred} \rangle ::= N|O|P|Q|R|S|T|U|V|W|X|Y|Z$
- $\langle \text{lp} \rangle ::= ($
- $\langle \text{rp} \rangle ::= )$
- $\langle \text{quant} \rangle ::= \forall|\exists$

# Context free, non-regular grammars

- $\langle \text{const} \rangle ::= a|b|c|d|e|f|g|h|i|j|k|l|m|n|o|p$
- $\langle \text{var} \rangle ::= q|r|s|t|u|v|w|x|y|z$
- $\langle \text{pred} \rangle ::= A|B|C|D|E|F|G|H|I|J|K|L|M$
- $\langle \text{pred} \rangle ::= N|O|P|Q|R|S|T|U|V|W|X|Y|Z$
- $\langle \text{lp} \rangle ::= ($
- $\langle \text{rp} \rangle ::= )$
- $\langle \text{quant} \rangle ::= \forall|\exists$
- $\langle \text{not} \rangle ::= \neg$

# Context free, non-regular grammars

- $\langle \text{const} \rangle ::= a|b|c|d|e|f|g|h|i|j|k|l|m|n|o|p$
- $\langle \text{var} \rangle ::= q|r|s|t|u|v|w|x|y|z$
- $\langle \text{pred} \rangle ::= A|B|C|D|E|F|G|H|I|J|K|L|M$
- $\langle \text{pred} \rangle ::= N|O|P|Q|R|S|T|U|V|W|X|Y|Z$
- $\langle \text{lp} \rangle ::= ($
- $\langle \text{rp} \rangle ::= )$
- $\langle \text{quant} \rangle ::= \forall|\exists$
- $\langle \text{not} \rangle ::= \neg$
- $\langle \text{binop} \rangle ::= \wedge|\vee|\rightarrow|\leftrightarrow$

# Context free, non-regular grammars

- $\langle \text{const} \rangle ::= a|b|c|d|e|f|g|h|i|j|k|l|m|n|o|p$
- $\langle \text{var} \rangle ::= q|r|s|t|u|v|w|x|y|z$
- $\langle \text{pred} \rangle ::= A|B|C|D|E|F|G|H|I|J|K|L|M$
- $\langle \text{pred} \rangle ::= N|O|P|Q|R|S|T|U|V|W|X|Y|Z$
- $\langle \text{lp} \rangle ::= ($
- $\langle \text{rp} \rangle ::= )$
- $\langle \text{quant} \rangle ::= \forall|\exists$
- $\langle \text{not} \rangle ::= \neg$
- $\langle \text{binop} \rangle ::= \wedge|\vee|\rightarrow|\leftrightarrow$
- $\langle \text{term} \rangle ::= \langle \text{const} \rangle|\langle \text{var} \rangle$

# Context free, non-regular grammars

- $\langle \text{const} \rangle ::= a|b|c|d|e|f|g|h|i|j|k|l|m|n|o|p$
- $\langle \text{var} \rangle ::= q|r|s|t|u|v|w|x|y|z$
- $\langle \text{pred} \rangle ::= A|B|C|D|E|F|G|H|I|J|K|L|M$
- $\langle \text{pred} \rangle ::= N|O|P|Q|R|S|T|U|V|W|X|Y|Z$
- $\langle \text{lp} \rangle ::= ($
- $\langle \text{rp} \rangle ::= )$
- $\langle \text{quant} \rangle ::= \forall|\exists$
- $\langle \text{not} \rangle ::= \neg$
- $\langle \text{binop} \rangle ::= \wedge|\vee|\rightarrow|\leftrightarrow$
- $\langle \text{term} \rangle ::= \langle \text{const} \rangle|\langle \text{var} \rangle$
- $\langle \text{atom} \rangle ::= \langle \text{pred} \rangle \langle \text{term} \rangle|\langle \text{atom} \rangle \langle \text{term} \rangle$

# Context free, non-regular grammars

- $\langle \text{const} \rangle ::= a|b|c|d|e|f|g|h|i|j|k|l|m|n|o|p$
- $\langle \text{var} \rangle ::= q|r|s|t|u|v|w|x|y|z$
- $\langle \text{pred} \rangle ::= A|B|C|D|E|F|G|H|I|J|K|L|M$
- $\langle \text{pred} \rangle ::= N|O|P|Q|R|S|T|U|V|W|X|Y|Z$
- $\langle \text{lp} \rangle ::= ($
- $\langle \text{rp} \rangle ::= )$
- $\langle \text{quant} \rangle ::= \forall|\exists$
- $\langle \text{not} \rangle ::= \neg$
- $\langle \text{binop} \rangle ::= \wedge|\vee|\rightarrow|\leftrightarrow$
- $\langle \text{term} \rangle ::= \langle \text{const} \rangle|\langle \text{var} \rangle$
- $\langle \text{atom} \rangle ::= \langle \text{pred} \rangle\langle \text{term} \rangle|\langle \text{atom} \rangle\langle \text{term} \rangle$
- $\langle \text{phi} \rangle ::= \langle \text{atom} \rangle|\langle \text{not} \rangle\langle \text{phi} \rangle|\langle \text{quant} \rangle\langle \text{var} \rangle\langle \text{phi} \rangle$



# Context free, non-regular grammars

- $\langle \text{const} \rangle ::= a|b|c|d|e|f|g|h|i|j|k|l|m|n|o|p$
- $\langle \text{var} \rangle ::= q|r|s|t|u|v|w|x|y|z$
- $\langle \text{pred} \rangle ::= A|B|C|D|E|F|G|H|I|J|K|L|M$
- $\langle \text{pred} \rangle ::= N|O|P|Q|R|S|T|U|V|W|X|Y|Z$
- $\langle \text{lp} \rangle ::= ($
- $\langle \text{rp} \rangle ::= )$
- $\langle \text{quant} \rangle ::= \forall|\exists$
- $\langle \text{not} \rangle ::= \neg$
- $\langle \text{binop} \rangle ::= \wedge|\vee|\rightarrow|\leftrightarrow$
- $\langle \text{term} \rangle ::= \langle \text{const} \rangle|\langle \text{var} \rangle$
- $\langle \text{atom} \rangle ::= \langle \text{pred} \rangle\langle \text{term} \rangle|\langle \text{atom} \rangle\langle \text{term} \rangle$
- $\langle \text{phi} \rangle ::= \langle \text{atom} \rangle|\langle \text{not} \rangle\langle \text{phi} \rangle|\langle \text{quant} \rangle\langle \text{var} \rangle\langle \text{phi} \rangle$
- $\langle \text{phi} \rangle ::= \langle \text{lp} \rangle\langle \text{phi} \rangle\langle \text{binop} \rangle\langle \text{phi} \rangle\langle \text{rp} \rangle$

# Parsing context free languages

- Adding a stack memory to our NFA gives us a *push down automaton* (PDA).

# Parsing context free languages

- Adding a stack memory to our NFA gives us a *push down automaton* (PDA).
- We only access a stack at one end: pushing a symbol on top, or popping one off and discarding it.

# Parsing context free languages

- Adding a stack memory to our NFA gives us a *push down automaton* (PDA).
- We only access a stack at one end: pushing a symbol on top, or popping one off and discarding it.
- We can't search for a symbol in the middle of a stack, but that means that stack access is always independent of how much material is stored there.

# Parsing context free languages

- Adding a stack memory to our NFA gives us a *push down automaton* (PDA).
- We only access a stack at one end: pushing a symbol on top, or popping one off and discarding it.
- We can't search for a symbol in the middle of a stack, but that means that stack access is always independent of how much material is stored there.
- Transitions on the next diagram include requirements for the next input symbol (just like the NFA), operations on the stack, or both.

# Parsing context free languages

- Adding a stack memory to our NFA gives us a *push down automaton* (PDA).
- We only access a stack at one end: pushing a symbol on top, or popping one off and discarding it.
- We can't search for a symbol in the middle of a stack, but that means that stack access is always independent of how much material is stored there.
- Transitions on the next diagram include requirements for the next input symbol (just like the NFA), operations on the stack, or both.
- -/- means leave the stack unchanged;

# Parsing context free languages

- Adding a stack memory to our NFA gives us a *push down automaton* (PDA).
- We only access a stack at one end: pushing a symbol on top, or popping one off and discarding it.
- We can't search for a symbol in the middle of a stack, but that means that stack access is always independent of how much material is stored there.
- Transitions on the next diagram include requirements for the next input symbol (just like the NFA), operations on the stack, or both.
- $-/-$  means leave the stack unchanged;
- $/\$$  means push  $\$$  on the top of the stack;

# Parsing context free languages

- Adding a stack memory to our NFA gives us a *push down automaton* (PDA).
- We only access a stack at one end: pushing a symbol on top, or popping one off and discarding it.
- We can't search for a symbol in the middle of a stack, but that means that stack access is always independent of how much material is stored there.
- Transitions on the next diagram include requirements for the next input symbol (just like the NFA), operations on the stack, or both.
- $-/-$  means leave the stack unchanged;
- $/\$$  means push  $\$$  on the top of the stack;
- $\$/$  means pop  $\$$  off the top of the stack;



# Pushdown Automaton




Figure 3: PDA Parser for the predicate logic grammar