

1 Data-Structure

1.1 Treap

```

1 template<class S,
2     S (*node_pull)(S, S),
3     S (*node_init)(S),
4     class T,
5     S (*mapping)(S, T),
6     T (*tag_pull)(T, T),
7     T (*tag_init)()>
8 struct Treap{
9     struct node{
10         node *l = NULL,*r = NULL,*p = NULL;
11         int pri = mt(),sz = 1;
12         S info;
13         T tag = tag_init();
14         bool rev;
15         node(S k) : info(k){}
16         ~node(){
17             for(auto &i:{l,r})
18                 delete i;
19         }
20         void all_apply(T t,bool is_rev){
21             if(is_rev){
22                 swap(l,r);
23                 rev^=1;
24             }
25             info = mapping(info, t);
26             tag = tag_pull(tag, t);
27         }
28         void push(){
29             for(auto &i:{l,r})
30                 if(i)i->all_apply(tag, rev);
31             tag = tag_init();
32             rev = 0;
33         }
34         void pull(){
35             sz = 1,info = node_init(info);
36             for(auto &i:{l,r}){
37                 if(i){
38                     sz+=i->sz,i->p = this;
39                     info = node_pull(info,i->info);
40                 }
41             }
42         }
43     };
44     node *root = NULL;
45     int size(node *a){
46         return a?a->sz:0;
47     }
48     int size(){
49         return size(root);
50     }
51     node *merge(node *a,node *b){
52         if(!a or !b)return a?:b;
53         if(a->pri>b->pri){
54             a->push();
55             a->r = merge(a->r,b);
56             a->r->p = a;
57             a->pull();
58             return a;
59         }
60         else{
61             b->push();
62             b->l = merge(a,b->l);
63             b->l->p = b;
64             b->pull();
65             return b;
66         }
67     }
68     void split(node *t, long long k, node *&a, node *&b, bool bst)
69     {
70         if(!t){a = b = NULL;return;}
71         t->push();
72         if((bst==0 and size(t->l)+1<=k) or (bst==1 and t->info.key
73             <=k)){
74             a = t;
75             split(t->r, ( bst ? k : k - size(t->l) - 1 ), a->r, b,
76                 bst);
77             if(b)b->p = NULL;
78             a->pull();
79         }
80         else{
81             b = t;
82             split(t->l, k, a, b->l, bst);
83             if(a)a->p = NULL;
84             b->pull();
85         }
86     }
87     node *insert(long long idx, S x,bool bst = 0){
88         node *a,*b;
89         split(root, idx, a, b, bst);
90         node *tmp = new node(x);

```

```

88         root = merge(a, merge(tmp, b));
89         return tmp;
90     }
91     void erase(long long l,long long r,bool bst = 0){
92         node *a,*b,*c;
93         split(root, (bst? l-1 : l), a, b, bst);
94         split(b, (bst? r : r - l + 1), b, c, bst);
95         delete b;
96         root = merge(a,c);
97     }
98     S operator [](int x){
99         node *a, *b, *c;
100         split(root, x, a, b, 0);
101         split(b, 1, b, c, 0);
102         assert(b!=NULL);
103         S ans = b->info;
104         root = merge(a, merge(b, c));
105         return ans;
106     }
107     void update(long long l,long long r,T t,bool bst = 0){
108         node *a, *b, *c;
109         split(root, (bst? l - 1 : l), a, b, bst);
110         split(b, (bst? r : r - l + 1), b, c, bst);
111         if(b)b->all_apply(t, 0);
112         root = merge(a, merge(b, c));
113     }
114     void reverse(long long l,long long r,bool bst = 0){
115         node *a, *b, *c;
116         split(root, (bst? l - 1 : l), a, b, bst);
117         split(b, (bst? r : r - l + 1), b, c, bst);
118         if(b)b->all_apply(tag_init(), 1);
119         root = merge(a, merge(b, c));
120     }
121     int rank(long long k){
122         node *a, *b;
123         split(root, k - 1, a, b, 1);
124         int ans = size(a);
125         root = merge(a, b);
126         return ans;
127     }
128     S* find_next(long long k){
129         node *a, *b, *c;
130         split(root, k - 1, a, b, 1);
131         split(b, 1, b, c, 0);
132         S* ans = NULL;
133         if(b)ans = &b->info;
134         root = merge(a, merge(b, c));
135         return ans;
136     }
137     S* find_prev(long long k){
138         node *a, *b, *c;
139         split(root, k , a, b, 1);
140         split(a, size(a) - 1, a, c, 0);
141         S* ans = NULL;
142         if(c)ans = &c->info;
143         root = merge(merge(a, c), b);
144         return ans;
145     }
146     S query(long long l,long long r,bool bst = 0){
147         node *a, *b, *c;
148         split(root, (bst? l - 1 : l), a, b, bst);
149         split(b, (bst? r : r - l + 1), b, c, bst);
150         assert(b!=NULL);
151         S ans = b->info;
152         root = merge(a, merge(b, c));
153         return ans;
154     }
155 };

```

1.2 Segtree

```

1 template<class S,
2     S (*node_pull)(S, S),
3     S (*node_init)(),
4     class T,
5     S (*mapping)(S, T),
6     T (*tag_pull)(T, T),
7     T (*tag_init)()>
8 struct segment_tree{
9     struct node{
10         S seg;
11         T tag = tag_init();
12         int l,r;
13         node(S _seg = node_init(),int _l = -1,int _r = -1) : seg(
14             _seg), l(_l), r(_r){}
15         friend node operator +(const node &lhs,const node &rhs){
16             if(lhs.l==-1)return rhs;
17             if(rhs.l==-1)return lhs;
18             return node(node_pull(lhs.seg,rhs.seg),lhs.l,rhs.r);
19         }
20     };
21     vector<node>arr;
22     void all_apply(int idx,T t){
23         arr[idx].seg = mapping(arr[idx].seg, t);

```

```

23     arr[idx].tag = tag_pull(arr[idx].tag, t);
24 }
25 void push(int idx){
26     all_apply(idx<<1, arr[idx].tag);
27     all_apply(idx<<1|1, arr[idx].tag);
28     arr[idx].tag = tag_init();
29 }
30 inline void build(const vector<S> &v, const int &l, const int &
31     r, int idx = 1){
32     if(idx==1)arr.resize((r-l+1)<<2);
33     if(l==r){
34         arr[idx].seg = v[l];
35         arr[idx].tag = tag_init();
36         arr[idx].l = arr[idx].r = l;
37         return;
38     }
39     int m = (l+r)>>1;
40     build(v, l, m, idx<<1);
41     build(v, m+1, r, idx<<1|1);
42     arr[idx] = arr[idx<<1]+arr[idx<<1|1];
43 }
44 inline void update(const int &q1, const int &qr, T t, int idx =
45     1){
46     assert(q1<=qr);
47     if(q1<=arr[idx].l and arr[idx].r<=qr){
48         all_apply(idx, t);
49         return;
50     }
51     push(idx);
52     int m = (arr[idx].l+arr[idx].r)>>1;
53     if(q1<=m)update(q1, qr, t, idx<<1);
54     if(qr>m)update(q1, qr, t, idx<<1|1);
55     arr[idx] = arr[idx<<1]+arr[idx<<1|1];
56 }
57 inline S query(const int &q1, const int &qr, int idx = 1){
58     assert(q1<=qr);
59     if(q1<=arr[idx].l and arr[idx].r<=qr){
60         return arr[idx].seg;
61     }
62     push(idx);
63     int m = (arr[idx].l+arr[idx].r)>>1;
64     S ans = node_init(), lhs = node_init(), rhs = node_init();
65     if(q1<=m)lhs = query(q1, qr, idx<<1);
66     if(qr>m)rhs = query(q1, qr, idx<<1|1);
67     ans = node_pull(lhs, rhs);
68     return ans;
69 }
70 };

```

1.3 DsuUndo

```

1 struct dsu_undo{
2     vector<int>sz, p;
3     int comps;
4     dsu_undo(int n){
5         sz.assign(n+5, 1);
6         p.resize(n+5);
7         for(int i = 1; i<=n; ++i)p[i] = i;
8         comps = n;
9     }
10    vector<pair<int, int>>opt;
11    int Find(int x){
12        return x==p[x]?x:Find(p[x]);
13    }
14    bool Union(int a, int b){
15        int pa = Find(a), pb = Find(b);
16        if(pa==pb)return 0;
17        if(sz[pa]<sz[pb])swap(pa, pb);
18        sz[pa]+=sz[pb];
19        p[pb] = pa;
20        opt.push_back({pa, pb});
21        comps--;
22        return 1;
23    }
24    void undo(){
25        auto [pa, pb] = opt.back();
26        opt.pop_back();
27        p[pb] = pb;
28        sz[pa]-=sz[pb];
29        comps++;
30    }
31 };

```

1.4 DSU

```

1 struct DSU{
2     vector<int>sz;
3     int n;
4     DSU(int _n):n(_n){
5         sz.assign(n+1, -1);
6     }

```

```

7     int Find(int x){
8         return sz[x]<0?x:sz[x] = Find(sz[x]);
9     }
10    bool Union(int a, int b){
11        int pa = Find(a), pb = Find(b);
12        if(pa==pb)return 0;
13        if((-sz[pa])<(-sz[pb]))swap(pa, pb);
14        sz[pa]+=sz[pb];
15        sz[pb] = pa;
16        return 1;
17    }
18 };

```

1.5 Fenwick

```

1 template<class T>struct fenwick_tree{
2     int n;
3     vector<T>arr;
4     inline int lowbit(int x){
5         return x&(-x);
6     }
7     fenwick_tree(int _n):n(_n){
8         arr.assign(n+5, 0);
9     }
10    T query(int x){
11        T ans = 0;
12        for(int i = x; i>0; i-=lowbit(i)){
13            ans+=arr[i];
14        }
15        return ans;
16    }
17    void update(int x, T y){
18        for(int i = x; i<=n; i+=lowbit(i)){
19            arr[i]+=y;
20        }
21    }
22 };

```

1.6 Persistent DSU

```

1 int rk[200001] = {};
2 struct Persistent_DSU{
3     rope<int>*p;
4     int n;
5     Persistent_DSU(int _n = 0):n(_n){
6         if(n==0)return;
7         p = new rope<int>;
8         int tmp[n+1] = {};
9         for(int i = 1; i<=n; ++i)tmp[i] = i;
10        p->append(tmp, n+1);
11    }
12    Persistent_DSU(const Persistent_DSU &tmp){
13        p = new rope<int>(*tmp.p);
14        n = tmp.n;
15    }
16    int Find(int x){
17        int px = p->at(x);
18        return px==x?x:Find(px);
19    }
20    bool Union(int a, int b){
21        int pa = Find(a), pb = Find(b);
22        if(pa==pb)return 0;
23        if(rk[pa]<rk[pb])swap(pa, pb);
24        p->replace(pb, pa);
25        if(rk[pa]==rk[pb])rk[pa]++;
26        return 1;
27    }
28 };

```

1.7 TimingSegtree

```

1 template<class T, class D>struct timing_segment_tree{
2     struct node{
3         int l, r;
4         vector<T>opt;
5     };
6     vector<node>arr;
7     void build(int l, int r, int idx = 1){
8         if(idx==1)arr.resize((r-l+1)<<2);
9         if(l==r){
10            arr[idx].l = arr[idx].r = l;
11            arr[idx].opt.clear();
12            return;
13        }
14        int m = (l+r)>>1;
15        build(l, m, idx<<1);
16        build(m+1, r, idx<<1|1);
17        arr[idx].l = l, arr[idx].r = r;
18        arr[idx].opt.clear();

```

```

19 }
20 void update(int ql,int qr,T k,int idx = 1){
21     if(ql<=arr[idx].l and arr[idx].r<=qr){
22         arr[idx].opt.push_back(k);
23         return;
24     }
25     int m = (arr[idx].l+arr[idx].r)>>1;
26     if(ql<=m)update(ql,qr,k,idx<<1);
27     if(qr>m)update(ql,qr,k,idx<<1|1);
28 }
29 void dfs(D &d,vector<int>&ans,int idx = 1){
30     int cnt = 0;
31     for(auto [a,b]:arr[idx].opt){
32         if(d.Union(a,b))cnt++;
33     }
34     if(arr[idx].l==arr[idx].r)ans[arr[idx].l] = d.comps;
35     else{
36         dfs(d,ans,idx<<1);
37         dfs(d,ans,idx<<1|1);
38     }
39     while(cnt-->0)d.undo();
40 }
41 };

```

1.8 AreaOfRectangles

```

1 long long AreaOfRectangles(vector<tuple<int,int,int,int>>v){
2     vector<tuple<int,int,int,int>>tmp;
3     int L = INT_MAX,R = INT_MIN;
4     for(auto [x1,y1,x2,y2]:v){
5         tmp.push_back({x1,y1+1,y2,1});
6         tmp.push_back({x2,y1+1,y2,-1});
7         R = max(R,y2);
8         L = min(L,y1);
9     }
10    vector<long long>seg((R-L+1)<<2),tag((R-L+1)<<2);
11    sort(tmp.begin(),tmp.end());
12    function<void(int,int,int,int,int,int)>update = [&](int ql,
13        int qr,int val,int l,int r,int idx){
14        if(ql<=l and r<=qr){
15            tag[idx]+=val;
16            if(tag[idx])seg[idx] = r-l+1;
17            else if(l==r)seg[idx] = 0;
18            else seg[idx] = seg[idx<<1]+seg[idx<<1|1];
19            return;
20        }
21        int m = (l+r)>>1;
22        if(ql<=m)update(ql,qr,val,l,m,idx<<1);
23        if(qr>m)update(ql,qr,val,m+1,r,idx<<1|1);
24        if(tag[idx])seg[idx] = r-l+1;
25        else seg[idx] = seg[idx<<1]+seg[idx<<1|1];
26    };
27    long long last_pos = 0,ans = 0;
28    for(auto [pos,l,r,val]:tmp){
29        ans+=(pos-last_pos)*seg[l];
30        update(l,r,val,L,R,1);
31        last_pos = pos;
32    }
33    return ans;
34 }

```

1.9 SparseTable

```

1 template<class T,T (*op)(T,T)>struct sparse_table{
2     int n;
3     vector<vector<T>>mat;
4     sparse_table(): n(0){}
5     sparse_table(const vector<T>&v){
6         n = (int)(v.size());
7         mat.resize(30);
8         mat[0] = v;
9         for(int i = 1;(1<<i)<=n;++i){
10             mat[i].resize(n-(1<<i)+1);
11             for(int j = 0;j<n-(1<<i)+1;++j){
12                 mat[i][j] = op(mat[i-1][j],mat[i-1][j+(1<<(i-1))]);
13             }
14         }
15     }
16     T query(int ql,int qr){
17         int k = __lg(qr-ql+1);
18         return op(mat[k][ql],mat[k][qr-(1<<k)+1]);
19     }
20 };

```

1.10 VEBTree

```

1 // Can correctly work with numbers in range [0; MAXN]
2 // Supports all std::set operations in O(1) on random queries /
3 // dense arrays, O(log64(N)) in worst case (sparse array).
4 // Count operation works in O(1) always.
5 template<unsigned int MAXN>
6 class fast_set {
7 private:
8     static const unsigned int PREF = (MAXN <= 64 ? 0 :
9         MAXN <= 4096 ? 1 :
10         MAXN <= 262144 ? 1 + 64 :
11         MAXN <= 16777216 ? 1 + 64 + 4096 :
12         MAXN <= 1073741824 ? 1 + 64 + 4096 + 262144 :
13         227) + 1;
14     static constexpr unsigned long long lowest_bits11[] = {0ULL,
15         1ULL, 3ULL, 7ULL, 15ULL, 31ULL, 63ULL, 127ULL, 255ULL,
16         511ULL, 1023ULL, 2047ULL, 4095ULL, 8191ULL, 16383ULL,
17         32767ULL, 65535ULL, 131071ULL, 262143ULL, 524287ULL,
18         1048575ULL, 2097151ULL, 4194303ULL, 8388607ULL, 16777215ULL,
19         33554431ULL, 67108863ULL, 134217727ULL, 268435455ULL,
20         536870911ULL, 1073741823ULL, 2147483647ULL, 4294967295ULL,
21         8589934591ULL, 17179869183ULL, 34359738367ULL,
22         68719476735ULL, 137438953471ULL, 274877906943ULL,
23         549755813887ULL, 1099511627775ULL, 2199023255551ULL,
24         4398046511103ULL, 8796093022207ULL, 17592186044415ULL,
25         35184372088831ULL, 70368744177663ULL, 140737488355327ULL,
26         281474976710655ULL, 562949953421311ULL, 1125899906842623ULL,
27         2251799813685247ULL, 4503599627370495ULL,
28         9007199254740991ULL, 18014398509481983ULL,
29         36028797018963967ULL, 72057594037927935ULL,
30         144115188075855871ULL, 288230376151711743ULL,
31         576460752303423487ULL, 1152921504606846975ULL,
32         2305843009213693951ULL, 4611686018427387903ULL,
33         9223372036854775807ULL, 18446744073709551615ULL};
34     static const unsigned int SZ = PREF + (MAXN + 63) / 64 + 1;
35     unsigned long long m[SZ] = {0};
36
37     inline unsigned int left(unsigned int v) const {
38         return (v - 62) * 64;
39     }
40
41     inline unsigned int parent(unsigned int v) const {
42         return v / 64 + 62;
43     }
44
45     inline void setbit(unsigned int v) {
46         m[v >> 6] |= 1ULL << (v & 63);
47     }
48
49     inline void resetbit(unsigned int v) {
50         m[v >> 6] &= ~(1ULL << (v & 63));
51     }
52
53     inline unsigned int getbit(unsigned int v) const {
54         return m[v >> 6] >> (v & 63) & 1;
55     }
56
57     inline unsigned long long childs_value(unsigned int v) const {
58         return m[left(v) >> 6];
59     }
60
61     inline int left_go(unsigned int x, const unsigned int c) const {
62         const unsigned long long rem = x & 63;
63         unsigned int bt = PREF * 64 + x;
64         unsigned long long num = m[bt >> 6] & lowest_bits11[rem + c];
65         if(num) {
66             return (x ^ rem) | __lg(num);
67         }
68         for(bt = parent(bt); bt > 62; bt = parent(bt)) {
69             const unsigned long long rem = bt & 63;
70             num = m[bt >> 6] & lowest_bits11[rem];
71             if(num) {
72                 bt = (bt ^ rem) | __lg(num);
73                 break;
74             }
75         }
76         if(bt == 62) {
77             return -1;
78         }
79         while(bt < PREF * 64) {
80             bt = left(bt) | __lg(m[bt - 62]);
81         }
82         return bt - PREF * 64;
83     }
84
85     inline int right_go(unsigned int x, const unsigned int c) const {
86         const unsigned long long rem = x & 63;
87         unsigned int bt = PREF * 64 + x;
88         unsigned long long num = m[bt >> 6] & ~lowest_bits11[rem + c];
89         if(num) {
90             return (x ^ rem) | __builtin_ctzll(num);
91         }
92         for(bt = parent(bt); bt > 62; bt = parent(bt)) {

```

```

22     const unsigned long long rem = bt & 63;
23     num = m[bt >> 6] & ~lowest_bitsll[rem + 1];
24     if(num) {
25         bt = (bt ^ rem) | __builtin_ctzll(num);
26         break;
27     }
28 }
29 if(bt == 62) {
30     return -1;
31 }
32 while(bt < PREF * 64) {
33     bt = left(bt) | __builtin_ctzll(m[bt - 62]);
34 }
35 return bt - PREF * 64;
36 }
37
38 public:
39 fast_set() {
40     assert(PREF != 228);
41     setbit(62);
42 }
43
44 bool empty() const {return getbit(63);}
45
46 void clear() {
47     fill(m, m + SZ, 0);
48     setbit(62);
49 }
50
51 bool count(unsigned int x) const {
52     return m[PREF + (x >> 6)] >> (x & 63) & 1;
53 }
54
55 void insert(unsigned int x) {
56     for(unsigned int v = PREF * 64 + x; !getbit(v); v = parent(
57         v)){
58         setbit(v);
59     }
60 }
61
62 void erase(unsigned int x) {
63     if(!getbit(PREF * 64 + x)) {
64         return;
65     }
66     resetbit(PREF * 64 + x);
67     for(unsigned int v = parent(PREF * 64 + x); v > 62 && !
68         childs_value(v); v = parent(v)) {
69         resetbit(v);
70     }
71 }
72
73 int find_next(unsigned int x) const {
74     return right_go(x, 0);
75 }
76
77 int find_prev(unsigned int x) const {
78     return left_go(x, 1);
79 }
80 };

```

1.11 DynamicSegtree

```

1
2 template<class T>struct dynamic_segment_tree{
3     struct node{
4         node *l = NULL,*r = NULL;
5         T sum;
6         node(T k = 0): sum(k){}
7         node(node *p){if(p)*this = *p;}
8         ~node(){
9             for(auto &i:{l,r})
10                 if(i)delete i;
11         }
12         void pull(){
13             sum = 0;
14             for(auto i:{l,r})
15                 if(i)sum+=i->sum;
16         }
17     }*root = NULL;
18     int n;
19     dynamic_segment_tree(){}
20     dynamic_segment_tree(const dynamic_segment_tree<T>&tmp){root
21         = new node(tmp.root);}
22     void update(node *&t,int pos,T k,int l,int r){
23         if(!t)t = new node();
24         if(l==r)return t = new node(k),void();
25         int m = (l+r)>>1;
26         t = new node(t);
27         if(pos<=m)update(t->l,pos,k,l,m);
28         else update(t->r,pos,k,m+1,r);
29         t->pull();
30     }void update(int pos,T k,int l = -1e9,int r = 1e9){update(
31         root,pos,k,l,r);}
32     T query(node *&t,int ql,int qr,int l,int r){

```

```

31     if(!t)return 0;
32     if(ql<=l and r<=qr)return t->sum;
33     int m = (l+r)>>1;
34     T ans = 0;
35     if(ql<=m)ans+=query(t->l,ql,qr,l,m);
36     if(qr>m)ans+=query(t->r,ql,qr,m+1,r);
37     return ans;
38 }T query(int ql,int qr,int l = -1e9,int r = 1e9){return query
39     (root,ql,qr,l,r);}
40 };

```

1.12 ZkwSegtree

```

1 template<class S,
2     S (*node_pull)(S, S),
3     S (*node_init)(),
4     class F,
5     S (*mapping)(S, F),
6     F (*tag_pull)(F, F),
7     F (*tag_init)()>
8 class segment_tree {
9 public:
10     segment_tree() : segment_tree(0) {}
11     explicit segment_tree(int _n) : segment_tree(vector<S>(_n,
12         node_init())) {}
13     explicit segment_tree(const vector<S>& v) : n((int) v.size())
14     {
15         log = std::__lg(2 * n - 1);
16         size = 1 << log;
17         d = vector<S>(size << 1, node_init());
18         lz = vector<F>(size, tag_init());
19         for(int i = 0; i < n; i++) {
20             d[size + i] = v[i];
21         }
22         for(int i = size - 1; i; --i) {
23             update(i);
24         }
25     }
26     void set(int p, S x) {
27         assert(0 <= p && p < n);
28         p += size;
29         for(int i = log; i; --i) {
30             push(p >> i);
31         }
32         d[p] = x;
33         for(int i = 1; i <= log; ++i) {
34             update(p >> i);
35         }
36     }
37     S get(int p) {
38         assert(0 <= p && p < n);
39         p += size;
40         for(int i = log; i; --i) {
41             push(p >> i);
42         }
43         return d[p];
44     }
45     S operator[](int p) {
46         return get(p);
47     }
48     S query(int l, int r) {
49         r++;
50         assert(l<=r);
51         l += size;
52         r += size;
53         for(int i = log; i; i--) {
54             if(((l >> i) << i) != 1) {
55                 push(l >> i);
56             }
57             if(((r >> i) << i) != r) {
58                 push(r >> i);
59             }
60         }
61         S sml = node_init(), smr = node_init();
62         while(l < r) {
63             if(l & 1) {
64                 sml = node_pull(sml, d[l++]);
65             }
66             if(r & 1) {
67                 smr = node_pull(d[--r], smr);
68             }
69             l >>= 1;
70             r >>= 1;
71         }
72         return node_pull(sml, smr);
73     }
74     void apply(int p, F f) {
75         assert(0 <= p && p < n);
76         p += size;
77         for(int i = log; i; i--) {
78             push(p >> i);
79         }
80         d[p] = mapping(f, d[p]);
81         for(int i = 1; i <= log; i++) {

```

```

80     update(p >> i);
81 }
82 }
83 void update(int l, int r, F f) {
84     r++;
85     assert(l<=r);
86     l += size;
87     r += size;
88     for(int i = log; i; i--) {
89         if(((l >> i) << i) != 1) {
90             push(l >> i);
91         }
92         if(((r >> i) << i) != r) {
93             push((r - 1) >> i);
94         }
95     }
96     {
97         int l2 = l, r2 = r;
98         while(l < r) {
99             if(l & 1) {
100                 all_apply(l++, f);
101             }
102             if(r & 1) {
103                 all_apply(--r, f);
104             }
105             l >>= 1;
106             r >>= 1;
107         }
108         l = l2;
109         r = r2;
110     }
111     for(int i = 1; i <= log; i++) {
112         if(((l >> i) << i) != 1) {
113             update(l >> i);
114         }
115         if(((r >> i) << i) != r) {
116             update((r - 1) >> i);
117         }
118     }
119 }
120 private:
121 int n, size, log;
122 vector<S> d;
123 vector<F> lz;
124 inline void update(int k) { d[k] = node_pull(d[k << 1], d[k
    << 1 | 1]); }
125 void all_apply(int k, F f) {
126     d[k] = mapping(d[k], f);
127     if(k < size) {
128         lz[k] = tag_pull(lz[k], f);
129     }
130 }
131 void push(int k) {
132     all_apply(k << 1, lz[k]);
133     all_apply(k << 1 | 1, lz[k]);
134     lz[k] = tag_init();
135 }
136 };

```

1.13 MoAlgo

```

1 struct qry{
2     int ql,qr,id;
3 };
4 template<class T>struct Mo{
5     int n,m;
6     vector<pii>ans;
7     Mo(int _n,int _m): n(_n),m(_m){
8         ans.resize(m);
9     }
10    void solve(vector<T>&v,vector<qry>&q){
11        int l = 0,r = -1;
12        vector<int>cnt,cntcnt;
13        cnt.resize(n+5);
14        cntcnt.resize(n+5);
15        int mx = 0;
16        function<void(int)>add = [&](int pos){
17            cntcnt[cnt[v[pos]]]--;
18            cnt[v[pos]]++;
19            cntcnt[cnt[v[pos]]]++;
20            mx = max(mx,cnt[v[pos]]);
21        };
22        function<void(int)>sub = [&](int pos){
23            if(--cntcnt[cnt[v[pos]]] and cnt[v[pos]]==mx)mx--;
24            cnt[v[pos]]--;
25            cntcnt[cnt[v[pos]]]++;
26            mx = max(mx,cnt[v[pos]]);
27        };
28        sort(all(q),[&](qry a,qry b){
29            static int B = max((int)1,n/max((int)sqrt(m),(int)1));
30            if(a.ql/B!=b.ql/B)return a.ql<b.ql;
31            if((a.ql/B)&1)return a.qr>b.qr;
32            return a.qr<b.qr;
33        });

```

```

34    for(auto [ql,qr,id]:q){
35        while(l>ql)add(--l);
36        while(r<qr)add(++r);
37        while(l<ql)sub(l++);
38        while(r>qr)sub(r--);
39        ans[id] = {mx,cntcnt[mx]};
40    }
41 }
42 };

```

1.14 Hash

```

1 struct custom_hash {
2     static uint64_t splitmix64(uint64_t x) {
3         x += 0x9e3779b97f4a7c15;
4         x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
5         x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
6         return x ^ (x >> 31);
7     }
8     size_t operator()(uint64_t x) const {
9         static const uint64_t FIXED_RANDOM = chrono::steady_clock::
            now().time_since_epoch().count();
10        return splitmix64(x + FIXED_RANDOM);
11    }
12    size_t operator()(pair<uint64_t,uint64_t> x) const {
13        static const uint64_t FIXED_RANDOM = chrono::steady_clock::
            now().time_since_epoch().count();
14        return splitmix64(3*x.first + x.second + FIXED_RANDOM);
15    }
16 };
17 template<class T,class U>using hash_map = gp_hash_table<T,U,
    custom_hash>;

```

1.15 RedBlackTree

```

1 template<class T, typename cmp=less<>>struct _tree{//#include<
    bits/extc++.h>
2     tree<pair<T,int>,null_type,cmp,rb_tree_tag,
        tree_order_statistics_node_update>st;
3     int id = 0;
4     void insert(T x){st.insert({x,id++});}
5     void erase(T x){st.erase(st.lower_bound({x,0}));}
6     int order_of_key(T x){return st.order_of_key(*st.lower_bound
        ({x,0}));}
7     T find_by_order(int x){return st.find_by_order(x)->first;}
8     T lower_bound(T x){return st.lower_bound({x,0})->first;}
9     T upper_bound(T x){return st.upper_bound({x,(int)1e9+7})->
        first;}
10    T smaller_bound(T x){return (--st.lower_bound({x,0}))->first
        ;}
11 };

```

2 Geometry

2.1 Theorem

- Pick' s Theorem

$$A = I + \frac{B}{2} - 1$$

$$A := Area$$

$$i := PointsInside$$

$$B := PointsBoundary$$

2.2 PointInPolygon

```

1 template<class T>
2 int PointInPolygon(const vector<Point<T>> &Poly, const Point<T>
    p){
3     int ans = 0;
4     for(auto a = --Poly.end(),b = Poly.begin();b!=Poly.end();a =
        b++){
5         if(PointOnSegment(*a,*b,p)){
6             return -1;
7         }
8         if(seg_intersect(p,p+Point<T>(2e9+7,1),*a,*b)){
9             ans = !ans;
10        }
11    }
12    return ans;
13 }

```

2.3 PointInConvex

```

1 template<class T>
2 int PointInConvex(const vector<Point<T>>&C,const Point<T>&p){
3     if(btw(C[0],C[1],p) || btw(C[0],C.back(),p))return -1;
4     int l = 0,r = (int)C.size()-1;
5     while(l<=r){
6         int m = (l+r)>>1;
7         auto a1 = (C[m]-C[0])^(p-C[0]);
8         auto a2 = (C[(m+1)%C.size()-1]-C[0])^(p-C[0]);
9         if(a1>=0 and a2<=0){
10             auto res = (C[(m+1)%C.size()-1]-C[m])^(p-C[m]);
11             return res > 0 ? 1 : (res >= 0 ? -1 : 0);
12         }
13         if(a1 < 0) r = m-1;
14         else l = m+1;
15     }
16     return 0;
17 }

```

2.4 MaximumDistance

```

1 template<class T>
2 T MaximumDistance(vector<Point<T>>&p){
3     vector<Point<T>>C = ConvexHull(p,0);
4     int n = C.size(),t = 2;
5     T ans = 0;
6     for(int i = 0;i<n;i++){
7         while(((C[i] - C[t]) ^ (C[(i+1)%n] - C[t])) < ((C[i] - C[(t+1)%n]) ^ (C[(i+1)%n] - C[(t+1)%n]))) t = (t + 1)%n;
8         ans = max({ans, abs2(C[i] - C[t]), abs2(C[(i+1)%n] - C[t])});
9     }
10     return ans;
11 }

```

2.5 PolarAngleSort

```

1 template<class T>
2 bool cmp(const Point<T> &a,const Point<T> &b){
3     int lhs = (a.y < 0 || a.y==0 && a.x > 0) ? 0 : (1 + (a.x != 0 || a.y != 0));
4     int rhs = (b.y < 0 || b.y==0 && b.x > 0) ? 0 : (1 + (b.x != 0 || b.y != 0));
5     if(lhs != rhs) {
6         return lhs < rhs;
7     }
8     long long area = (a^b);
9     return area ? area > 0 : abs(a.x) + abs(a.y) < abs(b.x) + abs(b.y);
10 }

```

2.6 MinimumDistance

```

1 template<class T>
2 T MinimumDistance(vector<Point<T>>&p,int l = -1,int r = -1){
3     if(l==r and r==1){
4         sort(p.begin(),p.end(),[](Point<T> a,Point<T> b){
5             if(a.x!=b.x)return a.x<b.x;
6             return a.y<b.y;
7         });
8         p.erase(unique(p.begin(),p.end()),p.end());
9         return MinimumDistance(p,0,p.size()-1);
10    }
11    if(l==r)return numeric_limits<T>::max();
12    int m = (l+r)>>1,mid_pos = p[m].x;
13    T ans = min(MinimumDistance(p,l,m),MinimumDistance(p,m+1,r));
14    vector<Point<T>>tmp((r-l+1),Point<T>(0,0));
15    merge(p.begin()+l,p.begin()+m+1, p.begin()+m+1,p.begin()+r+1,
16          tmp.begin(), [](Point<T> a,Point<T> b){return a.y<b.y;});
17    for(int i = l;i<=r;i++)p[i] = tmp[i-l];
18    tmp.clear();
19    for(int i = l;i<=r;i++){
20        if((p[i].x-mid_pos)*(p[i].x-mid_pos)<ans){
21            tmp.push_back(p[i]);
22        }
23    }
24    int n = tmp.size();
25    for(int i = 0;i<n;i++){
26        for(int j = i+1;j<n;j++){
27            ans = min(ans,abs2(tmp[i]-tmp[j]));
28            if(((tmp[i].y-tmp[j].y)*(tmp[i].y-tmp[j].y))>ans){
29                break;
30            }
31        }
32    }
33 }

```

```

31 }
32 return ans;
33 }

```

2.7 ConvexHull

```

1 template<class T>
2 vector<Point<T>> ConvexHull(vector<Point<T>> v,bool Boundary = 1){
3     sort(begin(v),end(v),[](Point<T> &a,Point<T> &b){
4         if(a.x!=b.x)return a.x<b.x;
5         return a.y<b.y;
6     });
7     vector<Point<T>>ans;
8     int t = 1;
9     auto add = [](Point<T> &p){
10         while(ans.size() > t and ((p - ans[ans.size() - 2])^(ans.back() - ans[ans.size() - 2])) > (Boundary ? 0 : 0-eps))
11             ans.pop_back();
12         ans.push_back(p);
13     };
14     for(int i = 0; i < v.size(); ++i) add(v[i]);
15     t = ans.size();
16     for(int i = (int)(v.size()-2); i >= 0; --i) add(v[i]);
17     if(v.size() > 1) ans.pop_back();
18     return ans;
19 }

```

2.8 Template

```

1 template<class T>
2 struct Point{
3     T x,y;
4     Point(T x = 0,T y = 0) : x(x), y(y) {}
5     Point operator + (const Point &b) const {
6         return Point(x + b.x,y + b.y);
7     }
8     Point operator - (const Point &b) const {
9         return Point(x - b.x,y - b.y);
10    }
11    Point operator * (T b) const {
12        return Point(x*b,y*b);
13    }
14    Point operator / (T b) const {
15        return Point(x/b,y/b);
16    }
17    T operator * (const Point &b) const {
18        return x * b.x + y * b.y;
19    }
20    T operator ^ (const Point &b) const {
21        return x * b.y - y * b.x;
22    }
23 };
24 int sign(double a){
25     return fabs(a) < eps ? 0 : a > 0 ? 1 : -1;
26 }
27 template<class T>
28 double abs(const Point<T>&p){
29     return sqrtl(p*p);
30 }
31 template<class T>
32 T abs2(const Point<T>&p){
33     return p*p;
34 }
35 template<class T>
36 int ori(Point<T> a,Point<T> b,Point<T> c){
37     return sign((b-a)^(c-a));
38 }
39 template<class T>
40 bool collinearity(Point<T> p1,Point<T> p2,Point<T> p3){
41     return sign((p1-p3)^(p2-p3)) == 0;
42 }
43 template<class T>
44 bool btw(Point<T> p1,Point<T> p2,Point<T> p3) {
45     if(!collinearity(p1, p2, p3)) return 0;
46     return sign((p1-p3)*(p2-p3)) <= 0;
47 }
48 template<class T>
49 bool PointOnSegment(const Point<T> &p1,const Point<T> &p2,
50                    const Point<T> &p3){
51     return collinearity(p1,p2,p3) && btw(p1,p2,p3);
52 }
53 template<class T>
54 bool seg_intersect(Point<T> p1, Point<T> p2, Point<T> p3, Point<T> p4) {
55     int a123 = ori(p1, p2, p3);
56     int a124 = ori(p1, p2, p4);
57     int a341 = ori(p3, p4, p1);
58     int a342 = ori(p3, p4, p2);
59     if(a123 == 0 && a124 == 0)

```



```

59     return btw(p1, p2, p3) || btw(p1, p2, p4) || btw(p3, p4, p1
60         ) || btw(p3, p4, p2);
61     return a123 * a124 <= 0 && a341 * a342 <= 0;
62 }
63 template<class T>
64 double area(vector<Point<T>> v){
65     if(v.size()<=2)return 0;
66     double ans = 0;
67     for(int i = 1;i<v.size()-1;++i){
68         ans+=(v[i]-v[0])^(v[i+1]-v[0]));
69     }
70     return abs(ans)/2.;
71 }

```

3 Graph

3.1 HLD

```

1 struct HLD{
2     int n,root;
3     vector<int>dep,father,sz,mxson,topf,id;
4     HLD(int _n,int _root,vector<vector<int>>&g): n(_n),root(_root
5         ){
6         dep.resize(n+5);
7         father.resize(n+5);
8         sz.resize(n+5);
9         mxson.resize(n+5);
10        topf.resize(n+5);
11        id.resize(n+5);
12        function<void(int,int)>dfs = [&](int u,int p){
13            dep[u] = dep[p]+1;
14            father[u] = p;
15            sz[u] = 1;
16            mxson[u] = 0;
17            for(auto v:g[u]){
18                if(v!=p){
19                    dfs(v,u);
20                    sz[u]+=sz[v];
21                    if(sz[v]>sz[mxson[u]])mxson[u] = v;
22                }
23            };
24            function<void(int,int)>dfs2 = [&](int u,int top){
25                static int idn = 0;
26                topf[u] = top;
27                id[u] = ++idn;
28                if(mxson[u])dfs2(mxson[u],top);
29                for(auto v:g[u]){
30                    if(v!=father[u] and v!=mxson[u]){
31                        dfs2(v,v);
32                    }
33                };
34            };
35            dfs(root,0);
36            dfs2(root,root);
37        }
38        int query(int u,int v,const auto &qry,const auto &op){
39            int ans = 0;
40            while(topf[u]!=topf[v]){
41                if(dep[topf[u]]<dep[topf[v]])swap(u,v);
42                ans = op(ans,qry(id[topf[u]],id[v]));
43                u = father[topf[u]];
44            }
45            if(id[u]>id[v])swap(u,v);
46            ans = op(ans,qry(id[u],id[v]));
47            return ans;
48        }
49        void update(int u,int v,int val,const auto &upd){
50            while(topf[u]!=topf[v]){
51                if(dep[topf[u]]<dep[topf[v]])swap(u,v);
52                upd(id[topf[u]],id[u],val);
53                u = father[topf[u]];
54            }
55            if(id[u]>id[v])swap(u,v);
56            upd(id[u],id[v],val);
57        }
58    };

```

3.2 Bridges

```

1 vector<pii> findBridges(const vector<vector<int>>& g) {
2     int n = (int) g.size();
3     vector<int> id(n, -1), low(n);
4     vector<pii> bridges;
5     function<void(int, int)> dfs = [&](int u, int p) {
6         static int cnt = 0;
7         id[u] = low[u] = cnt++;
8         for(auto v : g[u]) {
9             if(v == p) continue;

```

```

10         if(id[v] != -1) low[u] = min(low[u], id[v]);
11         else {
12             dfs(v, u);
13             low[u] = min(low[u], low[v]);
14             if(low[v] > id[u]) bridges.EB(u, v);
15         }
16     };
17     for(int i = 0; i < n; ++i) {
18         if(id[i] == -1) dfs(i, -1);
19     }
20     return bridges;
21 }
22 }

```

3.3 TwoSat

```

1 struct two_sat{
2     SCC s;
3     vector<bool>ans;
4     int have_ans = 0;
5     int n;
6     two_sat(int _n) : n(_n) {
7         ans.resize(n+1);
8         s = SCC(2*n);
9     }
10    int inv(int x){
11        if(x>n)return x-n;
12        return x+n;
13    }
14    void add_or_clause(int u, bool x, int v, bool y){
15        if(!x)u = inv(u);
16        if(!y)v = inv(v);
17        s.add_edge(inv(u), v);
18        s.add_edge(inv(v), u);
19    }
20    void check(){
21        if(have_ans!=0)return;
22        s.build();
23        for(int i = 0;i<n;++i){
24            if(s.scc[i]==s.scc[inv(i)]){
25                have_ans = -1;
26                return;
27            }
28            ans[i] = (s.scc[i]<s.scc[inv(i)]);
29        }
30        have_ans = 1;
31    }
32 };

```

3.4 MCMF

```

1 template<class Cap_t, class Cost_t>
2 class MCMF {
3 public:
4     struct Edge {
5         int from;
6         int to;
7         Cap_t cap;
8         Cost_t cost;
9         Edge(int u, int v, Cap_t _cap, Cost_t _cost) : from(u), to(
10             v), cap(_cap), cost(_cost) {}
11     };
12     static constexpr Cap_t EPS = static_cast<Cap_t>(1e-9);
13     int n;
14     vector<Edge> edges;
15     vector<vector<int>> g;
16     vector<Cost_t> d;
17     vector<bool> in_queue;
18     vector<int> previous_edge;
19     MCMF() {}
20     MCMF(int _n) : n(_n+1), g(_n+1), d(_n+1), in_queue(_n+1),
21         previous_edge(_n+1) {}
22     void add_edge(int u, int v, Cap_t cap, Cost_t cost) {
23         assert(0 <= u && u < n);
24         assert(0 <= v && v < n);
25         g[u].push_back(edges.size());
26         edges.emplace_back(u, v, cap, cost);
27         g[v].push_back(edges.size());
28         edges.emplace_back(v, u, 0, -cost);
29     }
30     bool spfa(int s, int t) {
31         bool found = false;
32         fill(d.begin(), d.end(), numeric_limits<Cost_t>::max());
33         d[s] = 0;
34         in_queue[s] = true;
35         queue<int> que;

```

```

39 que.push(s);
40 while(!que.empty()) {
41     int u = que.front();
42     que.pop();
43     if(u == t) {
44         found = true;
45     }
46     in_queue[u] = false;
47     for(auto& id : g[u]) {
48         const Edge& e = edges[id];
49         if(e.cap > EPS && d[u] + e.cost < d[e.to]) {
50             d[e.to] = d[u] + e.cost;
51             previous_edge[e.to] = id;
52             if(!in_queue[e.to]) {
53                 que.push(e.to);
54                 in_queue[e.to] = true;
55             }
56         }
57     }
58 }
59 return found;
60 }
61
62 pair<Cap_t, Cost_t> flow(int s, int t, Cap_t f =
    numeric_limits<Cap_t>::max()) {
63     assert(0 <= s && s < n);
64     assert(0 <= t && t < n);
65     Cap_t cap = 0;
66     Cost_t cost = 0;
67     while(f > 0 && spfa(s, t)) {
68         Cap_t send = f;
69         int u = t;
70         while(u != s) {
71             const Edge& e = edges[previous_edge[u]];
72             send = min(send, e.cap);
73             u = e.from;
74         }
75         u = t;
76         while(u != s) {
77             Edge& e = edges[previous_edge[u]];
78             e.cap -= send;
79             Edge& b = edges[previous_edge[u] ^ 1];
80             b.cap += send;
81             u = e.from;
82         }
83         cap += send;
84         f -= send;
85         cost += send * d[t];
86     }
87     return make_pair(cap, cost);
88 }
89 };

```

3.5 LCA

```

1 vector<vector<int>>>g,dp;
2 vector<int>deep;
3 void build(int root,int n){
4     dp.assign(25,vector<int>(n+5));
5     deep.assign(n+5,0);
6     function<void(int,int,int)>dfs = [&](int u,int p,int dis){
7         dp[0][u] = p;
8         deep[u] = dis;
9         for(auto v:g[u]){
10             if(v==p)continue;
11             dfs(v,u,dis+1);
12         }
13     };
14     dfs(root,0,1);
15     for(int i = 1;i<=20;++i){
16         for(int j = 1;j<=n;++j){
17             dp[i][j] = dp[i-1][dp[i-1][j]];
18         }
19     }
20 }
21 int LCA(int u,int v){
22     if(deep[u]<deep[v])swap(u,v);
23     for(int i = 20;i>=0;--i){
24         if(deep[dp[i][u]]>=deep[v])
25             u = dp[i][u];
26     }
27     if(u==v)return u;
28     for(int i = 20;i>=0;--i){
29         if(dp[i][u]!=dp[i][v])u = dp[i][u],v = dp[i][v];
30     }
31     return dp[0][u];
32 }

```

3.6 CentroidDecomposition

```

1 vector<vector<int>>>g;
2 vector<int>sz,tmp;
3 vector<bool>vis; //visit_centroid
4 int tree_centroid(int u,int n){
5     function<void(int,int)>dfs1 = [&](int u,int p){
6         sz[u] = 1;
7         for(auto v:g[u]){
8             if(v==p)continue;
9             if(vis[v])continue;
10            dfs1(v,u);
11            sz[u]+=sz[v];
12        }
13    };
14    function<int(int,int)>dfs2 = [&](int u,int p){
15        for(auto v:g[u]){
16            if(v==p)continue;
17            if(vis[v])continue;
18            if(sz[v]*2<n)continue;
19            return dfs2(v,u);
20        }
21        return u;
22    };
23    dfs1(u,-1);
24    return dfs2(u,-1);
25 }
26 int cal(int u,int p = -1,int deep = 1){
27     int ans = 0;
28     tmp.pb(deep);
29     sz[u] = 1;
30     for(auto v:g[u]){
31         if(v==p)continue;
32         if(vis[v])continue;
33         ans+=cal(v,u,deep+1);
34         sz[u]+=sz[v];
35     }
36     //calcuat the answer
37     return ans;
38 }
39 int centroid_decomposition(int u,int tree_size){
40     int center = tree_centroid(u,tree_size);
41     vis[center] = 1;
42     int ans = 0;
43     for(auto v:g[center]){
44         if(vis[v])continue;
45         ans+=cal(v);
46         for(int i = sz(tmp)-sz[v];i<sz(tmp);++i){
47             //update
48         }
49     }
50     while(!tmp.empty()){
51         //roll_back(tmp.back())
52         tmp.pop_back();
53     }
54     for(auto v:g[center]){
55         if(vis[v])continue;
56         ans+=centroid_decomposition(v,sz[v]);
57     }
58     return ans;
59 }

```

3.7 BCC AP

```

1 struct BCC_AP{
2     int dfn_cnt = 0,bcc_cnt = 0,n;
3     vector<int>dfn,low,ap,bcc_id;
4     stack<int>st;
5     vector<bool>vis,is_ap;
6     vector<vector<int>>>bcc;
7     BCC_AP(int _n):n(_n){
8         dfn.resize(n+5),low.resize(n+5),bcc.resize(n+5),vis.resize(
9             n+5),is_ap.resize(n+5),bcc_id.resize(n+5);
10    }
11    inline void build(const vector<vector<int>>>&g,int u,int p =
12        -1){
13        int child = 0;
14        dfn[u] = low[u] = ++dfn_cnt;
15        st.push(u);
16        vis[u] = 1;
17        if(g[u].empty() and p==-1){
18            bcc_id[u] = ++bcc_cnt;
19            bcc[bcc_cnt].push_back(u);
20            return;
21        }
22        for(auto v:g[u]){
23            if(v==p)continue;
24            if(!dfn[v]){
25                build(g,v,u);
26                child++;
27                if(dfn[u]<=low[v]){
28                    is_ap[u] = 1;
29                    bcc_id[u] = ++bcc_cnt;
30                    bcc[bcc_cnt].push_back(u);
31                    while(vis[v]){
32                        bcc_id[st.top()] = bcc_cnt;

```



```

31         bcc[bcc_cnt].push_back(st.top());
32         vis[st.top()] = 0;
33         st.pop();
34     }
35 }
36 low[u] = min(low[u], low[v]);
37 }
38 low[u] = min(low[u], dfn[v]);
39 }
40 if(p == -1 and child < 2) is_ap[u] = 0;
41 if(is_ap[u]) ap.push_back(u);
42 }
43 };

```

3.8 SCC

```

1 struct SCC{
2     int n, cnt = 0, dfn_cnt = 0;
3     vector<vector<int>>> g;
4     vector<int> sz, scc, low, dfn;
5     stack<int> st;
6     vector<bool> vis;
7     SCC(int _n = 0) : n(_n){
8         sz.resize(n+5), scc.resize(n+5), low.resize(n+5), dfn.resize(n
9         +5), vis.resize(n+5);
10        g.resize(n+5);
11    }
12    inline void add_edge(int u, int v){
13        g[u].push_back(v);
14    }
15    inline void build(){
16        function<void(int, int)> dfs = [&](int u, int dis){
17            low[u] = dfn[u] = ++dfn_cnt, vis[u] = 1;
18            st.push(u);
19            for(auto v : g[u]){
20                if(!dfn[v]){
21                    dfs(v, dis+1);
22                    low[u] = min(low[u], low[v]);
23                }
24                else if(vis[v]){
25                    low[u] = min(low[u], dfn[v]);
26                }
27            }
28            if(low[u] == dfn[u]){
29                ++cnt;
30                while(vis[u]){
31                    auto v = st.top();
32                    st.pop();
33                    vis[v] = 0;
34                    scc[v] = cnt;
35                    sz[cnt]++;
36                }
37            }
38            for(int i = 0; i <= n; ++i){
39                if(!scc[i]){
40                    dfs(i, 1);
41                }
42            }
43        }
44        vector<vector<int>>> compress(){
45            vector<vector<int>>> ans(cnt+1);
46            for(int u = 0; u <= n; ++u){
47                for(auto v : g[u]){
48                    if(scc[u] == scc[v]){
49                        continue;
50                    }
51                    ans[scc[u]].push_back(scc[v]);
52                }
53            }
54            for(int i = 0; i <= cnt; ++i){
55                sort(ans[i].begin(), ans[i].end());
56                ans[i].erase(unique(ans[i].begin(), ans[i].end()), ans[i]
57                .end());
58            }
59            return ans;
60        };

```

3.9 LineContainer

```

1 template<class T>
2 T floor_div(T a, T b) {
3     return a / b - ((a ^ b) < 0 && a % b != 0);
4 }
5
6 template<class T>
7 T ceil_div(T a, T b) {
8     return a / b + ((a ^ b) > 0 && a % b != 0);
9 }
10

```

```

11 namespace line_container_internal {
12
13 struct line_t {
14     mutable long long k, m, p;
15
16     inline bool operator<(const line_t& o) const { return k < o.k
17     ; }
18     inline bool operator<(long long x) const { return p < x; }
19 };
20 } // LineContainerInternal
21
22 template<bool MAX>
23 struct line_container : std::multiset<line_container_internal::
24     line_t, std::less<>> {
25     static const long long INF = std::numeric_limits<long long>::
26     max();
27
28     bool isect(iterator x, iterator y) {
29         if(y == end()) {
30             x->p = INF;
31             return 0;
32         }
33         if(x->k == y->k) {
34             x->p = (x->m > y->m ? INF : -INF);
35         } else {
36             x->p = floor_div(y->m - x->m, x->k - y->k);
37         }
38         return x->p >= y->p;
39     }
40
41     void add_line(long long k, long long m) {
42         if(!MAX) {
43             k = -k;
44             m = -m;
45         }
46         auto z = insert({k, m, 0}), y = z++, x = y;
47         while(isect(y, z)) {
48             z = erase(z);
49         }
50         if(x != begin() && isect(--x, y)) {
51             isect(x, y = erase(y));
52         }
53         while((y = x) != begin() && (--x)->p >= y->p) {
54             isect(x, erase(y));
55         }
56     }
57
58     long long get(long long x) {
59         assert(!empty());
60         auto l = *lower_bound(x);
61         return (1.k * x + 1.m) * (MAX ? +1 : -1);
62     }
63 };

```

3.10 Dinic

```

1 template<class T>
2 struct Dinic{
3     struct edge{
4         int from, to;
5         T cap;
6         edge(int _from, int _to, T _cap) : from(_from), to(_to),
7         cap(_cap) {}
8     };
9     int n;
10    vector<edge> edges;
11    vector<vector<int>>> g;
12    vector<int> cur, h;
13    Dinic(int _n) : n(_n+1), g(_n+1) {}
14    void add_edge(int u, int v, T cap){
15        g[u].push_back(edges.size());
16        edges.push_back(edge(u, v, cap));
17        g[v].push_back(edges.size());
18        edges.push_back(edge(v, u, 0));
19    }
20    bool bfs(int s, int t){
21        h.assign(n, -1);
22        h[s] = 0;
23        queue<int> que;
24        que.push(s);
25        while(!que.empty()) {
26            int u = que.front();
27            que.pop();
28            for(auto id : g[u]) {
29                const edge& e = edges[id];
30                int v = e.to;
31                if(e.cap > 0 && h[v] == -1) {
32                    h[v] = h[u] + 1;
33                    if(v == t) {
34                        return 1;
35                    }
36                    que.push(v);
37                }
38            }
39        }
40    }

```

```

37     }
38 }
39 return 0;
40 }
41 T dfs(int u, int t, T f) {
42     if(u == t) {
43         return f;
44     }
45     T r = f;
46     for(int& i = cur[u]; i < (int) g[u].size(); ++i) {
47         int id = g[u][i];
48         const edge& e = edges[id];
49         int v = e.to;
50         if(e.cap > 0 && h[v] == h[u] + 1) {
51             T send = dfs(v, t, min(r, e.cap));
52             edges[id].cap -= send;
53             edges[id ^ 1].cap += send;
54             r -= send;
55             if(r == 0) {
56                 return f;
57             }
58         }
59     }
60     return f - r;
61 }
62 T flow(int s, int t, T f = numeric_limits<T>::max()) {
63     T ans = 0;
64     while(f > 0 && bfs(s, t)) {
65         cur.assign(n, 0);
66         T send = dfs(s, t, f);
67         ans += send;
68         f -= send;
69     }
70     return ans;
71 }
72 vector<pair<int,int>> min_cut(int s) {
73     vector<bool> vis(n);
74     vis[s] = true;
75     queue<int> que;
76     que.push(s);
77     while(!que.empty()) {
78         int u = que.front();
79         que.pop();
80         for(auto id : g[u]) {
81             const auto& e = edges[id];
82             int v = e.to;
83             if(e.cap > 0 && !vis[v]) {
84                 vis[v] = true;
85                 que.push(v);
86             }
87         }
88     }
89     vector<pair<int,int>> cut;
90     for(int i = 0; i < (int) edges.size(); i += 2) {
91         const auto& e = edges[i];
92         if(vis[e.from] && !vis[e.to]) {
93             cut.push_back(make_pair(e.from, e.to));
94         }
95     }
96     return cut;
97 }
98 };

```

4 Math

4.1 Numbers

- Bernoulli numbers

$$B_0 = 1, B_1^{\pm} = \pm \frac{1}{2}, B_2 = \frac{1}{6}, B_3 = 0$$

$$\sum_{j=0}^m \binom{m+1}{j} B_j = 0, \text{EGF is } B(x) = \frac{x}{e^x - 1} = \sum_{n=0}^{\infty} B_n \frac{x^n}{n!}.$$

$$S_m(n) = \sum_{k=1}^n k^m = \frac{1}{m+1} \sum_{k=0}^m \binom{m+1}{k} B_k^+ n^{m+1-k}$$

- Stirling numbers of the second kind Partitions of n distinct elements into exactly k groups.

$$S(n, k) = S(n-1, k-1) + kS(n-1, k), S(n, 1) = S(n, n) = 1$$

$$S(n, k) = \frac{1}{k!} \sum_{i=0}^k (-1)^{k-i} \binom{k}{i} i^n$$

$$x^n = \sum_{i=0}^n S(n, i) (x)_i$$

- Pentagonal number theorem

$$\prod_{n=1}^{\infty} (1 - x^n) = 1 + \sum_{k=1}^{\infty} (-1)^k \left(x^{k(3k+1)/2} + x^{k(3k-1)/2} \right)$$

- Catalan numbers

$$C_n^{(k)} = \frac{1}{(k-1)n+1} \binom{kn}{n}$$

$$C^{(k)}(x) = 1 + x[C^{(k)}(x)]^k$$

- Eulerian numbers

Number of permutations $\pi \in S_n$ in which exactly k elements are greater than the previous element. k j :s s.t. $\pi(j) > \pi(j+1)$, $k+1$ j :s s.t. $\pi(j) \geq j$, k j :s s.t. $\pi(j) > j$.

$$E(n, k) = (n-k)E(n-1, k-1) + (k+1)E(n-1, k)$$

$$E(n, 0) = E(n, n-1) = 1$$

$$E(n, k) = \sum_{j=0}^k (-1)^j \binom{n+1}{j} (k+1-j)^n$$

4.2 ExtendGCD

```

1 // @return $x, $y s.t. $ax + by = \gcd(a, b)$
2 ll ext_gcd(ll a, ll b, ll& x, ll& y) {
3     if(b == 0) {
4         x = 1; y = 0;
5         return a;
6     }
7     ll x2, y2;
8     ll c = a % b;
9     if(c < 0) c += b;
10    ll g = ext_gcd(b, c, x2, y2);
11    x = y2;
12    y = x2 - (a / b) * y2;
13    return g;
14 }

```

4.3 BerlekampMassey

```

1 template <typename Tfield>
2 std::pair<int, std::vector<Tfield>> find_linear_recurrence(
3     const std::vector<Tfield> &S) {
4     int N = S.size();
5     using poly = std::vector<Tfield>;
6     poly C_reversed{1}, B{1};
7     int L = 0, m = 1;
8     Tfield b = 1;
9
10    // adjust: C(x) <- C(x) - (d / b) x^m B(x)
11    auto adjust = [](poly C, const poly &B, Tfield d, Tfield b,
12        int m) -> poly {
13        C.resize(std::max(C.size(), B.size() + m));
14        Tfield a = d / b;
15        for (unsigned i = 0; i < B.size(); i++) C[i + m] -= a * B[i];
16        return C;
17    };
18
19    for (int n = 0; n < N; n++) {
20        Tfield d = S[n];
21        for (int i = 1; i <= L; i++) d += C_reversed[i] * S[n - i];
22
23        if (d == 0) m++;
24        else if (2 * L <= n) {
25            poly T = C_reversed;
26            C_reversed = adjust(C_reversed, B, d, b, m);
27            L = n + 1 - L;
28            B = T;
29            b = d;
30            m = 1;
31        } else {
32            C_reversed = adjust(C_reversed, B, d, b, m++);
33        }
34    }
35    return std::make_pair(L, C_reversed);
36 }
37
38 // Calculate $x^N \bmod f(x)$
39 // Known as `Kitamasa method`
40 // Input: f_reversed: monic, reversed (f_reversed[0] = 1)
41 // Complexity: $O(K^2 \log N)$ ($K$: deg. of $f$)
42 // Example: (4, [1, -1, -1]) -> [2, 3]
43 // (x^4 = (x^2 + x + 2)(x^2 - x - 1) + 3x + 2)
44 // Reference: http://misawa.github.io/others/fast_kitamasa_method.html
45 // http://sugarknri.hatenablog.com/entry/2017/11/18/233936
46 template <typename Tfield>
47 std::vector<Tfield> monomial_mod_polynomial(long long N, const
48     std::vector<Tfield> &f_reversed) {
49     assert(!f_reversed.empty() and f_reversed[0] == 1);
50     int K = f_reversed.size() - 1;
51     if (!K) return {};
52     int D = 64 - __builtin_clzll(N);
53     std::vector<Tfield> ret(K, 0);
54     ret[0] = 1;
55     auto self_conv = [](std::vector<Tfield> x) -> std::vector<
56         Tfield> {
57         int d = x.size();

```

```

54     std::vector<Tfield> ret(d * 2 - 1);
55     for (int i = 0; i < d; i++) {
56         ret[i * 2] += x[i] * x[i];
57         for (int j = 0; j < i; j++) ret[i + j] += x[i] * x[
58             j] * 2;
59     }
60     return ret;
61 };
62 for (int d = D; d--;) {
63     ret = self_conv(ret);
64     for (int i = 2 * K - 2; i >= K; i--) {
65         for (int j = 1; j <= K; j++) ret[i - j] -= ret[i] *
66             f_reversed[j];
67     }
68     ret.resize(K);
69     if ((N >> d) & 1) {
70         std::vector<Tfield> c(K);
71         c[0] = -ret[K - 1] * f_reversed[K];
72         for (int i = 1; i < K; i++) { c[i] = ret[i - 1] -
73             ret[K - 1] * f_reversed[K - i]; }
74         ret = c;
75     }
76 }
77 // Guess k-th element of the sequence, assuming linear
78 // recurrence
79 // initial_elements: 0-ORIGIN
80 // Verify: abc198f https://atcoder.jp/contests/abc198/
81 // submissions/21837815
82 template <typename Tfield>
83 Tfield guess_kth_term(const std::vector<Tfield> &
84     initial_elements, long long k) {
85     assert(k >= 0);
86     if (k < static_cast<long long>(initial_elements.size()))
87         return initial_elements[k];
88     const auto f = find_linear_recurrence<Tfield>(
89         initial_elements).second;
90     const auto g = monomial_mod_polynomial<Tfield>(k, f);
91     Tfield ret = 0;
92     for (unsigned i = 0; i < g.size(); i++) ret += g[i] *
93         initial_elements[i];
94     return ret;
95 }

```

4.4 InvGCD

```

1 pair<long long, long long> inv_gcd(long long a, long long b) {
2     a %= b;
3     if(a < 0) a += b;
4     if(a == 0) return {b, 0};
5     long long s = b, t = a;
6     long long m0 = 0, m1 = 1;
7     while(t) {
8         long long u = s / t;
9         s -= t * u;
10        m0 -= m1 * u;
11        swap(s, t);
12        swap(m0, m1);
13    }
14    if(m0 < 0) m0 += b / s;
15    return {s, m0};
16 }

```

4.5 GeneratingFunctions

- Ordinary Generating Function $A(x) = \sum_{i \geq 0} a_i x^i$

$$\begin{aligned}
 & - A(rx) \Rightarrow r^n a_n \\
 & - A(x) + B(x) \Rightarrow a_n + b_n \\
 & - A(x)B(x) \Rightarrow \sum_{i=0}^n a_i b_{n-i} \\
 & - A(x)^k \Rightarrow \sum_{i_1+i_2+\dots+i_k=n} a_{i_1} a_{i_2} \dots a_{i_k} \\
 & - xA(x)' \Rightarrow na_n \\
 & - \frac{A(x)}{1-x} \Rightarrow \sum_{i=0}^n a_i
 \end{aligned}$$

- Exponential Generating Function $A(x) = \sum_{i \geq 0} \frac{a_i}{i!} x^i$

$$\begin{aligned}
 & - A(x) + B(x) \Rightarrow a_n + b_n \\
 & - A^{(k)}(x) \Rightarrow a_{n+k} \\
 & - A(x)B(x) \Rightarrow \sum_{i=0}^n \binom{n}{i} a_i b_{n-i} \\
 & - A(x)^k \Rightarrow \sum_{i_1+i_2+\dots+i_k=n} \binom{n}{i_1, i_2, \dots, i_k} a_{i_1} a_{i_2} \dots a_{i_k} \\
 & - xA(x) \Rightarrow na_n
 \end{aligned}$$

- Special Generating Function

$$\begin{aligned}
 & - (1+x)^n = \sum_{i \geq 0} \binom{n}{i} x^i \\
 & - \frac{1}{(1-x)^n} = \sum_{i \geq 0} \binom{n-1}{i} x^i
 \end{aligned}$$

4.6 Theorem

- Cramer's rule

$$\begin{aligned}
 ax + by = e & \Rightarrow x = \frac{ed - bf}{ad - bc} \\
 cx + dy = f & \Rightarrow y = \frac{af - ec}{ad - bc}
 \end{aligned}$$

- Kirchhoff's Theorem

Denote L be a $n \times n$ matrix as the Laplacian matrix of graph G , where $L_{ii} = d(i)$, $L_{ij} = -c$ where c is the number of edge (i, j) in G .

- The number of undirected spanning in G is $|\det(\tilde{L}_{11})|$.
- The number of directed spanning tree rooted at r in G is $|\det(\tilde{L}_{rr})|$.

- Tutte's Matrix

Let D be a $n \times n$ matrix, where $d_{ij} = x_{ij}$ (x_{ij} is chosen uniformly at random) if $i < j$ and $(i, j) \in E$, otherwise $d_{ij} = -d_{ji}$. $\frac{\text{rank}(D)}{2}$ is the maximum matching on G .

- Cayley's Formula

- Given a degree sequence d_1, d_2, \dots, d_n for each labeled vertices, there are $\frac{(n-2)!}{(d_1-1)!(d_2-1)!\dots(d_n-1)!}$ spanning trees.
- Let $T_{n,k}$ be the number of labeled forests on n vertices with k components, such that vertex $1, 2, \dots, k$ belong to different components. Then $T_{n,k} = kn^{n-k-1}$.

- Erdős–Gallai theorem

A sequence of nonnegative integers $d_1 \geq \dots \geq d_n$ can be represented as the degree sequence of a finite simple graph on n vertices if and only if $d_1 + \dots + d_n$

is even and $\sum_{i=1}^k d_i \leq k(k-1) + \sum_{i=k+1}^n \min(d_i, k)$ holds for every $1 \leq k \leq n$.

- Gale–Ryser theorem

A pair of sequences of nonnegative integers $a_1 \geq \dots \geq a_n$ and b_1, \dots, b_n is bigraphic if and only if $\sum_{i=1}^n a_i = \sum_{i=1}^n b_i$ and $\sum_{i=1}^k a_i \leq \sum_{i=1}^n \min(b_i, k)$ holds for every $1 \leq k \leq n$.

- Fulkerson–Chen–Anstee theorem

A sequence $(a_1, b_1), \dots, (a_n, b_n)$ of nonnegative integer pairs with $a_1 \geq \dots \geq a_n$ is digraphic if and only if $\sum_{i=1}^n a_i = \sum_{i=1}^n b_i$ and $\sum_{i=1}^k a_i \leq \sum_{i=1}^k \min(b_i, k-1) + \sum_{i=k+1}^n \min(b_i, k)$ holds for every $1 \leq k \leq n$.

- Möbius inversion formula

$$\begin{aligned}
 & - f(n) = \sum_{d|n} g(d) \Leftrightarrow g(n) = \sum_{d|n} \mu(d) f\left(\frac{n}{d}\right) \\
 & - f(n) = \sum_{n|d} g(d) \Leftrightarrow g(n) = \sum_{n|d} \mu\left(\frac{d}{n}\right) f(d)
 \end{aligned}$$

- Spherical cap

- A portion of a sphere cut off by a plane.
- r : sphere radius, a : radius of the base of the cap, h : height of the cap, θ : $\arcsin(a/r)$.
- Volume $= \pi h^2 (3r - h) / 3 = \pi h (3a^2 + h^2) / 6 = \pi r^3 (2 + \cos \theta) (1 - \cos \theta)^2 / 3$.
- Area $= 2\pi r h = \pi (a^2 + h^2) = 2\pi r^2 (1 - \cos \theta)$.

4.7 FloorSum

```

1 // @param $n < 2^{32}$
2 // @param $l \leq m < 2^{32}$
3 // @return $\sum_{i=0}^{n-1} \lfloor \frac{ai+b}{m} \rfloor \pmod{2^{64}}$
4 ull floor_sum_unsigned(ull n, ull m, ull a, ull b) {
5     ull ans = 0;
6     while(true) {
7         if(a >= m) {
8             ans += n * (n - 1) / 2 * (a / m);
9             a %= m;
10        }
11        if(b >= m) {
12            ans += n * (b / m);
13            b %= m;
14        }
15        ull y_max = a * n + b;
16        if(y_max < m) break;
17        n = (ull)(y_max / m);
18        b = (ull)(y_max % m);
19        swap(m, a);
20    }
21    return ans;
22 }
23
24 ll floor_sum(ll n, ll m, ll a, ll b) {
25     assert(0 <= n && n < (1LL << 32));

```

```

26 assert(1 <= m && m < (1LL << 32));
27 ull ans = 0;
28 if(a < 0) {
29     ull a2 = (a % m + m) % m;
30     ans -= 1ULL * n * (n - 1) / 2 * ((a2 - a) / m);
31     a = a2;
32 }
33 if(b < 0) {
34     ull b2 = (b % m + m) % m;
35     ans -= 1ULL * n * ((b2 - b) / m);
36     b = b2;
37 }
38 return ans + floor_sum_unsigned(n, m, a, b);
39 }

```

4.8 Factorizer

```

1 template<class T>
2 vector<pair<T, int>> MergeFactors(const vector<pair<T, int>>& a
3     , const vector<pair<T, int>>& b) {
4     vector<pair<T, int>> c;
5     int i = 0, j = 0;
6     while(i < SZ(a) || j < SZ(b)) {
7         if(i < SZ(a) && j < SZ(b) && a[i].F == b[j].F) {
8             c.EB(a[i].F, a[i].S + b[j].S);
9             ++i, ++j;
10            continue;
11        }
12        if(j == SZ(b) || (i < SZ(a) && a[i].F < b[j].F)) c.PB(a[i]
13            ++j);
14        else c.PB(b[j++]);
15    }
16    return c;
17 }
18 template<class T>
19 vector<pair<T, int>> RhoC(const T& n, const T& c) {
20     if(n <= 1) return {};
21     if(n % 2 == 0) return MergeFactors({{2, 1}}, RhoC(n / 2, c));
22     if(is_prime_constexpr(n)) return {{n, 1}};
23     T x = 2, saved = 2, p = 1, lam = 1;
24     while(true) {
25         x = (x * x % n + c) % n;
26         T g = __gcd((x - saved) % n, n);
27         if(g != 1) return MergeFactors(RhoC(g, c + 1), RhoC(n / g,
28             c + 1));
29         if(p == lam) {
30             saved = x;
31             p <<= 1;
32             lam = 0;
33         }
34         lam += 1;
35     }
36     return {};
37 }
38 template<class T>
39 vector<pair<T, int>> Factorize(T n) {
40     if(n <= 1) return {};
41     return RhoC(n, T(1));
42 }
43 template<class T>
44 vector<T> BuildDivisorsFromFactors(const vector<pair<T, int>>&
45     factors) {
46     int total = 1;
47     for(int i = 0; i < SZ(factors); ++i) total *= factors[i].
48         second + 1;
49     vector<T> divisors;
50     divisors.reserve(total);
51     divisors.PB(1);
52     for(auto [p, cnt] : factors) {
53         int sz = SZ(divisors);
54         for(int i = 0; i < sz; ++i) {
55             T cur = divisors[i];
56             for(int j = 0; j < cnt; ++j) {
57                 cur *= p;
58                 divisors.PB(cur);
59             }
60         }
61     }
62     // sort(ALL(divisors));
63     return divisors;
64 }

```

4.9 PowMod

```

1 constexpr long long Pow(long long x, long long n, int m) {
2     if(m == 1) return 0;
3     unsigned int _m = (unsigned int)(m);
4     unsigned long long r = 1;
5     x %= m;
6     if(x < 0) x += m;
7     unsigned long long y = x;

```

```

8     while(n) {
9         if(n & 1) r = (r * y) % _m;
10        y = (y * y) % _m;
11        n >>= 1;
12    }
13    return r;
14 }

```

4.10 CRT

```

1 // @return
2 // ${text}{remainder, modulo}$
3 // or
4 // $0, 0$ if do not exist
5 pair<long long, long long> crt(const vector<long long>& r,
6     const vector<long long>& m) {
7     assert(r.size()==m.size());
8     int n = r.size();
9     // Contracts: 0 <= r0 < m0
10    long long r0 = 0, m0 = 1;
11    for(int i = 0; i < n; i++) {
12        assert(1 <= m[i]);
13        long long r1 = r[i] % m[i];
14        if(r1 < 0) r1 += m[i];
15        long long m1 = m[i];
16        if(m0 < m1) {
17            swap(r0, r1);
18            swap(m0, m1);
19        }
20        if(m0 % m1 == 0) {
21            if(r0 % m1 != r1) return {0, 0};
22            continue;
23        }
24        long long g, im;
25        tie(g, im) = inv_gcd(m0, m1);
26        long long u1 = (m1 / g);
27        if((r1 - r0) % g) return {0, 0};
28        long long x = (r1 - r0) / g % u1 * im % u1;
29        r0 += x * m0;
30        m0 *= u1;
31        if(r0 < 0) r0 += m0;
32    }
33    return {r0, m0};

```

4.11 DiscreteLog

```

1 int DiscreteLog(int s, int x, int y, int m) {
2     constexpr int K = 0;
3     hash_map<int, int> p;
4     int b = 1;
5     for(int i = 0; i < K; ++i) {
6         p[y] = i;
7         y = 1LL * y * x % m;
8         b = 1LL * b * x % m;
9     }
10    for(int i = 0; i < m + 10; i += K) {
11        s = 1LL * s * b % m;
12        if(p.find(s) != p.end()) return i + K - p[s];
13    }
14    return -1;
15 }
16 int DiscreteLog(int x, int y, int m) {
17     if(m == 1) return 0;
18     int s = 1;
19     for(int i = 0; i < 100; ++i) {
20         if(s == y) return i;
21         s = 1LL * s * x % m;
22     }
23     if(s == y) return 100;
24     int p = 100 + DiscreteLog(s, x, y, m);
25     return (pow_mod(x, p, m) != y ? -1 : p);
26 }

```

4.12 LinearSieve

```

1 vector<bool> is_prime;
2 vector<int> primes, phi, mobius, least;
3 void linear_sieve(int n) {
4     n += 1;
5     is_prime.resize(n);
6     least.resize(n);
7     fill(2 + begin(is_prime), end(is_prime), true);
8     phi.resize(n); mobius.resize(n);
9     phi[1] = mobius[1] = 1;
10    least[0] = 0, least[1] = 1;
11    for(int i = 2; i < n; ++i) {
12        if(is_prime[i]) {
13            primes.push_back(i);

```

```

14     phi[i] = i - 1;
15     mobius[i] = -1;
16     least[i] = i;
17 }
18 for(auto j : primes) {
19     if(i * j >= n) break;
20     is_prime[i * j] = false;
21     least[i * j] = j;
22     if(i % j == 0) {
23         mobius[i * j] = 0;
24         phi[i * j] = phi[i] * j;
25         break;
26     } else {
27         mobius[i * j] = mobius[i] * mobius[j];
28         phi[i * j] = phi[i] * phi[j];
29     }
30 }
31 }
32 }

```

5 Misc

5.1 FastIO

```

1 inline char gc() {
2     static const int BUF_SIZE = 1 << 22;
3     static int Counts = 1 << 23;
4     static char Buffer[BUF_SIZE];
5     static char *Pointer = Buffer, *End = Buffer;
6     if(Pointer == End) {
7         if(Counts < BUF_SIZE) {
8             return EOF;
9         }
10        Counts = fread(Buffer, 1, BUF_SIZE, stdin);
11        Pointer = Buffer;
12        End = Buffer + Counts;
13    }
14    return *(Pointer++);
15 }
16
17 template<class T>
18 inline void read(T& x) {
19     static char c;
20     do {
21         c = gc();
22     } while(c < '0' && c != '-');
23     bool neg = (c == '-');
24     if(!neg) {
25         x = c - '0';
26     } else x = 0;
27     while((c = gc()) >= '0') {
28         x = (x << 3) + (x << 1) + (c & 15);
29     }
30     if(neg) {
31         x = -x;
32     }
33 }
34
35 template<class T, class... U>
36 inline void read(T& a, U&... b) {
37     read(a);
38     read(b...);
39 }
40
41 template<class T>
42 inline void write(T temp, char end = '\n') {
43     static short digits[20], P;
44     if(temp == 0) {
45         putchar_unlocked('0');
46         putchar_unlocked(end);
47         return;
48     }
49     if(temp < 0) {
50         putchar_unlocked('-');
51         write(-temp, end);
52         return;
53     }
54     P = -1;
55     while(temp) {
56         digits[++P] = temp % 10;
57         temp /= 10;
58     }
59     while(P >= 0) {
60         putchar_unlocked(digits[P--] + '0');
61     }
62     putchar_unlocked(end);
63     return;
64 }

```

5.2 Debug

```

1 #ifdef LOCAL
2     #define eprintf(...) { fprintf(stderr, __VA_ARGS__); fflush(
3         stderr); }
4 #else
5     #define eprintf(...) 42
6 #endif

```

5.3 Discrete

```

1 template<class T>
2 vector<int> Discrete(const vector<T>&v){
3     vector<int>ans;
4     vector<T>tmp(v);
5     sort(begin(tmp),end(tmp));
6     tmp.erase(unique(begin(tmp),end(tmp)),end(tmp));
7     for(auto i:v)ans.push_back(lower_bound(begin(tmp),end(tmp),i)
8         -tmp.begin()+1);
9     return ans;
10 }

```

5.4 DuiPai

```

1 #include<bits/stdc++.h>
2 using namespace std;
3 int main(){
4     string sol,bf,make;
5     cout<<"Your solution file name :";
6     cin>>sol;
7     cout<<"Brute force file name :";
8     cin>>bf;
9     cout<<"Make data file name :";
10    cin>>make;
11    system(("g++ "+sol+" -o sol").c_str());
12    system(("g++ "+bf+" -o bf").c_str());
13    system(("g++ "+make+" -o make").c_str());
14    for(int t = 0;t<10000;++t){
15        system("./make > ./1.in");
16        double st = clock();
17        system("./sol < ./1.in > ./1.ans");
18        double et = clock();
19        system("./bf < ./1.in > ./1.out");
20        if(system("diff ./1.out ./1.ans")) {
21            printf("\033[0;31mWrong Answer\033[0m on test #%d",t);
22            return 0;
23        }
24        else if(et-st>=2000){
25            printf("\033[0;32mTime Limit exceeded\033[0m on test #%d, Time %.0lfms\n",t,et-st);
26            return 0;
27        }
28        else {
29            printf("\033[0;32mAccepted\033[0m on test #%d, Time %.0lfms\n", t, et - st);
30        }
31    }
32 }

```

5.5 Timer

```

1 const clock_t startTime = clock();
2 inline double getCurrentTime() {
3     return (double) (clock() - startTime) / CLOCKS_PER_SEC;
4 }

```

5.6 TernarySearch

```

1 // return the maximum of $f(x)$ in $[L, r]$
2 double ternary_search(double l, double r) {
3     while(r - l > EPS) {
4         double m1 = l + (r - l) / 3;
5         double m2 = r - (r - l) / 3;
6         double f1 = f(m1), f2 = f(m2);
7         if(f1 < f2) l = m1;
8         else r = m2;
9     }
10    return f(l);
11 }
12
13 // return the maximum of $f(x)$ in $[L, r]$
14 int ternary_search(int l, int r) {
15     while(r - l > 1) {

```

```

16     int mid = (l + r) / 2;
17     if(f(m) > f(m + 1)) r = m;
18     else l = m;
19 }
20 return r;
21 }

```

6 Other

6.1 TouristIO

```

1 static struct FastInput {
2     static constexpr int BUF_SIZE = 1 << 20;
3     char buf[BUF_SIZE];
4     size_t chars_read = 0;
5     size_t buf_pos = 0;
6     FILE *in = stdin;
7     char cur = 0;
8
9     inline char get_char() {
10         if(buf_pos >= chars_read) {
11             chars_read = fread(buf, 1, BUF_SIZE, in);
12             buf_pos = 0;
13             buf[0] = (chars_read == 0 ? -1 : buf[0]);
14         }
15         return cur = buf[buf_pos++];
16         // return cur = getchar_unlocked();
17     }
18
19     inline void tie(int) {}
20
21     inline explicit operator bool() {
22         return cur != -1;
23     }
24
25     inline static bool is_blank(char c) {
26         return c <= ' ';
27     }
28
29     inline bool skip_blanks() {
30         while(is_blank(cur) && cur != -1) {
31             get_char();
32         }
33         return cur != -1;
34     }
35
36     inline FastInput& operator>>(char& c) {
37         skip_blanks();
38         c = cur;
39         return *this;
40     }
41
42     inline FastInput& operator>>(string& s) {
43         if(skip_blanks()) {
44             s.clear();
45             do {
46                 s += cur;
47             } while(!is_blank(get_char()));
48         }
49         return *this;
50     }
51
52     template<class T>
53     inline FastInput& read_integer(T& n) {
54         // unsafe, doesn't check that characters are actually
55         // digits
56         n = 0;
57         if(skip_blanks()) {
58             int sign = +1;
59             if(cur == '-') {
60                 sign = -1;
61                 get_char();
62             }
63             do {
64                 n += n * 10 + (cur - '0');
65             } while(!is_blank(get_char()));
66             n *= sign;
67         }
68         return *this;
69     }
70
71     template<class T>
72     inline typename enable_if<is_integral<T>::value, FastInput
73         &>::type operator>>(T& n) {
74         return read_integer(n);
75     }
76
77     #if!defined(_WIN32) || defined(_WIN64)
78     inline FastInput& operator>>(__int128& n) {
79         return read_integer(n);
80     }
81     #endif

```

```

80
81     template<class T>
82     inline typename enable_if<is_floating_point<T>::value,
83         FastInput&>::type operator>>(T& n) {
84         // not sure ifreally fast, for compatibility only
85         n = 0;
86         if(skip_blanks()) {
87             string s;
88             (*this) >> s;
89             sscanf(s.c_str(), "%Lf", &n);
90         }
91         return *this;
92     }
93
94     } fast_input;
95
96     #define cin fast_input
97
98     static struct FastOutput {
99         static constexpr int BUF_SIZE = 1 << 20;
100         char buf[BUF_SIZE];
101         size_t buf_pos = 0;
102         static constexpr int TMP_SIZE = 1 << 20;
103         char tmp[TMP_SIZE];
104         FILE *out = stdout;
105
106         inline void put_char(char c) {
107             buf[buf_pos++] = c;
108             if(buf_pos == BUF_SIZE) {
109                 fwrite(buf, 1, buf_pos, out);
110                 buf_pos = 0;
111             }
112             // putchar_unlocked(c);
113         }
114
115         ~FastOutput() {
116             fwrite(buf, 1, buf_pos, out);
117         }
118
119         inline FastOutput& operator<<(char c) {
120             put_char(c);
121             return *this;
122         }
123
124         inline FastOutput& operator<<(const char* s) {
125             while(*s) {
126                 put_char(*s++);
127             }
128             return *this;
129         }
130
131         inline FastOutput& operator<<(const string& s) {
132             for(int i = 0; i < (int) s.size(); i++) {
133                 put_char(s[i]);
134             }
135             return *this;
136         }
137
138         template<class T>
139         inline char* integer_to_string(T n) {
140             // beware of TMP_SIZE
141             char* p = tmp + TMP_SIZE - 1;
142             if(n == 0) {
143                 *--p = '0';
144             }
145             else {
146                 bool is_negative = false;
147                 if(n < 0) {
148                     is_negative = true;
149                     n = -n;
150                 }
151                 while(n > 0) {
152                     *--p = (char) ('0' + n % 10);
153                     n /= 10;
154                 }
155                 if(is_negative) {
156                     *--p = '-';
157                 }
158                 return p;
159             }
160         }
161
162         template<class T>
163         inline typename enable_if<is_integral<T>::value, char*>::type
164             stringify(T n) {
165             return integer_to_string(n);
166         }
167
168         #if!defined(_WIN32) || defined(_WIN64)
169         inline char* stringify(__int128 n) {
170             return integer_to_string(n);
171         }
172         #endif
173
174         template<class T>
175         inline typename enable_if<is_floating_point<T>::value, char
176             *>::type stringify(T n) {
177             sprintf(tmp, "%.17f", n);
178             return tmp;
179         }

```



```

174 }
175
176 template<class T>
177 inline FastOutput& operator<<(const T& n) {
178     auto p = stringify(n);
179     for(; *p != 0; p++) {
180         put_char(*p);
181     }
182     return *this;
183 }
184 } fast_output;
185
186 #define cout fast_output

```

7 Setup

7.1 Template

```

1 #include <bits/extc++.h>
2 #include <bits/stdc++.h>
3 #pragma GCC optimize("O3,unroll-loops")
4 #pragma GCC target("avx2,bmi,bmi2,lzcnt,popcnt")
5 #define IOS ios::sync_with_stdio(0),cin.tie(0),cout.tie(0)
6 #define int long long
7 #define double long double
8 #define pb push_back
9 #define sz(x) (int)(x).size()
10 #define all(v) begin(v),end(v)
11 #define debug(x) cerr<<#x<<" = "<<x<<'\n'
12 #define LINE cout<<"\n-----\n"
13 #define endl '\n'
14 #define VI vector<int>
15 #define F first
16 #define S second
17 #define MP(a,b) make_pair(a,b)
18 #define rep(i,m,n) for(int i = m;i<=n;++i)
19 #define res(i,m,n) for(int i = m;i>=n;--i)
20 #define gcd(a,b) __gcd(a,b)
21 #define lcm(a,b) a*b/gcd(a,b)
22 #define Case() int _;cin>>_;for(int Case = 1;Case<=++;Case)
23 #define pii pair<int,int>
24 using namespace __gnu_cxx;
25 using namespace __gnu_pbds;
26 using namespace std;
27 template <typename K, typename cmp = less<K>, typename T =
    cmp, T>;
28 template <typename K, typename M = null_type> using _hash =
    gp_hash_table<K, M>;
29 const int N = 1e6+5,L = 20,mod = 1e9+7;
30 const long long inf = 2e18+5;
31 const double eps = 1e-7,pi = acos(-1);
32 void solve(){
33 }
34 signed main(){
35     IOS;
36     solve();
37 }

```

8 String

8.1 DynamicKMP

```

1 template<int ALPHABET, int (*f)(char)>
2 class DynamicKMP {
3 public:
4     DynamicKMP() {}
5
6     DynamicKMP(const string& s) {
7         reserve(s.size());
8         for(const char& c : s) {
9             push(c);
10        }
11    }
12
13    void push(char c) {
14        int v = f(c);
15        dp.emplace_back();
16        dp.back()[v] = (int) dp.size();
17        if(p.empty()) {
18            p.push_back(0);
19            return;
20        }
21        int i = (int) p.size();
22        for(int j = 0; j < ALPHABET; ++j) {
23            if(j == v) {
24                p.push_back(dp[p[i - 1]][j]);

```

```

25        } else {
26            dp.back()[j] = dp[p[i - 1]][j];
27        }
28    }
29 }
30
31 void pop() {
32     p.pop_back();
33     dp.pop_back();
34 }
35
36 int query() const {
37     return p.back();
38 }
39
40 vector<int> query_all() const {
41     return p;
42 }
43
44 void reserve(int sz) {
45     p.reserve(sz);
46     dp.reserve(sz);
47 }
48
49 private:
50     vector<int> p;
51     vector<array<int, ALPHABET>> dp;
52 };

```

8.2 RollingHash

```

1 template<int HASH_COUNT, bool PRECOMPUTE_POWERS = false>
2 class Hash {
3 public:
4     static constexpr int MAX_HASH_PAIRS = 10;
5
6     // {mul, mod}
7     static constexpr const pair<int, int> HASH_PAIRS[] =
8         {{827167801, 999999937}, {998244353, 999999929},
9          {146672737, 922722049}, {204924373, 952311013},
10          {585761567, 955873937}, {484547929, 901981687},
11          {856009481, 987877511}, {852853249, 996724213},
12          {937381759, 994523539}, {116508269, 993179543}};
13
14     Hash() : Hash("") {}
15
16     Hash(const string& s) : n(s.size()) {
17         static_assert(HASH_COUNT > 0 && HASH_COUNT <=
18             MAX_HASH_PAIRS);
19         for(int i = 0; i < HASH_COUNT; ++i) {
20             const auto& p = HASH_PAIRS[i];
21             pref[i].resize(n);
22             pref[i][0] = s[0];
23             for(int j = 1; j < n; ++j) {
24                 pref[i][j] = (1LL * pref[i][j - 1] * p.first + s[j]) %
25                     p.second;
26             }
27         }
28         if(PRECOMPUTE_POWERS) {
29             build_powers(n);
30         }
31     }
32
33     void add_char(char c) {
34         for(int i = 0; i < HASH_COUNT; ++i) {
35             const auto& p = HASH_PAIRS[i];
36             pref[i].push_back((1LL * (n == 0 ? 0 : pref[i].back()) *
37                 p.first + c) % p.second);
38         }
39         n += 1;
40         if(PRECOMPUTE_POWERS) {
41             build_powers(n);
42         }
43     }
44
45     // Return hash values for [l, r)
46     array<int, HASH_COUNT> substr(int l, int r) {
47         array<int, HASH_COUNT> res{};
48         for(int i = 0; i < HASH_COUNT; ++i) {
49             res[i] = substr(i, l, r);
50         }
51         return res;
52     }
53
54     array<int, HASH_COUNT> merge(const vector<pair<int, int>>&
55         seg) {
56         array<int, HASH_COUNT> res{};
57         for(int i = 0; i < HASH_COUNT; ++i) {
58             const auto& p = HASH_PAIRS[i];
59             for(auto [l, r] : seg) {
60                 res[i] = (1LL * res[i] * get_power(i, r - l) + substr(i,
61                     l, r)) % p.second;
62             }
63         }
64     }
65 }

```

```

54     return res;
55 }
56
57 // build powers up to x^k
58 void build_powers(int k) {
59     for(int i = 0; i < HASH_COUNT; ++i) {
60         const auto& p = HASH_PAIRS[i];
61         int sz = (int) POW[i].size();
62         if(sz > k) {
63             continue;
64         }
65         if(sz == 0) {
66             POW[i].push_back(1);
67             sz = 1;
68         }
69         while(sz <= k) {
70             POW[i].push_back(1LL * POW[i].back() * p.first % p.
71                 second);
72             sz += 1;
73         }
74     }
75
76     inline int size() const {
77         return n;
78     }
79 private:
80     int n;
81     static vector<int> POW[MAX_HASH_PAIRS];
82     array<vector<int>, HASH_COUNT> pref;
83
84     int substr(int k, int l, int r) {
85         assert(0 <= k && k < HASH_COUNT);
86         assert(0 <= l && l <= r && r <= n);
87         const auto& p = HASH_PAIRS[k];
88         if(l == r) {
89             return 0;
90         }
91         int res = pref[k][r - 1];
92         if(l > 0) {
93             res -= 1LL * pref[k][l - 1] * get_power(k, r - 1) % p.
94                 second;
95         }
96         if(res < 0) {
97             res += p.second;
98         }
99         return res;
100     }
101
102     int get_power(int a, int b) {
103         if(PRECOMPUTE_POWERS) {
104             build_powers(b);
105             return POW[a][b];
106         }
107         const auto& p = HASH_PAIRS[a];
108         return power(p.first, b, p.second);
109     }
110 };
111 template<int A, bool B> vector<int> Hash<A, B>::POW[Hash::
    MAX_HASH_PAIRS];

```

8.3 SuffixArray

```

1 struct suffix_array{
2     int n;
3     vector<int>SA, Rank, LCP;
4     void counting_sort(vector<int>&v, auto getkey){
5         int n = 0;
6         for(auto i:v)n = max(n, getkey(i)+1);
7         vector<int>bucket(n), ans(v.size());
8         for(auto i:v)++bucket[getkey(i)];
9         partial_sum(begin(bucket), end(bucket), begin(bucket));
10        for(auto ite = v.rbegin(); ite!=v.rend(); ++ite)ans[--bucket[
11            getkey(*ite)]] = move(*ite);
12        v.swap(ans);
13        return;
14    }
15    suffix_array(string s):n(s.size()){
16        SA.resize(n), Rank.resize(n), LCP.resize(n);
17        for(int i = 0; i<n; ++i)SA[i] = i;
18        sort(SA.begin(), SA.end(), [&](int a, int b){
19            return s[a]<s[b];
20        });
21        for(int i = 0; i<n; ++i){
22            Rank[SA[i]] = (i?Rank[SA[i-1]]+(s[SA[i]]!=s[SA[i-1]]):SA
23                [0]);
24        }
25        for(int k = 0; (1<<k)<=n; ++k){
26            vector<int>idx;
27            for(int i = n-(1<<k); i<n; ++i)idx.push_back(i);
28            for(auto i:SA)if(i>=(1<<k))idx.push_back(i-(1<<k));
29            counting_sort(idx, [&](int a){return Rank[a];});
30            SA.swap(idx);

```

```

29     vector<int>new_rank(n);
30     new_rank[SA[0]] = 0;
31     for(int i = 1; i<n; ++i){
32         auto cmp = [&](int a, int b){
33             return Rank[a]!=Rank[b] or a+(1<<k)>=n or Rank[a+(1<<
34                 k)]!=Rank[b+(1<<k)];
35         };
36         new_rank[SA[i]] = new_rank[SA[i-1]]+cmp(SA[i-1], SA[i]);
37     }
38     Rank.swap(new_rank);
39     for(int i = 0, k = 0; i<n; ++i){
40         if(Rank[i]==0)continue;
41         if(k--<0);
42         while(i+k<n and SA[Rank[i]-1]+k<n and s[i+k]==s[SA[Rank[i]
43             ]-1+k])++k;
44         LCP[Rank[i]] = k;
45     }
46 };

```

8.4 Trie

```

1 template<int ALPHABET = 26, char MIN_CHAR = 'a'>
2 class trie {
3 public:
4     struct Node {
5         int go[ALPHABET];
6         Node() {
7             memset(go, -1, sizeof(go));
8         }
9     };
10
11     trie() {
12         newNode();
13     }
14
15     inline int next(int p, int v) {
16         return nodes[p].go[v] != -1 ? nodes[p].go[v] : nodes[p].go[
17             v] = newNode();
18     }
19
20     inline void insert(const vector<int>& a, int p = 0) {
21         for(int v : a) {
22             p = next(p, v);
23         }
24     }
25
26     inline void clear() {
27         nodes.clear();
28         newNode();
29     }
30
31     inline int longest_common_prefix(const vector<int>& a, int p
32         = 0) const {
33         int ans = 0;
34         for(int v : a) {
35             if(nodes[p].go[v] != -1) {
36                 ans += 1;
37                 p = nodes[p].go[v];
38             } else {
39                 break;
40             }
41         }
42         return ans;
43     }
44 private:
45     vector<Node> nodes;
46
47     inline int newNode() {
48         nodes.emplace_back();
49         return (int) nodes.size() - 1;
50     };

```

ACM ICPC Team

Reference -

LeeJiaHuaPlayMinecraft

Contents

1 Data-Structure

1.1 Treap	1
1.2 Segtree	1
1.3 DsuUndo	2
1.4 DSU	2
1.5 Fenwick	2
1.6 Persistent DSU	2
1.7 TimingSegtree	2
1.8 AreaOfRectangles	3
1.9 SparseTable	3
1.10 VEBTree	3
1.11 DynamicSegtree	4
1.12 ZkwSegtree	4
1.13 MoAlgo	5
1.14 Hash	5
1.15 RedBlackTree	5

2 Geometry

2.1 Theorem	5
2.2 PointInPolygon	5
2.3 PointInConvex	6
2.4 MaximumDistance	6
2.5 PolarAngleSort	6
2.6 MinimumDistance	6
2.7 ConvexHull	6
2.8 Template	6

3 Graph

3.1 HLD	7
3.2 Bridges	7
3.3 TwoSat	7
3.4 MCMF	7
3.5 LCA	8
3.6 CentroidDecomposition	8
3.7 BCC AP	8
3.8 SCC	9
3.9 LineContainer	9
3.10 Dinic	9

4 Math

4.1 Numbers	10
4.2 ExtendGCD	10
4.3 BerlekampMassey	10
4.4 InvGCD	11
4.5 GeneratingFunctions	11
4.6 Theorem	11
4.7 FloorSum	11
4.8 Factorizer	12
4.9 PowMod	12
4.10 CRT	12
4.11 DiscreteLog	12
4.12 LinearSieve	12

5 Misc

5.1 FastIO	13
5.2 Debug	13
5.3 Discrete	13
5.4 DuiPai	13
5.5 Timer	13
5.6 TenarySearch	13

6 Other

6.1 TouristIO	14
---------------	----

7 Setup

7.1 Template	15
--------------	----

8 String

8.1 DynamicKMP	15
8.2 RollingHash	15
8.3 SuffixArray	16
8.4 Trie	16

ACM ICPC Judge Test - LeeJiaHuaPlayMinecraft

C++ Resource Test

```
1 #include <bits/stdc++.h>
2 using namespace std;
3
4 namespace system_test {
5
6     const size_t KB = 1024;
7     const size_t MB = KB * 1024;
8     const size_t GB = MB * 1024;
9
10    size_t block_size, bound;
11    void stack_size_dfs(size_t depth = 1) {
12        if (depth >= bound)
13            return;
14        int8_t ptr[block_size]; // 若無法編譯將 block_size 改成常數
15        memset(ptr, 'a', block_size);
16        cout << depth << endl;
17        stack_size_dfs(depth + 1);
18    }
19
20    void stack_size_and_runtime_error(size_t block_size, size_t
        bound = 1024) {
21        system_test::block_size = block_size;
22        system_test::bound = bound;
23        stack_size_dfs();
24    }
25
26    double speed(int iter_num) {
27        const int block_size = 1024;
28        volatile int A[block_size];
29        auto begin = chrono::high_resolution_clock::now();
30        while (iter_num--)
31            for (int j = 0; j < block_size; ++j)
32                A[j] += j;
33        auto end = chrono::high_resolution_clock::now();
34        chrono::duration<double> diff = end - begin;
35        return diff.count();
```

```
36    }
37
38    void runtime_error_1() {
39        // Segmentation fault
40        int *ptr = nullptr;
41        *(ptr + 7122) = 7122;
42    }
43
44    void runtime_error_2() {
45        // Segmentation fault
46        int *ptr = (int *)memset;
47        *ptr = 7122;
48    }
49
50    void runtime_error_3() {
51        // munmap_chunk(): invalid pointer
52        int *ptr = (int *)memset;
53        delete ptr;
54    }
55
56    void runtime_error_4() {
57        // free(): invalid pointer
58        int *ptr = new int[7122];
59        ptr += 1;
60        delete[] ptr;
61    }
62
63    void runtime_error_5() {
64        // maybe illegal instruction
65        int a = 7122, b = 0;
66        cout << (a / b) << endl;
67    }
68
69    void runtime_error_6() {
70        // floating point exception
71        volatile int a = 7122, b = 0;
72        cout << (a / b) << endl;
73    }
74
75    void runtime_error_7() {
76        // call to abort.
77        assert(false);
78    }
79
80    } // namespace system_test
81
82    #include <sys/resource.h>
83    void print_stack_limit() { // only work in Linux
84        struct rlimit l;
85        getrlimit(RLIMIT_STACK, &l);
86        cout << "stack_size = " << l.rlim_cur << " byte" << endl;
87    }
```