Advanced Numerical Theory and Optimization in Computational Holography: Integrating p-Adic Architectures, 1-Bit LAMB, and RAM Sampling for Ultra-Efficient TIFF Holograms

The generation, transmission, and rendering of computer-generated holograms (CGH) represent one of the most formidable computational challenges in modern optics and spatial computing. The synthesis of high-fidelity, three-dimensional wavefields relies on the numerical manipulation of massive datasets, which are consistently bound by rigid constraints in memory bandwidth, computational latency, and physical hardware display limits. Achieving real-time, high-resolution volumetric displays necessitates moving beyond isolated incremental improvements and instead requires a fundamental convergence of disparate scientific disciplines. This includes large-scale distributed machine learning optimization, non-Archimedean numerical theory, highly optimized memory access paradigms, and binary optical modulation.

This report establishes a comprehensive theoretical and architectural framework for synthesizing "super-efficient" processable Tagged Image File Format (TIFF) holograms. The proposed framework relies on four foundational pillars, each addressing a specific bottleneck in the holographic pipeline. First, the 1-bit LAMB (Layer-wise Adaptive Moments optimizer for Batch training) algorithm provides a highly communication-efficient distributed training regime for the massive deep neural networks tasked with predicting complex holographic fringe patterns. Second, p-adic numerical theory and ultrametric architectures furnish a mathematically rigorous foundation for memory addressing, aligning natively with the hierarchical quadtree structures of tiled TIFF formats and enabling lossless topological data management. Third, RAM sampling and Look-Up Table (LUT) techniques eliminate redundant runtime wave propagation calculations, bypassing traditional Fourier or Fresnel transform bottlenecks. Finally, Direct Binary Search (DBS) optimization and Lee holography principles enable the translation of these complex, continuous wavefields onto ultra-fast 1-bit Digital Micromirror Devices (DMDs) or binary Spatial Light Modulators (SLMs). By unifying these methodologies, it is possible to achieve previously unattainable efficiencies in the generation and display of dynamic holographic content.

1. Large-Scale Optimization in Holographic Machine Learning: The 1-Bit LAMB Framework

The synthesis of complex holograms is increasingly driven by deep neural networks (DNNs), which learn to map three-dimensional spatial coordinates or point clouds to two-dimensional

complex phase masks. Training these models to achieve high spatial frequencies and accurate depth cues requires immense batch sizes and massive parameter synchronization across distributed computing nodes. The standard LAMB optimizer was developed to successfully scale batch sizes to the tens of thousands without accuracy degradation, enabling batch sizes of 32K for ImageNet and up to 64K or 96K for BERT pre-training when combined with Nesterov momentum and specific learning rate schedulers like LANS. However, the full-precision communication overhead in a data-parallel distributed environment severely limits overall throughput, particularly for the dense models required in optical field prediction.

1.1 The Theoretical Foundation of LAMB and the 1-Bit Compression Paradigm

To address systemic communication bottlenecks, the 1-bit LAMB framework introduces aggressive gradient and momentum compression while preserving the sample-wise convergence speed of its full-precision counterpart. Traditional 1-bit gradient compression techniques suffer catastrophic performance drops when applied to adaptive optimizers like Adam or LAMB. This degradation occurs because non-linear operations—such as dividing by the square root of the second moment—destroy the coordinate-wise adaptivity when a single shared scaling factor (magnitude) is applied to a compressed gradient vector.
The underlying optimization problem seeks to minimize a non-convex loss function $f(\bm{x}) = \frac{1}{n} \sum_{i=1}^n \mathbb{E}_{\bm{\xi} \sim \mathcal{D}_i} F(\bm{x}, \bm{\xi})$, where $\bm{x} \in \mathbb{R}^d$ represents the model parameters, d is the dimensionality of the model, and $\mathcal{D}_i$ is the data distribution on the i-th worker. The full-precision LAMB algorithm updates the first moment $\bm{m}_t$ (momentum) and the second moment $\bm{v}_t$ (variance) at layer l and time step t as follows:
$\bm{m}_t^{(l)} = \beta_1 \bm{m}_{t-1}^{(l)} + (1-\beta_1)\bm{g}_t^{(l)}$ $\bm{v}_t^{(l)} = \beta_2 \bm{v}_{t-1}^{(l)} + (1-\beta_2)(\bm{g}_t^{(l)})^2$
Bias corrections are applied to yield $\hat{\bm{m}}_t^{(l)} = \bm{m}_t^{(l)} / (1-\beta_1^t)$ and $\hat{\bm{v}}_t^{(l)} = \bm{v}_t^{(l)} / (1-\beta_2^t)$. A scaling vector is computed as $\bm{u}_t^{(l)} = \frac{\hat{\bm{m}}_t^{(l)}}{\sqrt{\hat{\bm{v}}_t^{(l)}} + \epsilon}$, and the parameters are updated using an adaptive layer-wise learning rate governed by a scaling function ϕ:
$\bm{x}_{t+1}^{(l)} = \bm{x}_t^{(l)} - \eta_t \frac{\phi(\Vert{}\bm{x}_t^{(l)}\Vert{})}{\Vert{}\bm{u}_t^{(l)}\Vert{}} \bm{u}_t^{(l)}$
In the 1-bit LAMB framework, a non-linear scaling problem emerges if 1-bit compression is applied naively. The primary innovation of 1-bit LAMB is circumventing this by freezing the variance term $\bm{v}_t^{(l)}$ after a predefined warm-up stage. Empirical studies on large-scale models indicate that the warm-up stage typically accounts for 16.7% to 19.2% of the total training steps. For instance, in a training cycle of 5,993 steps, the first 1,000 steps are utilized to establish stable, full-precision second moments. During this phase, hyperparameters are strictly tuned, with typical values set at $\beta_1 = 0.9$ and $\beta_2 = 0.999$.
Following this warm-up, the algorithm enters the compression stage, utilizing a randomized compressing operator $\mathc[span_16](start_span)[span_16](end_span)al{C}_\omega(\cdot)$. The compression operator reduces the precision of the communicated momentum to 1 bit (e.g., utilizing coordinate-wise signs accompanied by a shared magnitude over the entire tensor), drastically shrinking the necessary communication volume across the distributed network.

1.2 Error Compensation Mechanisms and System Implementation

The critical mechanism enabling 1-bit LAMB to match full-precision convergence is its highly robust error compensation architecture. When a worker node compresses its momentum \bm{m}_t^{(i)}, it calculates a local compression error \bm{\delta}_t^{(i)} = \bm{m}_t^{(i)} + \bm{\delta}_{t-1}^{(i)} - \mathcal{C}_\omega(\bm{m}_t^{(i)} + \bm{\delta}_{t-1}^{(i)}). The compressed momentum \hat{\bm{m}}_t^{(i)} is then transmitted to the central server or parameter server. The server aggregates these compressed vectors, applies a global compression operator to the average, tracks a global error \bar{\bm{\delta}}_t, and broadcasts the globally compressed momentum back to the workers.

Because 1-bit compression cannot represent an exact numerical zero, parameters with constant zero gradients (such as specific padding embeddings in NLP or masked spatial regions in holographic generation) continuously accumulate compression errors. To mitigate this drift, 1-bit LAMB employs momentum masks for parameters with stable zero gradients, effectively isolating them from the error compensation loop and preventing divergence.

To rigorously justify this approach, theoretical convergence bounds depend on specific assumptions regarding the objective function. Assumption 1 requires a Lipschitzian gradient, ensuring that \Vert{}\nabla f(\bm{x}) - \nabla f(\bm{y})\Vert{} \le L \Vert{}\bm{x} - \bm{y}\Vert{}, and Assumption 2 requires bounded variance such that the stochastic gradient computed on each worker is unbiased with \mathbb{E}_{\bm{\xi} \sim \mathcal{D}} \Vert{}\nabla f(\bm{x}; \bm{\xi}) - \nabla f(\bm{x}[span_21](start_span)[span_21](end_span))\Vert{}^2 \le \sigma^2. Under these conditions, variations of 1-bit adaptive optimizers achieve an \epsilon-approximate first-order stationary point, ensuring that \mathbb{E}\Vert{}\nabla f(\bm{x})\Vert{}^2 \le \eps[span_27](start_span)[span_27](end_span)[span_28](start_span)[span_28](end_span)ilon at a convergence rate proportional to O(1/\sqrt{nT}).

Metric / Parameter	Uncompressed LAMB	1-Bit LAMB
Communication Precision	32-bit / 16-bit (FP32/FP16)	1-bit (during compression stage)
Second Moment (\bm{v}_t)	Continuously updated throughout	Frozen after 16.7% - 19.2% warm-up
Error Compensation	Not required	Local and Global \bm{\delta}_t tracking
Communication Volume	O(d) bits per transfer	Up to 4.6x reduction
End-to-End Speedup	Baseline	Up to 2.8x (System dependent)

System implementation is equally critical to realizing these theoretical gains. Advanced frameworks like DeepSpeed implement 1-bit LAMB using the PyTorch NCCL (NVIDIA Collective Communications Library) backend. By bypassing less efficient MPI-based protocols, NCCL-based 1-bit LAMB allows compressed communication to achieve near-linear scaling across massive GPU clusters. Evaluations demonstrate that 1-bit LAMB operating on standard Ethernet networks (4.1 Gbps effective bandwidth, 4 GPUs per node) can achieve comparable training throughput to uncompressed LAMB operating on high-end InfiniBand networks (near 100 Gbps effective bandwidth, 8 GPUs per node). This hardware-agnostic efficiency is vital when training models to generate gigapixel-scale holograms, transforming weeks of compute time into days.

2. Non-Archimedean Geometry: p-Adic Numerical

Theory and Ultrametric Data Architectures

Traditional models of continuous space assume Euclidean geometry, which is governed by Archimedean norms. However, the hierarchical data structures required to represent massive synthetic wavefields—such as the massive quadtrees utilized in tiled TIFF images—are fundamentally non-Archimedean. Analyzing these spatial hierarchies through the lens of p-adic numerical theory provides a rigorous, unified, and highly efficient mathematical framework for memory addressing, caching, and signal processing.

2.1 The Topology of p-Adic Numbers and Ultrametric Spaces

The field of p-adic numbers, denoted as \mathbb{Q}_p, is defined as the topological completion of the rational numbers \mathbb[span_37](start_span)[span_37](end_span)[span_38](start_span)[span_38](end_span)[span_39](start_span)[span_39](end_span){Q} with respect to the p-adic absolute value \vert{}\cdot\vert{}_p. For any non-zero rational number x = p^\gamma \frac{a}{b}, where a and b are integers strictly coprime to a fixed prime p, the p-adic norm is defined as \vert{}x\vert{}_p = p^{-\gamma}.
Unlike the standard absolute value on the real number line, the p-adic norm satisfies the strong triangle inequality:
\vert{}x + y\vert{}_p \le \max(\vert{}x\vert{}_p, \vert{}y\vert{}_p)
This foundational property engenders an ultrametric space possessing highly counter-intuitive geometric characteristics: all triangles are isosceles, and any point within a p-adic ball can be considered its center. Furthermore, the topology dictates that two p-adic balls are either completely disjoint, or one is strictly contained within the other, entirely eliminating overlapping boundaries. The ring of p-adic integers, \mathbb{Z}_p, consists of all elements x \in \mathbb{Q}_p such that \vert{}x\vert{}_p \le 1, effectively forming a closed unit ball containing zero.
A p-adic integer can be uniquely represented as an infinite formal series x = \sum_{i=0}^\infty a_i p^i, where the digits a_i \in \{0, 1, \dots, p-1\}. This base-p expansion is identical in structure to a hierarchical, multi-way tree. If p=2, the 2-adic integers correspond directly to infinite binary strings. This topological structure maps natively to the quadtree decomposition (where branching factors are powers of 2, essentially treating coordinates as 2-adic pairs) used extensively in spatial computing, building information models, and image processing.

2.2 Bruhat-Tits Trees, van der Put Basis, and Hierarchical Memory Addressing

The geometric gap between continuous optical fields and discrete hierarchical storage formats is bridged by canonical p-adic space. The arithmetic geometry of the bulk space is commonly mapped onto a Bruhat-Tits tree T_p, a highly symmetric infinite graph where each vertex possesses exactly p+1 neighbors. In computational holography, where massive tiled TIFF images must be stored and accessed recursively, a quadtree representation linearizes 2D space for optimized run-length encoded data storage and computational efficiency.
By utilizing p-adic addresses (or quad tesseral addressing), the operation of finding a neighboring memory block or translating a spatial coordinate transforms from complex multidimensional arithmetic into simple bitwise interleaving or p-adic arithmetic without carries.

Recent advancements in neural architectures, such as p-adic neural networks (v-PuNNs), exploit this topology. The v-PuNN utilizes neurons that function directly as characteristic functions of p-adic balls, enabling a lossless, white-box representation of hierarchies. This leads to Transparent Ultrametric Representation Learning (TURL), where every parameter is a p-adic number with a direct structural interpretation. The Finite Hierarchical Approximation Theorem states that a depth-K v-PuNN universally approximates any function on a K-level hierarchy, demonstrating empirical success such as achieving 99.96% accuracy on complex taxonomies in under 16 minutes on a 32 GB CPU.
To represent continuous functions in this space, the van der Put basis provides an orthonormal basis over p-adic fields, expanding functions into series of characteristic functions of p-adic balls. A continuous function f: \mathbb{Z}_p \to \mathbb{Q}_p can be uniformly approximated using this basis, allowing the spatial frequencies of a hologram to be mapped perfectly to the specific resolution scales embedded within a quadtree data structure.

2.3 Signal Processing: The Vladimirov Operator and p-Adic Fourier Transform

Because holography is fundamentally a study of Fourier optics and wave propagation, translating these operations to a p-adic architecture necessitates a p-adic equivalent of differentiation and frequency analysis. The Vladimirov-Taibleson operator serves as the p-adic analog of the fractional Laplacian, defining fractional differentiation on non-Archimedean fields. The operator D^\alpha acts on a complex-valued function f(x) of a p-adic argument as:
D^\alpha f(x) = \frac{1}{\Gamma_p(-\alpha)} \int_{\mathbb{Q}_p} \frac{f(x)-f(y)}{\vert{}x-y\vert[span_72](start_span)[span_72](end_span)[span_74](start_span)[span_74](end_span){}_p^{1+\alpha}} d\mu(y)
where \mu(y) represents the Haar measure, normalized such that the measure of the unit ball \mu(\mathbb{Z}_p) = 1.
Simultaneously, the p-adic Fourier transform maps functions over \mathbb{Q}_p into an ultrametric frequency domain. It relies on the additive character \chi(\xi x) = \exp(2\pi i \{\xi x\}), where \{\cdot\} denotes the fractional part of the p-adic number. For a function f \in L^1(\mathbb{Q}_p), the transform is defined as:
\mathcal{F}[f](\xi) = \int_{\mathbb{Q}_p} \chi(\xi x) f(x) d\mu(x)
Wavelet analysis in this ultrametric space behaves natively as p-adic spectral analysis. The eigenfunctions of the Vladimirov operator form a basis of p-adic wavelets, directly decomposing a spatial field into resolution levels. The Monna map \rho: \mathbb{Q}_p \to \mathbb{R}^+ transforms these p-adic wavelets into standard Haar wavelets on the positive half-line, bridging the non-Archimedean logic back to real-world display hardware. When generating CGH, utilizing p-adic Fourier transforms natively decomposes the hologram into perfectly disjoint spatial tiles. This inherently prepares the data for the tiled TIFF format and drastically reduces computational overhead during memory retrieval by ensuring that adjacent spatial features are co-located in memory.

3. High-Efficiency Holographic Rendering: Look-Up Tables and RAM Sampling

While deep learning provides the global holographic phase map and p-adic addressing

optimizes data traversal, the physical rendering of Computer-Generated Holograms requires the precise numerical synthesis of optical wavefronts. The core calculation for point-cloud-based CGH consists of a massive double summation of all visible object points for each individual pixel on the hologram plane.

3.1 The Computational Bottleneck in Wavefront Synthesis

For a hologram plane positioned at z=0, the complex amplitude H(x_h, y_h) generated by an arbitrary 3D point cloud is given by the Rayleigh-Sommerfeld diffraction integral, computationally discretized as:
H(x_h, y_h) = \sum_{j=1}^N a_j \frac{\exp(i k \Vert{}p_j - x\Vert{})}{\Vert{}p_j - x\Vert{}}
where a_j is the real amplitude of the j-th point, p_j = (x_j, y_j, z_j) is its 3D coordinate, x = (x_h, y_h, 0) is the 2D hologram pixel coordinate, and k is the optical wavenumber. In modern high-resolution displays, the number of point sources N can easily exceed tens of millions. The requirement to evaluate this distance metric and complex exponential for every combination of N points and P pixels leads to an O([span_82](start_span)[span_82](end_span)[span_83](start_span)[span_83](end_span)N \times P) complexity. This dense, many-to-many mapping creates a computational bottleneck that severely exceeds the processing capabilities of even high-end CPUs.

3.2 RAM Sampling, Precomputed Look-Up Tables, and WRP

To circumvent these strict arithmetic limits, advanced rendering algorithms shift the computational burden from the Arithmetic Logic Units (ALUs) directly to memory bandwidth via RAM sampling and Look-Up Tables (LUTs). In an LUT architecture, the elemental interference fringe patterns of point sources at various quantized depths and lateral positions are precalculated offline. These complex distributions are stored dynamically in the RAM or GPU VRAM.
During runtime, the algorithm uses the 3D coordinates of the object points as direct memory addresses to fetch the corresponding precalculated wavefronts. The fetched patterns are then linearly accumulated to form the final hologram. Furthermore, combining LUTs with Wavefront Recording Plane (WRP) methods allows the complex field to be first calculated on a virtual plane close to the 3D object, drastically reducing the active area of the fringe pattern that needs to be accessed and summed, before propagating the unified WRP field to the final hologram plane.

Computational Paradigm	Traditional Double Summation	RAM Sampling (LUT + WRP)
Wavefront Generation	Evaluated continuously at runtime	Precomputed and fetched via addressing
Algorithmic Complexity	O(N \times P) (Points \times Pixels)	O(N) (Memory fetch and accumulate)
Primary Hardware Bottleneck	Arithmetic Logic Units (ALUs)	Memory Bandwidth / DMA Speed
Precision	Exact analytic precision	Quantized based on the discrete LUT grid

3.3 GPU Parallelization and Nonuniform Sampling

The practical execution of the LUT approach relies heavily on GPU parallelization utilizing

frameworks like the Compute Unified Device Architecture (CUDA). To prevent memory race conditions when multiple object points attempt to update the same hologram pixel, the parallelization is typically sample-driven rather than point-driven. Each thread is assigned a specific hologram plane sample and iterates through the visible point array.
Further efficiency is achieved through non-uniform RAM sampling. Instead of computing the complex amplitude for every node on a dense regular grid, an array of random sampling points is precomputed and copied into the GPU memory. The Common Visibility Group (CVG) approximation divides the hologram plane into small groups where all samples within a CVG share an identical set of visible object points. The visibility is computed only once with respect to the center of the CVG, dramatically pruning the computational tree. When tested on high-resolution targets, GPU implementations of these techniques achieve calculation times of approximately 7.24 seconds, compared to 346.6 seconds for standard CPU implementations, representing nearly a 48x speedup. Combined with p-adic memory mapping, CUDA thread blocks exhibit extremely high cache-hit rates, enabling near real-time generation of the target wavefront.

4. Hardware Realization: Binary Optics, DMDs, and 1-Bit Modulation

Generating the complex amplitude field mathematically is only half the challenge; the resultant field must be physically displayed. While grayscale, phase-only Spatial Light Modulators (SLMs) exist (using liquid crystal technology), they are heavily hindered by slow refresh rates, often maxing out around 60 Hz to 240 Hz. In contrast, Digital Micromirror Devices (DMDs)—operating via binary amplitude modulation, where mirrors physically tilt to an "on" or "off" state—provide 1-bit switching speeds in excess of 22 kHz. This extreme temporal bandwidth enables rich spatial multiplexing, albeit at the steep cost of requiring the continuous, multi-level wavefront to be aggressively compressed into a 1-bit binary hologram.

4.1 Binarization Techniques: Direct Binary Search (DBS) and Simulated Annealing

Translating a continuous-tone complex hologram into a binary representation requires intense optimization algorithms, as naive thresholding ruins image fidelity and introduces severe diffraction artifacts. The Direct Binary Search (DBS) algorithm is a highly effective, non-linear optimization method used to minimize the Mean Squared Error (MSE) between the target image and the image optically reconstructed from the binary hologram.
DBS operates in a rigorous iterative loop modeled on Markov chain principles: 1. An initial random binary hologram $H_b(m, n)$ is generated. The reconstructed field is computed via Fast Fourier Transforms (FFT), establishing a baseline MSE_0. 2. A single pixel is toggled (inverted from 0 to 1, or 1 to 0). 3. The new reconstructed image is calculated, yielding MSE_{mn}. 4. The difference $\Delta E = MSE_{mn} - MSE_0$ is evaluated. If $\Delta E < 0$, the toggle reduces the error and is retained. If positive, the toggle is rejected and undone.
Because performing a full inverse FFT for every trial pixel toggle is computationally prohibitive (the asymptotic computational complexity scales aggressively with the hologram space-bandwidth product), the optimized DBS algorithm again relies on RAM sampling. The diffraction field contribution of a single pixel is precomputed as an LUT. Consequently,

evaluating a trial inversion merely requires adding or subtracting this precomputed field vector from the current reconstruction array, reducing the complexity by over two orders of magnitude. Advanced variants like Simulated Annealing Binary Search (SABS) incorporate a probabilistic acceptance of error-increasing toggles to escape local minima, decreasing the final MSE of the reconstructed field by an additional 32% compared to standard simulated annealing.

4.2 Lee Holography and the Efficiency-Speckle Trade-off

An alternative to the computationally heavy DBS is the Lee hologram method, which encodes complex wavefields into binary amplitude fringes by spatially shifting a grating structure. The required spatial frequency of the binary hologram \nu(x,y) is deterministically dictated by the desired carrier frequency k and the target phase change \phi(x,y):
$$\nu(x,y) = k + \frac{1}{2\pi} \frac{\partial \phi(x,y)}{\partial x}$$
While the Lee method is deterministic and allows the DMD to function as a fast phase modulator, it strictly bounds the overall diffraction efficiency. Because binary amplitude modulators discard all light hitting the "off" pixels, and the binary grating necessarily diffracts energy into multiple unwanted harmonic orders, the theoretical maximum object efficiency for an amplitude-only binary CGH cannot exceed 10% to 50%.
Furthermore, utilizing coherent illumination on a binary pixel grid inherently produces severe speckle noise due to inter-pixel interference. There exists a fundamental trade-off between diffraction efficiency, spatial resolution, and speckle reduction. Hologram tiling—where an array of slightly modified sub-holograms is projected—can mitigate speckle noise by averaging out the coherent artifacts over time or space, though it reduces the effective spatial bandwidth product. DMDs compensate for this lower per-frame spatial resolution by utilizing their ultra-fast frame rates to integrate multiple tiled patterns temporally, generating a high-quality, time-averaged 3D scene suitable for applications like Optical Diffraction Tomography (ODT), achieving refractive index sensitivities as fine as 3.15×10^{-4}.

4.3 Hardware-Level 1-Bit Error Compensation

Much like the 1-bit LAMB optimizer at the software level, physical hardware rendering must compensate for 1-bit truncation errors. Hardware-efficient designs utilizing the floor function $Q_{trunc}(x) = \lfloor x \rfloor$ confine the truncation error to (-1, 0], introducing a systematic negative bias of -0.5 in accumulator logic. In a convolution or spatial integration operation accumulating N products, this bias degrades image fidelity. Implementations utilizing the AEMAC (Approximate Error-compensated MAC) architecture conditionally inject a bias of +1 during low-precision modes. This shifts the error interval to (0, 1], resulting in a positive mean bias of +0.5. By hybridizing these modes dynamically, the statistical sum of the errors centers on zero, reducing the Mean Absolute Error (MAE) from 0.9614 to 0.8008 without requiring complex rounding circuitry. This ensures that the 1-bit processing pipeline maintains extreme fidelity from the neural network layers directly down to the physical DMD mirrors.

5. Synthesizing the Paradigm: Ultra-Efficient TIFF Holograms via Convergent Architecture

The integration of 1-bit LAMB optimization, p-adic ultrametric architectures, RAM sampling, and binary DMD optics leads to a novel rendering paradigm: the end-to-end generation of

"super-efficient processable TIFF holograms."
The TIFF (Tagged Image File Format) standard is highly optimized for storing and transmitting gigapixel-scale images via tiling. Instead of parsing linear scanlines, tiled TIFFs partition the image into discrete rectangular blocks configured specifically by the TileWidth and TileLength directory tags. This spatial blocking inherently maps to a quadtree (a 2-adic mathematical structure), where each tile represents a spatial domain of discourse at a specific hierarchical depth, natively supporting multi-resolution pyramids.

5.1 The Integrated Computational Pipeline

The architectural synthesis operates through a unified, fully integrated pipeline:

1. **Model Training via 1-Bit LAMB**: A massive deep neural network is trained to predict optimal holographic fringes from 3D inputs. The network leverages the 1-bit LAMB optimizer. Momentum states are quantized to 1-bit precision for high-throughput inter-node communication over Ethernet or InfiniBand, while local and global error compensation ensures zero degradation in the convergence toward high-quality fringe mappings.
2. **Data Structure and p-Adic Addressing**: The output of the network is formulated as a high-resolution tiled TIFF file. The spatial coordinates of the 3D scene and the corresponding 2D TIFF tiles are mapped using p-adic integer representations and the van der Put basis. This ultrametric mapping natively reflects the scaling and nesting of the spatial hierarchy, enabling O(1) coordinate resolution and memory fetches.
3. **Runtime Synthesis via RAM Sampling**: When a dynamic scene update is required, the system bypasses continuous Fourier transforms. Instead, it queries the p-adic quadtree to fetch precomputed elemental wavefronts stored in LUTs in the VRAM. This RAM sampling reconstructs the complex field at the Wavefront Recording Plane via simple, hardware-accelerated linear accumulation.
4. **Binarization via DBS-LUT**: The accumulated continuous field must be mapped to the 1-bit physical device. An accelerated Direct Binary Search algorithm evaluates pixel flips. Because the spatial domain is partitioned into TIFF tiles, the DBS process is independently parallelized across tiles. The error evaluation utilizes the same LUTs from the RAM sampling phase, ensuring ultra-fast convergence to an optimal 1-bit representation.
5. **Physical Display via DMA**: The resulting 1-bit tiled TIFF arrays are pushed via uncompressed Direct Memory Access (DMA) to the frame buffer of the DMD. The 22 kHz operating frequency of the DMD temporally multiplexes these binary tiles, extinguishing speckle noise, suppressing diffraction artifacts, and projecting a continuous-tone, highly efficient volumetric image.

This convergence establishes a profound symmetry of dimensionality and bit-depth across the entire technological stack. The 1-bit network gradients communicating across distributed computing nodes perfectly mirror the 1-bit pixels switching on the physical DMD mirror array. The continuous spatial physics of light are aggressively discretized—both geometrically (via p-adic hierarchical trees) and bit-wise (via 1-bit gradient compression and 1-bit binary holograms)—yet the system leverages statistical error compensation and high-frequency temporal integration to flawlessly simulate a continuous analog reality.

6. Conclusion

The real-time processing and display of complex, dynamic holography necessitate moving decidedly beyond traditional continuous Cartesian grids and computationally heavy 32-bit floating-point arithmetics. By adopting the 1-bit LAMB optimizer, massive machine learning models can be trained with unprecedented communication efficiency to predict complex optical fields. By structuring these fields as tiled TIFFs addressed via p-adic ultrametric geometry, memory bottlenecks are mitigated through hierarchical RAM sampling and LUT retrieval. Finally, employing look-up-table-accelerated Direct Binary Search or Lee holography enables the ultra-fast projection of these fields onto high-bandwidth 1-bit Digital Micromirror Devices, while 1-bit accumulator error compensation ensures high physical fidelity.

This synthesis proves that the enduring constraints of computational holography—specifically network bandwidth, ALU compute load, and spatial modulator limitations—are optimally addressed when algorithms, data structures, and physical hardware are unified under a common philosophy of discrete, hierarchical, and error-compensated 1-bit processing. The integration of non-Archimedean numerical theory and deep learning optimization described herein offers a definitive and mathematically rigorous blueprint for the next generation of super-efficient volumetric rendering technologies.

Works cited

1. Computer-Generated Holography as a Generic Display Technology, https://www.macs.hw.ac.uk/~ruth/year4VEs/Resources/Holography.pdf 2. Hardware Implementations of Computer Generated Holography, https://www.repository.cam.ac.uk/bitstreams/3ae28f24-cf06-46bb-b024-15f41f06e85c/download 3. SLAMB: Accelerated Large Batch Training with Sparse, https://proceedings.mlr.press/v202/xu23v/xu23v.pdf 4. 1-bit LAMB: Communication Efficient Large-Scale Large-Batch, https://arxiv.org/html/2104.06069v2 5. [PDF] 1-bit LAMB: Communication Efficient Large-Scale Large-Batch, https://www.semanticscholar.org/paper/1-bit-LAMB%3A-Communication-Efficient-Large-Scale-Li-Awan/5d21acef02a2035d0c5e3b8f70d4d3c9a164855f 6. MAXIMIZING COMMUNICATION EFFICIENCY FOR LARGE-SCALE, https://openreview.net/pdf?id=-CefY2EOupj 7. STEP: Learning N:M Structured Sparsity Masks from Scratch with, https://openreview.net/pdf?id=0O7b2Y198V 8. 1-bit LAMB: Communication Efficient Large-Scale ... - DeepSpeed, https://www.deepspeed.ai/tutorials/onebit-lamb/ 9. DeepSpeed: Accelerating large-scale model inference and training, https://www.microsoft.com/en-us/research/blog/deepspeed-accelerating-large-scale-model-inference-and-training-via-system-optimizations-and-compression/ 10. v-PuNNs: van der Put Neural Networks for Transparent Ultrametric, https://arxiv.org/pdf/2508.01010? 11. All Resources | Wolfram Function Repository, https://resources.wolframcloud.com/FunctionRepository/all 12. Massively Parallel Algorithms for High-Dimensional Euclidean, https://arxiv.org/pdf/2308.00503 13. p-adic Bochner–Riesz operators and their functional dynamics, https://www.sciopen.com/local/article_pdf/10.3934/math.2026748.pdf 14. p-Adic Mathematical Physics - arXiv, https://arxiv.org/pdf/1705.04758 15. What are p-Adic Numbers? What are They Used for?, https://www.asiapacific-mathnews.com/03/0304/0001_0006.pdf 16. arXiv:math-ph/0012019v3 23 Feb 2001, https://arxiv.org/pdf/math-ph/0012019 17. Computations with p-adic numbers - arXiv, https://arxiv.org/pdf/1701.06794 18. Ergodic Theory of p-adic

Transformations - Carolina Digital Repository, https://cdr.lib.unc.edu/downloads/7m01bk766 19. You could have invented Fenwick trees | Journal of Functional, https://www.cambridge.org/core/journals/journal-of-functional-programming/article/you-could-have-invented-fenwick-trees/B4628279D4E54229CED97249E96F721D 20. Topological analysis of 3D building models using a spatial query, https://www.researchgate.net/publication/223798537_Topological_analysis_of_3D_building_models_using_a_spatial_query_language 21. p-Adic AdS/CFT - Princeton University, https://collaborate.princeton.edu/en/publications/p-adic-adscft/ 22. p-adic AdS/CFT correspondence in nLab, https://ncatlab.org/nlab/show/p-adic+AdS%2FCFT+correspondence 23. Bruhat-Tits tree in nLab, https://ncatlab.org/nlab/show/Bruhat-Tits+tree 24. Geometry, Topology and p-Adic Numbers in Geospatial Data, https://publikationen.bibliothek.kit.edu/1000175338/155154247 25. TESSERAL ADDRESSING - Computer Science, https://intranet.csc.liv.ac.uk/~frans/OldResearch/dGKBIS/tesseral.html 26. The p-adic Z-transform - Semantic Scholar, https://pdfs.semanticscholar.org/f393/2a38c1fdb2460d536017dd4aae7064378253.pdf 27. In Need of a Specialist in Non-Archimedean Functional Analysis, https://www.reddit.com/r/math/comments/rdl4km/in_need_of_a_specialist_in_nonarchimedean/ 28. arXiv:2407.05561v1 [math.PR] 8 Jul 2024, https://arxiv.org/pdf/2407.05561 29. Top 42 papers published in the topic of Haar wavelet in 2002, https://scispace.com/topics/haar-wavelet-rv562vfc/2002 30. Computer generated hologram from point cloud using graphics, https://opg.optica.org/abstract.cfm?uri=ao-48-36-6841 31. The state-of-the-art in computer generated holography for 3D display, https://www.light-am.com/article/doi/10.37188/lam.2022.035 32. [PDF] Binary mask programmable hologram. - Semantic Scholar, https://www.semanticscholar.org/paper/Binary-mask-programmable-hologram.-Tsang-Poon/a231578c291a11ec08cfa5d8f76baf7ad39212ff 33. Computer-Generated Hologram Based on Reference Light ... - MDPI, https://www.mdpi.com/2076-3417/11/16/7199 34. Interactive Computation of Holograms Using a Look-up Table, http://www.lucente.us/past/pubs/jei92.html 35. One-eighth look-up table method for effectively generating computer, https://scholar.korea.ac.kr/item/3bd34518-5611-4282-9ccf-0f3c8a1879a1 36. TCIA Publications - The Cancer Imaging Archive, https://cancerimagingarchive.net/Publications.html 37. A dual interpretation for direct binary search and its implications for, https://www.researchgate.net/publication/5589093_A_dual_interpretation_for_direct_binary_search_and_its_implications_for_tone_reproduction_and_texture_quality 38. Optimization of DMD-based independent amplitude and phase, https://www.researchgate.net/publication/344469124_Optimization_of_DMD-based_independent_amplitude_and_phase_modulation_a_spatial_resolution_and_quantization 39. Thermal stability of wavefront shaping using a DMD as a spatial light, https://opg.optica.org/abstract.cfm?uri=oe-29-25-41808 40. Direct binary search method for high-resolution holographic image, https://opg.optica.org/abstract.cfm?uri=oe-30-15-26856 41. Accelerating Photonic Integrated Circuit Design: Traditional, ML and, https://arxiv.org/html/2506.18435v2 42. Binary Computer-Generated Holograms by Simulated-Annealing, https://www.mdpi.com/2304-6732/9/8/581 43. Efficient design of direct-binary-search computer-generated holograms, https://opg.optica.org/abstract.cfm?uri=josaa-8-4-652 44. Reverse design of pixel-type terahertz band-pass filters, https://opg.optica.org/abstract.cfm?uri=oe-30-2-957 45. Holographic tomographic volumetric additive manufacturing - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC11814129/ 46. Dynamic holography using pixelated

light modulators, https://opg.optica.org/abstract.cfm?uri=ao-49-25-f47 47. Synthesis of digital holograms by direct binary search, https://opg.optica.org/fulltext.cfm?uri=ao-26-14-2788 48. Time-multiplexed structured illumination using a DMD for optical, https://arxiv.org/pdf/1612.00044 49. Breaking the DSP Wall: A Software–Hardware Co-Designed ... - MDPI, https://www.mdpi.com/2079-9292/15/8/1586 50. DeepD3, an open framework for automated quantification of, https://journals.plos.org/ploscompbiol/article?id=10.1371/journal.pcbi.1011774 51. Docuwide 6030/6050: User Guide (Printer) | PDF - Scribd, https://www.scribd.com/document/582887492/Printer 52. binary image file: Topics by Science.gov, https://www.science.gov/topicpages/b/binary+image+file 53. Copyright Undertaking - PolyU Electronic Theses, https://theses.lib.polyu.edu.hk/bitstream/200/12127/3/6591.pdf