Processable Holographic Computation: Simulating Geometric Diffusion through MHz-Rate Optical Field RAM-Sampling and Dynamic Pixel Relocation

The paradigm of optical computing has historically been constrained by a persistent dichotomy between passive data storage—such as high-density holographic memory—and active, yet structurally rigid, matrix-vector multiplication architectures. A groundbreaking evolution in this domain is the emergence of the "processable hologram." This framework redefines the optical field not merely as a repository of static volumetric data, but as an active, massively parallel, and continuously evolving computational medium. This architectural leap represents a fundamental departure from classical von Neumann computational constraints, instead utilizing the physical properties of wave optics to compute solutions through the physical simulation of continuous geometric diffusion.

The fundamental ethos of the processable hologram relies on abandoning the sequential, pipeline-driven processing characteristic of traditional digital logic. Instead, the system is designed to project all computational possibilities and all information-bearing pixels simultaneously. By representing the entire computational field in a single coherent state, the system evaluates all localized interactions in parallel through free-space diffraction and optical interference. Operating at an optimal Megahertz (MHz) refresh rate, this optical state space evolves rapidly. The computational loop is actively closed by RAM-sampling the resulting optical field and feeding the digitized optical state into a low-latency C# software harness. During this RAM-sampling phase, the software harness analyzes the optical readout, identifies specific information-bearing pixels, and dynamically relocates them across the spatial light modulator (SLM) array. This relocation ensures that the pixels project their phase and amplitude information from a different physical origin point, effectively mapping them to a different location within the simulated numerical space or topological shape that the hologram represents. The subsequent re-projection and re-sampling of these altered fields allow the system to simulate highly complex phenomena. Principally, this iterative relocation and projection cycle represents computation via geometric diffusion, where the relocation of information naturally follows the gradients of differential equations operating on arbitrary, evolving manifolds.

This report provides an exhaustive, multi-disciplinary analysis of the theoretical physics, mathematical models, optoelectronic hardware, and software engineering mechanisms that govern the five-stage processable holographic compute cycle.

1. The Ethos of Parallel State Representation

The initial stage of the processable holographic cycle demands the simultaneous representation of the complete computational field. In classical digital systems, variables are

processed through discrete logic gates in a serialized pipeline, meaning that large state spaces must be explored iteratively or through highly energy-intensive cluster parallelism. In contrast, the processable hologram projects the complete field—comprising both the established data points (information-bearing pixels) and the untraversed solution space (encoded possibilities)—as a single complex amplitude distribution.

1.1 Volumetric Encoding and the Superposition of Possibilities

In volume holography, information is exclusively encoded within the spatial structure of optical fields[1]. While traditional volume holography focuses on ultra-high-density archival storage—approaching theoretical limits of petabits per cubic centimeter by multiplexing volume holograms with two-photon spectral hole-burning in specialized crystals[1]—the processable hologram utilizes this massive density for active, simultaneous computation.

When a coherent light source illuminates a highly multiplexed Spatial Light Modulator (SLM), the resulting optical wavefront acts as a physical superposition of all possible computational states. Every pixel acts as an independent neuron or computational node, transmitting continuous-variable information via its phase and amplitude. As the light propagates through free space, these nodes interact with one another at the speed of light. The interference pattern generated at the focal plane or sampling plane represents a global evaluation of all localized interactions simultaneously.

By representing the entire field together, the system projects every "possibility" as a distinct spatial frequency or phase modulation. The computation relies on how these possibilities constructively or destructively interfere, effectively executing a physical Fourier transform or a diffractive neural network forward pass in zero elapsed time, limited exclusively by the picosecond-scale time-of-flight of the photons[2]. The encoding of these possibilities relies on the precise calibration of the SLM, ensuring that the phase retardation introduced at each pixel accurately maps to the desired initial conditions of the simulated numerical space.

1.2 Hardware Constraints: The Necessity of MHz-Rate Modulation

To evolve this field dynamically, the system requires a mechanism to alter the spatial distribution of light at rates that can outpace or match high-speed electronic feedback loops. Conventional liquid-crystal-on-silicon (LCoS) SLMs suffer from intrinsically slow modulation mechanisms. Due to the physical relaxation times of nematic liquid crystal molecules and the limitations of electrical addressing circuits, traditional LCoS devices are typically capped at refresh rates between 60 Hz and a few kilohertz[3]. While Digital Micromirror Devices (DMDs) based on microelectromechanical systems (MEMS) offer faster mechanical actuation in the tens of kilohertz, they are generally limited to binary amplitude or binary phase modulation, which is insufficient for the continuous-variable mathematics required in geometric diffusion[3].

To achieve the optimal MHz operating rate required for continuous geometric diffusion simulation, the processable hologram must utilize advanced electro-optic materials governed by the Pockels effect. Materials such as barium titanate ($\mathrm{BaTiO_3}$ or BTO) exhibit massive electro-optic coefficients (e.g., $r_{42} = 923\ \mathrm{pm/V}$) and feature ultrafast response times in the sub-picosecond range[6].

When BTO is embedded within a two-dimensional array of vertically oriented, one-sided microcavities (acting as Fabry-Perot resonators formed by Distributed Bragg Reflectors), an applied electric field shifts the refractive index of the BTO via the linear Pockels effect. This index shift detunes the resonant frequency of the microcavity, yielding a complete 0 to 2π phase shift in the reflected wavefront under CMOS-compatible voltages (typically less than 10V)[6].

Because the Pockels effect relies on the displacement of electron clouds rather than the physical reorientation of molecules, these BTO-based phase-only SLMs can be driven at frequencies extending from the MHz regime up to 65 GHz[6]. In the context of the processable hologram, operating at an "optimal MHz rate" is a critical architectural choice. While the optical hardware can push into the multi-GHz regime, the MHz rate represents the optimal harmonization point between the physical evolution of the SLM and the electronic RAM-sampling latency required for the C# software harness to perform logical pixel relocations without dropping frames or inducing system desynchronization.

SLM Technology	Primary Modulation Mechanism	Typical Refresh Rate Limit	Suitability for Processable Holography
Nematic LCoS	Liquid crystal molecular rotation	60 Hz - 1 kHz	Low. Phase transition is too slow for real-time iterative diffusion loops[3].
Digital Micromirror (DMD)	Mechanical tilting of micro-mirrors	20 kHz - 50 kHz	Moderate. Fast, but fundamentally limited to binary amplitude/phase modulation[3].
BTO Microcavity (Electro-Optic)	Pockels effect (refractive index shift)	10 MHz - 65 GHz	High. Supports continuous MHz evolution with full 0 to 2π continuous phase modulation[6].
Phase-Change Materials (PCM)	Reversible crystalline/amorphous shifts	~1 GHz	High. Non-volatile nature reduces static energy

			consumption significantly[2].

2. Evolving the Field via Free-Space Optical Operators

Once the complete field is represented on the MHz-capable SLM, the second phase of the compute cycle involves the evolution of that field. This evolution is not computed algorithmically by a processor; rather, it occurs physically as the optical wavefront propagates through free space. The physics of optical diffraction act as the core computational engine, processing the highly parallel encoded possibilities.

2.1 The Mathematics of the Angular Spectrum Method

To accurately utilize free-space propagation as a computational operator, the physical transition of the wave must be modeled precisely. The most robust physical optics framework for this is the Angular Spectrum Method (ASM), which yields an exact solution to the homogeneous Helmholtz equation without relying on paraxial approximations (such as those found in Fresnel or Fraunhofer diffraction models)[7].

In the ASM framework, the complex optical field at the source plane (the SLM), denoted as $U(x, y, 0)$, is decomposed into a superposition of infinite plane waves via a two-dimensional Fourier transform:

$$A(k_x, k_y; 0) = \iint U(x, y, 0) e^{-i(k_x x + k_y y)} \, dx dy$$

where k_x and k_y represent the spatial frequencies corresponding to the directional cosines of the propagating waves[8].

Each decomposed plane wave is then propagated over a physical distance z by applying a phase shift $e^{ik_z z}$, where the axial wave number is given by $k_z = \sqrt{k^2 - k_x^2 - k_y^2}$ and $k = \frac{2\pi}{\lambda}$ [8]. The evolved computational field at the sampling plane is subsequently recovered via an inverse Fourier transform:

$$U(x, y, z) = \iint A(k_x, k_y; 0) e^{ik_z z} e^{i(k_x x + k_y y)} \, dk_x dk_y$$

For the processable hologram, the ASM precisely dictates how the encoded possibilities

interfere to form a cohesive data structure at the destination plane. However, simulating arbitrary numerical shapes and spaces often requires shifting the optical data off-axis or modeling thick computational elements. Standard ASM suffers from strict Nyquist sampling limitations when the propagation angles become steep or when the destination plane is laterally shifted[7].

To counter this, advanced numerical propagators such as the Shifted Angular Spectrum Method (Shift-BEASM) or the Geometry-Aware Phase-Compensated ASM (GAPC-ASM) are mathematically simulated in the hardware alignment[9]. By utilizing shifted band-extended algorithms, the system can compute free-space diffraction between two parallel planes with an off-axis offset, effectively extending the bandwidth using a nonuniform fast Fourier transform[9]. This physical propagation computes the continuous interaction of all pixels, evaluating the global state of the simulated numerical space in the time it takes light to traverse the physical cavity.

2.2 Optical Diffractive Neural Networks and Time-Lens Implementations

The physical evolution of the field closely mirrors the architecture of Recurrent Diffractive Deep Neural Networks (RD2NNs) and time-lens optical neural networks (TL-ONNs)[11]. In an RD2NN, the spatially modulated signals are treated recursively in a loop, utilizing beam splitters to feed a portion of the evolved output back into the input SLM[11]. The processable hologram expands upon this by utilizing the MHz refresh rate of the SLM to multiplex the images in the time/frequency domain[11].

Similarly, time-lens algorithms employ second-order phase modulations in the time domain, transmitted through dispersive optical fibers, where temporal points act as neurons[12]. The processable hologram combines spatial diffraction and temporal multiplexing, allowing the field to evolve at the chosen numerical operating rate. The physical diffraction calculates the forward pass, effectively functioning as an ultra-high-speed analog processor where the matrix multiplications are performed at the speed of light, avoiding the severe latency typical of digital electronic MAC (Multiply-Accumulate) operations[13].

3. RAM-Sampling the Resident Field

The processable hologram is fundamentally distinct from a static optical projector because its output is continuously monitored, digitized, and reintegrated into the compute cycle. This third step is achieved through high-speed RAM-sampling, wherein the optically evolved field is captured, digitized, and held in an electronic memory buffer to aid the performance of subsequent computations.

3.1 Photonic Detection and Conversion Constraints

To read information and identify which pixels require relocation, the continuous-wave optical field must be discretized by high-speed photodetector arrays coupled with Analog-to-Digital Converters (ADCs). In high-bandwidth photonic computing, the readout latency represents the primary bottleneck. The lowest achievable electronic latency is realized via Flash ADCs, which feature an estimated delay of approximately 80 picoseconds for their dynamic comparators

and 30 picoseconds for their encoding gates[13].
This physical limitation bounds strictly latency-dependent photonic feedback networks to operating speeds of approximately 10 Giga-Samples per second (GS/s)[13]. However, because the processable hologram operates optimally in the MHz regime to sync with the software harness, the ADCs are operating well within their maximum theoretical bandwidth. High-speed photodetectors capable of 32 Gb/s and ADCs capable of 32 GSPS are commercially mature technologies, ensuring that the inversion rate and sampling rate of the optical field are not limiting factors[14].
To sample at the target MHz regime effectively without dropping data, the optical field is focused onto the sensor arrays. Experimental photonic RAM architectures, which leverage phase-change materials (PCM) like GST alloys or ultra-low power nanocavities, allow for integrated optical buffers where the read speed is dictated merely by the photon's time-of-flight[2]. Nevertheless, to interact with the computational logic of the C# harness, this photonic data must cross into the electronic domain.

3.2 Bypassing CPU Overhead with PCIe and DMA

The RAM-sampling process converts the optical interference pattern—which represents the physically solved state of the current geometrical diffusion step—into an electronic numerical matrix. For the system to maintain its MHz operating rate, it cannot rely on traditional CPU-mediated data transfers. Standard interrupt-driven I/O protocols introduce substantial latency and jitter, which would instantly desynchronize the SLM projection from the software state.
Instead, the hardware utilizes Direct Memory Access (DMA) over a high-bandwidth Peripheral Component Interconnect Express (PCIe) bus. A PCIe frame grabber or custom optical readout board equipped with a DMA controller handles the data transfer from the ADC directly into the system's physical RAM[16]. The DMA controller bypasses the Central Processing Unit entirely, executing zero-copy memory writes into pre-allocated memory buffers[18].
This architecture guarantees that the resident field is sampled and digitized with deterministic, microsecond-level latency. The resulting data structure in the RAM provides the C# software harness with a real-time, high-fidelity snapshot of the encoded possibilities and their interference patterns, ready for algorithmic evaluation.

4. Pixel Relocation via the C# Harness

With the optical field successfully RAM-sampled, the computation transitions from the continuous physical domain into the discrete software domain. The core objective of the C# harness in step four is to read the sampled information, evaluate it against the target computational state, and determine which specific pixels require relocation. The harness then alters the SLM coordinates of these pixels so they project their information from a different spatial location in the subsequent cycle.

4.1 Unmanaged Memory and Real-Time C# Constraints

C# is traditionally a managed, object-oriented language utilizing an automatic Garbage Collector (GC) to handle memory allocation and deallocation[16]. In high-performance, real-time control systems—such as an optical feedback loop operating at MHz rates—standard C#

memory management is theoretically catastrophic. The GC introduces non-deterministic pauses (often lasting several milliseconds) that would severely stall the computational pipeline, causing the SLM to idle or project stale frames.

To circumvent the limitations of the managed environment, the software harness relies heavily on the unsafe code context within C# and utilizes Platform Invocation Services (P/Invoke). When the DMA controller writes the optical matrix into physical RAM, it deposits the data into pinned, unmanaged memory buffers[16]. By operating in an unsafe block, the C# application can utilize raw C-style pointers to directly access these memory addresses[22].

This approach completely bypasses the .NET Garbage Collector, allowing the harness to iterate over the massive pixel arrays in real-time. Modern SDKs designed for spatial light modulators, such as those integrated via the Bonsai API or specialized PCIe controllers, natively support these low-level memory operations, achieving processing times of less than 10 milliseconds even for complex per-pixel exposure control[23].

4.2 The Logic of Spatial Relocation

The act of identifying which pixels to move around is the logical crucible of the processable hologram. In this paradigm, the pixels are not static image elements; they are active vectors of information carrying amplitude, phase, and physical coordinates.

When the C# harness reads the unmanaged DMA buffer, it evaluates the local intensities and phase gradients of the sampled optical field. An algorithmic filter—such as a gradient descent solver or a topological clustering algorithm—identifies pixels that represent converged computational solutions, or conversely, those trapped in sub-optimal local minima.

Once identified, the C# harness calculates new x, y coordinates for these pixels based on the topological rules of whatever space or shape the hologram is simulating numerically. By issuing commands to the SLM SDK, the harness physically alters the origin point of that specific plane wave on the BTO microcavity array.

This relocation fundamentally alters how that pixel's information will diffract and interfere in the next cycle. By moving a pixel to a new location on the SLM, its angular spectrum contribution is shifted[9]. If the hologram is simulating a specific numerical shape—such as a fluid dynamic containment field, an encrypted manifold, or a high-dimensional neural network parameter space—relocating the pixels effectively molds the boundaries and interior metrics of that shape[9].

A vital third-order insight reveals that this C# relocation acts as a mechanism for *non-local topological interaction*. While physical wave propagation is strictly local and bound by continuous free-space metrics, the software harness can instantaneously "teleport" a pixel from one side of the simulated numerical space to the other. This allows the computational system to bridge disjointed manifolds, escape thermodynamic equilibrium states rapidly, and inject macroscopic boundary changes that would be impossible in strictly continuous physical systems.

5. Computation via Geometric Diffusion

The culminating step of the cycle requires sampling the changed field again, allowing those relocations to influence subsequent computations. As explicitly established, this iterative loop

of projecting, evolving, sampling, and relocating represents computation via geometric diffusion. To rigorously unpack this, we must examine the mathematics of differential geometry and how dynamic pixel relocation serves as an exact numerical analog for geometric partial differential equations (PDEs).

5.1 The Laplace-Beltrami Operator and Heat Kernels

In both physics and computational mathematics, diffusion is defined as a process that equilibrates spatial variations in concentration, intensity, or information[26]. In a flat Euclidean space, isotropic diffusion is governed by the standard heat equation $\frac{\partial u}{\partial t} = \Delta u$. However, when computation requires optimizing over complex, non-Euclidean data structures (such as a simulated 3D numerical shape or a curved topological manifold), the diffusion must be geometric.

On a smooth surface or manifold $\mathcal{M}$, the equivalent of the Euclidean Laplacian is the Laplace-Beltrami operator, $\Delta_{\mathcal{M}}$ [26]. Geometric diffusion is formally described by the nonlinear parabolic PDE:

$$\frac{\partial u}{\partial t} = \Delta_{\mathcal{M}} u$$

where $u(x,t)$ is the information density (or pixel intensity) at point x and time t[27].

The solution to this diffusion equation is governed by the heat kernel, $K_t(x,y)$, which represents the amount of information (or heat) transferred from point x to point y over time t[27]. On a spherical manifold S^n, for example, the heat kernel can be explicitly characterized using spherical harmonics and Gegenbauer polynomials:

$$p_t(x,y) = \sum_{\ell=0}^{\infty} e^{-D\ell(\ell+n-1)t} \, \frac{2\ell+n-1}{n-1} \frac{1}{A_{S^n}} C_\ell^{(n-1)/2}\left(\langle x,y\rangle\right)$$

where D is the diffusion constant and C_ℓ represents the Gegenbauer polynomial[28].

In the processable hologram, the free-space diffraction of light inherently and physically mimics this diffusion process. As light propagates, the Angular Spectrum spreads the spatial frequencies, acting as a physical smoothing operator perfectly analogous to the application of a heat kernel or a Gaussian filter on a Riemannian manifold[26]. The optical step physically

computes the forward pass of the Laplace-Beltrami operator instantly.

5.2 Pixel Relocation as Mean Curvature Flow

While the optical propagation calculates the raw diffusion of the field, the C# harness pixel relocation acts as the dynamic evolution of the manifold's geometry itself.

In advanced surface processing and computer graphics, geometric diffusion is intimately linked to Mean Curvature Motion (MCM) or curvature flow. From differential geometry, the mean curvature vector $\mathbf{HN}$ equals the Laplace-Beltrami operator applied to the surface identity coordinates $\mathbf{x}$:

$$\Delta_{\mathcal{M}}\mathbf{x} = -\mathbf{H}(\mathbf{x})\mathbf{N}(\mathbf{x})$$

where $\mathbf{H}$ is the mean curvature (the sum of principal curvatures) and $\mathbf{N}$ is the surface normal[26].

When the C# harness samples the optical field, it essentially evaluates the current curvature and gradient of the information concentration across the resident field. By deciding to relocate a pixel, the harness performs a discrete integration step of the geometric diffusion equation. It actively moves the data point along the gradient of the surface, simulating higher-order geometric flows such as the surface diffusion flow:

$$V_n = \Delta_{\mathcal{M}}\mathbf{H}$$

where the normal velocity V_n of the surface evolution is driven by the Laplacian of the mean curvature[31].

By altering the pixel's coordinate on the SLM, the software effectively alters the metric tensor g_{ij} and the resulting shape operator of the simulated numerical space[26]. The subsequent optical projection (Step 5) diffuses light according to this newly deformed manifold geometry.

5.3 Overcoming Geometry-Physics Confounding

A prominent failure mechanism when attempting to solve PDE dynamics across varying or evolving domains using standard neural operators is "geometry-physics confounding"[33]. When a PDE is expressed on a changing geometry, the geometric variations alter the governing differential operators. Isotropic physical diffusion on a curved surface can appear through spatially varying and anisotropic coefficients, making it highly difficult for a classical digital system to implicitly infer the physics from the geometry[33].

To solve a PDE like a reaction-diffusion equation $\partial_t u = \Delta_x u + r(u)$ on a changing

domain $\Omega_g(t)$, classical methods must define a complex mapping $\Phi_g(\xi, t)$ and pull back the fields to a reference domain using the geometric diffusion factor $\mathbf{K}_g = j_g \mathbf{J}_g^{-1} \mathbf{J}_g^{-T}$ [33]. The processable hologram gracefully bypasses this confounding. The geometry is intrinsically encoded in the spatial layout of the SLM pixels via the C# harness, and the physics (diffusion) is evaluated optically via actual wave mechanics (Helmholtz equation). The C# harness does not need to compute complex Jacobian matrix transformations ($\mathbf{J}_g$) to pull back the physics to a reference domain. Instead, by merely relocating the pixels, the harness dynamically reconfigures the physical geometry. The optical physics naturally computes the updated PDE state over the new geometry at the speed of light, ensuring precise, unconfounded calculation of the geometric diffusion.

Processing Stage	Domain	Hardware / Software	Primary Mechanism	Mathematical Equivalent
1. Representation	Optical	BTO SLM	Pockels Effect	Initialization of $u(x, 0)$ on manifold $\mathcal{M}$ [cite: 6, 27]
2. Evolution	Optical	Free Space	Wave Diffraction (ASM)	Heat Kernel application $K_t(x, y)$ [cite: 7, 8]
3. RAM-Sampling	Electronic	Photodiode, ADC, PCIe	Direct Memory Access (DMA)	Digitization of field $u(x, t +$ [cite: 13, 18]
4. Relocation	Software	C# unsafe API	Pixel coordinate shifting	Mean Curvature Flow mapping $\Delta_{\mathcal{M}} \mathbf{x}$ [cite: 22, 26]
5. Re-Sampling	Hybrid	SLM to Detector	Feedback Loop	Iterative PDE time-stepping[3]

				1

6. Systemic Implications and Broader Applications

The integration of the five-step processable hologram cycle establishes a computational architecture that transcends traditional bounds. By framing computation as a geometric diffusion problem solved via the physical manipulation of light, several groundbreaking applications and systemic implications emerge.

6.1 Optoelectronic Neuromorphic Accelerators

Current optical computing systems, such as diffractive optical neural networks, generally feature fixed diffractive layers or rely on slow LCoS updates, rendering time-multiplexed recurrent architectures difficult to scale and adapt in real-time[5]. By incorporating MHz-rate BTO SLMs and the C# DMA feedback loop, the processable hologram functions as an ultra-high-speed optoelectronic recurrent neural network. The pixel relocations can be used to dynamically re-route optical weights and biases. When a pixel is relocated, its diffraction pattern interacts with different neighboring pixels, effectively re-wiring the neural network's topology on the fly based on the sampled gradient of the loss landscape.

6.2 Bypassing the Von Neumann Bottleneck

In conventional high-performance computing, the Von Neumann bottleneck restricts theoretical performance limits due to the limited data throughput between the CPU and the system RAM. The processor spends excessive clock cycles waiting for data fetches. The processable hologram bypasses this by utilizing the free-space optical cavity as both the processor and the volatile memory. The massive parallel calculation (the diffusion) occurs photonically. The electronic DMA-to-C# harness is only invoked for topological updates (pixel relocation). This drastically reduces electronic power consumption while providing processing speeds capped only by the temporal resolution of the optical-to-electronic conversion components[5].

6.3 Advanced Surface Processing and Encryption

Because the system inherently calculates the Laplace-Beltrami operator, it is highly optimized for surface fairing, noise removal, and texture processing on 3D meshes[26]. Anisotropic geometric diffusion, which modifies the diffusion coefficient at geometric edges to preserve sharp features while smoothing planar regions, can be simulated effortlessly by programming the C# harness to restrict pixel relocation near high-intensity gradients[26].

Furthermore, random phase encoding in volume holographic storage is a unique technique for image encryption[36]. The dynamic relocation of pixels by the C# harness can serve as a continuously evolving cryptographic key. Because the interference pattern relies on the exact sub-wavelength position of millions of pixels, intercepting the RAM-sampled readout is useless without the real-time C# relocation algorithm that defines the topological geometry of the next cycle.

7. Conclusion

The processable hologram represents a sophisticated, multi-disciplinary synthesis of wave

optics, advanced materials science, high-speed electronic engineering, and differential geometry. By rejecting the static nature of classical holography, this paradigm embraces the optical field as an active, massively parallel compute space.

Through the continuous projection of all encoded possibilities and information-bearing pixels, the system harnesses the deterministic, speed-of-light propagation of waves—governed by the Angular Spectrum Method—to naturally execute complex geometric diffusion operations. The integration of MHz-rate electro-optic SLMs, driven by the Pockels effect in barium titanate microcavities, ensures that this optical evolution occurs at a pace relevant for real-time, iterative computation.

Crucially, it is the integration of the C# software harness via low-latency RAM-sampling and PCIe DMA that elevates this system from a simple optical calculator to a dynamic, topology-altering computational engine. By algorithmically identifying and relocating information-bearing pixels using unsafe unmanaged memory environments, the software actively molds the simulated numerical space. This relocation mimics the evolution of manifolds via Mean Curvature Flow and the Laplace-Beltrami operator, allowing the system to solve highly complex Partial Differential Equations on changing domains effortlessly, completely avoiding geometry-physics confounding.

In essence, the ethos of the processable hologram is the absolute unification of physical optics and digital topology. It utilizes the C# software harness to dynamically shape the geometry, and relies on the physical diffraction of light to compute the diffusion. This iterative, non-local feedback loop opens a promising and highly scalable frontier for optoelectronic computing, establishing a robust foundation for the next generation of predictive PDE modeling, neuromorphic processing, and complex topological simulation.

Works cited

1. (PDF) ULTRAHIGH DENSITY OPTICAL DATA STORAGE, https://www.researchgate.net/publication/237239014_ULTRAHIGH_DENSITY_OPTICAL_DATA_STORAGE
2. Prospects and applications of photonic neural networks, https://www.queensu.ca/physics/shastrilab/sites/shastwww/files/uploaded_files/publications/journals/69_Huang_APX_prospects_2022.pdf
3. What is a Spatial Light Modulator (SLM)? - GoPhotonics.com, https://www.gophotonics.com/community/what-is-a-spatial-light-modulator-slm
4. Thorlabs · Spatial Light Modulators, https://www.thorlabs.com/spatial-light-modulators
5. Free-space Optical Computing Systems, https://d-nb.info/1360967540/34
6. High-Speed Phase-Only Spatial Light Modulators with Two, https://ntt-research.com/wp-content/uploads/2022/08/High-Speed-Phase-Only-Spatial-Light-Modulators-with-Two-Dimensional-Tunable-Microcavity-Arrays.pdf
7. Scalable angular spectrum propagation - Optica Publishing Group, https://opg.optica.org/abstract.cfm?uri=optica-10-11-1407
8. 6.3: Angular Spectrum Method - Physics LibreTexts, https://phys.libretexts.org/Bookshelves/Optics/BSc_Optics_(Konijnenberg_Adam_

and_Urbach)/06%3A_Scalar_diffraction_optics/6.04%3A_Angular_Spectrum_Method
9. Shifted angular spectrum method for off-axis numerical propagation., https://www.semanticscholar.org/paper/Shifted-angular-spectrum-method-for-off-axis-Matsushima/69cd7f5613360b8c9c0a7b4cbb8a170d3aff2bee
10. Geometry-aware phase compensation for sampling-efficient angular, https://opg.optica.org/oe/fulltext.cfm?uri=oe-34-8-15244
11. Recurrent diffractive deep neural networks - Optica Publishing Group, https://opg.optica.org/oe/abstract.cfm?uri=oe-32-27-48093
12. Optical Machine Learning Using Time-Lens Deep Neural NetWorks, https://www.mdpi.com/2304-6732/8/3/78
13. Full article: Prospects and applications of photonic neural networks, https://www.tandfonline.com/doi/full/10.1080/23746149.2021.1981155
14. Iterative photonic processor for fast complex-valued matrix inversion, https://opg.optica.org/prj/upcoming_pdf.cfm?id=468097
15. Towards integrated magneto-photonic devices for all-optical reading, https://research.tue.nl/files/226578264/20221201_Demirer_hf.pdf
16. GitHub - openoct/OCTSharp: Open Source C# Software for OCT, https://github.com/OCTSharpImaging/OCTSharp
17. Coaxlink Octo - Allied Vision, https://www.alliedvision.com/en/products/frame-grabbers/coaxlink-octo
18. Understanding Frame Grabbers in Vision Systems - Active Silicon, https://www.activesilicon.com/wp-content/uploads/ActiveSilicon-White-Paper-Understanding-Frame-Grabbers-in-Vision-Systems.pdf
19. Interpol review of digital evidence for 2019–2022 - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC10311174/
20. Communications of the ACM - February 2020, https://redes.fi-b.unam.mx/fi_acm/2020/communications202002-dl.pdf
21. OCTSharp: an open-source and real-time OCT imaging software, https://www.researchgate.net/publication/374987580_OCTSharp_An_Open-Source_and_Real-time_OCT_Imaging_Software_Based_on_C
22. Applications Handbook - United Electronic Industries, https://www.ueidaq.com/uploads/applications-handbook-12-13.pdf
23. HSP1K: High-Speed Spatial Light Modulator - AVR Optics, https://www.avr-optics.com/catalog/spatial_light_modulators___scanning_systems/xy_slm/hsp1k
24. A closed-loop, all-electronic pixel-wise adaptive imaging system for, https://pmc.ncbi.nlm.nih.gov/articles/PMC9957502/
25. Spatial Light Modulator Software | Products | Santec AOC, https://aoc.santec.com/en/products/slm/software/
26. Anisotropic Geometric Diffusion in Surface Processing, https://www.cs.jhu.edu/~misha/ReadingSeminar/Papers/Clarenz00.pdf
27. Scale-Space Representation of Scalar Functions on 2D Manifolds, http://perception.inrialpes.fr/Publications/2011/ZBH11a/Spectral-Scalespace.pdf
28. A Parameterization-Based Numerical Method for Isotropic and,

https://pmc.ncbi.nlm.nih.gov/articles/PMC2773135/
29. Spectral geometry of shapes, https://ucsp.edu.pe/sibgrapi2013/eproceedings/tutorials/T4-handouts.pdf
30. Spherical Geometry Diffusion - Emergent Mind, https://www.emergentmind.com/topics/spherical-geometry-diffusion
31. Discrete Surface Modelling Using Partial Differential Equations - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC2760856/
32. A Parameterization-based Numerical Method for Isotropic and, https://sipi.usc.edu/~ajoshi/ajoshi_tip_09_paper.pdf
33. (PDF) Geometry-physics confounding impairs PDE learning across, https://www.researchgate.net/publication/415149922_Geometry-physics_confounding_impairs_PDE_learning_across_varying_domains
34. Geometry–physics confounding impairs PDE learning across ... - arXiv, https://arxiv.org/html/2609.38623v1
35. Direct electromagnetic information processing with planar diffractive, https://pmc.ncbi.nlm.nih.gov/articles/PMC11259158/
36. holographic surveillance system: Topics by Science.gov, https://www.science.gov/topicpages/h/holographic+surveillance+system
37. Michelson Interferometric Optical Complex Convolution ... - ProQuest, https://search.proquest.com/openview/25c93853de5c3e7532ed66e88f854680/1?pq-origsite=gscholar&cbl=18750&diss=y