The Bit and the Anti-Bit: Mimicking Cosmic Quantum States to Unlock Digital Holography

Introduction

The pursuit of fully realized digital holography represents one of the most formidable challenges in modern optical engineering, computational physics, and quantum information theory. For decades, the objective has been the seamless reconstruction of three-dimensional light fields that provide perfect depth cues—motion parallax, binocular disparity, and accommodation—indistinguishable from physical reality. However, classical computational paradigms have consistently encountered an insurmountable mathematical and thermodynamic bottleneck: the exponential scaling of computational complexity required to process and project wavefield propagation at the tera-pixel scale[1]. It has become increasingly evident that classical models of computation, constrained by standard serial processing and localized information theory, cannot support the data architectures required for next-generation volumetric displays.

To bypass this barrier, theoretical frameworks have begun looking toward the foundational structures of the universe itself. The universe, according to modern theoretical physics, may fundamentally operate as a holographic information structure[2]. Through the lens of the holographic principle, the Anti-de Sitter/Conformal Field Theory (AdS/CFT) correspondence, and advanced tensor networks, spacetime geometry and gravity are understood as emergent properties of lower-dimensional quantum entanglement[3]. Unlocking digital holography requires mimicking these exact cosmic quantum states. By transitioning from classical bits to quantum superpositions, and adopting novel theoretical constructs such as the bit and anti-bit model—a framework designed to probe non-local tomography and gravitationally induced entanglement—computational holography can undergo a fundamental paradigm shift[6].

The convergence of the bit/anti-bit algebraic framework, tensor network architectures, and biphoton interferometry provides the requisite blueprint for Quantum Computer-Generated Holography (QGH)[1]. This report provides an exhaustive technical analysis of how cosmic-like quantum states, non-local tomography, and entanglement structures must be harnessed to decode the bulk-boundary mechanisms of the universe and, subsequently, apply those exact principles to generate and manipulate tera-pixel digital holograms.

The Thermodynamic Limits of Classical Computation

To understand the necessity of mimicking cosmic quantum states, it is first required to establish the thermodynamic and informational boundaries of the classical bit. The concept of the bit, traditionally confined to binary logic, inherently possesses a physical and thermodynamic reality. Landauer's principle establishes the minimal thermodynamic cost associated with the processing of information, formally stating that the amount of heat Q produced when erasing a classical bit—setting a state with equal probabilities of being 0 or 1 strictly to 1 or 0—is strictly

bounded[8].

$$Q \geq kT \ln 2$$

Here, k is the Boltzmann constant and T is the temperature of the environment[8]. In highly optimized classical systems such as Static Random-Access Memory (SRAM), information is typically maintained using intersecting conductors known as the bit line and the anti-bit line[8]. In such architectures, the state of the memory cell is defined by the voltage differential between the bit line (V_1) and the anti-bit line (V_2). According to Kirchhoff's circuit law, analytical solutions for these systems demonstrate a stable state where $V_1 - V_2 > 0$ defines a logical 0, while $V_1 - V_2 < 0$ defines a logical 1[8].

However, as computational scales approach the atomic level required for tera-pixel holographic displays, thermal fluctuations increasingly dominate. The voltages V_1 and V_2 transition from deterministic values to probabilistic distributions $p(V_1, V_2)$ [8]. Finite-time operations in nanoscale classical systems result in excess heat production, necessitating finite-time generalizations of Landauer's principle:

$$Q \geq T \ln 2 + T\langle \mu \rangle_t$$

where t represents the duration of the protocol and $\langle \mu \rangle_t$ denotes the expected dynamic activity of the system[8]. Integrating entropy production ΔS over the duration of the erasure protocol reveals a stark physical limit: decreasing the erasure error ϵ inevitably leads to an exponential increase in total thermodynamic dissipation[8]. The thermodynamics of the classical bit and its physical counterpart, the anti-bit line, represent the absolute limits of classical computation.

Koomey's law, which states that the number of computations executable per joule of dissipated energy doubles approximately every 1.6 years, is rapidly approaching a hard physical wall due to these thermal constraints[8]. The energy requirements to compute a tera-pixel hologram classically would result in catastrophic energy consumption and heat dissipation due to this fundamental erasure cost[8]. Surmounting this limit requires abandoning the classical, localized binary architecture in favor of quantum systems where information is conserved unitarily rather than erased disruptively.

The Mathematical Formalism of the Anti-Bit and Quantum Message Spaces

In quantum mechanics, the concept of the "anti-bit" evolves from a mere physical wire in an SRAM circuit into a profound algebraic construct. Historically, the prefix "anti-" in physics traces back to the Dirac equation, which predicted the existence of antimatter by allowing for negative energy states—particles possessing the same mass but opposite charge and physical behaviors, such as the positron (anti-electron) spiraling in the opposite direction of an electron within an electromagnetic field[9]. In advanced quantum information theory, the "anti-bit" assumes a structural role, representing specific states, operational inverses, or constrained Hilbert space sectors that allow for the modeling of complex, non-classical interactions without the entropic penalties of classical bit erasure[10].

To circumvent Landauer's limit in the calculation of digital holograms, information must be processed within a Quantum Message Space (QMS). A quantum message space is defined as a Hilbert space $\mathcal{H}$ coupled with an orthonormal basis $(\delta_a)_{a \in FG(2)}$ indexed by the elements of the free group $FG(2)$ on two bits[10]. In this advanced algebraic topology, the values 0 and 1 are defined as bits that construct positive messages, whereas the values 2 and 3 operate as the anti-bit values[10]. The free group identity is represented by the empty string Λ [10].

Any quantum state ϱ in this message space functions as a message source, inducing a probability distribution with a weight determined by the trace[10]. When evaluating the entropy dynamics, if ϱ is a prior state before measurement, the probability that a received message equals a bit string a is given by $\langle \delta_a | \varrho(\delta_a) \rangle / \mathrm{Trace}(\varrho)$ [10]. Should a measurement occur and alter the state to $F(\varrho)$, the information lost by the system (or entropy gained) is quantifiable as $-\log_2 \mathrm{Trace}(F(\varrho))/\mathrm{Trace}(\varrho)$ [10].

The Destructive Read Memory Cell and Reversible Operations

To process holography unitarily, classical read/write mechanisms must be replaced by quantum operations that utilize these anti-bits. Consider a Destructive Read Memory Cell existing in state δ_b where $b \in \{0, 1\}$ [10]. Reading and restoring the stored bit without triggering a classical erasure penalty requires measuring the observable $\delta_\Lambda \otimes \delta_\Lambda^*$, which determines whether a message exists[10].

The state transitions are governed by unitary operators V_0, V_1, V_2, V_3, where V_z is the unique unitary operator mapping the state δ_x to $\delta_{x \cdot z}$ [10]. To write a value a to the cell, the system utilizes the anti-bit values to perform a reversible erasure. Applying the anti-bit operator

V_3 to δ_b yields $V_3(\delta_b)$, which returns the empty string δ_Λ if $b = 1$, but results in δ_{03} if $b = 0$ [10]. Subsequently applying combinations of anti-bit operators, such as $V_a \circ V_2 \circ V_1$, allows the system to shift bits in and out like a shift register, managing bit strings of arbitrary length while conserving the total number of bits[10].

By treating memory as a quantum message space populated by bits and algebraic anti-bits, computational systems can execute continuous, reversible unitary operations. This fundamentally eliminates the Landauer erasure limit that currently bottlenecks classical holographic processing units.

Cosmic Entanglement and the Bose-Marletto-Vedral Paradigm

To engineer computational systems capable of processing holographic scales of information, theorists study how the universe inherently processes information—specifically, how gravity mediates entanglement. A critical development in this domain is the Bose-Marletto-Vedral (BMV) experiment, which explores whether a locally classical mediator (such as a gravitational field) can entangle two distant quantum masses[6]. Proving this mathematically requires a framework that steps beyond standard quantum theory, giving rise to the bit and anti-bit model[6]. The bit and anti-bit model is a toy theory explicitly constructed to demonstrate how entanglement can be generated through local interactions with a gravitational mediator that is strictly classical (i.e., it does not exhibit observable spacetime superpositions)[6]. The model scrutinizes various constraints, including fermions obeying parity superselection rules and non-Abelian Ising anyons—particles frequently utilized in lattice gauge field theory and topological quantum computing[6].

In the bit/anti-bit formalism, systems are comprised of bits (B) and anti-bits (A), both associated with standard two-dimensional Hilbert spaces ($\mathcal{H}_A \simeq \mathbb{C}^2 \simeq \mathcal{H}_B$)[7]. However, the rules governing their interactions and pure states differ profoundly from classical composite systems. A system consisting exclusively of n bits, denoted as $(0, n)$, or exclusively of m anti-bits, denoted as $(m, 0)$, allows for no superpositions[7]. The pure states are strictly tensor products of computational basis states:

$$|\psi\rangle_S = |i_1\rangle \otimes \cdots \otimes |i_n\rangle \in \mathcal{H}_{B_1} \otimes \cdots \otimes \mathcal{H}_{B_n}$$

Because no superpositions are permitted in homogenous systems, they behave locally like purely classical bits[7]. The non-classicality emerges solely when bits and anti-bits are combined. In a mixed composite system of n bits and m anti-bits (m, n) where $n \geq m$, the

permissible pure states are expanded. They take the form:

$$\sum_i \lambda_i |i, \sigma, q\rangle \otimes |j_{m+1}\rangle \otimes \cdots \otimes |j_n\rangle$$

Here, $|j_{m+1}\rangle \otimes \cdots \otimes |j_n\rangle$ is an $(n-m)$ -bit classical basis state, and the composite basis state $|i, \sigma, q\rangle$ is defined by a permutation σ mapping the bits to the anti-bits[7].

Superpositions of states sharing the same matching permutation σ are strictly valid[7].

Non-Local Tomography and its Computational Implications

Because the allowed states of bit and anti-bit composites are strictly larger than those in a standard classical composition, the theory exhibits non-local tomography[6]. Local tomography is a foundational assumption in standard quantum mechanics, postulating that the global state of a composite system can be entirely deduced by performing correlated measurements on its local subsystems[6]. In non-locally tomographic theories, the global state contains topological information that is utterly invisible to any set of local measurements[6].

Feature	Standard Quantum Theory	Bit / Anti-Bit Model (BMV)	Computational Holography Implication
System Locality	Tomographically Local	Non-Locally Tomographic	Eliminates the need to compute independent, localized pixel data sequentially.
Superposition Constraints	Universal across all Hilbert spaces	Restricted to mixed (m, n) composite states	Allows for highly compressed point-cloud encoding without full quantum overhead.
Mediator State Dynamics	Requires quantum superposition to mediate entanglement	Can remain strictly classical (bits) while mediating entanglement	Enables classical intermediate hardware to handle quantum-generated

			holographic phase data.
Entanglement Generation	Mediated via quantum exchange operators	Mediated via permutation and classical swapping operations	Drastically reduces the computational complexity of tracking lightwave interactions.

To simulate the BMV experiment, a specific permutation of anti-bits and bits is constructed, for example, $(2, 4)$ arranged sequentially as $A_1B_1B_2B_3B_4A_2$ [7]. The first quantum system (Qubit 1) is encoded in the pair (A_1, B_1), the second quantum system (Qubit 2) in (B_4, A_2), and the classical gravitational mediator is represented by the purely classical bits (B_2, B_3) [7]. Through simple classical bit-swapping operations across the local classical bit sector, entanglement is mediated between the distant qubits. The mediator never enters a superposition and maintains a fully classical local description, proving that classical mediators can entangle quantum states[6].

This cosmic parallel has profound implications for digital holography. If the universe utilizes non-locally tomographic structures to generate emergent entanglement across spacetime without requiring the underlying medium to be in a globally superposed state, then computational holography must harness analogous non-local data structures. By abandoning strictly localized pixel-by-pixel wavefield calculations and adopting algorithms where the global holographic state is encoded in non-local permutations (analogous to the bit anti-bit composite states), the computational burden of tracking independent localized phases is eliminated.

The Holographic Principle and Spacetime as Computation

The necessity of utilizing quantum mechanics to calculate holograms is fundamentally validated by the universe's own architecture. The holographic principle is a property of string theories and a theoretical pillar of quantum gravity postulating that the full physical description of a volume of space (the bulk) can be entirely encoded on a lower-dimensional boundary surrounding that region[3].

This principle originates from black hole thermodynamics. Bekenstein and Hawking demonstrated that the maximum entropy (and thus the information capacity) of a black hole scales not with its three-dimensional volume, but with the two-dimensional surface area of its event horizon[3]. Therefore, the information content of all matter and energy that falls into a black hole is perfectly isomorphic to the thermal fluctuations inscribed on the boundary surface,

rendering the 3D interior theoretically illusory[3].
Attempts to generalize this entropy bound to broader spacetimes faced paradoxes, such as "Wheeler's bags of gold"—solutions in general relativity where an arbitrarily large volume is bounded by a small surface area, seemingly violating holographic capacity[3]. However, frameworks such as the Fischler-Susskind holographic bound and Raphael Bousso's covariant entropy bound, which is based upon null hypersurfaces, successfully extended the holographic mapping to general cosmological spacetimes[3]. Ultimately, these bounds confirm that holographic noise—the root-mean-square transverse holographic fluctuation amplitude at the Planck length—encodes the fundamental information limits of reality[3].
The most precise mathematical realization of this principle is the Anti-de Sitter/Conformal Field Theory (AdS/CFT) correspondence (Maldacena duality)[3]. It establishes an exact equivalence between a higher-dimensional quantum gravity theory formulated in negatively curved Anti-de Sitter (AdS) space (the bulk) and a Conformal Field Theory (CFT) residing strictly on the lower-dimensional boundary[3]. In this framework, the three-dimensional reality experienced as continuous spacetime is a holographic projection generated by quantum entanglement operating on a distant, two-dimensional boundary[2]. The entangled qubits on the boundary weave together the fabric of spacetime, creating an emergent geometry that obeys Einstein's general relativity[2].
If the 3D spacetime is the "screen," the higher-dimensional boundary is the "processor" executing the computations[2]. This cosmic duality implies that any ultimate volumetric holographic display must mathematically mirror AdS/CFT. It must map a heavily condensed, lower-dimensional dataset (the 2D Spatial Light Modulator) into a fully projected, interactive 3D bulk volume without information loss.

Tensor Networks: The Computational Scaffolding of Holography

To bridge the theoretical elegance of AdS/CFT with actionable computational algorithms, physicists rely on Tensor Networks. A tensor network is a systematic graphical and algebraic formulation used to efficiently represent complex quantum many-body wavefunctions in an exponentially large Hilbert space by breaking down the global state into a network of interconnected local tensors[4]. Tensor networks naturally obey entanglement area laws, making them the perfect framework for translating the boundary CFT into bulk holographic geometry[11].

Multiscale Entanglement Renormalization Ansatz (MERA)

The Multiscale Entanglement Renormalization Ansatz (MERA) is a hierarchical, layered tensor network designed to capture the properties of critical systems and conformal field theories[11]. MERA features a causal-cone structure composed of distinct elements:

- **Disentanglers:** Tensors that remove local entanglement between adjacent sites to simplify the state representation before scaling[12].
- **Isometries:** Coarse-graining tensors that map the disentangled state into a lower-dimensional effective Hilbert space, iterating this process across multiple scales[12].

The structure of MERA reproduces the hyperbolic geometry of an AdS time-slice. The extra

dimension introduced by the iterative layers of the MERA network is precisely identified as the emergent holographic radial direction in the AdS bulk[4].

Matrix Product States (MPS) and Statistical Mechanics

For one-dimensional quantum states, the corresponding tensor network is the Matrix Product State (MPS)[12]. The MPS decomposes a global quantum state into a chain of rank-three tensors, providing a highly compressed format for describing complex correlations.

The application of MPS to holographic modeling is deeply tied to statistical mechanics. In the double-scaled Sachdev-Ye-Kitaev (DSSYK) model—a prominent model for holographic duality and quantum chaos—the transfer matrix T is diagonalized using chord number states $|n\rangle$ and q-deformed oscillators[15]. Specifically, the creation and annihilation operators of chords dictate the moment of the transfer matrix[15]. Remarkably, the transfer matrix of DSSYK maps directly to the Markov matrix M of the Asymmetric Simple Exclusion Process (ASEP), a statistical mechanical model governing particle hopping on a 1D lattice[15].

The stationary state of ASEP is exactly formulated as an MPS of an open XXZ spin chain[15]. In this formulation, state configurations are defined by paths through the tensor network. When parameter $q = 0$, the state is represented as a sum over Dyck paths with unit coefficients, identically mirroring the ground state of the Fredkin spin chain[15]. By adding an extra height direction as a holographic coordinate, the MPS expands into a multi-layered holographic tensor network composed of 4-index tensors with finite bond dimensions[15].

By importing these exact tensor network frameworks into computational engineering, one can map the algorithms of MERA and MPS into field-programmable gate arrays (FPGAs) or quantum processors. A holographic display driven by tensor networks bypasses classical ray tracing; it constructs the 2D hologram by running the MERA tensor network in reverse, mathematically projecting the 3D point-cloud (the AdS bulk) onto the spatial light modulator (the boundary CFT)[16].

Classical Bottlenecks in Computer-Generated Holography (CGH)

To fully appreciate the necessity of adopting tensor networks and quantum models, one must quantify the failure of classical Computer-Generated Holography (CGH). The fundamental goal of CGH is to compute the interference fringe patterns generated by light waves emitted from a 3D object and store them on a two-dimensional Spatial Light Modulator (SLM)[1].

Pioneering efforts by Benton's group at the Massachusetts Institute of Technology developed acousto-optic modulator-based displays that produced horizontal parallax with large viewing angles, while contemporary systems utilize liquid crystal displays[1]. However, the primary metrics for a holographic display—the size of the reconstructed image and its viewing angle—are heavily bounded by the physical properties of the SLM, specifically the total number of pixels and the pixel pitch p (the physical distance between adjacent pixels). The maximum viewing

angle θ is dictated by the diffraction limit:

$$\theta = 2 \arcsin\left(\frac{\lambda}{2p}\right)$$

where λ is the wavelength of the illuminating light[1].

If an advanced 4K resolution SLM is utilized, possessing a pixel pitch of $p = 4\ \mu\text{m}$ and illuminated by a standard red laser ($\lambda = 633\ \text{nm}$), the resulting viewing angle is an incredibly narrow 9°, and the image size is confined to a microscopic $15.4 \times 8.6\ \text{mm}$ [1]. To achieve a practical, life-sized 3D holographic image—for instance, measuring $0.5\ \text{m} \times 0.5\ \text{m}$ with a 90° viewing angle at $\lambda = 633\ \text{nm}$—the SLM would require a pixel pitch of $0.5\ \mu\text{m}$ and a staggering total of over 1 tera-pixel ($10^6 \times 10^6$ pixels)[1].
Calculating the wavefield propagation for a 1 tera-pixel hologram from a 1 tera-point 3D object cloud using classical algorithms involves immense computational costs. Even with highly optimized acceleration algorithms—such as polygon-based, layer-based, light-field algorithms, or sparse matrix multiplication—classical GPUs and FPGAs cannot achieve video-rate generation at the tera-pixel scale[1]. The rendering process falls victim to the thermodynamic limits of the classical bit.

Quantum Computer-Generated Holography (QGH)

The solution to this computational apocalypse lies in Quantum Computer-Generated Holography (QGH). As proposed by Shimobaba and Ito, QGH fundamentally abandons serial classical processing in favor of quantum mechanical parallelism[1].
In the QGH paradigm, the traditional point-cloud algorithm is mapped onto a quantum computational framework[1]. The spatial coordinates and phase information of the 3D point-cloud data are encoded not as classical binary strings, but as superposition states of qubits[1]. Because the state space of a quantum computer grows exponentially as 2^n with the addition of n qubits, an immense amount of spatial data can be represented with a relatively small number of highly entangled qubits.
Once the point-cloud data is initialized as a global superposition state, the interactions of all lightwaves emitted from the point cloud onto the hologram plane are calculated simultaneously using the intrinsic principles of quantum mechanics[1]. Instead of computing discrete ray traces, the quantum processor applies a series of unitary transformations across the entire superposition state simultaneously.

The 10^6 Acceleration Factor

The impact of this quantum parallelism is mathematically profound. For the standard of calculating a 1 tera-pixel hologram from 1 tera-object points, analytical studies reveal that QGH accelerates the hologram computation by a factor of 10^6 (a one-million-fold acceleration) compared to classical computer-generated holography[1].

Computational Paradigm	Data Representation	Core Mathematical Operation	Scale Capacity	Relative Acceleration (Tera-pixel)
Classical CGH	Binary Arrays	Iterative Ray/Wave Tracing	Giga-pixel (Max)	1x (Baseline)
Quantum CGH (QGH)	Qubit Superpositions	Global Unitary Transformations	Tera-pixel and beyond	10^6 x

The implementation of QGH mirrors the underlying physics of cosmic quantum states. Just as the bit/anti-bit model demonstrated that non-locally tomographic permutations can entangle disparate components without tracking classical intermediaries[7], QGH leverages global entanglement to bypass the need to compute independent pixel values. Furthermore, the unitary transformations applied in the quantum circuit to generate the QGH interference pattern are mathematically isomorphic to the tensor network operations that map bulk object data to the boundary SLM.

Biphoton Digital Holography: Capturing Quantum Phase

While QGH focuses on calculating synthetic holograms utilizing quantum computation, the realization of fully unlocked digital holography also requires the ability to capture, measure, and image complex physical light fields utilizing quantum states. Classical quantitative phase imaging (QPI) relies on interferometric stability to measure the phase delay introduced by transparent objects, commonly used in label-free biological imaging[18]. However, classical imaging is fundamentally limited by the Rayleigh diffraction limit and standard shot noise. By employing entangled quantum states of light, specifically spatially entangled photon pairs, these limitations are surpassed[18].

Biphoton digital holography operates in analogy to off-axis digital holography, but shifts the paradigm into the quantum regime[19]. High-dimensional biphoton states, which possess unbounded degrees of freedom such as orbital angular momentum (OAM), time-bins, and

spatial radial modes, are utilized to encode massive amounts of phase and amplitude information[19].

The Mechanism of Biphoton Holography

The generation of highly correlated spatial photon pairs is typically achieved through Spontaneous Parametric Down-Conversion (SPDC)[19]. A high-frequency pump laser illuminates a 0.5-mm-thick type-I β -barium borate (BBO) nonlinear crystal[19]. Inside the crystal, single pump photons are probabilistically annihilated to create a pair of lower-frequency, highly entangled photons (signal and idler).

In biphoton digital holography, a spatial superposition of two distinct pump fields is created—an unknown state containing the structural information of an object, and a known reference state (typically an 810 nm classical comparison standard)[18]. As the superposed pump beam undergoes SPDC, the spatial characteristics and phases are directly transferred to the generated biphoton wavefunctions[19].

The mathematical representation of the coincidence count rate, which measures the simultaneous detection of an idler photon at coordinate X_1 and a signal photon at coordinate X_2 , is defined by the absolute square of the total biphoton wavefunction[19]:

$$\mathcal{C}(X_1, X_2) = |\psi_r(X_1, X_2) + \psi_u(X_1, X_2)|^2$$

where ψ_r represents the reference biphoton state and ψ_u represents the unknown state[19]. The expansion of this equation generates the cross-term $[\psi_r^* \psi_u + \psi_r \psi_u^*]$, which constitutes the quantum interference pattern[19].

To capture this pattern without laborious raster scanning, ultra-fast event-based time-tagging cameras, such as the TPX3CAM, are employed[18]. Operating across a 256×256 pixel matrix, these cameras detect the arrival time of individual photons with nanosecond resolution, allowing for the simultaneous extraction of spatial and temporal correlations[18]. By filtering these coincidence measurements and isolating the spatial correlations, the phase and amplitude of the unknown biphoton state are precisely reconstructed[19].

This reconstruction heavily utilizes the Transport of Intensity Equation (TIE), valid for paraxial propagation of fields with irrotational phase[18]. The TIE equates to a Poisson equation for the phase, taking the form:

$$\nabla_\perp^2 \phi$$

where ϕ is the unknown phase and $\nabla_{\perp}^{2}$ is the Laplacian in the transverse coordinates[18].

Accelerated State Tomography

Historically, characterizing the full quantum state of high-dimensional biphotons required exhaustive projective measurements, a process whose complexity scales quadratically with the dimensionality of the Hilbert space[19]. Biphoton digital holography revolutionizes this process. By parallelizing the measurements across the TPX3CAM array and utilizing interferometric phase reconstruction, the measurement time is reduced to mere seconds. This represents an acceleration of three orders of magnitude over previous methods, achieving highly reliable characterizations with an average fidelity of 87% across arbitrary spatial mode bases[19].
This optical achievement is the physical inverse of QGH. While QGH uses qubits to compute classical interference fringes for projection, biphoton digital holography uses quantum interference to compute and extract the state of a physical object.

Synthesizing Cosmic Models and Digital Architectures

The ultimate unlocking of digital holography rests upon recognizing that computational algorithms, optical engineering, and cosmological models are converging upon the exact same mathematical structures.

1. **The Architecture of Data:** Standard classical rendering treats space as a fundamentally localized grid of voxels, a method proven computationally and thermodynamically fatal for tera-pixel resolutions[1]. The bit/anti-bit model in the BMV experiment demonstrates that nature operates differently. Entanglement and structural information can be mediated by entirely non-locally tomographic systems without requiring localized superpositions of the mediator[6]. Holographic software must adopt this non-local approach, abandoning pixel-by-pixel tracking for global topological data structures utilizing quantum message spaces and algebraic anti-bits[7].
2. **The Mechanism of Translation:** The holographic principle dictates that a 3D bulk volume is perfectly isomorphic to a 2D boundary, constrained by covariant entropy bounds and holographic noise[3]. The mathematical tool utilized to compute this translation in physics is the tensor network—specifically MERA and continuous Matrix Product States mapped through systems like ASEP and Fredkin spin chains[11]. These tensor networks natively act as highly efficient compression algorithms and quantum error-correcting codes[21]. Therefore, the operating systems driving future spatial light modulators must be programmed fundamentally using tensor network contraction algorithms, allowing an extremely dense 2D phase map to unspool into a robust 3D light field.
3. **The Engine of Execution:** Translating these tensor networks from theory to projection requires the 10^{6} acceleration factor provided by Quantum Computer-Generated Holography[1]. Only by mapping the point-cloud data to the superposition states of qubits can the simultaneous lightwave interactions be processed at the tera-pixel scale[1].

When an object is captured via the high-fidelity entanglement scanning of biphoton digital holography[19], its phase data is inherently quantum. That quantum state can be fed directly into

the QGH tensor network pipeline without the need to destructively collapse it into classical bits. The quantum processor maintains the phase superposition, computes the boundary geometry, and projects the resulting interference pattern via the SLM. This creates a purely quantum computational pipeline from capture to display, fundamentally bypassing the Landauer thermodynamic limits of classical bit erasure[8].

The pursuit of volumetric, tera-pixel digital holography represents a frontier that cannot be conquered by scaling up existing classical technologies. The mathematical limits of viewing angles, pixel density, and computational capacity dictate that traditional computer-generated holography is fundamentally obsolete at this requisite scale. Instead, the paradigm must shift toward the fundamental quantum mechanics that govern the architecture of spacetime itself. To fully unlock digital holography is not merely to build a better display; it is to engineer a localized, computable mimicry of the quantum fabric of the universe itself.

Works cited

1. Quantum computer-generated holography - Optica Open - Figshare, https://preprints.opticaopen.org/articles/preprint/Quantum_computer-generated_holography/27123561
2. Space-time may be a sort of hologram generated by quantum, https://www.reddit.com/r/space/comments/bm6sq4/spacetime_may_be_a_sort_of_hologram_generated_by/
3. Holographic principle - Wikipedia, https://en.wikipedia.org/wiki/Holographic_principle
4. Tensor Networks Initiative - Perimeter Institute, https://perimeterinstitute.ca/tensor-networks-initiative
5. Holography beyond AdS/CFT by Nicholas S Salzetta A dissertation, https://escholarship.org/content/qt3jx0w209/qt3jx0w209.pdf?v=lg
6. Bose-Marletto-Vedral experiment without observable spacetime, https://arxiv.org/pdf/2506.21122
7. https://arxiv.org/abs/2506.21122
8. Learning optimal erasure of a Static Random Access Memory, https://www.researchgate.net/publication/385528586_Learning_optimal_erasure_of_a_Static_Random_Access_Memory
9. Physicists have observed the light spectrum of antimatter for first time, https://www.reddit.com/r/Futurology/comments/5jdrbw/physicists_have_observed_the_light_spectrum_of/
10. Introduction to Quantum Message Space - arXiv, https://arxiv.org/pdf/cs/0507032
11. Hyperinvariant Tensor Networks and Holography. - Semantic Scholar, https://www.semanticscholar.org/paper/Hyperinvariant-Tensor-Networks-and-Holography.-Evenbly/b28d09e5d8193376620a820406278fcf0fab673e
12. Tensor network - Wikipedia, https://en.wikipedia.org/wiki/Tensor_network
13. Review Articles & Learning Resources - Tensor Network, https://tensornetwork.org/reviews_resources.html
14. Lorentzian Holographic Gravity and the Time-Energy ... - SID,

https://www.sid.ir/fileserver/je/38732-279722-x-1134001.pdf
15. Holographic tensor network for double-scaled SYK - SciPost.org, https://scipost.org/SciPostPhys.19.4.083/pdf
16. MicroCloud Hologram Inc. Utilizes FPGA to Accelerate Tensor, https://www.moomoo.com/news/post/64175579/microcloud-hologram-inc-utilizes-fpga-to-accelerate-tensor-network-computing
17. Tomoyoshi Shimobaba Professor at Chiba University - ResearchGate, https://www.researchgate.net/profile/Tomoyoshi-Shimobaba-2
18. Quantum phase imaging via diffraction of correlated bi-photon states, https://pubs.aip.org/aip/app/article/11/6/066116/3395181/Quantum-phase-imaging-via-diffraction-of
19. Interferometric imaging of amplitude and phase of spatial biphoton, https://www.researchgate.net/publication/373116232_Interferometric_imaging_of_amplitude_and_phase_of_spatial_biphoton_states
20. Fig. 8 Noise reduction factor (NRF) and Fano factor as a function of, https://www.researchgate.net/figure/Noise-reduction-factor-NRF-and-Fano-factor-as-a-function-of-the-averaging-filter-size_fig5_372308525
21. Holographic codes from hyperinvariant tensor networks - PMC - NIH, https://pmc.ncbi.nlm.nih.gov/articles/PMC10640591/
22. Tensor network models of AdS/qCFT - Quantum Journal, https://quantum-journal.org/papers/q-2022-02-03-643/