The Non-Archimedean Architecture of Information: From 2-adic Bits and Anti-Bits to p-adic Qubits and Negentropy

The conceptualization of information, state spaces, and physical reality has traditionally been deeply anchored in the continuous, Archimedean geometry of the real and complex number fields. However, the discovery that space-time at the Planck scale might exhibit fundamentally discrete, fractal, or totally disconnected topologies has necessitated a rigorous reevaluation of the mathematical fields underpinning both quantum mechanics and information theory. By utilizing the p-adic number fields—derived from an alternative completion of the rational numbers—theoretical physics and computer science intersect in a strictly non-Archimedean geometry.

This report provides an exhaustive, expert-level theoretical continuum of p-adic information theory. The analysis extends from the foundational definitions of p-adic absolute values and metric spaces to their profound physical and computational implications. It systematically explores the classical 2-adic bit and the boolean "anti-bit" of two's complement arithmetic, the peculiar algebraic structures of composite g-adic systems, the rigid analytic geometry of the p-adic upper half plane, the formulation of non-Archimedean quantum information via the p-adic qubit, and cosmological models of conscious information via Zero Energy Ontology and the Negentropy Maximization Principle.

The Algebraic and Topological Foundations of p-adic Spaces

To translate classical and quantum information into a p-adic framework, one must first rigorously construct the field of p-adic numbers, $\mathbb{Q}_p$. This construction arises from a fundamental theorem in algebraic number theory. Ostrowski's Theorem asserts that every non-trivial absolute value on the field of rational numbers $\mathbb{Q}$ is equivalent either to the standard Euclidean absolute value (which yields the real numbers $\mathbb{R}$ upon completion) or to one of the p-adic absolute values (which yields the p-adic numbers $\mathbb{Q}_p$), where p is an arbitrary prime[1].

This theorem establishes a strict philosophical and mathematical dichotomy: all possible continuous metric spaces over $\mathbb{Q}$ are divided definitively into the Archimedean and the non-Archimedean[1].

The p-adic Valuation and the Ultrametric Inequality

The foundation of p-adic analysis is the p-adic valuation. For a fixed prime p, any non-zero rational number $x \in \mathbb{Q}$ can be uniquely factored according to the fundamental theorem of arithmetic as $x = p^k(a/b)$, where a and b are integers coprime to p, and k is an integer[1]. The p-adic valuation, denoted $v_p(x)$, is defined as this exponent k[1]. Conceptually, the p-adic valuation describes the degree of divisibility of a number by the prime p; highly divisible numbers have large positive valuations, while fractions with high powers of p in the denominator have highly negative valuations[1]. For the element zero, which is infinitely divisible by any prime, the valuation is defined as $v_p(0) = +\infty$[1].

From this valuation, the p-adic absolute value is defined as $|x|_p = p^{-v_p(x)}$ for $x \neq 0$, and $|0|_p = 0$[1]. This absolute value behaves radically differently from its Euclidean counterpart. It satisfies the standard positivity and multiplicativity axioms, meaning $|x|_p = 0$ if and only if $x = 0$, and $|xy|_p = |x|_p|y|_p$[1]. The multiplicativity follows directly from the additive property of the valuation: $v_p(xy) = v_p(x) + v_p(y)$[1].

However, instead of the classical triangle inequality, the p-adic absolute value adheres to the strong triangle inequality, also known as the ultrametric condition. For any rational numbers x and y, the valuation satisfies $v_p(x + y) \geq \min(v_p(x), v_p(y))$[1]. Consequently, the absolute value satisfies $|x + y|_p \leq \max(|x|_p, |y|_p)$[1]. This single condition radically alters the geometry of the space.

The ultrametric inequality gives rise to a totally disconnected topology. In a p-adic metric space, every point within a ball is its center, and every open ball is simultaneously closed (clopen)[2]. Furthermore, all triangles formed by three points in this space are strictly isosceles, meaning that out of any three points, at least two of the distances between them must be exactly equal[3].

The field of p-adic numbers, $\mathbb{Q}_p$, is defined as the metric completion of $\mathbb{Q}$ with respect to this

specific p-adic absolute value, mirroring how the real numbers are the completion of the rationals under the Euclidean absolute value[2].

Topological/Metric Property	Archimedean (Reals, R)	Non-Archimedean (p-adics, Qp)
Triangle Inequality	$\|x+y\| \leq \|x\| + \|y\|$	$\|x+y\|_p \leq \max(\|x\|_p, \|y\|_p$
Topology	Connected, continuous, standard open sets	Totally disconnected, totally bounded clopen sets
Series Convergence	$\sum a_n$ converges if partial sums reach a limit	$\sum a_n$ converges strictly if and only if $\|a_n\|_p \to 0$
Geometric Triangles	Can be scalene, isosceles, or equilateral	All triangles are isosceles (two sides are always equal)
Positivity and Ordering	Ordered field (contains positive and negative domains)	Unordered field (no intrinsic concept of positive numbers)
Formal Representation	Infinite digits to the right of the decimal point	Infinite digits to the left of the decimal point

The Ring of p-adic Integers and Formal Expansions

Within $\mathbb{Q}_p$, the set of elements with an absolute value less than or equal to 1 forms a commutative ring known as the p-adic integers, denoted $\mathbb{Z}_p$. Because the p-adic absolute value of non-zero numbers only takes discrete values in integer powers of p, $\mathbb{Z}_p$ can be rigorously defined as the unit ball $\mathbb{Z}_p = \{x \in \mathbb{Q}_p : |x|_p \leq 1\}$ [2]. This implies that $\mathbb{Z}_p$ contains all standard integers, as the valuation of any integer is non-negative, meaning its absolute value is p^0 or smaller[8].

Analytically, any p-adic integer $x \in \mathbb{Z}_p$ can be uniquely expressed as an infinite formal power series in base p, written as $x = \sum_{i=0}^{\infty} a_i p^i$, where each digit a_i is an integer in the restricted range $0 \leq a_i < p$ [8]. In this expansion, the arithmetic operations of addition and multiplication proceed exactly like standard base-p arithmetic, but they operate infinitely from right to left (from the least significant digit to the most significant digit), with carries propagating infinitely to the left[8].

For example, when performing 5-adic addition of an infinite repeating string like $\dots 33333_5$ and a finite string 24_5, the procedure mirrors standard addition: $3 + 4 = 7$, which is 12 in base-5, yielding a rightmost digit of 2 and a carry of 1 [11]. Moving left, $3 + 2$ plus the carried 1 equals 6, which is 11 in base-5, yielding a digit of 1 and a carry of 1. The infinite stream of digits seamlessly absorbs the carries[11].

Division in the p-adic integers is equally counterintuitive from a real-number perspective but algebraically consistent. Because infinite strings to the right of a decimal point are strictly forbidden in p-adic expansions (as they correspond to infinite positive powers of p^{-1}, which fail to converge in the ultrametric topology), fractions must be represented by infinite strings extending to the left[8]. For instance, in the 5-adic integers, the fraction $1/3$ cannot be represented by decimals; instead, it is computed via long division from right to left, resulting in the infinite integer string $\dots 1313132_5$ [11].

Alternatively, a powerful algebraic perspective defines $\mathbb{Z}_p$ as the inverse limit (or projective limit) of the finite quotient rings $\mathbb{Z}/p^n\mathbb{Z}$ as $n \to \infty$ [9]. An element of $\mathbb{Z}_p$ is a coherent sequence of residues modulo p^n [8]. This equivalence between the infinite sequence of digits and the coherent sequence of modular congruences is the precise mathematical mechanism that unites abstract non-Archimedean geometry with the discrete mathematics of modern computer science.

The Classical 2-adic Bit and the "Anti-Bit"

The abstract construction of p-adic numbers finds a direct, physical realization in the architecture of digital computing, specifically within the framework of 2-adic numbers. When the prime $p = 2$, the field $\mathbb{Q}_2$ and the ring $\mathbb{Z}_2$ provide the exact topological space required to formalize binary computation, the concept of the information bit, and its logical complement,

which operates as a computational "anti-bit".

Bits, Finite Registers, and the 2-adic Topology

In a classical computing system, information is encoded in binary digits (bits), representing deterministic states of 0 or 1. A processor evaluates these bits in fixed-size hardware registers, such as 8-bit, 32-bit, or 64-bit architectures. A sequence of N bits can be viewed mathematically as an element of the finite ring $\mathbb{Z}/2^N\mathbb{Z}$ [12]. However, when one considers a theoretical computer with an infinitely expandable memory register, the sequence of bits extends infinitely to the left, forming exactly the 2-adic integer expansion:

$x = b_0 + b_1 2 + b_2 2^2 + b_3 2^3 + \dots$ where each $b_i \in \{0, 1\}$ represents a single binary bit[9].

Therefore, a 2-adic integer is fundamentally an infinite bit-sequence[15]. Modern computing architectures implicitly treat all integer types as truncated 2-adic numbers[12]. When two numbers in a computer are added, subtracted, or multiplied, the arithmetic logic unit (ALU) operations are identical to 2-adic arithmetic, where carries propagate to the left. In a finite N-bit register, any carry that overflows the N-th most significant bit is simply discarded[13]. This hardware truncation corresponds perfectly to mathematical modulo arithmetic in $\mathbb{Z}/2^N\mathbb{Z}$, which is itself a localized, finite projection of the true infinite 2-adic limit[12].

Two's Complement Encoding and the Anti-Bit

The most profound theoretical connection between 2-adic mathematics and computer science is the representation of negative numbers and the mechanics of subtraction. Early computing architectures struggled with how to encode the negative of a binary number. A naive approach, known as sign-magnitude representation, allocated one bit for the sign and the rest for the absolute value; however, this led to dual representations of zero ($+0$ and -0) and mandated complex, inefficient arithmetic hardware[13]. The elegant mathematical solution, universally adopted in modern processors, is the two's complement encoding algorithm.

To find the two's complement (the negative representation) of a binary number, the system executes two steps: first, it takes the bitwise logical complement (inverting all 0s to 1s and all 1s to 0s), and second, it adds 1 to the least significant bit of the result[13]. The act of flipping a bit to its opposite state represents the creation of an "anti-bit." If an N-bit array x represents a specific digital state, the array of anti-bits, denoted $\sim x$ (the ones' complement), represents its diametric logical opposite[13].

The brilliance of the two's complement system is that it is not merely a clever engineering heuristic; it is an exact artifact of 2-adic geometry[13]. In the Euclidean real number system, negative numbers are denoted by an arbitrary minus sign. In a p-adic topological system, there

are no minus signs; negative numbers are natively represented by infinite sequences of digits that wrap around the modular boundaries of the space[9].

To rigorously demonstrate this, consider the 2-adic representation of the integer -1. By the definitions of algebraic groups, -1 is the specific number which, when added to 1, results in an identity of 0. In 2-adic arithmetic, if one adds 1 to an infinite string of 1s: $\dots 11111111_2 + 1_2 = \dots 00000000_2$ The carry bit propagates infinitely to the left, leaving an infinite string of zeros in its wake. Therefore, in the 2-adic metric space, the integer -1 is precisely defined as an infinite sequence of 1 bits: $-1 = \sum_{i=0}^{\infty} 2^i$ [12].

When computing the negative of an arbitrary positive number x in a finite N-bit computer register, the mathematical operation $-x = 2^N - x$ is performed[13]. Because the expression $2^N - 1$ is inherently a string of N ones, subtracting the state x from it mathematically forces the flipping of every single bit of x, thereby creating the anti-bit sequence[13].

Consequently, $-x$ is equivalent to the anti-bit sequence plus one: $-x = \sim x + 1$ [13]. This finite hardware operation is simply a rigorous truncation of the infinite 2-adic equation $-x = \sim x + 1$. The most significant bit in a finite register acts as the sign bit (1 for negative, 0 for positive), but this is merely a byproduct of truncating an infinite 2-adic string of 1s or 0s[17]. Thus, two's complement encoding is precisely 2-adic mathematical representation taken to its logical extreme[15].

Decimal Integer	**8-Bit Two's Complement**	**True 2-adic Expansion (Infinite bit-sequence)**
1	0000 0001	...0000 0000 0000 0001
-1	1111 1111	...1111 1111 1111 1111
127	0111 1111	...0000 0000 0111 1111
-127	1000 0001	...1111 1111 1000 0001
-29	1110 0011	...1111 1111 1110 0011

The anti-bit, therefore, serves as the geometrical mechanism that maps the positive domain of the 2-adic metric into the pseudo-negative domain. Because the 2-adic distance between two numbers is determined by the lowest power of 2 at which their bit-sequences differ, flipping all the bits and adding 1 fundamentally transforms the ultrametric location of the computational state, effectively moving it to the exact topological opposite within the $\mathbb{Z}_2$ ring.

The Collatz Conjecture and 2-adic Continuity

The 2-adic nature of computational states also provides profound theoretical pathways for analyzing recursive algorithms, most notably the Collatz Conjecture. The dynamics of the $3x+1$ problem can be mapped directly into the 2-adic integers through the Terras map, which generates a parity sequence of 0s (for even steps where division by 2 occurs) and 1s (for odd steps where $3x+1$ is applied)[15].

Because any given number processed through the Collatz rules yields an infinite sequence of parities, this parity sequence acts as a discrete bit-stream that exactly defines a unique 2-adic integer[15]. Let this parity mapping be defined as a function $Q(x)$. The theoretical beauty of the 2-adic metric is that $Q(x)$ is a continuous function. If two numbers x and y are 2-adically close (meaning $x-y$ is divisible by a remarkably high power of 2, indicating their least significant bits match up to a high index), then their corresponding Collatz parity sequences $Q(x)$ and $Q(y)$ will also be 2-adically close[15].

Furthermore, the 2-adic framework effortlessly handles negative numbers and fractions with odd denominators, domains where the standard Collatz trajectory is poorly defined over the reals. For example, the fraction $-1/3$ maps immediately to zero under the Terras map, yielding a parity sequence of $(1,0,0,0,\dots)$, which corresponds precisely to the 2-adic integer 1, meaning $Q(-1/3)=1$ [15]. The 2-adic limit of the divergent standard integer trajectories repeatedly points toward these rational p-adic targets, illustrating how infinite computational bit-sequences encapsulate complex dynamical attractors.

The Failure of Composite Bases: 10-adic Numbers and Idempotents

While 2-adic bits govern binary computation, it is vital to understand why information theory and theoretical physics strictly restrict themselves to p-adic spaces where the base p is a prime number, rather than a composite base like 10. The historical foundations of this restriction date back to Carl Friedrich Gauss, who performed undocumented calculations of "infinite

congruences" modulo 10^∞ and 11^∞, approximating roots of polynomials in what are now recognized as p-adic and g-adic metrics[24].

Gauss's computation of square roots in 10-adic geometry reveals a fundamental algebraic collapse. If one attempts to construct the ring of 10-adic integers $\mathbb{Z}_{10}$, the resulting mathematical structure ceases to be an integral domain[24]. Specifically, the 10-adic number system contains zero divisors—non-zero numbers that, when multiplied together, yield zero[12].

In a 10-adic system, it is possible to calculate a non-trivial infinite sequence a that satisfies the equation $a^2 = a$ [24]. Such an element is known as an idempotent. If $a^2 = a$, then $a^2 - a = 0$, which factors to $a(a-1) = 0$. Because a is neither 0 nor 1, the numbers a and $b = 1 - a$ act as orthogonal idempotents, meaning their product $ab = 0$ [24].

Because the unit 1 can be expressed as the sum of these orthogonal idempotents ($1 = a + b$), the ring $\mathbb{Z}_{10}$ fractures into a direct sum of two smaller rings: $\mathbb{Z}_{10} = \mathbb{Z}_2 \oplus \mathbb{Z}_5$ [24].

This algebraic fracturing means that division is impossible for a vast set of non-zero elements, completely destroying the ability to form a mathematical field. When computing states or propagating information, a topological space with zero divisors would allow non-zero data streams to arbitrarily annihilate each other during tensor multiplications. Thus, quantum mechanics, L-functions, and information coding universally demand prime bases ($p = 2, 3, 5, \dots$), where the lack of non-trivial idempotents guarantees the algebraic integrity of the field $\mathbb{Q}_p$ [12].

p-adic Geometry, Modular Forms, and L-Functions

The total disconnectedness of $\mathbb{Q}_p$ does not preclude the existence of complex analytical geometries; rather, it shifts the focus to rigid analytic spaces and Bruhat-Tits trees. This domain of p-adic geometry provides critical tools for analyzing L-functions and modular forms, mapping macroscopic number-theoretic properties into localized p-adic variables[25].

The classical upper half plane of complex numbers $\mathcal{H}$ is fundamental in defining modular forms. Its non-Archimedean analogue, the p-adic upper half plane $\mathcal{X}$, is constructed not as a continuous sheet, but as a rigid analytic space whose points are defined by complete extension fields of $\mathbb{Q}_p$ [26]. Geometrically, the structure of $\mathcal{X}$ is governed by the Bruhat-Tits tree, a

homogeneous graph where vertices represent equivalence classes of lattices, and edges define strict inclusion relations[26]. The tree structure guarantees that there are no closed cycles; every path is a unique ray extending toward an infinite set of ends, perfectly mirroring the unique digit expansion of p-adic integers[9].

This geometrical structure enables the formulation of p-adic L-functions. While classical L-functions (like the Riemann zeta function or Dirichlet L-functions) interpolate values over the complex plane, their p-adic counterparts interpolate special values across non-Archimedean limits[25]. For instance, a p-adic L-function $L_p(s, \chi)$ uses p-adic integration to encode the values of classical L-functions at non-positive integers, revealing deep properties like the p-adic class number formula[25]. Furthermore, evaluating the p-adic moments of these L-functions—the p-adic valuation of weighted central L-values—reveals profound asymptotic formulas regarding subconvexity and large values, tracking how highly divisible these L-values are by the prime p[27].

Crucially, in the study of elliptic curves and Galois representations, the p-adic representations of absolute Galois groups $\mathrm{Gal}(\bar{F}/F)$ dictate the arithmetic invariants of the curves[28]. The p-adic cyclotomic character, which tracks the Galois action on roots of unity, serves as the fundamental mechanism to evaluate the ramification and crystalline properties of these representations[28]. The translation of global rational properties into local p-adic Galois representations embodies the local-global principle (Hasse principle), where proving the existence of a solution across all p-adic completions confirms its existence in the global rational field[4].

p-adic Quantum Mechanics and the Non-Archimedean Qubit

While 2-adic mathematics elegantly describes classical hardware computation, the transition to quantum information requires extending these principles to formulate a state space capable of supporting superposition, entanglement, and unitary evolution. Standard quantum mechanics is built strictly upon continuous complex Hilbert spaces. p-adic quantum mechanics proposes an alternative wherein the field of complex numbers $\mathbb{C}$ is entirely replaced by a non-Archimedean field[7]. This paradigm shift, originally spearheaded in the late 1980s by Vladimirov, Volovich, and

Zelenov, is motivated by the physical hypothesis that at the Planck length ($l_P \approx 10^{-35}$ m), standard spacetime geometry breaks down into a non-Archimedean foam, rendering continuous real-number models fundamentally inadequate[7].

Quadratic Extensions and Isotropic Hilbert Spaces

To build a functional quantum theory, one requires a scalar field that mimics the algebraic completeness of the complex numbers. The field $\mathbb{Q}_p$ alone is not algebraically closed. To resolve this, physicists utilize unramified quadratic extensions of the p-adic numbers, denoted $\mathbb{Q}_{p,\mu}$ [5].

By introducing a formal symbol μ (which is strictly a non-square element in $\mathbb{Q}_p$, analogous to the imaginary unit i in $\mathbb{C}$), the quadratic extension is defined as the set of all elements $z = x + \mu y$, where $x, y \in \mathbb{Q}_p$ [6]. This extension acts as a two-dimensional vector space over $\mathbb{Q}_p$. Complex conjugation has a direct arithmetic analog: $\bar{z} = x - \mu y$, which allows for the definition of an inner product and a squared norm $z\bar{z} = x^2 - \mu y^2 \in \mathbb{Q}_p$ [6]. The non-Archimedean absolute value is extended uniquely to $\mathbb{Q}_{p,\mu}$ via the relation $|z|_{p,\mu} = |z\bar{z}|_p$ [6].

With this scalar field successfully defined, a p-adic Hilbert space can be constructed as a complete, non-Archimedean Banach space equipped with a canonical inner product[5]. However, profound topological differences immediately manifest. In a standard complex Hilbert space, the inner product induces the norm directly ($||x|| = \sqrt{\langle x, x \rangle}$), and the underlying field is ordered (meaning one can definitively establish mathematical positivity). In the p-adic setting, $\mathbb{Q}_p$ is an unordered field; there is no inherent topological concept of a "positive" p-adic number[6].

Consequently, a p-adic Hilbert space may contain isotropic vectors—non-zero state vectors x for which the inner product vanishes entirely ($\langle x, x \rangle = 0$)[5]. This breaks standard Cauchy-Schwarz mechanics. Thus, in p-adic spaces, orthogonality is redefined through the maximum metric: vectors x and y are norm-orthogonal if $||\alpha x + \beta y|| = \max(||\alpha x||, ||\beta y||)$ for all scalars[5].

Defining the p-adic Qubit and Symmetric Operator-Valued Measures

In standard quantum computing, a generic qubit is represented as a state vector in a two-dimensional complex Hilbert space, mathematically mapping to the fundamental representation of the special unitary group $SU(2)$. To define a precise p-adic qubit, one must identify a non-Archimedean analog of this symmetric rotation group[31].

Due to the algebraic constraints of non-isotropic quadratic forms over p-adic fields, compact p-adic special orthogonal groups only exist in finite dimensions of two, three, and four[31]. Specifically, $SO(3)_p$ forms the unique group of rotations on the configuration space $\mathbb{Q}_p^3$ [32]. The group $SO(3)_p$ is a topological group, completely regular, totally disconnected, locally compact, and profinite (it exists as the inverse limit of an infinite family of finite discrete groups)[31].

A p-adic qubit is therefore rigorously defined as a two-dimensional irreducible projective unitary representation of this compact p-adic special orthogonal group $SO(3)_p$ [31]. This representation assigns a unitary operator ray to every element in the topological group, acting directly on a two-dimensional p-adic Hilbert space[31].

Furthermore, because the p-adic field lacks total ordering, the standard formulation of a Positive Operator-Valued Measure (POVM) for describing quantum measurements cannot be maintained, as the term "positive" is geometrically meaningless in $\mathbb{Q}_p$ [6]. Instead, measurement in p-adic quantum mechanics relies on the novel concept of a Symmetric Operator-Valued Measure (SOVM)[6]. The state of a p-adic qubit is defined by a p-adic statistical operator, a density matrix ρ such that it equals its adjoint ($\rho = \rho^\dagger$) and its trace equals one ($\mathrm{Tr}(\rho) = 1$)[6]. Probabilities derived from these non-Archimedean states via SOVMs do not lie in the real continuous interval $[0, 1]$; they are elements of $\mathbb{Q}_p$ subject strictly to p-adic normalization constraints where the sum of the p-adic coefficients equals the identity 1[6].

Anti-Qubits, Unitary Inversion, and Zero Energy Ontology

The concept of the anti-bit in classical 2-adic computing (achieved via bitwise complementation and additive inversion) scales upward to the concept of the anti-qubit in the quantum domain. In

empirical quantum mechanics, the anti-qubit is often conceptualized using actual antimatter platforms (such as the recent trapping of antimatter qubits at CERN to test CPT parity violations) or via complex conjugate states undergoing mathematically inverted unitary evolutions[35].

The Unitary Inversion of the Anti-Qubit

In physical quantum circuits, if a standard qubit undergoes a unitary transformation U, the corresponding anti-qubit must undergo the inverse Hermitian transformation $U^\dagger$ to maintain global symmetry[35]. For instance, if a qubit and an anti-qubit pass through an identical magnetic field, the qubit experiences an alternating-current (AC) Stark shift of δ_q, while the anti-qubit experiences a mathematically inverted shift of $\delta_{\bar{q}} = -\delta_q$ [35]. This effectively inverts the z-component of the magnetic field experienced by the anti-qubit[35].

In the p-adic formulation, this inversion is deeply connected to the anti-automorphisms of the quadratic extension $\mathbb{Q}_{p,\mu}$ [32]. The anti-qubit state represents the precise p-adic conjugate state. Because the p-adic topological space $SO(3)_p$ is totally disconnected, continuous time-evolution (which is standardly governed by the continuous differential Schrödinger equation) does not exist. It must be replaced by path integrals or discrete sequences of unitary transition operators[30]. Applying the anti-qubit operator $U^\dagger$ essentially dictates backward discrete traversal through the profinite group structure of $SO(3)_p$.

Zero Energy Ontology (ZEO) and Anti-Particles

The relationship between quantum states and their inverted anti-states (anti-particles) gains profound geometric clarity when modeled via Topological Geometrodynamics (TGD), a sweeping unified framework heavily reliant on p-adic number fields to map cognition and physics[39]. Within TGD, the standard positive-energy ontology of classical quantum mechanics is wholly replaced by Zero Energy Ontology (ZEO)[39].

In ZEO, physical states are not just localized mass-energy points propagating linearly in time. Instead, a physical state is explicitly defined as a pair of positive and negative energy states located at the opposite light-like boundaries of a geometric construct known as a Causal Diamond (CD)[39]. By definition, all conserved quantum numbers for these zero-energy states strictly net to zero. Therefore, a particle traveling backward in time from the upper boundary of the CD is mathematically and physically interpreted as an anti-particle (or anti-state) moving forward in time from the lower boundary[40].

The temporal distance T between the tips of these Causal Diamonds dictates the permitted macroscopic physical scales, which align exactly with the p-adic length scale hypothesis[39]. This

hypothesis states that physically preferred p-adic primes (k) occur near powers of 2 (i.e., $p \approx 2^k$, strongly favoring Mersenne primes)[39]. The physical distance is mapped via the relation $L^2(k) = T(k)R$, bridging the 2-adic binary bit models at the micro-scale with massive cosmological distance boundaries at the macro-scale[39]. The anti-qubit and the classical anti-bit are therefore not merely mathematical reversed vectors; they are the fundamental negative-energy components of a zero-energy p-adic state, ensuring global conservation laws within a non-Archimedean universe.

Information Theory: p-adic Entropy, Negentropy, and NMP

When physical states and anti-states are fully mapped within a p-adic geometry, the measurement of the information extracted from these systems requires a radical departure from classical Shannon or von Neumann entropy. In the continuous Archimedean world, entropy universally measures the degree of ignorance or thermodynamic disorder within a physical system, and according to the Second Law of Thermodynamics, it must monotonically increase over time[45].

However, in the intersection of real and p-adic geometries—where physical physical matter (real metrics) and cognitive structures (p-adic metrics) interact—the entropy paradigm shifts entirely to accommodate the creation of genuine, conscious information.

p-adic Entropy and the Discovery of Negentropy

Classical Shannon entropy for a discrete system is defined by the formula $S = -\sum p_k \log(p_k)$. In a strictly p-adic setting, calculating the standard logarithm of a rational probability p_k directly is problematic because the standard logarithm outputs continuous real numbers, instantly breaking the non-Archimedean topological boundary[44].

The mathematical solution, heavily utilized in p-adic thermodynamics, is to replace the standard logarithm with the logarithm of the p-adic absolute norm of the probability: $\log_p(|p_k|_p)$ [44]. This yields a modified, topologically valid entropy formula known as p-adic entropy: $S_p = -\sum p_k \log_p(|p_k|_p)$ [44].

Because the p-adic norm $|p_k|_p$ always evaluates by definition to an integer power of p, the

resulting term $\log_p(p^n) = n$ is strictly integer-valued[44]. The final summation can then be smoothly mapped back to the real numbers for physical interpretation using canonical identification protocols[44].

The most revolutionary insight of this algebraic formulation is that, unlike Shannon entropy which is strictly non-negative in all real configurations, p-adic entropy can evaluate to a mathematically valid negative number[44]. When $S_p < 0$, the quantum system possesses negative entropy, universally referred to as **Negentropy**[45].

In standard quantum mechanics, entanglement between particles always generates thermodynamical entropy; an observer immediately loses information about the individual localized subsystems, reducing their pure states to mixed density matrices. In contrast, in p-adic quantum mechanics, if the entanglement coefficients lie in an algebraic extension of rational numbers (thereby existing simultaneously in both real and p-adic geometries), the evaluated p-adic entropy is negative. This Negentropic Entanglement represents a literal gain in conscious, structured information rather than a thermodynamic loss[45]. It binds quantum systems together non-destructively, acting as the fundamental theoretical foundation for stable cognitive representations, biological memory arrays, and arguably, the existence of life itself[44].

Information Metric	**Mathematical Formula**	**Domain**	**Implication for Quantum Entanglement**
Shannon Entropy	$S = -\sum p_k \log(p$	$\mathbb{R}$ (Reals)	Entanglement increases entropy (loss of local information, disorder).
p-adic Entropy	$S_p = -\sum p_k \log_p($	$\mathbb{Q}_p$ (p-adics)	Entanglement can yield $S_p < 0$.
Negentropy	$N = -S_p$ (when $S_p < 0$)	Intersection of $\mathbb{R}$ and $\mathbb{Q}_p$	Entanglement generates structured, conscious information (order).

The Negentropy Maximization Principle (NMP)

This profound mathematical phenomenon gives rise to the Negentropy Maximization Principle (NMP), which operates as the fundamental variational principle of p-adic dynamics, acting as the direct cognitive analogue to the Second Law of Thermodynamics in the physical sector[44]. NMP dictates that the state reductions in any quantum measurement will inherently tend to maximize the generation of negentropy[48].

Under NMP, a system will naturally and irreversibly evolve toward states of higher negentropic entanglement[46]. The apparent physical contradiction with the Second Law of Thermodynamics is neatly resolved through a generalized thermodynamic conservation equation. The creation of p-adic negentropy in the cognitive/dark sector necessitates a compensatory generation of ordinary thermodynamic entropy in the real/physical sector[46]. The thermodynamic inequality $\Delta S_{real} - \Delta N_{p-adic} \geq 0$ theoretically ensures that while local physical disorder (heat, waste) inevitably increases, the global cognitive and structural information (negentropy) within the universe increases simultaneously[46].

This provides a mathematically rigorous cosmological explanation for both biological evolution and advanced computational intelligence: living entities and processors consume physical energy (via cellular metabolism or electrical power dissipation) to generate vital structural negentropy through p-adic algebraic entanglement[44].

Clarification: Probabilistic Bits (p-bits) vs. p-adic Bits

Given the dense nomenclature of modern information theory, it is mathematically essential to distinguish the deeply algebraic p-adic framework from superficially similar terminology in modern engineering, specifically "probabilistic bits" or p-bits[53].

Introduced to bridge the engineering gap between classical deterministic bits and highly sensitive cryogenic quantum qubits, p-bits are classical hardware computing elements whose outputs rapidly fluctuate between 0 and 1 based strictly on an external probability parameter[34]. While p-bits are highly relevant to stochastic machine learning models and simulating quantum annealing algorithms on classical hardware, their theoretical foundation remains purely Archimedean. They rely entirely on standard continuous real probability distributions summing to 1 over the real number line[34]. They do not invoke ultrametric spaces, p-adic absolute valuations, non-Archimedean states, or SOVMs, and thus they entirely lack the topological and algebraic properties of the true p-adic qubit or the 2-adic bit discussed in this report[34].

Conclusion

The pursuit of modeling reality at its most fundamental computational and physical scales

reveals that the continuous, real-number framework is inherently insufficient. The alternative—the p-adic completion of the rational numbers via Ostrowski's Theorem—provides a universe of totally disconnected, non-Archimedean topologies perfectly suited for both discrete digital computation and exotic quantum states.

The p-adic architecture fundamentally unifies classical and quantum concepts of information. At the classical extreme, the 2-adic numbers explicitly define the infinite topological geometry of the computing "bit" and mathematically enforce the "anti-bit" through two's complement arithmetic, proving that computational negation is not a mere hardware convenience but an innate, unavoidable property of non-Archimedean spaces. Furthermore, the analysis of composite bases like the 10-adics demonstrates exactly why fields require prime bases to avoid algebraic fracturing via zero divisors.

At the quantum and cosmological extreme, quadratic extensions of $\mathbb{Q}_p$ allow for the construction of $SO(3)_p$ symmetric p-adic qubits, where quantum measurement strictly requires Symmetric Operator-Valued Measures rather than standard continuous probabilities. Extending this non-Archimedean geometry to Zero Energy Ontology gives geometric reality to the anti-qubit as a time-reversed entity traversing the boundaries of a Causal Diamond.

Ultimately, the p-adic framework redefines the fundamental nature of information itself; by utilizing p-adic norms within entropy calculations, the mathematics naturally and spontaneously yields negentropy. Guided by the Negentropy Maximization Principle, the universe can be accurately modeled as an information-processing entity that actively converts thermodynamic decay into localized, algebraically entangled conscious information. The translation of binary states, quantum superpositions, and biological entropy into the p-adic metric thus stands as one of the most cohesive theoretical bridges between pure algebraic number theory, computer science, and topological quantum physics.

Works cited

1. AN INTRODUCTION TO THE p-ADIC NUMBERS - UChicago Math, http://math.uchicago.edu/~may/REU2020/REUPapers/Pomerantz.pdf
2. p-adic Analysis in Arithmetic Geometry, https://www.mathe2.uni-bayreuth.de/stoll/teaching/pAdicAnalysis-WS2015/Skript-pAdicAnalysis-pub-print.pdf
3. Learning with the p-adics - arXiv, https://arxiv.org/pdf/2512.22692
4. An Infinite Universe of Number Systems | Quanta Magazine, https://www.quantamagazine.org/how-the-towering-p-adic-numbers-work-20201019/
5. A p-Adic Model of Quantum States and the p-Adic Qubit - UNICAM, https://pubblicazioni.unicam.it/retrieve/067c9b87-b7c0-47ce-856f-2056cb8841ee/e

ntropy-25-00086.pdf
6. A p-Adic Model of Quantum States and the p-Adic Qubit - MDPI, https://www.mdpi.com/1099-4300/25/1/86
7. A p-Adic Model of Quantum States and the p-Adic Qubit, https://pdfs.semanticscholar.org/effa/3da6a478a18c3ceef63ddfcb799ab0033f30.pdf
8. p-adic number - Wikipedia, https://en.wikipedia.org/wiki/P-adic_number
9. Computations with p-adic numbers - arXiv, https://arxiv.org/pdf/1701.06794
10. p-adic Integer -- from Wolfram MathWorld, https://mathworld.wolfram.com/p-adicInteger.html
11. P-adic arithmetic | Good Math/Bad Math, http://www.goodmath.org/blog/2012/12/12/p-adic-arithmetic/
12. p-adic numbers - Berkeley math circle, https://mathcircle.berkeley.edu/sites/default/files/handouts/2020/BMC_Adv_p-adic_numbers_notes.pdf
13. Understanding Two's Complement Basics | PDF - Scribd, https://www.scribd.com/document/248521214/Two-s-Complement
14. Computing the k-error 2-adic complexity of a binary sequence of, http://paper.ijcsns.org/07_book/200603/200603A09.pdf
15. The 2-adic integers, Collatz, and Q(x), part 3 (this one's short!) - Reddit, https://www.reddit.com/r/Collatz/comments/1jkse8x/the_2adic_integers_collatz_and_qx_part_3_this/
16. 2-adic numbering for binary tilings - 11011110, https://11011110.github.io/blog/2024/10/28/2-adic-numbering-binary.html
17. Two's Complement - GeeksforGeeks, https://www.geeksforgeeks.org/digital-logic/twos-complement/
18. 2s Complement - CS2100 - NUS Computing, https://www.comp.nus.edu.sg/~adi-yoga/CS2100/notes/ch03e3.html
19. Two's Complement trick revealed - The Miners - Codeminer42, https://blog.codeminer42.com/twos-complement-trick-revealed/
20. How does the 2's complement describe a negative number in binary?, https://math.stackexchange.com/questions/4356142/how-does-the-2s-complement-describe-a-negative-number-in-binary
21. Two's Complement, https://www.rit.edu/academicsuccesscenter/sites/rit.edu.academicsuccesscenter/files/documents/math-handouts/DM3_TwosComplement_BP_9_22_14.pdf
22. Two's complement - Wikipedia, https://en.wikipedia.org/wiki/Two%27s_complement
23. Two's Complement: A Guide | Built In, https://builtin.com/articles/twos-complement
24. Gauss and p-adic numbers - arXiv, https://arxiv.org/html/2510.11559v2
25. Anticyclotomic p-adic L-functions and Ichino's formula, https://pi.math.cornell.edu/~dcollins/PrincetonThesis.pdf
26. The p-adic upper half plane, https://swc-math.github.io/aws/2007/DasguptaTeitelbaumNotesMar10.pdf
27. p-adic moments of L-functions - arXiv, https://arxiv.org/pdf/2507.01836

28. CMI SUMMER SCHOOL NOTES ON p-ADIC HODGE THEORY, https://math.stanford.edu/~conrad/papers/notes.pdf
29. On the p-adic cohomology of the Lubin-Tate tower, https://people.mpim-bonn.mpg.de/scholze/pAdicCohomLT.pdf
30. p-adic quantum mechanics - Wikipedia, https://en.wikipedia.org/wiki/P-adic_quantum_mechanics
31. Composing p-adic qubits: from representations of SO(3)$_ ... - arXiv, https://arxiv.org/pdf/2601.13808
32. Invariant measures on p-adic Lie groups - arXiv, https://arxiv.org/pdf/2306.07110
33. Untitled - IQIS 2023, https://iqis2023.it/wp-content/uploads/2023/09/Book_of_Poster_IQIS2023.pdf
34. Qubits and P-bits - LiveJournal, https://gwillen.livejournal.com/68947.html
35. Superconducting antiqubits achieve optimal phase estimation via, https://quantumsteampunk.umiacs.io/public/docs/25_Song_Superconducting.pdf
36. Scientists just made the 1st antimatter 'qubit.' Here's why it could be, https://www.space.com/science/scientists-just-made-the-1st-antimatter-qubit-heres-why-it-could-be-a-big-deal
37. A quantum leap for antimatter measurements – Home - CERN, https://home.cern/quantum-leap-antimatter-measurements/
38. Tachyon Dynamics in Open String Theory1 - arXiv, https://arxiv.org/pdf/hep-th/0410103
39. p-Adic Numbers and Generalization of Number Concept Contents, https://tgdtheory.fi/pdfpool/padmat.pdf
40. (PDF) Geometry and physics - ResearchGate, https://www.researchgate.net/publication/41398872_Geometry_and_physics
41. The most recent vision about zero energy ontology and p-adicization, https://matpitka.blogspot.com/2008/09/most-recent-vision-about-p-adicization.html
42. some experiments in number theory, https://people.math.harvard.edu/~knill/primes/papers/gaussian.pdf
43. Quadratic Primal Space (Conjectures) - Creative Science & Philosophy, https://pesla.blogspot.com/2011/03/quadratic-primal-space-conjectures.html?m=1
44. Possible Role of p-Adic Numbers in Bio-Systems Contents, https://tgdtheory.fi/pdfpool/biopadc.pdf
45. Appendix 2 TDG and Artificial Intelligence Summary and Discussion, https://journalofnonlocality.org/index.php/jnonlocality/article/download/104/84
46. Generalization of thermodynamics allowing negentropic, https://scireprints.lu.lv/167/1/thermolife.pdf
47. Conscious Information and Intelligence Contents, http://tgdtheory.fi/pdfpool/intsysc.pdf
48. Why Mersenne Primes Are So Special? 1 Introduction 2 How to, https://distantreader.org/stacks/journals-ojs/pst/pst-1004.pdf
49. Quantum Mind in TGD Universe - SciSpace, https://scispace.com/pdf/quantum-mind-in-tgd-universe-68jxpo4zbz.pdf
50. The TGD View of The Possible Role of Spin Glass Phase & p-adic, https://prespacetime.com/index.php/pst/article/download/1886/1753

51. Is it possible to measure cognitive entanglement ... - TGD diary, https://matpitka.blogspot.com/2025/12/is-it-possible-to-measure-cognitive.html
52. FQxI QSpace - Foundational Questions Institute Community, https://qspace.fqxi.org/competitions/entry/372
53. p-bits: Bridging the gap between standard bits and q-bits - AIP.ORG, https://www.aip.org/scilights/p-bits-bridging-the-gap-between-standard-bits-and-q-bits