Gewu Insight - Windows Preview Guide

Windows Preview 0.1.21 - desktop from local source.

Start the source desktop

Double-click Start Gewu Insight.cmd in the repository. Windows Preview 0.1.21 uses dist/windows-preview-0.1.21 and the local .venv Python environment. Close the Gewu window to stop its service. Native code changes require a matching shell; Python and interface changes load after restarting.

Your existing Library remains at %USERPROFILE%\Gewu Insight Preview. Its selection is recorded in %USERPROFILE%\.gewu-insight\preview-workspace.txt. File > Open Data Folder shows the actual location. A missing selected database stops startup instead of silently creating an empty replacement. SQLite is authoritative.

This local source delivery does not use an installer. Installed Preview 0.1.19 has been removed; its archived copy is for recovery only. Windows 11 x64 and WebView2 are the validated environment. New computers require a compatible shell, Python dependencies and WebView2.

Library and Paper Files

The shared product now includes the macOS updates through 8a27895: canonical paper identities and old-key aliases, publication notices, resource deduplication, unified metadata tasks and 20 Paper Files types. Corrections, retractions and related notices keep their own identifiers and links to the original research paper.

Library, Spaces and Shortcuts share the same managed files. Additional placements use Windows .lnk shortcuts, not duplicate PDFs. Paper Files offers Move to Another Paper and Create Paper from File. Identical bytes are reused while import sources remain recorded; different versions and annotations remain distinct. Manual Default choices are preserved.

Use column headers to sort Title, Authors, Year, Journal or Time added. Settings > Add to Library chooses the default destination. File and folder moves update their references together; interrupted moves are recovered from a journal. Startup does not scan or reorganize the whole historical Library.

Library Recycle and removal of private managed files use Windows Shell recovery with a verified backup. Other active Library, Space and Publications references and external originals are retained. The operating-system Recycle Bin can restore successfully deleted bytes; add a restored file again to reattach it.

Refresh Info and research monitors

Refresh Info is shared by individual papers, folders, the whole Library and imports. Quick and Full refresh use persistent progress with Pause, Continue, Stop and history. Manual DOI/arXiv corrections record their history. Network failures remain visible and can be retried.

Author Monitor shows cached papers immediately and refreshes in the background. Metadata work is limited to the author scope and rotates through unfinished papers. Temporary access failures back off and recover without treating an abnormal response as an empty publication list.

Subject Monitor preserves earlier results when settings change; an explicit successful refresh replaces its window. Calendar counts use numbers only. My Publications import remains resumable, and deleting a placement protects papers still referenced elsewhere. PDF downloads remain explicit.

Loader and file handling

File > Library Loader opens an independent window. Closing hides it and retains the source, draft and task. Refresh Info and identifier recovery use the same window. Show in Library in a log locates the paper in the main window while retaining the task result.

Drag a Paper Files icon or name to File Explorer or a compatible app to copy/open the real file. Drop files into Library to import them. Paper Files accepts drops across its column; internal managed-file drops use the move/ownership workflow and duplicate gestures are ignored. Cross-application behavior depends on the receiving application.

Folder renames, managed shortcuts, long filenames, copy races and interrupted transactions have Windows-specific handling. Open in Default App follows Windows file associations; Show in File Explorer reveals the file. There is no separate default-reader setting.

Browser and PDFs

Browser keeps its own website session. Home is local Favorites; tabs and Back/Forward retain browser-owned documents where available. Ctrl+L focuses the address bar, Ctrl+F opens Find, Ctrl+T creates a tab, Ctrl+W closes it, Ctrl+R reloads and Ctrl+[returns to the research workspace. Address suggestions use local history.

Save to Gewu reviews metadata, identity, file type and destination. A loaded PDF, including an embedded PDF, can be saved from its original response bytes. Use Loaded PDF never silently requests the file again. If those bytes are no longer available, reopen the PDF or explicitly use Get PDF. Supported download-type PDFs preview in the same tab.

PDF capture supports up to 128 MB. Save Download uses retained bytes for a loaded PDF; other explicit downloads use the current Browser session. The original publisher filename and main/supplement classification are retained. Science main-text validation and First Release classification are shared with macOS.

Only verified publisher or authorized repository sources are accepted for paper downloads; every redirect is checked. Sign in with your own publisher or institution account in Browser. Unknown sources and unsupported routes stop. These features do not bypass subscriptions or website verification.

Bookmarks supports HTML import/export and manual Sync from Chrome for one selected subtree. Existing local changes and source deletions are preserved and Chrome is not modified. Clear Monitor Cache affects the local research view, not Browser cookies or sign-ins.

Reading and AI Access

Space opens the built-in preview; Up/Down follows Paper Files and Esc closes it. PDFs scroll continuously, Ctrl+wheel zooms, and thumbnails jump to pages. Open in Default App provides the reader associated with Windows. Markdown supports collapsed YAML/source properties, wide tables/code and offline mathematical formulas without changing the original file.

Settings > AI Access is off by default. Create a named connection with explicit collection and operation permissions. The MCP adapter defines 24 tools, including folder browsing, read-only file delivery, delivery release, separately authorized uploads/imports, metadata and file/folder organization. Tools available to a connection depend on its grant.

Copy the generated MCP Configuration into your local AI client. The source desktop uses its .venv and local adapter; keep the App running. The URL file follows port changes after restart. Tokens are displayed only at creation and should not be shared.

get_paper_file supplies an authorized read-only client copy, never direct Library or SQLite access. Use delivery status/release to manage quotas. save_analysis appends a classified Markdown note and cannot edit earlier files or analyses. New write operations require separate permissions and writable folders. Upgrading does not expand an existing grant.

External authorized changes refresh the visible Library while preserving selection and reading position where possible. Gewu does not run an AI model or upload papers merely because AI Access is enabled. Review generated notes against the original sources.

Updates, recovery and platform scope

Before updating, close the App and retain a verified SQLite/file backup plus the matching source and shell. This upgrade preserves the existing Windows Library while adding schema 22. Do not open an upgraded Library with an older shell/source or substitute an older database.

The local service and workspace renderer have bounded recovery. Browser tabs and unsent website forms are kept when their separate browser process remains alive. Repeated failures stop and show a recovery message. An operating-system crash and unsaved research-form edits cannot be guaranteed recoverable.

Apple Passwords/AutoFill, Safari sync and macOS system Quick Look are outside the requested Windows scope. Real institution-authenticated publisher routes, every third-party drag target and other Windows hardware still require field validation.

Help > Contact Us opens info@gewu-insight.com; Help also links the product website. Logs are under the Library logs folder. This source desktop is a local development delivery; formal installer signing and distribution remain separate.