Gewu Insight

User Guide

Windows 1.0.0

October 8, 2026

Library · Paper Files · Publications
Journal · Subject · Author · Browser · AI Access

A complete Windows edition of the shared 49-topic manual. Interface names match the Windows application. The HTML edition supports topic search; this PDF has linked contents and bookmarks.

Contents

1 Orientation 5

1-1 Welcome . . . 5

1-2 Guided Tour . . . 8

1-3 Your First Session . . . 11

2 Product Concepts and Architecture 15

2-1 System Architecture at a Glance . . . 15

2-2 The Persistent Paper Object . . . 16

2-3 Why SQLite Is the Core . . . 18

2-4 Visible Research Files . . . 20

2-5 The Personal Research Workspace . . . 21

2-6 From Discovery to Durable Memory . . . 23

2-7 State, Scope, and Safe Change . . . 24

3 User Manual 26

3-1 Workspace Navigation . . . 26

3-1.1 Library Layout . . . 26

3-1.2 Navigate with Mouse and Keyboard . . . 26

3-1.3 Folders, Shortcuts, and Spaces . . . 28

3-1.4 Search, List View, and Table View . . . 29

3-2 Papers and Files . . . 30

3-2.1 Add Papers and Files . . . 30

3-2.2 Use Paper Details . . . 31

3-2.3 Edit DOI and arXiv Identifiers . . . 32

3-2.4 Refresh Info: One Paper, a Folder, or the Library . . . 33

3-2.5 Understand Paper Files . . . 35

3-2.6 Preview Files . . . 37

3-2.7 Choose File Types and the Default File . . . 37
3-2.8 Add and Classify Attachments . . . 39
3-2.9 Download and Sync Versions . . . 39
3-2.10 Move a Standalone File into Paper Files . . . 41
3-2.11 Delete and Recover Items . . . 42
3-3 Import and Transfer . . . 43
3-3.1 Use Folder Loader . . . 43
3-3.2 Make a Portable Desktop Copy . . . 45
3-3.3 Back Up and Upgrade . . . 45
3-4 My Publications . . . 47
3-4.1 My Publications . . . 47
3-5 Journal Monitor . . . 49
3-5.1 Journal Monitor . . . 49
3-6 Subject Monitor . . . 51
3-6.1 Subject Monitor . . . 51
3-7 Author Monitor . . . 53
3-7.1 Author Monitor . . . 53
3-8 Browser . . . 56
3-8.1 Browse, Bookmark, and Revisit Websites . . . 56
3-9 Settings and Safety . . . 61
3-9.1 Literature Data Sources . . . 61
3-9.2 arXiv Scope Settings . . . 62
3-9.3 Field Settings . . . 62
3-9.4 Preview Settings . . . 63
3-9.5 Default Add to Library Folder . . . 63
3-9.6 Website Links . . . 64
3-9.7 AI Access . . . 65
3-9.8 Naming and PDF Rename Rules . . . 72

3-9.9 How Gewu Insight Stores Files . . . 73

3-9.10 Local Data and Privacy . . . 74

4 Product Identity **76**

4-1 Visual Identity and Cultural Elements . . . 76

4-2 The calligraphic name . . . 76

4-3 The app icon and the seal-script watermark . . . 77

4-4 Why the three marks are used differently . . . 78

5 Technical and Operational Reference **79**

5-1 Keyboard Shortcuts . . . 79

5-2 Publisher and Network Access . . . 79

5-3 Startup, Monitor Cache, and Text Size . . . 80

5-4 Troubleshooting . . . 82

5-5 Storage Reference . . . 86

1 Orientation

1-1 Welcome

Gewu Insight is a local workspace for collecting papers, preserving their files and versions, and following journals, subjects, authors, and your own publications.

Windows 1.0.0 · October 8, 2026

Source-available research software. The Gewu Insight Academic and Non-Commercial Research License permits downloading, installing, building, running and modifying the software for academic/non-commercial research. Original and modified versions, derivative works and patches may be shared free of charge for those purposes under the same research-use terms, with retained notices and clearly identified modifications. Public research forks and pull requests within those terms need no separate permission. Commercial use, commercial redistribution, sublicensing and integration into commercial products or services require separate prior written authorization. Copyright © 2026 Lingyuan Kong and Zhengran Wu. All rights reserved except for those express permissions. Read the complete LICENSE, also included with the local distribution and in the application folder, before use. This is not an open-source license.

1-1.1 Why this workspace exists

Research rarely arrives as one clean collection. A paper may first appear in a feed, later acquire an arXiv version and a DOI, be downloaded under several filenames, reappear through an author's profile, and eventually become part of a project or your own publication record. Publisher pages, alerts, PDFs, folders, notes, and citation services each preserve only part of that history.

Gewu Insight is designed to keep those fragments connected. It treats discovery, identity, files, versions, organization, reading state, and provenance as parts of one continuing research process. The aim is not to accumulate the largest possible list. The aim is to preserve enough context that a useful paper remains understandable and usable months or years after it was first found.

1-1.2 Why the name 格物洞见

The name draws on the Chinese idea of 格物致知 and expresses a way of doing research shaped by physics: begin with real-world phenomena and experimental observations, and seek to understand what lies behind them.

Element	Role
格物 · **Gewu**	Investigate things as they occur in the real world. Let concrete phenomena, experimental observations, and questions from nature give research its starting point.
洞见 · **Insight**	Seek the patterns and mechanisms behind phenomena through physical pictures, intuition, imagination, and insightful guesses. Mathematics is a tool for developing that understanding.

The name expresses the research outlook that this workspace supports.

Gewu Insight keeps papers, versions, supporting files, and research notes connected so you can return to experimental results, compare physical pictures, and pursue emerging ideas. Read the full explanation in Visual Identity and Cultural Elements.

Investigate nature through experimental phenomena; seek insight through physical pictures and intuition.
（从实验现象中格物，以物理图像和直觉求洞见。）

1-1.3 Five design commitments

Principle	What it means
Local ownership	Your live database and managed research files remain in the selected local workspace. Online services contribute evidence; they do not own the workspace.
Visible evidence	PDFs and attachments remain real files that File Explorer, Preview, and other applications can inspect.
Continuity over time	A preprint, later DOI, publication version, annotations, and personal contexts can accumulate around one persistent paper object.
Explicit state and provenance	Completed, empty, partial, failed, downloaded, imported, and retried are different states. Sources and operational outcomes should remain visible.
Researcher control	Automation assists discovery and maintenance, but classification, interpretation, organization, and scientific judgment remain yours.

Local-first does not mean offline-only

The durable workspace is local, while supported discovery, metadata, profile, and download features may require network access and remain subject to source, publisher, and institutional availability. Verify uncertain matches and versions; the app does not bypass access controls.

1-1.4 Windows desktop edition

This manual describes Gewu Insight 1.0.0 for Windows. Install the versioned Setup.exe, then open **Gewu Insight** from the Start menu. The installer includes Python, .NET and application dependencies. It reuses Microsoft WebView2 or installs it from Microsoft when needed.

Requires 64-bit Windows 10 version 1607 (build 14393) or later, including 1803, or Windows 11. The x64 package does not support 32-bit Windows or Windows 10 on ARM.

The six workspaces share the same paper identities, file classifications and SQLite records. Windows supplies File Explorer, file associations, Recycle Bin, a built-in PDF reader and a WebView2 Browser. Apple Passwords/AutoFill, Safari source sync and macOS system Quick Look are not Windows features.

Your research files and SQLite records live in the selected **Gewu Database**, independently of the installed program and any development checkout. The default for a new database is %USERPROFILE%\Gewu Database; an existing database may be elsewhere. Use **File > Open Gewu Database** to locate the actual folder.

The startup selection is recorded in %USERPROFILE%\.gewu-insight\database-location.ini. SQLite owns the database identity and research state; the locator only remembers which database to open.

The default program folder is %LOCALAPPDATA%\Programs\Gewu Insight. Existing installation and Library selections take precedence. Updating the program does not move your Library; uninstalling retains research data.

1-1.5 What this guide covers

This guide follows the work you do in the app: put papers into the Library, organize them, manage publication versions and attachments, review new literature, and keep the database and files safe. It describes the current interface rather than the history of the project.

1-1.6 What Gewu Insight is—and is not

It is	It is not only
A local research workspace that connects discovery, identity, files, versions, organization, and durable state.	An RSS reader that forgets a result after it leaves the feed.
A visible file and resource system built around persistent paper identities.	A PDF folder whose filenames must carry every piece of meaning.
A personal research memory shared by Library, Spaces, publications, and monitors.	Five unrelated tools that happen to occupy the same window.
A system that records evidence and assists repeatable work.	A black-box ranking or summary engine that replaces scientific judgment.

1-1.7 Six main tabs

• **Library** — your managed papers, folders, spaces, versions, and related files.

• **My Publications** — your publication list, citation metrics, author roles, and export tools.

• **Journal Monitor** — papers published on a selected date, organized by journal and field.

• **Subject Monitor** — topic-based discovery from supported online sources and feeds.

• **Author Monitor** — monitored researchers, profile-linked discovery, and newly found work.

• **Browser** — Google search, websites, online PDFs, hierarchical bookmarks, and local browsing history.

1-1.8 One continuous research loop

Element	Role
Acquire **Find**	Journal, Subject, and Author Monitor introduce relevant candidates.
Identify **Recognize**	DOI, arXiv, title, authors, and source evidence are connected to a shared record.
Resolve **Preserve**	Metadata, files, versions, roles, paths, and provenance are made explicit.
Remember **Understand**	Library, Spaces, My Publications, reading state, and personal organization retain meaning.

What you save, read, classify, and follow becomes context for the next cycle. The five research views share this loop; Browser supplies a separate place to explore websites.

Important

SQLite is the source of truth for Gewu Insight. Do not replace, rebuild, or edit the database by hand. Use the app to move, classify, or delete managed items.

1-1.9 Choose a path through this guide

This is one comprehensive manual with three complementary reading paths. The **operational path** explains how to use the app; the **concept and architecture path** explains why the workspace is organized this way; and the **technical reference path** documents storage, database, network, migration, and troubleshooting details. They remain together so visible behavior, product principles, and implementation constraints do not drift apart.

If you want to	Continue with
Start using the app now	Read **Part I · Orientation**, then use **Part III · User Manual** as the operational guide.
Understand the product idea and architecture	Read **Part II · Product Concepts and Architecture**, followed by **Part IV · Product Identity**.
Maintain, migrate, or inspect the system	Use **Part V · Technical and Operational Reference**, with Part II for the underlying model.
Look up one operation	Use the topic list or press Ctrl+F to search this guide.
Prepare an upgrade or move to another computer	Read Back Up and Upgrade before changing the installation.

1-1.10 Open this guide

Choose **Help > User Guide** to open this searchable local manual. Search filters topics; Previous and Next follow the reading order. Use **Print Guide** inside the guide to open the complete PDF for reading or printing. Both editions work offline.

Choose **Help > About Gewu Insight** for the application version and build, original artwork, product description, credits, copyright and research-use license summary. Its **User Guide** link opens this manual; **GitHub** opens the project website.

This Windows edition retains all 49 shared topics and the linked Product Identity chapters. macOS screenshots are omitted because their title bars, menus and platform controls do not represent Windows.

1-1.11 Contact Us

Choose Help > Contact Us to open info@gewu-insight.com in your default email application. Include the installed version, affected workflow and steps to reproduce; omit passwords, tokens and private research data. Review and send the message yourself.

Official website: gewu-insight.com.

See also: Guided Tour · Your First Session · System Architecture at a Glance · How Gewu Insight Stores Files

1-2 Guided Tour

The top chooses a work mode; the panes move from context on the left to the active object and its evidence; the bottom preserves navigation and progress without reshaping the workspace.

1-2.1 Read the interface as a sentence

Gewu Insight uses a consistent left-to-right grammar. The exact number of panes changes with the task, but their meaning remains stable: choose a research context, narrow it to an object, inspect its evidence, then act. This lets a dense workspace remain predictable without hiding the underlying files and relationships.

Element	Role
Top **Choose a mode**	Library, My Publications, one of the three discovery monitors, or Browser.
Left **Set the context**	A root, folder, date, journal, subject, author, or filter defines the working scope.
Center **Select the object**	Browse folders, paper lists, search results, or the resources belonging to one paper.
Right **Inspect and act**	Read metadata and evidence; open, download, classify, refresh, export, or reorganize.

The bottom edge is reserved for progress, breadcrumbs, and view controls so background work does not repeatedly resize the main content.

1-2.2 The Library window

Area	Purpose
1. Source tabs	Library, shortcuts, and independent Spaces.
2. Folder columns	Move from broad folders to the selected item.
3. Item column	Papers, files, and child folders in the current location.
4. Paper Files	One flat list of resources with independent type, annotation, source, and Default status.
5. Details	Metadata, identifiers, actions, citations, and folder membership.

1-2.3 Follow selection from broad to specific

A selected item does not always mean “open this file.” In a folder column, selection establishes the next level of context. In the item column, it identifies the active paper or standalone file. In Paper Files, it identifies one resource inside the active paper bundle. Paper Details then describes the shared work rather than merely repeating the selected filename.

Selection	What becomes active	What remains shared
A Library folder	Its child folders and items.	The papers keep their identities, resources, and other placements.
A paper in the item column	Its Paper Files bundle and Paper Details.	The same work can still belong to other folders, monitors, or My Publications.
A resource in Paper Files	That version or attachment for preview, classification, or file action.	The parent paper remains the active scholarly object.
A Monitor result	Its discovery evidence, report, and available actions.	Adding it to Library reuses the cataloged paper record when identity has been resolved.

1-2.4 Tabs across the top

Click a top tab to change workspaces and focus that tab. Left/Right then switch tabs; Down enters the page. Monitors show calendars, filters and papers. Browser has a Bookmarks/History sidebar beside a native webpage. Progress messages stay in reserved status areas.

The top-right search control expands on hover or focus. Each research workspace retains its query; clear it with ×. Use the Windows title bar to move, maximize or restore the window.

Window movement, snapping and virtual desktops follow your Windows configuration. Start a drag from the native title bar; tabs and search controls have their own actions.

Area	Primary question	Typical next action
Library	What have I chosen to keep, and how is it organized?	Read, classify files, move, copy, attach, or recover.
My Publications	Which works are mine, and what authorship or citation context do they carry?	Verify roles and metrics, refresh, order, or export.
Journal Monitor	What appeared in selected journals on a given date?	Filter, inspect, download, or add to Library.
Subject Monitor	What matches a defined scientific topic across supported sources?	Review source evidence and preserve useful results.
Author Monitor	What is new in the work of a researcher I follow?	Inspect the author relationship, open the work, or add a Library placement.
Browser	What can I find on the web without leaving this workspace?	Search Google, read a website or online PDF, save a bookmark, or revisit history.

1-2.5 Watch one paper move through the workspace

Element	Role
Discovered	A Monitor records where and when the work was observed.
Cataloged	Identity evidence connects the observation to a persistent paper record.
Organized	A Library folder, Space, or My Publications adds personal context.
File-backed	Downloaded or attached resources become available in Paper Files and File Explorer.

These states can overlap. A cataloged Monitor result may have no local file, and a downloaded file does not have to belong to a Library folder immediately.

1-2.6 Resize a pane

1. **Point to a divider.** Move the pointer to the vertical line between two panes.

2. **Drag the divider.** Move it left or right until the useful content fits.

3. **Release.** The app uses the new working width without changing the underlying files.

Note

The right-side Paper Details area scrolls independently. A long author list or citation section does not move the Library columns.

1-2.7 Recognize stable and temporary state

Selection, keyboard focus, menus, and scroll position are temporary interface state. Paper identity, placements, resource properties, read state, provenance, and completed operations persist when saved. A breathing progress message means work is active, not that a paper or folder was created.

Keep the active context visible

Before moving, deleting, or attaching, check the focused pane and selected Paper Details. Similar names can identify different targets: a paper placement, one Paper Files resource, or a standalone file.

See also: Library Layout · Navigate with Mouse and Keyboard · Keyboard Shortcuts

1-3 Your First Session

Start with one paper, confirm its identity and context, then inspect or add a local file when the work is file-backed.

1-3.1 Open your Gewu Database first

1. Install the versioned Setup.exe and open **Gewu Insight** from the Start menu. Setup selects the program directory and database directory independently. A configured installation remembers its database.

2. During installation or first-start database setup, choose **Use existing Gewu Database** for an existing collection. Select the whole folder containing data/paper_monitor.sqlite, not the SQLite file or the inner data folder.

3. Choose **Create new Gewu Database** only for a new collection, using a new or empty folder. This is separate from creating a Space in the current Library.

4. Use **File > Open Gewu Database** to reveal the active folder. This reveals the current database in File Explorer; it does not switch databases.

If the remembered database is unavailable, reconnect its disk or locate the intended existing folder. Gewu does not silently replace it with an empty database. A populated database moved to a different path also needs its managed file references and Windows shortcuts verified; selecting a copied folder alone is not a migration.

1-3.2 Choose your starting route

You do not need to prepare a perfect record before beginning. Start from the strongest evidence you already have, then let the paper object become richer over time.

You already have	Start here	What Gewu Insight does first
A local PDF or another research file	Drag it into the target Library folder, or use the folder's add command.	Preserves a visible file, creates a catalog record, and attempts to extract or resolve identity evidence.
A DOI, arXiv identifier, supported URL, or title	Choose **Add Paper** in the target folder and enter the evidence.	Creates or reuses the metadata record. Download or attach a PDF separately when needed.
A useful result in Journal, Subject, or Author Monitor	Select the result and choose **Add to Library**.	Adds a Library placement for the cataloged paper while retaining its discovery provenance.

External originals stay separate

Folder Loader and ordinary file import are designed to preserve the external source rather than silently reorganize it. The managed copy and the source path can both remain part of the provenance.

1-3.3 Add and inspect a paper

1. **Open Library.** Select an existing folder, or create one from the context menu.

2. **Add a paper.** Drag a PDF into the folder, or open the target folder, Right-click blank space in its contents, choose **Add Paper**, and enter a DOI, arXiv identifier, supported URL, or title.

3. **Select the new item.** Paper Details appears at the right. Gewu Insight attempts to identify the work. A local file is recorded only when you imported one or a supported download succeeded.

4. **Check DOI and arXiv.** Edit either identifier and press Return. Wait for the green **Identifier updated** or **Identifier saved** message, then use **Refresh Info** to retrieve metadata.

5. **Inspect the available evidence.** If a local PDF exists, choose **Open in Default App**, or enter Paper Files and press Space for Preview. If no file exists yet, use **Open Website** or download a supported version when one is available.

The paper now has a cataloged paper record, a stable Gewu Key, and a Library placement. A cataloged paper may have no local file; that state is valid. A file resource exists only after a file is imported, downloaded, or attached. An independent non-PDF file instead uses an internal storage key without a public Gewu Key in Paper Details.

1-3.4 Understand what may now exist

Element	Role
Always **Catalog record**	Title, authors, identifiers, source evidence, and a stable internal paper identity.
Always **Library placement**	A relationship that makes the paper visible in the folder you selected.
When file-backed **File record**	Type, annotation state, source, stored path, fingerprints, and Default status when known.
When file-backed **Visible local file**	The actual PDF or attachment that File Explorer and Preview can open.

A cataloged-only paper legitimately has the first two objects and no local file. A file-backed paper also has resource metadata and real bytes. These objects cooperate, but they are not interchangeable.

1-3.5 Verify the identity before enriching it

1. **Compare the title and authors with the PDF.** A similar title is useful evidence but not sufficient proof.

2. **Check the DOI and arXiv fields.** A work can have both. Correct an inaccurate identifier before refreshing more metadata or downloading another version.

3. **Read the source and journal information.** Confirm that a publication record belongs to this work rather than a cited paper or a similarly named article.

4. **Keep uncertainty visible.** It is safer to leave a field empty than to confirm a plausible but wrong identifier.

1-3.6 Complete the first Paper Files bundle

A cataloged-only paper may have no local file, and nothing is missing merely because Paper Files is empty. Continue with these steps after you import, download, or attach a file and the paper becomes file-backed.

1. **Select the paper to show Paper Files.** Cards initially show File type and size. Click a card's size footer to show or hide Annotation and Source.

2. **Classify the available file.** Use its small type, annotation, and source controls. Do not infer these facts from the filename alone.

3. **Add related material if you have it.** Add a supplement, annotated copy, note, presentation, data file, code file, or other attachment. Import first, then classify the resource.

4. **Check the default file. Open in Default App** and Library preview use the resolved default when applicable. Selecting **Set as Default** preserves the resource identity and content. The managed Default becomes the main file, including for non-PDF formats; the other files remain in Associated Files. An automatic fallback is available even before you choose a Default manually.

5. **Reveal one file in File Explorer.** Choose **Show in File Explorer** and confirm the real managed file exists where the database expects it.

Principle	What it means
Cataloged and organized	The shared paper record and Library placement are durable even when no local file has been added.
File-backed	After a file is added, its independent file properties and physical bytes can be inspected separately from paper identity and folder context.

1-3.7 Optional: verify shared identity

Copy the paper to a second Library folder, then select it there. The title, Gewu Key, Paper Files, and metadata should remain the same because the second folder contains another placement for the shared paper—not an unrelated duplicate. Delete only the extra placement when you are finished with the check.

1-3.8 Next useful actions

• Use **Download** when a better publication version is available.

• Use **Paper Files** to classify imported PDFs or add notes, data, slides, and supplements.

• Add the paper to another folder without creating a second independent work record.

• Back up the project before a large import or migration.

1-3.9 Use the collection while writing

1. **Collect a working set.** Create a project folder or Space and copy relevant papers into it. Copies share the same Gewu Key and Paper Files.

2. **Check the version you cite.** Correct DOI/arXiv if needed, use Refresh Info, and inspect the actual Default PDF. Metadata refresh does not download a publication PDF.

3. **Keep reading notes with the paper.** Add your Markdown notes through **Add File**, or explicitly ask an authorized AI connection to append an analysis. Review the note against the source.

4. **Reuse references.** Use **Copy Code** for BibTeX or **Copy Reference** where shown. Check names, publication year and version in the resulting manuscript. **Export List** in My Publications exports your publication list; it is not a general manuscript editor.

5. **Preserve your baseline.** Make a closed, complete backup before large maintenance operations. Normal reading and writing do not require repeatedly refreshing the whole Library.

1-3.10 Finish with a safe baseline

Your first session is complete when you can answer two questions for every paper: What is this work, and why is it in this folder? If the paper is file-backed, answer two more: Which file is the default, and where are the real bytes? Paper Details, Paper Files, and File Explorer should answer the applicable questions without contradicting one another.

Principle	What it means
Identity checked	The title, authors, DOI, and arXiv evidence do not point to different works.
Placement understood	The Library folder expresses personal organization, not a second scholarly identity.
Resource classified when present	If the paper is file-backed, its files can have independent type, annotation, and source descriptions.
File visible when present	If the paper is file-backed, the expected managed file opens from the app and can be revealed in File Explorer.

Create the backup habit early

Before a major import, upgrade, or migration, quit Gewu Insight and back up both the SQLite database and the managed file roots. A database-only copy lacks some bytes; a files-only copy lacks the relationships and state that make the workspace intelligible.

See also: Add Papers and Files · Use Paper Details · Understand Paper Files · Back Up and Upgrade

2 Product Concepts and Architecture

2-1 System Architecture at a Glance

Gewu Insight is a local research system that coordinates structured state, visible files, and a personal workspace. It is not simply a web page placed in front of a folder.

2-1.1 How the parts cooperate

Element	Role
Native desktop shell	Starts the app, owns Help and Browser, and connects Preview, File Explorer, and native file actions to the portable core.
Personal Research Workspace	Library, Spaces, My Publications, and the three Monitor views you see and operate.
External research sources	Publisher pages, feeds, metadata services, scholarly profiles, and preprint services.
Local application service	Interprets your actions, resolves identities, schedules network work, and coordinates database and file changes.
SQLite state core	Owns identity, relationships, resource descriptions, preferences, provenance, and durable workflow state.
Visible Research Files	PDFs, versions, supplements, notes, data, and other files that remain inspectable in the native file manager and document applications.

The interface sends an intention to the local service. The service validates it and coordinates SQLite with the relevant files; the UI does not directly treat a File Explorer folder as the database.

The desktop window presents the local Python service and SQLite workspace. The Windows shell supplies File Explorer, file associations, Recycle Bin, PDF reading and WebView2 browsing. Network sources contribute metadata and files while the durable workspace stays local.

2-1.2 What each persistent layer answers

Browser is a separate web surface. Its native WebView2 views load websites directly, not through the Python service. The local service stores bookmarks and history in SQLite; WebView2 manages a separate persistent website profile. External pages do not receive the Library's local API bridge. Visiting a page, saving a bookmark, or downloading through Browser does not create a paper or assign a Gewu Key; import the paper explicitly.

Layer	Questions it answers	What it does not decide alone
SQLite	What is this paper? Where is it referenced? Which resources belong to it? What happened in the last operation?	It does not contain the bytes of your PDFs and attachments.
Filesystem	Which real files can the native file manager, PDF reader, or another application open?	A filename or folder position alone does not define paper identity, version priority, or monitor membership.
Personal Research Workspace	How should the shared state be presented for discovery, reading, organization, and action?	It is a projection of saved state, not a separate copy of the collection.

System relationship

Persistent research workspace = structured SQLite state + visible research files, coordinated by the local application.

2-1.3 Why this separation matters

A paper can appear in a Monitor, the Library, a Space, and My Publications without becoming four unrelated papers. It can also acquire a DOI after first arriving as an arXiv preprint, or acquire a publication PDF while retaining earlier versions. The database preserves continuity across those changes; visible files preserve user ownership and inspectability.

Terminology

This guide uses **Personal Research Workspace** for the on-screen projection and **Visible Research Files** for assets visible to the native filesystem. These are explanatory terms, not menu names. Together they form the visible workspace, but they serve different roles.

See also: The Persistent Paper Object · Why SQLite Is the Core · Visible Research Files

2-2 The Persistent Paper Object

Gewu Insight treats a scholarly work as an object that persists through discovery, publication, file changes, and personal organization—not as a temporary search result or a single PDF.

2-2.1 One identity can accumulate evidence

Element	Role
Identity evidence	DOI, arXiv identifier, title, authors, journal, dates, and source identifiers.
Resources	Publication PDFs, preprints, accepted manuscripts, supplements, annotations, and attachments.
Contexts	Library folders, Spaces, My Publications, and Monitor relationships.
Durable state	Read status, metadata quality, provenance, download state, retries, and timestamps.
One shared paper identity · one stable Gewu Key	The internal identity stays stable when an external identifier, filename, folder location, or preferred PDF changes.

Identifiers help resolve and enrich a paper, while the Gewu Key provides continuity inside Gewu Insight.

The central record uses an internal paper identity. A DOI or arXiv identifier is important evidence attached to that identity, but neither is a safe universal primary key: an early preprint may have no DOI, an imported PDF may initially have no reliable identifier, and an incorrect identifier may later be corrected.

2-2.2 Do not collapse four different things

Object	Meaning	Example
Paper record	The shared scholarly identity and normalized metadata.	The work that later connects arXiv and a journal DOI.
Placement or relation	Why and where the paper appears in your workspace.	A Library folder entry, a shortcut, a My Publications role, or an Author Monitor association.
Resource record	A described file or retrievable version belonging to the paper.	Preprint v2, published version, supplementary material, peer review file, or data file.
Physical file	The bytes stored at a real path on disk.	A PDF under data/Library or an associated attachment.

System relationship

Paper record ≠ workspace placement ≠ resource record ≠ physical file.

2-2.3 What happens when the same paper is found again

Journal, Subject, and Author Monitor can encounter the same work from different directions. Identity resolution is designed to reuse one shared paper record and add source or context relationships. Copying a paper to another Library folder likewise creates another placement rather than a second independent identity. Its metadata, Gewu Key, versions, and attachments remain shared.

When the available evidence is insufficient or contradictory, separate candidates can remain until their identifiers or metadata are corrected. Automatic metadata enrichment retains conflicting evidence instead of overwriting a saved identity or forcing a merge. File import follows a distinct preservation rule: a PDF matched to an existing paper is kept in its Paper Files and shown in the chosen folder, even if its detected metadata conflicts. Review that assignment and use the file reassignment commands when necessary. The shared-object model is the resolution target; it does not justify merging uncertain works merely because their titles look similar.

A network observation can be transient while acquisition is running. Once a result is cataloged as a shared paper record, it has a Gewu Key even if a particular Monitor view does not display that key. A Monitor result may still have no local Paper Files because no file has been downloaded or attached; adding it to Library creates a visible placement rather than inventing a new scholarly identity.

Gewu Insight also manages independent non-PDF files, such as Markdown overviews, spreadsheets and images. These ordinary files have an internal storage key so that their location and attachments remain trackable, but the App does not display a scholarly Gewu Key for them. A PDF paper can have a public Gewu Key before its DOI or arXiv identity is known; a standalone Markdown note does not become a paper merely by being imported.

2-2.4 Identity corrections should preserve continuity

Editing a DOI or arXiv identifier changes evidence on the existing paper. It should not silently make an unrelated second paper, rename every file, or discard your folder placements and read history. When evidence conflicts, inspect the title, authors, venue, and files before confirming the correction.

Important

Similar titles are not proof of identity, and matching filenames are not proof that two resources are the same. Use identifiers, metadata, file fingerprints, and provenance together.

See also: Edit DOI and arXiv Identifiers · Understand Paper Files · The Personal Research Workspace

2-3 Why SQLite Is the Core

SQLite is the source of truth for Gewu Insight because it preserves the identity, relationships, resource registry, and operational memory that neither a filename nor an exported report can express.

2-3.1 Four families of structured state

Element	Role
SQLite state authority	A local transactional database stored with the project.
Identity and metadata	Shared papers, external identifiers, normalized title and authors, dates, fields, and Gewu Key.
Relationships and context	Library placements, folder tree, Spaces, My Publications, and Monitor associations.
Resource registry	File types, paths, source evidence, hashes, annotation state, and default preferences.
Operational memory	Fetch runs, import batches, source tasks, reads, settings, failures, and retries; also Browser bookmarks and history.

Table names and schema versions can evolve; these four responsibilities are the stable user-level model.

The database does not store the PDF bytes themselves. It stores enough structured information to understand the files: which paper they belong to, what file type they represent, where they are, where they came from, whether they are annotated, and which one should be used by default.

2-3.2 Why a folder scan is not an equivalent database

File Explorer can show that paper.pdf exists. It cannot reliably say whether it is a published version or a preprint, whether it is annotated, where it came from, whether the same work is also in My Publications, or which file is the manual default. Those facts live in SQLite.

2-3.3 Transactions, relationships, and WAL

Database mechanism	User-facing purpose
Transactions	Keep a multi-step state change together so a partly applied edit is less likely to become the visible truth.
Foreign-key relationships	Connect a resource or placement to the correct shared paper instead of relying on a coincidentally similar filename.
WAL (write-ahead logging)	Lets foreground reading and background updates coexist more safely than repeated full-file rewrites.
Schema migration	Adds new structures and backfills required state during an upgrade rather than asking the user to rebuild the database.

WAL improves normal concurrency; it is not a substitute for a coherent backup. Close Gewu Insight before copying its live database, and back up the managed files with it.

2-3.4 Durable preferences and shipped defaults

Journal subscriptions are durable SQLite state as well. The database preserves which journals are enabled, their identifiers and source settings, and their display order. The journal catalog shipped with a newer app version is a set of defaults, not an instruction to overwrite your personal list.

On the first upgrade that introduces durable subscriptions, Gewu Insight seeds the database from the existing journal configuration and history. After that one-time seed, adding, disabling, restoring, or reordering a journal changes the database record. Replacing source code or rebuilding the app does not silently re-enable a journal you removed or discard journals you added.

Cross-layer changes

SQLite transactions protect database state. A file move and its database update cannot be one native SQLite transaction, so the local service coordinates the steps and uses validation or compensating recovery when a filesystem operation fails.

2-3.5 Exports and provenance

JSON, HTML, Markdown, Word, LaTeX, and PDF outputs are derived artifacts. They can be regenerated, shared, or inspected, but editing them does not alter the source records. Raw source evidence may also be retained inside SQLite for provenance; this does not turn an external JSON export into a second source of truth.

2-3.6 Paper-level Monitor provenance

Normalized paper-source observations are the authority for how a canonical paper was encountered. Each observation identifies a source kind, provider name, and stable source key, and keeps first-seen and last-seen times. The same paper and effective source update one observation instead of increasing the provenance count indefinitely.

Journal Monitor also connects each observed paper to the relevant fetch run. The run supplies the journal, requested date window, status, and timing; the paper-level observation records that the reporting source saw this particular work. Subject and Author Monitor relationships can point to the same canonical paper, so three discovery routes add context without manufacturing three scholarly identities.

A bibliographic metadata refresh can add a newly proven source, but it cannot erase an earlier Journal, Subject, or Author observation. Display counts and the older raw-source list are compatibility projections of the normalized observations rather than an independent truth. When two paper identities are safely merged, their source observations move to the surviving canonical paper and duplicate observations converge.

Discovery is not storage

A provenance relationship does not by itself create a Library placement or a local PDF. It records how the work entered view. Organization and file acquisition remain separate, explicit actions.

2-3.7 What the app does during an upgrade

On startup, the storage layer reads the database schema version, checks for required tables and fields, applies additive migrations in order, ensures required roots exist, and backfills stable keys or resource records where older data needs them. A normal migration preserves paper identities, folder placements, monitored-journal choices, fetch provenance, and file paths. This is why a project upgrade should preserve the existing database and files rather than replace them with an empty database.

Do not edit the live database manually

A seemingly small manual change can violate a relationship that is not visible in one table. Use the app for normal work and make a closed, complete backup before any diagnostic intervention.

See also: Back Up and Upgrade · Local Data and Privacy · Storage Reference

2-4 Visible Research Files

Your PDFs and attachments remain real local files. Gewu Insight adds a resource model around them so several versions and related materials can belong to one paper without hiding them inside an opaque cloud library.

2-4.1 One paper, one file bundle

Element	Role
Persistent Paper Object	Owns the resource relationships and decides which usable file is the default.
Default file	The automatically ranked or explicitly preferred valid file used by Open in Default App and Library preview.
Associated Files	Earlier versions, supplements, annotated copies, presentations, notes, data, code, images, and other attachments.
Paper Files	Flat peer records with independent type, annotation state, and source.
Supplements	Publisher or author-provided supporting files.
Files and figures	User material such as notes, slides, data, code, and extracted or attached images.

The Paper Files pane presents this as a compact bundle rather than another File Explorer hierarchy.

2-4.2 Managed and linked resources

Storage mode	Meaning	Safe expectation
Managed	The active stored path is inside the Gewu Insight project data area.	Move, classify, replace, or delete it through the app so paths and relationships change together.
Linked	The active stored path remains outside the managed project data area.	Availability depends on that external path, and the app should not silently reorganize it.

A resource can be managed while retaining a separate external source path as provenance. The existence of that source path does not by itself make the managed copy a linked resource, and the external original remains protected.

Folder Loader is a migration-oriented workflow. It imports a visible collection as a collection instead of asking you to classify every incoming file as an attachment before identity resolution. The original source path and the managed result remain conceptually distinct.

2-4.3 How the default file is resolved

An explicit manual default takes precedence while it remains available and valid. Otherwise, usable files are ranked as Corrected published version, Published version, Accepted manuscript, then Preprint. If none is available, Unknown or Other files provide a stable fallback: prefer the existing main file, otherwise the earliest PDF, otherwise the earliest remaining eligible file. No publication type is inferred from this fallback.

Correction notices, supplements, peer review files, Perspective, News and Views, Summary, Analysis, Source Data and Source Code do not become the automatic default. You may choose an available valid resource manually. Missing files, Invalid file and unresolved identity-conflict files are excluded from automatic selection; some bundles can therefore have no eligible automatic Default.

Published files

The user-facing type is **Published version**. A later formal correction can be classified as **Corrected published version**; the correction notice itself remains a separate peer.

2-4.4 Fingerprints and annotations

In the normal App PDF import, attachment and download workflows, exact SHA-256, content-oriented fingerprint, annotation count, and annotated state are computed as the resource is registered. They do not depend on a later refresh. Exact SHA-256 answers “are these bytes identical?” Adding a highlight or note normally changes those bytes. The content fingerprint is designed to recognize the same underlying document while discounting annotation-only changes, allowing clean and annotated copies to be related without treating them as blindly interchangeable.

Gewu Insight counts user-created comments and markup—such as highlights, notes, drawings, stamps, and form edits—as annotations. Structural PDF elements such as publisher hyperlinks, internal navigation links, and ordinary page actions do not make a freshly downloaded publisher or arXiv PDF **Annotated**.

An exact duplicate can be reused instead of stored twice. A clean PDF and an annotated copy may have different exact hashes but the same content fingerprint; both can be retained when the annotation state is meaningful.

2-4.5 Why File Explorer and the UI do not look identical

The filesystem must expose practical paths and folders; the UI must expose the meaning of one paper bundle. A Library paper can therefore retain a compatibility primary file in the visible topic folder while related files live under a mirrored Associated Files path. Paper Files deliberately presents all resource records as flat peers instead of mirroring those physical directories.

Important

Do not manually move or rename managed resources in File Explorer. The bytes may still exist, but the saved path and live workspace can disagree. Use an app-supported move, repair, or restore; do not assume a restart will rediscover an arbitrary manual move.

The separate MCP import workflow requires metadata from the AI and performs file integrity checks without the full PDF identification or image-fingerprint workflow. It never starts Resolve as part of import.

See also: Understand Paper Files · Choose File Types and the Default File · How Gewu Insight Stores Files

2-5 The Personal Research Workspace

The five research views—Library, My Publications, Journal Monitor, Subject Monitor, and Author Monitor—share research objects. Browser is the sixth main tab, with its own website session. Moving between research views does not reset a paper's identity.

Element	Role
Journal Monitor	Discovers work by publication venue and date.
Subject Monitor	Discovers work through topic definitions and supported feeds or searches.
Author Monitor	Discovers work through a researcher relationship.
One shared paper identity	Metadata, identifiers, resources, provenance, and state accumulate here.
Library and shortcuts	A durable managed collection with logical placements and fast entry points.
Spaces	Independent organizational roots for projects, courses, or collaborations.
My Publications	Your authorship, role, metrics, ordering, and export context on the same paper.

The same paper can participate in several contexts. Each context adds meaning; it does not require an unrelated duplicate record.

2-5.1 Views are relational projections

A Library folder answers “where do I organize this?” My Publications answers “how does this relate to my authorship?” Author Monitor answers “how does this relate to this researcher?” These are different relationships to the same possible work. The interface queries those relationships and projects the relevant controls, status, and files for the current task.

2-5.2 Library placements and shortcuts

A paper can have more than one Library placement. Copying it to another folder reuses the shared identity and resources. A shortcut tab is another entry point to a Library location, not another paper collection. A Space is an independent organizational root, but papers placed there can still reuse the same identity model.

2-5.3 Discovery does not require immediate file management

A Monitor result may remain a discovery relationship with metadata and status but no local Paper Files. A cataloged work already has a Gewu Key, which Author Monitor also shows. Downloading or attaching a file creates a resource relationship; adding the paper to Library creates a managed placement. Neither action should manufacture a second work merely because the user entered from another tab.

2-5.4 Why the same action can have different scope

Removing an author from Author Monitor removes that monitored-author relationship. Removing a shortcut removes an entry point. Moving a Library placement changes organization. Deleting a managed resource changes the paper's file bundle. The selected view supplies scope, while SQLite preserves what remains shared.

A useful mental model

The UI shows a personal map of a shared object graph. It is “visible” because you can navigate and act on it, but SQLite—not pixels on the screen—preserves the graph.

See also: Folders, Shortcuts, and Spaces · My Publications · State, Scope, and Safe Change

2-6 From Discovery to Durable Memory

Gewu Insight connects monitoring, identity resolution, version handling, and personal organization into one repeatable research loop.

Element	Role
1. Acquire	Journal, Subject, Author, Folder Loader, or a direct identifier introduces a candidate.
2. Identify	DOI, arXiv, title, authors, source evidence, and existing records are reconciled.
3. Resolve	Metadata, file types, annotation states, sources, paths, hashes, and a default preference are established.
4. Remember	Placements, authorship, reading state, provenance, completion, and failures persist.

The loop is continuous because a work can acquire better evidence, a new publication version, or a new personal context later.

2-6.1 A paper can change without losing its history

1. **Acquire an early work.** Subject Monitor finds an arXiv preprint. Its source and discovery context are stored.

2. **Identify the work.** The title, authors, and arXiv identifier connect it to one shared paper identity.

3. **Resolve its first resource.** A preprint PDF becomes the automatic default because no higher-priority file is available.

4. **Remember your context.** You add it to a Library folder, read it, and attach notes or data.

5. **Acquire new evidence later.** Journal Monitor or a metadata refresh finds the published DOI. Use Download, or open the publisher PDF in Browser and choose Save to Gewu, to acquire the file.

6. **Resolve without erasing.** The published file becomes the automatic default unless a manual choice is sticky; the preprint and its provenance remain peer records.

2-6.2 Operational state is part of scientific memory

A result count alone is ambiguous. The app distinguishes work that was never attempted from work that completed with no results, partially completed, failed, or entered a cooldown before retry. It also remembers imports, downloads, metadata refreshes, source tasks, and read state so the next action can be informed rather than blindly repeated.

State	Meaning	Reason to preserve it
Empty and complete	The requested source or date was checked and returned no matching records.	Prevents “zero” from being mistaken for “not run.”
Partial	Some sources completed while another did not.	Allows a targeted retry instead of discarding useful completed work.
Failed	An operation produced a specific error.	Makes the failure visible and avoids pretending the result is authoritative.
Cooldown or retry scheduled	A remote service asked the app to wait or a transient error needs backoff.	Reduces repeated traffic and protects normal foreground use.

2-6.3 Background work should not seize the foreground

Fetches, metadata refreshes, and imports report progress in reserved status areas and save their state. You should still be able to browse already stored material. Where callers share an online service, service-specific pacing, locks, cooldowns, and retry policies coordinate their requests. These controls reduce unnecessary traffic; they cannot guarantee that a publisher will never rate-limit or block a network address.

The loop is user-directed

Gewu Insight preserves the consequences of what you monitor, save, read, ignore, classify, and publish. It does not silently replace your research judgment with an invisible global keyword filter.

See also: Journal Monitor · Subject Monitor · Author Monitor

2-7 State, Scope, and Safe Change

A safe local research workspace changes only the object and relationship you intended while preserving shared identity, resources, provenance, and recoverable state.

2-7.1 Eight invariants behind normal operations

Principle	What it means
One shared identity	The same scholarly work should not fragment merely because several sources or folders found it.
Many contexts, not blind copies	Folders, Spaces, monitors, and My Publications add relationships around the shared paper.
Deletion has scope	Removing one relationship should not destroy unrelated relationships or shared resources.
State survives restart	Saved reading and workflow state, retries, failures, versions, and provenance are durable.
Repeated operations converge	Refreshing, importing, or downloading the same evidence should not create endless duplicates.
Good metadata is protected	A weak or empty response should not silently erase stronger saved evidence.
Database and files agree	Saved resource paths should point to the intended real files after an app-managed move.
Failure remains inspectable	Deletion, import, move, and network failure should preserve enough state to recover or retry.

2-7.2 Read an action by its scope

Action	Intended scope	What should remain
Remove an Author Monitor profile	The monitored-author relation and its profile context.	Shared papers, Library placements, My Publications, and managed files.
Remove a shortcut	That fast entry point.	The underlying Library folder and its papers.
Copy a paper to another folder	Add another placement.	One shared paper identity and resource bundle.
Move a paper in the app	Change its managed placement and corresponding stored paths.	Gewu Key, metadata, versions, and associations.
Make another file default	Change the reading preference; the selected managed file becomes the main file.	Paper and resource identity, file contents and all other resources. The previous main file is retained in Associated Files, including when the new Default is not a PDF.
Delete an associated file	That resource relationship and its managed file, subject to confirmation.	The paper identity and unrelated resources.

Recycle follows active ownership. As long as any normal Library, Space or My Publications placement uses a paper, its original must remain outside the local Recycle directory. Removing a folder applies this rule to its whole subtree. Re-adding a recycled paper to a normal location brings its original back out, with SQLite paths and shortcuts updated together. See Delete and Recover Items for the separate rules for placements, individual attachments and permanent deletion.

2-7.3 Recovery is part of the design

Recycle keeps ordinary removals recoverable. Import batches and operation status provide evidence about what ran. Resource paths, hashes, and provenance help diagnose missing or duplicate files. The app can migrate older storage structure forward, but migration is not a reason to discard the previous database or original files.

2-7.4 Back up one coherent research asset

A reliable backup contains the SQLite database and the managed file roots from the same closed application state. Copying only the database preserves descriptions without every artifact; copying only folders preserves bytes without all identities, relationships, classifications, and operation history. A portable desktop copy is useful for sharing visible folder material, but it is not automatically a complete live-workspace backup.

Before a major update or migration

Quit Gewu Insight, preserve the entire project data set, verify the backup can be read, then update the software in place. Do not create a fresh empty database and attempt to reconstruct the workspace from export files.

See also: Delete and Recover Items · Back Up and Upgrade · Troubleshooting

3 User Manual

3-1 Workspace Navigation

3-1.1 Library Layout

The Library uses a File Explorer-style column view, but the database—not the visible folder alone—defines the paper and its relationships.

Read the columns from left to right

1. **Source:** the main Library, a shortcut, or a Space.

2. **Folders:** each selection opens its children in the next column.

3. **Items:** the papers and other files in the selected folder.

4. **Paper Files:** shown only when a paper or managed file can expose related files.

5. **Paper Details:** metadata and actions for the selected work.

Use the breadcrumb

The breadcrumb at the bottom displays the full managed path. A shortcut shows the real ancestry from Library or its independent Space root, including folders above the shortcut target. Its alias does not replace that path. Hover over the path to read it in full when space is limited. The segments are informational; use the columns or Left Arrow to navigate to a parent. The **List View / Table View** control at the lower right changes the representation of items without moving them.

Follow background work in the bottom bar

Folder Loader, batch Refresh Info, and individual downloads or refreshes have separate activity indicators. A long batch stays visible alongside a smaller operation instead of combining their messages. Indicators share the available footer width, shorten long text with an ellipsis, and keep navigation controls available. If many tasks no longer fit, scroll the indicator area horizontally. Hover over an indicator to read its full message and available task details. The activity dot marks work in progress; a paused task remains visible without that running animation.

The footer's **Details** opens the current Loader operation, or an active/paused Refresh Info task when no Loader notice is present. For a particular saved refresh, use **Loader > Refresh All Metadata** and select it under **Refresh tasks**. These task details are separate from the right-side **Paper Details**. See the complete close, return and stop workflow.

Folder Details

When you select a folder, the right side shows its name, type, and the number of child folders and items. This is informational; it is not another folder level.

See also: Folders, Shortcuts, and Spaces · Search, List View, and Table View · Understand Paper Files

3-1.2 Navigate with Mouse and Keyboard

Library and Space columns form one keyboard path with Paper Files. Focus moves into Paper Files with the Right Arrow and returns to the selected paper with the Left Arrow.

Move through folders and papers

• Press ↑ or ↓ to change the selection in the focused column.

• Press → on a folder to enter it.

• Press ← to return to its parent.

• Double-click a Library paper row to open its Default file: PDFs open in the Windows default PDF application; other formats use their Windows application. An unclassified legacy import falls back to its available current file.

Move between the source rail and Library columns

1. **Return to the leftmost Library column.** Press ← once more to move focus to the vertical source rail.

2. **Press ↑ or ↓ on the rail.** Move through Library, shortcuts, and Spaces. The highlighted source opens immediately; you do not need to press Return.

3. **Press →.** Focus enters the first visible Library column for that source. Its active row changes from the quieter background selection to the stronger blue content selection.

While the source rail owns focus, the current row in the adjacent column remains visible in a quieter blue so you do not lose your place. The rail keeps focus while you move between sources and releases it only after you press →. Once you are navigating Library content, pressing ↑ at the first row stays in the Library instead of unexpectedly moving to the app tabs across the top.

Enter and leave Paper Files

1. **Select a paper in the main item column.** Paper Files appears to its right. No Paper Files card is highlighted yet.

2. **Press →.** Focus enters Paper Files and the active card gains a light-blue selection. The main paper remains visible with a quieter selection color.

3. **Press ↑ or ↓.** Move through the flat Paper Files list.

4. **Press ←.** Focus returns to the main paper. Paper Files no longer shows an active card.

The same focus rules apply in the main Library, a shortcut, and every Space. Paper Files is a database-backed view of the selected work rather than a physical child folder, but the keyboard transition is intentionally continuous: → enters the bundle, ← returns to the same paper, and the next ↑ or ↓ moves in the main item column.

Preview while navigating

In Paper Files, press Space to open Preview. While Preview is open, use ↑ and ↓ to follow adjacent files. Press Space again or close Preview to dismiss it.

Use the Preview window

• For a PDF, use the thumbnail strip to jump to a page and scroll the page area independently.

• Drag the title bar to reposition the preview. Drag its resize corner when you need more reading space.

• Choose **Open in Default App** when you want the full the Windows default PDF application application.

• When Preview is already open, changing the Paper Files selection updates the preview without requiring another open action.

Note

Single-click selects a Paper Files item. Double-click opens it. This prevents an accidental external app launch while you are classifying files.

See also: Understand Paper Files · Preview Files · Keyboard Shortcuts

3-1.3 Folders, Shortcuts, and Spaces

Folders organize a root. Shortcuts provide another entrance to the Library. Spaces keep an independent root for a project or research context.

Renaming a managed folder or Space also renames its local storage. Use the App's Rename command so its main directory, mirrored Associated Files paths and shortcuts stay consistent. Existing paper identities, file contents, classifications and Default choices are retained. A busy-file message means the operation could not finish yet; allow the active file operation to finish and retry. Renaming a Shortcut changes its label rather than its target folder.

Choose the right structure

Structure	Use it for	What it changes
Library folder	A durable topic hierarchy inside the main collection.	Creates or moves a managed path.
Shortcut tab	Fast access to a Library location you use often.	Adds another entry point; it does not duplicate the paper record.
Space	An independent project, course, collaboration, or temporary collection.	Uses its own managed root under data/Spaces.

Create, rename, or move

1. **Right-click the relevant folder area.** Choose **New Folder**, **Rename**, **Copy**, or **Paste**.

2. **For a move, drag the item to its destination.** Wait for the destination to indicate it can receive the item, then release.

3. **Check the breadcrumb and Paper Details.** After the operation completes, the visible path and folder membership reflect the new location.

Shortcut and Space tabs can be dragged to change their order. Their inactive colors distinguish the tab groups; the active tab uses the common selected style. With the keyboard, press ← from the leftmost content column to focus this rail, use ↑ and ↓ to open another source, then press → to enter its content.

Use the Space or Shortcut heading

The persistent heading identifies the source in both List View and Table View, even after you open a nested folder. It spans that source's folder and content area, including Paper Files when visible, and stops before Paper Details. The nested folder keeps its own heading below it.

Open the **…** menu at the right of the heading, or Right-click the source tab, for **Rename** and source actions. Renaming a shortcut changes its navigation label, not the underlying folder. Spaces also offer **Move Space to Library** here. These commands replace the former toolbar of large buttons.

To add a paper inside the current folder, Right-click blank space in that folder and choose **Add Paper**. Library, shortcuts and Spaces use the same inline input. **Add Paper** from the source heading menu targets that source's root; check the destination before submitting.

Color folders and remove navigation entries

Right-click an ordinary folder and choose **Color** to change its folder color. Protected roots do not offer this command. On the source rail, **Remove Shortcut** removes only the shortcut, leaving its folder and papers intact. **Remove Empty Space** works only after both its managed contents and remaining files are empty; move the Space into Library if you want to keep its hierarchy.

Work with several entries

Ctrl-click to add or remove individual entries from a selection. Shift-click, or hold Shift while using the arrow keys, to extend a range in the current folder. Copy the selected entries with Ctrl+C, paste into the active destination with Ctrl+V, or press Delete to apply the normal reference-aware deletion rules.

To include an existing Library paper in your own publication list, select one or more paper rows, Right-click, and choose **Add to My Publications**. This adds the publication relationship to the same paper and Gewu Key; it does not remove the Library placement. Review authorship roles in My Publications afterward.

To update the information for one project or topic, Right-click its active folder and choose **Refresh Info**. The task includes every subfolder once per Gewu Key and follows the same cooldowns as the all-Library task. See Refresh Info: One Paper, a Folder, or the Library.

Copy a paper to another folder

A Library copy creates another placement of the same paper. Windows secondary main-file locations use .lnk shortcuts, and secondary Associated Files locations point to the canonical bundle. Versions and attachments remain associated with that paper; a placement copy does not create another unrelated identity.

Move an entire Space into Library

Use this when a temporary or project Space should become part of the permanent Library hierarchy.

1. **Select the Space on the left rail.** Open the Space that you want to keep as a normal Library folder.

2. **Open the heading's … menu and choose Move Space to Library.** You can also Right-click the Space tab. The move sheet explains that the Space will become a folder with the same name.

3. **Choose Destination in My Library.** Select the Library folder that should contain the moved Space.

4. **Confirm the move.** The complete Space hierarchy, including its files and subfolders, moves together.

When the move finishes, the Space tab is removed and Library opens the moved folder. Canonical paper identities, folder placements, and Paper Files resource associations remain connected; the operation does not create duplicate paper records.

Important

Move managed papers in Gewu Insight, not directly in File Explorer. The app updates the visible file, associated bundle, and live database paths together.

See also: How Gewu Insight Stores Files · Delete and Recover Items

3-1.4 Search, List View, and Table View

Search locates items across the managed collection. List View emphasizes browsing; Table View emphasizes metadata comparison.

Search the collection

1. **Select the search control in the top-right corner.**

2. **Enter a title, author, journal, identifier, or filename.** Results may come from the Library and Spaces.

3. **Select a result.** Its Paper Details and managed path become available.

4. **Clear the search.** Return to the previous Library location.

Edit the query and use fuzzy matching

Double-click a word, drag to select characters, or use Ctrl+A to select the focused query. Type to replace it or press Delete. Ctrl+F focuses workspace search; each research tab retains its own query.

Library matching tolerates small spelling errors, partial words and word endings, with exact matches ranked first. Server and visible-result matching share the same rules. It searches saved titles, authors, journals, identifiers and filenames, not every PDF's full text. Try a surname or title fragment if a long query finds nothing.

This is fuzzy text matching; it does not generate Chinese/English translations, acronym expansions or concept-level synonyms. Subject Monitor discovery uses separate, literal keywords. Library searches do not change those keywords or request online discovery.

Switch views

Choose **View > List View** or **View > Table View**. You can also use Shift+Ctrl+V. Changing the view does not rename, move, or rewrite files. Active Library search uses its result list and disables Table View. Clear the search to use Table View for the current folder again.

In either view, Right-click the folder contents and choose **Sort by Name** or **Sort by Modified Time** for folder ordering. These commands clear any active table-column sort.

Sort by a table column

1. **Click Title, Authors, Year, Journal, or Time added.** The first click sorts ascending: displayed text alphabetically, Year numerically, or Time added from oldest to newest.

2. **Click again to reverse.** The header arrow shows the direction.

3. **Continue navigating.** Library, shortcuts and Spaces retain the chosen column and direction. Keyboard movement and range selection follow the visible order.

Folders stay above papers, and missing metadata stays below known values in either direction. Sorting preserves the selected paper, its identity and its files.

Time added shows when that folder or paper placement was added, in local date and time. It is separate from the publication date and the file’s modification time. A Shortcut shows the original placement’s time; renaming, moving or refreshing metadata does not reset it. A new copied placement has its own addition time. Click again for newest first. In a narrow window, scroll the table horizontally to reach all five headers; the headers and rows move together.

See also: Library Layout · Keyboard Shortcuts

3-2 Papers and Files

3-2.1 Add Papers and Files

A normal Library import creates a managed local copy and a database record. The original source file remains where it was.

Drag a paper into a folder

1. **Open the destination folder in Library.**

2. **Drag a PDF from File Explorer into the item area.** Drop it on the folder or in its contents.

3. **Wait for the item to appear.** The app copies the file into managed storage and begins local identification.

4. **Review Paper Details.** Confirm the title, DOI, arXiv identifier, and file classification.

Add a paper by DOI, arXiv ID, URL, or title

1. **Open the destination folder.** The resolved paper will be placed in that Library, Shortcut or Space folder.

2. **Choose Add Paper.** Right-click blank space in the folder contents and choose the command to open the inline lookup field.

3. **Enter a DOI, arXiv identifier, supported article URL, or title.** A DOI or arXiv identifier is the strongest identity clue.

4. **Press Return or click Add Paper once.** The app resolves the query and adds the paper to the displayed destination. A failed lookup leaves an error in the inline form.

5. **Review the added paper in Details.** Check its title, authors, identifiers, journal and year, especially after using a title query.

If the identity already exists, Gewu Insight reuses the canonical paper and adds the selected folder placement rather than creating an unrelated duplicate.

Note

A paper record does not require a local PDF. **Add Paper** creates or reuses the metadata record; it does not automatically download a PDF. Use **Download** or **Add File** separately when you want a managed local file.

Note

A file added to an existing paper's **Paper Files** bundle is an attachment or version of that paper. A normal folder drop creates or reuses a paper placement in that folder. When identity matching finds an existing paper, the incoming file joins its Paper Files; different PDFs are retained even when they share a DOI.

Folder drops and Folder Loader use the same import rules. An identity mismatch keeps the file with the matched paper, preserves its existing metadata and Default, and records the filename and identifiers in **Details**. It does not pause for a review decision. Import status stays in the bottom bar until dismissed; failed or stopped imports also refresh Library so completed items remain visible. A temporary progress connection failure triggers reconnection rather than reporting that the import stopped.

See also: Add and Classify Attachments · Use Folder Loader · Move a Standalone File into Paper Files

3-2.2 Use Paper Details

Paper Details combines actions, identifiers, metadata, and citation counts. Library, My Publications, and Author Monitor start with the paper title, without a separate heading bar. The available actions occupy two rows: Open in Default App, Download and Open Website first; Google Scholar, Get DOI and Refresh Info second. Each button label stays on one line.

Top actions

Action	What it does
Open in Default App	Opens the preferred local PDF in the Windows default PDF application.
Download	Retrieves the best available paper file without overwriting a different preserved version.
Open Website	Opens the publisher, DOI, arXiv, or best known work page using Website Links: Gewu Insight Browser by default, or the system default browser.
Google Scholar	Searches for the work in Google Scholar.
Get DOI	Examines local paper files for DOI or arXiv evidence.
Refresh Info	Refreshes paper information using its saved DOI or arXiv ID. Hover over the button to see the latest result below it.

File management

Library uses the adjacent **Paper Files** column; Paper Details does not repeat a Files box. My Publications keeps its collapsible **Files · n** management panel. Author Monitor shows a compact local filename with the full path on hover; **Get DOI** appears when a local PDF is available.

Metadata rows

The title appears once at the top. The rows below include authors, journal, date, DOI, arXiv, Gewu Key, citation, fields, and folder membership when available. **Gewu Key** is the stable, human-visible storage handle for a cataloged work record. It is not a DOI, arXiv identifier, or the database's relational primary key.

Compare citation sources

Merged Citations brings together the counts returned by OpenAlex, Semantic Scholar, Crossref, NASA ADS, and saved Google Scholar data when those services have a match. Select a source label to show its saved count in the headline; this does not start a refresh. The merged estimate compares published, preprint, and already-merged records rather than simply adding every provider's total. Separate published/preprint estimates can be combined, so this is not a verified count of unique citing papers. The yearly histogram uses OpenAlex data and does not switch provider when you select another count. PubMed Details supplies identifiers and indexing information, not another citation-count source.

Inspect influential citations

When Semantic Scholar reports an **Influential** count, select it to inspect citing papers that Semantic Scholar classifies as especially meaningful to the cited work. This is Semantic Scholar’s classification, not a score calculated by Gewu Insight. The list can include citation context, intent, citing authors, venue, year, and citation counts when the service supplies them.

Influential Citations is fetched on demand and cached locally for several hours. A saved API key gives Gewu Insight an individual Semantic Scholar allowance, but it is still limited to about one request per second and can be temporarily throttled. If the service returns a rate-limit message, the app pauses repeat requests for a few minutes; the paper record, existing citation totals, and any previously displayed result remain unaffected.

Read and reuse the record

• A representative first figure, when available, provides a visual checkpoint above the actions.

• **Abstract** keeps the paper summary in the independently scrolling details pane.

• **BibTeX** and **Copy Code** provide a citation record for reference software or LaTeX.

• **Nature Reference** and **Copy Reference** provide a formatted reference string.

• **Folders** lists every Library location for the shared work. Remove a location there only when you intend to remove that reference.

Note

Gewu Key is assigned when a work is first cataloged in SQLite, before Add to Library. Its row remains visible in Author Monitor, including while details load; a missing value shows (undefined). Adding to Library reuses the existing key and updates the view without creating a second identity.

See also: Edit DOI and arXiv Identifiers · Understand Paper Files · How Gewu Insight Stores Files

3-2.3 Edit DOI and arXiv Identifiers

DOI and arXiv can identify the same work across publication stages. Correct either value in Paper Details before downloading or synchronizing versions.

Save or correct either identifier

1. **Select the DOI or arXiv value.** Enter the identifier, including in an empty row. DOI URLs are accepted; arXiv accepts forms such as arXiv:2106.14849 and valid legacy IDs.

2. **Press Return.** Wait for the server to save it. The field leaves editing and the green message above the metadata reads **Identifier updated**, or **Identifier saved** if unchanged. Invalid input stays editable with an error.

3. **Choose Refresh Info.** Saving alone does not request remote metadata. Refresh uses the saved DOI and/or arXiv ID; a DOI is not required for an arXiv-only paper. A changed DOI still in the editor is saved before refresh.

4. **Inspect the result.** Hover over **Refresh Info** for its information box below the button: changed fields, last check, source outcomes and conflicts. Keyboard focus also reveals it; pointer departure or Escape dismisses it.

To clear either identifier, save an empty value with Return. Both rows remain available for later edits. The arXiv row also has an arrow to open its website and a download control for the latest available PDF.

Replace an incorrectly identified work

If an automatically recognized DOI belongs to the wrong article or book, replace it and press Return first. Clearing and then entering the correct value also records a correction. On the next Refresh Info, a primary source must return that exact corrected identifier before the old automatic bibliography can be replaced. The old information is retained in correction history; missing or mismatched responses leave it available while you retry. This is why an ordinary automatic conflict guard does not prevent a verified manual correction.

The correction keeps the same Gewu Key, paper locations, files, classifications, Default and user notes. It does not move the paper into another object's bundle. If another paper already owns the entered identifier, the app reports the conflict instead of merging the two; inspect both records before proceeding. After a correction is applied, later refreshes use the normal conflict checks again.

Follow a preprint into publication

Explicit links from arXiv, Crossref, OpenAlex, Semantic Scholar or configured ADS can connect a preprint and its published DOI. A newly linked DOI loads detailed publication metadata while retaining the arXiv ID. Title similarity alone cannot bind identifiers. Manual corrections and cleared values are preserved; a DOI owned by another Gewu Key is reported without merging records.

Saved Library, Space and My Publications papers are refreshed when you request it, including through a batch Refresh Info task. Saving a paper does not schedule periodic metadata refreshes. Author Monitor separately completes missing identifiers and abstracts for monitored publications, with bounded attempts and a daily allowance. This completion work does not download PDFs, change Paper Files or Default, create placements, or move your selection and focus.

The bottom bar shows a running refresh, then green **Refresh complete**. Partial results preserve successful updates; the hover report explains unavailable sources and retry times. For batch scope and shared cooldowns, see Refresh Info: One Paper, a Folder, or the Library.

Important

Confirm an identifier before running a version sync. A wrong identifier can attach files from a different work.

See also: Download and Sync Versions · Literature Data Sources

3-2.4 Refresh Info: One Paper, a Folder, or the Library

Use one information-refresh service for a single paper, a selected folder, the active Library collection, or the metadata stage of an import. Choose the scope before starting.

Choose the operation you need

Entry point	Scope and behavior
Paper Details > Refresh Info	One paper, using Full. Either saved DOI or arXiv is sufficient; see identifier correction.
Folder context menu > Refresh Info	The selected active Library/Space folder and all descendants, once per Gewu Key. Choose Quick or Full; default Full.
Loader > Refresh All Metadata	Active Library and Space papers, excluding Recycle. It is not a refresh of every Monitor-only database record. Choose Quick or Full; default Full.
Folder Loader metadata mode	Imported papers use the chosen Skip, Quick or Full setting after file import and identifier recovery. File Explorer folder drops retain their separate import behavior.
Automatic background checks	Bounded completion of missing identifiers and abstracts in Author Monitor. Saved papers do not enter a periodic refresh queue.

Refresh known works

1. **Choose the scope.** Use **Loader > Refresh All Metadata**, or Right-click a Library/Space folder and choose **Refresh Info**. A folder task includes all its subfolders. Recycle is excluded.

2. **Choose Quick or Full.** Folder and all-Library tasks default to Full. Quick updates core information and DOI/arXiv links; Full adds detailed authors and citation sources.

3. **Choose Start Refresh.** Each Gewu Key is checked once, even when it has several files or locations. The bottom status bar shows the task while you continue browsing.

4. **Review the log.** Counts distinguish updated, unchanged, partial, failed, cooldown skipped and missing DOI/arXiv records. Missing identifiers remain visible; use the separate identifier search when needed.

5. **Pause, continue, or stop. Pause** finishes the current paper and saves the remaining queue. Select the task under **Refresh tasks** and choose **Continue**, including after reopening or restarting. **Stop** ends the remaining queue permanently for that task while keeping completed results and history. Interrupted running refresh tasks reopen paused; stopped tasks cannot be continued.

Batch and import work skips compatible successful checks from any entry point within three days. A changed identifier does not inherit the old identifier's cooldown. Full satisfies a later Quick task; Quick does not block Full. Partial retries reuse recent successful source responses and retry failed sources. A direct Paper Details refresh can check again immediately, while shared source rate limits still apply. Author Monitor completion retains its separate retry limits and daily allowance; Google Scholar protections are unchanged.

Refreshing a shared Gewu Key updates its information in every location. Folder locations, PDF files, Paper Files classifications and Default selections stay unchanged. Multiple tasks wait in a queue; a direct single-paper refresh has priority between papers. The task log shows the most recent 200 entries; totals and the remaining queue are retained.

Pausing means the current paper is still finishing; it changes to **Paused** when the saved queue can resume later. Keep browsing while it settles. A completed refresh uses green **Refresh complete** in the bottom bar, including partial results. This reports that the operation ended, not that every source answered. Detailed outcomes remain in the task window and, for a single paper, below **Refresh Info** on hover. A transport failure or rejected operation still reports its error.

Jump from a log entry to Library, then return

1. **Click a paper entry in the scrolling log.** Entries linked to a paper offer **Show in Library** on hover. You can also focus an entry and press Return or Space. General process messages and older entries without a saved paper link are plain text.

2. **Inspect the selected paper.** The task window closes after the paper is revealed in Library. Its folder and paper selection are restored for this destination. Closing the window does not pause or stop the background job.

3. **Return through the bottom bar's Details.** While the Loader or refresh task remains active or paused, reopen its progress window and continue reading the log. For completed refreshes, reopen **Loader > Refresh All Metadata** and select the saved task in **Refresh tasks**.

The same log navigation is available in Folder Loader after an entry has been associated with a saved paper. Selecting text in the log lets you copy it without opening the paper. If the referenced item is no longer available, the window shows an error instead of silently navigating to another work.

Close, pause, and stop are different

Action	What happens
Close the task window	Hide the window and keep working. The task continues while the app is running; Details returns to it.
Pause / Continue	Refresh Info finishes the current paper, saves the remaining queue and can resume it later, including after an app restart.
Stop	End a running or paused Refresh Info task. Stopping lets the current paper finish safely. Completed changes and history stay, but the remaining queue will not resume. Start Refresh creates another task if needed.
Stop Import / Stop Search	Folder Loader or identifier search stops at its next safe checkpoint. Completed imports and identifier changes stay. Stop Import also ends that import's linked metadata queue; it is not Delete Import.

A stopped task no longer leaves a resumable progress indicator in the footer. Folder import and identifier search use their own Stop controls; they do not offer the batch refresh's Pause/Continue pair.

Find missing identifiers

1. **Choose Loader > Find All Missing Identifiers.**

2. **Choose Start Search.** The app checks active Library and Space PDFs using Crossref, OpenAlex, and Semantic Scholar where available.

3. **Review uncertain matches.** Refresh or recover DOI evidence as needed, and edit an incorrect arXiv identifier inline before downloading versions.

Verified “not found” checks and transient failures use cooldowns so a repeated run does not immediately send the same requests. Bulk missing-identifier work does not use Google Scholar.

See also: Literature Data Sources · Publisher and Network Access · Edit DOI and arXiv Identifiers

3-2.5 Understand Paper Files

A paper is one work record that can own several PDFs and related files. Paper Files shows that bundle without pretending it is another Library folder level.

Compact cards for one flat bundle

The Paper Files column is a flat peer list, not a hierarchy of version or attachment folders. Each card shows its filename, **File type**, and size by default. Click the size footer or its chevron to expand **Annotation** and **Source** into separate rows; click again to collapse them. The chevron points down when collapsed and up when expanded. Each card expands independently, and the choice lasts for the current session. File type remains visible because it identifies a preprint, accepted manuscript, published version, supplement, or other resource. The **Default** marker identifies the preferred file.

Select, open, or act on a file

• Single-click a card to select it.

• Drag a Paper Files icon or filename to File Explorer or a compatible application to copy or open the real file. Library file icons use the same native drag. The receiving application determines its accepted formats and drag behavior; not every external destination has been verified.

• Double-click a card to open it.

• Double-click the paper row to the left to open the paper's Default file, independently of the highlighted resource card. PDFs open in the Windows default PDF application. For unclassified files, automatic selection uses a stable Unknown/Other fallback when available; you do not have to choose a Default manually first.

• Press Space to use Preview.

• Right-click a card for **Open**, **Preview**, **Show in File Explorer**, default-file controls, **Change File Type**, or **Delete from Paper Files** where allowed. Right-click blank space in Paper Files for **Add File** and, when the paper has an arXiv identifier, **Sync Versions**. Those bundle-wide commands do not appear on an individual file card.

• Press Delete or Backspace while Paper Files has keyboard focus to remove only the selected removable resource after confirmation. This does not delete the parent paper or its other files.

The current main file remains protected from direct deletion. Choosing **Set as Default** makes that resource the preferred file for opening and preview. For a privately managed paper with an active folder placement, it becomes the main file and the other resources belong in Associated Files. This applies to PDFs and non-PDFs alike. File IDs, classification and bytes are preserved; unrelated same-name files are not overwritten. **Use Automatic Selection** releases a manual choice and returns to the priority and fallback rules in Default selection.

Library Paper Details no longer repeats this bundle. In My Publications, which has no adjacent Paper Files column, the collapsible **Files** panel keeps its file-management controls. **Show in File Explorer** reveals a physical file.

Deleting a private managed attachment uses Windows Recycle Bin and a verified recovery backup before its file registration is removed. Shared files and external originals remain protected. A failed operation stays visible; do not assume a failure deleted the file.

Attachment deletion is shared. Every placement of the same Gewu Key uses this Paper Files bundle. Deleting one attachment here removes it from that paper everywhere; it does not merely hide it from the current folder. The current Default and protected primary file must be changed before they can be removed. This differs from deleting a Library placement, which follows the reference-aware Recycle rules.

Correct a file's paper assignment

If an imported PDF was matched to the wrong paper, Right-click its card and choose **Move to Another Paper**. Search the destination in Library by title, DOI, or Gewu Key, select it, and choose **Move File**. To make it independent, choose **Create Paper from File**, enter a title, and choose **Create Paper**. The new paper appears in the current Library folder with a new Gewu Key and no guessed DOI.

Only the selected file changes ownership when using these card commands. Its bytes, file ID, classification and source information remain intact; a name collision may require a unique filename. A source with remaining files keeps its identity and selects another eligible Default. An emptied, unshared source is removed as an independent

Library item rather than left as a fileless link. Protected shared relationships can prevent that removal. For a PDF, the new independent paper receives a new Gewu Key and uses the file as its Default. A detached non-PDF remains an ordinary standalone file with an internal storage key and no public Gewu Key in the App. Managed paths follow the change: an attachment goes into the destination bundle in Associated Files; a newly independent file goes into its main folder. Explicit reassignment is respected on repeat imports. Historical analysis text is not rewritten.

AI Access can perform file ownership moves and rename files only with the separate move or rename permissions described in AI Access. Reading and adding analyses do not grant these permissions. Existing file contents cannot be edited or overwritten through AI Access.

Understand a Missing File row

Missing File means that SQLite still has a resource record, but the file is not present at the recorded local path. Gewu Insight keeps genuine missing resources visible so you can identify and repair them; it hides only an older untyped migration alias when it can prove that the alias has already been replaced by the same paper's live canonical file.

A missing attachment is not another copy of the default PDF merely because both rows have a similar name. Check **Show in File Explorer**, the paper's Associated Files bundle, and Recycle before deleting or importing anything. The default resource and explicitly typed attachments remain visible even when their paths need repair.

See also: Preview Files · Choose File Types and the Default File · Add and Classify Attachments · Navigate with Mouse and Keyboard

3-2.6 Preview Files

Select a local Library or Paper Files item and press Space to inspect it inside Gewu Insight.

Read and navigate

1. Select the resource and press **Space**. Up/Down follows the file list; Escape closes the preview.

2. PDFs use continuous pages, a thumbnail rail and native wheel scrolling. Use **Ctrl+wheel** to zoom the PDF. Wider pages can be panned horizontally.

3. Use **Open in Default App** for the Windows reader associated with the file. Double-clicking the Library paper row opens its Default file; double-clicking a Paper Files row opens that specific file.

Read Markdown notes

Markdown supports headings, lists, quotations, code, tables and offline mathematical formulas. Leading YAML appears under collapsible **Properties**; analysis provenance appears under **Source record**. These values belong to the note and do not overwrite Paper Details.

Text wraps to the reading area; wide tables and code scroll independently. Nearby images can display locally, remote images remain explicit links, and raw HTML is escaped. Large notes are limited to a 256 KiB preview with a truncation notice; the original file is unchanged. Open the original to read beyond the preview.

Other files and recovery

Supported images, media and text can be inspected in the workspace. Unsupported formats offer an **Open File** action using Windows file associations. If a preview stalls, close it, select the file again and retry; check that the original file exists. There is no macOS system Quick Look mode on Windows.

See also: Preview Settings · Navigate with Mouse and Keyboard · Understand Paper Files · Troubleshooting

3-2.7 Choose File Types and the Default File

The default file is the preferred local representation of the paper. Choose it manually or let Gewu Insight select it. Default appears first in the file list; Up and Down follow the visible order.

Automatic selection

The automatic order is **Corrected published version**, **Published version**, **Accepted manuscript**, then **Preprint**. Within a type, a later recognized version normally wins. If none is eligible, an available **Unknown** or **Other** file supplies a fallback: keep the existing main file where possible, otherwise choose the earliest PDF, otherwise the earliest remaining eligible file. This includes standalone RTF, image and other non-PDF imports; it does not relabel them as published papers.

Automatic and manual eligibility

The four publication types above take priority over the Unknown/Other fallback. Correction and retraction notices, expressions of concern, withdrawal notices, addenda, supplementary material, peer review files, Perspective, News and Views, Summary, Analysis, Source Data and Source Code are not automatic candidates. Missing, Invalid file and unresolved identity-conflict files are also excluded. You may manually choose an existing valid file, including a supporting file. A manual choice is sticky across rescans, metadata refreshes, and later downloads until you choose **Use Automatic Selection**. Newly arriving files remain peer rows and do not erase or silently reclassify older files.

Choose a file manually

1. **Enter Paper Files, or expand Files in My Publications.**

2. **Select the file you want.**

3. **Choose Set as Default.** This file will be used by **Open in Default App** and paper preview. You can also pin the automatically selected Default this way.

The selected file becomes the manual default. In a managed paper with an active placement, it becomes the main file and the former main file moves to Associated Files. This applies to non-PDF defaults too. The article and file identities stay unchanged. External originals and files shared with another article are protected; existing names are retained unless a collision requires a unique name.

Return to automatic selection

Choose **Use Automatic Selection** for a manually selected default. Gewu Insight evaluates the eligible file types again.

Classify files without collapsing annotation state

In Library, File type stays visible on each card. Click the size footer to reveal Annotation and Source, then change each control independently. In My Publications, expand Files to see all three controls directly. File type uses exactly these labels:

• **Preprint**, **Accepted manuscript**, **Published version**, and **Corrected published version**

• **Correction notice**, **Retraction notice**, **Expression of concern**, **Withdrawal notice**, **Addendum**, **Supplementary material**, and **Peer review file**

• **Perspective**, **News and Views**, **Summary**, and **Analysis**

• **Source Data** and **Source Code**

• **Other**, **Unknown**, and **Invalid file**

Use Perspective or News and Views for related commentary, Summary or Analysis for reading notes and interpretation, and Source Data or Source Code for the accompanying research material. These labels describe this file's role; they do not change the parent paper's publication type or Gewu Key. They are not automatically promoted to Default. File extension alone does not determine the role.

Annotation state is selected independently as **Annotated**, **Unannotated**, or **Unknown**. Source is independently recorded as **Publisher**, **Preprint server**, **Institutional repository**, **User import**, **Other**, or **Unknown**. Manual type

and annotation choices survive later fingerprint rescans.

Publisher is used only when a recognized publisher host or a publisher-specific acquisition path provides that evidence. arXiv, bioRxiv, and medRxiv are shown as **Preprint server**; repository hosts remain **Institutional repository**; ordinary local additions are **User import**; and a generic web download with no stronger evidence remains **Other**. A real host can appear after the source label when useful. Internal migration or ingestion markers are never user-facing source details, and choosing a different source clears a stale provider detail rather than appending it to the new choice.

Note

Changing File type can change the automatic Default. The selected managed Default and its main file location are synchronized together. Annotation and Source remain independent properties; changing a label does not apply a filename template or rewrite the PDF.

See also: Download and Sync Versions · Add and Classify Attachments

3-2.8 Add and Classify Attachments

Import first, classify afterward. This keeps the add operation simple and lets you set type, annotation state, and source after seeing the file in context.

Add a file to the paper

1. **Right-click blank space in the Paper Files area and choose Add File.** In My Publications, expand Files and use Add File.

2. **Select one or more local files.** Confirm the file chooser.

3. **Wait for the new row.** A new item begins as **Unknown** unless its source proves a more specific type.

4. **Select its compact controls.** Choose File type; in Library, click the size footer to expand Annotation and Source. My Publications shows those controls directly in its Files panel.

Attachment types

The same file-type choices apply to every row and to Browser capture. Use **Summary** or **Analysis** for notes, **Source Data** for research data, and **Source Code** for code; use **Other** when none fits. File extension and MIME type remain separate from this classification. Existing files keep their saved labels until you change them.

Adding the same unchanged file to the same paper again reuses its existing resource, including when its source path or filename has changed. Matching uses exact file contents; an edited or annotated PDF with different bytes remains a separate version. A shared DOI alone does not make two files duplicates.

Add by drag and drop

Drag one or more File Explorer files anywhere in the visible Paper Files column: over its heading, an existing card, or the empty gray area. No card needs to be expanded. Wait for the whole-column drop highlight, confirm the selected destination paper, then release. The files are copied into that paper's associated bundle and appear in Paper Files. The same behavior applies in Library, shortcuts and Spaces.

Important

Invalid or unreadable PDFs are rejected at file ingress. Existing migrated records that can be proven invalid remain visible as **Invalid file** for audit and repair, but cannot become a default.

See also: Move a Standalone File into Paper Files · How Gewu Insight Stores Files

3-2.9 Download and Sync Versions

Downloads add a version to the paper bundle. They do not silently overwrite a different preserved PDF.

Paper downloads accept verified publisher or authorized repository sources and check redirects. Unverified destinations stop. Use your legitimate institutional or publisher access; Gewu does not bypass subscriptions or website verification.

Download the best available paper

1. **Verify DOI and arXiv.** Make sure the identifiers belong to the selected work.

2. **Choose Download at the top of Paper Details.** Gewu Insight first tries the best available published file, then supported alternatives.

3. **Wait for the status message.** Existing files are preserved if the incoming file is a different version; a manual default stays selected.

4. **Inspect Paper Files.** Every preserved file appears in the same flat list. Automatic ranking may select the new PDF as Default and synchronize its main file location; a manual default remains unchanged. Earlier files stay in the bundle.

Keep downloading while you work

You can select other papers, switch workspaces or add another Monitor result to Library while a download runs. The running state belongs to each paper, and completion updates that paper without selecting it or returning to an earlier tab. Repeating Download for the same running paper shares its request; another paper has its own request. Ordinary Download reuses an existing valid local PDF. Downloads do not resume automatically after quitting the App.

If the ordinary download cannot retrieve a PDF

1. Choose **Open Website** and open the article in Gewu's **Browser**.

2. Complete the website's normal access or sign-in steps yourself. Open its PDF; in an embedded article viewer, use its PDF download control to open the received PDF in Browser.

3. Choose **Save to Gewu**, verify the Gewu Key and PDF in Details, then save. An existing active Library/Space placement is reused unless you explicitly choose another folder.

This is a manual Browser workflow, not a promise that every publisher or Download button has an invisible Browser fallback. A legitimate local PDF can also be attached with **Add File**. See Save an article and PDF to Library.

Download arXiv files

• Use the download icon in the **arXiv** row to retrieve the latest arXiv PDF.

• Right-click blank space in Paper Files and choose **Sync Versions** to retrieve all available arXiv revisions such as v1, v2, and v3. In My Publications, use Sync Versions inside the expanded Files panel. The command is available when the paper has an arXiv identifier.

• Each revision is labeled with its arXiv version when known.

Duplicate protection

Gewu Insight computes exact SHA-256 and PDF content fingerprints as each new resource is registered. An exact duplicate is reused instead of stored twice. A clean PDF and a genuinely annotated copy can share a content fingerprint while retaining different exact hashes, annotation counts, and labels.

Validation before replacement

A response is not accepted merely because it begins with %PDF-. Structural PDF validation rejects empty files, HTML responses, truncated downloads, missing valid endings, and content that cannot be parsed as a PDF. A download is written to a temporary file and replaces the destination only after validation succeeds. If the request or stream fails, an existing valid file remains untouched and a partial file is not registered as a resource.

Classification follows the file that actually arrived

A publisher download is classified from the file and source actually returned. A corrected published version outranks a published version automatically; a publisher reference or accepted preview remains an accepted manuscript. Science PDFs recognized as First Release are classified as Accepted manuscript in Gewu, even when the paper metadata already names Science. A correction notice remains a separate peer and never becomes automatic merely because it came from a publisher.

A PDF URL stored in bibliographic metadata is only a retrieval lead. It does not create a Paper Files row until a download actually succeeds, the returned bytes pass validation, and a local resource is registered.

If a download is skipped because the local bytes already exist, that skipped operation does not relabel the existing file from metadata or a newly discovered URL. Correct the file type explicitly if the saved classification itself is wrong.

Note

A Monitor result is not forced into a Library placement. Where download is available, a local resource can belong to the cataloged paper even before you add that paper to Library or My Publications.

Science main article and supplementary PDFs

The Science download workflow obtains and validates the main article first, then appends available supplementary PDFs to the combined reading file. A supplement, reporting checklist or supplementary-only response cannot stand in for the main article. If the main PDF cannot be obtained, the download reports failure instead of registering a supplement as a successful article download.

Inspect the combined PDF and any download message to check what was actually retrieved; access to the article webpage does not guarantee access to every PDF. Non-PDF material is not converted into PDF pages. The file type follows the main article's version, while the displayed filename uses the returned publisher name or a meaningful paper-based fallback. Re-downloading preserves other files and an explicitly chosen Default.

See also: Choose File Types and the Default File · Publisher and Network Access · Edit DOI and arXiv Identifiers

3-2.10 Move a Standalone File into Paper Files

If a data, image, presentation, or other file was imported as its own Library item, drag it onto the correct paper's Paper Files area to make it an attachment.

Convert an independent item

1. **Select the destination paper.** Keep its Paper Files inspector visible.

2. **Begin dragging the standalone item.** The main paper remains the active destination while you drag.

3. **Move the pointer into the Paper Files drop zone.** Wait for the drop feedback that identifies the target paper.

4. **Release the pointer.** Gewu Insight validates the move, adopts the file into the paper bundle, and removes its independent Library position.

5. **Classify the attachment.** Choose **Supplementary material** for an actual paper supplement, **Source Data** for data, **Source Code** for code, **Summary** or **Analysis** for notes, or **Other** when none fits. Expand the size footer to set Annotation and Source separately. See the complete current file-type list.

The physical file and database link now belong to the destination paper; the former standalone entry is gone.

Make a Paper Files resource independent again

Drag a resource's icon or filename from Paper Files onto a Library folder or that folder's content area. The file leaves its former paper and moves from Associated Files into the destination's main folder. A PDF becomes an independent paper with a new Gewu Key; a non-PDF becomes an ordinary standalone file with only an internal storage key. Right-clicking the resource and choosing **Create Paper from File** performs the same separation in the current folder, with an editable title. The former paper keeps its remaining files.

To transfer just one resource between existing papers, use **Move to Another Paper** or drag it into the other paper's Paper Files area. A Library paper-row drag adopts the source paper's files as a group; it removes the former independent identity only when the conversion is safe. A single-file RTF therefore disappears from its former folder and becomes one resource of the destination paper.

Check the destination

Dragging within Gewu Insight changes ownership or location. Dragging a file to File Explorer or the Desktop makes an external copy and leaves Paper Files intact. Dragging from File Explorer into Paper Files imports a managed copy and keeps the external original.

If the conversion cannot finish

The file moves and database changes are coordinated as one recoverable operation. If any step fails, Gewu Insight restores the original standalone files and rolls back the paper, Library item, resource relationships, and fingerprint fields. The source should remain usable rather than becoming a half-converted attachment.

Important

If the source item is shared by another Library reference or protected relationship, Gewu Insight may refuse a destructive conversion. Add a copy with **Add File** instead.

See also: Add and Classify Attachments · Folders, Shortcuts, and Spaces

3-2.11 Delete and Recover Items

Deleting a paper reference either removes only that reference or moves the last active Library/Space reference to Recycle. Final deletion inside Recycle is reference-aware and uses the Windows Recycle Bin for managed files.

Delete a Library reference

1. **Right-click the item.**

2. **Choose Delete.**

3. **Check the result.** If another active Library or Space location, or My Publications, still refers to the same work, only the selected reference is removed. Otherwise the item moves to **Recycle** and remains recoverable.

What happens to the original and attachments

A paper's original can move into the local Recycle directory only when no normal Library, Space or My Publications placement still uses it. The same check applies when you delete or drag a whole folder: retained papers keep their originals in normal storage, or move to a surviving location. Recycle entries can remain shortcuts to those retained originals. Other paper records sharing the registered bytes are protected too.

Recovering, copying or adding a recycled paper back to an active location brings its original out of Recycle. This includes Monitor additions, Browser saves and Add to My Publications. If a recovery parent has also been recycled, an active fallback is used. The app synchronizes SQLite file paths, Associated Files and File Explorer shortcuts while retaining Gewu Keys, file IDs, classification, Default and file contents. These checks apply during file operations; they do not silently sweep historical disk remnants.

Deleting a single removable **Paper Files** attachment is a different action: its private managed copy goes directly to Windows Recycle Bin and its file registration is removed from the shared paper. Other files and the parent paper stay. All placements of the same Key see this attachment change. Shared bytes and external originals remain protected.

Delete from My Publications

Select one or more publications and choose **Delete**. If a Library, Space, Shortcut or Recycle location still refers to the work, its shared article record, Gewu Key and files remain. Otherwise, deleting this last placement also removes the article record and its identifier tasks from SQLite; private managed files move to Windows Recycle Bin. External originals and bytes shared with other articles are preserved. Import history does not keep an otherwise unreferenced article alive.

Removing every currently saved article of a running profile import pauses that import. Continue Import does not restore previously removed source entries. An explicit Add All Publications recheck after completion can add those articles again.

Recover an item

1. **Open Recycle.**

2. **Right-click the item and choose Recover.**

3. **Confirm the restored location.**

Delete permanently

Final deletion of Library items takes place inside Recycle. Choosing **Delete** on a folder moves that folder intact, including its subfolders and unregistered contents, to Windows Recycle Bin. The confirmation lists the folders and files to move. Original imported source files outside Gewu Insight are not touched. If another Library, Space, Recycle or My Publications location still refers to the paper, its shared record, Gewu Key, Paper Files and Default remain; any required local files are retained outside the folder being removed. Only papers with no remaining references are removed from SQLite.

Empty Recycle

Right-click the Recycle root folder or blank space directly inside it to choose **Empty Recycle**. This clears every Recycle entry and moves all contents of its local disk directory to Windows Recycle Bin, including unregistered files, empty folders and broken shortcuts. The Recycle root remains. This command is not offered on files or folders inside Recycle.

The deletion confirmation has a bounded height and an independently scrolling item list. Read the selected scope, then confirm. A failure remains visible for retry instead of reporting success. **Empty Recycle** clears the application's Recycle; it does not empty Windows Recycle Bin.

See also: Back Up and Upgrade · How Gewu Insight Stores Files

3-3 Import and Transfer

3-3.1 Use Folder Loader

Folder Loader imports an existing directory tree into managed Library storage while preserving relative paths.

Import a folder

1. Choose Loader > Open Loader. In Browser, Ctrl+L focuses its address field; use the menu to open Loader.

2. **Choose the source folder.** Review the displayed path before starting.

3. **Select a metadata mode. Skip metadata** — fastest; import files and structure only. **Quick refresh** — recommended for most migrations. **Full refresh** — more network work and a longer run.

4. **Choose Import.** Follow progress in the live log. Use **Stop Import** if necessary.

5. **Review the result.** Open previous logs or the result guide when items need attention.

Follow a folder drop without keeping Loader open

Dropping an external folder into Library starts Folder Loader in the background; it does not need to open the Loader window first. The Library footer shows import progress. Choose **Details** beside the activity indicators to open the live Loader window, inspect progress and read the log. Closing it leaves the import running, and Details opens it again. When the import has finished, Details still opens the retained result until you choose **Dismiss**; previous reports remain available in Loader.

Click a log entry linked to a paper to **Show in Library**. The window closes after the item is revealed, without interrupting the job. General progress messages cannot identify a Library item. Use the footer's Details to return, or **Loader > Open Loader** to review saved reports. See log navigation and task controls.

Stop Import finishes at the next safe checkpoint, preserves completed files and ends any linked metadata queue. It does not undo the import. The separate **Delete Import** command has a different, destructive purpose.

What Folder Loader preserves

• The source folder’s relative hierarchy.

• Existing managed targets and files on repeated imports.

• An existing main file rather than overwriting it, plus edited versions with different contents.

• A verified exported Paper Files relationship when a Gewu Insight manifest is present.

Folder Loader copies into Gewu Insight’s managed storage. It does not move, rename, or delete the external source files and folders you selected. Loader, Paper Details, folder and all-Library refresh use the same service and refresh history. **Quick refresh** updates core information (title, authors, journal and date) and verified DOI/arXiv links; **Full refresh** adds detailed authors, citations and other source data. Recovered identifiers use the selected mode. Partial source failures remain visible in the log and are not recorded as a fully successful refresh.

Identity mismatches and partial imports

Loader and File Explorer folder drops share the same matching and file-preservation policy. When a DOI, title or existing identifier disagrees with the matched paper, the incoming file is still saved in its Paper Files and the paper is placed in the target folder. Existing metadata and Default are preserved. PDFs with different bytes but the same DOI are kept as separate files; an exact unchanged copy already owned by that paper reuses its existing resource even after a source rename or move; the import continues without a mandatory review prompt.

The live log and **Result Guide** identify each mismatch by filename, detected DOI, existing DOI and Gewu Key. Correct a wrong assignment later from the file card's **Move to Another Paper** or **Create Paper from File** command. This preserves the PDF; it does not certify that the identified DOI is correct.

A disk or other import error can still stop a batch. Completed items remain available, and the result shows the failing file and actual progress. For a background drop, use the bottom bar's **Details** to reopen its current result and **Dismiss** when finished. Previously saved results remain available in Loader logs.

Delete an import batch

Delete Import is a rollback for the selected Loader batch, not a way to forget a log. Stop an active import first. The command removes database records created by that batch, eligible empty folders, its Loader reports, and managed local copies associated with the batch; eligible paths are sent to the Windows Recycle Bin. It never deletes the original external source directory.

Important

Review the selected batch and make a backup before using Delete Import, especially if you have already reorganized or reused imported items.

Note

For an ordinary folder, Loader does not guess paper-to-attachment relationships from similar filenames. A verified Gewu Insight export manifest can restore those relationships. After paper identity and ownership are known, the normal Default and Associated Files rules determine where that paper's managed files belong.

See also: Make a Portable Desktop Copy · Refresh Info: One Paper, a Folder, or the Library · Back Up and Upgrade

3-3.2 Make a Portable Desktop Copy

Make Copy Desktop creates a self-contained copy for transfer, inspection, or re-import.

Create a copy

1. **Right-click the non-root Library folder you want to export.**
2. **Choose Make Copy Desktop.**
3. **Wait for the completion message.** Open the resulting Desktop folder in File Explorer.
4. **Confirm representative files.** Check a paper with versions or attachments as well as a normal folder.

What is included

The export replaces managed filesystem shortcuts with real files, includes relevant Associated Files, and writes a verified manifest describing paper-file relationships. This lets Folder Loader restore the bundle on another installation without guessing from filenames.

Important

Do not edit or discard the export manifest before migration. Without it, Loader correctly treats the files as an ordinary folder and does not infer hidden associations.

See also: Use Folder Loader · Back Up and Upgrade · How Gewu Insight Stores Files

3-3.3 Back Up and Upgrade

Back up the selected Gewu Database and keep the installer for your current version. The executable alone is not your Library.

Keep the three locations separate

Location	Purpose
Installed program	Normally %LOCALAPPDATA%\Programs\Gewu Insight. Setup updates the application, bundled runtimes and guide.
Selected Gewu Database	Contains data, reports, config and backups, including SQLite, managed Library/Space files and notes. It stays in place during a program update.
Source checkout	Development code and build tools. Daily use starts the installed App from the Start menu; editing source does not update the installed App.

Create a consistent backup

1. Use **File > Open Gewu Database** to find the selected folder. Save website drafts and finish or stop background tasks.

2. Choose **File > Exit** and wait for the App and service to stop. Copy the entire database folder from this closed state, including hidden files, data/paper_monitor.sqlite, any accompanying WAL/SHM files, managed Library/Space files, Associated Files, notes, configuration and backups.

3. Preserve external originals used by Shortcuts separately. Keep Windows .lnk files intact; a shortcut does not contain its target's bytes. Historical import-source paths are provenance and need not be active file dependencies.

4. Keep %USERPROFILE%\.gewu-insight\database-location.ini, the current installer and relevant AI-client configuration as separate recovery material. Browser profiles are separate from the research folder.

5. Verify SQLite integrity, the copied file list and representative files on a separate copy. Store the backup outside the live database and keep the original until the replacement has been checked.

SQLite is authoritative. Copying only JSON exports, the program folder or a database file while it is changing is not a full backup. Do not replace the active database with an older file just to address a display problem.

Update the installed application

After a verified backup, close Gewu Insight and run the newer versioned Setup.exe. Open **Gewu Insight** from the Start menu, then check the selected data folder, existing papers and file access. Check the application version and build in **Help > About Gewu Insight**. Windows **Settings > Apps** also lists the installed version. Keep the previous installer and backup until verification is complete. Do not open the Library with an older incompatible version.

Move a database

For a collection already separate from the program, a routine App update keeps the same folder, identity, Gewu Keys and file classifications. Uninstalling retains research data, the locator and browser sign-ins. A move to another path needs an offline, verified migration of operational file paths and Windows shortcuts; retain the original and do not merge two populated database folders. Do not run the source service and installed App against the same collection.

Browser and credential boundaries

Bookmarks and history are in SQLite. WebView2 website profiles live separately under %LOCALAPPDATA%\Gewu Insight\Databases\<identity>\Browser; logs and cache use the adjacent Logs and Cache folders. The profile is not a portable sign-in export. Expect to sign in again on another computer. Browser tabs and unsent forms are memory-only and are not restored after quitting.

Metadata API keys and AI Access information can be present in workspace data. Keep full backups private. Exporting bookmarks produces bookmark HTML, not cookies, passwords or browsing history.

Transfer selected research files

Use Make a Portable Desktop Copy for a selected collection. Retain its export manifest and use Folder Loader to restore the file relationships. A portable collection is not a full backup of settings, monitor history and the database. Whole-workspace macOS-to-Windows migration requires separate validation of paths and platform files.

See also: Make a Portable Desktop Copy · Storage Reference · Troubleshooting

3-4 My Publications

3-4.1 My Publications

My Publications keeps a managed publication list, citation sources, author-role statistics, and export tools for your own work.

Choose your profile

1. **Enter a name, optional affiliations, or an exact Google Scholar profile URL.** For a name search, use Name; affiliation A; affiliation B.

2. **Choose Find Profile.** Review candidate profiles carefully.

3. **Choose Use Profile to review candidates individually, or Add All Publications to import the complete profile.** The saved strip shows the active name and profile photo. Select the photo to open the profile using Website Links; use the remove control to forget it.

Already have the paper in Library? Right-click its row and choose **Add to My Publications**. Multiple selected papers can be added together. The publication list and Library then refer to the same work, files, and Gewu Key.

Add all publications or choose individual papers

Use Profile opens a candidate list where each article retains its own **Add** button. To import the author's entire profile, choose **Add All Publications** beside the correct search profile or at the top of its article candidate list. These controls appear only inside the search/add area; the normal publication table keeps its original layout. The complete import reads successive source pages until the profile ends; it is independent of the 200-title candidate preview and has no 300- or 5,000-paper cutoff. Existing canonical articles and My Publications entries are reused.

The bottom status bar continuously shows active import counts and DOI/arXiv progress, including running, processed, paused, and retry-needed states. Completed imports move into **Import history**, which distinguishes original import counts from articles currently saved in My Publications. When only history remains, the footer entry reads **History**. Old imports do not appear in a new author search; its own status or error stays visible in the search panel. Choose **Details** in that bar to view full progress and import controls without searching again. The search/add panel opens when searching or choosing a profile and stays open until you choose its **Close** button; clicking a publication or completing a task does not dismiss it. Closing the panel keeps background work running and preserves the table position. **Pause Import** preserves completed work; **Continue Import** resumes it. An interrupted source page is retried without adding its successful articles twice. A blocked, unreadable, repeated, or interrupted source page is reported as incomplete with a short reason and guidance to try again later. Technical connection details stay in the diagnostic log. Individual identity conflicts do not stop later articles and remain reported for review and retry. Adding all again after completion explicitly checks the profile from its first page for additional articles.

Both individual Add and Add All automatically queue missing DOI/arXiv identifiers. Articles are saved first, and identifier completion runs separately in the background. Its progress distinguishes matched, unmatched, failed, and pending work. Switching tabs does not stop either task; unfinished work resumes after app restart. Identifier updates preserve the article's Gewu Key and file relationships. The existing per-candidate **Retry ID** remains available. When saved articles have unmatched or failed identifiers, **Retry Unresolved IDs** appears with progress inside the search/add area. Pausing the profile import does not pause identifier work already queued. Articles without a confident match remain saved. This operation does not automatically download PDFs.

After Scholar reports an access restriction, Gewu Insight applies a shared 24-hour pause to Scholar requests. The prompt shows the local retry time; this is an application pause, not a Google-provided IP-ban deadline. Changing authors or restarting does not clear it.

Add and update publications

• Use the identifier/title field and **Add** to add a DOI, arXiv record, supported identifier, or title.

• Choose **Refresh Metrics** to update citation services and PubMed data.

• **First as listed** is calculated automatically from the active profile name and the resolved author order, including the profile's English and Chinese name forms.

• Use **Co-1st**, **Co-corr.**, and **Rev.** in Paper Details to mark co-first authorship, corresponding authorship, and review/perspective papers. Leave Co-1st unchecked for a solo first-author paper. These manual roles are preserved during metric refresh.

• Use the star to highlight a paper. Star state is independent from citation refresh and export inclusion.

• Drag rows into a manual order when a curated sequence matters more than date or citation sorting.

• Choose **Comments** to build or open a citation-comments report from citing-paper metadata. This is not a personal note field.

• Use **Hide** or **Show** in the context menu to control export inclusion. Use **Open in File Explorer** or **Delete** for the corresponding local action.

Edit manual records and author marks

A publication without either a DOI or arXiv identifier exposes **Manual Metadata**. Edit Title, Authors, Journal, Date, Volume, Issue, and Pages, then choose **Save Metadata**. Separate author names with semicolons or new lines. Once an identifier is present, use identifier-based metadata controls instead.

Select an author name in the publication's author list to inspect affiliations and set **First author**, **Co-first author**, or **Corresponding author** for that named author. Checkbox changes save immediately. These individual author marks are separate from the publication's Co-1st, Co-corr., and Rev. summary controls.

Build a citation-comments report

Comments gathers citing-paper metadata and available Semantic Scholar citation-context sentences, then writes a local report that groups strong praise, positive impact statements, cautions, and unmatched citing records. It helps you review how later literature describes a publication; it does not modify the publication metadata or replace your own notes.

The report is a generated local reading artifact. Network services may return fewer contexts than citation records, and a temporary rate limit can leave some entries without quoted context. Reopen or rebuild the report later to retry the available sources; an existing report remains on disk until you deliberately replace or remove it.

Work with files

My Publications uses the same Paper Details and flat Paper Files model as Library. Expand **Files · n** within the details to inspect its resources; Library instead has an adjacent Paper Files column. The publication Files panel shows File type, Annotation, and Source controls directly; the size-footer expansion belongs to Library cards. A publication can keep a default PDF, earlier versions, supplements, notes, presentations, data, and other attachments under the same Gewu Key.

Read the summary

The lower summary includes publication counts, identifier coverage, h-index and i10 information, journal distribution, merged citation maxima, and major-paper role counts. Select a role statistic to filter the table where supported.

Export a list

Choose **Export List**, then select LaTeX PDF, LaTeX source, Overleaf project ZIP, or Word document. Papers excluded from export remain visible in My Publications but are omitted from the generated list. The export follows the current visible table, including its search, role/journal filters, and row order, and excludes rows marked Hide. Clear filters and search first if you want the full included list. Exporting never replaces the SQLite source.

The Overleaf option creates a project ZIP, copies it to the Desktop, and opens Overleaf using Website Links. The status message reports the saved path. It does not upload your files or create an Overleaf project automatically; import the ZIP yourself on the website.

See where a reordered row will land

When dragging a publication to change its manual order, a translucent copy follows the pointer. A blue circle and horizontal line mark the insertion position. The other rows stay in place during the drag; release to apply the order. This changes the publication list order, not the paper's file location.

See also: Literature Data Sources · Use Paper Details · Local Data and Privacy

3-5 Journal Monitor

3-5.1 Journal Monitor

Journal Monitor collects papers for a selected publication date and lets you narrow the result by journal, preprint source, and field.

Refresh a date

1. **Select a day in the calendar.** Small numbers below a day show stored result counts.

2. **Choose Refresh.** The app requests all configured journal sources for that date.

3. **Right-click the journal in Journal Filter and use Refresh This Journal when only that journal needs another attempt.** This avoids re-requesting journals that are already complete.

4. **Choose arXiv separately if needed.** This keeps journal and preprint work explicit.

5. **Watch the bottom status area.** It reports the current source and completion without changing the page height.

Manage monitored journals

Open **Journal Settings** to add or manage a journal by name, ISSN, or known publication history. When an ISSN is missing, the app can look up a matching journal record before saving it. Review the match rather than relying on a similar title alone.

Drag journals vertically in **Journal Filter** or **Journal Settings** to set their order. The saved order controls the filter list and the journal groups in the report. Removing a journal disables the subscription without erasing its previously collected papers or its saved history.

Your enabled list, disabled history, ISSNs, source identifier, section policy, logo source, and display order are saved in SQLite. Product updates can add better built-in source definitions, but those defaults do not replace this personal state. Adding a previously removed journal restores it at the end of the active order.

Understand counts and filters

The number beside each journal is the total stored count for that journal on the selected day. It is deliberately independent of **Field Filter**. The field checkboxes narrow the paper cards you can see; they do not rewrite the journal totals. A journal can therefore show a nonzero count while the current field selection hides every one of its papers.

Calendar counts summarize stored day results. A zero count is meaningful only after the relevant source completed successfully. Read the source status before interpreting zero as "the journal published nothing."

Daily scheduled updates

Journal Monitor is designed to keep a daily cached record through its scheduled update workflow. A scheduled run and a manual refresh use the same stored day results, so opening a date does not require downloading it again. Use a manual refresh when a scheduled source was missed, partial, or needs verification.

The scheduler belongs to the running local UI service; it does not wake a sleeping computer or run while that service is stopped. See When automatic updates run for the current timing and restart boundaries.

Journal logos and mathematical text

Configured journal logos are downloaded into a local cache and reused from disk. The first successful request may require network access; changing dates and later launches should not repeatedly download the same logo. The cache is presentation data and can be rebuilt without changing subscriptions or papers.

Supported inline LaTeX in titles and abstracts is typeset after the math renderer becomes ready. On a cold launch, raw source may be visible briefly, then the current day is rendered again automatically; changing to another date and back should not be necessary. Title normalization also preserves recognized proper names and source capitalization such as *Su–Schrieffer–Heeger* and *Monte Carlo* while still cleaning all-uppercase metadata and formula spacing.

How discovery provenance is preserved

Each stored Journal result is related to the canonical paper, the fetch run, and the source that reported it. The run preserves the journal, requested date window, status, and timing. Seeing the same paper from Crossref and OpenAlex records both source observations against the same paper identity; seeing it again within one run does not create a duplicate relationship. Later runs remain separately traceable.

The same canonical paper can also acquire Subject Monitor and Author Monitor relationships. These discovery paths explain why the work is visible; they do not automatically add a Library placement or create a local Paper Files resource.

Filter and inspect

Use **Journal Filter**, **Preprint Filter**, and **Field Filter**. Journal and field choices combine to determine the visible cards, while the journal counts continue to describe the full selected day. Enable **Figures** to show a representative image when available. Selecting a result opens its report and actions.

Act on a result

• **Open Website** opens the publisher or best known record using Website Links: a new built-in Browser tab by default, or the Windows default browser when selected.

• **Add to Library** begins the placement workflow described below; after that, **Show in Library** returns to the managed paper.

• **Download** retrieves the paper file. **PDF** opens an existing local PDF in Preview, and **Delete PDF** removes that managed download and resets its status.

• When a reading note exists, **Note** opens it in the right-side drawer. The list compresses but keeps its own scroll position. **Delete Note** removes the note and resets analysis status.

Read an existing Note

Note appears when a reading note has already been generated. It opens the saved note on demand in a right-side drawer; the report area compresses and each side scrolls independently. Drag the divider to resize the note. **Hide list** gives the note more space; **Show list** restores the report. Closing the drawer keeps the note. **Delete Note** is a separate action that removes it and resets its analysis status. Links in the note follow Website Links.

Add a Journal result to Library

1. **Choose Add to Library on the result.** The Library destination chooser opens without leaving the selected date.

2. **Choose the target Library folder.** This is the visible folder placement for the managed paper.

3. **Complete the add.** The card changes to **Show in Library**; use it to reveal the existing placement later.

The operation links the Journal discovery to the canonical paper, preserves its source and run provenance, and adds the chosen Library placement. It does not automatically download a PDF. Choose **Download** separately when you also want a local file. If the paper is already managed, **Show in Library** reveals it instead of creating a duplicate identity.

Per-paper status text and the bottom progress area make completed downloads and background work visible, which helps avoid repeating the same action.

Note

“No matching papers” and “source fetch failed” are different outcomes. Check the source status before concluding that a date is empty.

The destination chooser initially selects your Settings > Add to Library default, initially **Library / unsorted**. You can confirm another active Library or Space folder for this addition. The choice does not change the global default.

Journal tabs identify the journal by a supported wordmark or by text. APS titles, including Physical Review Letters, Physical Review X and Reviews of Modern Physics, use readable journal names rather than a publisher icon or a page image.

See also: Subject Monitor · Publisher and Network Access · Add Papers and Files

3-6 Subject Monitor

3-6.1 Subject Monitor

Subject Monitor discovers papers for reusable topics. Each subject stores a name and literal discovery terms; an optional copied prompt can help you draft those terms outside the app.

Create a subject

1. **Choose Add Subject.**

2. **Enter a clear name and discovery keywords.** Describe the field broadly enough to find variants, but avoid unrelated general terms.

3. **Use Copy Suggested Prompt if you want Codex-assisted wording.** Review the prompt before using it.

4. **Save and arrange the subject.** Subjects can be edited, deleted, and reordered.

Keywords use case-insensitive literal matching. Enter the words or phrases you expect to appear; they are not regular expressions and are not silently expanded into unrelated concepts.

Edit keywords without losing history

Right-click a subject and choose **Edit**. Saving a new name or keywords keeps its existing paper list, calendar counts, selection, and reading position. New keywords apply to future retrieval. Existing date windows, including empty and incomplete results, remain preserved after a keyword change; background retries and later local arXiv matching do not silently reclassify those windows.

Choose **Refresh This Subject** explicitly to rebuild that subject's selected date with the current keywords. A successful refresh replaces only that result window; other dates and subjects remain unchanged. An incomplete refresh preserves previous results. Editing during an active retrieval discards the obsolete result instead of

replacing history. Deleting a subject still clears its Subject Monitor matches, without deleting the underlying shared papers or Library files. Previously cleared matches from an older software version are not automatically reconstructed by this fix.

Keep one subject selected across dates

Selecting a subject makes it the active topic until you choose another one. Moving to a date with no result does not switch the tab back to the first subject, and a subject with zero papers remains selectable. The calendar's day numbers describe the active subject, so you can see which dates contain papers for that topic rather than a total across every subject. The count beside each subject tab describes that subject on the selected date.

The calendar shows the stored count as a number, including **0**, for the selected subject and date. Counts have no completeness marker. A date with no stored results and no fetch record remains blank. While a fetch is running, the progress indicator remains visible.

The **Discovery** row describes the recorded retrieval status for the selected subject. A completed retrieval is not a guarantee that every relevant paper has been found. Switching subjects changes the counts and recorded status; reopening the app preserves the status stored in SQLite.

Refresh subjects

1. **Select a calendar date.** Selecting a date only loads the result already stored for that day; it does not start a network request.

2. **Choose Refresh.** The command refreshes every configured subject for the currently selected date. The arXiv display option is enabled by default; clear it when you want to hide arXiv cards without changing what is stored.

3. **Read source status.** A source can be complete, partial, empty, or failed. Source-level retries are managed by the background scheduler.

4. **Cancel if necessary.** Completed results remain distinguishable from unfinished work.

Refresh one subject

Right-click a subject and choose **Refresh This Subject** when only that topic needs another pass. Use the main **Refresh** command when every configured subject should run for the selected date.

The current candidate layer can draw from local arXiv data, local APS RSS data, OpenAlex, Crossref, Semantic Scholar, and PubMed. It does not depend on a fixed number of feeds. Results still pass topic filtering and deduplication before display.

Inspect and keep a result

Select a paper to read its title, authors, abstract, source, date, identifier, topic score, and matched subject terms. Use **Open Website**, **Download**, **PDF**, and the note controls in the same way as Journal Monitor. Choose **Add to Library** to create a managed reference, or **Show in Library** when one already exists.

Add a Subject result to Library

1. **Choose Add to Library on the matching paper.** The subject and selected date remain in place while the destination chooser opens.

2. **Select the target Library folder.** The same canonical paper can be placed in a durable topic hierarchy without losing the Subject relationship.

3. **Complete the add.** Use **Show in Library** on later visits to reveal the managed placement.

Adding the result preserves the matched subject, score, terms, and discovery provenance. The paper remains visible in Subject Monitor immediately after adding it; its action becomes **Show in Library**, while the selected subject, date, and reading position stay in place. It does not automatically download a PDF; use **Download** separately. Repeated discovery of the same identity updates relationships rather than creating unrelated paper

records.

Important

Subject Monitor rejects Zenodo records during ingestion and when cached results are displayed. There is no Zenodo show/hide option.

The destination chooser initially selects your Settings > Add to Library default, initially **Library / unsorted**. You can confirm another active Library or Space folder for this addition. The choice does not change the global default.

See also: Journal Monitor · Publisher and Network Access

3-7 Author Monitor

3-7.1 Author Monitor

Author Monitor follows researchers and separates a first-import baseline from newly discovered work.

Add an author

1. **Choose the add-author control.**

2. **Enter a name and optional affiliations, or an exact profile URL.** Google Scholar and ResearchGate profile URLs are supported where the profile can be resolved.

3. **Confirm the correct person.** The initial result set becomes the baseline rather than a batch of unread “new” papers.

Understand profile and publication sources

Google Scholar profiles refresh through Scholar with shared pacing and cooldown. A ResearchGate URL identifies the public profile; its publications are matched separately through OpenAlex when configured. If unavailable, Gewu Insight automatically falls back to Semantic Scholar. Confirm the proposed person, especially for similar names.

Without a verified publication-data match, the ResearchGate profile and homepage can be saved, but automatic publication refresh remains unavailable. Profile, publication, and citation sources remain distinct evidence; a fallback does not change the author identity.

Reorder monitored authors

Drag an author in the left list to change its order. A translucent preview follows the pointer, and a blue circle with a horizontal line shows where it will be inserted. Other authors stay in place until you release. The order does not change the author’s profile source or publication records.

Review updates

Later refreshes can mark newly discovered publications as unread. Use the **New** filter and other author/result controls to focus the list. Select **Date** or **Citations** to sort; selecting the active sort reverses its direction. **Conferences · n** opens conference publications in a separate, independently scrolling popover, so they are not missing from the ordinary article list. Close the popover with its close control or Escape.

Right-click **New** and choose **Read All**. For one selected author, it marks every unread publication as read, including offscreen papers; other authors keep their unread state, even for a shared paper. With **All Authors** selected, it marks all authors' new publications as read. Papers and Library placements are preserved. The New filter remains active; click New again to see read papers. Read state persists after reopening.

Background work and status

Opening this tab reuses available local cards, including older cached lists, while the background checks for changes. It does not start another Scholar fetch. Background list updates retain your selection, reading position, open controls and details.

The bottom bar keeps publication checks separate from **Author metadata · All authors**. **Checking status...** means that these summary counts are still loading; it does not mean all papers are being repaired. Metadata counts cover all monitored authors, not just the selected author, and are recalculated from current missing information even during a daily pause. Ready work, retry waits and papers needing manual lookup are distinct; hover over shortened text for its full message.

Automatic DOI and abstract completion uses other metadata services, independently of Scholar profile checks. It rotates between authors and reuses shared paper identities: up to 20 papers per batch and 80 per local day, yielding between papers after about two minutes and resting at least five minutes between batches. Recent attempts wait seven days before automatic retry, with at most three automatic attempts per paper. Papers still unresolved then need manual lookup; completed papers are not periodically refreshed. Progress reservations and rest times survive restarting; explicit identifier commands remain available separately.

Scholar requests remain serialized, with 4–8 seconds between requests, 12–24 seconds between profile pages and 45–90 seconds between automatic author checks. Every request checks the shared workspace cooldown again before sending, including My Publications imports. Access restrictions pause Scholar for 24 hours; manual actions and restarts do not bypass or reset that pause. This is Gewu's protective waiting period, not a promised unblock time from Google.

A red **Google Scholar paused** message means the shared Scholar access cooldown is active. New restriction messages may identify HTTP 403, HTTP 429 or a verification page; an older generic message may lack that detail. A VPN exit can affect access, but the pause text alone cannot identify the cause. Changing networks or restarting does not clear the saved waiting period. Cached papers and non-Scholar metadata sources remain available.

A refresh reports identity review

If one publication conflicts with an existing identity, the refresh preserves existing papers and files and continues with the remaining publications. The result reports how many need review and identifies the first affected record, Gewu Key and reason. Read the full message before editing: incomplete identity evidence, contradictory metadata and a protected merge are different cases. Compare the title, authors and identifiers; do not delete files or create another copy to silence the warning. A review message can persist after the refresh finishes and is not itself a running repair task.

Recover after a network interruption

A temporary connection failure shows **Google Scholar temporarily unavailable** in the bottom bar. Hover over it for the author, error and retry details. Cached publications remain available. After the connection returns, keep the App running: failed transport requests have a paced automatic retry queue, including before the normal 10:00 daily check. The message clears after a successful retry, not immediately when Wi-Fi reconnects.

An unreadable Scholar publication list is a failed check, not evidence of no publications. Saved papers and the last successful check are retained. Automatic checks stop probing other Scholar authors in that pass, wait an hour, and allow at most three unsuccessful page probes per day before waiting for the next daily check. An access restriction has its separate cooldown. You can use **Refresh This Author** for a deliberate retry when permitted.

Refresh one author or find missing identifiers

Right-click the author and choose **Refresh This Author** to update that person's publications. **Find Missing Identifiers** checks eligible papers for that author. To check only one unidentified paper, Right-click the paper and choose **Find Missing Identifier**; it is disabled when an identifier already exists or a lookup is running. These online lookups differ from **Get DOI**, which uses an available local PDF.

Update citation profiles

For a Google Scholar author, use the circular arrow beside the name or Right-click the author and choose **Update All Scholar Citations**. Review the request estimate, then confirm **Update All Citations**. This rereads only that author's Scholar profile, updates citation counts and discovers new publications. It does not start a Library-wide metadata refresh. Follow the bottom progress status until it finishes.

Manage the profile image

Right-click an author and choose **Edit Homepage** to edit the website, or **Change Photo** / **Add Photo** to choose a local portrait. Downloaded Scholar avatars are saved locally. Opening the author list does not need to reopen SQLite or contact the image host for every row; a manual photo takes precedence. Without a valid local photo, the list can show initials until you refresh or replace the image.

Discovery entries and managed papers

An Author Monitor result is a cataloged shared record, with a Gewu Key shown in its details even before it has Library placements or local files. A missing key displays (undefined) until record data is available. Add to Library preserves the existing key and updates the view; downloading or attaching a file creates a resource relationship.

When repeated discoveries identify the same work

Stable Scholar entries, normalized DOI and version-independent arXiv identities are reused across discovery and later metadata updates. When two existing records are safely confirmed as one work, Author Monitor keeps one card for that author. The same paper can still appear under several different authors. Unread state is retained if either repeated entry was unread.

Reconciliation preserves Library and publication relationships, source history, registered files, classification and manual Default. Old Gewu Keys continue to resolve to the surviving paper. Contradictory manual identifiers, competing manual Default choices or insufficient identity evidence keep records separate for review. A shared DOI is not permission to indiscriminately merge every historical duplicate; startup performs no historical merge sweep.

Add an author result to Library

1. **Select the publication and choose Add to Library.** This opens the Library destination chooser without removing the author from view.

2. **Choose the target Library folder.** The selected placement becomes the durable organizational path for the shared paper record.

3. **Complete the add.** The action becomes **Show in Library**, which reveals the managed paper later.

The author-publication relationship and canonical identity remain intact. Adding a placement does not automatically download a PDF, and a paper already managed elsewhere is reused rather than duplicated.

Remove a monitored author

Right-click the author and choose **Remove from Monitor**. Removing an author deletes the monitoring relationship and its monitor state. It does not delete papers already added to Library, their managed PDFs, or their Paper Files bundles.

Note

Google Scholar requests are paced and protected by a cooldown. Repeated manual refreshes during a block do not improve the result.

The destination chooser initially selects your Settings > Add to Library default, initially **Library / unsorted**. You can confirm another active Library or Space folder for this addition. The choice does not change the global default.

See also: My Publications · Publisher and Network Access · Local Data and Privacy

3-8 Browser

3-8.1 Browse, Bookmark, and Revisit Websites

Browser is the sixth main tab, after Author Monitor. By default, website links across Library, My Publications and all three Monitors switch here, opening a new webpage tab without replacing existing pages. This includes Open Website and Google Scholar links. Choose Settings > Website Links to use the system default browser instead.

Search and navigate

1. **Open Browser.** On first use, Home displays your local Favorites folder. Later switches return to your selected webpage; use Home to return to Favorites. A paper link opens its destination directly in the unused first tab. No Google webpage is loaded for Home.

2. **Use the address field.** Enter a website address or search terms. Plain search terms go to Google; an address opens directly. Use Ctrl+L to focus the field.

3. **Navigate normally.** Back, Forward, Reload/Stop, and Home act on the selected tab. Home uses the content area for Favorites; websites, search results, sign-in pages and PDFs use it for browsing.

4. **Switch between workspaces.** Returning from Library or a Monitor preserves the current page and browsing position without reloading merely because the main tab changed.

Return to the source workspace: Ctrl+[. After a website link in Library, My Publications, Journal Monitor, Subject Monitor, or Author Monitor brings you here, press Ctrl+left bracket to return to that workspace's retained selection and scroll position. The physical left-bracket key also works with a Chinese input method selected. It works from the webpage or address field and leaves Browser tabs open; it is not webpage Back. Each linked webpage tab retains its own source for this App session, including related PDF tabs. Switching tabs selects the corresponding return destination. Library links retain the original paper and occurrence; an unrelated address entered in the toolbar clears that tab’s association. Entering Browser directly does not create a source. Close any open dialog first.

Local Home, online search. Favorites is available without loading Google, even after restarting the App. Home has no Google logo, search box or account controls; use the toolbar address field to search. Reload on Home refreshes local bookmarks, not a website. Site icons may need a connection; missing icons show initials. Webpages and sign-in remain online and share Browser's existing profile.

When you search or follow a link from Home, Home remains visible while the destination begins loading, then gives way to that destination. It should not flash the page you visited before Home. A cancelled or failed pending navigation leaves Home available rather than presenting that older page as the result.

Ctrl+F opens Find on Page. Enter selects the next match and Shift+Enter the previous match. Browser is part of the Windows desktop application; a separately hosted web UI does not embed a second browser engine.

Favorites on Home. Favorites/Favourites (including localized names) supplies the tiles; use **Create Favorites Folder** if missing. Open nested folders and return through breadcrumbs; use **Add Favorite** or right-click to edit. The grid uses the whole main area, without a Google section or divider. Excess tiles use Previous/Next, not vertical scrolling. Bottom bars align; hiding the sidebar keeps Favorites visible. Opening google.com explicitly shows an ordinary webpage, without Home-specific styling or zoom. Bookmarks are not sent to Google.

Use multiple webpage tabs

Below the address toolbar, adjoining rectangular tabs show × at the far left of each tab, with its icon and title centered together, above the webpage column only. The sidebar begins directly below the toolbar; it is not pushed down by the webpage tabs. The top-right **+** (**New Tab**, Ctrl+T) opens Home. Switching preserves each page, position and Back/Forward history without reloading or stopping background loads.

Right-click a webpage link and choose Open Link in New Tab. Bookmarks, Favorites and History provide Open in New Tab in their context menus. Ordinary clicks open in the current tab; new-window links can create another tab.

× or Ctrl+W closes a tab; closing the last opens Home. Left/Right switches focused tabs. Up to 32 tabs stay in memory, not restored after App quit. Save drafts before closing; bookmarks, history, downloads and sign-ins remain.

Save and organize bookmarks

The sidebar's top tabs switch between **Bookmarks** and **History**, without a repeated heading. The compact **B** (Bookmarks menu), **+** (New Folder), and Search sit along the bottom, even at the minimum sidebar width. History shows Clear History and Search there instead. Drag the sidebar's right edge to resize it or use the toolbar to collapse it. Width, tab, and expanded folders are saved locally.

1. **Add a page.** Use the bookmark toolbar button, **Share > Add Bookmark**, or Ctrl+D. The native sheet starts with the page title and address.

2. **Choose a location.** Edit the name or address and choose a folder under **Add to**. The previous destination is remembered. Saving the same address in the same folder reuses the existing bookmark.

3. **Create nested folders.** Use **New Folder**, or right-click a folder to create a child folder. The editor can also rename a folder or choose another parent.

4. **Arrange the tree.** Drag an item into the middle of a folder row to move it inside, or to a row edge to reorder it. Drop on the top **Bookmarks** tab to move to the root. A folder cannot move inside itself or its descendants.

5. **Save by dragging.** Drag the website icon beside the address field, or a webpage link, into a bookmark folder. Confirm the name and destination in the same native sheet.

Search filters bookmark names and addresses. Right-click a bookmark for **Open**, **Edit Bookmark**, or **Delete**. Deleting a folder requires confirmation and removes its contained bookmarks, not websites, browsing history, downloaded files, or papers. A bookmark is a saved link, not an offline webpage copy.

Import and export bookmarks

Choose **B > Import** at the bottom of Bookmarks and select a Safari or Chrome bookmark HTML file. Safari versions with **File > Export Bookmarks** produce HTML; newer Safari versions may use **File > Export Browsing Data to File** and produce ZIP. Select bookmarks only when exporting. Gewu accepts a ZIP containing exactly one bookmark HTML file and ignores all other members. In Chrome, use **Bookmark Manager > menu > Export Bookmarks**.

Imports go into **Imported Bookmarks**, retaining folders, order, names, and supported links. Repeating an import merges matching folder names and reuses the same URL in the same folder; existing bookmarks are not overwritten. The result reports added bookmarks, new folders, duplicates, and skipped links. Local addresses, application links, and recognized authorization links are skipped. Limits are 10 MB, 20,000 source entries, and 64 folder levels; invalid files do not partially import.

B > Export saves the full tree as standard bookmark HTML; right-click a folder for **Export Folder**. Safari and Chrome can import this format. Exports contain no history, cookies, or passwords, but their bookmark names and URLs are readable by anyone with the file. Keep personal exports private.

Sync one source folder into Gewu

1. Choose B > Sync from Chrome. This is a manual, one-way operation; it does not watch the source or write changes back to Chrome.

2. Select Chrome's Bookmarks file from the intended local profile, normally under %LOCALAPPDATA%/Google/Chrome/User Data/Default/ or a Profile directory. Only that selected file is read. Choose its folder/subtree, then confirm the manual one-way sync.

3. **Choose one folder.** The next sheet lists source folder paths and bookmark counts. **Sync Selected Folder** includes that folder and its descendants, not its siblings or the whole profile. Cancel leaves Gewu bookmarks unchanged.

4. **Review the result.** New links and folders are added. Stable source identifiers allow later source title/address changes to update entries created by sync. Pre-existing matches and items edited or moved in Gewu are kept. Source deletions do not delete local bookmarks. The result reports additions, updates, local changes kept, and skipped links.

The selected folder is placed at the Bookmarks root; matching folder names and same-folder URLs are reused. Sync tracking lives in SQLite, independently of papers and website sessions. Legacy source entries without stable identifiers merge by folder/name/URL rather than overwriting local edits. Switching source files or profiles is a separate source. Limits match import (10 MB, 20,000 entries, 64 levels), with at most 2,000 folders in the chooser. Invalid input or a failed transaction leaves no partial sync.

Windows supports manual Sync from Chrome using one selected local bookmark file and subtree. Safari source sync is not offered. Import an exported bookmark HTML file when no supported local source is available; source files are not modified.

Navigate Browser with arrows

From the top **Browser** workspace tab, press Down to enter the toolbar. Left/Right moves among available toolbar controls; Enter activates one. At the address field, Enter or typing starts editing; its arrows then edit text or browse address suggestions. Escape returns to the toolbar. Up from the toolbar returns to the top Browser tab, where Left/Right changes workspaces. The Library exception is unchanged: Up within Library content does not ascend to its top workspace tab.

Down from the toolbar selects the current webpage tab. Left/Right selects adjacent webpage tabs; Down enters Favorites or the native webpage. Favorites uses directional tile selection and Enter to open. At the left edge, Left enters the visible sidebar on its currently active Bookmarks/History tab; Down traverses its list and footer controls. Right returns to the main area. A hidden sidebar is never selected. In the sidebar header, Left focuses the other collection tab and Enter activates it.

Inside an ordinary webpage, arrows remain WebView2 scrolling controls. Once Up reaches the document top, it can hand focus back to webpage tabs; two more Up presses reach the top Browser tab. Left at a document's left boundary can enter the visible sidebar. Inputs, editable text, framed/PDF content, and recognized or uncertain custom widgets keep their own keys; no form values are read or filled. A boundary check runs only after an eligible arrow press, without background polling. Use Ctrl+L, then Escape, to return to the toolbar from a document that retains its own arrows.

Website icons

Bookmarks, Favorites and webpage tabs use a disposable local icon cache, separate from SQLite. Icons come directly from sites (at most two concurrent requests), without cookies, credentials, whole-article fetching or third-party icon services. Visits may supply a nonstandard icon URL. Missing icons use globes or Home initials; bookmark lists are never sent to an icon service.

Revisit and clear history

History groups loaded main pages by Today, Yesterday, and date, with names, sites, visit times, search, and pagination. Subresources, main-tab switches, and cached Home returns add no visits; Reload updates the existing record. Click to revisit; right-click to bookmark or delete a visit.

Clear History confirms Last hour, Last 24 hours, Last 7 days, or All history. It preserves bookmarks, downloads, cookies, and sign-ins. History remains until deleted; authorization callbacks and recognized signed-download URLs are excluded.

Address suggestions from your history

As you type in the toolbar address field, Gewu searches saved local visit titles and URLs. Address prefixes rank first, followed by matching titles; visit frequency and recency help order the results. A matching address can complete the typed prefix with its remaining text selected. These are local history suggestions, not live Google suggestions, and typing does not send a suggestion request to a search engine.

Use ↑/↓, then Enter to open a result, or click it to open directly. Escape dismisses suggestions and restores your typed query. Without a chosen completion, Enter opens an address or searches Google normally. Clearing history also removes those visits from suggestions; bookmark search remains a separate sidebar control.

Read PDFs and save downloads

Viewable PDFs stay inline, including attachment/download links, with article/PDF Back/Forward navigation. In a publisher's HTML viewer, click its PDF download link: Browser receives the PDF using its current website session and opens it in that tab, including supported page-generated files. **Opening PDF…** shows progress. Switching tabs does not interrupt it or let completion take focus; leaving the source page or closing its tab cancels that pending preview. Website sign-in and consent pages remain visible.

Preview uses temporary browser storage, not your Downloads folder or Library. PDF attachment previews accept up to 128 MB and two minutes per transfer. Save to Gewu and the bottom-right **Save Download** arrow reuse a complete loaded PDF; they do not silently download it again. Both the bottom-right arrow and the PDF viewer's own download arrow open a native save dialog, initially in Downloads. Confirm the filename and destination to write the file; Cancel leaves it unsaved. Original-file copies are temporary and bounded; navigating to another document or closing its tab releases them. To import a PDF, use **Save to Gewu** below or import a saved file. Library PDFs still open in the Windows default PDF application.

System networking and Clash rules

Browser uses WebView2 and the current system network configuration. Gewu does not change proxies or Clash rules. Verify the actual route for publisher, PDF, login and CDN hosts independently; institutional access remains subject to the website.

Save an article and PDF to Library

Save to Gewu opens a compact dialog with **File type**, **Add to Library**, Cancel and Save to Library. Click the double-arrow **Details** to expand article identity and PDF controls. Set its default under **Settings > Website Links**.

1. **Open the article or PDF.** Follow **Open Website** from a research workspace, or find the article directly in Browser. Wait for the page to finish loading and click **Save to Gewu**.

2. **Review identity in Details.** Check the title, DOI and Gewu Key. An existing DOI or known arXiv identity reuses its paper record, including a record discovered only in a Monitor. A new article receives its own Key when saved. If needed, enter a DOI/arXiv ID and click **Identify**. Without an identifier, enter the article title and choose **Use this title**; metadata can be completed later.

3. **Choose the PDF in Details.** For a directly opened PDF or a detected embedded PDF (such as an IEEE full-text viewer), Gewu reads the loaded original and parses its information again. It does not request the PDF from the publisher again. If several loaded PDFs are present, select the intended one first. **Use Loaded PDF** retries this local read. If WebView2 cannot supply the complete original, an error is shown; **Download PDF Again** explicitly requests another download. On an article page, select a detected link and click **Get PDF**, or choose a local PDF. Each file must be readable and no larger than 128 MB. Check the filename and leave **Include this PDF in Paper Files** selected to attach it.

4. **Choose the destination.** Click the folder button under **Add to Library**. The same column picker used by Journal and Subject Monitor shows **My Library** and Spaces on the left, then subfolders in successive columns. Check the full path and click **Confirm** to select the destination. Choose the file type, then click **Save to Library** to import. Recognized publisher article PDFs suggest **Published version**, while recognized Science First Release PDFs suggest **Accepted manuscript**. Recognized arXiv, bioRxiv, medRxiv, ChemRxiv and Research Square

preprints suggest **Preprint**, regardless of the article's journal metadata. Review the suggestion; uncertain files remain **Unknown**. The first article PDF becomes Default in the main folder, even if Unknown. Supplements stay separate, and manual Default is preserved. Source follows the PDF's actual website: Publisher, Preprint server, Institutional repository or Other. Local files use User import without a webpage source.

Opening Details, identifying or cancelling imports nothing. Save reuses an existing active Library or Space placement, preferring the selected occurrence of that same paper. Attaching a PDF does not add a root-level entry. To add another location, explicitly choose and confirm its folder. Papers with no active placement use the folder saved in Settings > Add to Library, initially **Library / unsorted**, unless you confirm another folder. An unavailable saved default falls back to unsorted. Review creates no placement; the destination is checked again on Save. Paper Files refreshes immediately. Exact duplicates retain their existing source and settings; distinct versions stay separate, and manual Default is preserved. **Show in Library** selects the saved occurrence. Browser keeps the webpage.

Use the original paper or correct the target

A tab opened with Open Website or the arXiv arrow remembers its source paper and Library occurrence, including related PDF tabs. Save to Gewu uses that existing paper when the current evidence agrees or provides no conflicting identifier. Manually corrected DOI/arXiv values take precedence over old automatic matches. If the page identifies another work, the source is not forced onto it.

1. **Enter the correct existing Gewu Key in Details.** Press Return or choose **Use Key**.

2. **Wait for Target updated.** Check the displayed title, Key, existing-article status and **Add to Library** path. The review switches to that paper's active location when available. An unknown Key produces an error and creates nothing.

3. **Review any conflicting evidence.** If the page or PDF identifies another work, explicitly confirm that this file belongs to the selected target before saving. Changing the identifier afterward requires another review.

4. **Check the PDF and File type, then save.** Selecting a target attaches the file without replacing that paper's DOI, metadata or manual Default. Choose **Automatic** to return to automatic identity detection.

What Article only means. No PDF is currently included in the review. Article identification and PDF attachment are separate: identifying a DOI can find the existing paper without attaching a file. Expand Details and inspect the PDF controls. A loaded complete PDF can be reused through **Use Loaded PDF**; otherwise open the site's actual PDF or choose a local file. This status alone does not mean the publisher has no PDF.

If PDF retrieval fails: retry after opening the site's PDF, choose a downloaded local PDF, or save the article alone. Errors stay visible; missing or conflicting identity opens Details. If storage fails after saving the article, retry reuses its record and placement. Browser capture uses its current WebView2 session without exporting sign-in cookies. It cannot bypass a site's login, access rights or embedded-browser restrictions. The collector currently belongs to Gewu's built-in Browser; a Safari extension is not included.

Privacy and compatibility boundaries

Bookmarks/history use local SQLite; cookies/cache use Browser's persistent profile, not Chrome synchronization. Browsing/search reaches websites, but external pages have no Library/credential bridge. Local/file/application addresses are blocked. Standard internal child documents use WebView2's origin and sandbox rules; they cannot become address-bar destinations. HTTP recovery retries once as same-host HTTPS GET, without replaying forms or bypassing certificates; errors include reason/code. The local server rejects cross-site API requests and unrecognized hosts.

Website sign-in on Windows

Complete normal publisher or institutional sign-in yourself in Browser. Its WebView2 profile is separate from Chrome and Edge. Gewu does not import their cookies or credentials. Apple Passwords and its AutoFill trigger are not available in this Windows application.

Review PDF identity before saving

Save to Gewu matches the PDF to the selected article. An article's correction metadata pointing back to its own DOI does not by itself make the article a notice. A genuine correction or other publication notice is reviewed under its original article; check the displayed target and file classification. If the original article cannot be resolved, enter its Gewu Key and confirm the attachment.

If PDF drawing order joins a distant ellipsis to a title-page DOI, Gewu checks the layout of that same page. It accepts the complete DOI only when the evidence is unambiguous. Different article identifiers still require review, and the saved PDF bytes are unchanged.

3-9 Settings and Safety

3-9.1 Literature Data Sources

Use **Literature Data Sources** to configure services for literature discovery, metadata, citations, and version matching.

Built-in sources work without setup. Optional credentials improve access or coverage for supported services.

Open settings

Choose Settings > Literature Data Sources. The dialog provides provider settings and separate connection tests.

Available services

Service	Configuration
Crossref, arXiv, DataCite	Built in; no key field is required.
OpenAlex	Optional OpenAlex API key.
Semantic Scholar	Optional API key. Anonymous access remains available.
NASA ADS	Optional API token for astronomy and physics coverage.

Save a credential

1. **Paste the credential into its service field.**

2. **Choose Save beside that service.** Each service has its own Save, Test, and Clear controls.

3. **Choose Test and read the status underneath.** This checks service access; it does not refresh every paper. Then refresh one paper to inspect the available citation evidence.

A configured field shows fixed round dots by default, while the detailed status below continues to report saving, connection, or quota information. The dots do not expose the key or its length. Click **Show** inside the field to reveal the saved key, or inspect a newly typed key; click **Hide** to mask it again. A saved key is retrieved only on Show, and its displayed value is cleared on Hide or when settings closes. Type a replacement and choose **Save** to change the key; **Clear** removes the locally saved key. A configured environment key can remain available. Avoid screenshots or screen sharing while a key is visible.

Semantic Scholar sends its key in the official x-api-key header. Requests share a low-rate queue and use exponential backoff after rate limits or temporary failures.

OpenAlex status reports the remaining daily free allowance and its reset time when available. Gewu uses only that free allowance and falls back to other metadata sources when it is exhausted; it does not spend paid OpenAlex

credits. A saved key is not proof that every remote request will succeed.

Important

Credentials are local-only: store them in local SQLite or approved environment variables. Do not place keys in source files, logs, exported reports, tests, or Git.

See also: arXiv Scope Settings · Field Settings · Local Data and Privacy · Publisher and Network Access

3-9.2 arXiv Scope Settings

Choose one or more arXiv subject archives for discovery. Selections can span several research fields or combine several groups within one field.

Open arXiv Scope Settings

Choose **Settings > arXiv Scope Settings**. The window lists every supported primary subject and its archive groups. Select at least one group, then choose **Save**.

Understand the hierarchy

The first level identifies a broad arXiv subject such as Physics, Computer Science, Mathematics, Economics, Electrical Engineering and Systems Science, Quantitative Biology, Quantitative Finance, or Statistics. Each checkbox represents an archive group beneath that subject. For example, **Physics > Condensed Matter** includes all cond-mat.* leaf categories.

You may select several groups under Physics, or combine groups across primary subjects. Categories shared by more than one scope are fetched only once.

Default and saved behavior

• The default selection is only **Physics > Condensed Matter**.

• **Restore Defaults** changes the selection in the window; choose **Save** to apply it.

• Saving changes future arXiv refresh coverage and rebuilds the available **Preprint Filter** categories.

• Previously saved papers remain in SQLite. Changing scopes never deletes earlier discoveries.

Note

The category checkboxes in Journal Monitor are display filters. They do not narrow the discovery scope selected here.

See also: Journal Monitor · Field Settings · Literature Data Sources · Publisher and Network Access

3-9.3 Field Settings

Choose which research fields appear as separate filters across the workspaces.

Open Field Settings

Choose **Settings > Field Settings**. Select a field to show it as a separate filter and label. Clear it to collect that field under **Other Fields**, then choose **Save**. Closing without saving leaves the earlier presentation in effect.

Default organization

Shown separately by default	Grouped under Other Fields by default
Physics	Astronomy & Astrophysics
Quantum Information	Particle & Nuclear Physics
Materials Science	Mathematics
Chemistry	Computer Science
	Biology & Medicine
	Statistics
	Economics & Finance
	Electrical Engineering
	Earth & Environmental Science
	Social Sciences
	Unclassified records

How the visible filters behave

• **Other Fields** appears immediately above **All Fields**.

• **All Fields** is always the final choice and includes every classified paper.

• Changing this setting updates field filters, counts, badges, and Paper Details across Journal Monitor, Subject Monitor, Library, My Publications, and Author Monitor.

• Canonical field assignments stay in SQLite and reappear when a field is selected again.

Note

Use **Restore Defaults** to save the four-field default immediately. Field Settings do not change arXiv discovery coverage; configure that separately in **arXiv Scope Settings**.

See also: arXiv Scope Settings · Literature Data Sources · Journal Monitor · Subject Monitor

3-9.4 Preview Settings

Open Settings > Preview Settings to inspect the built-in preview preference.

Windows offers **Gewu Insight for all files**. The macOS hybrid and all-native options are not shown. Space opens the supported built-in reader or a file card for the selected resource.

Open in Default App is separate: it follows Windows file associations. Gewu Insight has no separate default-PDF-reader setting. Set the associated application in Windows when needed.

See also: Preview Files · Understand Paper Files · Navigate with Mouse and Keyboard

3-9.5 Default Add to Library Folder

Choose where a newly added paper starts. The initial default is Library / unsorted ; existing Browser captures keep their active paper location.

Set or restore the default

1. Open **Settings > Add to Library**.

2. Choose **Choose Folder**, select an active Library or Space folder in the column picker, and confirm it.

3. Choose **Save**. Closing the settings window without saving discards the new choice. **Restore Default** immediately saves Library / unsorted again.

How each entry point uses it

Entry point	Destination
Journal, Subject or Author Monitor > Add to Library	The picker preselects the saved default. Confirm another folder to override it for this addition.
Browser > Save to Gewu, existing active paper	Reuse that paper's active Library/Space placement, preferring the originating selected occurrence of the same Key. The new default does not create another location.
Browser > Save to Gewu, no active placement	Use the saved default, unless you explicitly choose and confirm another folder.
Folder Add Paper, File Explorer drop or Folder Loader	Keep the destination of that explicit operation. This preference does not redirect an import already aimed at a folder.

The preference follows the selected folder when it is renamed or moved. If it is deleted, recycled or unavailable, a later default addition falls back to Library / unsorted. Recycle cannot be chosen. If an explicitly selected destination becomes unavailable before Save, choose a valid destination again.

This affects future additions only. It does not relocate existing papers, change Gewu Keys, copy PDFs, alter file classification or change Default. Choosing a local disk path is not the same as choosing a managed Library folder.

See also: Save an article and PDF to Library · Folders, Shortcuts, and Spaces · Use Folder Loader

3-9.6 Website Links

Choose one browser preference for website actions across your research workspaces.

Open **Settings > Website Links**, select an option, and click **Save**. The choice applies to the next website action and is remembered after restarting Gewu Insight. Closing the dialog without saving leaves the previous preference in effect.

Option	Behavior
Gewu Insight Browser (default)	Opens a new built-in Browser tab, preserving existing pages. Press Ctrl+[to return to the source workspace.
System Default Browser	Opens the website in the default web browser selected in Windows. Your current Gewu workspace stays in place.

This applies to Library (including Spaces), My Publications, Journal Monitor, Subject Monitor, and Author Monitor: **Open Website**, publisher arrows, DOI/arXiv links, Google Scholar, author profiles and homepages, citation sources, remote PDF links, Overleaf, and links inside Note. **Restore Default** saves Gewu Insight Browser and collapses Save to Gewu Details by default.

Show Details by default controls how Save to Gewu opens. It is off initially; Save remembers it after restart. Toggling Details inside one dialog preserves its fields and does not change this preference. Unsaved settings changes are discarded.

Local files open through Windows file associations; File Explorer, the built-in preview and downloads keep their own actions. Browser's explicit Open in Default Browser opens the Windows default browser with its separate website session. Changing Website Links does not transfer cookies or existing tabs.

See also: Browse, Bookmark, and Revisit Websites · Use Paper Details · Preview Settings

3-9.7 AI Access

Give an AI client access to selected papers through their stable Gewu Keys, without navigating the interface.

Settings > AI Access is off by default. Normal App use needs no AI token. Enabling it does not start a model, analyze papers or upload your library. Requests happen only when a connected AI client calls the local service.

API, MCP and your token

Name	Meaning in this connection
API	**Application Programming Interface**: the operations another program can request from Gewu Insight.
MCP	**Model Context Protocol**: a shared way for an AI client to discover and call tools. Gewu's local MCP adapter translates those calls into its API requests.
Access token	A private credential issued by Gewu Insight. It authorizes a connection's paper collection and permissions; it is separate from your AI account login and from text tokens counted by models.
Gewu Key	The stable identifier of a paper. It selects the article; the access token authorizes access to it.

Methodology: a stateful information infrastructure

Gewu Insight gives people and AI clients a shared, persistent research workspace. **Stateful** means that cataloged papers, their identities, registered files and saved analyses remain available between tasks. SQLite is the source of truth for records and relationships; the documents remain local files. The Gewu Key lets a person or an authorized AI return to the same paper across conversations and clients.

The API exposes supported operations with defined inputs and structured results. An AI can retrieve a paper by key without navigating the interface or depending on the internal database schema. MCP makes those operations discoverable as tools; a script can use the HTTP API directly. Both use the same underlying records and authorization rules. Gewu supplies the material and stores approved results; the connected AI performs the analysis.

Design choice	How it helps research work
Stable paper identity	Use one Gewu Key to connect the article, its files and analyses across tasks. A title or filename is not the identity, and knowing a key does not grant access.
Explicit, bounded operations	Search with pagination and read selected pages or text chunks. Programs can compose these steps and limit unnecessary retrieval without relying on screen coordinates.
Persistent, traceable results	Save a Markdown analysis under the same key with source file references. People can inspect it in Paper Files, and another authorized session can retrieve it later.

This provides a foundation for continuing literature analysis and reusing saved knowledge. It does not automatically preserve an AI's conversation or reasoning, build a semantic memory index, or synchronize model memory. A later session must explicitly retrieve the records and notes it needs; access still depends on its current grant and the continued availability of those records and files.

Two API routes, one authorization boundary

Route	Where permission is checked
AI client → MCP adapter → Gewu API	The adapter sends the connection token to the API. MCP does not grant additional access.
AI client or script → Gewu API	The caller supplies the same kind of token directly. Skipping MCP does not skip API authorization.

For either route, the API checks that AI access is enabled, the token is valid, unexpired and unrevoked, the requested paper is in the connection's collection, and the operation is permitted. Metadata access alone does not authorize directory browsing, file reading or analysis writing. The native App uses a separate private workspace session for normal human use; an AI token cannot call those internal UI endpoints.

Interface authorization and local file permissions

AI Access controls requests through Gewu's interfaces. It does not encrypt or isolate SQLite and document files from software that already has operating-system permission to read them. Such software can read the disk without contacting MCP or the API; administrator privileges are not necessarily required. Turning off AI Access or revoking a token stops access through that grant, but does not revoke independent filesystem permissions. This broader local access is outside the AI Access permission boundary.

Create a connection

1. Keep Gewu Insight running and enable **AI access**.

2. Expand **New Connection** and enter a name you will recognize.

3. Choose Library, Spaces and My Publications; one folder and its subfolders using the usual folder picker; or specific Gewu Keys. A folder connection follows current membership.

4. Article metadata and file names are readable by default. Separately allow directory browsing, file contents and/or adding new Markdown analyses when your task needs them.

5. Choose an expiry, then **Create Connection**. The default is 30 days.

6. Use **Copy MCP Configuration** to obtain the local adapter path, Python executable, port and token. Enter these in your AI client's MCP settings using its required format. See the Codex example below.

Keep the connection private

The token is shown only after creation. Store it in client configuration, not in a chat message or shared document. If it is lost, revoke that connection and create another. An AI client may send authorized content to its model provider.

What an authorized AI can do

Tool	Result
search_papers	Search authorized titles, DOI, Gewu Keys and abstracts, with pagination.
list_folders	List authorized Library and Space roots, or a folder's direct children, with stable IDs, logical paths and filtered counts. Requires directory-browsing permission.
list_folder_papers	List each authorized paper placement and its Gewu Key in a directory, directly or recursively. Includes pagination and minimal metadata. Requires directory-browsing permission.
get_paper	Get the article metadata, file inventory and Default file ID for a Gewu Key.
get_paper_file	Get an original PDF or registered attachment as a read-only temporary copy on the local AI client's machine, with paper metadata, file ID and actual SHA-256. Requires file-reading permission.
get_file_delivery_status	Show used and remaining temporary capacity, file slots and active delivery IDs for this MCP connection.
release_paper_file	Release a temporary copy by its delivery ID after reading finishes, and show the restored quota. Original Paper Files and saved analyses are preserved.
read_paper	Extract PDF text by page or read text/Markdown chunks. Use get_paper_file for the original file when text extraction is insufficient.
save_analysis	Add a new Markdown analysis to the same paper's Paper Files when writing analyses is allowed.

For example, give the AI a Gewu Key, ask it to read the Default PDF, and save a Chinese analysis with source page references. The saved note records its connection, time, key, request ID and supplied source file hash/pages. It remains an ordinary associated Markdown file, available in built-in Preview. Returning to Library refreshes the selected paper's file panel.

Saving an analysis preserves the article identity, existing files, metadata and Default choice. A retry using the same request ID and identical content reuses the saved file. A new analysis needs a new request ID. Existing file contents, including earlier AI analyses, cannot be edited or overwritten. Creating folders, importing files, moving or renaming existing items and filling missing metadata require separate permissions.

New analyses are registered as Markdown notes: **File type: Other**, **Annotation: Unannotated**, and **Source: Other** with **AI analysis** and the connection name as source detail. File size, content hash, creation time and analysis provenance are recorded. These categories are assigned by Gewu; the AI cannot relabel its note as a published paper.

Let an AI import a prepared collection

Open **Settings > AI Access** and expand **Edit write permissions** for the intended connection. Choose operations, then click **Library** or root Space names under **Writable collections**. Selected rows stay blue and include all active subfolders; click again to deselect. My Publications is not a write destination in this editor. Choose **Save Write Access**, then reconnect the AI client to refresh its tools.

Saved remains beside the editor title even when collapsed. Saved selections survive closing Settings and restarting the App. **Unsaved changes** requires saving; **Not saved** retains your draft for retry. Earlier child-only grants show **Some subfolders only** and stay limited until you explicitly select their root. No write permission is added automatically.

Selected write collections also become readable; other existing read permissions and tokens stay unchanged. An empty selection grants no existing write destination. **Create Spaces** grants access only to each new Space this connection creates. Choose directory browsing separately if the AI needs to explore the tree.

Tool	Purpose
create_space	Create a new Space and return its folder ID.
create_folder	Create a nested folder under a writable Library or Space folder.
move_folder / rename_folder	Move a complete folder subtree or rename a folder/Space, synchronizing the actual directories.
move_file / rename_file	Move an item or Paper File, or rename its placement/filename under the existing file ownership rules.
upload_file	Transfer one prepared client-local file to temporary staging and return its upload ID.
import_paper	Register an uploaded PDF with metadata supplied by the AI, in the chosen folder.
import_file	Import an independent non-PDF file in any format, such as a direction overview in Markdown.
add_paper_file	Append a file of any format to the specified existing Gewu Key.
update_paper_metadata	Fill missing fields from AI-supplied facts and a source URL; preserve existing values and report disagreements.
get_upload_status release_upload	Check upload capacity or release an unused staged upload.
resolve_paper get_resolve_status	Start or check a separately requested Resolve job for one existing paper. Never part of an import.

The AI must bring the paper metadata. A paper import requires title, authors, publication type, journal or repository, known publication date or year, DOI and arXiv status, and the source URL. A genuinely absent identifier uses an explicit null value. If required facts are missing, the AI must find them using its own sources and retry. Import does not search a PDF for identifiers, fetch metadata online, call Resolve or queue enrichment. Supplied facts retain their source and connection provenance; Gewu does not claim to have verified them. Import performs file integrity checks but does not decompress every PDF image to compute an advisory content fingerprint; PDF annotation status initially remains Unknown.

Choose ownership explicitly. Import an independent Markdown overview with import_file. Attach a paper-specific analysis, spreadsheet, image or code file with add_paper_file and the owning Gewu Key. An ordinary non-PDF file retains its internal storage key but has no public Gewu Key field in the App. It does not become a scholarly paper simply because the AI imported it.

Reuse the existing paper identity. A matching DOI or arXiv identity reuses the existing Gewu Key and adds its placement in the requested folder. A different incoming PDF is retained as another Paper File. A valid manual Default remains; otherwise eligible versions use the normal priority: Corrected published version, Published version, Accepted manuscript, then Preprint. This also applies to add_paper_file. The automatic Default becomes the managed main file; other versions stay in Associated Files and folder aliases are synchronized. Supplements and analyses do not take automatic Default. Identical bytes reuse the file and its classification and record the import source. Similar titles alone never merge papers. Uncollected provider/Monitor records, including managed download PDFs, reuse the same Key through a writable destination and the normal archive workflow. Unreadable private collections, notes or external files still require user access review. DOI and arXiv pointing to different records remain an identity conflict.

Publication notices belong to the original article. Corrections, errata and retraction notices retain their own DOI, title and date as associated notice metadata. They do not create another research-paper Gewu Key or become the automatic Default. For MCP import, the AI must supply publication_notice with the notice kind, original article DOI and an evidence URL; import the original first if absent. Missing or ambiguous relations require review and never trigger Resolve. Paper Files shows linked notices while retaining the original article and its files.

The main file of a new object goes in the selected Library or Space folder. Its other files go in the existing mirrored Associated Files bundle. Multiple placements share that bundle and use the normal aliases. The AI supplies folder IDs and file ownership; Gewu calculates and maintains the physical paths according to the same storage rules used by the App.

Complete one file at a time. Upload one file, immediately register it with the appropriate import or attachment tool, then proceed to the next. Each successful file import immediately releases that file's staging; it does not wait for an entire folder or batch. Do not upload a whole collection before registering files. Capacity limits apply to currently retained files, not the total number or size of a literature collection.

Upload staging allows up to 256 MiB per file and 512 MiB or 16 currently staged files per connection. If it fills, register ready uploads or release unused ones, then continue without reconnecting. Failed transfers remove their partials; unused ready uploads expire after 24 hours, while active transfers are retained. Read copies have their separate limits below and must be released only after all readers finish. Actual free disk space and single-file limits still apply.

Keep a stable request ID for every write and a separate ID for its upload. Retry an interrupted response with the same arguments and ID to reuse its result. Existing files are never overwritten. If the result says alias synchronization is pending, retry that same import to finish the folder shortcuts.

Resolve remains independent. Enable its separate permission only when needed. It operates on one existing writable paper, requires an explicit standalone purpose, and returns a job immediately. Known DOI/arXiv is used first; PDF identifier extraction also needs file-reading permission. Results fill missing fields while preserving existing values and Default. At most two jobs run concurrently, and their network lookup does not block imports. The AI must never use this tool to prepare or complete import metadata.

Let an AI organize files and folders

Enable **Move folders**, **Rename folders and Spaces**, **Move files and change Paper Files ownership** or **Rename files** separately. Select the source and destination collections, save, and reconnect the client. Every affected location must be writable, including other placements of the same record. My Publications remains outside these write permissions.

Use a folder ID to move a whole subtree or rename a folder/Space. The actual directory and its mirrored Associated Files move together; empty folders and existing contents are retained. Library, Unsorted and Recycle are protected. A folder cannot move into itself or a descendant. A Space root may be moved into Library using the same conversion rules as the App.

For files, select either a membership ID from directory browsing or an exact Gewu Key and numeric file ID from Paper Files. A membership moves the whole item to another folder, or attaches its files to another record. A specific Paper File moves to another record or becomes an independent item in a folder. Independent non-PDF files keep their ordinary-file behavior. Renaming a membership changes its label and disk projection; renaming a Paper File changes that filename and must retain its extension. The bibliographic title stays unchanged.

File contents, IDs, classifications and provenance stay intact. The main file stays in its owning directory; other files use Associated Files. Transfers follow the App's existing ownership rules: the source chooses a remaining Default if necessary, the target keeps its existing Default, and an emptied source may retire. Final-file transfers from records with multiple placements are rejected. Moving into a folder that already contains the same record reuses that membership without losing files.

Operations do not run Resolve, upload existing files again or consume transfer staging. Use identical arguments and the same request ID to retry an interrupted response or finish pending shortcut synchronization. Unrelated files

are never overwritten. External originals cannot be renamed through MCP; a permitted ownership transfer of an externally linked file keeps the original and uses the App's managed-copy rule.

Browse a directory and its papers

Directory browsing is a separate, read-only permission. For a new connection, select **Browse authorized directories and paper memberships**. For an existing connection, select **Allow directory browsing** beside its name. This adds folders:read without replacing the token, changing the paper collection or granting file reading or analysis writing. Existing connections are not expanded automatically. Reconnect the AI client's MCP connection to discover the two new tools.

These directories are the logical folders in Library and Spaces, not disk paths. A Space uses a stable folder_id just like any folder. Shortcuts lead to the original target; they do not duplicate its membership. My Publications-only papers remain available through search and get_paper. Recycle and trashed folders or items are excluded.

Selected collection	Visible directories and memberships
Library, Spaces and My Publications	All active Library and Space folders, including empty ones, and their active paper placements.
One folder and its subfolders	Only that folder and its active descendants. The displayed path starts there; parents, siblings and outside placements stay hidden.
Specific Gewu Keys	Only folders containing those papers and the parent paths needed to reach them. Enabling directory browsing allows these folder names to be read; unrelated branches and their counts stay hidden.

For example, ask the AI to list the papers in your AI Space and preserve their folder classifications:

1. Call list_folders without a parent to discover visible roots. Follow next_cursor until it is null, and identify AI by its name, kind and path.

2. Use AI's returned folder_id as parent_id in list_folders to inspect its children. Repeat as needed to map the folder hierarchy.

3. Call list_folder_papers with that folder_id. By default it returns direct members; set recursive to true to include descendants. Follow every page. Each page defaults to 50 entries, with a maximum of 100.

4. Keep the returned membership_id, folder_id and gewu_key together. One paper can have several placements; use the Gewu Key to avoid reading it repeatedly while retaining its classifications. Call get_paper for the selected key before reading files.

Names can repeat, so use folder IDs and the returned ID/name path segments instead of treating a display path as a unique identifier. Each call states its directory explicitly; navigating in another task does not change a shared current directory.

Keep a multi-page collection walk consistent

Pass the first returned revision with subsequent directory calls. A visible rename, move, deletion or membership change returns collection_changed; discard the incomplete walk and start again without the old cursor or revision. Folder IDs survive renames and moves, while deleted and recreated folders get new IDs. A folder grant follows its root ID, but descendants moved outside it lose access. Ordinary metadata refreshes do not interrupt membership pagination; bibliography fields remain current, not a historical snapshot.

Give the original PDF to the AI client

Use get_paper_file with the Gewu Key and a file ID from get_paper, or default. When no Default exists, choose an explicit file ID. Gewu checks the connection and transfers the original bytes. The client receives a read-only temporary copy, title, authors, DOI, file classification and actual SHA-256. Its own tools can read the PDF, inspect pages and figures, or run OCR. Gewu does not render pages, run OCR, upload the file to a model or fetch a replacement from the DOI.

The delivered copy is separate from Paper Files and never syncs changes back. Write rendered pages and intermediate results separately. A file is limited to 64 MiB, with up to 256 MiB or 64 retained copies per MCP session. Each delivery returns a delivery_id and quota showing used and remaining bytes and file slots. Use get_file_delivery_status to check capacity and find active delivery IDs.

Remaining capacity is reported to the AI client in these tool results; it is not a separate Library or AI Access status meter. Ask the connected assistant to check file-delivery status when you need the current amount.

After every reader, rendering and OCR task finishes with a copy, call release_paper_file with its delivery ID. This frees its temporary quota immediately; original Paper Files, saved analyses and derived outputs remain unchanged. Keep the source file ID, SHA-256 and page references for citations and saving analyses. Active repeat delivery shares the same copy and ID, so finish all its users before release. Repeating a release is safe. No files are automatically evicted: when quota is full, release finished copies and retry.

Unreleased copies last until normal MCP process exit. The two local management tools also work offline or after grant expiry; they cannot retrieve new files. Reconnect MCP once after upgrading to discover them, after finishing work with old copies. A client needs access to the adapter's local filesystem; a returned path is not a cloud PDF attachment. If unavailable, report that limitation rather than reading the source Library directly.

Revocation, expiry or disabling AI Access prevents new deliveries. Copies already delivered to a client cannot be recalled. File transfer uses local disk and memory; PDF processing done by a client on the same computer can still compete for resources. Gewu adds no automatic whole-document OCR workload.

A repeatable research workflow

1. **Identify.** Give the AI an authorized Gewu Key, or use search_papers to find candidates and confirm the intended paper with get_paper.

2. **Read.** Inspect the file inventory, then use get_paper_file to obtain the original PDF and read its temporary copy with the AI client's tools. For text-only requests, read_paper remains available. Retain the returned file ID, SHA-256 and page references.

3. **Analyze and save.** Ask the AI to produce a Chinese Markdown analysis. With analysis-writing permission, call save_analysis under the same key and include the source references. Reuse the request ID only for an identical retry; changed source bytes require a fresh read before saving.

4. **Release.** Once all work using a temporary copy finishes, call release_paper_file with its delivery ID. Check the returned remaining quota, then proceed to the next paper without restarting MCP.

5. **Review and continue.** Inspect the note in Paper Files. In another task, retrieve that same paper and explicitly read the saved note before continuing. Each session works with the current authorized state.

These steps can be combined into a scripted workflow or repeated over a selected collection. Pagination and bounded reads help control how much material is retrieved; they do not guarantee model accuracy or a particular speed. Review the analysis against its cited sources.

Connect a local MCP client on Windows

1. Keep Gewu Insight running on the intended database. In **Settings > AI Access**, enable access and create a named connection with only the required collections and operations.

2. Use **Copy MCP Configuration**. Copy the generated command, arguments and environment values into your client's local STDIO server configuration. Keep each path, including spaces, as one argument.

3. The installed application provides its own Python runtime and MCP adapter. Use the exact generated paths; no separate Python installation is needed.

4. Preserve GEWU_API_URL_FILE and GEWU_DATABASE_IDENTITY when generated. They follow the current local port and bind the connection to the selected database. Keep GEWU_API_TOKEN private; the token is shown only at creation.

5. Reload the client's MCP connection, list tools and check a familiar authorized Gewu Key and its Paper Files before requesting writes.

Codex, DeepSeek Harness, Claude Code and other clients supporting a local STDIO MCP server can use this adapter. Map the generated command, arguments and environment into that client's configuration format. Create a separate named Gewu connection for each client. Client model login or API keys are separate from the Gewu token; GEWU_API_URL is a local API address, not a remote MCP server URL.

Reconnect after an App or database move

A verified migration preserves connection permissions and scope; moving the folder does not itself require a new token. Keep the installed App open on the intended database. Update changed runtime, adapter or endpoint paths from its generated configuration, retaining the existing client's own token and unrelated settings. Preserve the database identity and URL-file fields. If these values did not change, keep them. The adapter command points to the installed program, not the research folder.

The client must run where it can access the adapter's local files. A returned file path is not a cloud attachment. This manual does not change your AI client's configuration or its model settings.

Pause, revoke and review

Turn off **Enable AI access** to pause all connections. **Revoke** stops one connection and removes it from the active Connections list; expired connections also stop working. Re-enabling access resumes connections that are still valid. Expand **Recent Activity** to review requests and outcomes as separate rows in an independently scrolling list, and choose **Refresh** to update it. Tokens, prompts and full file text are not included in that activity log.

Limits and troubleshooting

The AI client must run on the same computer, and Gewu Insight's local service must be running. The local MCP adapter supports protocol 2025-11-25 and earlier negotiated versions. There is no remote MCP endpoint in this version. Developers can retrieve the authenticated API v1 specification at /api/v1/openapi.json.

Original file delivery has a 64 MiB file limit and includes every page. PDF text extraction through read_paper is limited to ten pages per request and a bounded extraction time; text attachments are returned in chunks. Scanned PDFs may need OCR in the AI client; no OCR or model runs automatically in Gewu. Analysis notes are limited to 256 KiB. A busy response means retry later. An unavailable paper or file may be outside the connection's collection, missing, or no longer accessible.

Source editing, building and temporary tests require no AI token; calling this API against your collection does require one. Configure each client with the collection and operations its task needs. The interface and filesystem permission boundary is explained above.

See also: Understand Paper Files · Preview Files · Local Data and Privacy

3-9.8 Naming and PDF Rename Rules

Display naming and physical PDF renaming are separate choices. Review metadata before renaming files.

Choose the Library naming rule

Choose **Settings > Naming Rule > Use Title** or **Use Citation**. The choice is saved immediately and supplies the default name for a newly added Library placement that has no name yet. It does not rename the existing collection. The default rule is Use Citation; physical PDF renaming uses the separate template below.

Configure PDF renaming

Open **Settings > PDF Rename Settings**. A template can use tokens such as:

• {author} or {authors}

• {year}

• {title}

• {journal}

• {doi}

Edit **Filename Template** and inspect the sample **Preview**, then choose **Save** or press Return. **Default** immediately saves the standard {author}_{year}_{title} template. Saving a template does not rename existing PDFs; apply it through the Library rename action below.

Rename one item from metadata

1. **Confirm its DOI, title, author, journal, and year.**

2. **Right-click the item.**

3. **Choose Auto rename from Metadata.**

4. **Verify the result in the Library and File Explorer.** To rename several PDFs, select only local PDF paper rows, Right-click, and choose **Auto rename n selected**. Each file uses its own metadata; the progress message reports renamed, already named, and skipped items.

Note

Choosing a Default PDF can move it to the main file folder and archive the previous main PDF in Associated Files. This does not apply the filename template or rewrite file contents; name conflicts use a unique filename. Use a naming or rename action to apply your preferred naming rule.

See also: Choose File Types and the Default File · Folders, Shortcuts, and Spaces

3-9.9 How Gewu Insight Stores Files

The visible Library stays simple: each file-backed paper has a main managed file at one canonical location, while its other privately managed resources live in Associated Files. Paper Files presents these resources together as one flat list.

One work, several representations

Each managed paper has one database identity and a stable **Gewu Key**. DOI and arXiv are external identifiers attached to that identity; neither is used as the sole storage identity.

Where the files go

• The Default is the main file in the visible Library, Space, or My Publications tree. It may be a PDF or another file type.

• Other PDF versions belong in the associated bundle, usually under Versions.

• Supporting information goes to Supplements.

• Other resources use the bundle's Figures or Files areas as appropriate; the file-type label remains separate from its physical subfolder.

The associated bundle mirrors the paper's managed path under data/Associated Files. When you move the paper in the UI, Gewu Insight moves the associated bundle and refreshes live paths.

Why the UI and File Explorer look different

The UI presents a paper as one item with a flat Paper Files list inside it. File Explorer shows the Default as the main file in the normal tree and the remaining managed resources in Associated Files. Choosing a different Default synchronizes both locations, including for non-PDFs, while preserving file identity, classification and bytes. With no manual Default, the automatic priority and fallback rules still select the main file when an eligible resource exists.

Copies and filesystem shortcuts

When one Gewu Key appears in several folders, it shares one Paper Files bundle. The main file stays at its canonical location. Other Windows placements use .lnk shortcuts and their associated directories point to the canonical bundle. Make Copy Desktop resolves these pointers into real files for a portable export.

A surviving normal Library, Space or My Publications placement keeps the original outside the local Recycle directory. Deleting or dragging a folder checks each paper; restoring or re-adding a recycled paper migrates its original back to normal storage. SQLite resource paths and secondary shortcuts follow. See Delete and Recover Items.

The canonical location stays stable while it is still an active placement. If that location is removed or moved, Gewu Insight uses a surviving Library, Space or My Publications placement and updates its aliases. External originals, files shared with another paper, and occupied destinations are protected; do not replace an unrelated file to force a layout change.

Important

Do not manually move an Associated Files bundle or replace an alias in File Explorer. Use Gewu Insight so the database and physical paths change together.

See also: Storage Reference · Make a Portable Desktop Copy · Understand Paper Files

3-9.10 Local Data and Privacy

Gewu Insight runs a local interface and keeps its authoritative library database on your Windows computer. Network requests occur only for the features that need external metadata, pages, profiles, or files.

Local components

• The Windows desktop starts its local service on a free loopback port. Its current address is recorded for MCP discovery; do not assume port 8765. The service is local to this computer.

• SQLite stores papers, identities, relationships, settings, and operational state.

• Browser bookmarks, folders, history, and sidebar preferences also live in SQLite. Browser cookies and cache use a separate persistent WebView2 profile; they are not shared with Chrome or Edge or exported with the database.

• Managed PDFs, attachments, photos, and generated reports stay in selected local workspace directories.

• JSON files are exports or diagnostics; they are not the authoritative database.

External requests

Metadata refresh, citation counts, journal/subject/author discovery, profile images, website opening, and downloads can contact their named services. The app paces services that require strict request limits.

Protect credentials

Optional service credentials belong only in Literature Data Sources or approved environment variables. They must not appear in a screenshot, support message, Git commit, or exported diagnostic file.

See also: Literature Data Sources · Back Up and Upgrade · Publisher and Network Access

4 Product Identity

4-1 Visual Identity and Cultural Elements

The name Gewu Insight (格物洞见) expresses a way of doing research shaped by the practice of physics: begin with the real world, and seek to see what lies behind its phenomena.

Gewu (格物) means investigating things. Here, it emphasizes starting from concrete phenomena, experimental observations, and questions that nature presents to us. Research should remain in contact with the world it seeks to understand. Abstract ideas and theories gain their purpose from that contact; they should not become castles in the air, sustained only by further abstraction.

Insight (洞见) means seeing through phenomena to the patterns and mechanisms beneath them. It values physical pictures, intuition, imagination, and the ability to make an insightful guess—to recognize what may be happening before every step has been expressed in equations. A useful physical picture can reveal which features matter, suggest a mechanism, and open a direction that formal derivation alone might not make apparent. Mathematics serves as a tool for thinking, expression, and calculation. Absolute formal rigor, axiomatic completeness, and mathematical elegance are not ends in themselves, nor should they constrain the search for physical understanding.

This outlook also shapes the purpose of the software. Research literature brings us into contact with other researchers' experiments, observations, interpretations, and ideas. Gewu Insight keeps these materials connected: a paper retains its identity across versions, its figures and supporting files remain accessible, and related work and research notes can be organized together and revisited over time.

These functions support the everyday work from which insight can emerge: returning to an experimental result, comparing competing physical pictures, noticing an unexpected connection, or recording a conjecture worth pursuing. The researcher brings the questions, intuition, and judgment; the workspace helps keep the material close at hand and the developing line of thought connected to its sources.

Investigate nature through experimental phenomena; seek insight through physical pictures and intuition.
（从实验现象中格物，以物理图像和直觉求洞见。）

The calligraphic Chinese name, the app icon, and the seal-script watermark give this research outlook a visual identity.

The marks do not decorate every surface. Each has a different job: the icon identifies the application, the calligraphic name gives the product a human signature, and the quiet seal-script pattern belongs to transitional or otherwise empty space.

4-2 The calligraphic name



The transparent production artwork used in the About panel. From left to right the picture contains 見、洞、物、格; read in the traditional direction from right to left, it says 格物洞見.

This is a 祝枝山行草集字 composition: four separately documented historical character forms were assembled into one wordmark. It is therefore accurate to call it “a collection of characters in the calligraphic style of Zhu Zhishan,” but not “a title written by Zhu Zhishan.” No surviving single inscription titled 格物洞見 is being claimed.

4-2.1 How the four characters were assembled

Reading order	Reference character	Recorded hand and script	Role in the product artwork
1	格	祝枝山 · 行书	Begins the product name when read from the right.
2	物	祝枝山 · 草书	Completes the classical term 格物.
3	洞	祝枝山 · 草书	Introduces 洞見, insight gained by seeing through a subject.
4	見	祝枝山 · 草书	Closes the traditional form of the name.

The selected glyphs were optically balanced into a common line: scale, spacing, ink tone, edge cleanup, and transparent alpha were normalized while the characteristic strokes were retained. The production preparation used a Codex-assisted image workflow. The interface and accessibility text use the contemporary simplified product name 格物洞见; the artwork deliberately preserves the traditional character 見 and traditional right-to-left composition.

Provenance and reuse

The character links above are retained as provenance for the design process. The source thumbnails do not state a clear open-reuse licence. They should not be treated as public-domain assets merely because they are viewable online. Gewu retains rights only in its own original contributions to the assembled artwork; its software License does not grant rights in the underlying third-party glyph images. Their redistribution and commercial-use permissions remain to be confirmed.

4-3 The app icon and the seal-script watermark

4-3.1 The app icon



The icon's two blue-violet fields read simultaneously as an open book and two sides of a field of view. The white eye and central point suggest observation and focus; the tapered center also recalls a pen nib or the spine of a book.

This description is the product's visual reading of the finished mark, not a claim that every interpretation was specified in an original design brief.

4-3.2 The seal-script watermark

The 2×2 motif is a digital rendering in 汉仪篆书繁. Read down the right column and then down the left, its four characters are 格、物、洞、见. It uses simplified 见 because that is the supported glyph in the selected digital typeface.

The mark is a light-line screen motif inspired by seal composition, not a photograph or facsimile of a historical carved seal. Typeface licensing remains separate from the product artwork.

4-4 Why the three marks are used differently

Mark	Role
Icon · recognition	Use at application scale: Dock, startup identity, About, and platform packaging.
Calligraphy · signature	Use where the Chinese name can be read deliberately, especially the About panel and identity materials.
Seal script · atmosphere	Use at very low opacity in startup transitions or quiet lower-right space, never where it competes with paper details.

Together the three registers establish the product's visual identity: the icon is contemporary and operational; the calligraphy is personal and gestural; the seal-script watermark is historical in reference but restrained in use. Their common purpose is to make the name visible without turning the research workspace into a themed illustration.

See also: Welcome · The Personal Research Workspace · Startup, Monitor Cache, and Text Size

5 Technical and Operational Reference

5-1 Keyboard Shortcuts

Shortcuts depend on the focused workspace, file list, webpage or text field.

Shortcut or control	Action and scope
Arrow keys / Enter	Navigate the focused Library columns, Paper Files, calendars and author list. In text inputs and webpages, editing and page navigation retain their normal meaning.
Space / Escape	Open or close the selected local file preview; Escape dismisses an active transient control. Space does not open a preview while typing.
Ctrl+F	Search the current research workspace, or Find on Page in Browser. In this guide, focus topic search.
Ctrl+L	Focus Browser's address field. Use Loader > Open Loader outside Browser.
Ctrl+D / Ctrl+R	Bookmark or reload the current Browser page.
Ctrl+T / Ctrl+W	Create or close a Browser tab. Closing the last tab creates Home.
Ctrl+[	Return from a research link opened in Browser to its source workspace. Direct Browser entry has no return checkpoint.
Ctrl+wheel	Zoom the built-in PDF reader.
Ctrl+C / Ctrl+X / Ctrl+V / Ctrl+A	Copy, cut, paste or select all in the focused supported context. A Library placement action differs from editing text.
View > List View / Table View	Switch Library presentation.
Right-click	Open the context menu for the selected item or blank area.
File > Exit	Close the Windows application and stop its service. Save webpage drafts first; tabs are not restored after quit.

5-1.1 Monitor navigation

In Journal or Subject calendars, Left/Right moves a day and Up/Down a week. Enter selects the date. In the paper area, Up/Down selects papers and Escape returns to the calendar. Author Monitor uses Left/Right between its author and paper panes. Arrow commands do not apply while typing in an input.

See also: Navigate with Mouse and Keyboard · Understand Paper Files

5-2 Publisher and Network Access

Publishers can rate-limit shared VPN addresses or automated-looking traffic. Gewu Insight reduces overlap and request rate, but it cannot remove a publisher block.

5-2.1 If a publisher page is blocked

1. **Stop repeated refreshes.** Additional requests can extend a temporary block.

2. **Try your direct connection.** If the page works with VPN off, investigate the VPN route, quota or exit address before treating it as a product or certificate failure.

3. **Use Open Website or an external browser.** Complete any normal institutional login or publisher interaction yourself.

4. **Download only when authorized.** Add a legitimately obtained PDF with **Add File**.

5-2.2 Why figures may arrive later

Figure and article-page retrieval is queued behind discovery work and uses caching. This reduces simultaneous RSS, page, and image requests to the same publisher. A paper can appear before its representative image.

5-2.3 Browser and your system network

The Browser tab uses native WebView2 requests and does not proxy pages through the Python server. System proxy or TUN capture can send its traffic into Clash; only then do the active rules determine DIRECT or proxy routing. A DIRECT rule uses your current physical network, which must itself provide institutional access. Gewu Insight neither changes these rules nor guarantees a particular route; use Clash connection records to verify the actual route. See Browse, Bookmark, and Revisit Websites for downloads, sign-in limits, and the separate browser profile.

5-2.4 Secure-connection failures and VPN interruptions

A secure-connection error can reflect network, VPN, routing, system time or certificate problems. Restore the connection, then reload once. The error alone does not prove an expired site certificate. Certificate verification remains enabled.

5-2.5 Service rate limits

Semantic Scholar, Google Scholar, and some publisher sources use shared pacing, cooldowns, or exponential backoff. Let the bottom status area settle before starting the same action again.

Important

Do not attempt to bypass a paywall, CAPTCHA, browser verification, or access control. Use your authorized browser session or attach a file you obtained legitimately.

See also: Journal Monitor · Download and Sync Versions · Troubleshooting

5-3 Startup, Monitor Cache, and Text Size

The Windows shell starts a local service for your selected workspace and opens the research interface when it is ready.

5-3.1 Normal startup

Open **Gewu Insight** from the Start menu and wait for the startup screen to finish. Use one window for a workspace; its lock prevents a second desktop process from writing to the same Library. If the selected database is missing, startup stops instead of silently creating an empty replacement.

The installed application includes its runtime dependencies. Keep the selected Library available. If startup fails after an interrupted installation, close the application and rerun its versioned Setup.exe.

Missing, read-only, identity-mismatched or newer-schema databases stop startup with an explanation. Locate the correct database or use the required newer App; do not delete the database to clear an error. When closing, Gewu waits for active requests and database work before releasing its locks.

5-3.2 Startup is not a Library cleanup

Ordinary startup does not reorganize the whole Library, merge historical duplicate files, or make a new full database backup. Managed layout and duplicate protections apply when you import or change the affected paper and files. Keep your own regular Back Up and Upgrade.

If a file move was interrupted before its database and disk changes finished together, startup recovers only the recorded unfinished operation before background workers start. A launch with no unfinished move goes directly to normal preparation. An ambiguous conflict is reported and preserved for repair rather than overwriting a destination or triggering a full-library sweep.

5-3.3 Automatic local-server recovery

The Windows shell retries an unexpectedly stopped service within a bounded restart budget. Workspace-renderer recovery is also bounded. Repeated failures show a recovery message instead of restarting indefinitely.

The separate Browser process can keep tabs and unsent website forms during service recovery while it stays alive. This does not guarantee recovery after an operating-system crash or App exit. Unsaved research-form edits can be lost when the workspace reloads.

5-3.4 When automatic updates run

Automatic monitoring runs inside the local UI service with startup delays, periodic checks and saved completion/retry state. Keep Windows awake and Gewu Insight running. Closing the main Windows window stops its service. A late launch checks due work; it does not guarantee a run at the exact scheduled minute.

Monitor	Current automatic schedule
Journal Monitor	Daily work becomes due from 09:00 in the computer's local time zone; stored completion and pending retry state determine what still needs work.
Subject Monitor	Daily work becomes due from 09:00 local time; incomplete sources have their own bounded retry state.
Author Monitor	Checks due authors from 10:00 local time; already checked authors are not blindly fetched again on every scheduler tick. Failed transport checks use a separate paced retry queue, including before 10:00. Unrecognized Scholar pages use an hourly delay and a daily failure cap; access cooldowns still apply. Opening an author does not force a full profile fetch each time.
arXiv	Uses its separate announcement-ready schedule and buffer, not the journal's 09:00 rule. Read the displayed update/countdown state.

These are local scheduler rules, not guarantees of remote source completion or a hosted monitoring service. Manual Refresh remains available for the selected scope; repeated broad refreshes can worsen a source's rate limit.

5-3.5 If the app cannot start

1. Close the existing Gewu Insight window normally before reopening the selected database. If startup still fails, inspect %LOCALAPPDATA%/Gewu Insight/Databases/<identity>/Logs/windows-launcher.log; do not remove the database or start an older incompatible App.

2. **Open the launcher log.** Check %LOCALAPPDATA%/Gewu Insight/Databases/<identity>/Logs/windows-launcher.log for the first error.

3. **Allow the first startup to finish.** After an upgrade, wait through the migration window before treating the preparation panel as a failure.

4. **Start the app again once if recovery does not complete.** Avoid opening several copies while the first is still preparing.

5. **Preserve the database.** Do not delete SQLite as a startup fix.

5-3.6 Clear a stale interface

Choose **Settings > Clear Monitor Cache** if a monitor still shows stale downloaded images or rendered web assets after an app update. This clears disposable monitor presentation cache, not the SQLite database, saved paper records, or managed PDFs.

This is not Browser's Clear History command and does not clear Browser sign-in cookies or external browser data. Use **Browser > History > Clear History** for visit records only.

5-3.7 Choose a comfortable text size

Choose **Settings > Font Size**, then select **Compact**, **Standard**, **Large**, **Larger**, or **Extra Large**. The workspace previews the choice immediately while keeping panel dimensions, icons, and window controls unchanged.

Cancel, the Escape key, or clicking outside the sheet restores the previously saved size. **Restore Default** previews Standard and still requires Save. Choose **Save** to keep the preference in the local SQLite settings. New app sessions apply the saved size automatically.

See also: Troubleshooting · Local Data and Privacy

5-4 Troubleshooting

Start with the visible status and the selected work. Avoid broad repair actions until you know whether the problem is network, metadata, database state, or a local path.

5-4.1 A PDF cannot be found after a move

1. Reselect the paper and try **Show in File Explorer**.

2. If the move happened in Gewu Insight, close and reopen the item to refresh the view.

3. If the file was moved manually in File Explorer, return it if possible, then organize it through the app.

4. Check Recycle before importing another copy.

5-4.2 Paper Files shows Missing File

This label is a path-state warning, not a failed metadata lookup: SQLite still knows the resource, but the recorded file path does not currently exist. Check **Show in File Explorer**, the corresponding data/Associated Files bundle, and Recycle. If the file was moved outside Gewu Insight, restore it before reorganizing it through the app. Do not delete the row merely because its filename resembles the default PDF; explicitly typed attachments and the default resource remain visible for recovery.

5-4.3 Preview is slow on the first open

A large or previously unseen PDF may need an initial structural read and thumbnail render. The main document should appear before the full thumbnail strip. Leave the preview open briefly instead of pressing Space repeatedly; later opens can reuse page information and cached thumbnails. If the viewer never produces a page, use **Open in Default App** to check whether the file itself is valid.

5-4.4 Markdown stays on Loading Markdown

The note is read and formatted locally. Unchanged notes may reopen from a validated memory cache; first opens and changed files need a fresh render. A stalled preview shows an error after about 15 seconds. Close and reopen it to retry, or open the file directly in its normal application. Very large notes show a bounded, marked preview. No metadata refresh, DOI lookup or reimport is needed just to preview Markdown.

5-4.5 Markdown begins with unexpected metadata

Collapse **Source record** and **Properties** to read the body. If a header is malformed, the reader may show its escaped source instead of properties. The preview does not rewrite the original note. Wide tables and code blocks have their own horizontal scrolling.

5-4.6 PDF switching flashes in built-in Preview

Switching files can briefly expose loading while a new document is prepared. Let it finish or use Open in Default App to read the file separately. Windows has no macOS system Quick Look mode; Preview Settings cannot switch to it.

5-4.7 The wrong file is the default

1. Open Paper Files and verify every file type.

2. Correct a mislabeled Corrected published version, Published version, Accepted manuscript, or Preprint; expand the size footer to set annotation separately.

3. Choose **Set as Default** for the desired valid file, or choose **Use Automatic Selection** to resume automatic selection.

5-4.8 A duplicate appears after download

Compare file size and classification. New downloads use exact SHA-256 and PDF content fingerprints. A copy with annotations may be retained intentionally. Exact byte duplicates are reused, while clean and annotated peers can both remain. Keep the intended default before deleting any redundant non-default row.

5-4.9 A corrected DOI still shows old metadata

Press Return in the DOI field and wait for **Identifier updated**. Then choose **Refresh Info**. Hover over the button to check whether the exact corrected identifier was found or a service is waiting to retry. Saving an identifier and retrieving its bibliography are separate steps. Do not erase files or create another paper merely to bypass a metadata conflict; see Edit DOI and arXiv Identifiers.

5-4.10 Refresh complete reports partial results

Green **Refresh complete** means the operation ended. Successful source updates are retained even if another source was unavailable. The hover report and batch task window retain the detailed outcomes and cooldowns. Repeating a broad task immediately is usually unnecessary.

5-4.11 A normal Library item points into Recycle

With an active Library, Space or My Publications placement, app-managed operations keep or return its original to normal storage. A recycled occurrence may instead be a shortcut to that retained original. For a historical discrepancy, inspect the selected Key, file path and surviving locations before taking action. Do not empty Recycle or manually delete the path as a diagnostic shortcut.

5-4.12 Search misses the phrase you expected

Try a title fragment, surname or exact identifier. Library supports spelling tolerance and word variants, but does not automatically translate languages or invent synonyms. It searches saved metadata and names, not a semantic index of PDF content. Clear the search to return to normal folder browsing.

5-4.13 A monitor shows no papers

Read the source status. An empty successful source is not the same as a failed fetch. In Subject Monitor, allow scheduled source-level retries to finish, or use the selected subject's refresh command when a manual retry is needed. In Journal Monitor, confirm the date and filters. If a VPN is involved, test a direct connection without repeatedly refreshing.

5-4.14 Author Monitor shows a red Scholar pause

Check the stated retry time and full status message. A saved access cooldown survives restart and network changes; it is separate from a temporary connection failure or the all-author metadata counter. See Author Monitor status and recovery. Repeated refreshes do not remove a cooldown. A completed refresh that says papers need identity review instead concerns those records' identifiers or metadata, not the network.

5-4.15 A journal count and the visible cards disagree

This is usually expected when **Field Filter** is active. Journal counts describe all stored papers for the selected journal and day; field choices narrow the visible cards. Clear or broaden the field selection before diagnosing a missing fetch.

5-4.16 A journal disappeared from the configured list

Open **Journal Settings** and inspect the disabled history before editing configuration files. Removing a journal disables its subscription but preserves previously collected papers and history. Add it again to restore monitoring. Because the subscription list is SQLite state, replacing source files should not be used as a journal-list repair.

5-4.17 LaTeX remains visible as source text

On a cold launch, allow the math renderer a moment to become ready. The active day should re-render automatically. If raw $...$ text remains, check network availability for the renderer, then reload the same view once; switching calendar dates should not be required.

5-4.18 Folder Loader looks incomplete

Open the live or previous Loader log and the result guide. Confirm the metadata mode, source path, and any stop action. Re-running the same source should reuse existing files rather than overwrite the primary PDF.

5-4.19 A default file cannot be deleted

The Default is kept as the protected main file, including for non-PDFs. Choose another eligible resource with **Set as Default** before removing the old main file from Paper Files. The old resource remains in Associated Files until you explicitly remove it. To remove the paper itself, use the normal Library reference/Recycle workflow, which preserves shared references. Do not bypass a main-file warning in File Explorer. An **Invalid file** remains an audit record and is never eligible to become Default.

5-4.20 Change where website links open

Open Settings > Website Links and save **System Default Browser** to use the browser selected in Windows. The default, **Gewu Insight Browser**, opens a new built-in webpage tab or reuses its unused first tab. This covers website actions in all five research views, including publisher arrows, DOI/arXiv links, scholarly profiles, citation-source links, and links inside Note. Existing web pages stay open. Local PDF, Preview, File Explorer, download, and file-import actions are unchanged.

5-4.21 Home works offline but a website will not load

Home displays local Favorites without a Google request. Missing site icons fall back to initials; they do not prevent opening Home. Search results and account actions require a connection. Read the load error, check the destination and Clash route, and try Reload once. A website may reject embedded browsers or have its own session policy; an unsupported-browser banner alone does not prove why a sign-in ended. Open in Default Browser is a manual compatibility fallback, with a separate sign-in session.

5-4.22 A publisher stays on security verification

An embedded Browser can still be rejected by a publisher's verification. Reload once; if it repeats, use Open in Default Browser and complete the site's normal access steps yourself. The external browser has a separate session. Do not repeatedly retry or bypass the challenge.

5-4.23 Website sign-in is unavailable

Apple Passwords and the macOS AutoFill trigger are not part of Windows Preview. Complete sign-in yourself in Browser. If a website rejects the embedded browser, use Open in Default Browser; its sign-in session is separate. Do not copy cookies or credentials into the research interface.

5-4.24 A long task keeps returning as Continue

That task was paused or interrupted, so its remaining queue is saved. Choose the footer's **Details**, or open **Loader > Refresh All Metadata** and select the task. Choose **Stop** to end it permanently. Completed work remains. Closing the window merely hides it; **Pause** deliberately keeps it resumable.

5-4.25 Two Paper Files cards seem to be the same file

Two folders showing the same Gewu Key normally share a single Paper Files bundle. Within that bundle, different edited PDFs can have similar names. Use **Show in File Explorer** and inspect each resource before deleting anything. Exact unchanged reimports are reused, but changing a DOI, restarting, or clearing Monitor Cache is not a historical duplicate-repair command. If two cards reveal the same physical file, report the Gewu Key and the steps that produced it through **Help > Contact Us**.

5-4.26 Contact support

Help > Contact Us opens info@gewu-insight.com in the Windows default email application. If none is configured, use your preferred mail service. Include the installed version, operation and error; omit passwords and tokens. Review and send the message yourself.

See also: Back Up and Upgrade · Startup, Monitor Cache, and Text Size · Publisher and Network Access

5-5 Storage Reference

These paths describe the selected workspace layout. They are useful for backup and diagnosis, not for routine manual reorganization.

Location	Purpose
data/paper_monitor.sqlite	Authoritative database for papers, identities, relationships, settings, operational state, Browser bookmarks, and visit history. May contain saved metadata API keys; treat backups as private.
data/cache/journal_logos	Rebuildable local image cache for configured Journal Monitor logos.
data/Library	Visible main Library root, canonical main files and secondary Windows .lnk shortcuts.
data/Spaces	Independent Space roots.
data/My Publications	Managed local files for My Publications.
data/Associated Files	Mirrored bundles for versions, supplements, and attachments.
data/pdfs	Legacy managed PDF location retained for compatibility where needed.
reports	Generated reading notes and reports. These are artifacts, not the database.
%LOCALAPPDATA%/Gewu Insight/Databases/<identity>/Logs/windows-launcher.log	Windows launcher diagnostics when the local UI cannot start.

Preview page thumbnails use a separate, automatically trimmed temporary cache. It is rebuildable preview data, not part of the Library, Associated Files, or the SQLite record, so it does not belong in a research backup.

Browser website data is under %LOCALAPPDATA%/Gewu Insight/Databases/<identity>/Browser. Logs and Cache are adjacent, separate from SQLite bookmarks/history and the selected Gewu Database. Copying browser data does not guarantee usable sign-ins on another computer.

5-5.1 Associated Files layout

An associated bundle follows the managed scope and path, then a work-specific bundle. Its children separate Versions, Supplements, and Files. The exact physical name can change as the paper moves; the Gewu Key remains stable.

5-5.2 Database and exports

SQLite is the only source of truth. JSON, HTML, Markdown, Word, LaTeX, and PDF outputs are exports, diagnostics, or reading artifacts. Editing one of them does not edit the Library record.

Important

Do not delete, rebuild, or “clean” the database because a generated JSON file looks stale. Diagnose the selected record and local path first.

See also: How Gewu Insight Stores Files · Back Up and Upgrade · Local Data and Privacy