

Assembly of long, error-prone reads using repeat graphs

Mikhail Kolmogorov, Jeffrey Yuan, Yu Lin, and Pavel A. Pevzner

05.07.2021

Genome assembly in general

- ▶ reconstruct target sequence from the reads

Genome assembly in general

- ▶ reconstruct target sequence from the reads
- ▶ different graph structures (De-Bruijn, Overlap-layout, String)

Genome assembly in general

- ▶ reconstruct target sequence from the reads
- ▶ different graph structures (De-Bruijn, Overlap-layout, String)
- ▶ repeats → assembly fragmentation

Genome assembly in general


- ▶ reconstruct target sequence from the reads
- ▶ different graph structures (De-Bruijn, Overlap-layout, String)
- ▶ repeats \rightarrow assembly fragmentation
- ▶ error rate long read \leftrightarrow short read

Genome assembly in general

- ▶ reconstruct target sequence from the reads
- ▶ different graph structures (De-Bruijn, Overlap-layout, String)
- ▶ repeats \rightarrow assembly fragmentation
- ▶ error rate long read \leftrightarrow short read
- ▶ Flye should resolve these repeats correctly


Disjointigs

- ▶ most assemblers spent much time on correct contig assembly




Disjointigs

- ▶ most assemblers spent much time on correct contig assembly
- ▶ Flye uses a different approach:




Disjointigs

- ▶ most assemblers spent much time on correct contig assembly
- ▶ Flye uses a different approach:
- ▶ we don't care (at least at the initial stage)




Disjointigs

- ▶ most assemblers spent much time on correct contig assembly
- ▶ Flye uses a different approach:
- ▶ we don't care (at least at the initial stage)
- ▶ correct assembly graph




Disjointigs

- ▶ most assemblers spent much time on correct contig assembly
- ▶ Flye uses a different approach:
- ▶ we don't care (at least at the initial stage)
- ▶ correct assembly graph
- ▶ generate paths from overlapping reads without checking for correct assembly -> disjointigs




Disjointigs

- ▶ current assemblers use much time on correct contig assembly
- ▶ Flye uses a different approach:
- ▶ generate paths from overlapping reads without checking for correct assembly -> disjointigs



Disjointigs


- ▶ current assemblers use much time on correct contig assembly
- ▶ Flye uses a different approach:
- ▶ generate paths from overlapping reads without checking for correct assembly -> disjointigs




Repeat graph creation




Repeat graph creation





Repeat graph creation




Repeat graph creation



Repeat graph creation



Results




References

Appendix

Dot plot creation

-	9	10	-	-	9	10	-	-	5	6
8	5	6	-	-	1	2	-	0	1	2
0	1	2	3	4	5	6	7	8	9	10
A	C	T	G	G	C	T	G	A	C	T



Repeat graphs

- ▶ generalization of de bruijn graphs

```
>- from disjointigs = random walk of reads on the repeat graph  
>- means the repeat graph hasn't to be known
```

Repeat graphs

- ▶ generalization of de bruijn graphs
- ▶ structure

```
>- from disjointigs = random walk of reads on the repeat graph  
>- means the repeat graph hasn't to be known
```


Repeat graphs

- ▶ generalization of de bruijn graphs
- ▶ structure
- ▶ creation

>- from disjointigs = random walk of reads on the repeat graph

>- means the repeat graph hasn't to be known

Difference repeat graph de Bruijn graph

- ▶ A-Bruijn graph (alignments) generalizes the de Bruijn graph

Difference repeat graph de Bruijn graph

- ▶ A-Bruijn graph (alignments) generalizes the de Bruijn graph
- ▶ We thus argue that the time has come to explain that the breakpoint graphs and the de Bruijn graphs are two identical data structures (if one ignores a cosmetic difference between them) as they both represent specific instances of a general notion of the A-Bruijn graph introduced in [13]. The A-Bruijn graphs are based on representing genomes as sets of labeled paths and further gluing identically labeled edges (breakpoint graphs) or vertices (de Bruijn graphs) in the resulting paths.


Difference repeat graph de Bruijn graph

- ▶ A-Bruijn graph (alignments) generalizes the de Bruijn graph
- ▶ We thus argue that the time has come to explain that the breakpoint graphs and the de Bruijn graphs are two identical data structures (if one ignores a cosmetic difference between them) as they both represent specific instances of a general notion of the A-Bruijn graph introduced in [13]. The A-Bruijn graphs are based on representing genomes as sets of labeled paths and further gluing identically labeled edges (breakpoint graphs) or vertices (de Bruijn graphs) in the resulting paths.
- ▶ de Bruijn graphs need correct bases

Difference repeat graph de Bruijn graph


- ▶ A-Bruijn graph (alignments) generalizes the de Bruijn graph
- ▶ We thus argue that the time has come to explain that the breakpoint graphs and the de Bruijn graphs are two identical data structures (if one ignores a cosmetic difference between them) as they both represent specific instances of a general notion of the A-Bruijn graph introduced in [13]. The A-Bruijn graphs are based on representing genomes as sets of labeled paths and further gluing identically labeled edges (breakpoint graphs) or vertices (de Bruijn graphs) in the resulting paths.
- ▶ de Bruijn graphs need correct bases
- ▶ otherwise tangled graph

Segmental duplications




- ▶ Segmental duplications are duplicated blocks of genomic DNA typically ranging in size from 1-200 kb (IHGSC 2001)

Segmental duplications




- ▶ Segmental duplications are duplicated blocks of genomic DNA typically ranging in size from 1-200 kb (IHGSC 2001)
- ▶ They often contain sequence features such as high-copy repeats and gene sequences with intron-exon structure

Contigity improvement




- ▶ colors are contigs
- ▶ color changes -> fragmented



Repeat graph creation






Repeat graph creation



Repeat graph creation



Repeat graph creation



Repeat resolution