

Community Detection in Networks

Hesam Ipakchi

Imperial College London

hesam.ipakchi10@imperial.ac.uk



24th June, 2014

- ▶ Community structure in networks
 - ▶ Intuitive Definition
 - ▶ Example illustrations
- ▶ Community detection algorithms
 - ▶ Algorithms studied
 - ▶ Synthetic data testing set-up
 - ▶ Comparison using results from testing
- ▶ Application on financial networks
 - ▶ Motivation
 - ▶ Application on a static network
 - ▶ Extension to dynamic (time-evolving) networks

Community structure in networks

- ▶ Networks are represented by graphs, consisting of nodes and edges
- ▶ **Communities** are groups of nodes with denser connections within groups and sparser connections between groups
- ▶ **Community detection** algorithms involve partitioning the network into communities
- ▶ Many real-world applications including social networks, biological networks, financial networks...

Example illustrations



Community detection algorithms

Study a range of algorithms based on different techniques:

- ▶ Spectral clustering
- ▶ Modularity Optimisation
 - ▶ Greedy algorithms
 - ▶ Spectral algorithms
 - ▶ Simulated annealing
- ▶ Belief propagation
- ▶ Non-linear power iteration

NOT considering massive data sets or overlapping communities!

Statistical block models

Compare algorithms in a synthetic data testing framework

- ▶ Use statistical block models to generate random graphs which exhibit community structure
- ▶ Tweaking model parameters captures varying network properties (e.g. size, sparsity, number of communities, edge-occurrence probabilities)
- ▶ Provides theoretical setting to test and compare algorithms
- ▶ Two popular models: planted partition model, 'hidden clique model'

Synthetic data testing set-up

For each community detection algorithm:

- ▶ Decide upon an appropriate generative model for this specific algorithm
- ▶ Construct synthetic data set by generating various networks with different underlying parameters of the model
- ▶ Apply the algorithm to each network in the data set and measure accuracy

Comparison of algorithms

Algorithm	Advantages ✓	Disadvantages ✗
Spectral Clustering	Simple	Accuracy ↓ as sparsity ↑ Quite slow Need no. of communities as an input
Greedy method	Simple Fast Works on larger graphs	Accuracy ↓ as sparsity ↑
Belief propagation	Very good accuracy Very fast (for sparse) Works on larger graphs	

Problem: generative models are not well representative of real-world networks!

Financial Networks: Motivation

Consider portfolio selection problem for investor: how to select assets to form the 'best' portfolio that aligns with risk and return preferences?

- ▶ Famous technique: **mean-variance portfolio theory**
- ▶ **Idea:** construct portfolio which generates the mean return desired but with lowest variance of all possible selections.
- ▶ Ideal case: make portfolio with lowest possible inter-asset correlations
- ▶ Use sample estimates of mean, variance and cross-correlation of asset returns from historical data
- ▶ Also beneficial for dynamic rebalancing of portfolio for risk management

Financial Networks: Construction

One possible approach: construct an undirected, fully connected and weighted graph!



- ▶ Each node represents an asset, with the (standardised) time series of returns for the asset associated with the node
- ▶ Weight of an edge connecting two nodes is the cross-correlation between the two time series' associated with those nodes (based on time averages)
- ▶ Weighted adjacency matrix of the graph is the empirical correlation matrix of the asset returns!

Idea: communities in financial networks represent groups of assets whose aggregate average correlation is higher within groups and lower between groups

∴ provide investors with (small number of) 'baskets' of assets

Our data set

- ▶ Collected daily price data for 80 stocks traded on FTSE 100 exchange between 01/01/2004 and 11/11/2013



Community detection approach

Underlying technique: **modularity optimisation**

- ▶ First consider two 'naive' modularity maximisation methods: greedy algorithm and spectral relaxation
- ▶ Then consider two 'modified' modularity methods, tailored for this specific application: spectral clustering and Louvain method
- ▶ **Result:** able to detect finer-tuned and more communities using tailored approach \implies higher quality partitions and notable improvement for adapted modularity techniques

Problem: only considered one static network so far! Require **dynamic** community detection to capture time-evolving correlation structure

Extension to dynamic networks

Need to alter our approach:

1. Construct time-evolving networks from data set


- ▶ Use **time-windowing** procedure to generate set of 'network slices' and create one correlation matrix per time window
- ▶ For our data set: window size of 100, overlap length of 10 \implies 240 correlation matrices

2. Apply dynamic community detection algorithm

- ▶ Consider the **generalised Louvain method** previously applied to empirical neuroscience data in the literature
- ▶ Similar procedure to Louvain method but designed to optimise a generalised notion of modularity for dynamic networks
- ▶ Use modified modularity matrices as input for each network slice to tailor the method for our application

Evaluation

- ▶ Able to understand **temporal evolution of communities** with smooth transitions in community memberships obtained
- ▶ Similar procedure is applicable for **different asset classes** if data sets are collected



But... the generalised Louvain method is slow and performance depends on appropriate parameter choice

Future work

Some directions for research in this area...

- ▶ Lack of a consensus on precise definition of a ‘community’ \implies **no single benchmark** to compare algorithms exists
- ▶ Little focus on **overlapping communities** which could lead to better models for real-world networks
- ▶ Increase in availability of time-stamped network data sets enables the study and application of **dynamic community detection** algorithms
- ▶ Significant improvements in **computational complexity** enables partitioning of networks with up to millions of nodes, but algorithms are approximate methods and not very reliable

Summary

- ▶ Introduced concept of community structure in networks and motivated use for community detection algorithms
- ▶ Mentioned several community detection algorithms and described the synthetic-data testing framework used to compare them
- ▶ Considered a real-world application of financial networks
- ▶ Identified time-evolving communities consisting of FTSE 100 stocks over the last decade
- ▶ Several interesting and important research directions exist

Thanks for listening!

Any Questions?