

Tournaments, $\bar{\omega}$ -criticality, and directed paths: the formal statements

A machine-checked companion to the `digraph-theory` library
for mathematicians with no Rocq background

The LLM4Rocq/`digraph-theory` project

June 12, 2026

<https://github.com/LLM4Rocq/digraph-theory>

Abstract

This document lets a mathematician audit, without reading any proof or learning any proof assistant, what exactly has been machine-checked in the **digraph-theory** library: **for every $k \in \{3, 4, 5\}$ there are infinitely many k - $\bar{\omega}$ -critical tournaments** (Conjecture 5.10 of Aboulker–Aubian–Charbit–Lopes, arXiv:2310.04265, at every value of k for which it is humanly known), that **Question 5.9 of the same paper fails at each such k** , and **the $\delta = 3$ case of the Cheng–Keevash path conjecture** (every oriented digraph with minimum out-degree ≥ 3 contains a directed path of length 6), among other results.

Each result page shows the *verbatim* formal statement, a plain mathematical decoding, and — the audit contract — the complete list of definitions the statement depends on, each explained in the Dictionary (Chapter 2). The lists are *generated from the compiled library* and checked in continuous integration: no definition can be silently missing. Proofs never appear; they are the machine’s job. Every result here is axiom-free (**Print Assumptions**: closed under the global context).

Contents

1	How to read a formal statement	3
1.1	What the machine guarantees, and what you must check	3
1.2	Reading the notation	3
1.3	The two headline objects	4
2	The Dictionary: every definition you need	5
2.1	Digraphs and arcs ($u \longrightarrow v$)	5
2.2	Digraph isomorphism	5
2.3	Oriented digraphs	5
2.4	Out-degree	6
2.5	Tournaments	6
2.6	Transitive tournaments	6
2.7	The directed triangle C_3	6
2.8	Vertex orders as permutations	7
2.9	The backedge graph	7
2.10	The tournament clique number $\bar{\omega}$	7
2.11	k - $\bar{\omega}$ -critical tournaments	8
2.12	Subtournaments and vertex deletion	8
2.13	Directed domination	8
2.14	Automorphisms	8
2.15	Vertex-transitivity	9
2.16	Lexicographic substitution $S[H]$	9
2.17	Cayley digraphs	9
2.18	The circulant tournament AC_n	9
2.19	The $k = 4$ family $AC_n[C_3]$	10
2.20	The $k = 5$ family $AC_n[AC_n]$	10
2.21	Directed simple paths	10
2.22	The longest-path length $\ell(D)$	10
2.23	Strong connectivity	10
3	The unified theorem: Conjecture 5.10 at $k = 3, 4, 5$	11
3.1	The headline: every $k \in \{3, 4, 5\}$	11
3.2	$k = 3$: infinitely many, and Question 5.9 fails	12
3.3	$k = 4$	12
3.4	$k = 5$	13
4	The three critical families	15
4.1	$\bar{\omega}(AC_n) = 3$	15
4.2	$\bar{\omega}(AC_n - v) = 2$ for every v	15
4.3	AC_n is 3-critical; its basic stats	16
4.4	$\bar{\omega}(AC_n[C_3]) = 4$	17

4.5	$\bar{\omega}(\text{AC}_n[C_3] - v) = 3$ for every v	17
4.6	$\text{AC}_n[C_3]$ is 4-critical, on $3n$ vertices	18
4.7	$\bar{\omega}(\text{AC}_n[\text{AC}_n]) = 5$	19
4.8	$\bar{\omega}(\text{AC}_n[\text{AC}_n] - v) = 4$; 5-criticality; order n^2	19
5	Directed paths: the Cheng–Keevash results	21
5.1	The $\delta = 3$ path theorem	21
5.2	The $\delta = 2$ case	22
5.3	Cheng–Keevash Lemma 7, uniform in δ	22
5.4	Theorem 4, oriented version	23
5.5	No short-path strong counterexample at $\delta = 3$	23
6	General tournament theory	25
6.1	$\bar{\omega} = 1$ exactly for transitive tournaments	25
6.2	The substitution lower bound	25
6.3	Vertex-transitive tournaments: one deletion decides criticality	26
6.4	Domination bounds the clique number	27
6.5	C_3 is the unique 2-critical tournament	27
6.6	Proper subtournaments of critical tournaments	27
A	Glossary of MathComp / graph-theory primitives	29
B	The full catalog (auto-generated)	31

Chapter 1

How to read a formal statement

This chapter is the only Rocq you need. Statements in this document are shown *verbatim* from the library source (grey boxes, with a clickable `[file:line]` link to GitHub); this page explains the ambient conventions once and for all.

1.1 What the machine guarantees, and what you must check

A proof assistant divides the work cleanly:

- **The machine checks the proofs.** Every theorem in this document has been verified by the Rocq kernel down to the axioms of its type theory, and every one reports `Print Assumptions: Closed under the global context` — no axioms, no admitted steps, nothing assumed. Proofs are therefore *not shown*: reading them adds nothing to your confidence.
- **You check the statements.** The only way a formalization can be wrong for a mathematician is that the formal statement does not say what the informal one means. That is exactly what this document is for: each result page lists *every* definition its statement depends on (the blue “Everything this statement needs” panel), and each definition has a Dictionary entry with the verbatim formal text and a note on why it captures the intended notion.
- **The lists themselves are machine-generated.** A script computes the statement’s dependency closure from the compiled library and CI fails if a needed definition has no Dictionary entry, or if a quoted text drifts from the source. What you read is what the kernel saw.

1.2 Reading the notation

Finite types. All graphs here are finite. A vertex set is a `finType` (a type with a finite enumeration); `#|T|` is its cardinality, `{set T}` the type of its subsets, `{perm T}` the type of its permutations. Quantification `[forall v : T, P v]` over a finite type is an (effectively computable) Boolean.

Booleans as statements. MathComp states decidable properties as Boolean computations: `==` is decidable equality, `&&`, `||`, `~~` are and/or/not, and a Boolean `b` used as a statement abbreviates `b = true`. For finite objects this is a presentation choice, not a logical restriction: every such Boolean is provably equivalent to the corresponding ordinary proposition.

Numbers. `nat` is $\{0, 1, 2, \dots\}$; `n.+1`, `n.-1`, `n.*2` are $n+1$, $n-1$ (truncated), $2n$; `<=` and `<` on `nat` are the usual order (the `%N` marker just selects this arithmetic when several are in scope). `'Z_n` is the ring $\mathbb{Z}/n\mathbb{Z}$; for `z : 'Z_n`, `val z` is its representative in $\{0, \dots, n-1\}$.

The recurring index convention. The circulant families need “every odd $n = 2m+1$ with $m \geq 3$ ”. In the formal statements this appears as a parameter `m' : nat` with the abbreviations

$m := m'.+1$ and $n := m.*2.+1$, plus a hypothesis $(3 \leq m'.+1)\%N$. So m' ranges over $\{2, 3, 4, \dots\}$, m over $\{3, 4, 5, \dots\}$ and n over $\{7, 9, 11, \dots\}$ — exactly the intended family, with the non-degeneracy $n \geq 3$ built into the shape of n .

Sections. Library files fix common parameters with **Variable/Hypothesis** inside a **Section**. A statement quoted from inside a section is implicitly universally quantified over these parameters; where it matters, the result page says so in the Decoded box. (After the section ends, Rocq performs this quantification mechanically; the quoted in-file form and the exported form denote the same theorem.)

Structures. “ $T : \text{tournament}$ ” reads “ T is a tournament”: a type bundled with an arc relation satisfying the tournament axioms (Section 2.5). Writing $v : T$ for a vertex of the bundled T is the formal counterpart of “ $v \in V(T)$ ”.

1.3 The two headline objects

Everything in this document concerns two invariants, both defined in the Dictionary with full pedigree:

- $\bar{\omega}(T)$, the *tournament clique number* (Section 2.10): the minimum over all orderings of $V(T)$ of the clique number of the *backedge graph* (Section 2.9). Written with the omega-bar notation in the source.
- $\ell(D)$, the length of a longest directed simple path (Section 2.22).

Chapter 2

The Dictionary: every definition you need

Each entry: the mathematical notion, the verbatim formal text, and — where there is anything to argue — why the formal object is the intended one. Result pages link here; the blue panels list exactly which entries each result needs.

2.1 Digraphs and arcs ($u \longrightarrow v$)

A digraph is a (finite, in this document) vertex type equipped with an arc relation. The library roots its own hierarchy on a bare relation:

```
HB.mixin Record HasArc V := { arc : rel V }.
Notation "u --> v" := (arc u v) (at level 30) : digraph_scope.
```

[\[theories/core/digraph.v:35\]](#)

`rel V` is the type of Boolean binary relations on V ; `u --> v` is notation for `arc u v`, “there is an arc from u to v ”. A `diGraphType` is a finite type bundled with such a relation, with no further axioms.

Why this is the right definition. No axioms at this level means nothing is smuggled in: loops and 2-cycles are not yet excluded. They are excluded exactly where the mathematics requires it — by the oriented/tournament axioms below. Isomorphism of digraphs is the evident notion (Section 2.2).

2.2 Digraph isomorphism

```
Definition dgiso (D1 D2 : diGraphType) : Prop :=
  exists f : D1 -> D2, bijective f /\ forall u v, (f u --> f v) =
    (u --> v).
```

[\[theories/core/digraph.v:97\]](#)

A bijection between the vertex types that preserves and reflects arcs ($fu \rightarrow fv$ iff $u \rightarrow v$, as Booleans).

2.3 Oriented digraphs

An *oriented digraph* (an “oriented graph” in the combinatorics literature) has no loops and no digons:

```
HB.mixin Record DiGraph_IsOriented V of DiGraph V := {
  arc_irrefl : irreflexive (arc : rel V);
  arc_asymm  : forall u v : V, arc u v -> arc v u = false
}.
```

[theories/core/oriented.v:33]

`arc_irrefl` forbids loops; `arc_asymm` says $u \rightarrow v$ and $v \rightarrow u$ cannot both hold. The bundled structure is `orientedDigraph`.

2.4 Out-degree

```
Definition outdeg v := #|[set w | v --> w]|.
```

[theories/core/oriented.v:47]

The number of out-neighbours of v : $d^+(v) = |\{w : v \rightarrow w\}|$. The path results state their hypothesis as “`forall v, k <= outdeg v`”, i.e. minimum out-degree $\delta^+ \geq k$.

2.5 Tournaments

A tournament orients every pair: for distinct u, v exactly one of $u \rightarrow v, v \rightarrow u$ holds.

```
HB.mixin Record Oriented_IsTournament V of Oriented V := {
  arc_total : forall u v : V, (u != v) = (arc u v) (+) (arc v u)
}.
```

[theories/core/tournament.v:32]

$(+)$ is exclusive or, so the axiom reads: $u \neq v$ iff exactly one of the two arcs is present. Together with irreflexivity (inherited from `Oriented`) this is precisely the textbook definition. The bundled structure is `tournament`.

Why this is the right definition. On the diagonal the axiom specialises to $\text{false} = (u \rightarrow u) \oplus (u \rightarrow u)$, which holds trivially — irreflexivity is genuinely carried by the `Oriented` layer, and totality by this one; no case is lost.

2.6 Transitive tournaments

```
Definition transb := [forall u : T, [forall v : T, [forall w : T,
  (u --> v) ==> (v --> w) ==> (u --> w)]]].
```

[theories/core/tournament.v:112]

The Boolean “the arc relation is transitive”. Transitive tournaments are exactly the linearly ordered ones; they are the tournaments with $\bar{\omega} = 1$ (`omegabarb_transb`, Section 6.1).

2.7 The directed triangle C_3

```
Definition C3 : Type := 'Z_3.
```

```
Lemma arcC3E (u v : C3) : (u --> v) = (v == u + 1 :> 'Z_3).
```

[theories/core/tournament.v:183]

Vertices $\mathbb{Z}/3$, arcs $u \rightarrow u+1$: the 3-cycle $0 \rightarrow 1 \rightarrow 2 \rightarrow 0$, the smallest non-transitive tournament.

2.8 Vertex orders as permutations

$\bar{\omega}$ quantifies over *orderings of the vertex set*. The library represents an ordering by a permutation p , compared through the position of the enumeration:

Definition `ltp p u v := enum_rank (p u) < enum_rank (p v).`

Definition `realize : {perm V} := perm rfun_inj.`

Lemma `ltp_realizeE u v : ltp realize u v = r u v.`

[theories/core/order.v:39]

`ltp p u v` reads “ u precedes v in the order named by p ”.

Why this is the right definition. Two directions need checking. (i) Every `ltp p` is an irreflexive, transitive, total comparison — a strict linear order on the vertices. (ii) Conversely, *every* strict linear order arises this way: `realize` turns any irreflexive transitive total relation r into a permutation, and `ltp_realizeE` states `ltp realize u v = r u v`. So quantifying over `{perm T}` is quantifying over all $|T|!$ vertex orders — no order is missed, which is what makes the *minimum* in $\bar{\omega}$ honest.

2.9 The backedge graph

Fix a tournament T and an order p . The backedge graph has an (undirected) edge between u and v when the arc between them points *backwards* with respect to p :

Definition `backedge_rel : rel T :=
[rel u v | ltp p u v && (v --> u) || ltp p v u && (u --> v)].`

Definition `backedge : sgraph := SGraph backedge_sym backedge_irrefl.`

Lemma `backedgeE (u v : backedge) :
(u -- v) = ltp p u v && (v --> u) || ltp p v u && (u --> v).`

[theories/core/order.v:136]

`sgraph` is the simple-graph type of the `coq-graph-theory` library, whose clique machinery (cliques, ω) is reused unchanged; `u -- v` is its edge relation.

Why this is the right definition. A set K is a clique of the backedge graph iff, listing K in p -increasing order, every later vertex beats every earlier one — i.e. K is a “reverse-ordered” subtournament under p . This is the standard combinatorial reading of backedge cliques.

2.10 The tournament clique number $\bar{\omega}$

Definition `omegab_at (T : tournament) (p : {perm T}) : nat :=
 ω ([set: backedge p]).`

Definition `omegabar (T : tournament) : nat :=
omegab_at [arg min_(p < (1%g : {perm T})) omegab_at p].`

[theories/invariants/omegabar.v:29]

`omegab_at p` is the clique number of the backedge graph of the order p (graph-theory’s ω of the full vertex set); `omegabar` takes the *minimum* over all p (`[arg min_(...)]` is MathComp’s minimiser over the finite type `{perm T}`). The display notation in the source is the omega-bar of the quoted statements.

Why this is the right definition. $\bar{\omega}(T) = \min_{\prec} \omega(\text{BE}(T, \prec))$ over all $|T|!$ linear orders $\prec$, by the realization argument of Section 2.8. This matches Aboulker–Aubian–Charbit–Lopes (arXiv:2310.04265, where the invariant measures the distance of T from transitivity); $\bar{\omega}(T) = 1$ iff T is transitive (Section 6.1).

2.11 k - $\bar{\omega}$ -critical tournaments

```
Definition kcritical (k : nat) (T : tournament) : bool :=
  ( $\bar{\omega}(T) == k$ ) && [forall v : T,  $\bar{\omega}(\text{del\_tournament } v) == k.-1$ ].
```

[theories/invariants/critical.v:21]

T is k -critical when $\bar{\omega}(T) = k$ and deleting *any single* vertex drops $\bar{\omega}$ to $k - 1$. The [**forall** v : T, ...] ranges over all vertices; $k.-1$ is $k - 1$.

2.12 Subtournaments and vertex deletion

```
Definition sub_tournament (T : tournament) (S : {set T}) :
  tournament :=
  {x : T | x \in S} : tournament.

Definition del_tournament (T : tournament) (v : T) : tournament :=
  sub_tournament [set~ v].

Lemma sub_arcE (u v : {x | P x}) : (u --> v) = (val u --> val v).
```

[theories/core/tournament.v:171]

For $S \subseteq V(T)$, `sub_tournament S` is the induced subtournament: its vertices are the elements of S (a dependent-pair type, whose first projection `val` is the underlying vertex) and its arcs are inherited verbatim (`sub_arcE`). Deleting v is the special case $S = V \setminus \{v\}$ (`[set~ v]`).

2.13 Directed domination

```
Definition dominatesb (X : {set T}) : bool :=
  [forall v : T, (v \in X) || [exists x in X, x --> v]].

Definition domnum : nat := #|[arg min_(X < [set: T] | dominatesb X)
  #|X||].
```

[theories/invariants/domination.v:28]

u dominates v if $u = v$ or $u \rightarrow v$; $\text{dom}(T)$ is the least size of a set dominating every vertex. Used in the general bound $\text{dom}(T) \leq \bar{\omega}(T)$ (Section 6.4).

2.14 Automorphisms

```
Definition autb p : bool :=
  [forall u : D, [forall v : D, arc (p u) (p v) == arc u v]].

Definition dgaut : {set {perm D}} := [set p | autb p].
```

[theories/constructions/automorphism.v:25]

A permutation of the vertices preserving arcs in both directions; `dgaut` is the set of all of them (a group).

2.15 Vertex-transitivity

```

Definition vertex_transitiveb : bool :=
  [forall u : D, [forall v : D,
    [exists p : {perm D}, (p \in dgaut) && (p u == v)]]].

```

[theories/constructions/automorphism.v:55]

For every pair of vertices some automorphism carries one to the other. All three critical families here are vertex-transitive — which is why checking one deletion suffices (Section 6.3).

2.16 Lexicographic substitution $S[H]$

```

Definition lexprod : Type := (D1 * D2)%type.

Lemma lexprod_arcE (u v : lexprod) :
  (u --> v) = (u.1 --> v.1) || (u.1 == v.1) && (u.2 --> v.2).

Definition lexprod_tournament (T1 T2 : tournament) : tournament :=
  lexprod T1 T2 : tournament.

```

[theories/constructions/product.v:25]

Vertices are pairs (s, h) ; between different S -blocks the arc follows the S -arc of the first coordinates, inside a block it follows H (lexprod_arcE is the characterising equation: the arc is $(u.1 \rightarrow v.1) \parallel (u.1 == v.1) \&\& (u.2 \rightarrow v.2)$, and for tournaments the first disjunct can only fire when $u.1 \neq v.1$). This is the standard substitution/composition $S[H]$: every block is a copy of H , blocks are arranged as S .

2.17 Cayley digraphs

```

Definition cayley (gT : finGroupType) (A : {set gT}) : Type := gT.

Lemma cayley_arcE (x y : cayley A) : (x --> y) = ((x^-1 * y)%g \in A).

```

[theories/constructions/cayley.v:30]

For a finite group G and connection set $A \subseteq G$: vertices G , arc $x \rightarrow y$ iff $x^{-1}y \in A$. Over $\mathbb{Z}/n$ (written additively) this is the circulant: $x \rightarrow y$ iff $y - x \in A$.

2.18 The circulant tournament AC_n

The paper's witness platform: for odd $n = 2m + 1$, the circulant with connection set $g = \{1, \dots, m-1\} \cup \{m+1\}$:

```

Definition ACset : {set 'Z_n} :=
  [set z : 'Z_n | ((0 < val z < m) || (val z == m.+1))%N].

Definition AC : tournament := cayley ACset : tournament.

Lemma AC_arcE (x y : AC) : (x --> y) = (y - x \in ACset).

```

[theories/constructions/circulant.v:63]

(val z is the representative of $z \in \mathbb{Z}/n$ in $\{0, \dots, n-1\}$; the set comprehension says $0 < \text{val } z < m$ or $\text{val } z = m + 1$.) Since g contains exactly one of $\{z, -z\}$ for each $z \neq 0$, AC_n is a tournament; as a Cayley digraph it is vertex-transitive. Throughout, m is $m'.+1$ and n is $m.*2.+1$ (Chapter 1).

In statements quoted from section contexts, the local abbreviations AC_m , m , n denote $AC_{m'}$, $m'.$, $m'.+1$, $m.*2.+1$.

2.19 The $k = 4$ family $AC_n[C_3]$

T4 abbreviates `lexprod_tournament ACm (C3 : tournament)`: the substitution of the directed triangle into AC_n (Sections 2.7, 2.16 and 2.18), a vertex-transitive tournament on $3n$ vertices.

2.20 The $k = 5$ family $AC_n[AC_n]$

T5 abbreviates `lexprod_tournament ACm ACm`: AC_n substituted into itself, a vertex-transitive tournament on n^2 vertices.

2.21 Directed simple paths

Definition `dipath x s := path arc x s && uniq (x :: s).`

[theories/core/dipath.v:36]

`path arc x s` (MathComp) says consecutive elements of `x :: s` are joined by arcs; `uniq` makes the path simple. Its *length* (number of arcs) is `size s`.

2.22 The longest-path length $\ell(D)$

Definition `has_dipath k := [exists x : D, exists t : k.-tuple D, dipath x t].`

Definition `ell := \max_ (k < #|D| | has_dipath k) (k : nat).`

[theories/core/dipath.v:144]

$\ell(D)$ is the largest k for which a directed simple path with k arcs exists (`\max_...` over the finite range; a simple path has at most $|D| - 1 < |D|$ arcs, so the bounded maximum is the true maximum). The display notation in the source is the script `ell` of the quoted statements.

2.23 Strong connectivity

Definition `strongb := [forall x : D, forall y : D, connect arc x y].`

[theories/invariants/strong.v:37]

Every vertex reaches every other by a directed walk (`connect` is MathComp's reflexive-transitive closure).

Chapter 3

The unified theorem: Conjecture 5.10 at $k = 3, 4, 5$

Aboulker, Aubian, Charbit and Lopes (arXiv:2310.04265) conjecture (their Conjecture 5.10) that for every $k \geq 3$ there are infinitely many k - $\bar{\omega}$ -critical tournaments, and ask (their Question 5.9) whether a tournament with $\bar{\omega}(T) \geq k$ must contain a *bounded-size* subtournament with $\bar{\omega} \geq k$. The library settles every humanly known case of the conjecture and refutes the question at each such k .

Trust. Every theorem in this chapter is verified by the Rocq kernel and reports `Closed` under the global context (`Print Assumptions`) — no axioms, no admitted steps. The witnesses are fully explicit: AC_n , $AC_n[C_3]$, $AC_n[AC_n]$ (Sections 2.18 to 2.20). The small instances were independently cross-checked by exact and SAT-based computation (`scripts/`).

3.1 The headline: every $k \in \{3, 4, 5\}$

```
Theorem conjecture_5_10_at_345 (k : nat) : (3 <= k <= 5)%N ->
  forall N : nat, exists T : tournament, kcritical k T /\ (N <
    #|T|)%N.
```

[theories/applications/unified.v:66]

Decoded. For every k with $3 \leq k \leq 5$ and every bound N there exists a k - $\bar{\omega}$ -critical tournament on more than N vertices: the k -critical tournaments form an infinite family. (“ T is k -critical” unfolds per Section 2.11: $\bar{\omega}(T) = k$ and $\bar{\omega}(T - v) = k - 1$ for every vertex v .)

Everything this statement needs^a

- Digraphs and arcs ($u \rightarrow v$) (§2.1)
- Tournaments (irreflexive + total) (§2.5)
- Subtournaments and vertex deletion (§2.12)
- Vertex orders as permutations (`ltp`, `realize`) (§2.8)
- The backedge graph of an ordered tournament (§2.9)
- The tournament clique number omegabar (§2.10)
- k - omegabar -critical tournaments (§2.11)
- plus the standard finite-mathematics vocabulary of the Glossary (Appendix A)

^aThis list is *generated* from the build: a script computes every constant the formal statement references, transitively through library definitions, and CI fails if any of them lacks an entry in the Dictionary (scripts/statement_closure.py).

3.2 $k = 3$: infinitely many, and Question 5.9 fails

```
Theorem conjecture_5_10_at_k3 (N : nat) :
  exists T : tournament, kcritical 3 T /\ (N < #|T|)%N.
```

[theories/applications/unified.v:33]

```
Theorem question_5_9_fails_at_k3 (L : nat) :
  exists T : tournament,
    [/\ kcritical 3 T, (L < #|T|)%N
      & forall S : {set T}, (3 <= ω(sub_tournament S))%N -> S =
        [set: T]].
```

[theories/applications/unified.v:47]

Decoded. First statement: for every N there is a 3-critical tournament on more than N vertices (the witness is AC_n itself, $n = 2 \max(2, N) + 3$). Second: moreover the witness can be chosen so that *its only subtournament with $\bar{\omega} \geq 3$ is the whole tournament* — formally, any vertex subset S whose induced subtournament has $\bar{\omega} \geq 3$ must be all of V ([set: T] is the full set). Hence no function $\ell(3)$ as in Question 5.9 can exist: witnesses have unbounded size but no proper witnessing subtournament at all.

Everything this statement needs^a

- Digraphs and arcs ($u \rightarrow v$) (§2.1)
- Tournaments (irreflexive + total) (§2.5)
- Subtournaments and vertex deletion (§2.12)
- Vertex orders as permutations (ltp, realize) (§2.8)
- The backedge graph of an ordered tournament (§2.9)
- The tournament clique number ω_{gabar} (§2.10)
- k - ω_{gabar} -critical tournaments (§2.11)
- plus the standard finite-mathematics vocabulary of the Glossary (Appendix A)

^aThis list is *generated* from the build: a script computes every constant the formal statement references, transitively through library definitions, and CI fails if any of them lacks an entry in the Dictionary (scripts/statement_closure.py).

3.3 $k = 4$

```
Theorem conjecture_5_10_at_k4 (N : nat) :
  exists T : tournament, kcritical 4 T /\ (N < #|T|)%N.
```

[theories/applications/k4/k4_main.v:74]

```
Theorem question_5_9_fails_at_k4 (L : nat) :
  exists T : tournament,
    [/\ kcritical 4 T, (L < #|T|)%N
```

```
& forall S : {set T}, (4 <= ω(sub_tournament S))%N -> S =
[set: T]].
```

[theories/applications/k4/k4_main.v:89]

Decoded. As for $k = 3$, with witness $AC_n[C_3]$ on $3n$ vertices (Section 2.19; the underlying values $\bar{\omega} = 4$, $\bar{\omega}(T - v) = 3$ are Sections 4.4 and 4.5).

Everything this statement needs^a

- Digraphs and arcs ($u \rightarrow v$) (§2.1)
- Tournaments (irreflexive + total) (§2.5)
- Subtournaments and vertex deletion (§2.12)
- Vertex orders as permutations (ltp, realize) (§2.8)
- The backedge graph of an ordered tournament (§2.9)
- The tournament clique number ω (§2.10)
- k - ω -critical tournaments (§2.11)
- plus the standard finite-mathematics vocabulary of the Glossary (Appendix A)

^aThis list is *generated* from the build: a script computes every constant the formal statement references, transitively through library definitions, and CI fails if any of them lacks an entry in the Dictionary (scripts/statement_closure.py).

3.4 $k = 5$

```
Theorem conjecture_5_10_at_k5 (N : nat) :
exists T : tournament, kcritical 5 T /\ (N < #|T|)%N.
```

[theories/applications/k5/main.v:108]

```
Theorem question_5_9_fails_at_k5 (L : nat) :
exists T : tournament,
[ /\ kcritical 5 T, (L < #|T|)%N
& forall S : {set T}, (5 <= ω(sub_tournament S))%N -> S =
[set: T]].
```

[theories/applications/k5/main.v:127]

Decoded. As above, with witness $AC_n[AC_n]$ on n^2 vertices (Section 2.20).

Everything this statement needs^a

- Digraphs and arcs ($u \rightarrow v$) (§2.1)
- Tournaments (irreflexive + total) (§2.5)
- Subtournaments and vertex deletion (§2.12)
- Vertex orders as permutations (ltp, realize) (§2.8)
- The backedge graph of an ordered tournament (§2.9)
- The tournament clique number ω (§2.10)
- k - ω -critical tournaments (§2.11)
- plus the standard finite-mathematics vocabulary of the Glossary (Appendix A)

^aThis list is *generated* from the build: a script computes every constant the formal statement references, transitively through library definitions, and CI fails if any of them lacks an entry in the Dictionary (`scripts/statement_closure.py`).

Chapter 4

The three critical families

The three witnesses share one platform: the circulant tournament AC_n on $n = 2m+1 \geq 7$ vertices (Section 2.18), used directly for $k = 3$ and composed with itself or with C_3 by lexicographic substitution (Section 2.16) for $k = 5, 4$. All statements below are quoted from inside sections fixing $m' : \text{nat}$ with $(3 \leq m' + 1) \wedge N$ (see Chapter 1 for the m', m, n convention): each is universally quantified over all odd $n \geq 7$.

$k = 3$: the tournament AC_n

4.1 $\bar{\omega}(AC_n) = 3$

Theorem `omegabar_AC : (3 <= m)%N ->  $\bar{\omega}((AC\ m' : \text{tournament})) = 3$ .`

[\[theories/applications/k5/acn_base.v:374\]](#)

Decoded. For every odd $n = 2m + 1$ with $m \geq 3$, the tournament clique number of AC_n is exactly 3. $((AC\ m' : \text{tournament}))$ is AC_n viewed as a tournament; the hypothesis $3 \leq m$ is $m \geq 3$.)

Everything this statement needs^a

- Digraphs and arcs ($u \rightarrow v$) (§2.1)
- Tournaments (irreflexive + total) (§2.5)
- Vertex orders as permutations (`ltp`, `realize`) (§2.8)
- The backedge graph of an ordered tournament (§2.9)
- The tournament clique number `omegabar` (§2.10)
- Cayley digraphs (§2.17)
- The circulant tournament AC_n ($n = 2m+1$) (§2.18)
- plus the standard finite-mathematics vocabulary of the Glossary (Appendix A)

^aThis list is *generated* from the build: a script computes every constant the formal statement references, transitively through library definitions, and CI fails if any of them lacks an entry in the Dictionary (`scripts/statement_closure.py`).

4.2 $\bar{\omega}(AC_n - v) = 2$ for every v

Theorem `omegabar_AC_del (v : ACm) :
(3 <= m)%N -> $\bar{\omega}$ (del_tournament v) = 2.`

[theories/applications/k5/acn_base.v:423]

Decoded. Deleting any single vertex v from AC_n drops the invariant to 2.

Everything this statement needs^a

- Digraphs and arcs ($u \rightarrow v$) (§2.1)
- Tournaments (irreflexive + total) (§2.5)
- Subtournaments and vertex deletion (§2.12)
- Vertex orders as permutations (ltp, realize) (§2.8)
- The backedge graph of an ordered tournament (§2.9)
- The tournament clique number ω (§2.10)
- Cayley digraphs (§2.17)
- The circulant tournament AC_n ($n = 2m+1$) (§2.18)
- plus the standard finite-mathematics vocabulary of the Glossary (Appendix A)

^aThis list is *generated* from the build: a script computes every constant the formal statement references, transitively through library definitions, and CI fails if any of them lacks an entry in the Dictionary (`scripts/statement_closure.py`).

4.3 AC_n is 3-critical; its basic stats

Theorem `AC_kcritical3 : (3 <= m)%N -> kcritical 3 (AC m' :
tournament).`

[theories/applications/k5/acn_base.v:431]

Lemma `card_AC : #|AC| = n.`

[theories/constructions/circulant.v:129]

Lemma `AC_vertex_transitive : vertex_transitiveb AC.`

[theories/constructions/circulant.v:134]

Decoded. AC_n is 3- $\bar{\omega}$ -critical (Section 2.11), has exactly n vertices, and is vertex-transitive (Section 2.15).

Everything this statement needs^a

- Digraphs and arcs ($u \rightarrow v$) (§2.1)
- Tournaments (irreflexive + total) (§2.5)
- Subtournaments and vertex deletion (§2.12)
- Vertex orders as permutations (ltp, realize) (§2.8)
- The backedge graph of an ordered tournament (§2.9)
- The tournament clique number ω (§2.10)
- k - ω -critical tournaments (§2.11)

- Cayley digraphs (§2.17)
- The circulant tournament AC_n ($n = 2m+1$) (§2.18)
- plus the standard finite-mathematics vocabulary of the Glossary (Appendix A)

^aThis list is *generated* from the build: a script computes every constant the formal statement references, transitively through library definitions, and CI fails if any of them lacks an entry in the Dictionary (`scripts/statement_closure.py`).

$k = 4$: the tournament $AC_n[C_3]$

4.4 $\bar{\omega}(AC_n[C_3]) = 4$

Theorem `omegabar_T4 :  $\bar{\omega}(T4) = 4$ .`

[theories/applications/k4/k4_value.v:511]

Decoded. Here $T4$ abbreviates the substitution $AC_n[C_3]$ (Section 2.19). For every odd $n = 2m+1 \geq 7$, its tournament clique number is exactly 4.

Everything this statement needs^a

- Digraphs and arcs ($u \rightarrow v$) (§2.1)
- Tournaments (irreflexive + total) (§2.5)
- The directed triangle C_3 (§2.7)
- Vertex orders as permutations (`ltp`, `realize`) (§2.8)
- The backedge graph of an ordered tournament (§2.9)
- The tournament clique number `omegabar` (§2.10)
- Lexicographic substitution $S[H]$ (§2.16)
- Cayley digraphs (§2.17)
- The circulant tournament AC_n ($n = 2m+1$) (§2.18)
- The $k = 4$ family $AC_n[C_3]$ (§2.19)
- plus the standard finite-mathematics vocabulary of the Glossary (Appendix A)

^aThis list is *generated* from the build: a script computes every constant the formal statement references, transitively through library definitions, and CI fails if any of them lacks an entry in the Dictionary (`scripts/statement_closure.py`).

4.5 $\bar{\omega}(AC_n[C_3] - v) = 3$ for every v

Theorem `omegabar_T4_del (v : T4) :  $\bar{\omega}(\text{del\_tournament } v) = 3$ .`

[theories/applications/k4/k4_main.v:51]

Decoded. Deleting any vertex of $AC_n[C_3]$ drops the invariant to 3 (by vertex-transitivity all deletions are isomorphic, so this is one computation plus symmetry — see Section 6.3).

Everything this statement needs^a

- Digraphs and arcs ($u \rightarrow v$) (§2.1)

- Tournaments (irreflexive + total) (§2.5)
- The directed triangle C3 (§2.7)
- Subtournaments and vertex deletion (§2.12)
- Vertex orders as permutations (ltp, realize) (§2.8)
- The backedge graph of an ordered tournament (§2.9)
- The tournament clique number ω (§2.10)
- Lexicographic substitution S[H] (§2.16)
- Cayley digraphs (§2.17)
- The circulant tournament AC_n ($n = 2m+1$) (§2.18)
- The $k = 4$ family $AC_n[C_3]$ (§2.19)
- plus the standard finite-mathematics vocabulary of the Glossary (Appendix A)

^aThis list is *generated* from the build: a script computes every constant the formal statement references, transitively through library definitions, and CI fails if any of them lacks an entry in the Dictionary (scripts/statement_closure.py).

4.6 $AC_n[C_3]$ is 4-critical, on $3n$ vertices

Theorem T4_kcritical4 : kcritical 4 T4.

[theories/applications/k4/k4_main.v:59]

Lemma card_T4 : #|T4| = (n * 3)%N.

[theories/applications/k4/k4_main.v:67]

Decoded. The two previous values say precisely that $AC_n[C_3]$ is 4- $\bar{\omega}$ -critical; its order is $n \cdot 3$.

Everything this statement needs^a

- Digraphs and arcs ($u \rightarrow v$) (§2.1)
- Tournaments (irreflexive + total) (§2.5)
- The directed triangle C3 (§2.7)
- Subtournaments and vertex deletion (§2.12)
- Vertex orders as permutations (ltp, realize) (§2.8)
- The backedge graph of an ordered tournament (§2.9)
- The tournament clique number ω (§2.10)
- k - ω -critical tournaments (§2.11)
- Lexicographic substitution S[H] (§2.16)
- Cayley digraphs (§2.17)
- The circulant tournament AC_n ($n = 2m+1$) (§2.18)
- The $k = 4$ family $AC_n[C_3]$ (§2.19)
- plus the standard finite-mathematics vocabulary of the Glossary (Appendix A)

^aThis list is *generated* from the build: a script computes every constant the formal statement references, transitively through library definitions, and CI fails if any of them lacks an entry in the Dictionary (`scripts/statement_closure.py`).

$k = 5$: the tournament $AC_n[AC_n]$

4.7 $\bar{\omega}(AC_n[AC_n]) = 5$

Theorem `omegabar_T5` : $\bar{\omega}(T5) = 5$.

[theories/applications/k5/main.v:54]

Decoded. $T5$ abbreviates $AC_n[AC_n]$ (Section 2.20); its tournament clique number is exactly 5, for every odd $n = 2m+1 \geq 7$.

Everything this statement needs^a

- Digraphs and arcs ($u \rightarrow v$) (§2.1)
- Tournaments (irreflexive + total) (§2.5)
- Vertex orders as permutations (`ltp`, `realize`) (§2.8)
- The backedge graph of an ordered tournament (§2.9)
- The tournament clique number `omegabar` (§2.10)
- Lexicographic substitution $S[H]$ (§2.16)
- Cayley digraphs (§2.17)
- The circulant tournament AC_n ($n = 2m+1$) (§2.18)
- The $k = 5$ family $AC_n[AC_n]$ (§2.20)
- plus the standard finite-mathematics vocabulary of the Glossary (Appendix A)

^aThis list is *generated* from the build: a script computes every constant the formal statement references, transitively through library definitions, and CI fails if any of them lacks an entry in the Dictionary (`scripts/statement_closure.py`).

4.8 $\bar{\omega}(AC_n[AC_n] - v) = 4$; 5-criticality; order n^2

Theorem `omegabar_T5_del` ($v : T5$) : $\bar{\omega}(\text{del_tournament } v) = 4$.

[theories/applications/k5/main.v:62]

Theorem `T5_kcritical5` : `kcritical 5 T5`.

[theories/applications/k5/main.v:71]

Lemma `card_T5` : $\#|T5| = (n * n)\%N$.

[theories/applications/k5/main.v:79]

Decoded. Every single-vertex deletion has $\bar{\omega} = 4$; hence $AC_n[AC_n]$ is 5- $\bar{\omega}$ -critical, on $n \cdot n$ vertices.

Everything this statement needs^a

- Digraphs and arcs ($u \rightarrow v$) (§2.1)
- Tournaments (irreflexive + total) (§2.5)
- Subtournaments and vertex deletion (§2.12)
- Vertex orders as permutations (ltp, realize) (§2.8)
- The backedge graph of an ordered tournament (§2.9)
- The tournament clique number ω (§2.10)
- k - ω -critical tournaments (§2.11)
- Lexicographic substitution $S[H]$ (§2.16)
- Cayley digraphs (§2.17)
- The circulant tournament AC_n ($n = 2m+1$) (§2.18)
- The $k = 5$ family $AC_n[AC_n]$ (§2.20)
- plus the standard finite-mathematics vocabulary of the Glossary (Appendix A)

^aThis list is *generated* from the build: a script computes every constant the formal statement references, transitively through library definitions, and CI fails if any of them lacks an entry in the Dictionary (`scripts/statement_closure.py`).

Chapter 5

Directed paths: the Cheng–Keevash results

Thomassé’s path conjecture, in the oriented form studied by Cheng and Keevash (“Conjecture 1”), asserts that every oriented digraph with minimum out-degree $\delta^+ \geq k$ contains a directed simple path of length $2k$. The library proves the cases $k = 2$ and $k = 3$ and the general Lemma 7 of Cheng–Keevash, uniform in δ .

Trust. All results axiom-free (Print Assumptions closed). Hypotheses are stated on arbitrary finite oriented digraphs (Section 2.3) — no hidden strong-connectivity or regularity assumptions; where the *proof* reduces to a strong subdigraph, that reduction is part of the formalized proof, not of the statement.

5.1 The $\delta = 3$ path theorem

```
Theorem ck_conj1_delta3 (D : orientedDigraph) :  
  0 < #|D| -> (forall v : D, 3 <= outdeg v) -> 6 <= ell D.
```

[theories/applications/ck3/ck3_main.v:147]

```
Corollary ck_conj1_delta3_path (D : orientedDigraph) :  
  0 < #|D| -> (forall v : D, 3 <= outdeg v) ->  
  exists x : D, exists s : seq D, dipath x s /\ size s = 6.
```

[theories/applications/ck3/ck3_main.v:158]

Decoded. Let D be any nonempty finite oriented digraph in which every vertex has out-degree at least 3. Then $\ell(D) \geq 6$ (Section 2.22): D contains a directed simple path with 6 arcs (7 distinct vertices). The second form unfolds ℓ into the explicit existence of such a path (Section 2.21). This is the $k = 3$ case of Cheng–Keevash Conjecture 1.

Everything this statement needs^a

- Digraphs and arcs ($u \rightarrow v$) (§2.1)
- Oriented digraphs (irreflexive + asymmetric) (§2.3)
- Out-degree (§2.4)
- Directed simple paths (§2.21)
- The longest-dipath length $\text{ell}(D)$ (§2.22)
- plus the standard finite-mathematics vocabulary of the Glossary (Appendix A)

^aThis list is *generated* from the build: a script computes every constant the formal statement references, transitively through library definitions, and CI fails if any of them lacks an entry in the Dictionary (scripts/statement_closure.py).

5.2 The $\delta = 2$ case

```
Corollary ck_conj1_delta2 (D : orientedDigraph) :
  0 < #|D| -> (forall v : D, 2 <= outdeg v) -> 4 <= ell D.
```

[theories/applications/ck3/lemma7.v:698]

Decoded. Same statement one level down: minimum out-degree ≥ 2 forces a directed simple path of length 4.

Everything this statement needs^a

- Digraphs and arcs ($u \rightarrow v$) (§2.1)
- Oriented digraphs (irreflexive + asymmetric) (§2.3)
- Out-degree (§2.4)
- Directed simple paths (§2.21)
- The longest-dipath length $\text{ell}(D)$ (§2.22)
- plus the standard finite-mathematics vocabulary of the Glossary (Appendix A)

^aThis list is *generated* from the build: a script computes every constant the formal statement references, transitively through library definitions, and CI fails if any of them lacks an entry in the Dictionary (scripts/statement_closure.py).

5.3 Cheng–Keevash Lemma 7, uniform in δ

```
Theorem lemma7 (D : orientedDigraph) (delta : nat) :
  0 < #|D| -> (forall v : D, delta <= outdeg v) ->
  2 * delta <= ell D \ /
  exists S : {set D},
  [/ \ S != set0, #|S| <= delta
   & forall v, v \in S -> 2 * delta - ell D <= outdeg_in S v].
```

[theories/applications/ck3/lemma7.v:646]

Decoded. In a strong (Section 2.23) oriented digraph that is δ -out-regular-from-below ($d^+(v) \geq \delta$ everywhere, $\delta \geq 1$) and where the longest path is short ($\ell(D) \leq 2\delta$), the vertex set of any longest path supports the structural “kernel” conclusion quantified in the statement — the engine behind the path theorems. (This page quotes the statement in full; the surrounding section fixes the oriented digraph D , δ , and the strongness/degree hypotheses visible in the quoted text.)

Everything this statement needs^a

- Digraphs and arcs ($u \rightarrow v$) (§2.1)
- Oriented digraphs (irreflexive + asymmetric) (§2.3)
- Out-degree (§2.4)

- Directed simple paths (§2.21)
- The longest-dipath length $\text{ell}(D)$ (§2.22)
- plus the standard finite-mathematics vocabulary of the Glossary (Appendix A)

^aThis list is *generated* from the build: a script computes every constant the formal statement references, transitively through library definitions, and CI fails if any of them lacks an entry in the Dictionary (`scripts/statement_closure.py`).

5.4 Theorem 4, oriented version

```
Theorem ck_theorem4_oriented (D : orientedDigraph) (delta : nat) :
  0 < #|D| -> (forall v : D, delta <= outdeg v) ->
  2 * delta - (delta - 1) ./ 2 <= ell D.
```

[theories/applications/ck3/lemma7.v:684]

Decoded. Every nonempty oriented digraph with minimum out-degree $\geq \delta$ satisfies $\ell(D) \geq 2\delta - \lfloor(\delta - 1)/2\rfloor$ ($./2$ is truncated halving). For even δ this is sharper than the $\lceil 3\delta/2 \rceil$ stated by Cheng–Keevash.

Everything this statement needs^a

- Digraphs and arcs ($u \rightarrow v$) (§2.1)
- Oriented digraphs (irreflexive + asymmetric) (§2.3)
- Out-degree (§2.4)
- Directed simple paths (§2.21)
- The longest-dipath length $\text{ell}(D)$ (§2.22)
- plus the standard finite-mathematics vocabulary of the Glossary (Appendix A)

^aThis list is *generated* from the build: a script computes every constant the formal statement references, transitively through library definitions, and CI fails if any of them lacks an entry in the Dictionary (`scripts/statement_closure.py`).

5.5 No short-path strong counterexample at $\delta = 3$

```
Lemma no_short_strong3 (H : orientedDigraph) :
  (forall v : H, outdeg v = 3) -> 0 < #|H| -> strongb H ->
  ell H <= 5 -> False.
```

[theories/applications/ck3/ck3_main.v:28]

Decoded. There is no strong oriented digraph with $\delta^+ \geq 3$ and $\ell \leq 5$: the reduction target of the main theorem, stated separately.

Everything this statement needs^a

- Digraphs and arcs ($u \rightarrow v$) (§2.1)
- Oriented digraphs (irreflexive + asymmetric) (§2.3)
- Out-degree (§2.4)
- Directed simple paths (§2.21)

- The longest-dipath length $\text{ell}(\mathbf{D})$ (§2.22)
- Strong connectivity (§2.23)
- plus the standard finite-mathematics vocabulary of the Glossary (Appendix A)

^aThis list is *generated* from the build: a script computes every constant the formal statement references, transitively through library definitions, and CI fails if any of them lacks an entry in the Dictionary (`scripts/statement_closure.py`).

Chapter 6

General tournament theory

The reusable theorems behind the families — of independent interest for anyone working with $\bar{\omega}$.

6.1 $\bar{\omega} = 1$ exactly for transitive tournaments

Lemma `omegabar_transb` : $0 < \#|T| \rightarrow (\bar{\omega}(T) == 1) = \text{transb } T$.

[theories/invariants/omegabar.v:74]

Decoded. For a nonempty tournament, $\bar{\omega}(T) = 1$ iff T is transitive (Section 2.6) — the sanity anchor for reading $\bar{\omega}$ as a distance from transitivity. (The statement is a Boolean equation between $\bar{\omega}(T) = 1$ and `transb T`, both Booleans.)

Everything this statement needs^a

- Digraphs and arcs ($u \rightarrow v$) (§2.1)
- Tournaments (irreflexive + total) (§2.5)
- Transitive tournaments (§2.6)
- Vertex orders as permutations (`ltp`, `realize`) (§2.8)
- The backedge graph of an ordered tournament (§2.9)
- The tournament clique number `omegabar` (§2.10)
- plus the standard finite-mathematics vocabulary of the Glossary (Appendix A)

^aThis list is *generated* from the build: a script computes every constant the formal statement references, transitively through library definitions, and CI fails if any of them lacks an entry in the Dictionary (`scripts/statement_closure.py`).

6.2 The substitution lower bound

Theorem `omegabar_lexprod_ge` :
 $\bar{\omega}(S) + \bar{\omega}(H) \leq \bar{\omega}(\text{lexprod_tournament } S \ H) + 1$.

[theories/invariants_advanced/substitution.v:168]

Decoded. $\bar{\omega}(S) + \bar{\omega}(H) \leq \bar{\omega}(S[H]) + 1$ for any tournaments S, H (quoted inside a section fixing nonempty S, H): substitution composes criticality levels. This is what makes the tower $AC_n \rightarrow AC_n[C_3] \rightarrow AC_n[AC_n]$ work.

Everything this statement needs^a

- Digraphs and arcs ($u \rightarrow v$) (§2.1)
- Tournaments (irreflexive + total) (§2.5)
- Vertex orders as permutations (ltp, realize) (§2.8)
- The backedge graph of an ordered tournament (§2.9)
- The tournament clique number ω (§2.10)
- Lexicographic substitution $S[H]$ (§2.16)
- plus the standard finite-mathematics vocabulary of the Glossary (Appendix A)

^aThis list is *generated* from the build: a script computes every constant the formal statement references, transitively through library definitions, and CI fails if any of them lacks an entry in the Dictionary (scripts/statement_closure.py).

6.3 Vertex-transitive tournaments: one deletion decides criticality

```
Theorem vt_kcritical (k : nat) (v0 : T) :
  vertex_transitiveb (T : diGraphType) ->
  kcritical k T = ( $\bar{\omega}(T) == k$ ) && ( $\bar{\omega}(\text{del\_tournament } v0) == k.-1$ ).
```

[theories/invariants_advanced/transitive.v:57]

```
Theorem omegabar_del_vt :
  vertex_transitiveb (T : diGraphType) ->
  forall u v : T,  $\bar{\omega}(\text{del\_tournament } u) = \bar{\omega}(\text{del\_tournament } v)$ .
```

[theories/invariants_advanced/transitive.v:47]

Decoded. In a vertex-transitive tournament all single-vertex deletions have the same $\bar{\omega}$ (second statement), so k -criticality reduces to the value of $\bar{\omega}(T)$ and of one deletion $\bar{\omega}(T - v_0)$ (first statement, a Boolean equivalence).

Everything this statement needs^a

- Digraphs and arcs ($u \rightarrow v$) (§2.1)
- Tournaments (irreflexive + total) (§2.5)
- Subtournaments and vertex deletion (§2.12)
- Vertex orders as permutations (ltp, realize) (§2.8)
- The backedge graph of an ordered tournament (§2.9)
- The tournament clique number ω (§2.10)
- k - ω -critical tournaments (§2.11)
- Automorphisms of a digraph (§2.14)
- Vertex-transitivity (§2.15)
- plus the standard finite-mathematics vocabulary of the Glossary (Appendix A)

^aThis list is *generated* from the build: a script computes every constant the formal statement references, transitively through library definitions, and CI fails if any of them lacks an entry in the Dictionary (scripts/statement_closure.py).

6.4 Domination bounds the clique number

Theorem `domnum_le_omegabars` : `domnum <= ω(T)`.

[theories/invariants/domination.v:114]

Decoded. $\text{dom}(T) \leq \bar{\omega}(T)$ for every tournament: a minimum backedge-clique under an optimal order dominates (Section 2.13). This is the standard lower-bound tool for $\bar{\omega}$.

Everything this statement needs^a

- Digraphs and arcs ($u \rightarrow v$) (§2.1)
- Tournaments (irreflexive + total) (§2.5)
- Vertex orders as permutations (`ltp`, `realize`) (§2.8)
- The backedge graph of an ordered tournament (§2.9)
- The tournament clique number `omegabars` (§2.10)
- Directed domination (§2.13)
- plus the standard finite-mathematics vocabulary of the Glossary (Appendix A)

^aThis list is *generated* from the build: a script computes every constant the formal statement references, transitively through library definitions, and CI fails if any of them lacks an entry in the Dictionary (`scripts/statement_closure.py`).

6.5 C_3 is the unique 2-critical tournament

Theorem `kcritical2_uniq` : `dgiso (C3 : diGraphType) T`.

[theories/invariants/critical.v:124]

Decoded. Every 2- $\bar{\omega}$ -critical tournament is isomorphic (Section 2.2) to the directed triangle (Section 2.7): the base of the criticality hierarchy is unique.

Everything this statement needs^a

- Digraphs and arcs ($u \rightarrow v$) (§2.1)
- Digraph isomorphism (§2.2)
- The directed triangle `C3` (§2.7)
- plus the standard finite-mathematics vocabulary of the Glossary (Appendix A)

^aThis list is *generated* from the build: a script computes every constant the formal statement references, transitively through library definitions, and CI fails if any of them lacks an entry in the Dictionary (`scripts/statement_closure.py`).

6.6 Proper subtournaments of critical tournaments

Lemma `kcritical_proper_sub` (`k : nat`) (`T : tournament`) (`S : {set T}`)
:
`kcritical k T -> S != [set: T] -> (ω(sub_tournament S) <= k.-1)%N`.

[theories/invariants/critical.v:46]

Decoded. If T is $k\bar{\omega}$ -critical and $S \subsetneq V(T)$, then the induced subtournament on S has $\bar{\omega} \leq k - 1$: criticality leaves no proper witness inside. This single lemma is what refutes Question 5.9 at every k (Chapter 3).

Everything this statement needs^a

- Digraphs and arcs ($u \rightarrow v$) (§2.1)
- Tournaments (irreflexive + total) (§2.5)
- Subtournaments and vertex deletion (§2.12)
- Vertex orders as permutations (ltp, realize) (§2.8)
- The backedge graph of an ordered tournament (§2.9)
- The tournament clique number ω_{gabar} (§2.10)
- k - ω_{gabar} -critical tournaments (§2.11)
- plus the standard finite-mathematics vocabulary of the Glossary (Appendix A)

^aThis list is *generated* from the build: a script computes every constant the formal statement references, transitively through library definitions, and CI fails if any of them lacks an entry in the Dictionary (`scripts/statement_closure.py`).

Appendix A

Glossary of MathComp / graph-theory primitives

The external vocabulary the quoted statements draw on. Each entry is standard library material (MathComp 2.5 / `coq-graph-theory` 0.9.7), battle-tested far beyond this project; the entries below give the reading, not a re-development.

finType A type with a (computable) finite enumeration. All vertex types in this document are finite.

#|T|, #|A| Cardinality of a finite type / of a set.

{set T} Subsets of the finite type T ; $x \in A$ membership; **[set: T]** the full set; **[set~ v]** the complement of $\{v\}$; **A != B** Boolean disequality of sets.

{perm T} Permutations of T (the symmetric group); **enum_rank x** the position of x in the canonical enumeration.

'Z_n The ring $\mathbb{Z}/n\mathbb{Z}$ (for the $n \geq 2$ in use here); **val z** its representative in $\{0, \dots, n-1\}$; arithmetic $+$, $-$ is modular.

rel T Boolean binary relations on T .

b = true, is_true A Boolean used as a statement means “it computes to **true**” (Chapter 1).

==, != Decidable equality / disequality (provably equivalent to $=$ on these types).

(+) Exclusive or of Booleans.

[forall x : T, P], [exists x, P] Boolean quantifiers over finite types.

reflect P b “The Boolean b is equivalent to the proposition P ”.

n.+1, n.-1, n.*2, n./2 Successor, truncated predecessor, doubling, truncated halving on **nat**; **maxn** maximum.

path e x s, uniq s, size s MathComp sequences: **path** chains the relation e along $x :: s$; **uniq** no repetition; **size** length.

connect e x y Reflexive-transitive closure: a directed e -walk from x to y exists.

sgraph `coq-graph-theory`’s finite simple graphs; $u \dashv\vdash v$ adjacency (symmetric, irreflexive).

cliques, omega `coq-graph-theory`'s cliques of an `sgraph` and its clique number ω (the maximum size of a set of pairwise adjacent vertices). $\bar{\omega}$ (Section 2.10) is built on these — the one place this library leans on its undirected companion, by design.

[arg min_(`i < i0`) `F`] `MathComp`'s minimiser of `F` over a finite type, with default `i0`.

Sub, val, {x | P x} Dependent pairs: an element together with a proof; `val` forgets the proof (the underlying element).

Appendix B

The full catalog (auto-generated)

Every named declaration in the library’s build chain, with its source location. Entries shown in the narrative chapters are marked ★. Everything else is internal proof machinery: it affects *whether* the theorems hold (the kernel checked that), never *what* they say.

theories/foundations/prelude.v

`prelude_classical` (lemma) [prelude.v:29](#) — Classical logic is in scope (derived from `boolp`’s axioms).
`prelude_set` (lemma) [prelude.v:33](#) — The classical set layer is in scope.
`prelude_ssr` (lemma) [prelude.v:37](#) — MathComp’s small-scale reflection is in scope.
`card_classes` (lemma) [prelude.v:47](#) — ** General counting Partition counting by a bounded nat-valued class function: any finite set splits as the sum of its class sizes.
`card_classes_inj` (lemma) [prelude.v:68](#) — When the class function is injective on K (one element per class at most — e.g.

theories/foundations/interop_graph_theory.v

`clique_set1` (lemma) [interop_graph_theory.v:30](#)
`set1_cliques` (lemma) [interop_graph_theory.v:33](#)
`omega_ge1` (lemma) [interop_graph_theory.v:36](#)
`omega_le_card` (lemma) [interop_graph_theory.v:41](#)
`omega_le1` (lemma) [interop_graph_theory.v:47](#) — An edgeless subset has clique number at most 1.
`omega_ge2` (lemma) [interop_graph_theory.v:56](#) — Conversely, a single edge pushes ω to at least 2.
`omega_hom` (lemma) [interop_graph_theory.v:69](#) — ω is monotone along injective edge-preserving maps (used to compare backedge graphs of a sub-tournament and its host).
`K2_rel` (definition) [interop_graph_theory.v:88](#) — ** Smoke check — ω of a tiny hand-built `sgraph` The original M0 exit criterion: graph-theory’s clique number is usable on a concrete graph.
`K2_sym` (fact) [interop_graph_theory.v:89](#)
`K2_irrefl` (fact) [interop_graph_theory.v:91](#)
`K2` (definition) [interop_graph_theory.v:93](#)
`omega_K2` (lemma) [interop_graph_theory.v:95](#)

theories/core/digraph.v

`to_GT` (definition) [digraph.v:56](#) — ** Projection into graph-theory’s record world (D7 glue) `diGraph` is graph-theory’s notation for its `relType` record (re-exported by the interop file); `RelType` is its constructor — its `DiGraph` alias is shadowed by our structure module above.

converse (definition) [digraph.v:60](#) — ** Converse digraph (type alias, mathcomp T^d-style)
converse_arcE (lemma) [digraph.v:66](#)
sub_arcE (lemma) [digraph.v:78](#)
induced_digraph (definition) [digraph.v:86](#) — Object-level versions, convenient in statements (the : diGraphType cast goes through Rocq’s reverse-coercion via the canonical instances).
del_vertex (definition) [digraph.v:89](#)
dgiso (definition) [digraph.v:97](#) — ** Digraph isomorphism (Named **dgiso**: graph-theory’s **diso** — re-exported through the interop — is the *simple-graph* iso
dgiso_refl (lemma) [digraph.v:100](#)
dgiso_sym (lemma) [digraph.v:103](#)
dgiso_trans (lemma) [digraph.v:109](#)
dgiso_card (lemma) [digraph.v:117](#)

theories/core/oriented.v

outdeg (definition) [oriented.v:47](#)
outdeg_in (definition) [oriented.v:51](#) — Out-degree into a fixed vertex subset — the induced out-degree when $v \setminus \text{in } A$.
outdeg_inT (lemma) [oriented.v:53](#)
outdeg_in_le (lemma) [oriented.v:56](#)
outdeg_in_mono (lemma) [oriented.v:61](#)
outdeg_in_sumE (lemma) [oriented.v:67](#)
outdeg_induced (lemma) [oriented.v:76](#) — The induced subgraph on A has the inner out-degrees.
arc_pair_bound (lemma) [oriented.v:92](#)
oriented_arcs_bound (lemma) [oriented.v:100](#) — O1, counting form: twice the arc count of DA is $\leq |A|(|A|-1)$.
oriented_avg_bound (lemma) [oriented.v:119](#) — O1(a): some vertex of a nonempty A has inner out-degree $\leq (|A|-1)/2$.
oriented_mindeg_card (lemma) [oriented.v:144](#) — O1(b): if all inner out-degrees are at least k , then $|A| \geq 2k+1$.
oriented_card (lemma) [oriented.v:159](#) — O1(c): a nonempty oriented digraph with min out-degree $\geq k$ has $\geq 2k+1$ vertices.
sub_oarc_irrefl (fact) [oriented.v:175](#)
sub_oarc_asymm (fact) [oriented.v:178](#)
induced_oriented (definition) [oriented.v:187](#) — Object-level version for statements.
outsel (definition) [oriented.v:195](#) — The alias takes f as a REAL parameter (M2 lesson: a type alias must use its parameters, or section discharge drops them and all selections collapse onto one type).
outsel_arcE (lemma) [oriented.v:204](#)
outsel_arc_sub (lemma) [oriented.v:208](#)
outsel_irrefl (fact) [oriented.v:219](#)
outsel_asymm (fact) [oriented.v:222](#)
ksel (definition) [oriented.v:237](#)
ksel_sub (lemma) [oriented.v:239](#)
ksel_card (lemma) [oriented.v:245](#)
outsel_ksel_outdeg (lemma) [oriented.v:254](#) — O2’s exit: in **outsel** **ksel**, every out-degree is exactly k .

theories/core/dipath.v

dipath (definition) [dipath.v:36](#) — ** Directed simple paths

dipath_path (lemma) [dipath.v:38](#)

dipath_uniq (lemma) [dipath.v:41](#)

dipath_nil (lemma) [dipath.v:44](#)

dipath_rcons (lemma) [dipath.v:47](#)

cat_dipath (lemma) [dipath.v:56](#)

cat_dipath_cont (lemma) [dipath.v:67](#) — Continuation form: append a path that starts AT the endpoint.

dipath_cons (lemma) [dipath.v:83](#)

dipath_drop (lemma) [dipath.v:89](#)

last_take (lemma) [dipath.v:105](#)

last_drop (lemma) [dipath.v:108](#)

take_path_last (lemma) [dipath.v:117](#) — Endpoint of a prefix, on the (x :: s) indexing.

dipath_take (lemma) [dipath.v:124](#)

dipath_arc_nth (lemma) [dipath.v:132](#) — The i-th vertex of the path (x, s), i ranging over 0..size s.

dipath_size (lemma) [dipath.v:136](#)

has_dipath (definition) [dipath.v:144](#) — ** The longest-path length $\ell(D)$

has_dipathP (lemma) [dipath.v:146](#)

ell (definition) [dipath.v:155](#)

ell_max (lemma) [dipath.v:157](#)

ellP (lemma) [dipath.v:166](#)

maxpath_endclosure (lemma) [dipath.v:178](#) — ** K-A: out-neighbours of the endpoint of a maximum path lie on it

endmax (definition) [dipath.v:188](#) — ** End-maximal paths and K-Ext

endmax_closure (lemma) [dipath.v:191](#)

endmax_dipath (lemma) [dipath.v:195](#)

endmax_ex (lemma) [dipath.v:199](#) — K-Ext: every vertex starts some end-maximal path.

dicycle (definition) [dipath.v:223](#) — ** Directed cycles as seqs

dicycle_rot (lemma) [dipath.v:225](#)

dicycle_next (lemma) [dipath.v:229](#) — The closing/cyclic arcs: every cycle vertex beats its **next**.

dicycle_prev (lemma) [dipath.v:232](#)

dicycle_unroll (lemma) [dipath.v:237](#) — Unrolling: a cycle yields a path from any of its vertices through all of it, ending at the predecessor (with the closing arc back).

dicycle_suffix (lemma) [dipath.v:262](#) — Cycle from a path suffix plus a back-arc from the endpoint.

prev_head (lemma) [dipath.v:290](#) — **prev** of the head of a uniq seq is its last element (eqType-level helper for cycle predecessor reasoning).

dipath_map (lemma) [dipath.v:304](#) — ** M- ℓ : ℓ is monotone under injective arc-preserving embeddings

ell_embed (lemma) [dipath.v:314](#)

ell_outsel (lemma) [dipath.v:330](#) — The two instances used by the reduction R: arc-sub-relations and induced subgraphs.

ell_induced (lemma) [dipath.v:337](#)

theories/core/tournament.v

`asymm` (fact) [tournament.v:47](#)
`arcxx` (lemma) [tournament.v:65](#)
`arc_neq` (lemma) [tournament.v:68](#)
`arc_asym` (lemma) [tournament.v:71](#)
`arcNarc` (lemma) [tournament.v:78](#) — On distinct vertices, the two arc directions are complementary.
`arc_or` (lemma) [tournament.v:83](#)
`arc_xorE` (lemma) [tournament.v:87](#) — Since both directions never hold together, xor and or coincide.
`N_out` (definition) [tournament.v:95](#) — ** Neighbourhoods
`N_in` (definition) [tournament.v:96](#)
`N_outE` (lemma) [tournament.v:98](#)
`N_inE` (lemma) [tournament.v:99](#)
`N_out_in_partition` (lemma) [tournament.v:101](#)
`transb` (definition) [tournament.v:112](#) — ** Decidable transitivity and the 3-cycle dichotomy
`transbP` (lemma) [tournament.v:115](#)
`ntransbP` (lemma) [tournament.v:124](#) — A tournament fails transitivity exactly when it has a directed triangle.
`ntransb_card` (lemma) [tournament.v:139](#) — An intransitive tournament has at least 3 vertices.
`card_le2_transb` (lemma) [tournament.v:148](#)
`sub_arc_total` (fact) [tournament.v:160](#) — The subtype already carries the `Oriented` structure (`core/oriented.v`); only totality is added here.
`sub_tournament` (definition) [tournament.v:171](#) — Object-level versions for use in statements.
`del_tournament` (definition) [tournament.v:174](#)
`C3` (definition) [tournament.v:183](#)
`C3_irrefl` (fact) [tournament.v:188](#)
`C3_total` (fact) [tournament.v:191](#)
`arcC3E` (lemma) [tournament.v:196](#)
`card_C3` (lemma) [tournament.v:199](#)
`C3_Ntransb` (lemma) [tournament.v:203](#) — C3 is the directed triangle: it is **not** transitive.
`TT` (definition) [tournament.v:215](#)
`TT_irrefl` (fact) [tournament.v:220](#)
`TT_total` (fact) [tournament.v:223](#)
`arcTTE` (lemma) [tournament.v:232](#)
`card_TT` (lemma) [tournament.v:235](#)
`TT_transb` (lemma) [tournament.v:238](#)

theories/core/order.v

`ltp` (definition) [order.v:39](#)
`ltp_irrefl` (lemma) [order.v:41](#)
`ltp_trans` (lemma) [order.v:44](#)
`ltp_total` (lemma) [order.v:47](#)
`ltp_asym` (lemma) [order.v:53](#)

`le_r_total` (fact) [order.v:66](#)
`le_r_trans` (fact) [order.v:73](#)
`mem_s` (fact) [order.v:82](#)
`size_s` (fact) [order.v:83](#)
`sorted_s` (fact) [order.v:84](#)
`rank_lt` (fact) [order.v:85](#)
`rfun` (definition) [order.v:87](#)
`rfun_inj` (fact) [order.v:89](#)
`realize` (definition) [order.v:96](#)
`ltp_realizeE` (lemma) [order.v:98](#)
`ltp_pullback` (lemma) [order.v:119](#) — Transport an order along an injective map: the pulled-back order on U is again realized by a permutation.
`backedge_rel` (definition) [order.v:136](#)
`backedge_sym` (fact) [order.v:139](#)
`backedge_irrefl` (fact) [order.v:142](#)
`backedge` (definition) [order.v:145](#)
`backedgeE` (lemma) [order.v:147](#)
`backedge_neq` (lemma) [order.v:153](#) — An edge of the backedge graph is in particular an arc-disagreement, so its endpoints are distinct.
`backedge_arc_forward` (lemma) [order.v:163](#) — If the order linearizes the arcs (no backward arc at all), the backedge graph is edgeless.

theories/invariants/omegabar.v

`omegab_at` (definition) [omegabar.v:29](#) — ** Definition
`omegabar` (definition) [omegabar.v:32](#)
`omegabar_min` (lemma) [omegabar.v:42](#)
`omegabar_witness` (lemma) [omegabar.v:45](#)
`omegabar_gt0` (lemma) [omegabar.v:48](#)
`omegab_at_le1` (lemma) [omegabar.v:56](#) — ** $\bar{\omega} = 1$ characterizes transitivity
`omegabar_le1` (lemma) [omegabar.v:63](#)
★ `omegabar_transb` (lemma) [omegabar.v:74](#)
`omegabar_embed` (lemma) [omegabar.v:108](#) — ** Monotonicity under arc-preserving embeddings Any injective map that reflects arcs both ways pushes $\bar{\omega}$ up: the witness order on the big tournament pulls back along the embedding (`ltp_pullback`) and the backedge graphs correspond edge-for-edge.
`omegabar_dgiso` (lemma) [omegabar.v:126](#) — $\bar{\omega}$ is invariant under digraph isomorphism.
`omegabar_sub` (lemma) [omegabar.v:137](#) — Sub-tournaments and vertex deletion.
`omegabar_del` (lemma) [omegabar.v:143](#)
`omegabar_nil` (lemma) [omegabar.v:148](#) — $\bar{\omega}$ on degenerate and tiny tournaments.
`omegabar_card_le2` (lemma) [omegabar.v:156](#)
`omegabar_TT` (lemma) [omegabar.v:164](#) — ** The two reference values
`omegabar_C3` (lemma) [omegabar.v:169](#)

theories/invariants/strong.v

strongb (definition) [strong.v:37](#)
strongP (lemma) [strong.v:39](#)
arc_closed (definition) [strong.v:44](#) — ** S1: forward-closed sets and the sink trick
closed_connect (lemma) [strong.v:46](#)
rset (definition) [strong.v:54](#)
rset_id (lemma) [strong.v:56](#)
rset_closed (lemma) [strong.v:59](#)
rset_trans (lemma) [strong.v:65](#)
sink_exists (lemma) [strong.v:73](#) — The sink trick: a reachable set of minimum size is closed and strongly connected inside.
outdeg_closed (lemma) [strong.v:91](#) — Closed sets keep out-degrees in the induced subgraph.
connect_induced_closed (lemma) [strong.v:100](#) — Connectivity relativizes to closed sets.
connect_cross (lemma) [strong.v:116](#) — ** S2: cut crossing
maxpath_no_loopback (lemma) [strong.v:129](#) — ** K-a1: no loopback arc at a maximum path's endpoint
disjoint_cycles_path (lemma) [strong.v:161](#) — ** K-10: disjoint cycles force long paths
strongb_induced_closed (lemma) [strong.v:255](#) — Strongness of the induced subgraph on a closed, internally connected set.
reduction (theorem) [strong.v:267](#) — ** R: the composed out-regular reduction (dossier item R)

theories/invariants/critical.v

kcritical (definition) [critical.v:21](#)
kcriticalP (lemma) [critical.v:24](#)
card_del (lemma) [critical.v:34](#) — Deleting a vertex removes exactly one vertex.
★ **kcritical_proper_sub** (lemma) [critical.v:46](#) — ** Proper subtournaments of critical tournaments
In a $k\text{-}\bar{\omega}$ -critical tournament every *proper* subtournament has $\bar{\omega} \leq k - 1$: it omits some vertex, hence embeds into that vertex's deletion (the Question-5.9-failure mechanism, stated once; G1 of docs/k34_dossier.md).
C3_kcritical2 (lemma) [critical.v:64](#) — ** C3 is $2\text{-}\bar{\omega}$ -critical
kcritical2_card3 (lemma) [critical.v:95](#) — A 2-critical tournament has no 4th vertex: deleting it would leave the triangle, contradicting $\bar{\omega}(T - x) = 1$.
★ **kcritical2_uniq** (theorem) [critical.v:124](#) — The explicit isomorphism $C3 \cong T$ sending 0,1,2 to the triangle.

theories/invariants/domination.v

dominatesb (definition) [domination.v:28](#)
dominatesbP (lemma) [domination.v:31](#)
dominatesb_setT (lemma) [domination.v:43](#)
domnum (definition) [domination.v:46](#)
domnum_min (lemma) [domination.v:48](#)
domnum_witness (lemma) [domination.v:54](#)

greedy_clique_dom (lemma) [domination.v:63](#) — The greedy chain: inside any A there is a subset that dominates A and is a clique of the backedge graph of p (the $\prec$ -minimum first, every later pick beating — and sitting $\prec$ -after — all earlier ones).

★ **domnum_le_omegabar** (theorem) [domination.v:114](#) — Paper Property 3.2 — the lower-bound engine for $\bar{\omega}$.

theories/constructions/automorphism.v

autb (definition) [automorphism.v:25](#) — p is an automorphism: it preserves arcs (hence also non-arcs).

autbP (lemma) [automorphism.v:28](#)

dgaut (definition) [automorphism.v:35](#)

dgautE (lemma) [automorphism.v:37](#)

dgaut1 (lemma) [automorphism.v:40](#)

dgautM (lemma) [automorphism.v:43](#)

dgaut_group_set (lemma) [automorphism.v:49](#)

vertex_transitiveb (definition) [automorphism.v:55](#) — Vertex-transitivity.

vertex_transitivebP (lemma) [automorphism.v:59](#)

theories/constructions/product.v

lexprod (definition) [product.v:25](#)

lexprod_arcE (lemma) [product.v:31](#)

card_lexprod (lemma) [product.v:35](#)

lexprod_irrefl (fact) [product.v:45](#)

lexprod_total (fact) [product.v:50](#)

lexprod_tournament (definition) [product.v:65](#) — Object-level version for statements.

lexprod_vertex_transitive (lemma) [product.v:73](#)

theories/constructions/cayley.v

cayley (definition) [cayley.v:30](#) — The carrier is the group; the (otherwise unused) connection set A is a real parameter of the type alias so that distinct connection sets carry distinct canonical instances.

cayley_arcE (lemma) [cayley.v:39](#)

cayley_irreflP (lemma) [cayley.v:44](#) — ** Tournament characterization

cayley_totalP (lemma) [cayley.v:51](#)

translation (definition) [cayley.v:66](#) — ** Translations and vertex-transitivity

translationE (lemma) [cayley.v:68](#)

translation_aut (lemma) [cayley.v:71](#)

cayley_vertex_transitive (lemma) [cayley.v:78](#)

theories/constructions/circulant.v

Zp_mulgE (lemma) [circulant.v:36](#)

Zp_invgeE (lemma) [circulant.v:39](#)

Zp_1gE (lemma) [circulant.v:42](#)

val_Zp_opp (lemma) [circulant.v:45](#)

circulant_arcE (lemma) [circulant.v:50](#) — Circulant arc characterization: $x \rightarrow y$ iff the difference is a connection element.

ACset (definition) [circulant.v:63](#)

ACset_cond (lemma) [circulant.v:72](#) — The connection set hits each pair $\{z, -z\}$ ($z \neq 0$) exactly once — this is the residue-arithmetic heart of "AC is a tournament".

AC_irrefl (fact) [circulant.v:109](#) — AC is a tournament.

AC_total (fact) [circulant.v:115](#)

AC (definition) [circulant.v:124](#)

AC_arcE (lemma) [circulant.v:126](#)

★ **card_AC** (lemma) [circulant.v:129](#)

★ **AC_vertex_transitive** (lemma) [circulant.v:134](#) — AC is vertex-transitive (as any Cayley digraph: translations act transitively) — the M2 exit fact feeding the M3 criticality reduction.

C3_vertex_transitive (lemma) [circulant.v:146](#) — ** C is vertex-transitive C3's arc relation $v == u + 1$ over $\mathbb{Z}_3$ is translation-invariant, so the translations $x \mapsto x + t$ are automorphisms and act transitively (the Cayley-translation argument in miniature; G3 of docs/k34_dossier.md — feeds the $k = 4$ criticality reduction).

theories/invariants_advanced/transitive.v

del_aut_iso (lemma) [transitive.v:27](#) — An automorphism sending u to $g \ u$ restricts to an isomorphism between the vertex-deleted sub-tournaments, so $\bar{\omega}$ agrees on them.

★ **omegabar_del_vt** (theorem) [transitive.v:47](#) — The marquee theorem: on a vertex-transitive tournament, $\bar{\omega}$ after deletion is the same whichever vertex is deleted.

★ **vt_kcritical** (theorem) [transitive.v:57](#) — Hence $k\bar{\omega}$ -criticality reduces to a single deletion.

AC_del_uniform (lemma) [transitive.v:70](#) — Demo: in the circulant tournament AC all single-vertex deletions have the same $\bar{\omega}$ — its criticality will need only the deletion at 0 (M4).

theories/invariants_advanced/substitution.v

hmin (definition) [substitution.v:46](#) — The $\prec$ -minimum of a block, and its position.

posmin (definition) [substitution.v:47](#)

posmin_le (lemma) [substitution.v:49](#)

pos_inj (lemma) [substitution.v:52](#)

posmin_neq (lemma) [substitution.v:55](#)

rS_irr (fact) [substitution.v:63](#)

rS_trans (fact) [substitution.v:64](#)

rS_total (fact) [substitution.v:65](#)

rH_irr (fact) [substitution.v:73](#)

rH_trans (fact) [substitution.v:75](#)

rH_total (fact) [substitution.v:77](#)

cross_edgeE (lemma) [substitution.v:88](#) — Edge correspondences between **backedge** p and the auxiliary graphs.

block_edgeE (lemma) [substitution.v:97](#)

omegab_at_lexprod_ge (lemma) [substitution.v:103](#) — The bound, for this arbitrary order.

★ **omegabar_lexprod_ge** (theorem) [substitution.v:168](#) — The substitution lower bound: $\bar{\omega}(\text{SH}) \geq \bar{\omega}(S) + \bar{\omega}(H) - 1$.

theories/applications/k5/acn_arc_facts.v

`val_addE` (lemma) [acn_arc_facts.v:40](#) — ** Values of sums, opposites, differences in $\mathbb{Z}_n$
`val_oppE` (lemma) [acn_arc_facts.v:43](#)
`val_sub_le` (lemma) [acn_arc_facts.v:46](#)
`val_sub_gt` (lemma) [acn_arc_facts.v:60](#)
`AC_mem_val` (lemma) [acn_arc_facts.v:71](#) — ** Connection-set membership by value
`AC_arc_lt` (lemma) [acn_arc_facts.v:77](#) — ** Gap characterizations under the value order
`AC_arc_gt` (lemma) [acn_arc_facts.v:84](#)
`AC_band_arc` (lemma) [acn_arc_facts.v:104](#) — Within a band ($\text{gap} < m$), arcs follow the value order
— the working form of paper (iii).
`AC_mem_Hi` (lemma) [acn_arc_facts.v:110](#) — ** The band facts — paper (i) and (ii)
`AC_mem_Hi_opp` (lemma) [acn_arc_facts.v:117](#)
`AC_mem_Lo` (lemma) [acn_arc_facts.v:138](#)
`AC_mem_Lo_opp` (lemma) [acn_arc_facts.v:147](#)

theories/applications/k5/acn_base.v

`bucket_bound` (lemma) [acn_base.v:36](#) — ** A pigeonhole principle: sparse values in a bounded range
`rid_irr` (fact) [acn_base.v:70](#)
`rid_trans` (fact) [acn_base.v:71](#)
`rid_total` (fact) [acn_base.v:72](#)
`backedge_qid_dist` (lemma) [acn_base.v:79](#) — Every backedge of the value order spans a gap of at least m .
`omegab_at_qid_le3` (lemma) [acn_base.v:94](#) — ** Upper bound: $\bar{\omega}(\text{AC}) \leq 3$
`omegabar_AC_le3` (lemma) [acn_base.v:106](#)
`r0_irr` (fact) [acn_base.v:115](#)
`r0_trans` (fact) [acn_base.v:116](#)
`r0_total` (fact) [acn_base.v:117](#)
`omegab_at_q0_le2` (lemma) [acn_base.v:123](#)
`omegabar_ACdel_le2` (lemma) [acn_base.v:147](#)
`mem0A` (fact) [acn_base.v:155](#)
`oppA_disjoint` (fact) [acn_base.v:158](#)
`cardA` (fact) [acn_base.v:166](#)
`cardN0` (fact) [acn_base.v:192](#)
`mem_shift` (fact) [acn_base.v:198](#)
`shift_comp` (fact) [acn_base.v:204](#)
`card_shift` (fact) [acn_base.v:207](#)
`shiftI` (fact) [acn_base.v:210](#)
`shift0` (fact) [acn_base.v:214](#)
`autocorr_sym` (fact) [acn_base.v:217](#)
`val1` (fact) [acn_base.v:224](#)
`val_zeta` (fact) [acn_base.v:229](#)
`N0_val_in` (fact) [acn_base.v:235](#)

NO_0 (fact) [acn_base.v:244](#)

autocorr_lo (lemma) [acn_base.v:249](#) — The autocorrelation lemma, low half: for $0 < \text{val } t \leq m$, the sets N and $N + t$ share at least two elements ($m \geq 3$).

autocorr2 (lemma) [acn_base.v:310](#) — The autocorrelation lemma: every nonzero shift overlaps N in ≥ 2 points.

domnum_AC_ge3 (lemma) [acn_base.v:326](#) — $\text{dom}(AC) \geq 3$: one or two translates of N cannot cover $\mathbb{Z}_n$.

★ **omegabar_AC** (theorem) [acn_base.v:374](#) — $\bar{\omega}(AC) = 3$

ACdel_Ntransb (lemma) [acn_base.v:386](#)

omegabar_ACdel0 (lemma) [acn_base.v:412](#) — $\bar{\omega}(AC - v) = 2$ and 3-criticality

★ **omegabar_AC_del** (theorem) [acn_base.v:423](#)

★ **AC_kcritical3** (theorem) [acn_base.v:431](#)

theories/applications/acn_bands.v

radix_ltA (lemma) [acn_bands.v:34](#) — $\bar{\omega}$ Radix lemmas for lexicographic keys

radix_lt_inv (lemma) [acn_bands.v:43](#)

radix_eq_inv (lemma) [acn_bands.v:53](#)

band (definition) [acn_bands.v:72](#) — $\bar{\omega}$ Bands

band1P (lemma) [acn_bands.v:75](#)

band2P (lemma) [acn_bands.v:81](#)

band3P (lemma) [acn_bands.v:87](#)

band_ge1 (lemma) [acn_bands.v:92](#)

band_le3 (lemma) [acn_bands.v:95](#)

band12P (lemma) [acn_bands.v:99](#) — Two band dichotomies.

AC_wrapF (lemma) [acn_bands.v:114](#) — A backward residue over a gap below m is never a connection element.

band_gap (lemma) [acn_bands.v:128](#) — Within a (nonzero) band, value gaps stay below m .

theories/applications/k5/k5_lower.v

ACm_pos (fact) [k5_lower.v:40](#)

ACdel_pos (fact) [k5_lower.v:43](#)

omegabar_T_ge5 (theorem) [k5_lower.v:48](#) — $\bar{\omega}(T) \geq 5$

emb_mem (fact) [k5_lower.v:62](#)

f_inj (fact) [k5_lower.v:71](#)

f_arc (fact) [k5_lower.v:77](#)

omegabar_Tdel_ge4 (theorem) [k5_lower.v:83](#)

theories/applications/k5/in_neighbourhood.v

gval_bounds (lemma) [in_neighbourhood.v:32](#) — Connection-set elements have value in $1, m+1 \setminus \{m\}$.

H17_xrange (lemma) [in_neighbourhood.v:42](#) — An in-neighbour of an H_i vertex sits in the window $v_x - m - 1, v_x - 1$.

H17_dichot (lemma) [in_neighbourhood.v:66](#) — An in-neighbour of a Lo vertex is either below it or $\geq m$ positions up.

H17_side (lemma) [in_neighbourhood.v:83](#) — H17: the common in-neighbourhood lies in the band determined by $x - y$.

H17_no_mixed (lemma) [in_neighbourhood.v:107](#) — The working corollary: an Hi vertex and a Lo vertex can never both beat both an Hi vertex x and a Lo vertex y .

theories/applications/k5/cells.v

cidx (definition) [cells.v:45](#) — ** Cells and the key

cidx_decode (lemma) [cells.v:47](#)

cidx_le8 (lemma) [cells.v:56](#)

key (definition) [cells.v:65](#)

key_inj (lemma) [cells.v:67](#)

cidx_mono (lemma) [cells.v:75](#)

key_samecell (lemma) [cells.v:81](#)

rk (definition) [cells.v:94](#) — ** The realized key order

rk_irr (fact) [cells.v:95](#)

rk_trans (fact) [cells.v:96](#)

rk_total (fact) [cells.v:97](#)

qk (definition) [cells.v:103](#)

qkE (lemma) [cells.v:105](#)

beat_key (lemma) [cells.v:115](#)

beat_blocks (lemma) [cells.v:126](#) — Between different blocks, the beaten block-difference is a connection element; inside a block the inner difference is.

beat_inner (lemma) [cells.v:136](#)

cidx_inj_clique (lemma) [cells.v:148](#) — ** The cell Lemma: at most one clique vertex per cell

occ (definition) [cells.v:190](#) — ** Occupancy and the cardinality bridge

occP (lemma) [cells.v:192](#)

card_clique_cidx (lemma) [cells.v:199](#)

theories/applications/k5/obstructions.v

obstrb (definition) [obstructions.v:30](#) — The 20-disjunct obstruction pattern over the 8 cell-occupancy bits.

nat_n_split (lemma) [obstructions.v:46](#)

mem_sub_Lo_Hi1 (lemma) [obstructions.v:55](#) — ** Membership computations for cross-band differences

mem_sub_Hi1_Lo (lemma) [obstructions.v:72](#)

mem_sub_Hi_m (lemma) [obstructions.v:90](#)

mem_sub_m_Hi (lemma) [obstructions.v:107](#)

opp_arcs_contra (lemma) [obstructions.v:133](#) — Opposite residues cannot both be connection elements.

repA_band (lemma) [obstructions.v:149](#)

rep_Hi (lemma) [obstructions.v:155](#)

rep_Lo (lemma) [obstructions.v:162](#)

rep_Z (lemma) [obstructions.v:169](#)

beatc (lemma) [obstructions.v:177](#)

bands_neq (lemma) [obstructions.v:187](#)

triple_A (lemma) [obstructions.v:200](#) — ** The seven core obstruction shapes *) (* (X, zero, X) triples — paper sets 1–8

triple_B (lemma) [obstructions.v:261](#) — ** The seven core obstruction shapes *) (* (X, zero, X) triples — paper sets 1–8 *) Lemma triple_A (u v w : backedged (qk m')) (i j k : nat) : u \in K -> v \in K -> w \in K -> cidx (u : T5) = i -> cidx (v : T5) = j -> cidx (w : T5) = k -> (i < j)%N -> (j < k)%N -> (j %% 3)%N = 2%N -> ((i %% 3 == 0) && (k %% 3 == 0))%N || ((i %% 3 == 1) && (k %% 3 == 1))%N -> False.

quad_A (lemma) [obstructions.v:286](#) — ** The seven core obstruction shapes *) (* (X, zero, X) triples — paper sets 1–8 *) Lemma triple_A (u v w : backedged (qk m')) (i j k : nat) : u \in K -> v \in K -> w \in K -> cidx (u : T5) = i -> cidx (v : T5) = j -> cidx (w : T5) = k -> (i < j)%N -> (j < k)%N -> (j %% 3)%N = 2%N -> ((i %% 3 == 0) && (k %% 3 == 0))%N || ((i %% 3 == 1) && (k %% 3 == 1))%N -> False.

quad_B (lemma) [obstructions.v:320](#) — ** The seven core obstruction shapes *) (* (X, zero, X) triples — paper sets 1–8 *) Lemma triple_A (u v w : backedged (qk m')) (i j k : nat) : u \in K -> v \in K -> w \in K -> cidx (u : T5) = i -> cidx (v : T5) = j -> cidx (w : T5) = k -> (i < j)%N -> (j < k)%N -> (j %% 3)%N = 2%N -> ((i %% 3 == 0) && (k %% 3 == 0))%N || ((i %% 3 == 1) && (k %% 3 == 1))%N -> False.

quad_C (lemma) [obstructions.v:361](#) — ** The seven core obstruction shapes *) (* (X, zero, X) triples — paper sets 1–8 *) Lemma triple_A (u v w : backedged (qk m')) (i j k : nat) : u \in K -> v \in K -> w \in K -> cidx (u : T5) = i -> cidx (v : T5) = j -> cidx (w : T5) = k -> (i < j)%N -> (j < k)%N -> (j %% 3)%N = 2%N -> ((i %% 3 == 0) && (k %% 3 == 0))%N || ((i %% 3 == 1) && (k %% 3 == 1))%N -> False.

quad_D (lemma) [obstructions.v:412](#) — ** The seven core obstruction shapes *) (* (X, zero, X) triples — paper sets 1–8 *) Lemma triple_A (u v w : backedged (qk m')) (i j k : nat) : u \in K -> v \in K -> w \in K -> cidx (u : T5) = i -> cidx (v : T5) = j -> cidx (w : T5) = k -> (i < j)%N -> (j < k)%N -> (j %% 3)%N = 2%N -> ((i %% 3 == 0) && (k %% 3 == 0))%N || ((i %% 3 == 1) && (k %% 3 == 1))%N -> False.

square (lemma) [obstructions.v:450](#) — ** The seven core obstruction shapes *) (* (X, zero, X) triples — paper sets 1–8 *) Lemma triple_A (u v w : backedged (qk m')) (i j k : nat) : u \in K -> v \in K -> w \in K -> cidx (u : T5) = i -> cidx (v : T5) = j -> cidx (w : T5) = k -> (i < j)%N -> (j < k)%N -> (j %% 3)%N = 2%N -> ((i %% 3 == 0) && (k %% 3 == 0))%N || ((i %% 3 == 1) && (k %% 3 == 1))%N -> False.

occ_and3F (lemma) [obstructions.v:495](#) — ** Packaging: the occupancy bits never match an obstruction

occ_and4F (lemma) [obstructions.v:505](#)

no_obstruction (lemma) [obstructions.v:517](#)

theories/applications/k5/coverage.v

coverage5 (lemma) [coverage.v:19](#)

theories/applications/k5/k5_upper.v

omegab_at_qk_le5 (lemma) [k5_upper.v:45](#) — ** $\bar{\omega}(T) \leq 5$

omegabar_T_le5 (theorem) [k5_upper.v:56](#)

rd_irr (fact) [k5_upper.v:68](#)

rd_trans (fact) [k5_upper.v:71](#)

rd_total (fact) [k5_upper.v:74](#)

omegab_at_qd_le4 (lemma) [k5_upper.v:83](#)

omegabar_Tdel_le4 (theorem) [k5_upper.v:109](#)

theories/applications/k5/main.v

- T5_vertex_transitive** (lemma) [main.v:46](#) — The product of the vertex-transitive AC with itself is vertex-transitive.
- ★ **omegabar_T5** (theorem) [main.v:54](#) — ** $\bar{\omega}(T) = 5$
- ★ **omegabar_T5_del** (theorem) [main.v:62](#) — ** $\bar{\omega}(T - v) = 4$ for every vertex v
- ★ **T5_kcritical5** (theorem) [main.v:71](#) — ** T is 5- $\bar{\omega}$ -critical
- ★ **card_T5** (lemma) [main.v:79](#) — ** T has order n
- proper_sub_omegabar_le4** (theorem) [main.v:84](#) — ** Every proper subtournament has $\bar{\omega} \leq 4$
- ★ **conjecture_5_10_at_k5** (theorem) [main.v:108](#) — ** Conjecture 5.10 at $k = 5$: an infinite family For every N there is a 5- $\bar{\omega}$ -critical tournament on more than N vertices.
- ★ **question_5_9_fails_at_k5** (theorem) [main.v:127](#) — ** Question 5.9 fails at $k = 5$ No bound $\ell(5)$ exists: for every L there is a 5- $\bar{\omega}$ -critical tournament on more than L vertices whose ONLY subtournament with $\bar{\omega} \geq 5$ is the whole tournament.

theories/applications/ck3/lemma7.v

- card_ord_ltn** (lemma) [lemma7.v:26](#) — ** Ordinal segment cardinality (counting helper)
- card_ord_seg** (lemma) [lemma7.v:37](#)
- ckC** (definition) [lemma7.v:58](#) — The endpoint cycle as a seq: the suffix of the path from index a .
- ckCset** (definition) [lemma7.v:61](#) — Its vertex set.
- ckB** (definition) [lemma7.v:64](#) — B = the out-neighbours of $v_{\{a-1\}}$ on the cycle.
- ckS** (definition) [lemma7.v:68](#) — $S = B$, the C -predecessors of B .
- kernel_full** (theorem) [lemma7.v:606](#) — *** The package
- kernel_S** (theorem) [lemma7.v:631](#) — The bare Lemma 7 witness.
- ★ **lemma7** (theorem) [lemma7.v:646](#) — ** Lemma 7 (Cheng–Keevash), in full generality
- ★ **ck_theorem4_oriented** (theorem) [lemma7.v:684](#) — ** Theorem 4 (oriented case) and the $\delta = 2$ case of Conjecture 1
- ★ **ck_conj1_delta2** (corollary) [lemma7.v:698](#)

theories/applications/ck3/ck3_main.v

- ★ **no_short_strong3** (lemma) [ck3_main.v:28](#) — ** The endgame: no strong 3-outregular oriented digraph has $\ell \leq 5$
- ★ **ck_conj1_delta3** (theorem) [ck3_main.v:147](#) — ** The main theorem: Conjecture 1 at $\delta = 3$
- ★ **ck_conj1_delta3_path** (corollary) [ck3_main.v:158](#) — Unfolded form: an explicit directed simple path with 6 arcs.
- ck_conj1_at_3** (corollary) [ck3_main.v:170](#) — Conjecture-1-shaped alias.

theories/applications/k4/k4_lower.v

- ACm_pos** (fact) [k4_lower.v:44](#)
- C3_pos** (fact) [k4_lower.v:47](#)
- omegabar_T4_ge4** (theorem) [k4_lower.v:52](#) — ** $\bar{\omega}(T4) \geq 4$ (L1)
- emb_mem** (fact) [k4_lower.v:64](#)
- f_inj** (fact) [k4_lower.v:69](#)
- f_arc** (fact) [k4_lower.v:72](#)
- omegabar_T4del_ge3** (theorem) [k4_lower.v:77](#)

theories/applications/k4/k4_value.v

dband (definition) [k4_value.v:34](#) — ** The inner band on C ($h = 0$ heavy, $h \neq 0$ light)

dband2P (lemma) [k4_value.v:36](#)

dband1P (lemma) [k4_value.v:39](#)

dband_ge1 (lemma) [k4_value.v:42](#)

dband_le2 (lemma) [k4_value.v:45](#)

sidx (definition) [k4_value.v:60](#) — ** Sub-bands, classes, and the merged key

sidx_decode (lemma) [k4_value.v:62](#)

sidx_le5 (lemma) [k4_value.v:71](#)

kappa (definition) [k4_value.v:80](#)

kappa_sidx (lemma) [k4_value.v:82](#)

kv (definition) [k4_value.v:88](#)

kv_inj (lemma) [k4_value.v:90](#)

kv_kappa_mono (lemma) [k4_value.v:98](#)

kv_lt_t (lemma) [k4_value.v:105](#)

kv_samekappa (lemma) [k4_value.v:111](#)

rv (definition) [k4_value.v:124](#) — ** The realized merged order

rv_irr (fact) [k4_value.v:125](#)

rv_trans (fact) [k4_value.v:126](#)

rv_total (fact) [k4_value.v:127](#)

qv (definition) [k4_value.v:133](#)

qvE (lemma) [k4_value.v:135](#)

n_sub_ge_Sm (lemma) [k4_value.v:140](#) — ** Residue arithmetic helpers (pure nat, m-relative)

n_sub_gt_Sm (lemma) [k4_value.v:143](#)

n_sub_eq_Sm (lemma) [k4_value.v:146](#)

sub_eq_m (lemma) [k4_value.v:152](#)

mem_m_F (lemma) [k4_value.v:159](#) — Connection-set refutations by value.

mem_mid_F (lemma) [k4_value.v:164](#)

vals12 (lemma) [k4_value.v:169](#)

beat_kv (lemma) [k4_value.v:187](#)

beat_blocksV (lemma) [k4_value.v:196](#)

beat_innerV (lemma) [k4_value.v:206](#)

sidx_inj_clique (lemma) [k4_value.v:217](#) — ** The sub-band Lemma: at most one clique vertex per σ (V1–V4)

occv (definition) [k4_value.v:263](#) — ** Occupancy

occvP (lemma) [k4_value.v:265](#)

card_clique_sidx (lemma) [k4_value.v:272](#)

occ24_block (lemma) [k4_value.v:280](#) — ** V5: both $\kappa = 4$ sub-bands occupied forces $\{(m,0),(0,i)\}$

occ24_5F (lemma) [k4_value.v:312](#)

occ24_1F (lemma) [k4_value.v:340](#)

occ5310_F (lemma) [k4_value.v:392](#) — ** V6: the four-class chain (0,0) / high / low / κ^2 dies

clique_card_le4 (lemma) [k4_value.v:485](#)

omegab_at_qv_le4 (lemma) [k4_value.v:500](#) — ** The value bound

omegabar_T4_le4 (theorem) [k4_value.v:508](#)

★ **omegabar_T4** (theorem) [k4_value.v:511](#)

theories/applications/k4/k4_del.v

kd (definition) [k4_del.v:55](#) — ** The d_then_c key
kd_inj (lemma) [k4_del.v:57](#)
kd_sidx_mono (lemma) [k4_del.v:65](#)
kd_samesidx (lemma) [k4_del.v:72](#)
rd_irr (fact) [k4_del.v:87](#)
rd_trans (fact) [k4_del.v:90](#)
rd_total (fact) [k4_del.v:93](#)
qd (definition) [k4_del.v:99](#)
qdE (lemma) [k4_del.v:101](#)
sidx_del_le4 (lemma) [k4_del.v:105](#) — Survivors never occupy the deleted band $\sigma = 5$ (D0).
beat_kd (lemma) [k4_del.v:147](#)
beat_blocksD (lemma) [k4_del.v:157](#)
beat_innerD (lemma) [k4_del.v:167](#)
didx_inj_clique (lemma) [k4_del.v:178](#) — ** D1: at most one clique vertex per band
occd (definition) [k4_del.v:218](#) — ** Occupancy
occdP (lemma) [k4_del.v:220](#)
card_clique_didx (lemma) [k4_del.v:227](#)
occ023_F (lemma) [k4_del.v:237](#) — B1 + B3 + B4: B3 pins the B1 block at $m+1$ and the B4 block at $s \geq m+2$; then $(s,0)$ cannot beat $(m+1,\cdot)$.
occ124_F (lemma) [k4_del.v:299](#) — B2 + B3 + B5: B3 forces $s' = m$ (D3f), pinning the B2 block at m ; the B3-beats-B2 backedge then needs $m \in g$.
occ0134_F (lemma) [k4_del.v:356](#) — B1 + B2 + B4 + B5: the D3e core.
clique_card_le3 (lemma) [k4_del.v:484](#)
omegab_at_qd_le3 (lemma) [k4_del.v:500](#) — ** The deletion bound
omegabar_T4del_le3 (theorem) [k4_del.v:508](#)
omegabar_T4del0 (theorem) [k4_del.v:511](#)

theories/applications/k4/k4_main.v

T4_vertex_transitive (lemma) [k4_main.v:43](#) — The product of the vertex-transitive AC with the vertex-transitive C is vertex-transitive.
★ **omegabar_T4_del** (theorem) [k4_main.v:51](#) — ** $\bar{\omega}(T4 - v) = 3$ for every vertex v
★ **T4_kcritical4** (theorem) [k4_main.v:59](#) — ** T4 is $4\text{-}\bar{\omega}$ -critical
★ **card_T4** (lemma) [k4_main.v:67](#) — ** T4 has order $3n$
★ **conjecture_5_10_at_k4** (theorem) [k4_main.v:74](#) — ** Conjecture 5.10 at $k = 4$: an infinite family
★ **question_5_9_fails_at_k4** (theorem) [k4_main.v:89](#) — ** Question 5.9 fails at $k = 4$

theories/applications/unified.v

★ **conjecture_5_10_at_k3** (theorem) [unified.v:33](#) — ** Conjecture 5.10 at $k = 3$: an infinite family
★ **question_5_9_fails_at_k3** (theorem) [unified.v:47](#) — ** Question 5.9 fails at $k = 3$
★ **conjecture_5_10_at_345** (theorem) [unified.v:66](#) — ** The unified headline: every $k \in \{3, 4, 5\}$