

1. Table Definitions

Contents

1	Table Definitions	1
1.1	all_files	2
1.2	files	2
1.3	host	2
1.4	host_ip	3
1.5	labels_graph_net_conn	3
1.6	labels_graph_nodes	4
1.7	labels_graph_process_summary	4
1.8	labels_networkx	4
1.9	lolbas	5
1.10	mitre_labels	5
1.11	process	5
1.12	process_conn_incr	7
1.13	process_exe_file_summary	8
1.14	process_file	8
1.15	process_file_summary	9
1.16	process_image_load	9
1.17	process_image_load_summary	10
1.18	process_lolbas_summary	10
1.19	process_mitre_summary	11
1.20	process_net_conn	11
1.21	process_net_summary	12
1.22	process_path	13
1.23	process_registry	13
1.24	process_registry_summary	14
1.25	process_summary	14
1.26	process_uber_summary	17
1.27	sigma_labels	20
1.28	sigma_labels_summary	20

1.1. all_files

Master list of filenames seen in the collect. Derived from process executions, dll loads and file usage activity.

Column	Data Type	Description
dll_num_rows	DOUBLE	Number of times used as a DLL
file_num_rows	DOUBLE	Number of times referenced in file read/write activity
filename	STRING	Fully qualified filename
num_hosts	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
process_num_rows	DOUBLE	Number of rows file was executed as a process

1.2. files

Files by hostname with summary information for executions, dlls and file usage.

Column	Data Type	Description
dll_first_seen	TIMESTAMP	Earliest time seen
dll_last_seen	TIMESTAMP	Latest time seen
dll_num_rows	DOUBLE	Number of times used as a DLL
file_first_seen	TIMESTAMP	Earliest time seen
file_id	STRING	Unique ID for a file. Hash of hostname+fully qualified filename
file_last_seen	TIMESTAMP	Latest time seen
file_num_rows	DOUBLE	Number of times referenced in file read/write activity
filename	STRING	Fully qualified filename
hostname	STRING	Hostname data collected from
max_process_term	TIMESTAMP	Maximum value in the interval
min_process_started	TIMESTAMP	Minimum value in the interval
process_num_rows	DOUBLE	Number of rows file was executed as a process

1.3. host

Unique entry for every instrumented host.

Column	Data Type	Description
Hostname	STRING	Hostname data collected from
ad_domain	STRING	Active directory host is joined to
agent_ids	STRING[]	List of agent ids. A long running host may have several dur to update, reinstalls, etc.
arch	STRING	Chip architecture
domain_role	STRING	Host role within the domain. Ex: domain controller, member, etc.
etl_version	STRING	Wintap data collection plugin version
first_seen	TIMESTAMP	Earliest time seen
has_battery	BOOLEAN	Does this host have a battery? Indicates laptop if true
last_boot	INT64	Time of last boot, in epoch seconds
last_seen	TIMESTAMP	Latest time seen
num_ad_domain	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_arch	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_domain_role	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.

Continued on next page

TABLE 3 – Continued from previous page

Column	Data Type	Description
num_etl_version	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_has_battery	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_last_boot	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_os	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_os_version	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_processor_count	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_processor_speed	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_rows	INT64	Number of row behind this summary
num_wintap_version	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
os	STRING	Host operating system
os_family	STRING	OS Family: windows, linux, osx
os_version	STRING	Operating System Version
processor_count	INTEGER	Number of processors cores
processor_speed	INT64	Speed of processors
wintap_version	STRING	Version Wintap core. Each plugin has its own version.

1.4. host_ip

Network interface information for hosts.

Column	Data Type	Description
Hostname	STRING	Hostname data collected from
MTU	INTEGER	Should be max transmtion unit, but its currently not collected.
agent_id	STRING	Agent ID is a unique id for a Wintap install on a host. It is created on initial startup after install.
first_seen	TIMESTAMP	Earliest time seen
interface	STRING	Should be the interface device name, but its currently not collected.
ip_addr	INT64	An IP address on the host. Stored as an integer
ip_addr_no	STRING	An IP address on the host. In dotted quad notation.
last_seen	TIMESTAMP	Latest time seen
mac	STRING	Mac address as string (colon delimited)
num_rows	INT64	Number of row behind this summary
os_family	STRING	OS Family: windows, linux, osx
private_gateway	STRING	IP of the gateway used by this interface

1.5. labels_graph_net_conn

Summarizes network-related labels by conn_id

Column	Data Type	Description
conn_id	STRING	Hash of "normalized" 5 tuple (ip1, port1, ip2, port2, L4 protocol). To represent A to B the same as B to A, the lower IP (as int) along with its port comes first in the hash preimage ordering. When ip1 == ip2, then the pair order is decided by lowest port instead.
label_num_hits	INT64	Number of unique labels hit
label_num_sources	INT64	Number of unique sources of labels
label_num_uniq_annotations	INT64	Number of unique annotations
label_source	STRING	For now, only a single source: "networkx"

1.6. labels_graph_nodes

Parse JSON in NetworkX files into a flat structure representing the nodes

Column	Data Type	Description
annotation	STRING	Annotations are manually added to specific nodes by the person creating the networkx graph of activity. Used to further highlight the activity.
filename	STRING	Fully qualified filename
id	STRING	Unique ID for the node in the graph. Often a PID_HASH, CONN_ID or similar.
label	STRING	Graph node label. Often a PROCESS_NAME or similar.
node_type	STRING	Type of node: PROCESS, NETWORK, FILE, etc.

1.7. labels_graph_process_summary

Summarizes process-related labels by pid_hash

Column	Data Type	Description
label_num_hits	INT64	Number of unique labels hit
label_num_sources	INT64	Number of unique sources of labels
label_num_uniq_annotations	INT64	Number of unique annotations
label_source	STRING	For now, only a single source: "networkx"
pid_hash	STRING	Globally unique process hash (hash from hostname, os pid, and start_time)

1.8. labels_networkx

Import of networkx graph data. Used primarily as base to build summary tables. Data in this table is JSON, tricky to work with directly.

Column	Data Type	Description
directed	BOOLEAN	Directed graph or not.
filename	STRING	Fully qualified filename
is_multigraph	BOOLEAN	Multigraph or not
links	STRUCT	List of links
nodes	STRUCT	List of nodes

1.9. lolbas

Joins process data with LOLBAS (Living Off the Land Binaries and Scripts) data. Summarizes LOLBAS-related activity by pid_hash.

Column	Data Type	Description
acknowledgements	STRING	Person who submitted the entry. May be more than 1.
author	STRING	Person or group who submitted the entry.
command	STRING	The command with arguments
command_category	STRING	Intent. Ex: EXECUTE, UAC BYPASS, CONCEAL, etc.
command_description	STRING	Description of the command
command_privileges	STRING	Required privileges to execute
command_usecase	STRING	Description of use case for attacker
date	DATE	Date created
description	STRING	Normal purpose of the command
detections	STRING	How to detect exploit: Many are URLs pointing to SIGMA rule, Defender, etc.
filename	STRING	Filename of executable. No path.
mitre_attck_technique	STRING	Specific MITRE attck code. Ex: T1003
operating_system	STRING	OSes binary is found on. Some very specific, some general.
paths	STRING	Paths where binary is found. More than one are comma separated.
resources	STRING	URL to more info
url	STRING	URL to LolBAS project about the exploit

1.10. mitre_labels

Column	Data Type	Description
analytic_id	STRING	Mitre analytic ID. Ex: CAR-2021-05-012
entity	STRING	Wintap entity ID (hash). The type of entity (PID_HASH, CONN_ID, etc) is defined in the ENTITY_TYPE column. Note: Currently, only PID_HASHes are identified.
entity_type	STRING	Wintap entity type. Determines what kind of hash is in the ENTITY column. Ex: PID_HASH, CONN_ID, FILE_ID
time	TIMESTAMP	Timestamp of activity

1.11. process

Each row is a process execution. Processes are the central object of this entire data model.

Column	Data Type	Description
agent_id	STRING	Agent ID is a unique id for a Wintap install on a host. It is created on initial startup after install.
args	STRING	Command line arguments
commit_charge	INT64	Commit charge is the total amount of virtual memory guaranteed for all processes to fit in physical memory and the page file.
commit_peak	INT64	Total memory committed
cpu_cycle_count	INT64	Always zero (note: more than zero cycles were generally used in a process)

Continued on next page

TABLE 11 – Continued from previous page

Column	Data Type	Description
cpu_utilization	INTEGER	Ignore: unable to collect. This *should* be a value indicating the percentage of cpu utilized by the process over its life, but turns out be harder to collect than expected.
exit_code	INT64	Process exit code
file_id	STRING	Unique ID for a file. Hash of hostname+fully qualified filename
file_md5	STRING	MD5 hash of the binary process/dll
file_sha2	STRING	SHA2 hash of the file contents
filename	STRING	Fully qualified filename
first_seen	TIMESTAMP	Earliest time seen
hard_fault_count	INTEGER	Count of hard page faults
hostname	STRING	Hostname data collected from
last_seen	TIMESTAMP	Latest time seen
num_agent_id	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_args	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_file_md5	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_file_sha2	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_parent_os_pid	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_parent_pid_hash	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_process_name	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_process_path	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_process_start	DOUBLE	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_process_stop	DOUBLE	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_user_name	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
os_family	STRING	OS Family: windows, linux, osx
os_pid	INTEGER	Operating system process id
parent_os_pid	INTEGER	OS Process ID of parent process
parent_pid_hash	STRING	PID_HASH of parent process
pid_hash	STRING	Globally unique process hash (hash from hostname, os pid, and start_time)
process_name	STRING	Filename of executable
process_path	STRING	Fully qualified path of the process executable
process_started	TIMESTAMP	Process start timestamp
process_started_seconds	DOUBLE	Process start time in unix epoch seconds
process_stop_seconds	DOUBLE	Process stop in unix epoch seconds
process_term	TIMESTAMP	Process termination timestamp
read_operation_count	INT64	Count of number of read operations
read_transfer_kilobytes	INT64	Number of K bytes read
token_elevation_type	INTEGER	Indicates UAC privilege status: 1 (Default) = no linked token, UAC disabled or non-admin account; 2 (Full) = elevated administrator with full rights after UAC approval; 3 (Limited) = filtered admin token before elevation with available full token; 4 = undocumented value, treat as unknown/reserved.
user_name	STRING	Username. Note that on windows there are many usernames that represent system or other background activity

Continued on next page

TABLE 11 – Continued from previous page

Column	Data Type	Description
write_operation_count	INT64	Count of number of write operations
write_transfer_kilobytes	INT64	Number of K bytes written

1.12. process_conn_incr

Network connection increments for each process. (KEY: PID_HASH + CONN_ID + INCR_START_SECS)

Column	Data Type	Description
Hostname	STRING	Hostname data collected from
agent_id	STRING	Agent ID is a unique id for a Wintap install on a host. It is created on initial startup after install.
conn_id	STRING	Hash of "normalized" 5 tuple (ip1, port1, ip2, port2, L4 protocol). To represent A to B the same as B to A, the lower IP (as int) along with its port comes first in the hash preimage ordering. When ip1 == ip2, then the pair order is decided by lowest port instead.
first_seen	TIMESTAMP	Earliest time seen
incr_start	TIMESTAMP	Start time of a 1 minute increment used to aggregate the high-volume events
last_seen	TIMESTAMP	Latest time seen
local_ip_addr	STRING	IP address on the host collecting data. This address is local to the host sensor. In dotted quad notation.
local_ip_int	INT64	IP of the host collecting this data as 32-bit int
local_port	INTEGER	Port of the process on the collecting host
max_10sec_eventcount	INTEGER	Maximum value in the interval
max_size	INT64	Maximum value in the interval
max_tcp_recv_count	INTEGER	Maximum value in the interval
max_tcp_recv_size	INT64	Maximum value in the interval
max_tcp_send_count	INTEGER	Maximum value in the interval
max_tcp_send_size	INT64	Maximum value in the interval
max_udp_recv_count	INTEGER	Maximum value in the interval
max_udp_recv_size	INT64	Maximum value in the interval
max_udp_send_count	INTEGER	Maximum value in the interval
max_udp_send_size	INT64	Maximum value in the interval
min_10sec_eventcount	INTEGER	Minimum value in the interval
min_size	INT64	Minimum value in the interval
min_tcp_recv_size	INT64	Minimum value in the interval
min_tcp_send_size	INT64	Minimum value in the interval
min_udp_recv_size	INT64	Minimum value in the interval
min_udp_send_size	INT64	Minimum value in the interval
num_raw_rows	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
os_family	STRING	OS Family: windows, linux, osx
pid_hash	STRING	Globally unique process hash (hash from hostname, os pid, and start_time)
process_name	STRING	Filename of executable
protocol	STRING	Layer 4 protocol (TCP, UDP)
remote_ip_addr	STRING	IP address the host collecting data is talking to. This address is remote to the host sensor. In dotted quad notation.
remote_ip_int	INT64	IP of the remote host for this connection increment as 32-bit int
remote_port	INTEGER	Port of the remote host for this connection increment
sq_size	DOUBLE	Squared size of bytes in network packet. Ask Chris B!

Continued on next page

TABLE 12 – Continued from previous page

Column	Data Type	Description
sq_tcp_recv_size	DOUBLE	Square of the values in the interval. (Ask Chris B)
sq_tcp_send_size	DOUBLE	Square of the values in the interval. (Ask Chris B)
sq_udp_recv_size	DOUBLE	Square of the values in the interval. (Ask Chris B)
sq_udp_send_size	DOUBLE	Square of the values in the interval. (Ask Chris B)
tcp_accept_count	DOUBLE	Number of TCP ACCEPT events on this connection for the time window
tcp_connect_count	DOUBLE	Number of TCP CONNECT events on this connection for the time window
tcp_disconnect_count	DOUBLE	Number of TCP DISCONNECT events on this connection for the time window
tcp_reconnect_count	DOUBLE	Number of TCP RECONNECT events on this connection for the time window
tcp_recv_count	DOUBLE	Number of TCP RECV events on this connection for the time window
tcp_recv_size	DOUBLE	Number of TCP RECV bytes received on this connection for the time window
tcp_retransmit_count	DOUBLE	Number of TCP RETRANSMIT events on this connection for the time window
tcp_send_count	DOUBLE	Number of TCP SEND events on this connection for the time window
tcp_send_size	DOUBLE	Number of TCP bytes sent for the time window
tcp_tcpcopy_count	DOUBLE	Number of TCP TCPCOPY events on this connection for the time window
tcp_tcpcopy_size	DOUBLE	Number of TCP TCPCOPY bytes on this connection for the time window
total_events	DOUBLE	Sum of events counts for this connection increment
total_size	DOUBLE	Number of bytes observed for this connection increment
udp_recv_count	DOUBLE	Number of UDP RECV events on this connection for the time window
udp_recv_size	DOUBLE	Number of UDP bytes received for the time window
udp_send_count	DOUBLE	Number of UDP SEND events on this connection for the time window
udp_send_size	DOUBLE	Number of UDP bytes sent for the time window

1.13. process_exe_file_summary

Summary of files used in process executions. Derived from all process executions resulting in a single row per file per host.

Column	Data Type	Description
file_id	STRING	Unique ID for a file. Hash of hostname+fully qualified filename
filename	STRING	Fully qualified filename
hostname	STRING	Hostname data collected from
max_process_term	TIMESTAMP	Maximum value in the interval
min_process_started	TIMESTAMP	Minimum value in the interval
process_num_rows	INT64	Number of rows file was executed as a process
source	STRING	Source of file: currently only PROCESS

1.14. process_file

File activity of processes. Activity is summarized to the PROCESS + FILE level. See RAW_PROCESS_FILE for activity detailed activity.

Column	Data Type	Description
Hostname	STRING	Hostname data collected from
activity_type	STRING	File activity type. Ex: READ, WRITE
agent_id	STRING	Agent ID is a unique id for a Wintap install on a host. It is created on initial startup after install.
bytes_requested	DOUBLE	Total bytes requested
event_count	DOUBLE	Total ETW events
file_hash	STRING	MD5 hash of the file
file_id	STRING	Unique ID for a file. Hash of hostname+fully qualified filename
filename	STRING	Name of the file
first_seen	TIMESTAMP	Earliest time seen
last_seen	TIMESTAMP	Latest time seen
max_event	TIMESTAMP	Maximum value in the interval
min_event	TIMESTAMP	Minimum value in the interval
num_raw_rows	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
pid_hash	STRING	Globally unique process hash (hash from hostname, os pid, and start_time)
process_name	STRING	Filename of executable

1.15. process_file_summary

File activity summarize to the process level.

Column	Data Type	Description
Close_Events	DOUBLE	Number of file close events
Create_Events	DOUBLE	Number of file create events
Delete_Events	DOUBLE	Number of file delete events
Hostname	STRING	Hostname data collected from
Read_Bytes	DOUBLE	File bytes read
Read_Events	DOUBLE	Number of file read events
Rename_Events	DOUBLE	Number of file rename events
SetInfo_Events	DOUBLE	
Write_Bytes	DOUBLE	File bytes written
Write_Events	DOUBLE	Number of file write events
agent_id	STRING	Agent ID is a unique id for a Wintap install on a host. It is created on initial startup after install.
first_seen	TIMESTAMP	Earliest time seen
last_seen	TIMESTAMP	Latest time seen
num_null_filename	DOUBLE	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_raw_rows	DOUBLE	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_uniq_file_hash	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
pid_hash	STRING	Globally unique process hash (hash from hostname, os pid, and start_time)
process_name	STRING	Filename of executable

1.16. process_image_load

DLLs loaded and unloaded by process.

Column	Data Type	Description
agent_id	STRING	Agent ID is a unique id for a Wintap install on a host. It is created on initial startup after install.
build_time	INT64	Build time of DLL
checksum	INTEGER	A checksum on the file contents of the DLL
default_base	STRING	Default base memory address
file_id	STRING	Unique ID for a file. Hash of hostname+fully qualified filename
file_md5	STRING	MD5 hash of the binary process/dll
filename	STRING	Filename of the loaded code
first_seen	TIMESTAMP	Earliest time seen
hostname	STRING	Hostname data collected from
image_base	STRING	Actual base memory address(?)
last_seen	TIMESTAMP	Latest time seen
max_image_size	INTEGER	Maximum value in the interval
min_image_size	INTEGER	Minimum value in the interval
num_load	DOUBLE	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_unload	DOUBLE	Number of unique values in the related column. Typically, the related column should only have 1 value.
pid_hash	STRING	Globally unique process hash (hash from hostname, os pid, and start_time)
process_name	STRING	Filename of executable

1.17. process_image_load_summary

Summarizes DLL and image load activity by process (pid_hash).

Column	Data Type	Description
agent_id	STRING	Agent ID is a unique id for a Wintap install on a host. It is created on initial startup after install.
dlls	STRING[]	List of DDL names as an array
first_seen	TIMESTAMP	Earliest time seen
hostname	STRING	Hostname data collected from
last_seen	TIMESTAMP	Latest time seen
num_uniq_files	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
pid_hash	STRING	Globally unique process hash (hash from hostname, os pid, and start_time)
process_name	STRING	Filename of executable

1.18. process_lolbas_summary

Column	Data Type	Description
lolbas_cats	STRING[]	List categories from hits
lolbas_mitre	STRING[]	List of Mitre codes from hits
lolbas_num_rows	INT64	Number of hits
lolbas_privs	STRING[]	List of privileges from hist
pid_hash	STRING	Globally unique process hash (hash from hostname, os pid, and start_time)

1.19. process_mitre_summary

Column	Data Type	Description
mitre_analytic_ids	STRING[]	List of analytic IDs from hits
mitre_analytic_types	STRING[][]	List of analytic types from hits
mitre_information_domains	STRING[]	List domains from hits. Ex: Analytic, Host, Network
mitre_num_rows	INT64	Number of hits
mitre_subtypes	STRING[][]	List of subtypes from hits. Ex: Map building, Anomaly, Host-flow. Process.
pid_hash	STRING	Globally unique process hash (hash from hostname, os pid, and start_time)

1.20. process_net_conn

Network connections for each process. These are summarize to the PROCESS and Network 5-tuple (KEY: PID_HASH + CONN_ID)

Column	Data Type	Description
Hostname	STRING	Hostname data collected from
agent_id	STRING	Agent ID is a unique id for a Wintap install on a host. It is created on initial startup after install.
conn_id	STRING	Hash of "normalized" 5 tuple (ip1, port1, ip2, port2, L4 protocol). To represent A to B the same as B to A, the lower IP (as int) along with its port comes first in the hash preimage ordering. When ip1 == ip2, then the pair order is decided by lowest port instead.
first_seen	TIMESTAMP	Earliest time seen
last_seen	TIMESTAMP	Latest time seen
local_ip_addr	STRING	IP address on the host collecting data. This address is local to the host sensor. In dotted quad notation.
local_port	INTEGER	Port of the process on the collecting host
num_raw_rows	DOUBLE	Number of unique values in the related column. Typically, the related column should only have 1 value.
os_family	STRING	OS Family: windows, linux, osx
pid_hash	STRING	Globally unique process hash (hash from hostname, os pid, and start_time)
process_name	STRING	Filename of executable
protocol	STRING	Layer 4 Protocol (TCP, UDP)
remote_ip_addr	STRING	IP address the host collecting data is talking to. This address is remote to the host sensor. In dotted quad notation.
remote_port	INTEGER	Port of the remote host for this connection increment
sq_size	DOUBLE	Squared size of bytes in network packet. Ask Chris B!
sq_tcp_recv_size	DOUBLE	Square of the values in the interval. (Ask Chris B)
sq_tcp_send_size	DOUBLE	Square of the values in the interval. (Ask Chris B)
sq_udp_recv_size	DOUBLE	Square of the values in the interval. (Ask Chris B)
sq_udp_send_size	DOUBLE	Square of the values in the interval. (Ask Chris B)
tcp_accept_count	DOUBLE	Number of TCP ACCEPT events on this connection
tcp_connect_count	DOUBLE	Number of TCP CONNECT events on this connection
tcp_disconnect_count	DOUBLE	Number of TCP DISCONNECT events on this connection
tcp_reconnect_count	DOUBLE	Number of TCP RECONNECT events on this connection
tcp_recv_count	DOUBLE	Number of TCP RECV events on this connection
tcp_recv_size	DOUBLE	Number of TCP RECV bytes received on this connection
tcp_retransmit_count	DOUBLE	Number of TCP RETRANSMIT events on this connection
tcp_send_count	DOUBLE	Number of TCP SEND events on this connection

Continued on next page

TABLE 20 – Continued from previous page

Column	Data Type	Description
tcp_send_size	DOUBLE	Number of TCP bytes sent
tcp_tcpcopy_count	DOUBLE	Number of TCP TCPCOPY events on this connection
tcp_tcpcopy_size	DOUBLE	Number of TCP TCPCOPY bytes on this connection
total_events	DOUBLE	Sum of events counts for this connection
total_size	DOUBLE	Number of bytes observed for this connection
udp_recv_count	DOUBLE	Number of UDP RECV events on this connection
udp_recv_size	DOUBLE	Number of UDP bytes received
udp_send_count	DOUBLE	Number of UDP SEND events on this connection
udp_send_size	DOUBLE	Number of UDP bytes sent on this connection

1.21. process_net_summary

Summarizes all network connections for a given process to the process level.

Column	Data Type	Description
Hostname	STRING	Hostname data collected from
agent_id	STRING	Agent ID is a unique id for a Wintap install on a host. It is created on initial startup after install.
avg_bytes	DOUBLE	Average bytes in an event
avg_packets	DOUBLE	Average packets per session done by the process
conn_id_count	INT64	Number of unique network connection IDs (5-tuples)
first_seen	TIMESTAMP	Earliest time seen
last_seen	TIMESTAMP	Latest time seen
max_bytes	DOUBLE	Maximum bytes in an event
max_packets	DOUBLE	Max packets per session done by the process
min_bytes	DOUBLE	Minimum bytes in an event
min_packets	DOUBLE	Min packets per session done by the process
net_recv_size	DOUBLE	Total bytes received by the process
net_rs_total	DOUBLE	Total bytes sent/received by the process
net_send_size	DOUBLE	Total bytes sent by the process
net_send_vs_recv	DOUBLE	Ratio of bytes sent vs received by the process
net_total_events	DOUBLE	Total events accross UDP/TCP
net_total_size	DOUBLE	Total bytes accross all events
num_raw_rows	DOUBLE	Number of unique values in the related column. Typically, the related column should only have 1 value.
os_family	STRING	OS Family: windows, linux, osx
pid_hash	STRING	Globally unique process hash (hash from hostname, os pid, and start_time)
process_name	STRING	Filename of executable
sq_size	DOUBLE	Squared size of bytes in network packet. Ask Chris B!
tcp_accept_count	DOUBLE	Number of TCP Accept for this process
tcp_connect_count	DOUBLE	Number of TCP Connects for this process
tcp_disconnect_count	DOUBLE	Number of TCP Disconnects for this process
tcp_reconnect_count	DOUBLE	Number of TCP Reconnects for this process
tcp_recv_count	DOUBLE	Number of TCP packets received by the process
tcp_recv_size	DOUBLE	Number of TCP bytes received by the process
tcp_retransmit_count	DOUBLE	Number of TCP retransmits by the process
tcp_rs_total	DOUBLE	Total TCP bytes sent/received by the process
tcp_send_count	DOUBLE	Number of TCP packets sent by the process
tcp_send_size	DOUBLE	Number of TCP bytes sent by the process
tcp_send_vs_recv	DOUBLE	Ratio of TCP bytes sent vs received by the process
tcp_tcpcopy_count	DOUBLE	Number of TCP copy events during the process
tcp_tcpcopy_size	DOUBLE	TCP copy bytes

Continued on next page

TABLE 21 – Continued from previous page

Column	Data Type	Description
udp_rcv_count	DOUBLE	Number of UDP packets received by the process
udp_rcv_size	DOUBLE	Number of UDP bytes received by the process
udp_rs_total	DOUBLE	Total UDP bytes received by the process
udp_send_count	DOUBLE	Number of UDP packets sent by the process
udp_send_size	DOUBLE	Number of UDP bytes sent by the process
udp_send_vs_rcv	DOUBLE	Ratio of UDP bytes sent vs received by the process

1.22. process_path

For each process, has the path to its root (parent process).

Column	Data Type	Description
agent_id	STRING	Agent ID is a unique id for a Wintap install on a host. It is created on initial startup after install.
hostname	STRING	Hostname data collected from
level	INTEGER	Distance from the kernel process
max_level	INTEGER	Ignore: The same value level. Artifact of the processing to generate the paths.
os_pid	INTEGER	Operating system process id
parent_os_pid	INTEGER	OS Process ID of parent process
parent_pid_hash	STRING	PID_HASH of parent process
pid_hash	STRING	Globally unique process hash (hash from hostname, os pid, and start_time)
process_name	STRING	Filename of executable
process_path	STRING	Fully qualified path of the process executable
ptree	STRING	Path to kernel using only PROCESS_NAMEs. Order and format is: =process-¿parent process-¿... Ex: =winlogon.exe-¿smss.exe-¿smss.exe-¿ntoskrnl.exe
ptree_list	STRING[]	Path to kernel using PID_HASHes. Stored as an list. List is order from process to kernel process
ptree_list_tuples	STRUCT	Path to kernel using named tuples of PID_HASH and PROCESS_NAME (list of maps). List is order from process to kernel process
seq	INTEGER	Ignore: Artifact left over from process. Level+1.

1.23. process_registry

Registry activity events. These are aggregated to PROCESS + Registry Key/Value

Column	Data Type	Description
activity_type	STRING	Type of registry activity. Ex: CREATEKEY, READ, WRITE, DELETEVALUE, DELETEKEY
agent_id	STRING	Agent ID is a unique id for a Wintap install on a host. It is created on initial startup after install.
event_count	DOUBLE	Total ETW events
first_seen	TIMESTAMP	Earliest time seen
hostname	STRING	Hostname data collected from
last_seen	TIMESTAMP	Latest time seen
max_event	TIMESTAMP	Maximum value in the interval
min_event	TIMESTAMP	Minimum value in the interval

Continued on next page

TABLE 23 – Continued from previous page

Column	Data Type	Description
num_raw_rows	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
pid_hash	STRING	Globally unique process hash (hash from hostname, os pid, and start_time)
process_name	STRING	Filename of executable
reg_data	STRING	Registry data, which is the most detailed part of the registry key. Strangely, it isn't data
reg_path	STRING	Registry path
reg_value	STRING	Registry value read or written

1.24. process_registry_summary

All registry activity events summarized to the PROCESS.

Column	Data Type	Description
agent_id	STRING	Agent ID is a unique id for a Wintap install on a host. It is created on initial startup after install.
createkeys	DOUBLE	Number of createkeys by process
deletekeys	DOUBLE	Number of deletekeys by process
deletevalues	DOUBLE	Number of deletevalues by process
first_seen	TIMESTAMP	Earliest time seen
hostname	STRING	Hostname data collected from
last_seen	TIMESTAMP	Latest time seen
pid_hash	STRING	Globally unique process hash (hash from hostname, os pid, and start_time)
process_name	STRING	Filename of executable
reads	DOUBLE	Number of reads by process
total_activity_types	DOUBLE	Total number of ETW events for all registry activity for a process
writes	DOUBLE	Number of writes by process

1.25. process_summary

Provides a unified summary of all process-related activities that are directly collected by Wintap. This includes:

- Process metadata (e.g., process_name, hostname, pid_hash).
- Registry activity (e.g., reads, writes, key creation/deletion).
- File activity (e.g., file reads, writes, and other events).
- Network activity (e.g., connections, data sent/received).
- Image loads (e.g., DLLs loaded by the process).
- Host-level metadata (e.g., OS, architecture).

Column	Data Type	Description
Close_Events	DOUBLE	Number of file close events
Create_Events	DOUBLE	Number of file create events
Delete_Events	DOUBLE	Number of file delete events
Read_Bytes	DOUBLE	File bytes read
Read_Events	DOUBLE	Number of file read events
Rename_Events	DOUBLE	Number of file rename events
SetInfo_Events	DOUBLE	
Write_Bytes	DOUBLE	File bytes written
Write_Events	DOUBLE	Number of file write events
agent_id	STRING	Agent ID is a unique id for a Wintap install on a host. It is created on initial startup after install.
arch	STRING	Host architecture

Continued on next page

TABLE 25 – Continued from previous page

Column	Data Type	Description
args	STRING	Process arguments. Note: as a simple string, no parsing done
avg_bytes	DOUBLE	Average bytes over the interval
avg_packets	DOUBLE	Average packets over the interval
commit_charge	INT64	Commit charge is the total amount of virtual memory guaranteed for all processes to fit in physical memory and the page file.
commit_peak	INT64	Total memory committed
conn_id_count	INT64	Number of unique network connection IDs (5-tuples)
cpu_cycle_count	INT64	Always zero (note: more than zero cycles were generally used in a process)
cpu_utilization	INTEGER	Ignore: unable to collect. This *should* be a value indicating the percentage of cpu utilized by the process over its life, but turns out be harder to collect than expected.
dll_first_seen	TIMESTAMP	Earliest time seen
dll_last_seen	TIMESTAMP	Latest time seen
dll_num_uniq_files	INT64	Number of unique DDLs by name
dlls	STRING[]	List of DDL names as an array
duration_seconds	DOUBLE	Elapsed process execution in seconds
exit_code	INT64	Process exit code
file_first_seen	TIMESTAMP	Earliest time seen
file_id	STRING	Unique ID for a file. Hash of hostname+fully qualified filename
file_last_seen	TIMESTAMP	Latest time seen
file_md5	STRING	MD5 hash of the binary process/dll
file_num_raw_rows	DOUBLE	Number of rows of file activity from the raw data.
file_sha2	STRING	SHA2 hash of the file contents
filename	STRING	Fully qualified filename
first_seen	TIMESTAMP	Earliest time seen
hard_fault_count	INTEGER	Count of hard page faults
hostname	STRING	Hostname data collected from
last_seen	TIMESTAMP	Latest time seen
max_bytes	DOUBLE	Max bytes in the interval
max_packets	DOUBLE	Max packets in the interval
min_bytes	DOUBLE	Min bytes in the interval
min_packets	DOUBLE	Max packets in the interval
net_first_seen	TIMESTAMP	Earliest time seen
net_last_seen	TIMESTAMP	Latest time seen
net_num_raw_rows	DOUBLE	Number of rows in the raw data
net_recv_size	DOUBLE	Total bytes received in the interval
net_rs_total	DOUBLE	Total bytes sent/received in the interval
net_send_size	DOUBLE	Total bytes sent in the interval
net_send_vs_recv	DOUBLE	Ratio of bytes sent/received in the interval
net_total_events	DOUBLE	Total network events in the interval
net_total_size	DOUBLE	Total bytes (send/receive) in the interval
num_agent_id	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_args	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_file_md5	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_file_sha2	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_null_filename	DOUBLE	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_parent_os_pid	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.

Continued on next page

TABLE 25 – Continued from previous page

Column	Data Type	Description
num_parent_pid_hash	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_process_name	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_process_path	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_process_start	DOUBLE	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_process_stop	DOUBLE	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_uniq_file_hash	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_user_name	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
os	STRING	Operating System
os_family	STRING	OS Family: windows, linux, osx
os_pid	INTEGER	Operating system process id
os_version	STRING	Operating System Version
parent_os_pid	INTEGER	OS Process ID of parent process
parent_pid_hash	STRING	PID_HASH of parent process
pid_hash	STRING	Globally unique process hash (hash from hostname, os pid, and start_time)
process_name	STRING	Filename of executable
process_path	STRING	Fully qualified path of the process executable
process_started	TIMESTAMP	Process start timestamp
process_started_seconds	DOUBLE	Process start time in unix epoch seconds
process_stop_seconds	DOUBLE	Process stop in unix epoch seconds
process_term	TIMESTAMP	Process termination timestamp
read_operation_count	INT64	Count of number of read operations
read_transfer_kilobytes	INT64	Number of K bytes read
reg_createkeys	DOUBLE	Registry keys created
reg_deletekeys	DOUBLE	Registry keys deleted
reg_deletevalues	DOUBLE	Registry values deleted
reg_first_seen	TIMESTAMP	Earliest time seen
reg_last_seen	TIMESTAMP	Latest time seen
reg_reads	DOUBLE	Registry read events
reg_totals	DOUBLE	Total registry events
reg_writes	DOUBLE	Registry write events
sq_size	DOUBLE	Squared size of bytes in network packet. Ask Chris B!
tcp_accept_count	DOUBLE	TCP Accepts
tcp_connect_count	DOUBLE	TCP connects
tcp_disconnect_count	DOUBLE	TCP disconnects
tcp_reconnect_count	DOUBLE	TCP reconnects
tcp_rcv_count	DOUBLE	TCP packets received
tcp_rcv_size	DOUBLE	TCP bytes received
tcp_retransmit_count	DOUBLE	TCP packets retransmitted
tcp_rs_total	DOUBLE	TCP bytes total (send/received)
tcp_send_count	DOUBLE	TCP bytes sent
tcp_send_size	DOUBLE	TCP packets sent
tcp_send_vs_rcv	DOUBLE	Ratio of TCP bytes sent/received
tcp_tcpcopy_count	DOUBLE	TCP copy events. We think this is an event that is internal to the network stack on the host.
tcp_tcpcopy_size	DOUBLE	TCP copy bytes

Continued on next page

TABLE 25 – Continued from previous page

Column	Data Type	Description
token_elevation_type	INTEGER	Indicates UAC privilege status: 1 (Default) = no linked token, UAC disabled or non-admin account; 2 (Full) = elevated administrator with full rights after UAC approval; 3 (Limited) = filtered admin token before elevation with available full token; 4 = undocumented value, treat as unknown/reserved.
udp_rcv_count	DOUBLE	UDP bytes received
udp_rcv_size	DOUBLE	UDP events received
udp_rs_total	DOUBLE	Total UDP bytes sent/received
udp_send_count	DOUBLE	UDP packets sent
udp_send_size	DOUBLE	UDP bytes sent
udp_send_vs_rcv	DOUBLE	Ratio of UDP bytes sent/recieved
user_name	STRING	Username. Note that on windows there are many usernames that represent system or other background activity
write_operation_count	INT64	Count of number of write operations
write_transfer_kilobytes	INT64	Number of K bytes written

1.26. process_uber_summary

The process_uber_summary view is an enhanced version of the process_summary view, incorporating additional threat intelligence and labeling data. It combines process activity summaries with external threat indicators such as SIGMA rules, MITRE ATT&CK techniques, LOLBAS (Living Off the Land Binaries and Scripts), and NetworkX graph labels. This comprehensive view provides a detailed and enriched dataset for advanced threat analysis and detection.

Column	Data Type	Description
Close_Events	DOUBLE	Number of file close events
Create_Events	DOUBLE	Number of file create events
Delete_Events	DOUBLE	Number of file delete events
Read_Bytes	DOUBLE	File bytes read
Read_Events	DOUBLE	Number of file read events
Rename_Events	DOUBLE	Number of file rename events
SetInfo_Events	DOUBLE	
Write_Bytes	DOUBLE	File bytes written
Write_Events	DOUBLE	Number of file write events
agent_id	STRING	Agent ID is a unique id for a Wintap install on a host. It is created on initial startup after install.
arch	STRING	Host architecture
args	STRING	Process arguments. Note: as a simple string, no parsing done
avg_bytes	DOUBLE	Average bytes over the interval
avg_packets	DOUBLE	Average packets over the interval
commit_charge	INT64	Commit charge is the total amount of virtual memory guaranteed for all processes to fit in physical memory and the page file.
commit_peak	INT64	Total memory committed
conn_id_count	INT64	Number of unique network connection IDs (5-tuples)
cpu_cycle_count	INT64	Always zero (note: more than zero cycles were generally used in a process)
cpu_utilization	INTEGER	Ignore: unable to collect. This *should* be a value indicating the percentage of cpu utilized by the process over its life, but turns out be harder to collect than expected.
critical_num_sigma_hits	DOUBLE	Number of unique Sigma rules hit
dll_first_seen	TIMESTAMP	Earliest time seen
dll_last_seen	TIMESTAMP	Latest time seen
dll_num_uniq_files	INT64	Number of unique DDLs by name

Continued on next page

TABLE 26 – Continued from previous page

Column	Data Type	Description
dlls	STRING[]	List of DDL names as an array
duration_seconds	DOUBLE	Elapsed process execution in seconds
exit_code	INT64	Process exit code
file_first_seen	TIMESTAMP	Earliest time seen
file_id	STRING	Unique ID for a file. Hash of hostname+fully qualified filename
file_last_seen	TIMESTAMP	Latest time seen
file_md5	STRING	MD5 hash of the binary process/dll
file_num_raw_rows	DOUBLE	Number of rows of file activity from the raw data.
file_sha2	STRING	SHA2 hash of the file contents
filename	STRING	Fully qualified filename
first_seen	TIMESTAMP	Earliest time seen
hard_fault_count	INTEGER	Count of hard page faults
high_num_sigma_hits	INT64	Number of unique Sigma rules hit
high_num_sigma_rows	INT64	Number of times Sigma rules hit for this entity
hostname	STRING	Hostname data collected from
label_num_hits	INT64	Number of unique labels hit
label_num_sources	INT64	Number of unique sources of labels
label_num_uniq_annotations	INT64	Number of unique annotations
label_source	STRING	For now, only a single source: "networkx"
last_seen	TIMESTAMP	Latest time seen
lolbas_cats	STRING[]	List categories from hits
lolbas_mitre	STRING[]	List of Mitre codes from hits
lolbas_num_rows	INT64	Number of hits
lolbas_privs	STRING[]	List of privileges from hits
low_num_sigma_hits	INT64	Number of unique Sigma rules hit
low_num_sigma_rows	INT64	Number of times Sigma rules hit for this entity
max_bytes	DOUBLE	Max bytes in the interval
max_packets	DOUBLE	Max packets in the interval
medium_num_sigma_hits	INT64	Number of unique Sigma rules hit
medium_num_sigma_rows	INT64	Number of times Sigma rules hit for this entity
min_bytes	DOUBLE	Min bytes in the interval
min_packets	DOUBLE	Max packets in the interval
mitre_analytic_ids	STRING[]	List of analytic IDs from hits
mitre_analytic_types	STRING[][]	List of analytic types from hits
mitre_information_domains	STRING[]	List domains from hits. Ex: Analytic, Host, Network
mitre_num_rows	INT64	Number of hits
mitre_subtypes	STRING[][]	List of subtypes from hits. Ex: Map building, Anomaly, Host-flow, Process.
net_first_seen	TIMESTAMP	Earliest time seen
net_last_seen	TIMESTAMP	Latest time seen
net_num_raw_rows	DOUBLE	Number of rows in the raw data
net_recv_size	DOUBLE	Total bytes received in the interval
net_rs_total	DOUBLE	Total bytes sent/received in the interval
net_send_size	DOUBLE	Total bytes sent in the interval
net_send_vs_recv	DOUBLE	Ratio of bytes sent/received in the interval
net_total_events	DOUBLE	Total network events in the interval
net_total_size	DOUBLE	Total bytes (send/receive) in the interval
num_agent_id	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_args	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_file_md5	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_file_sha2	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.

Continued on next page

TABLE 26 – Continued from previous page

Column	Data Type	Description
num_null_filename	DOUBLE	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_parent_os_pid	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_parent_pid_hash	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_process_name	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_process_path	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_process_start	DOUBLE	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_process_stop	DOUBLE	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_uniq_file_hash	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
num_user_name	INT64	Number of unique values in the related column. Typically, the related column should only have 1 value.
os	STRING	Operating System
os_family	STRING	OS Family: windows, linux, osx
os_pid	INTEGER	Operating system process id
os_version	STRING	Operating System Version
parent_os_pid	INTEGER	OS Process ID of parent process
parent_pid_hash	STRING	PID_HASH of parent process
pid_hash	STRING	Globally unique process hash (hash from hostname, os pid, and start_time)
process_name	STRING	Filename of executable
process_path	STRING	Fully qualified path of the process executable
process_started	TIMESTAMP	Process start timestamp
process_started_seconds	DOUBLE	Process start time in unix epoch seconds
process_stop_seconds	DOUBLE	Process stop in unix epoch seconds
process_term	TIMESTAMP	Process termination timestamp
read_operation_count	INT64	Count of number of read operations
read_transfer_kilobytes	INT64	Number of K bytes read
reg_createkeys	DOUBLE	Registry keys created
reg_deletekeys	DOUBLE	Registry keys deleted
reg_deletevalues	DOUBLE	Registry values deleted
reg_first_seen	TIMESTAMP	Earliest time seen
reg_last_seen	TIMESTAMP	Latest time seen
reg_reads	DOUBLE	Registry read events
reg_totals	DOUBLE	Total registry events
reg_writes	DOUBLE	Registry write events
sq_size	DOUBLE	Squared size of bytes in network packet. Ask Chris B!
tcp_accept_count	DOUBLE	TCP Accepts
tcp_connect_count	DOUBLE	TCP connects
tcp_disconnect_count	DOUBLE	TCP disconnects
tcp_reconnect_count	DOUBLE	TCP reconnects
tcp_rcv_count	DOUBLE	TCP packets received
tcp_rcv_size	DOUBLE	TCP bytes received
tcp_retransmit_count	DOUBLE	TCP packets retransmitted
tcp_rs_total	DOUBLE	TCP bytes total (send/received)
tcp_send_count	DOUBLE	TCP bytes sent
tcp_send_size	DOUBLE	TCP packets sent
tcp_send_vs_rcv	DOUBLE	Ratio of TCP bytes sent/received

Continued on next page

TABLE 26 – Continued from previous page

Column	Data Type	Description
tcp_tcpcopy_count	DOUBLE	TCP copy events. We think this is an event that is internal to the network stack on the host.
tcp_tcpcopy_size	DOUBLE	TCP copy bytes
token_elevation_type	INTEGER	Indicates UAC privilege status: 1 (Default) = no linked token, UAC disabled or non-admin account; 2 (Full) = elevated administrator with full rights after UAC approval; 3 (Limited) = filtered admin token before elevation with available full token; 4 = undocumented value, treat as unknown/reserved.
total_sigma_hits	DOUBLE	Total Sigma hits over all criticality levels
udp_rcv_count	DOUBLE	UDP bytes received
udp_rcv_size	DOUBLE	UDP events received
udp_rs_total	DOUBLE	Total UDP bytes sent/received
udp_send_count	DOUBLE	UDP packets sent
udp_send_size	DOUBLE	UDP bytes sent
udp_send_vs_rcv	DOUBLE	Ratio of UDP bytes sent/received
user_name	STRING	Username. Note that on windows there are many usernames that represent system or other background activity
write_operation_count	INT64	Count of number of write operations
write_transfer_kilobytes	INT64	Number of K bytes written

1.27. sigma_labels

The sigma_labels table is a key component in the threat detection pipeline, as it links process or entity activity to specific SIGMA rules. SIGMA is a standardized rule format for describing log-based detection patterns, often used for identifying suspicious or malicious behavior in systems. The sigma_labels table provides a mapping between entities (like processes) and the SIGMA rules that matched their activity, along with metadata about the severity and type of the detection.

Column	Data Type	Description
analytic_id	STRING	Specific SIGMA rule hit. Value is a GUID
entity	STRING	Wintap entity ID (hash). The type of entity (PID_HASH, CONN_ID, etc) is defined in the ENTITY_TYPE column. Note: Currently, only PID_HASHes are identified.
entity_type	STRING	Wintap entity type. Determines what kind of hash is in the ENTITY column. Ex: PID_HASH, CONN_ID, FILE_ID
time	TIMESTAMP	Timestamp of activity

1.28. sigma_labels_summary

Aggregates data from sigma_labels by PID_HASH and pivots the severity levels into separate columns (e.g., critical_num_sigma_hits, high_num_sigma_hits).

Column	Data Type	Description
critical_num_sigma_hits	DOUBLE	Number of unique Sigma rules hit
high_num_sigma_hits	INT64	Number of unique Sigma rules hit
high_num_sigma_rows	INT64	Number of times Sigma rules hit for this entity
low_num_sigma_hits	INT64	Number of unique Sigma rules hit
low_num_sigma_rows	INT64	Number of times Sigma rules hit for this entity
medium_num_sigma_hits	INT64	Number of unique Sigma rules hit
medium_num_sigma_rows	INT64	Number of times Sigma rules hit for this entity
pid_hash	STRING	Globally unique process hash (hash from hostname, os pid, and start_time)