2012 DODGE GRAND CARAVAN / UNDER-HOOD POWER DISTRIBUTION

TIPM fuse cavity guide

A printable cross-reference for the fuse labels in the Integrated Power Module (TIPM). It covers the owner's-manual cartridge (J) and mini-fuse (M) schedule.

USE THE COVER LABEL	USE THE SCREENSHOT INDEX
J## = cartridge fuse; M## = mini-fuse. These are the cavity labels shown in the 2012 Owner's Manual schedule. Match the molded/printed code on your TIPM cover.	#1-#58 = the sequence in the supplied StartMyCar fuse-list screenshots. The index helps find a row in this PDF; it is not an OEM cavity number or a spatial position.

KEEP J12 SEPARATE FROM SCREENSHOT #12.
J12 is a 30 A cartridge cavity for the rear HVAC blower / radiator-fan motor. Screenshot index #12 maps to J14, a 40 A rear-window defogger circuit.

Location and safe use

The Owner's Manual places the TIPM in the engine compartment near the battery. Use the diagram and label inside the vehicle's own cover to locate a physical cavity; this PDF is a lookup table, not a top-down slot map.

Use only the specified fuse type and rating. If a correctly rated replacement opens again, the circuit needs diagnosis. Reinstall the cover fully latched. Optional-equipment listings may not apply to every van.

This crosswalk matches the supplied #1-#58 list to Owner's Manual J/M cavity assignments by circuit and rating. The vehicle cover remains the final check. #43* is a cautious crosswalk match for M32; verify that code against your cover before acting.

Source documents

Owner Guide: official 2012 Mopar PDF, TIPM pages 578-584
Supplied list cross-check: StartMyCar 2012 Grand Caravan fusebox page

Independent user reference, not an OEM-issued publication. It does not include relay positions, connector pinouts, wire routing, or repair procedures. If this crosswalk and the vehicle cover disagree, follow the cover and vehicle-specific service information.

FUSE SCHEDULE / CARTRIDGE FUSES

OEM J cavities

The index column refers to the supplied #1-#58 screenshot list. J12 is in the Owner's Manual schedule but has no number in that screenshot list.

INDEX	OEM CAVITY	FUSE	CIRCUIT / ASSIGNMENT
#15	J1	40 A / Green	Power folding seat
#13	J2	30 A / Pink	Power liftgate module
#17	J3	30 A / Pink	Rear door module
#19	J4	25 A / Natural	Driver door node
#20	J5	25 A / Natural	Passenger door node
#11	J6	40 A / Green	Antilock brakes pump / stability control system
#6	J7	30 A / Pink	Antilock brakes valve / stability control system
#18	J8	40 A / Green	Power memory seat - if equipped
#3	J9	40 A / Green	Partial Zero Emissions Vehicle motor / flex fuel - if equipped
#10	J10	30 A / Pink	Headlamp wash / manifold tuning valve - if equipped
#9	J11	30 A / Pink	Power sliding door module / anti-theft module - if equipped
-	J12	30 A / Pink	HVAC rear blower, radiator fan motor
#7	J13	60 A / Yellow	Ignition-off draw (IOD) - main
#12	J14	40 A / Green	Rear window defogger
#16	J15	40 A / Green	Front blower
#2	J17	40 A / Green	Starter solenoid
#1	J18	20 A / Blue	Powertrain control module trans range
#14	J19	60 A / Yellow	Radiator fan
#5	J20	30 A / Pink	Front wiper low / high
#4	J21	20 A / Blue	Front / rear washer
#8	J22	25 A / Natural	Sunroof module

Source: 2012 Dodge Grand Caravan Owner's Manual, printed pp. 579-580. Cavity labels and descriptions are transcribed as a quick lookup; confirm the actual cover label.

FUSE SCHEDULE / MINI-FUSES

OEM M cavities · M1-M19

The M code is the cavity label; the # value is the separate supplied screenshot-list sequence.

INDEX	OEM CAVITY	FUSE	CIRCUIT / ASSIGNMENT
#49	M1	15 A / Blue	Rear center brake lamp / brake switch
#50	M2	20 A / Yellow	Trailer lighting, front fog lamps, intelligent battery sensor (IBS)
#21	M3	20 A / Yellow	Front / rear axle locker, vacuum pump motor
#51	M4	10 A / Red	Trailer tow
#58	M5	25 A / Natural	Inverter
#57	M6	20 A / Yellow	Power outlet #1 (ACC), rain sensor, cigar lighter; outlet location varies by configuration
#52	M7	20 A / Yellow	Power outlet #2 (BATT / ACC SELECT), center seat or console-rear configuration
#46	M8	20 A / Yellow	Front heated seat - if equipped
#48	M9	20 A / Yellow	Rear heated seat - if equipped
#37	M10	15 A / Blue	Ignition-off draw: video system, satellite radio, DVD, hands-free module, universal garage door opener, vanity lamp, streaming video module - if equipped
#39	M11	10 A / Red	Climate control system
#38	M12	30 A / Green	Amplifier / radio
#42	M13	20 A / Yellow	Instrument cluster, SIREN, clock module, multi-function control switch - if equipped
#47	M14	20 A / Yellow	Trailer tow - if equipped
#22	M15	20 A / Yellow	Rear-view mirror, instrument cluster, multi-function control switch, tire-pressure monitor, glow-plug module - if equipped
#44	M16	10 A / Red	Airbag module / occupant-classification module
#33	M17	15 A / Blue	Left tail / license / park lamp, running lamps
#31	M18	15 A / Blue	Right tail / park / running lamp
#25	M19	25 A / Natural	Powertrain

Source: 2012 Dodge Grand Caravan Owner's Manual, printed pp. 581-582.

FUSE SCHEDULE / MINI-FUSES

OEM M cavities · M20-M38

Asterisk on #43* marks the cautious index-to-cavity crosswalk noted on page 1.

INDEX	OEM CAVITY	FUSE	CIRCUIT / ASSIGNMENT
#53	M20	15 A / Blue	Instrument-cluster interior light, switch bank, steering-column module, steering-wheel switch
#26	M21	20 A / Yellow	Powertrain
#28	M22	10 A / Red	Horn
#32	M23	10 A / Red	Horn
#40	M24	25 A / Natural	Rear wiper
#41	M25	20 A / Yellow	Fuel pump, diesel lift pump - if equipped
#30	M26	10 A / Red	Power-mirror switch, driver-window switch
#54	M27	10 A / Red	Wireless control module, keyless-entry module
#29	M28	10 A / Red	Powertrain, transmission-control module
#56	M29	10 A / Red	Occupant-classification module
#35	M30	15 A / Blue	Rear-wiper module, power-folding mirror
#27	M31	20 A / Yellow	Back-up lamps
#43*	M32	10 A / Red	Airbag module, THATCHUM - if equipped
#23	M33	10 A / Red	Powertrain
#45	M34	10 A / Red	Park assist, heater climate-control module, headlamp wash, compass, rear camera, door lamps, flashlight, diesel-heater / radiator-fan options - if equipped
#34	M35	10 A / Red	Heated mirrors
#55	M36	20 A / Yellow	Power outlet #3 (instrument panel or console center)
#36	M37	10 A / Red	Antilock brakes, stability control, stop lamp, fuel pump
#24	M38	25 A / Natural	Door lock / unlock motors, liftgate lock / unlock motors

Source: 2012 Dodge Grand Caravan Owner's Manual, printed pp. 583-584.