protected llwith inheritance PHP Hypertext Preprocessor SL Review POST = invisible to users, no limit LIJIA XU (11) dynamic page ilesdata GET = visible to exemple, limit 2k chans Private louly internally in class 2. php Kaipt Lunguage pho collecting form data X NEVER USE GET for sensitive Into Interface Hist of methods must implement echo "word!" & Isript control user-access Sphp
 interface Animal Interface {
 public function make Sound();
 }
} class Animals session_startl) > must before <1.00771/027 ?> | language constant ercryt data.... public sname; 2? php Lookies = used to identify used public tunction hill Eclass Dog implements Ani-A each php statement must end with: session starte) a small file that the server echo"Hi";]-malInterface { Meanment Sname = John detinelname, value \$_SESSION([color]="red"; embeds on 1* multilue 5 must start letter or _ (cuse-insanthe) public function make sound() {

| Compare to the control of the co SZSSION [name] = John computed define a const class Dag extends Animal } } // tov the class comments *1 only letter number or_ Vow types | Case sons: the ?> setcookie(name, value, expire, path abstract timethous can only appear Use global to access \$5tv/ng = "Hello!" Strhy \$ name = 1806. Ed = new Doyl); in abstract abstract class domain, secure, httpanly) war Interpor \$ string 2= "good; trunction getManel) \$d > hil); [* A class inheriting from an setcookies) function must before how store sensitive Float global & name; string strings Into in copies <? Php Boolean echo sname; abstract class must implement Mello good \$ value = "John" 11 output Bas abstractclass AMAY setrophiel "user, shalve, timel) +18400430); /') all the abstract methods getNamel); Tuse one Auto convert: Sit = "10" Variable Variables Trust to object private scolor; static properties or madical 14 L'sset (\$_0000006('user'))){ NULL Resource is sun = sitt + sint sa = hello's specify echo "value is: " \$ COOKTE['user']; abstract public function eati; without \$a=2; \$b= \$a++//\$a=3, \$hello='H2!; | auothor public tunction setColor (\$c) & Creating an \$a=2;\$b= H\$a |\$b=2|ec40\$\$a; 1/Hi! 377 smyfile=fopen ("file, txt", "w") \$this > color = \$C; 1190=3 \$6=3 7=== × 11 x equal y and type r: read only 12?php smytle=fopen ("name:txt") scope resolution and, or, xor, &2, 11, ! W: write only levase or new | stxt = "John vi"; elass Apple extends Fruits operator: a: write only append メノニソラメニオリ \$X xor \$ 11 either \$x or \$y is frite (smytile stat); public function eatur 7: newfor write only Iclass my Classing XY = y => X= XY. y true, but NOT both true \$txt="bavid In"; rt: read/write echo leathagilo State nt vend write levase or new twite (dwytile that) \$myP=253} \$ names = array ("A", "B", E") /* can have diff 7 sebj = new Apple Of echo my Class: my P; at: read/write (new 4 no) at: read/unite(new fno) fclose(\$myfile)
X+: create new for read write ?> echo snames[1] 11"B" | types in array /\$06; > eat(); Associate Array: \$ names = array ("A) , "B"=72 tcloseletilename); Appanding to a file: final begunned defines methods can Not echo frames["B"] // outputs 2 multi Dallay can add elseit do { 11 run >= Once be overvidden in child classes, also close an open tile it lisset (\$_POST['text'])} 11cdoe here 12=11e (\$147) { defines clusses can Not be inhallted 3 while (condition) \$ name = & POST(+ext); and return a Boden scho \$13 for linit; test; incre) { 十(秋7=到)毛 (sneess of tail close) shandle = topen | namestat echo \$x; for each only 3 11 notice the symbos works for arms = include associate arms stead = file (names tx) }else{ twite (shoulde, trame." vi) toreuch (soving as \$ value) { } Scount = court (\$kad); filoset handle); 3 ? > 3 11 outputs 20 forench (\$ army as skey > \$ value) { \$ \$ 2 = 1: continue = skipping over what represent torough (spend as sling) solay = Tue (torm method = "post"> Switch (Solay) { echo slive; Name: Cimput type: "text" for (\$1=0; \$1(10; \$i++) \$ case Mon : 4(\$) <9(aunt) { echo "first day"; name="text"/> if1\$27.2==0){ continue Montputs name = "submit"/> breur; include cuse The's echo \$2.11: 13579 required \$2+7; case "wed" LIform> stuck=array ("A",") to php 3 function tunname () ? case"Thui: 11 spead is Allay echo womaday return tuncnamel) tall turt on hreute predetined Variables Hold array: array push (stack, "c"," "); oop I can be accessed anywhere incode Print-ristach); Isthis 11 a pseudo-variable class Dogs _-construct Ull auto called eupo" Friday"; \$ GET and \$ POST > collect public sleys=4; when new object instant atend dutu was entered into a form bregle; \$ - Set and \$ - Post is to collect under public function displaye) { class Agrison ? public \$ name; <form action = "first php"
method = "post" > edio neekand; echo Hhis - 1 (egs; publics age; 3 1/ outputs work day -- destruct is public function -- construct Name: <i pput type="text"</p> without breaks will | name="name" /> explicit ? // unset(\$p) sname, sage) {
> now Dow(): Style=name = \$nowe; heep running! <input type="submit" sd = new Dog(); sthis > age = tayes 31/class \$P= new Person (name = "submit" value="submit/> K3php Echo \$ POST Crave 1 CIP> \$dz->legs=2; \$d2->d'splay() 1/2 "806",40); </tons