

DevOrSysAdminScripts

Laurent Frédéric Bernard François Lyaudet
<https://lyaudet.eu/laurent/>
Laurent.Lyaudet@gmail.com

May 13, 2026

Abstract

Some “small” useful scripts for enhancing development or system-administrators tasks

Current version: 2026-05-13

Current number of commits: 946

Current git SHA1: c1d29e22bbbd926a5841b58f3da7f428b82e9134

Code lines: 12620 total lines, 11610 not empty lines, 1010 empty lines.

Contents

1	Files trees	4
2	Notes on licenses and dependencies	8
3	Listing of files	11
3.1	build_and_checks_dependencies/build_and_checks.exec.sh.tpl . . .	11
3.2	build_and_checks_dependencies/build_dependencies_notes.exec.php	14
3.3	build_and_checks_dependencies/build_dependencies_notes.lib.php	15
3.4	build_and_checks_dependencies/build_md_from_printable_md.exec.sh	
		21
3.5	build_and_checks_dependencies/check_shell_scripts_beginnings.lib.sh	
		23
3.6	build_and_checks_dependencies/check_shell_scripts_indentation.lib.sh	
		25
3.7	build_and_checks_dependencies/check_URLs.lib.sh	29
3.8	build_and_checks_dependencies/common_build_and_checks.exec.sh	31
3.9	build_and_checks_dependencies/common_build_and_checks.exec.sh.tpl	
		52
3.10	build_and_checks_dependencies/common_options.lib.sh	72
3.11	build_and_checks_dependencies/comparisons.lib.sh	85
3.12	build_and_checks_dependencies/create_PDF.exec.sh	89

3.51	build_and_checks_variables/shellcheck_notes.txt	227
3.52	build_and_checks.exec.sh	229
3.53	COPYING	231
3.54	COPYING.LESSER	246
3.55	git_helpers/git_checks.lib.sh	250
3.56	git_helpers/post-commit	252
3.57	git_helpers/post_commit_renaming_comment.lib.sh	254
3.58	git_helpers/pre-commit	263
3.59	IMAP_transfert.exec.py	264
3.60	LiensUtiles.txt	270
3.61	miscellaneous/funny.sh	271
3.62	miscellaneous/spampty_data.txt	272
3.63	miscellaneous/string_escaping.html	272
3.64	miscellaneous/string_escaping.xhtml	273
3.65	README.md.tpl	273
3.66	string_escaping.lib.php	276
3.67	unicode.lib.php	284
3.68	upgrade_build_and_checks.exec.sh	295
3.69	wget_sha512.lib.sh	299

1 Files trees

```
.
├── build_and_checks_dependencies
│   ├── build_and_checks.exec.sh.tpl
│   ├── build_dependencies_notes.exec.php
│   ├── build_dependencies_notes.lib.php
│   ├── build_md_from_printable_md.exec.sh
│   ├── check_shell_scripts_beginnings.lib.sh
│   ├── check_shell_scripts_indentation.lib.sh
│   ├── check_URLs.lib.sh
│   ├── common_build_and_checks.exec.sh
│   ├── common_build_and_checks.exec.sh.tpl
│   ├── common_options.lib.sh
│   ├── comparisons.lib.sh
│   ├── create_PDF.exec.sh
│   ├── generate_from_template.lib.sh
│   ├── get_common_text_glob_patterns.lib.sh
│   ├── grammar_and_spelling_check.lib.sh
│   ├── licenses_templates
│   │   ├── build_licenses_templates.exec.sh
│   │   ├── license_file_header_AGPLv3+.tpl
│   │   ├── license_file_header_GPLv3+.tpl
│   │   └── license_file_header_LGPLv3+.tpl
│   ├── lines_counts.lib.sh
│   ├── lines_filters.lib.sh
│   ├── lines_maps.lib.sh
│   ├── overwrite_if_not_equal.lib.sh
│   ├── python_black_complement.lib.sh
│   ├── python_isort_complement.lib.sh
│   ├── repository_data.lib.sh
│   ├── shell_checks_complement.lib.sh
│   ├── split_score.exec.php
│   ├── split_score.lib.php
│   ├── strings_functions.lib.sh
│   ├── too_long_code_lines.lib.sh
│   ├── update_common_build_and_checks.exec.sh
│   └── update_or_check_files_names_listing.exec.sh
├── build_and_checks.exec.sh
├── build_and_checks_variables
│   ├── bandit_baseline.json
│   ├── bandit.ini
│   ├── black.toml
│   ├── dependencies_data.json
│   ├── dependencies_notes.txt
│   └── DevOrSysAdminScripts.html.tpl
```

- DevOrSysAdminScripts.tex
- DevOrSysAdminScripts.tex.tpl
- files_names_listing.txt
- .gitignore
- licenses_notes.txt
- phpcs_ruleset.xml
- phpmd_baseline.xml
- pylintrc.toml
- repository_data.txt
- repository_data.txt.tpl
- ruff.toml
- shellcheck.ini
- shellcheck_notes.txt
- COPYING
- COPYING.LESSER
- DevOrSysAdminScripts.html
- DevOrSysAdminScripts.pdf
- git_helpers
 - git_checks.lib.sh
 - post-commit
 - post_commit_renaming_comment.lib.sh
 - pre-commit
- .gitignore
- IMAP_transfert.exec.py
- LiensUtiles.txt
- miscellaneous
 - a_long_long_long_long_long_long_long_long_filename_so_that_you_c
 - an_see_that_it_works.txt
 - funny.sh
 - spampty_data.txt
 - string_escaping.html
 - string_escaping.xhtml
 - yet_another_long_long_long_long_long_long_long_long_filename_so_
 - that_you_can_see_that_it_works.txt
- README.html
- README.md
- README.md.tpl
- string_escaping.lib.php
- unicode.lib.php
- upgrade_build_and_checks.exec.sh
- wget_sha512.lib.sh

6 directories, 77 files

```

[ 12K May 13 18:53] ./
├── [4.0K May 13 18:52] build_and_checks_dependencies/
│   ├── [4.4K May 12 19:33] build_and_checks.exec.sh.tpl*
│   ├── [1.2K May 12 19:31] build_dependencies_notes.exec.php*
│   ├── [8.3K May 12 19:31] build_dependencies_notes.lib.php
│   ├── [4.2K May 12 19:34] build_md_from_printable_md.exec.sh*
│   ├── [3.1K May 12 19:34] check_shell_scripts_beginnings.lib.sh
│   ├── [5.3K May 12 19:37] check_shell_scripts_indentation.lib.sh
│   ├── [3.9K May 13 17:50] check_URLs.lib.sh
│   ├── [ 38K May 13 17:51] common_build_and_checks.exec.sh*
│   ├── [ 34K May 13 13:51] common_build_and_checks.exec.sh.tpl
│   ├── [ 19K May 12 19:37] common_options.lib.sh
│   ├── [6.2K May 12 19:37] comparisons.lib.sh
│   ├── [ 22K May 12 19:37] create_PDF.exec.sh*
│   ├── [3.7K May 12 19:32] generate_from_template.lib.sh
│   ├── [2.0K May 12 19:37] get_common_text_glob_patterns.lib.sh
│   ├── [3.3K May 12 19:37] grammar_and_spelling_check.lib.sh
│   ├── [4.0K May 12 21:21] licenses_templates/
│   │   ├── [ 16K May 12 21:21] build_licenses_templates.exec.sh*
│   │   ├── [ 720 May 12 19:16] license_file_header_AGPLv3+.tpl
│   │   ├── [ 699 May 12 19:17] license_file_header_GPLv3+.tpl
│   │   └── [ 720 May 12 19:18] license_file_header_LGPLv3+.tpl
│   ├── [6.0K May 13 17:48] lines_counts.lib.sh
│   ├── [ 15K May 13 15:25] lines_filters.lib.sh
│   ├── [3.0K May 12 19:37] lines_maps.lib.sh
│   ├── [3.3K May 12 19:37] overwrite_if_not_equal.lib.sh
│   ├── [2.4K May 12 19:37] python_black_complement.lib.sh
│   ├── [3.1K May 13 15:29] python_isort_complement.lib.sh
│   ├── [2.9K May 13 15:08] repository_data.lib.sh
│   ├── [3.9K May 12 19:37] shell_checks_complement.lib.sh
│   ├── [2.0K May 12 19:31] split_score.exec.php*
│   ├── [3.2K May 12 19:31] split_score.lib.php
│   ├── [ 47K May 13 16:32] strings_functions.lib.sh
│   ├── [4.7K May 13 17:45] too_long_code_lines.lib.sh
│   ├── [4.4K May 12 19:37] update_common_build_and_checks.exec.sh*
│   └── [6.0K May 12 19:37] update_or_check_files_names_listing.exec.sh*
├── [4.6K May 13 17:51] build_and_checks.exec.sh*
├── [4.0K May 13 18:53] build_and_checks_variables/
│   ├── [ 15 Jan 5 20:00] bandit_baseline.json
│   ├── [ 25 Jan 5 18:49] bandit.ini
│   ├── [ 30 Feb 28 20:30] black.toml
│   ├── [5.1K Apr 17 16:50] dependencies_data.json
│   ├── [4.3K Apr 17 16:57] dependencies_notes.txt
│   ├── [5.7K May 12 19:31] DevOrSysAdminScripts.html.tpl
│   ├── [ 33K May 13 18:49] DevOrSysAdminScripts.tex
│   └── [4.2K May 12 19:38] DevOrSysAdminScripts.tex.tpl

```

```

— [4.9K May 13 18:47] files_names_listing.txt
— [ 23 Mar 24 19:33] .gitignore
— [1.4K Apr 17 16:49] licenses_notes.txt
— [ 13K Apr 17 09:38] phpcs_ruleset.xml
— [2.2K Apr 17 14:32] phpmd_baseline.xml
— [ 678 Feb 24 22:38] pylintrc.toml
— [5.5K May 13 17:14] repository_data.txt
— [ 932 May 13 13:46] repository_data.txt.tpl
— [1.4K May 12 12:26] ruff.toml
— [ 166 Mar 24 19:33] shellcheck.ini
— [3.6K May 13 17:18] shellcheck_notes.txt
— [ 34K May 6 2024] COPYING
— [7.5K Dec 27 21:48] COPYING.LESSER
— [499K May 13 18:49] DevOrSysAdminScripts.html
— [415K May 13 18:49] DevOrSysAdminScripts.pdf
— [4.0K May 13 17:28] git_helpers/
— [3.8K May 13 17:22] git_checks.lib.sh
— [2.1K May 12 19:31] post-commit*
— [ 15K May 13 17:28] post_commit_renaming_comment.lib.sh
— [1.8K May 12 19:31] pre-commit*
— [ 8 Mar 26 10:37] .gitignore
— [8.4K May 12 19:31] IMAP_transfert.exec.py
— [1.1K Mar 31 19:59] LiensUtiles.txt
— [ 24K May 13 18:45] miscellaneous/
— [ 0 Mar 4 09:13]
— a_long_long_long_long_long_long_long_long_filename_so_that_you_c
— an_see_that_it_works.txt
— [1.3K May 12 19:37] funny.sh
— [ 94 Mar 3 19:56] spampty_data.txt
— [ 461 May 13 18:15] string_escaping.html
— [ 653 May 12 14:38] string_escaping.xhtml
— [ 0 Mar 4 09:13]
— yet_another_long_long_long_long_long_long_long_long_filename_so_
— that_you_can_see_that_it_works.txt
— [8.1K May 12 12:17] README.html
— [4.3K Mar 22 21:29] README.md
— [4.3K Mar 22 21:29] README.md.tpl
— [7.5K May 13 18:16] string_escaping.lib.php
— [ 17K May 13 18:18] unicode.lib.php
— [6.4K May 13 18:46] upgrade_build_and_checks.exec.sh*
— [2.5K May 12 19:37] wget_sha512.lib.sh

```

6 directories, 77 files

2 Notes on licenses and dependencies

This repository is dual licensed. All the Bash scripts source code is covered by GPLv3+. All the PHP scripts source code is covered by LGPLv3+. All the Python scripts source code is covered by LGPLv3+.

The text of the licenses is available at: <https://www.gnu.org/licenses/>. The git repository of this source code is also available at: <https://github.com/LLyaudet/DevOrSysAdminScripts/>. Clone it with this URL: `git@github.com:LLyaudet/DevOrSysAdminScripts.git`.

Here is a listing of the dependencies of the code in this repository:

- The following dependencies are GPLv3+ licensed:
basename, bash (and its builtins), cat, chmod, cp, cut, date, diff, dirname, env, find, grep, head, mkdir, mv, realpath, rm, sed, sha512sum, shellcheck, sort, tail, touch, wc, wget, xargs;
- The following dependencies are GPLv2+ licensed:
more, pandoc, pdftex, pdflatex, tree;
- The following dependencies are GPLv2 licensed:
git, pylint;
- The following dependencies are LGPLv2.1+ licensed:
notify-send;
- The following dependencies are MIT licensed:
black, isort, mypy, phpdoc, pip, ruff, xmllint;
- The following dependencies are Apache-2.0 licensed:
bandit;
- The following dependencies are BSD-3-Clause licensed:
phpcs, phpmd;
- php is licensed under PHP License v3.01;
- tex is licensed under Knuth license;
- pcregrep, pcre2grep has a custom license from Cambridge University, but PCRE2 has BSD-3-Clause WITH PCRE2-exception,
- python3 is licensed under PSF License Version 2 and the Zero-Clause BSD license.

Remark: Some commands listed under GPLv3+ are POSIX and can have different implementations under another license; for example, `utils` `coreutils` is MIT licensed, whilst GNU `coreutils` is GPLv3+ licensed.

Bash can be found at the following URLs:

<https://www.gnu.org/software/bash/>,

<https://tiswww.case.edu/php/chet/bash/bashtop.html>,
<https://savannah.gnu.org/projects/bash/>.

GNU coreutils can be found at the following URLs:

<https://www.gnu.org/software/coreutils/>,
<https://savannah.gnu.org/projects/coreutils/>.

utils coreutils can be found at the following URLs:

<https://uutils.github.io/coreutils/>,
<https://github.com/uutils/coreutils>.

diff (GNU diffutils) can be found at the following URLs:

<https://www.gnu.org/software/diffutils/>,
<https://savannah.gnu.org/projects/diffutils/>.

find, xargs (GNU findutils) can be found at the following URLs:

<https://www.gnu.org/software/findutils/>,
<https://savannah.gnu.org/projects/findutils/>.

grep (GNU grep) can be found at the following URLs:

<https://www.gnu.org/software/grep/>,
<https://savannah.gnu.org/projects/grep/>.

sed (GNU sed) can be found at the following URLs:

<https://www.gnu.org/software/sed/>,
<https://savannah.gnu.org/projects/sed/>.

ShellCheck can be found at the following URLs:

<https://www.shellcheck.net/>,
<https://github.com/koalaman/shellcheck>.

GNU Wget can be found at the following URLs:

<https://www.gnu.org/software/wget/>,
<https://savannah.gnu.org/projects/wget/>.

more of util-linux can be found at the following URLs:

<https://www.kernel.org/pub/linux/utils/util-linux/>,
<https://git.kernel.org/pub/scm/utils/util-linux/util-linux.git/>,
<https://github.com/util-linux/util-linux> official?.

pandoc can be found at the following URLs:

<https://pandoc.org/>,
<https://github.com/jgm/pandoc>.

pdftex/pdflatex can be found at the following URLs:

<https://www.tug.org/applications/pdftex/>,
<https://tug.org/texlive/svn/>.

tree can be found at the following URLs:

<https://oldmanprogrammer.net/source.php?dir=projects/tree>,
<https://gitlab.com/OldManProgrammer/unix-tree>,
<https://github.com/Old-Man-Programmer/tree>.

git can be found at the following URLs:

<https://git-scm.com/about>,
<https://github.com/git/git>.

pylint can be found at the following URLs:

<https://www.pylint.org/>,
<https://pylint.readthedocs.io/en/stable/>,

<https://github.com/pylint-dev/pylint>,
<https://pypi.org/project/pylint/>.
notify-send can be found at the following URLs:
<https://gitlab.gnome.org/GNOME/libnotify/>,
<https://gnome.pages.gitlab.gnome.org/libnotify/>.
black can be found at the following URLs:
<https://github.com/psf/black>,
<https://black.readthedocs.io/en/stable/>,
<https://pypi.org/project/black/>.
isort can be found at the following URLs:
<https://pycqa.github.io/isort/>,
<https://github.com/pycqa/isort/>,
<https://pypi.org/project/isort/>.
mypy can be found at the following URLs:
<https://mypy-lang.org/>,
<https://mypy.readthedocs.io/en/stable/>,
<https://github.com/python/mypy>,
<https://pypi.org/project/mypy/>.
phpdoc (phpDocumentor) can be found at the following URLs:
<https://phpdoc.org/>,
<https://docs.phpdoc.org/>,
<https://github.com/phpdocumentor/phpdocumentor>.
pip can be found at the following URLs:
<https://pip.pypa.io/en/stable/>,
<https://github.com/pypa/pip>,
<https://pypi.org/project/pip/> (egg and chicken ;)).
ruff can be found at the following URLs:
<https://docs.astral.sh/ruff/>,
<https://github.com/astral-sh/ruff>,
<https://pypi.org/project/ruff/>.
xmllint (libxml2) can be found at the following URLs:
<https://gitlab.gnome.org/GNOME/libxml2/-/wikis/home>,
<https://gitlab.gnome.org/GNOME/libxml2>.
bandit can be found at the following URLs:
<https://bandit.readthedocs.io/en/latest/>,
<https://github.com/PyCQA/bandit>,
<https://pypi.org/project/bandit/>.
phpcs (PHP_CodeSniffer) can be found at the following URLs:
https://github.com/PHPCSStandards/PHP_CodeSniffer,
https://packagist.org/packages/squizlabs/php_codesniffer.
phpmd can be found at the following URLs:
<https://phpmd.org/>,
<https://github.com/phpmd/phpmd>,
<https://packagist.org/packages/phpmd/phpmd>.
php can be found at the following URLs:
<https://www.php.net/>,

<https://github.com/php/php-src>.
tex can be found at the following URL:
<https://ctan.org/tex-archive/systems/knuth/dist/tex>.
pcregrep, pcre2grep can be found at the following URLs:
<https://www.pcre.org/>,
<https://pcre2project.github.io/pcre2/>,
<https://github.com/PCRE2Project/pcre1>,
<https://github.com/PCRE2Project/pcre2>,
<https://github.com/PCRE2Project/pcre2/blob/main/src/pcre2grep.c>.
python3 can be found at the following URLs:
<https://www.python.org/>,
<https://docs.python.org/3/>.
If you see something that I missed regarding my dependencies, please tell me/email me :).

3 Listing of files

3.1 build_and_checks_dependencies/build_and_checks.exec.sh.tpl

```
1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023–2026 Laurent Frédéric Bernard François Lyaudet
24 # The file "build_and_checks.exec.sh.tpl" was renamed from
25 # "build_and_checks.sh.tpl" to "build_and_checks.exec.sh.tpl".
26 # The file "build_and_checks.exec.sh" generated from the file
```

```

27 # "build_and_checks.sh.tpl" or "build_and_checks.exec.sh.tpl"
28 # was renamed from
29 # "build_and_checks.sh" to "build_and_checks.exec.sh".
30
31 build_and_checks() {
32     # $1=work_directory
33     # Options:
34     #   --check-download=y|keep (=keep to keep the downloaded files)
35     #   --verbose
36     local LFBFL_work_directory="."
37     if [[ -n "$1" ]]; then
38         LFBFL_work_directory="$1"
39     fi
40     readonly LFBFL_work_directory
41
42     local LFBFL_verbose=""
43     if [[ "$*" == *--verbose* ]]; then
44         printf "%s %s\n" "$0" "$*"
45         LFBFL_verbose="--verbose"
46     fi
47     readonly LFBFL_verbose
48
49     local LFBFL_check_download=""
50     if [[ "$*" == *--check-download=keep* ]]; then
51         LFBFL_check_download="--check-download=keep"
52     elif [[ "$*" == *--check-download=y* ]]; then
53         LFBFL_check_download="--check-download=y"
54     fi
55     readonly LFBFL_check_download
56
57     source ./wget_sha512.lib.sh
58
59     LFBFL_subdir="build_and_checks_dependencies"
60     mkdir --parents "${LFBFL_subdir}/licenses_templates"
61     local LFBFL_variables_directory
62     LFBFL_variables_directory="${LFBFL_work_directory}/"
63     LFBFL_variables_directory+="build_and_checks_variables"
64     readonly LFBFL_variables_directory
65     mkdir --parents -- "${LFBFL_variables_directory}/temp"
66     if [[ ! -f "${LFBFL_variables_directory}/.gitignore" ]]; then
67         printf "temp/\nupgrade_venvs_ts\n"
68         > "${LFBFL_variables_directory}/.gitignore"
69     fi
70
71     local LFBFL_dependencies_URL
72     LFBFL_dependencies_URL="https://raw.githubusercontent.com/LLyaudet/"

```

```

73 LFBFL_dependencies_URL+="DevOrSysAdminScripts/main/${LFBFL_subdir}"
74 readonly LFBFL_dependencies_URL
75
76 declare -r LFBFL_common_file_name="common_build_and_checks.exec.sh"
77 local LFBFL_script_download_URL
78 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/"
79 LFBFL_script_download_URL+="${LFBFL_common_file_name}"
80 readonly LFBFL_script_download_URL
81 declare -r LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_common_file_name}"
82 @sha512_common_build_and_checks.exec.sh@
83 wget_sha512 "${LFBFL_file_path}"\
84     "${LFBFL_script_download_URL}"\
85     "${LFBFL_correct_sha512}"\
86     "${LFBFL_verbose}"\
87     "${LFBFL_check_download}"
88 chmod +x "${LFBFL_file_path}"
89
90 "${LFBFL_file_path}" "${LFBFL_work_directory}"\
91     "${LFBFL_dependencies_URL}"\
92     "${LFBFL_verbose}"\
93     "${LFBFL_check_download}"
94 }
95
96 if [[ "$*" == *--fixed-point-build* ]]; then
97     printf -- "--fixed-point-build\n"
98     source ./build_and_checks_dependencies/lines_filters.lib.sh"
99     LFBFL_work_directory="."
100     if [[ -n "$1" ]]; then
101         LFBFL_work_directory="$1"
102     fi
103     LFBFL_variables_directory="${LFBFL_work_directory}/"
104     LFBFL_variables_directory+="build_and_checks_variables"
105     LFBFL_data_file_name="${LFBFL_variables_directory}/"
106     LFBFL_data_file_name+="repository_data.txt"
107     LFBFL_repository_name=""
108     grep_variable "${LFBFL_data_file_name}" repository_name\
109         --result-variable-prefix="LFBFL_"\
110         --replace-line-returns-by=""
111     # Touching the 3 following files first let us iterate
112     # upgrade_build_and_checks 2 times instead of 3 to reach
113     # a fixed point.
114     touch -- "${LFBFL_variables_directory}/${LFBFL_repository_name}.tex"
115     touch -- "${LFBFL_work_directory}/${LFBFL_repository_name}.pdf"
116     touch -- "${LFBFL_work_directory}/${LFBFL_repository_name}.html"
117     # The two iterations of build_and_checks needs to complete
118     # during the same minute to have a fixed point.

```

```

119 build_and_checks "$@"
120 # build_and_checks "$@" second iteration below
121 # Then calling this script without --fixed-point-build should not
122 # yield any new superficial modifications.
123 fi
124
125 build_and_checks "$@"

```

3.2 build_and_checks_dependencies/build_dependencies_notes.exec.php

```

1  #!/usr/bin/php
2  <?php
3
4  /**
5   This file is part of DevOrSysAdminScripts.
6
7   DevOrSysAdminScripts is free software:
8   you can redistribute it and/or modify it
9   under the terms of the GNU Lesser General Public License
10  as published by the Free Software Foundation,
11  either version 3 of the License,
12  or (at your option) any later version.
13
14  DevOrSysAdminScripts is distributed
15  in the hope that it will be useful,
16  but WITHOUT ANY WARRANTY;
17  without even the implied warranty of
18  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
19  See the GNU Lesser General Public License for more details.
20
21  You should have received a copy of
22  the GNU Lesser General Public License
23  along with DevOrSysAdminScripts.
24  If not, see <https://www.gnu.org/licenses/>.
25
26  ©Copyright 2023–2026 Laurent Frédéric Bernard François Lyaudet
27
28  @category Executable
29  @package DevOrSysAdminScripts
30  @author Laurent Lyaudet <laurent.lyaudet@gmail.com>
31  @copyright 2023–2026 Laurent Frédéric Bernard François Lyaudet
32  @license https://www.gnu.org/licenses/lgpl-3.0.html LGPLv3+
33  */
34
35  declare(strict_types=1);
36  declare(encoding='UTF-8');

```

```

37
38 require_once 'string_escaping.lib.php';
39 require_once 'build_dependencies_notes.lib.php';
40
41 build_dependencies_notes($argv[1]);
42 ?>

```

3.3 build_and_checks_dependencies/build_dependencies_notes.lib.php

```

1  <?php
2
3  /**
4   This file is part of DevOrSysAdminScripts.
5
6   DevOrSysAdminScripts is free software:
7   you can redistribute it and/or modify it
8   under the terms of the GNU Lesser General Public License
9   as published by the Free Software Foundation,
10  either version 3 of the License,
11  or (at your option) any later version.
12
13  DevOrSysAdminScripts is distributed
14  in the hope that it will be useful,
15  but WITHOUT ANY WARRANTY;
16  without even the implied warranty of
17  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
18  See the GNU Lesser General Public License for more details.
19
20  You should have received a copy of
21  the GNU Lesser General Public License
22  along with DevOrSysAdminScripts.
23  If not, see <https://www.gnu.org/licenses/>.
24
25  ©Copyright 2023–2026 Laurent Frédéric Bernard François Lyaudet
26  2026-03-26T11:59+01:00: This file was renamed from
27  "build_dependencies_notes.exec.php"
28  to
29  "build_dependencies_notes.lib.php".
30
31  @category Library
32  @package DevOrSysAdminScripts
33  @author Laurent Lyaudet <laurent.lyaudet@gmail.com>
34  @copyright 2023–2026 Laurent Frédéric Bernard François Lyaudet
35  @license https://www.gnu.org/licenses/lgpl-3.0.html LGPLv3+
36  */
37

```

```

38 declare(strict_types=1);
39 declare(encoding='UTF-8');
40
41 // require_once 'string_escaping.lib.php';
42
43
44
45 /**
46 This function looks at the dependencies data found in a work directory,
47 and generate three files: a txt file, a TeX file (.sub),
48 and an HTML file (.sub) with the data in a nicer format.
49
50 @param string $s_work_directory The directory where the work must be done.
51
52 @return void
53 */
54 function build_dependencies_notes(string $s_work_directory) : void {
55     $s_subdir1 = $s_work_directory.'/build_and_checks_variables';
56     $s_subdir2 = $s_subdir1.'/temp';
57     $s_data_file_path = $s_subdir1.'/dependencies_data.json';
58     $s_data = file_get_contents($s_data_file_path);
59     $arr_data = json_decode($s_data, true);
60     $s_data_file_path2 = $s_subdir1.'/repository_data.txt';
61     $s_data2 = file_get_contents($s_data_file_path2);
62     $i_max_line_length = 70;
63     foreach(explode("\n", $s_data2) as $s_line){
64         if(str_starts_with($s_line, 'max_line_length=')){
65             $i_max_line_length = (
66                 (int) substr($s_line, strlen('max_line_length='))
67             );
68             break;
69         }
70     }
71
72     $s_result_content1 = '';
73     $s_result_content2 = '';
74     $s_result_content3 = '';
75
76     foreach($arr_data as $arr_dependency){
77         $s_URL_word = 'URL';
78         if(count($arr_dependency['URLs']) > 1){
79             $s_URL_word .= 's';
80         }
81
82         $s_result_content3 .= "<p>\n";
83

```



```

84     $s_dependency1 = $arr_dependency['dependency_name'];
85     $s_dependency2 = string_escaping\TeX\escape_text($s_dependency1);
86     $s_dependency3 = string_escaping\HTML\escape_text($s_dependency1);
87
88     $s_sentence_end = ' can be found at the following '.$s_URL_word.':';
89     $s_result_content1 .= $s_dependency1.$s_sentence_end."\n";
90     $s_result_content2 .= $s_dependency2.$s_sentence_end."\n\\newline\n";
91     $s_result_content3 .= $s_dependency3.$s_sentence_end."<br>\n";
92
93     for(
94         $i = 0, $i_max = count($arr_dependency['URLs']) - 1;
95         $i <= $i_max;
96         ++$i
97     ){
98         $mixed_URL = $arr_dependency['URLs'][$i];
99         $s_comment = '';
100         $s_URL = '';
101         if(is_array($mixed_URL)){
102             $s_URL = $mixed_URL['URL'];
103             $s_comment = $mixed_URL['comment'];
104         }
105         else{
106             $s_URL = $mixed_URL;
107         }
108         $i_URL_length = strlen($s_URL);
109         $i_comment_length = strlen($s_comment);
110
111         $s_result_content1 .= $s_URL;
112         $i_previous_line_length = $i_URL_length;
113         if($i_comment_length > 0){
114             if(
115                 $i_previous_line_length + $i_comment_length + 1
116                 > $i_max_line_length
117             ){
118                 $s_result_content1 .= "\n";
119             }
120             else{
121                 $s_result_content1 .= ' ';
122             }
123             $s_result_content1 .= $s_comment;
124         }
125         $s_result_content1 .= "\n";
126
127         if($i_URL_length > 60){
128             $s_result_content2 .= (
129                 "{\\small\n"

```

```

130         .' \url{'.'$s_URL.}"\n"
131         .' }'
132     );
133     $i_previous_line_length = 1;
134 }
135 else{
136     $s_result_content2 .= '\url{'.'$s_URL.'}';
137     $i_previous_line_length = $i_URL_length + 6;
138 }
139 if($i === $i_max){
140     ++$i_previous_line_length;
141 }
142 else{
143     $i_previous_line_length += 9;
144 }
145 $s_comment2 = string_escaping\TeX\escape_text($s_comment);
146 $i_comment_length2 = strlen($s_comment2);
147 if($i_comment_length2 > 0){
148     if(
149         $i_previous_line_length + $i_comment_length2 + 1
150         > $i_max_line_length
151     ){
152         $s_result_content2 .= "\n";
153     }
154     else{
155         $s_result_content2 .= ' ';
156     }
157     $s_result_content2 .= $s_comment2;
158 }
159 if($i === $i_max){
160     $s_result_content2 .= ".\n";
161 }
162 else{
163     $s_result_content2 .= ",\\newline\n";
164 }
165
166 $s_result_content3 .= (
167     "<a\n"
168     .'href="'.string_escaping\HTML\escape_attribute($s_URL)."\n"
169     ."><span style=\"font-family:monospace\"\n"
170     .'>'.string_escaping\HTML\escape_text($s_URL)."</span\n"
171     .'></a>'
172 );
173 if($s_comment !== ''){
174     $s_result_content3 .= (
175         ' '.string_escaping\HTML\escape_text($s_comment)

```

```

176         );
177     }
178     if($i === $i_max){
179         $s_result_content3 .= ".\n";
180     }
181     else{
182         $s_result_content3 .= ",<br>\n";
183     }
184 }//end for urls
185
186 $s_result_content1 .= "\n";
187 $s_result_content2 .= "\n";
188 $s_result_content3 .= "</p>\n\n";
189 }//end foreach($arr_data as $arr_dependency)
190
191 // Add a "footer".
192 $s_closing_sentence = (
193     "If you see something that I missed regarding my dependencies,\n"
194     ".please tell me/email me :).\n"
195 );
196 $s_result_content1 .= $s_closing_sentence;
197 $s_result_content2 .= $s_closing_sentence;
198 $s_result_content3 .= "<p>\n".$s_closing_sentence."</p>\n";
199
200 // We overwrite results if needed.
201 $s_result_path1 = $s_subdir1.'/dependencies_notes.txt';
202 $s_existing_result_content1 = '';
203 if(file_exists($s_result_path1)){
204     $s_existing_result_content1 = file_get_contents($s_result_path1);
205 }
206 if($s_result_content1 !== $s_existing_result_content1){
207     file_put_contents($s_result_path1, $s_result_content1);
208 }
209 /*
210 Example of generated content of dependencies_notes.txt:
211 -----
212 more of util-linux can be found at the following URLs:
213 https://www.kernel.org/pub/linux/utils/util-linux/
214 https://git.kernel.org/pub/scm/utils/util-linux/util-linux.git/
215 https://github.com/util-linux/util-linux official?
216 -----
217 */
218 $s_result_path2 = $s_subdir2.'/dependencies_notes.tex.sub';
219 $s_existing_result_content2 = '';
220 if(file_exists($s_result_path2)){
221     $s_existing_result_content2 = file_get_contents($s_result_path2);

```

```

222     }
223     if($s_result_content2 != $s_existing_result_content2){
224         file_put_contents($s_result_path2, $s_result_content2);
225     }
226     /*
227     Example of generated content of dependencies_notes.tex.sub:
228     -----
229     more of util-linux can be found at the following URLs:\newline
230     \url{https://www.kernel.org/pub/linux/utils/util-linux/},\newline
231     {\small
232         \url{https://git.kernel.org/pub/scm/utils/util-linux/util-linux.git/}
233     },\newline
234     \url{https://github.com/util-linux/util-linux} official?.
235     -----
236     */
237     $s_result_path3 = $s_subdir2.'/dependencies_notes.html.sub';
238     $s_existing_result_content3 = '';
239     if(file_exists($s_result_path3)){
240         $s_existing_result_content3 = file_get_contents($s_result_path3);
241     }
242     if($s_result_content3 != $s_existing_result_content3){
243         file_put_contents($s_result_path3, $s_result_content3);
244     }
245     /*
246     Example of generated content of dependencies_notes.html.sub:
247     <p>
248     more of util-linux can be found at the following URLs:<br>
249     <a
250     href="https://www.kernel.org/pub/linux/utils/util-linux/"
251     ><span style="font-family:monospace"
252     >https://www.kernel.org/pub/linux/utils/util-linux/</span
253     ></a>,<br>
254     <a
255     href="https://git.kernel.org/pub/scm/utils/util-linux/util-linux.git/"
256     ><span style="font-family:monospace"
257     >https://git.kernel.org/pub/scm/utils/util-linux/util-linux.git/</span
258     ></a>,<br>
259     <a
260     href="https://github.com/util-linux/util-linux"
261     ><span style="font-family:monospace"
262     >https://github.com/util-linux/util-linux</span
263     ></a> official?.
264     </p>
265     */
266 } //end build_dependencies_notes()
267 ?>

```

3.4 build_and_checks_dependencies/build_md_from_printable_md.exec.sh

```
1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
24 # This file was renamed from "build_md_from_printable_md.sh"
25 # to "build_md_from_printable_md.exec.sh".
26
27 LFBFL_subdir="build_and_checks_dependencies"
28 # shellcheck source=common_options.lib.sh
29 source "${LFBFL_subdir}/common_options.lib.sh"
30 # shellcheck source=overwrite_if_not_equal.lib.sh
31 source "${LFBFL_subdir}/overwrite_if_not_equal.lib.sh"
32
33 build_md_from_printable_md() {
34     # Options:
35     #   --verbose
36     #   --work-directory=""
37     #   --base-name="README"
38     declare -i LFBFL_i_verbose=0
39     get_verbose_option "$@"
40     local LFBFL_work_directory=""
41     get_work_directory_option "$@"
42     declare -a LFBFL_return_traps_stack
43     init_return_trap
44     pushd_to_work_directory --trap-popd
```

```

45 can_continue_after_enhanced_pushd || return 1
46
47 local LFBFL_base_name
48 get_some_option LFBFL_base_name --base-name README README 1 "$@"
49 if [[ LFBFL_i_verbose -eq 1 && "${LFBFL_base_name}" != "README" ]]; then
50     printf "Searching md file: %s.\n" "${LFBFL_base_name}"
51 fi
52
53 # Remove line returns here to keep lines short.
54 local LFBFL_sed_expression
55 LFBFL_sed_expression='s/(\n[ ]*\[[a-zA-Z0-9:-]*\]): [^\n\\]*\\\\n/\\1/Mg'
56 LFBFL_sed_expression+=';s/(\n[ ]*<http[^\n\\]*)\\\\n/\\1/Mg'
57 LFBFL_sed_expression+=';s/(\n[ ]*-<http[^\n\\]*)\\\\n/\\1/Mg'
58 readonly LFBFL_sed_expression
59 # Since Markdown can contain code, it is limited to Markdown URLs.
60 # Hence, it is way more complicated than 's/\\\\n//Mg' expression
61 # in other files.
62 # Another downside is that more than one pass is needed.
63
64 if [[ -f "${LFBFL_base_name}.md.tpl" ]]; then
65     sed --regexp-extended --null-data\
66         --expression="${LFBFL_sed_expression}"\
67         --expression="${LFBFL_sed_expression}"\
68         --expression="${LFBFL_sed_expression}"\
69         --expression="${LFBFL_sed_expression}"\
70         -- "${LFBFL_base_name}.md.tpl"\
71         > "${LFBFL_base_name}.md.temp"
72     overwrite_if_not_equal "${LFBFL_base_name}.md"\
73         "${LFBFL_base_name}.md.temp"
74 else
75     printf "No file %s.md.tpl\n" "${LFBFL_base_name}"
76     # Unfortunately, we cannot return early, since we want to propose
77     # HTML file generation with pandoc from .md file,
78     # if the file .md.tpl doesn't exist.
79 fi
80
81 if [[ ! -f "${LFBFL_base_name}.md" ]]; then
82     printf "No file %s.md\n" "${LFBFL_base_name}"
83     return 1
84 fi
85
86 pandoc --from=markdown --to=html --standalone\
87     --shift-heading-level-by=-1 --output="${LFBFL_base_name}.html.temp"\
88     -- "${LFBFL_base_name}.md"
89 # Correcting pandoc HTML "by hand".
90 # https://github.com/jgm/pandoc/issues/10957

```

```

91 # With the most open-minded answer found on Internet ;) XD.
92 # This second sed expression is what I need,
93 # but it may be unsuitable for you.
94 # Other problems:
95 # https://github.com/jgm/pandoc/issues/11484
96 local LFBFL_prewrap="s~(code \{(\n|[\^])*\}(\n|[\^])*)"
97 LFBFL_prewrap+="~\1 white-space: pre-wrap;\n\3~M"
98 readonly LFBFL_prewrap
99 sed --in-place --regexp-extended\
100 --expression='s~( <meta .*) />~\1>~g'\
101 --expression='s~<html .*>~<html lang="en">~'\
102 --expression='/ code\{white-space: pre-wrap;\}/d'\
103 -- "${LFBFL_base_name}.html.temp"
104 sed --in-place --regexp-extended --null-data\
105 --expression='s~(<img(\n|[\^a-z0-9])(\n|[\^>])*) />~\1>~Mg'\
106 --expression="${LFBFL_prewrap}"\
107 -- "${LFBFL_base_name}.html.temp"
108 overwrite_if_not_equal "${LFBFL_base_name}.html"\
109 "${LFBFL_base_name}.html.temp"
110
111 # java -Xss128M -jar "../jar_venv/vnu.jar" --exit-zero-always\
112 # --verbose "${LFBFL_base_name}.html"
113 }
114
115 build_md_from_printable_md "$@"

```

3.5 build_and_checks_dependencies/check_shell_scripts_beginnings.lib.sh

```

1 #!/usr/bin/env bash
2 # This file is part of DevOrSysAdminScripts.
3 #
4 # DevOrSysAdminScripts is free software:
5 # you can redistribute it and/or modify it
6 # under the terms of the GNU General Public License
7 # as published by the Free Software Foundation,
8 # either version 3 of the License,
9 # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of

```

```

19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
24 # This file was renamed from "check_shell_scripts_beginnings.sh"
25 # to "check_shell_scripts_beginnings.lib.sh".
26
27 LFBFL_subdir="build_and_checks_dependencies"
28 # shellcheck source=common_options.lib.sh
29 source "${LFBFL_subdir}/common_options.lib.sh"
30 # shellcheck source=lines_filters.lib.sh
31 source "${LFBFL_subdir}/lines_filters.lib.sh"
32
33 declare -gr LFBFL_SHELL_SCRIPT_BEGINNING="#!/usr/bin/env bash"
34
35 check_one_shell_script_beginning() {
36     # $1=file_path
37     #
38     # declare -r LFBFL_file_path=$(basename -- "$1")
39     # if [[ "${LFBFL_file_path}" =~ license_file_header_.*\.sh ]]; then
40     #     return 0
41     # fi
42     # diff <(head --lines=1 -- "$1") <(printf '#!/usr/bin/env bash')
43     # -----
44     # is of course slower than
45     # -----
46     # diff <(head --lines=1 -- "$1") <(printf '#!/usr/bin/env bash')
47     # -----
48     # is of course slower than
49     # -----
50     declare -r LFBFL_head=$(head --lines=1 -- "$1")
51     [[ "${LFBFL_head}" == "${LFBFL_SHELL_SCRIPT_BEGINNING}" ]]\
52     || printf "%s:File has wrong shell script beginning.\n" "$1"
53 }
54
55 check_shell_scripts_beginnings() {
56     # Options:
57     #     --verbose
58     #     --work-directory=""
59     declare -i LFBFL_i_verbose=0
60     get_verbose_option "$@"
61     local LFBFL_work_directory=""
62     get_work_directory_option "$@"
63     declare -a LFBFL_return_traps_stack
64     init_return_trap

```



```

65 pushd_to_work_directory --trap-popd
66 can_continue_after_enhanced_pushd || return 1
67
68 # shopt -s globstar
69 # for LFBFL_file_path in **/*.sh; do
70 local LFBFL_file_path
71 local LFBFL_head
72 declare -r LFBFL_s_files_paths=$(
73     find . -type f -name "*.sh" -printf '%P\n'\
74     | relevant_find
75 )
76 if [[ -z "${LFBFL_s_files_paths}" ]]; then
77     [[ LFBFL_i_verbose -eq 1 ]]\
78     && printf "check_shell_scripts_beginnings: No file found.\n"
79     return
80 fi
81 declare -a LFBFL_arr_files_paths
82 mapfile -t LFBFL_arr_files_paths <<< "${LFBFL_s_files_paths}"
83 for LFBFL_file_path in "${LFBFL_arr_files_paths[@]}"; do
84     [[ LFBFL_i_verbose -eq 1 ]]\
85     && printf "%s:Checking shell script beginning.\n"\
86     "${LFBFL_file_path}"
87     check_one_shell_script_beginning "${LFBFL_file_path}"
88 done
89 }

```

3.6 build_and_checks_dependencies/check_shell_scripts_indentation.lib.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of

```

```

19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
24
25 LFBFL_subdir="build_and_checks_dependencies"
26 # shellcheck source=common_options.lib.sh
27 source "${LFBFL_subdir}/common_options.lib.sh"
28 # shellcheck source=lines_filters.lib.sh
29 source "${LFBFL_subdir}/lines_filters.lib.sh"
30
31 check_one_shell_script_indentation() {
32     # $1=file_path
33     declare -r LFBFL_NULL_PREVIOUS_LINE="--"
34     declare -i LFBFL_i_file_with_error=0
35     local LFBFL_some_line
36     local LFBFL_previous_line="${LFBFL_NULL_PREVIOUS_LINE}"
37     local LFBFL_line_end
38     local LFBFL_previous_line_end
39     declare -i LFBFL_i_line_length
40     declare -i LFBFL_i_line_end_length
41     declare -i LFBFL_i_line_start_length
42     local LFBFL_spacing
43     declare -i LFBFL_i_offset
44     local LFBFL_substring1
45     local LFBFL_substring2
46     declare -r LFBFL_pattern='^ *-e '
47
48     # This grep would have been enough without some sed commands.
49     declare -r LFBFL_s_lines=$(
50         grep --before-context=1 --extended-regexp --line-number\
51             --regexp='^ ( ) * ([^ ]|$)' --with-filename -- "$1"
52     )
53     if [[ -z "${LFBFL_s_lines}" ]]; then
54         return
55     fi
56
57     declare -a LFBFL_arr_lines
58     mapfile -t LFBFL_arr_lines <<< "${LFBFL_s_lines}"
59     readonly LFBFL_arr_lines
60
61     for LFBFL_some_line in "${LFBFL_arr_lines[@]"; do
62         if [[ "${LFBFL_some_line}" == "${LFBFL_NULL_PREVIOUS_LINE}" ]]; then
63             # When switching between code fragments, we reinit.
64             # It cannot happen for other grep output lines with line-number.

```

```

65     LFBFL_previous_line="${LFBFL_NULL_PREVIOUS_LINE}"
66     continue
67 fi
68 # Note how it's funny that this loop always work because we check
69 # shell scripts beginnings in another script and thus we always
70 # have a line before.
71 if [[ "${LFBFL_previous_line}" == "${LFBFL_NULL_PREVIOUS_LINE}" ]];
72 then
73     LFBFL_previous_line="${LFBFL_some_line}"
74     continue
75 fi
76 # Remove the name of the file and then the line number.
77 LFBFL_line_end=${LFBFL_some_line#*:}
78 LFBFL_line_end=${LFBFL_line_end#*:}
79 # But for the previous line '-' or ':' is used instead of ':'
80 # and filenames with '-' are much more frequent than with ':'...
81 LFBFL_i_line_length=${#LFBFL_some_line}
82 LFBFL_i_line_end_length=${#LFBFL_line_end}
83 LFBFL_i_line_start_length=$((
84     LFBFL_i_line_length - LFBFL_i_line_end_length
85 ))
86 LFBFL_i_offset=$((LFBFL_i_line_start_length - 2))
87 # Checking if increasing number of digits in the line numbers
88 # (99 -> 100).
89 LFBFL_substring1=${LFBFL_previous_line:${LFBFL_i_offset}:1}
90 # Nice puzzle below :) Look for comments above :)
91 case ${LFBFL_substring1} in
92     -) ((LFBFL_i_offset += 1));;
93     :) ((LFBFL_i_offset += 1));;
94     [0-9]) ((LFBFL_i_offset += 2));;
95     *) printf ":-(\n";;
96 esac
97 LFBFL_previous_line_end=${LFBFL_previous_line:${LFBFL_i_offset}}
98 if [[ "${LFBFL_line_end}" =~ ${LFBFL_pattern} ]]; then
99     # Line starts with spacing and -e
100     # Keep max spaces
101     LFBFL_spacing=${LFBFL_line_end%%-*}
102     LFBFL_i_offset=${#LFBFL_spacing}
103     LFBFL_substring1=${LFBFL_line_end:${LFBFL_i_offset}:3}
104     LFBFL_substring2=${LFBFL_previous_line_end:${LFBFL_i_offset}:3}
105     if [[ "${LFBFL_substring1}" != "${LFBFL_substring2}" ]]; then
106         printf "%s\n" "${LFBFL_some_line}"
107         LFBFL_i_file_with_error=1
108     fi
109 else
110     printf "%s\n" "${LFBFL_some_line}"

```

```

111         LFBFL_i_file_with_error=1
112     fi
113     LFBFL_previous_line="${LFBFL_some_line}"
114 done
115
116 if [[ LFBFL_i_file_with_error -eq 1 ]]; then
117     printf "%s:File has some lines with odd number of spaces.\n" "$1"
118 fi
119 }
120
121 check_shell_scripts_indentation(){
122     # Options:
123     #   --verbose
124     #   --work-directory=""
125     declare -i LFBFL_i_verbose=0
126     get_verbose_option "$@"
127     local LFBFL_work_directory=""
128     get_work_directory_option "$@"
129     declare -a LFBFL_return_traps_stack
130     init_return_trap
131     pushd_to_work_directory --trap-popd
132     can_continue_after_enhanced_pushd || return 1
133
134     # shopt -s globstar
135     # for LFBFL_file_path in **/*.sh; do
136     local LFBFL_file_path
137     declare -r LFBFL_s_files_paths=$(
138         find . -type f -name "*.sh" -printf '%P\n'\
139         | relevant_find
140     )
141     if [[ -z "${LFBFL_s_files_paths}" ]]; then
142         [[ LFBFL_i_verbose -eq 1 ]]\
143         && printf "check_shell_scripts_indentation: No file found.\n"
144         return
145     fi
146     declare -a LFBFL_arr_files_paths
147     mapfile -t LFBFL_arr_files_paths <<< "${LFBFL_s_files_paths}"
148     readonly LFBFL_arr_files_paths
149     for LFBFL_file_path in "${LFBFL_arr_files_paths[@]}"; do
150         [[ LFBFL_i_verbose -eq 1 ]]\
151         && printf "%s:Checking shell script indentation.\n"\
152             "${LFBFL_file_path}"
153         check_one_shell_script_indentation "${LFBFL_file_path}"
154     done
155 }

```

3.7 build_and_checks_dependencies/check_URLs.lib.sh

```
1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
24 # This file was renamed from "check_URLs.sh" to "check_URLs.lib.sh".
25
26 LFBFL_subdir="build_and_checks_dependencies"
27 # shellcheck source=common_options.lib.sh
28 source "${LFBFL_subdir}/common_options.lib.sh"
29 # shellcheck source=get_common_text_glob_patterns.lib.sh
30 source "${LFBFL_subdir}/get_common_text_glob_patterns.lib.sh"
31 # shellcheck source=lines_filters.lib.sh
32 source "${LFBFL_subdir}/lines_filters.lib.sh"
33
34 check_URLs() {
35     # Options:
36     #   --verbose
37     #   --work-directory=""
38     declare -i LFBFL_i_verbose=0
39     get_verbose_option "$@"
40     local LFBFL_work_directory=""
41     get_work_directory_option "$@"
42     declare -a LFBFL_return_traps_stack
43     init_return_trap
44     pushd_to_work_directory --trap-popd
```

```

45 can_continue_after_enhanced_pushd || return 1
46
47 enhanced_set_shell_option pipefail --trap-unset
48
49 get_COMMON_TEXT_FILES_GLOB_PATTERNS
50
51 declare -Ar LFBFL_substitutions=(
52     ["http://www.gnu.org/licenses/"]="https://www.gnu.org/licenses/"
53 )
54
55 local LFBFL_pattern
56 local LFBFL_base_file_name
57 local LFBFL_substitution
58 local LFBFL_substitution2
59 local LFBFL_file_path
60 local LFBFL_s_files_paths
61 declare -a LFBFL_arr_files_paths
62 for LFBFL_pattern in "${COMMON_TEXT_FILES_GLOB_PATTERNS[@]}"; do
63     if [[ LFBFL_i_verbose -eq 1 ]]; then
64         printf "check_URLs: Iterating on pattern: %s.\n" "${LFBFL_pattern}"
65     fi
66     find . -type f -name "${LFBFL_pattern}" -printf '%P\0'\
67         | xargs -0 grep --with-filename -- 'http:'\
68         | grep --invert-match " | xargs -0 grep --with-filename -- 'htt'\
69         | grep --invert-match --perl-regexp\
70         "(['\"])http(:(['\"]*)\\1.*(['\"])\https\\2\\3"\
71         | grep --invert-match 'http://www.w3.org/1999/xhtml'\
72         | grep --invert-match\
73         --regexp='http://www.w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd'\
74         --regexp='http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd'\
75         --regexp='http://www.w3.org/TR/xhtml1/DTD/xhtml1-frameset.dtd'\
76         --regexp='http://www.w3.org/TR/xhtml1/DTD/xhtml11.dtd'
77     # Second grep after xargs grep just above will remove false positives
78     # from substitutions that fit on one line.
79
80     LFBFL_s_files_paths=$(
81         find . -type f -name "${LFBFL_pattern}" -printf '%P\n'\
82         | relevant_find\
83         | not_main_html_find
84     )
85     if [[ -z "${LFBFL_s_files_paths}" ]]; then
86         [[ LFBFL_i_verbose -eq 1 ]] && printf "check_URLs: No file found.\n"
87         continue
88     fi
89     mapfile -t LFBFL_arr_files_paths <<< "${LFBFL_s_files_paths}"
90     for LFBFL_file_path in "${LFBFL_arr_files_paths[@]}"; do

```

```

91     LFBFL_base_file_name=$(basename -- "${LFBFL_file_path}")
92     [[ "${LFBFL_base_file_name}" != "check_URLs.lib.sh" ]] \
93         || continue
94     if [[ LFBFL_i_verbose -eq 1 ]]; then
95         printf "check_URLs: Handling the file: %s.\n" "${LFBFL_file_path}"
96     fi
97     for LFBFL_substitution in "${!LFBFL_substitutions[@]}"; do
98         LFBFL_substitution2=${LFBFL_substitutions[${LFBFL_substitution}]}
99         if grep --quiet "${LFBFL_substitution}" -- "${LFBFL_file_path}";
100         then
101             sed --in-place \
102                 --expression="s|${LFBFL_substitution}|${LFBFL_substitution2}|g" \
103                 -- "${LFBFL_file_path}"
104         fi
105     done
106 done
107 done
108 }

```

3.8 build_and_checks_dependencies/common_build_and_checks.exec.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023–2026 Laurent Frédéric Bernard François Lyaudet
24 # The file "common_build_and_checks.exec.sh.tpl" was renamed from
25 # "common_build_and_checks.sh.tpl" to

```

```

26 # "common_build_and_checks.exec.sh.tpl".
27 # The file "common_build_and_checks.exec.sh" generated from the file
28 # "common_build_and_checks.sh.tpl"
29 # or "common_build_and_checks.exec.sh.tpl"
30 # was renamed from
31 # "common_build_and_checks.sh" to "common_build_and_checks.exec.sh".
32
33 common_build_and_checks() {
34     # $1 LFBFL_work_directory
35     # $2 LFBFL_dependencies_URL
36     # Options:
37     #   --check-download=y|keep (=keep to keep the downloaded files)
38     #   --verbose
39     local LFBFL_work_directory="${1:-.}"
40     LFBFL_work_directory=$(realpath -- "${LFBFL_work_directory}")
41     declare -r LFBFL_dependencies_URL="$2"
42     local LFBFL_verbose=""
43     declare -i LFBFL_i_verbose=0
44     if [[ "$*" == *--verbose* ]]; then
45         printf "%s %s\n" "$0" "$*"
46         LFBFL_verbose="--verbose"
47         LFBFL_i_verbose=1
48     fi
49     readonly LFBFL_verbose
50     readonly LFBFL_i_verbose
51     local LFBFL_check_download=""
52     if [[ "$*" == *--check-download=keep* ]]; then
53         LFBFL_check_download="--check-download=keep"
54     elif [[ "$*" == *--check-download=y* ]]; then
55         LFBFL_check_download="--check-download=y"
56     fi
57     readonly LFBFL_check_download
58
59     declare -a LFBFL_some_common_options=(
60         "${LFBFL_verbose}"
61         "--work-directory=${LFBFL_work_directory}"
62     )
63
64     source ./wget_sha512.lib.sh
65
66     local LFBFL_subdir="build_and_checks_dependencies"
67     declare -r LFBFL_subdir2="${LFBFL_subdir}/licenses_templates"
68     declare -r LFBFL_subdir3="build_and_checks_variables"
69     local LFBFL_file_name
70     local LFBFL_script_download_URL
71     local LFBFL_file_path

```



```

72     local LFBFL_correct_sha512
73
74     wrapped_wget_sha512() {
75         wget_sha512 "${LFBFL_file_path}" \
76             "${LFBFL_script_download_URL}" \
77             "${LFBFL_correct_sha512}" \
78             "${LFBFL_verbose}" \
79             "${LFBFL_check_download}"
80     }
81
82     LFBFL_file_name="build_dependencies_notes.exec.php"
83     LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
84     LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
85     LFBFL_correct_sha512='7fa2566b939e765b70bc48b8b15e0dab50823b50bae40'
86     LFBFL_correct_sha512+='97eeaac9f573139f60427f1d2c02fcf6a1bb4f89e21f'
87     LFBFL_correct_sha512+='ca39fd98859a5f4714b6359588e10ef96ec623d'
88     wrapped_wget_sha512
89     chmod +x "${LFBFL_file_path}"
90
91     LFBFL_file_name="build_dependencies_notes.lib.php"
92     LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
93     LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
94     LFBFL_correct_sha512='3136857d20aafaabbdcd2468012a55991518430a39a07'
95     LFBFL_correct_sha512+='e2f80572c39e51bda8599ac830cdb9ce83cbb606d034'
96     LFBFL_correct_sha512+='f971f8734b103feae78d48867a29d4d566f2201'
97     wrapped_wget_sha512
98
99     LFBFL_file_name="build_md_from_printable_md.exec.sh"
100    LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
101    LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
102    LFBFL_correct_sha512='500e10ac1b95a41b4d8c045bc7347a7473e7392168d3d'
103    LFBFL_correct_sha512+='7f40f3d8a08e8fcb1f5229e548729684e33687afa759'
104    LFBFL_correct_sha512+='34330727bf8b1884d45fda03a5407c9a6d798ef'
105    wrapped_wget_sha512
106    chmod +x "${LFBFL_file_path}"
107
108    LFBFL_file_name="check_shell_scripts_beginnings.lib.sh"
109    LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
110    LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
111    LFBFL_correct_sha512='0b3e861820e09148a141142c8bb5549e7fa29d906dda9'
112    LFBFL_correct_sha512+='5e0fe44132610910687e6f767f1050646abelea262b8'
113    LFBFL_correct_sha512+='37b3a5d5e79497d0cdc42e43d3c74967f266abb'
114    wrapped_wget_sha512
115
116    LFBFL_file_name="check_shell_scripts_indentation.lib.sh"
117    LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"

```

```

118 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
119 LFBFL_correct_sha512='3596fddc4b20ce353facac3e355e38fadb5593caee3c8'
120 LFBFL_correct_sha512+='05464aedd513d34860a79b296efa648dae18717ae4c0'
121 LFBFL_correct_sha512+='24a6df11eb0549c4797643427c49c4f80947840'
122 wrapped_wget_sha512
123
124 LFBFL_file_name="check_URLs.lib.sh"
125 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
126 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
127 LFBFL_correct_sha512='57113f2f2f0de5bb1e1c080232b8529ac347920b545fa'
128 LFBFL_correct_sha512+='d919c69fb4ab19898239e70384d586beb0f1d5f7f274'
129 LFBFL_correct_sha512+='f900bf0f8fc0ac7368aac6ec5b28ec4cef8fddf'
130 wrapped_wget_sha512
131
132 LFBFL_file_name="common_options.lib.sh"
133 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
134 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
135 LFBFL_correct_sha512='3cfaf6cea99f67ade931cf21e9f49658c421e182dc4ac'
136 LFBFL_correct_sha512+='211be526f9d99b2e57a09844991cf0d2e6d5e49c19e2'
137 LFBFL_correct_sha512+='a63bf9e8f1e3fe999542e9a4e45e5196b375fa9'
138 wrapped_wget_sha512
139
140 LFBFL_file_name="comparisons.lib.sh"
141 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
142 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
143 LFBFL_correct_sha512='f146beca0d7b4046c140f3b2292cec4c31515cf8c7dbe'
144 LFBFL_correct_sha512+='7e9b07fc6dae32513aff6692c6286fa31055caff1a20'
145 LFBFL_correct_sha512+='9a6a7384568fea0b50b3cbb2608a3ed9e6e5125'
146 wrapped_wget_sha512
147
148 LFBFL_file_name="create_PDF.exec.sh"
149 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
150 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
151 LFBFL_correct_sha512='af85eaa0bedae5519bf02e44cf31d825d18f4c6248b9f'
152 LFBFL_correct_sha512+='b256832edacbee60deff90b74ea5935104b246e526de'
153 LFBFL_correct_sha512+='8fd5628649e464dd730b5923d35b53008d16487'
154 wrapped_wget_sha512
155 chmod +x "${LFBFL_file_path}"
156
157 LFBFL_file_name="generate_from_template.lib.sh"
158 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
159 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
160 LFBFL_correct_sha512='5f322f27bd20d7042c729f4cb5d8f14f587b5b415c77e'
161 LFBFL_correct_sha512+='4a224902d8d4cdeb1483639ae85d81873c9f20c175bb'
162 LFBFL_correct_sha512+='4de76a6eaa3dbcbf8a300368e65bbd5303afd3d'
163 wrapped_wget_sha512

```

```

164
165 LFBFL_file_name="get_common_text_glob_patterns.lib.sh"
166 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
167 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
168 LFBFL_correct_sha512='6c2f4b4ddc270c3d2ce9c88327efcb17510f10cac9b0f'
169 LFBFL_correct_sha512+='88ca3b585dcba2d7997bed299a97102bff194fccae8c'
170 LFBFL_correct_sha512+='771db6e735412ec6d0f9b3ccbe8416f95e79dfa'
171 wrapped_wget_sha512
172
173 LFBFL_file_name="grammar_and_spelling_check.lib.sh"
174 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
175 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
176 LFBFL_correct_sha512='88cc4f031c05d576a74ea7b14e79077f06c53b3b8a294'
177 LFBFL_correct_sha512+='e9b8ddcfe884db5e2cb5cebde09a8d9aea7980fb595c'
178 LFBFL_correct_sha512+='85c562462fb67e10503a471ee46da89c8f73b47'
179 wrapped_wget_sha512
180
181 # /licenses_templates/ -----
182 local LFBFL_dependencies_URL2
183 LFBFL_dependencies_URL2="${LFBFL_dependencies_URL}/licenses_templates"
184 readonly LFBFL_dependencies_URL2
185 LFBFL_file_name="build_licenses_templates.exec.sh"
186 LFBFL_script_download_URL="${LFBFL_dependencies_URL2}/${LFBFL_file_name}"
187 LFBFL_file_path="./${LFBFL_subdir2}/${LFBFL_file_name}"
188 LFBFL_correct_sha512='81b6dadd88516f4e560e00efc40e7dfa50a15e4ecade7'
189 LFBFL_correct_sha512+='adfff2504771cd49fa5cc68c1f91e6d63a125465c997'
190 LFBFL_correct_sha512+='5749f50cbd1017dc822bc546aed2d0d52413f52'
191 wrapped_wget_sha512
192 chmod +x "${LFBFL_file_path}"
193
194 LFBFL_file_name="license_file_header_AGPLv3+.tpl"
195 LFBFL_script_download_URL="${LFBFL_dependencies_URL2}/${LFBFL_file_name}"
196 LFBFL_file_path="./${LFBFL_subdir2}/${LFBFL_file_name}"
197 LFBFL_correct_sha512='5dc0dc20914c57feee2e26c2d329f020f221357b11b0d'
198 LFBFL_correct_sha512+='0ff6add69941ad953f8356b68be32cd60df8c56e91a2'
199 LFBFL_correct_sha512+='716c9cbf70ab8698e74e6aacc9c5439a93cc2bc'
200 wrapped_wget_sha512
201
202 LFBFL_file_name="license_file_header_GPLv3+.tpl"
203 LFBFL_script_download_URL="${LFBFL_dependencies_URL2}/${LFBFL_file_name}"
204 LFBFL_file_path="./${LFBFL_subdir2}/${LFBFL_file_name}"
205 LFBFL_correct_sha512='2d4b31697e78ba36ee0e3bd2b5393a57e15b5f5e62b2e'
206 LFBFL_correct_sha512+='802b812dcb087588f63cb92a851b21180be24bf5dee4'
207 LFBFL_correct_sha512+='eff7927244cde817e964512eaa1fb51d9064c01'
208 wrapped_wget_sha512
209

```

```

210 LFBFL_file_name="license_file_header_LGPLv3+.tpl"
211 LFBFL_script_download_URL="${LFBFL_dependencies_URL2}/${LFBFL_file_name}"
212 LFBFL_file_path="./${LFBFL_subdir2}/${LFBFL_file_name}"
213 LFBFL_correct_sha512='43976b6dc9a54fcea0440cfaf87530dade73efe22b5ae'
214 LFBFL_correct_sha512+='a968453c9c5ac1fdc4d3798fdd445fb38a53f997da82'
215 LFBFL_correct_sha512+='7c30be6b7ad42d5e56ae90aac5095b9526b203d'
216 wrapped_wget_sha512
217 # -----
218
219 LFBFL_file_name="lines_counts.lib.sh"
220 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
221 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
222 LFBFL_correct_sha512='d131e24ad596988a6953b9362b13e5d17330f3bd8013b'
223 LFBFL_correct_sha512+='03fc2acf74a6b931660a619149cce59d1fa3b075c11c'
224 LFBFL_correct_sha512+='0a5e9c85e847b437d7bc3b58f034c00df3c5702'
225 wrapped_wget_sha512
226
227 LFBFL_file_name="lines_filters.lib.sh"
228 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
229 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
230 LFBFL_correct_sha512='d7b9d7456d18965b7910516cf80f96b5a89b76c59f315'
231 LFBFL_correct_sha512+='f7558487f5f37afc8d0af13d4f11928f7c2bec8a03a1'
232 LFBFL_correct_sha512+='7b49a9a5f71945d2a6fff955ce98518f5305234'
233 wrapped_wget_sha512
234
235 LFBFL_file_name="lines_maps.lib.sh"
236 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
237 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
238 LFBFL_correct_sha512='ccb9115be582a5b39790725dc96a628beb21b0c9951e7'
239 LFBFL_correct_sha512+='03a7a7bc8ab2736e3940ed3df6a2fcb04e75350c10d7'
240 LFBFL_correct_sha512+='3e92bcfada424b4049cc6141d41bf7901c0525b'
241 wrapped_wget_sha512
242
243 LFBFL_file_name="overwrite_if_not_equal.lib.sh"
244 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
245 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
246 LFBFL_correct_sha512='378f03b8ba77430e05db4ef5d5926803b466a87e1a2ec'
247 LFBFL_correct_sha512+='eef0b51036f25460a93a018bd86d3f90146b4dfec9ab'
248 LFBFL_correct_sha512+='15c5d1d57a526296bbdc4a0c03650088f3e9653'
249 wrapped_wget_sha512
250
251 LFBFL_file_name="python_black_complement.lib.sh"
252 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
253 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
254 LFBFL_correct_sha512='4f08461329f1b78b58e54f675fb433aec363de2c96a91'
255 LFBFL_correct_sha512+='34ba5e96f3c77b93c9d7d6e28771a0b886501c286457'

```

```

256 LFBFL_correct_sha512+= 'a4a410389556f180f2dc8f66d7956bf5dd5acf2'
257 wrapped_wget_sha512
258
259 LFBFL_file_name="python_isort_complement.lib.sh"
260 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
261 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
262 LFBFL_correct_sha512='f91f3236ff9720412b31ec9fec2a5a5b3ef2424931815'
263 LFBFL_correct_sha512+= 'c0e6d1bd9821e86ef80a13a27a3f6d831327dc4b9698'
264 LFBFL_correct_sha512+= '5935a75793c87bdf735c4ae2a94327289d1c2ed'
265 wrapped_wget_sha512
266
267 LFBFL_file_name="repository_data.lib.sh"
268 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
269 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
270 LFBFL_correct_sha512='8148fae16b5853b5ed6ca141b73b32f6d8695d8d34a54'
271 LFBFL_correct_sha512+= '73ad8e8cc0dab61d92e87fd925b6f25c0632f70b2fee'
272 LFBFL_correct_sha512+= '78ee53b0e3af6aa25b3cc58d8769292c3e4def'
273 wrapped_wget_sha512
274
275 LFBFL_file_name="shell_checks_complement.lib.sh"
276 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
277 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
278 LFBFL_correct_sha512='143575d86b5fc0fd78e575b6e46054b0c8facaf2c6df6'
279 LFBFL_correct_sha512+= '07dc596b6db0494c2b88211d5e0e011dee9abe70a2fc'
280 LFBFL_correct_sha512+= 'b8f2bc04eb5cd50b248b0afe423103ee1cd568b'
281 wrapped_wget_sha512
282
283 LFBFL_file_name="split_score.exec.php"
284 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
285 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
286 LFBFL_correct_sha512='53830be68f0ef9f1a0b9b16ald98d0a744a38b8fd0ee6'
287 LFBFL_correct_sha512+= '68f592aba2df7ec6c856eb1ced9ced7f3d21251699f8'
288 LFBFL_correct_sha512+= '7a352c8624d03ce5d5503692488c9e14a9ffb62'
289 wrapped_wget_sha512
290 chmod +x "${LFBFL_file_path}"
291
292 LFBFL_file_name="split_score.lib.php"
293 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
294 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
295 LFBFL_correct_sha512='e8333a215a02dd7250b01a5a8e8ec862b735735a52a95'
296 LFBFL_correct_sha512+= '2c9339cba94ffc9c1605fa4d84487be100fdff644c2e'
297 LFBFL_correct_sha512+= 'e68cae3569fbc2b0a5525817b33e21425cd2e2f'
298 wrapped_wget_sha512
299
300 LFBFL_file_name="strings_functions.lib.sh"
301 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"

```

```

302 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
303 LFBFL_correct_sha512=' 526bdaeca9ce0732ad429c16410909f9f8014eef9e031'
304 LFBFL_correct_sha512+=' 837c428786b19bc31fea3eff6c8d93eea260b9076b67'
305 LFBFL_correct_sha512+=' 71d21220528e70aa08a1a2fb7579926db662ff2'
306 wrapped_wget_sha512
307
308 LFBFL_file_name="too_long_code_lines.lib.sh"
309 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
310 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
311 LFBFL_correct_sha512=' 4d7ca9bd78576a15d16a922d05a27cbea465773625e04'
312 LFBFL_correct_sha512+=' 7eb7aad23374e104a5c2dfcc25bee4bfa4452b55672e'
313 LFBFL_correct_sha512+=' 2f99319cec2ca95cf06503b78add0b1408febef'
314 wrapped_wget_sha512
315
316 LFBFL_file_name="update_or_check_files_names_listing.exec.sh"
317 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
318 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
319 LFBFL_correct_sha512=' 188fa5dbcab63be8e0f5b3c8997e099c7259f7c804433'
320 LFBFL_correct_sha512+=' 581c2c05a7d9c7bd3d82bc424e2021afa90cb9e9d6a5'
321 LFBFL_correct_sha512+=' f84f549ed692c18b6351983c31b875846d7e1af'
322 wrapped_wget_sha512
323 chmod +x "${LFBFL_file_path}"
324
325 # shellcheck source=check_shell_scripts_beginnings.lib.sh
326 source "${LFBFL_subdir}/check_shell_scripts_beginnings.lib.sh"
327 # shellcheck source=check_shell_scripts_indentation.lib.sh
328 source "${LFBFL_subdir}/check_shell_scripts_indentation.lib.sh"
329 # shellcheck source=check_URLs.lib.sh
330 source "${LFBFL_subdir}/check_URLs.lib.sh"
331 # shellcheck source=common_options.lib.sh
332 source "${LFBFL_subdir}/common_options.lib.sh"
333 # shellcheck source=comparisons.lib.sh
334 source "${LFBFL_subdir}/comparisons.lib.sh"
335 # shellcheck source=generate_from_template.lib.sh
336 source "${LFBFL_subdir}/generate_from_template.lib.sh"
337 # shellcheck source=get_common_text_glob_patterns.lib.sh
338 source "${LFBFL_subdir}/get_common_text_glob_patterns.lib.sh"
339 # shellcheck source=grammar_and_spelling_check.lib.sh
340 source "${LFBFL_subdir}/grammar_and_spelling_check.lib.sh"
341 # shellcheck source=lines_counts.lib.sh
342 source "${LFBFL_subdir}/lines_counts.lib.sh"
343 # shellcheck source=lines_filters.lib.sh
344 source "${LFBFL_subdir}/lines_filters.lib.sh"
345 # shellcheck source=lines_maps.lib.sh
346 source "${LFBFL_subdir}/lines_maps.lib.sh"
347 # shellcheck source=overwrite_if_not_equal.lib.sh

```

```

348 source "${LFBFL_subdir}/overwrite_if_not_equal.lib.sh"
349 # shellcheck source=python_black_complement.lib.sh
350 source "${LFBFL_subdir}/python_black_complement.lib.sh"
351 # shellcheck source=python_isort_complement.lib.sh
352 source "${LFBFL_subdir}/python_isort_complement.lib.sh"
353 # shellcheck source=shell_checks_complement.lib.sh
354 source "${LFBFL_subdir}/shell_checks_complement.lib.sh"
355 # shellcheck source=strings_functions.lib.sh
356 source "${LFBFL_subdir}/strings_functions.lib.sh"
357 # shellcheck source=too_long_code_lines.lib.sh
358 source "${LFBFL_subdir}/too_long_code_lines.lib.sh"
359
360 enhanced_set_bash_option extglob
361 # shellcheck source=repository_data.lib.sh
362 source "${LFBFL_subdir}/repository_data.lib.sh"
363 # shellcheck disable=SC2154,SC2309
364 [[ i_enhanced_set_bash_option_extglob_result -eq 0 ]]\
365     && enhanced_unset_bash_option extglob
366
367 declare -a LFBFL_return_traps_stack
368 init_return_trap
369
370 enhanced_set_shell_option pipefail --trap-unset
371
372 declare -a LFBFL_some_common_options2=("${LFBFL_some_common_options[@]}")
373 keep_options LFBFL_some_common_options2 --verbose
374
375 printf "Building license headers\n"
376 "${LFBFL_subdir2}/build_licenses_templates.exec.sh"\
377     "${LFBFL_some_common_options[@]}"
378
379 printf "Building README.md\n"
380 "${LFBFL_subdir}/build_md_from_printable_md.exec.sh"\
381     --work-directory="${LFBFL_work_directory}"\
382     --base-name=README\
383     "${LFBFL_verbose}"
384
385 printf "Building other Markdown files\n"
386 local LFBFL_some_directory
387 declare -r LFBFL_readme="${LFBFL_work_directory}/README.md.tpl"
388 local LFBFL_s_files_paths
389 LFBFL_s_files_paths=$(
390     find "${LFBFL_work_directory}" -type f -name "*.md.tpl"\
391     | relevant_find
392 )
393 declare -a LFBFL_arr_files_paths

```

```

394 if [[ -n "${LFBFL_s_files_paths}" ]]; then
395     mapfile -t LFBFL_arr_files_paths <<< "${LFBFL_s_files_paths}"
396     for LFBFL_file_path in "${LFBFL_arr_files_paths[@]}; do
397         [[ "${LFBFL_file_path}" == "${LFBFL_readme}" ]] && continue
398         printf "Found template %s.\n" "${LFBFL_file_path}"
399         LFBFL_some_directory=$(dirname -- "${LFBFL_file_path}")
400         LFBFL_file_name=$(basename -- "${LFBFL_file_path}")
401         LFBFL_file_name=${LFBFL_file_name%.md.tpl}
402         "./${LFBFL_subdir}/build_md_from_printable_md.exec.sh" \
403             --work-directory="${LFBFL_some_directory}" \
404             --base-name="${LFBFL_file_name}" \
405             "${LFBFL_verbose}"
406     done
407 fi
408
409 printf "Building dependencies_notes\n"
410 # https://github.com/php/php-src/issues/21538
411 local LFBFL_annoying_warning
412 LFBFL_annoying_warning="PHP Warning: declare(encoding=...) ignored"
413 LFBFL_annoying_warning=" because Zend multibyte feature is turned off"
414 LFBFL_annoying_warning=" by settings in"
415 readonly LFBFL_annoying_warning
416 php -f="./${LFBFL_subdir}/build_dependencies_notes.exec.php" \
417     -- "${LFBFL_work_directory}" \
418     2>&1 \
419     | grep --invert-match "${LFBFL_annoying_warning}"
420
421 declare -i LFBFL_i_directory_changed
422 pushd_to_work_directory
423 LFBFL_i_directory_changed=$?
424 can_continue_after_enhanced_pushd || return 1
425
426 local LFBFL_data_file_path="${LFBFL_subdir3}/repository_data.txt"
427
428 declare -i LFBFL_i_max_line_length
429 grep_variable "${LFBFL_data_file_path}" max_line_length \
430     --result-variable-prefix=LFBFL_i_
431
432 LFBFL_some_common_options+=(
433     "--max-line-length=${LFBFL_i_max_line_length}"
434 )
435 LFBFL_some_common_options2+=(
436     "--max-line-length=${LFBFL_i_max_line_length}"
437 )
438
439 declare -i LFBFL_i_upgrade_venvs=0

```



```

440 local LFBFL_upgrade_venvs_ts_file="${LFBFL_subdir3}/upgrade_venvs_ts"
441 readonly LFBFL_upgrade_venvs_ts_file
442 declare -i LFBFL_i_upgrade_venvs_ts
443 declare -i LFBFL_i_current_ts
444 local LFBFL_upgrade_venvs_answer
445
446 local LFBFL_upgrade_venvs_time_interval_in_seconds=""
447 get_upgrade_venvs_time_interval_in_seconds "${LFBFL_data_file_path}"\
448     "${LFBFL_some_common_options2[@]}"
449
450 if [[ -f "${LFBFL_upgrade_venvs_ts_file}" ]]; then
451     LFBFL_i_upgrade_venvs_ts=$(
452         stat --format %Y -- "${LFBFL_upgrade_venvs_ts_file}"
453     )
454     LFBFL_i_current_ts=$(date +%s)
455     ((LFBFL_i_current_ts -= LFBFL_i_upgrade_venvs_ts))
456     ((LFBFL_i_current_ts -= LFBFL_upgrade_venvs_time_interval_in_seconds))
457     if [[ LFBFL_i_current_ts -gt 0 ]]; then
458         LFBFL_i_upgrade_venvs=1
459     fi
460 else
461     LFBFL_i_upgrade_venvs=1
462 fi
463 if [[ LFBFL_i_upgrade_venvs -eq 1 ]]; then
464     local LFBFL_upgrade_venvs=""
465     grep_variable "${LFBFL_data_file_path}" upgrade_venvs\
466         --result-variable-prefix=LFBFL_
467     if [[ "${LFBFL_upgrade_venvs}" != "auto" ]]; then
468         read -r -n 1 -t 10\
469             -p "Upgrade venvs and composer global? [Y/n]"\
470             LFBFL_upgrade_venvs_answer
471         if [[ "${LFBFL_upgrade_venvs_answer}" == "n" ]]; then
472             LFBFL_i_upgrade_venvs=0
473         fi
474     fi
475 fi
476
477 printf "Analyzing too long lines\n"
478 too_long_code_lines "${LFBFL_some_common_options2[@]}"
479
480 printf "Analyzing URLs\n"
481 check_URLs "${LFBFL_some_common_options2[@]}" \
482     | relevant_grep
483
484 printf "Analyzing strange characters: hover over in doubt\n"
485 # shellcheck disable=SC1111

```

```

486 LFBFL_usual_characters="\x00-\x7Fàâéèëëîïôûç@'\"L|«»..."
487 grep --binary-files=without-match --color=always --exclude-dir .git\
488     --line-number --perl-regexp --recursive --\
489     "[^${LFBFL_usual_characters}]" .\
490     | relevant_grep
491
492 printf "Grammar and spelling check\n"
493 grammar_and_spelling_check "${LFBFL_data_file_path}"\
494     "${LFBFL_some_common_options2[@]}"
495
496 printf "Running shellcheck\n"
497 LFBFL_s_files_paths=$(
498     find . -type f -name "*.sh"\
499     | relevant_find
500 )
501 if [[ -n "${LFBFL_s_files_paths}" ]]; then
502     mapfile -t LFBFL_arr_files_paths <<< "${LFBFL_s_files_paths}"
503     for LFBFL_file_path in "${LFBFL_arr_files_paths[@]"; do
504         shellcheck --rcfile="${LFBFL_subdir3}/shellcheck.ini"\
505             -- "${LFBFL_file_path}"
506     done
507 fi
508 printf "Running shell_checks_complement\n"
509 shell_checks_complement "${LFBFL_some_common_options2[@]}"
510
511 printf "Analyzing shell scripts beginnings\n"
512 check_shell_scripts_beginnings "${LFBFL_some_common_options2[@]}" \
513     | relevant_grep
514
515 printf "Analyzing shell scripts indentation\n"
516 check_shell_scripts_indentation "${LFBFL_some_common_options2[@]}" \
517     | relevant_grep
518
519 printf -- "---Python---\n"
520
521 maybe_deactivate(){
522     if command -v deactivate
523     then
524         deactivate
525     fi
526 }
527
528 source_without_return_trap(){
529     declare -i LFBFL_i_no_return_traps=1
530     # shellcheck disable=SC1090,SC1091
531     source -- "$1"

```

```

532     }
533
534     printf "Running isort\n"
535     local LFBFL_isort_venv=""
536     grep_variable "${LFBFL_data_file_path}" isort_venv\
537         --result-variable-prefix=LFBFL_\
538         --replace-line-returns-by=""
539     if [[ -n "${LFBFL_isort_venv}" ]]; then
540         maybe_deactivate
541         source_without_return_trap "${LFBFL_isort_venv}/bin/activate"
542     fi
543     if [[ LFBFL_i_upgrade_venvs -eq 1 ]]; then
544         pip install --upgrade isort
545     fi
546     isort --profile=black .
547     if [[ -n "${LFBFL_isort_venv}" ]]; then
548         deactivate
549     fi
550     printf "Running python_isort_complement\n"
551     python_isort_complement "${LFBFL_some_common_options2[@]}"
552
553     printf "Running black\n"
554     # First, we update the configuration file with max_line_length.
555     local LFBFL_update_max_length="s/^line-length = [0-9]*$/"
556     LFBFL_update_max_length+="/line-length = ${LFBFL_i_max_line_length}/"
557     sed --regexp-extended --expression="${LFBFL_update_max_length}"\
558         "${LFBFL_subdir3}/black.toml"\
559         > "${LFBFL_subdir3}/black.toml.temp"
560     overwrite_if_not_equal "${LFBFL_subdir3}/black.toml"\
561         "${LFBFL_subdir3}/black.toml.temp"
562
563     local LFBFL_black_venv=""
564     grep_variable "${LFBFL_data_file_path}" black_venv\
565         --result-variable-prefix=LFBFL_\
566         --replace-line-returns-by=""
567     if [[ -n "${LFBFL_black_venv}" ]]; then
568         maybe_deactivate
569         source_without_return_trap "${LFBFL_black_venv}/bin/activate"
570     fi
571     if [[ LFBFL_i_upgrade_venvs -eq 1 ]]; then
572         pip install --upgrade black
573     fi
574     black --config="${LFBFL_subdir3}/black.toml" .
575     if [[ -n "${LFBFL_black_venv}" ]]; then
576         deactivate
577     fi

```

```

578 printf "Running python_black_complement\n"
579 python_black_complement "${LFBFL_some_common_options2[@]}"
580
581 printf "Probing if mypy should be runned\n"
582 local LFBFL_mypy_venv=""
583 grep_variable "${LFBFL_data_file_path}" mypy_venv\
584     --result-variable-prefix=LFBFL_\
585     --replace-line-returns-by=""
586 if [[ -n "${LFBFL_mypy_venv}" ]]; then
587     maybe_deactivate
588     source_without_return_trap "${LFBFL_mypy_venv}/bin/activate"
589 fi
590 if [[ LFBFL_i_upgrade_venvs -eq 1 ]]; then
591     pip install --upgrade mypy
592 fi
593 local LFBFL_directory_path
594 declare -i LFBFL_i_no_toml=1
595 LFBFL_s_files_paths=$(
596     find . -type f -name "pyproject.toml" \
597     | relevant_find
598 )
599 if [[ -n "${LFBFL_s_files_paths}" ]]; then
600     mapfile -t LFBFL_arr_files_paths <<< "${LFBFL_s_files_paths}"
601     for LFBFL_file_path in "${LFBFL_arr_files_paths[@]"; do
602         if grep --quiet "Typing :: Typed" -- "${LFBFL_file_path}"; then
603             printf "Running mypy\n"
604             LFBFL_directory_path=$(dirname -- "${LFBFL_file_path}")
605             mypy -- "${LFBFL_directory_path}"
606         fi
607         LFBFL_i_no_toml=0
608     done
609 fi
610 if [[ LFBFL_i_no_toml -eq 1 ]]; then
611     printf "Running mypy\n"
612     mypy .
613 fi
614 if [[ -n "${LFBFL_mypy_venv}" ]]; then
615     deactivate
616 fi
617
618 printf "Running bandit\n"
619 LFBFL_bandit_venv=""
620 grep_variable "${LFBFL_data_file_path}" bandit_venv\
621     --result-variable-prefix=LFBFL_\
622     --replace-line-returns-by=""
623 if [[ -n "${LFBFL_bandit_venv}" ]]; then

```

```

624     maybe_deactivate
625     source_without_return_trap "${LFBFL_bandit_venv}/bin/activate"
626 fi
627 if [[ LFBFL_i_upgrade_venvs -eq 1 ]]; then
628     pip install --upgrade bandit
629 fi
630 bandit --ini="${LFBFL_subdir3}/bandit.ini"\
631     --baseline="${LFBFL_subdir3}/bandit_baseline.json"\
632     --recursive .
633 # Saving new baseline in temp if necessary.
634 bandit --ini="${LFBFL_subdir3}/bandit.ini"\
635     --format=json\
636     --output="${LFBFL_subdir3}/temp/bandit_baseline.json"\
637     --recursive .
638 if [[ -n "${LFBFL_bandit_venv}" ]]; then
639     deactivate
640 fi
641
642 printf "Running pylint\n"
643 LFBFL_pylint_venv=""
644 grep_variable "${LFBFL_data_file_path}" pylint_venv\
645     --result-variable-prefix=LFBFL_\
646     --replace-line-returns-by=""
647 if [[ -n "${LFBFL_pylint_venv}" ]]; then
648     maybe_deactivate
649     source_without_return_trap "${LFBFL_pylint_venv}/bin/activate"
650 fi
651 if [[ LFBFL_i_upgrade_venvs -eq 1 ]]; then
652     pip install --upgrade pylint
653 fi
654 pylint --rcfile="${LFBFL_subdir3}/pylintrc.toml" --recursive=y .
655 if [[ -n "${LFBFL_pylint_venv}" ]]; then
656     deactivate
657 fi
658
659 printf "Running ruff\n"
660 LFBFL_ruff_venv=""
661 grep_variable "${LFBFL_data_file_path}" ruff_venv\
662     --result-variable-prefix=LFBFL_\
663     --replace-line-returns-by=""
664 if [[ -n "${LFBFL_ruff_venv}" ]]; then
665     maybe_deactivate
666     source_without_return_trap "${LFBFL_ruff_venv}/bin/activate"
667 fi
668 if [[ LFBFL_i_upgrade_venvs -eq 1 ]]; then
669     pip install --upgrade ruff

```

```

670 fi
671 ruff check --config="${LFBFL_subdir3}/ruff.toml"
672 if [[ -n "${LFBFL_ruff_venv}" ]]; then
673     deactivate
674 fi
675 printf -- "----Python end---\n"
676
677 printf -- "----PHP---\n"
678 printf "Running PHP native linter\n"
679 LFBFL_s_files_paths=$(
680     find . -type f -name "*.php" \
681     | relevant_find
682 )
683 if [[ -n "${LFBFL_s_files_paths}" ]]; then
684     mapfile -t LFBFL_arr_files_paths <<< "${LFBFL_s_files_paths}"
685     for LFBFL_file_path in "${LFBFL_arr_files_paths[@]}"; do
686         php --syntax-check -f="${LFBFL_file_path}"
687     done
688 fi
689
690 printf "Running PHP_CodeSniffer\n"
691 if [[ LFBFL_i_upgrade_venvs -eq 1 ]]; then
692     composer global require squizlabs/php_codesniffer
693 fi
694 phpcs --report=code\
695     --standard=build_and_checks_variables/phpcs_ruleset.xml
696
697 printf "Running PHPMD\n"
698 if [[ LFBFL_i_upgrade_venvs -eq 1 ]]; then
699     composer global require phpmd/phpmd
700 fi
701
702 declare -r LFBFL_phpmd_baseline="${LFBFL_subdir3}/phpmd_baseline.xml"
703 local LFBFL_temp_phpmd_baseline="${LFBFL_subdir3}/temp/"
704 LFBFL_temp_phpmd_baseline+="phpmd_baseline.xml"
705 readonly LFBFL_temp_phpmd_baseline
706
707 local LFBFL_phpmd_rulesets="cleancode, codesize, controversial, "
708 LFBFL_phpmd_rulesets+="design, naming, unusedcode"
709 readonly LFBFL_phpmd_rulesets
710
711 phpmd --color --baseline-file="${LFBFL_phpmd_baseline}" \
712     . text "${LFBFL_phpmd_rulesets}"
713 # Saving new baseline in temp if necessary.
714 rm "${LFBFL_temp_phpmd_baseline}"
715 phpmd --color --generate-baseline\

```

```

716     --baseline-file="${LFBFL_temp_phpmd_baseline}"\
717     . text "${LFBFL_phpmd_rulesets}"
718     sed --in-place --expression='s/" file="/"\n    file="/g'\
719     "${LFBFL_temp_phpmd_baseline}"
720     sed --in-place --regexp-extended\
721     --expression='s~(file=".*")/>~\1\n    />~g'\
722     "${LFBFL_temp_phpmd_baseline}"
723     diff --suppress-common-lines\
724     "${LFBFL_phpmd_baseline}" "${LFBFL_temp_phpmd_baseline}"\
725     | grep --invert-match --regexp='<!-- ' --regexp='^[0-9]\+d[0-9]\+${'
726
727     printf "Running phpDocumentor\n"
728     # shellcheck disable=SC2312
729     docker run --rm --volume="$(pwd):/data" phpdoc/phpdoc
730     printf -- "---PHP end---\n"
731
732     printf -- "---JS---\n"
733     local LFBFL_npm_lint_directories=""
734     grep_variable "${LFBFL_data_file_path}" npm_lint_directories\
735     --result-variable-prefix=LFBFL_
736     if [[ -n "${LFBFL_npm_lint_directories}" ]]; then
737         printf "Running ESLint\n"
738         local LFBFL_JS_directory
739         declare -a LFBFL_arr_paths
740         mapfile -t LFBFL_arr_paths <<< "${LFBFL_npm_lint_directories}"
741         for LFBFL_JS_directory in "${LFBFL_arr_paths[@]"; do
742             (cd -- "${LFBFL_JS_directory}" && npm run lint)
743         done
744     fi
745     printf -- "---JS end---\n"
746
747     [[ LFBFL_i_directory_changed -eq 0 ]] && popd_from_work_directory
748
749     printf "Checking listed files\n"
750     "./${LFBFL_subdir}/update_or_check_files_names_listing.exec.sh"\
751     "${LFBFL_some_common_options[@]}"
752
753     printf "Creating the PDF file of the listing of the source code\n"
754     "./${LFBFL_subdir}/create_PDF.exec.sh" "${LFBFL_some_common_options[@]}"
755
756     pushd_to_work_directory --trap-popd
757     can_continue_after_enhanced_pushd || return 1
758
759     if [[ -f "${LFBFL_subdir3}/post_build.sh" ]]; then
760         "./${LFBFL_subdir3}/post_build.sh" "${LFBFL_verbose}"
761     fi

```

```

762
763 printf "Running xmllint\n"
764 # In some cases, we need to handle a cache of common DTDs by hand.
765 # XHTML DTDs validation can yield errors:
766 # see https://gitlab.gnome.org/GNOME/libxml2/-/work_items/1119
767 # If you use Ubuntu/Debian, install w3c-sgml-lib instead.
768 LFBFL_file_name="xhtml1-strict.dtd"
769 LFBFL_a="https://www.w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd"
770 LFBFL_script_download_URL="${LFBFL_a}"
771 LFBFL_file_path="./${LFBFL_subdir3}/temp/${LFBFL_file_name}"
772 LFBFL_correct_sha512='fe11db06c0e1741a9c460fe4f9cf167bca57f4dbe9746'
773 LFBFL_correct_sha512+='d8352bf19947168c9bcf1ae212eca035824293abb1f9'
774 LFBFL_correct_sha512+='7a0ac02d67a82d098c34905c8cf1b213c891cc0'
775 wrapped_wget_sha512
776
777 LFBFL_file_name="xhtml1-transitional.dtd"
778 LFBFL_a="https://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd"
779 LFBFL_script_download_URL="${LFBFL_a}"
780 LFBFL_file_path="./${LFBFL_subdir3}/temp/${LFBFL_file_name}"
781 LFBFL_correct_sha512='4bece71fbf75d4a68a900ed29b8ba4efaela9dfa447a5'
782 LFBFL_correct_sha512+='6fc8583da2531f9eadb0fb57bc4cf4990a82ac1da3b3'
783 LFBFL_correct_sha512+='c2892e38c88d70a80f8464b21f0bdef79a04843'
784 wrapped_wget_sha512
785
786 LFBFL_file_name="xhtml1-frameset.dtd"
787 LFBFL_a="https://www.w3.org/TR/xhtml1/DTD/xhtml1-frameset.dtd"
788 LFBFL_script_download_URL="${LFBFL_a}"
789 LFBFL_file_path="./${LFBFL_subdir3}/temp/${LFBFL_file_name}"
790 LFBFL_correct_sha512='f969c36d5ba7f6de42261c223f1a8958c8205cb938127'
791 LFBFL_correct_sha512+='ea5b7fce6bb2e03a529259e41aa3a429c64177893614'
792 LFBFL_correct_sha512+='f05e3f22bd9c46c61b37a83eb702a6d72ce2872'
793 wrapped_wget_sha512
794
795 LFBFL_file_name="xhtml11.dtd"
796 LFBFL_a="https://www.w3.org/TR/xhtml11/DTD/xhtml11.dtd"
797 LFBFL_script_download_URL="${LFBFL_a}"
798 LFBFL_file_path="./${LFBFL_subdir3}/temp/${LFBFL_file_name}"
799 LFBFL_correct_sha512='aa08bb274fd8c4d33bbcaf8993b2357c4e6c03fbdc34b'
800 LFBFL_correct_sha512+='1c46bb98332e21db824a11de43da9c6388032149a148'
801 LFBFL_correct_sha512+='42992c6d92e728e275817b656d1c333ca7f5d04'
802 wrapped_wget_sha512
803
804 LFBFL_file_name="xhtml-lat1.ent"
805 LFBFL_a="https://www.w3.org/MarkUp/DTD/xhtml-lat1.ent"
806 LFBFL_script_download_URL="${LFBFL_a}"
807 LFBFL_file_path="./${LFBFL_subdir3}/temp/${LFBFL_file_name}"

```



```

808 LFBFL_correct_sha512=' 3243f33c056e71ae995d51cd2418979a505875d53ec9b'
809 LFBFL_correct_sha512+=' 17310268232dfbda19f5a52794973db47e51058cbcb4'
810 LFBFL_correct_sha512+=' 4a86838fed4937e6adc29636e12741bdc93af04'
811 wrapped_wget_sha512
812
813 LFBFL_file_name="xhtml-special.ent"
814 LFBFL_a="https://www.w3.org/MarkUp/DTD/xhtml-special.ent"
815 LFBFL_script_download_URL="${LFBFL_a}"
816 LFBFL_file_path="./${LFBFL_subdir3}/temp/${LFBFL_file_name}"
817 LFBFL_correct_sha512=' ec8e78745673044993b2d57242f834c94f1615a0df653'
818 LFBFL_correct_sha512+=' 5882b84c1df223f652ce536cc6b17eece23ab6dae518'
819 LFBFL_correct_sha512+=' 60a6e562b20f7ef5440004d56f9dbe4ea58913f'
820 wrapped_wget_sha512
821
822 LFBFL_file_name="xhtml-symbol.ent"
823 LFBFL_a="https://www.w3.org/MarkUp/DTD/xhtml-symbol.ent"
824 LFBFL_script_download_URL="${LFBFL_a}"
825 LFBFL_file_path="./${LFBFL_subdir3}/temp/${LFBFL_file_name}"
826 LFBFL_correct_sha512=' 47ca9edba10776c5ea8bba5c0e3ea8dc1a94b2830eada'
827 LFBFL_correct_sha512+=' 2ebf2bec1101ca05066ce09c0e06ecef1af7785c1179'
828 LFBFL_correct_sha512+=' 0a61c2efdc959d89610b7b4b084bb60af89cf72'
829 wrapped_wget_sha512
830
831 declare -r LFBFL_s_files_for_xmllint=$(
832     find . -type f -iregex ".*\\.\\(xml\\|xhtml\\)" "\
833     | relevant_find\
834     | sort
835 )
836 if [[ -n "${LFBFL_s_files_for_xmllint}" ]]; then
837     LFBFL_xmllint_use_downloaded_DTDs=""
838     grep_variable "${LFBFL_data_file_path}" xmllint_use_downloaded_DTDs\
839     --result-variable-prefix=LFBFL_
840
841     declare -a LFBFL_arr_files_for_xmllint
842     mapfile -t LFBFL_arr_files_for_xmllint\
843     <<< "${LFBFL_s_files_for_xmllint}"
844     readonly LFBFL_arr_files_for_xmllint
845     local LFBFL_xmllint_files_without_DTD=""
846     grep_variable_with_multiple_files "${LFBFL_data_file_path}" "\
847     xmllint_files_without_DTD\
848     --result-variable-prefix=LFBFL_
849     declare -a LFBFL_arr_xmllint_files_without_DTD
850     if [[ -n "${LFBFL_xmllint_files_without_DTD}" ]]; then
851         mapfile -t LFBFL_arr_xmllint_files_without_DTD\
852         <<< "${LFBFL_xmllint_files_without_DTD}"
853     fi

```

```

854 for LFBFL_file_path in "${LFBFL_arr_xmllint_files_without_DTD[@]"}"; do
855     [[ LFBFL_i_verbose -eq 1 ]]\
856     && printf "xmllint on %s\n" "${LFBFL_file_path}"
857     # see https://gitlab.gnome.org/GNOME/libxml2/-/issues/1100
858     # https://gitlab.gnome.org/GNOME/libxml2/-/work_items/1100
859     # xmllint --pedantic --noout -- "${LFBFL_file_path}"
860     xmllint --pedantic --noout "${LFBFL_file_path}"
861 done
862
863 local LFBFL_file_path2
864 for LFBFL_file_path in "${LFBFL_arr_files_for_xmllint[@]"}"; do
865     for LFBFL_file_path2 in "${LFBFL_arr_xmllint_files_without_DTD[@]"}";
866     do
867         if [[ "${LFBFL_file_path}" == "${LFBFL_file_path2}" ]]; then
868             LFBFL_file_path=""
869         fi
870     done
871     if [[ "${LFBFL_file_path}" == "" ]]; then
872         continue
873     fi
874     [[ LFBFL_i_verbose -eq 1 ]]\
875     && printf "xmllint on %s\n" "${LFBFL_file_path}"
876     if [[
877         "${LFBFL_file_path}" == *.xhtml
878         && "${LFBFL_xmllint_use_downloaded_DTDs}" == "true"
879     ]]; then
880         if grep --fixed-strings\
881             "http://www.w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd"\
882             "${LFBFL_file_path}"
883         then
884             xmllint --pedantic --noout\
885                 --dtdvalid "./${LFBFL_subdir3}/temp/xhtml1-strict.dtd"\
886                 "${LFBFL_file_path}"
887         elif grep --fixed-strings\
888             "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd"\
889             "${LFBFL_file_path}"
890         then
891             xmllint --pedantic --noout\
892                 --dtdvalid "./${LFBFL_subdir3}/temp/xhtml1-transitional.dtd"\
893                 "${LFBFL_file_path}"
894         elif grep --fixed-strings\
895             "http://www.w3.org/TR/xhtml1/DTD/xhtml1-frameset.dtd"\
896             "${LFBFL_file_path}"
897         then
898             xmllint --pedantic --noout\
899                 --dtdvalid "./${LFBFL_subdir3}/temp/xhtml1-frameset.dtd"

```

```

900         "${LFBFL_file_path}"
901     elif grep --fixed-strings\
902         "http://www.w3.org/TR/xhtml1/DTD/xhtml11.dtd"\
903         "${LFBFL_file_path}"
904     then
905         xmllint --pedantic --noout\
906             --dtdvalid "./${LFBFL_subdir3}/temp/xhtml11.dtd"\
907             "${LFBFL_file_path}"
908     else
909         printf "Unknown XHTML DTD.\n"
910     fi
911 else
912     xmllint --pedantic --noout --valid "${LFBFL_file_path}"
913 fi
914 done
915 fi
916 # -----
917
918 # -----
919 # It is at the end that all the HTML files are generated and that
920 # we can check there are no mistakes.
921 printf "Running Nu W3C HTML CSS and SVG validator\n"
922 local LFBFL_upgrade_vnu_jar_time_interval_in_seconds=""
923 grep_variable "${LFBFL_data_file_path}"\
924     upgrade_vnu_jar_time_interval_in_seconds\
925     --result-variable-prefix=LFBFL_
926
927 if [[ "${LFBFL_upgrade_vnu_jar_time_interval_in_seconds}" == "wat" ]];
928 then
929     LFBFL_upgrade_vnu_jar_time_interval_in_seconds=${RANDOM}
930 fi
931
932 declare -i LFBFL_i_vnu_jar_ts
933 local LFBFL_vnu_jar_path=""
934 grep_variable "${LFBFL_data_file_path}" vnu_jar_path\
935     --result-variable-prefix=LFBFL_\
936     --replace-line-returns-by=""
937 if [[ -f "${LFBFL_vnu_jar_path}" ]]; then
938     LFBFL_i_vnu_jar_ts=$(stat --format %Y -- "${LFBFL_vnu_jar_path}")
939     LFBFL_i_current_ts=$(date +%s)
940     ((LFBFL_i_current_ts -= LFBFL_i_vnu_jar_ts))
941     ((
942         LFBFL_i_current_ts -= LFBFL_upgrade_vnu_jar_time_interval_in_seconds
943     ))
944     if [[ LFBFL_i_current_ts -gt 0 ]]; then
945         printf $'/!\\ATTENTION: Nu W3C validator is too old./!\\n'

```

```

946     printf "Go get the latest version here:\n"
947     printf "https://github.com/validator/validator/releases\n"
948 fi
949 # vnu has false positives for xhtml.
950 local LFBFL_use_vnu_for_xhtml=""
951 grep_variable "${LFBFL_data_file_path}" use_vnu_for_xhtml\
952     --result-variable-prefix=LFBFL_
953 local LFBFL_find_regexp
954 if [[ "${LFBFL_use_vnu_for_xhtml}" == "true" ]]; then
955     LFBFL_find_regexp=".*\\.\\(css\\|html\\|svg\\|xhtml\\)"
956 else
957     LFBFL_find_regexp=".*\\.\\(css\\|html\\|svg\\)"
958 fi
959 declare -r LFBFL_s_files_for_Nu=$(
960     find . -type f -iregex "${LFBFL_find_regexp}"\
961     | relevant_find
962 )
963 if [[ -n "${LFBFL_s_files_for_Nu}" ]]; then
964     declare -a LFBFL_arr_files_for_Nu
965     mapfile -t LFBFL_arr_files_for_Nu <<< "${LFBFL_s_files_for_Nu}"
966     readonly LFBFL_arr_files_for_Nu
967     java -Xss128M -jar "${LFBFL_vnu_jar_path}" --exit-zero-always\
968         --verbose -- "${LFBFL_arr_files_for_Nu[@]}"
969 fi
970 fi
971 # -----
972
973 if [[ LFBFL_i_upgrade_venvs -eq 1 ]]; then
974     touch -- "${LFBFL_upgrade_venvs_ts_file}"
975 fi
976 }
977
978 common_build_and_checks "$@"

```

3.9 build_and_checks_dependencies/common_build_and_checks.exec.sh.tpl

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #

```

```

11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
24 # The file "common_build_and_checks.exec.sh.tpl" was renamed from
25 # "common_build_and_checks.sh.tpl" to
26 # "common_build_and_checks.exec.sh.tpl".
27 # The file "common_build_and_checks.exec.sh" generated from the file
28 # "common_build_and_checks.sh.tpl"
29 # or "common_build_and_checks.exec.sh.tpl"
30 # was renamed from
31 # "common_build_and_checks.sh" to "common_build_and_checks.exec.sh".
32
33 common_build_and_checks() {
34     # $1 LFBFL_work_directory
35     # $2 LFBFL_dependencies_URL
36     # Options:
37     # --check-download=y|keep (=keep to keep the downloaded files)
38     # --verbose
39     local LFBFL_work_directory="${1:-.}"
40     LFBFL_work_directory=$(realpath -- "${LFBFL_work_directory}")
41     declare -r LFBFL_dependencies_URL="$2"
42     local LFBFL_verbose=""
43     declare -i LFBFL_i_verbose=0
44     if [[ "$*" == *--verbose* ]]; then
45         printf "%s %s\n" "$0" "$*"
46         LFBFL_verbose="--verbose"
47         LFBFL_i_verbose=1
48     fi
49     readonly LFBFL_verbose
50     readonly LFBFL_i_verbose
51     local LFBFL_check_download=""
52     if [[ "$*" == *--check-download=keep* ]]; then
53         LFBFL_check_download="--check-download=keep"
54     elif [[ "$*" == *--check-download=y* ]]; then
55         LFBFL_check_download="--check-download=y"
56     fi

```

```

57     readonly LFBFL_check_download
58
59     declare -a LFBFL_some_common_options=(
60         "${LFBFL_verbose}"
61         "--work-directory=${LFBFL_work_directory}"
62     )
63
64     source ./wget_sha512.lib.sh
65
66     local LFBFL_subdir="build_and_checks_dependencies"
67     declare -r LFBFL_subdir2="${LFBFL_subdir}/licenses_templates"
68     declare -r LFBFL_subdir3="build_and_checks_variables"
69     local LFBFL_file_name
70     local LFBFL_script_download_URL
71     local LFBFL_file_path
72     local LFBFL_correct_sha512
73
74     wrapped_wget_sha512() {
75         wget_sha512 "${LFBFL_file_path}" \
76             "${LFBFL_script_download_URL}" \
77             "${LFBFL_correct_sha512}" \
78             "${LFBFL_verbose}" \
79             "${LFBFL_check_download}"
80     }
81
82     LFBFL_file_name="build_dependencies_notes.exec.php"
83     LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
84     LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
85     @sha512_build_dependencies_notes.exec.php@
86     wrapped_wget_sha512
87     chmod +x "${LFBFL_file_path}"
88
89     LFBFL_file_name="build_dependencies_notes.lib.php"
90     LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
91     LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
92     @sha512_build_dependencies_notes.lib.php@
93     wrapped_wget_sha512
94
95     LFBFL_file_name="build_md_from_printable_md.exec.sh"
96     LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
97     LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
98     @sha512_build_md_from_printable_md.exec.sh@
99     wrapped_wget_sha512
100    chmod +x "${LFBFL_file_path}"
101
102    LFBFL_file_name="check_shell_scripts_beginnings.lib.sh"

```

```

103 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
104 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
105 @sha512_check_shell_scripts_beginnings.lib.sh@
106 wrapped_wget_sha512
107
108 LFBFL_file_name="check_shell_scripts_indentation.lib.sh"
109 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
110 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
111 @sha512_check_shell_scripts_indentation.lib.sh@
112 wrapped_wget_sha512
113
114 LFBFL_file_name="check_URLs.lib.sh"
115 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
116 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
117 @sha512_check_URLs.lib.sh@
118 wrapped_wget_sha512
119
120 LFBFL_file_name="common_options.lib.sh"
121 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
122 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
123 @sha512_common_options.lib.sh@
124 wrapped_wget_sha512
125
126 LFBFL_file_name="comparisons.lib.sh"
127 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
128 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
129 @sha512_comparisons.lib.sh@
130 wrapped_wget_sha512
131
132 LFBFL_file_name="create_PDF.exec.sh"
133 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
134 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
135 @sha512_create_PDF.exec.sh@
136 wrapped_wget_sha512
137 chmod +x "${LFBFL_file_path}"
138
139 LFBFL_file_name="generate_from_template.lib.sh"
140 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
141 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
142 @sha512_generate_from_template.lib.sh@
143 wrapped_wget_sha512
144
145 LFBFL_file_name="get_common_text_glob_patterns.lib.sh"
146 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
147 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
148 @sha512_get_common_text_glob_patterns.lib.sh@

```

```

149 wrapped_wget_sha512
150
151 LFBFL_file_name="grammar_and_spelling_check.lib.sh"
152 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
153 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
154 @sha512_grammar_and_spelling_check.lib.sh@
155 wrapped_wget_sha512
156
157 # /licenses_templates/ -----
158 local LFBFL_dependencies_URL2
159 LFBFL_dependencies_URL2="${LFBFL_dependencies_URL}/licenses_templates"
160 readonly LFBFL_dependencies_URL2
161 LFBFL_file_name="build_licenses_templates.exec.sh"
162 LFBFL_script_download_URL="${LFBFL_dependencies_URL2}/${LFBFL_file_name}"
163 LFBFL_file_path="./${LFBFL_subdir2}/${LFBFL_file_name}"
164 @sha512_build_licenses_templates.exec.sh@
165 wrapped_wget_sha512
166 chmod +x "${LFBFL_file_path}"
167
168 LFBFL_file_name="license_file_header_AGPLv3+.tpl"
169 LFBFL_script_download_URL="${LFBFL_dependencies_URL2}/${LFBFL_file_name}"
170 LFBFL_file_path="./${LFBFL_subdir2}/${LFBFL_file_name}"
171 @sha512_license_file_header_AGPLv3+.tpl@
172 wrapped_wget_sha512
173
174 LFBFL_file_name="license_file_header_GPLv3+.tpl"
175 LFBFL_script_download_URL="${LFBFL_dependencies_URL2}/${LFBFL_file_name}"
176 LFBFL_file_path="./${LFBFL_subdir2}/${LFBFL_file_name}"
177 @sha512_license_file_header_GPLv3+.tpl@
178 wrapped_wget_sha512
179
180 LFBFL_file_name="license_file_header_LGPLv3+.tpl"
181 LFBFL_script_download_URL="${LFBFL_dependencies_URL2}/${LFBFL_file_name}"
182 LFBFL_file_path="./${LFBFL_subdir2}/${LFBFL_file_name}"
183 @sha512_license_file_header_LGPLv3+.tpl@
184 wrapped_wget_sha512
185 # -----
186
187 LFBFL_file_name="lines_counts.lib.sh"
188 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
189 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
190 @sha512_lines_counts.lib.sh@
191 wrapped_wget_sha512
192
193 LFBFL_file_name="lines_filters.lib.sh"
194 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"

```



```

195 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
196 @sha512_lines_filters.lib.sh@
197 wrapped_wget_sha512
198
199 LFBFL_file_name="lines_maps.lib.sh"
200 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
201 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
202 @sha512_lines_maps.lib.sh@
203 wrapped_wget_sha512
204
205 LFBFL_file_name="overwrite_if_not_equal.lib.sh"
206 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
207 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
208 @sha512_overwrite_if_not_equal.lib.sh@
209 wrapped_wget_sha512
210
211 LFBFL_file_name="python_black_complement.lib.sh"
212 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
213 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
214 @sha512_python_black_complement.lib.sh@
215 wrapped_wget_sha512
216
217 LFBFL_file_name="python_isort_complement.lib.sh"
218 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
219 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
220 @sha512_python_isort_complement.lib.sh@
221 wrapped_wget_sha512
222
223 LFBFL_file_name="repository_data.lib.sh"
224 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
225 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
226 @sha512_repository_data.lib.sh@
227 wrapped_wget_sha512
228
229 LFBFL_file_name="shell_checks_complement.lib.sh"
230 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
231 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
232 @sha512_shell_checks_complement.lib.sh@
233 wrapped_wget_sha512
234
235 LFBFL_file_name="split_score.exec.php"
236 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
237 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
238 @sha512_split_score.exec.php@
239 wrapped_wget_sha512
240 chmod +x "${LFBFL_file_path}"

```

```

241
242 LFBFL_file_name="split_score.lib.php"
243 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
244 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
245 @sha512_split_score.lib.php@
246 wrapped_wget_sha512
247
248 LFBFL_file_name="strings_functions.lib.sh"
249 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
250 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
251 @sha512_strings_functions.lib.sh@
252 wrapped_wget_sha512
253
254 LFBFL_file_name="too_long_code_lines.lib.sh"
255 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
256 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
257 @sha512_too_long_code_lines.lib.sh@
258 wrapped_wget_sha512
259
260 LFBFL_file_name="update_or_check_files_names_listing.exec.sh"
261 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/${LFBFL_file_name}"
262 LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_file_name}"
263 @sha512_update_or_check_files_names_listing.exec.sh@
264 wrapped_wget_sha512
265 chmod +x "${LFBFL_file_path}"
266
267 # shellcheck source=check_shell_scripts_beginnings.lib.sh
268 source "${LFBFL_subdir}/check_shell_scripts_beginnings.lib.sh"
269 # shellcheck source=check_shell_scripts_indentation.lib.sh
270 source "${LFBFL_subdir}/check_shell_scripts_indentation.lib.sh"
271 # shellcheck source=check_URLs.lib.sh
272 source "${LFBFL_subdir}/check_URLs.lib.sh"
273 # shellcheck source=common_options.lib.sh
274 source "${LFBFL_subdir}/common_options.lib.sh"
275 # shellcheck source=comparisons.lib.sh
276 source "${LFBFL_subdir}/comparisons.lib.sh"
277 # shellcheck source=generate_from_template.lib.sh
278 source "${LFBFL_subdir}/generate_from_template.lib.sh"
279 # shellcheck source=get_common_text_glob_patterns.lib.sh
280 source "${LFBFL_subdir}/get_common_text_glob_patterns.lib.sh"
281 # shellcheck source=grammar_and_spelling_check.lib.sh
282 source "${LFBFL_subdir}/grammar_and_spelling_check.lib.sh"
283 # shellcheck source=lines_counts.lib.sh
284 source "${LFBFL_subdir}/lines_counts.lib.sh"
285 # shellcheck source=lines_filters.lib.sh
286 source "${LFBFL_subdir}/lines_filters.lib.sh"

```

```

287 # shellcheck source=lines_maps.lib.sh
288 source "${LFBFL_subdir}/lines_maps.lib.sh"
289 # shellcheck source=overwrite_if_not_equal.lib.sh
290 source "${LFBFL_subdir}/overwrite_if_not_equal.lib.sh"
291 # shellcheck source=python_black_complement.lib.sh
292 source "${LFBFL_subdir}/python_black_complement.lib.sh"
293 # shellcheck source=python_isort_complement.lib.sh
294 source "${LFBFL_subdir}/python_isort_complement.lib.sh"
295 # shellcheck source=shell_checks_complement.lib.sh
296 source "${LFBFL_subdir}/shell_checks_complement.lib.sh"
297 # shellcheck source=strings_functions.lib.sh
298 source "${LFBFL_subdir}/strings_functions.lib.sh"
299 # shellcheck source=too_long_code_lines.lib.sh
300 source "${LFBFL_subdir}/too_long_code_lines.lib.sh"
301
302 enhanced_set_bash_option extglob
303 # shellcheck source=repository_data.lib.sh
304 source "${LFBFL_subdir}/repository_data.lib.sh"
305 # shellcheck disable=SC2154,SC2309
306 [[ i_enhanced_set_bash_option_extglob_result -eq 0 ]]\
307     && enhanced_unset_bash_option extglob
308
309 declare -a LFBFL_return_traps_stack
310 init_return_trap
311
312 enhanced_set_shell_option pipefail --trap-unset
313
314 declare -a LFBFL_some_common_options2=("${LFBFL_some_common_options[@]}")
315 keep_options LFBFL_some_common_options2 --verbose
316
317 printf "Building license headers\n"
318 "${LFBFL_subdir2}/build_licenses_templates.exec.sh"\
319     "${LFBFL_some_common_options[@]}"
320
321 printf "Building README.md\n"
322 "${LFBFL_subdir}/build_md_from_printable_md.exec.sh"\
323     --work-directory="${LFBFL_work_directory}"\
324     --base-name=README\
325     "${LFBFL_verbose}"
326
327 printf "Building other Markdown files\n"
328 local LFBFL_some_directory
329 declare -r LFBFL_readme="${LFBFL_work_directory}/README.md.tpl"
330 local LFBFL_s_files_paths
331 LFBFL_s_files_paths=(
332     find "${LFBFL_work_directory}" -type f -name "*.md.tpl"\

```

```

333     | relevant_find
334 )
335 declare -a LFBFL_arr_files_paths
336 if [[ -n "${LFBFL_s_files_paths}" ]]; then
337     mapfile -t LFBFL_arr_files_paths <<< "${LFBFL_s_files_paths}"
338     for LFBFL_file_path in "${LFBFL_arr_files_paths[@]}"; do
339         [[ "${LFBFL_file_path}" == "${LFBFL_readme}" ]] && continue
340         printf "Found template %s.\n" "${LFBFL_file_path}"
341         LFBFL_some_directory=$(dirname -- "${LFBFL_file_path}")
342         LFBFL_file_name=$(basename -- "${LFBFL_file_path}")
343         LFBFL_file_name=${LFBFL_file_name%.md.tpl}
344         "${LFBFL_subdir}/build_md_from_printable_md.exec.sh" \
345             --work-directory="${LFBFL_some_directory}" \
346             --base-name="${LFBFL_file_name}" \
347             "${LFBFL_verbose}"
348     done
349 fi
350
351 printf "Building dependencies_notes\n"
352 # https://github.com/php/php-src/issues/21538
353 local LFBFL_annoying_warning
354 LFBFL_annoying_warning="PHP Warning: declare(encoding=...) ignored"
355 LFBFL_annoying_warning=" because Zend multibyte feature is turned off"
356 LFBFL_annoying_warning=" by settings in"
357 readonly LFBFL_annoying_warning
358 php -f="${LFBFL_subdir}/build_dependencies_notes.exec.php" \
359     -- "${LFBFL_work_directory}" \
360     2>&1 \
361     | grep --invert-match "${LFBFL_annoying_warning}"
362
363 declare -i LFBFL_i_directory_changed
364 pushd_to_work_directory
365 LFBFL_i_directory_changed=$?
366 can_continue_after_enhanced_pushd || return 1
367
368 local LFBFL_data_file_path="${LFBFL_subdir3}/repository_data.txt"
369
370 declare -i LFBFL_i_max_line_length
371 grep_variable "${LFBFL_data_file_path}" max_line_length \
372     --result-variable-prefix=LFBFL_i_
373
374 LFBFL_some_common_options+=(
375     "--max-line-length=${LFBFL_i_max_line_length}"
376 )
377 LFBFL_some_common_options2+=(
378     "--max-line-length=${LFBFL_i_max_line_length}"

```

```

379 )
380
381 declare -i LFBFL_i_upgrade_venvs=0
382 local LFBFL_upgrade_venvs_ts_file="${LFBFL_subdir3}/upgrade_venvs_ts"
383 readonly LFBFL_upgrade_venvs_ts_file
384 declare -i LFBFL_i_upgrade_venvs_ts
385 declare -i LFBFL_i_current_ts
386 local LFBFL_upgrade_venvs_answer
387
388 local LFBFL_upgrade_venvs_time_interval_in_seconds=""
389 get_upgrade_venvs_time_interval_in_seconds "${LFBFL_data_file_path}" \
390     "${LFBFL_some_common_options2[@]}"
391
392 if [[ -f "${LFBFL_upgrade_venvs_ts_file}" ]]; then
393     LFBFL_i_upgrade_venvs_ts=$(
394         stat --format %Y -- "${LFBFL_upgrade_venvs_ts_file}"
395     )
396     LFBFL_i_current_ts=$(date +%s)
397     ((LFBFL_i_current_ts -= LFBFL_i_upgrade_venvs_ts))
398     ((LFBFL_i_current_ts -= LFBFL_upgrade_venvs_time_interval_in_seconds))
399     if [[ LFBFL_i_current_ts -gt 0 ]]; then
400         LFBFL_i_upgrade_venvs=1
401     fi
402 else
403     LFBFL_i_upgrade_venvs=1
404 fi
405 if [[ LFBFL_i_upgrade_venvs -eq 1 ]]; then
406     local LFBFL_upgrade_venvs=""
407     grep_variable "${LFBFL_data_file_path}" upgrade_venvs \
408         --result-variable-prefix=LFBFL_
409     if [[ "${LFBFL_upgrade_venvs}" != "auto" ]]; then
410         read -r -n 1 -t 10 \
411             -p "Upgrade venvs and composer global? [Y/n]" \
412             LFBFL_upgrade_venvs_answer
413         if [[ "${LFBFL_upgrade_venvs_answer}" == "n" ]]; then
414             LFBFL_i_upgrade_venvs=0
415         fi
416     fi
417 fi
418
419 printf "Analyzing too long lines\n"
420 too_long_code_lines "${LFBFL_some_common_options2[@]}"
421
422 printf "Analyzing URLs\n"
423 check_URLs "${LFBFL_some_common_options2[@]}" \
424     | relevant_grep

```

```

425
426 printf "Analyzing strange characters: hover over in doubt\n"
427 # shellcheck disable=SC1111
428 LFBFL_usual_characters="\x00-\x7Fàâéèëëîïôûç@'\"`|«»..."
429 grep --binary-files=without-match --color=always --exclude-dir .git\
430     --line-number --perl-regexp --recursive --\
431     "[^${LFBFL_usual_characters}]" .\
432     | relevant_grep
433
434 printf "Grammar and spelling check\n"
435 grammar_and_spelling_check "${LFBFL_data_file_path}"\
436     "${LFBFL_some_common_options2[@]}"
437
438 printf "Running shellcheck\n"
439 LFBFL_s_files_paths=$(
440     find . -type f -name "*.sh"\
441     | relevant_find
442 )
443 if [[ -n "${LFBFL_s_files_paths}" ]]; then
444     mapfile -t LFBFL_arr_files_paths <<< "${LFBFL_s_files_paths}"
445     for LFBFL_file_path in "${LFBFL_arr_files_paths[@]"; do
446         shellcheck --rcfile="${LFBFL_subdir3}/shellcheck.ini"\
447             -- "${LFBFL_file_path}"
448     done
449 fi
450 printf "Running shell_checks_complement\n"
451 shell_checks_complement "${LFBFL_some_common_options2[@]}"
452
453 printf "Analyzing shell scripts beginnings\n"
454 check_shell_scripts_beginnings "${LFBFL_some_common_options2[@]}" \
455     | relevant_grep
456
457 printf "Analyzing shell scripts indentation\n"
458 check_shell_scripts_indentation "${LFBFL_some_common_options2[@]}" \
459     | relevant_grep
460
461 printf -- "---Python---\n"
462
463 maybe_deactivate() {
464     if command -v deactivate
465     then
466         deactivate
467     fi
468 }
469
470 source_without_return_trap() {

```

```

471     declare -i LFBFL_i_no_return_traps=1
472     # shellcheck disable=SC1090,SC1091
473     source -- "$1"
474 }
475
476 printf "Running isort\n"
477 local LFBFL_isort_venv=""
478 grep_variable "${LFBFL_data_file_path}" isort_venv\
479     --result-variable-prefix=LFBFL_\
480     --replace-line-returns-by=""
481 if [[ -n "${LFBFL_isort_venv}" ]]; then
482     maybe_deactivate
483     source_without_return_trap "${LFBFL_isort_venv}/bin/activate"
484 fi
485 if [[ LFBFL_i_upgrade_venvs -eq 1 ]]; then
486     pip install --upgrade isort
487 fi
488 isort --profile=black .
489 if [[ -n "${LFBFL_isort_venv}" ]]; then
490     deactivate
491 fi
492 printf "Running python_isort_complement\n"
493 python_isort_complement "${LFBFL_some_common_options2[@]}"
494
495 printf "Running black\n"
496 # First, we update the configuration file with max_line_length.
497 local LFBFL_update_max_length="s/^line-length = [0-9]*$"
498 LFBFL_update_max_length+="/line-length = ${LFBFL_i_max_line_length}/"
499 sed --regexp-extended --expression="${LFBFL_update_max_length}"\
500     "${LFBFL_subdir3}/black.toml"\
501     > "${LFBFL_subdir3}/black.toml.temp"
502 overwrite_if_not_equal "${LFBFL_subdir3}/black.toml"\
503     "${LFBFL_subdir3}/black.toml.temp"
504
505 local LFBFL_black_venv=""
506 grep_variable "${LFBFL_data_file_path}" black_venv\
507     --result-variable-prefix=LFBFL_\
508     --replace-line-returns-by=""
509 if [[ -n "${LFBFL_black_venv}" ]]; then
510     maybe_deactivate
511     source_without_return_trap "${LFBFL_black_venv}/bin/activate"
512 fi
513 if [[ LFBFL_i_upgrade_venvs -eq 1 ]]; then
514     pip install --upgrade black
515 fi
516 black --config="${LFBFL_subdir3}/black.toml" .

```

```

517     if [[ -n "${LFBFL_black_venv}" ]]; then
518         deactivate
519     fi
520     printf "Running python_black_complement\n"
521     python_black_complement "${LFBFL_some_common_options2[@]}"
522
523     printf "Probing if mypy should be runned\n"
524     local LFBFL_mypy_venv=""
525     grep_variable "${LFBFL_data_file_path}" mypy_venv\
526         --result-variable-prefix=LFBFL\
527         --replace-line-returns-by=""
528     if [[ -n "${LFBFL_mypy_venv}" ]]; then
529         maybe_deactivate
530         source_without_return_trap "${LFBFL_mypy_venv}/bin/activate"
531     fi
532     if [[ LFBFL_i_upgrade_venvs -eq 1 ]]; then
533         pip install --upgrade mypy
534     fi
535     local LFBFL_directory_path
536     declare -i LFBFL_i_no_toml=1
537     LFBFL_s_files_paths=$(
538         find . -type f -name "pyproject.toml"\
539         | relevant_find
540     )
541     if [[ -n "${LFBFL_s_files_paths}" ]]; then
542         mapfile -t LFBFL_arr_files_paths <<< "${LFBFL_s_files_paths}"
543         for LFBFL_file_path in "${LFBFL_arr_files_paths[@]"; do
544             if grep --quiet "Typing :: Typed" -- "${LFBFL_file_path}"; then
545                 printf "Running mypy\n"
546                 LFBFL_directory_path=$(dirname -- "${LFBFL_file_path}")
547                 mypy -- "${LFBFL_directory_path}"
548             fi
549             LFBFL_i_no_toml=0
550         done
551     fi
552     if [[ LFBFL_i_no_toml -eq 1 ]]; then
553         printf "Running mypy\n"
554         mypy .
555     fi
556     if [[ -n "${LFBFL_mypy_venv}" ]]; then
557         deactivate
558     fi
559
560     printf "Running bandit\n"
561     LFBFL_bandit_venv=""
562     grep_variable "${LFBFL_data_file_path}" bandit_venv\

```



```

563     --result-variable-prefix=LFBFL\
564     --replace-line-returns-by=""
565 if [[ -n "${LFBFL_bandit_venv}" ]]; then
566     maybe_deactivate
567     source_without_return_trap "${LFBFL_bandit_venv}/bin/activate"
568 fi
569 if [[ LFBFL_i_upgrade_venvs -eq 1 ]]; then
570     pip install --upgrade bandit
571 fi
572 bandit --ini="${LFBFL_subdir3}/bandit.ini"\
573     --baseline="${LFBFL_subdir3}/bandit_baseline.json"\
574     --recursive .
575 # Saving new baseline in temp if necessary.
576 bandit --ini="${LFBFL_subdir3}/bandit.ini"\
577     --format=json\
578     --output="${LFBFL_subdir3}/temp/bandit_baseline.json"\
579     --recursive .
580 if [[ -n "${LFBFL_bandit_venv}" ]]; then
581     deactivate
582 fi
583
584 printf "Running pylint\n"
585 LFBFL_pylint_venv=""
586 grep_variable "${LFBFL_data_file_path}" pylint_venv\
587     --result-variable-prefix=LFBFL\
588     --replace-line-returns-by=""
589 if [[ -n "${LFBFL_pylint_venv}" ]]; then
590     maybe_deactivate
591     source_without_return_trap "${LFBFL_pylint_venv}/bin/activate"
592 fi
593 if [[ LFBFL_i_upgrade_venvs -eq 1 ]]; then
594     pip install --upgrade pylint
595 fi
596 pylint --rcfile="${LFBFL_subdir3}/pylintrc.toml" --recursive=y .
597 if [[ -n "${LFBFL_pylint_venv}" ]]; then
598     deactivate
599 fi
600
601 printf "Running ruff\n"
602 LFBFL_ruff_venv=""
603 grep_variable "${LFBFL_data_file_path}" ruff_venv\
604     --result-variable-prefix=LFBFL\
605     --replace-line-returns-by=""
606 if [[ -n "${LFBFL_ruff_venv}" ]]; then
607     maybe_deactivate
608     source_without_return_trap "${LFBFL_ruff_venv}/bin/activate"

```

```

609 fi
610 if [[ LFBFL_i_upgrade_venvs -eq 1 ]]; then
611     pip install --upgrade ruff
612 fi
613 ruff check --config="${LFBFL_subdir3}/ruff.toml"
614 if [[ -n "${LFBFL_ruff_venv}" ]]; then
615     deactivate
616 fi
617 printf -- "----Python end---\n"
618
619 printf -- "----PHP---\n"
620 printf "Running PHP native linter\n"
621 LFBFL_s_files_paths=$(
622     find . -type f -name "*.php" \
623     | relevant_find
624 )
625 if [[ -n "${LFBFL_s_files_paths}" ]]; then
626     mapfile -t LFBFL_arr_files_paths <<< "${LFBFL_s_files_paths}"
627     for LFBFL_file_path in "${LFBFL_arr_files_paths[@]};" do
628         php --syntax-check -f="${LFBFL_file_path}"
629     done
630 fi
631
632 printf "Running PHP_CodeSniffer\n"
633 if [[ LFBFL_i_upgrade_venvs -eq 1 ]]; then
634     composer global require squizlabs/php_codesniffer
635 fi
636 phpcs --report=code\
637     --standard=build_and_checks_variables/phpcs_ruleset.xml
638
639 printf "Running PHPMD\n"
640 if [[ LFBFL_i_upgrade_venvs -eq 1 ]]; then
641     composer global require phpmd/phpmd
642 fi
643
644 declare -r LFBFL_phpmd_baseline="${LFBFL_subdir3}/phpmd_baseline.xml"
645 local LFBFL_temp_phpmd_baseline="${LFBFL_subdir3}/temp/"
646 LFBFL_temp_phpmd_baseline+="phpmd_baseline.xml"
647 readonly LFBFL_temp_phpmd_baseline
648
649 local LFBFL_phpmd_rulesets="cleancode, codesize, controversial, "
650 LFBFL_phpmd_rulesets+="design, naming, unusedcode"
651 readonly LFBFL_phpmd_rulesets
652
653 phpmd --color --baseline-file="${LFBFL_phpmd_baseline}" \
654     . text "${LFBFL_phpmd_rulesets}"

```

```

655 # Saving new baseline in temp if necessary.
656 rm "${LFBFL_temp_phpmd_baseline}"
657 phpmd --color --generate-baseline\
658     --baseline-file="${LFBFL_temp_phpmd_baseline}"\
659     . text "${LFBFL_phpmd_rulesets}"
660 sed --in-place --expression='s/" file="/"\n    file="/g'\
661     "${LFBFL_temp_phpmd_baseline}"
662 sed --in-place --regexp-extended\
663     --expression='s~(file=".*")/>~\1\n    />~g'\
664     "${LFBFL_temp_phpmd_baseline}"
665 diff --suppress-common-lines\
666     "${LFBFL_phpmd_baseline}" "${LFBFL_temp_phpmd_baseline}"\
667     | grep --invert-match --regexp='<!-- ' --regexp='^[0-9]\+d[0-9]\+${'
668
669 printf "Running phpDocumentor\n"
670 # shellcheck disable=SC2312
671 docker run --rm --volume=$(pwd):/data" phpdoc/phpdoc
672 printf -- "----PHP end---\n"
673
674 printf -- "----JS---\n"
675 local LFBFL_npm_lint_directories=""
676 grep_variable "${LFBFL_data_file_path}" npm_lint_directories\
677     --result-variable-prefix=LFBFL_
678 if [[ -n "${LFBFL_npm_lint_directories}" ]]; then
679     printf "Running ESLint\n"
680     local LFBFL_JS_directory
681     declare -a LFBFL_arr_paths
682     mapfile -t LFBFL_arr_paths <<< "${LFBFL_npm_lint_directories}"
683     for LFBFL_JS_directory in "${LFBFL_arr_paths[@]}; do
684         (cd -- "${LFBFL_JS_directory}" && npm run lint)
685     done
686 fi
687 printf -- "----JS end---\n"
688
689 [[ LFBFL_i_directory_changed -eq 0 ]] && popd_from_work_directory
690
691 printf "Checking listed files\n"
692 " ./${LFBFL_subdir}/update_or_check_files_names_listing.exec.sh"\
693     "${LFBFL_some_common_options[@]}"
694
695 printf "Creating the PDF file of the listing of the source code\n"
696 " ./${LFBFL_subdir}/create_PDF.exec.sh" "${LFBFL_some_common_options[@]}"
697
698 pushd_to_work_directory --trap-popd
699 can_continue_after_enhanced_pushd || return 1
700

```

```

701 if [[ -f "${LFBFL_subdir3}/post_build.sh" ]]; then
702     "./${LFBFL_subdir3}/post_build.sh" "${LFBFL_verbose}"
703 fi
704
705 printf "Running xmllint\n"
706 # In some cases, we need to handle a cache of common DTDs by hand.
707 # XHTML DTDs validation can yield errors:
708 # see https://gitlab.gnome.org/GNOME/libxml2/-/work_items/1119
709 # If you use Ubuntu/Debian, install w3c-sgml-lib instead.
710 LFBFL_file_name="xhtml1-strict.dtd"
711 LFBFL_a="https://www.w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd"
712 LFBFL_script_download_URL="${LFBFL_a}"
713 LFBFL_file_path="./${LFBFL_subdir3}/temp/${LFBFL_file_name}"
714 LFBFL_correct_sha512='fe11db06c0e1741a9c460fe4f9cf167bca57f4dbe9746'
715 LFBFL_correct_sha512+='d8352bf19947168c9bcf1ae212eca035824293abb1f9'
716 LFBFL_correct_sha512+='7a0ac02d67a82d098c34905c8cf1b213c891cc0'
717 wrapped_wget_sha512
718
719 LFBFL_file_name="xhtml1-transitional.dtd"
720 LFBFL_a="https://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd"
721 LFBFL_script_download_URL="${LFBFL_a}"
722 LFBFL_file_path="./${LFBFL_subdir3}/temp/${LFBFL_file_name}"
723 LFBFL_correct_sha512='4bece71fbf75d4a68a900ed29b8ba4efaela9dfa447a5'
724 LFBFL_correct_sha512+='6fc8583da2531f9eadb0fb57bc4cf4990a82ac1da3b3'
725 LFBFL_correct_sha512+='c2892e38c88d70a80f8464b21f0bdef79a04843'
726 wrapped_wget_sha512
727
728 LFBFL_file_name="xhtml1-frameset.dtd"
729 LFBFL_a="https://www.w3.org/TR/xhtml1/DTD/xhtml1-frameset.dtd"
730 LFBFL_script_download_URL="${LFBFL_a}"
731 LFBFL_file_path="./${LFBFL_subdir3}/temp/${LFBFL_file_name}"
732 LFBFL_correct_sha512='f969c36d5ba7f6de42261c223f1a8958c8205cb938127'
733 LFBFL_correct_sha512+='ea5b7fce6bb2e03a529259e41aa3a429c64177893614'
734 LFBFL_correct_sha512+='f05e3f22bd9c46c61b37a83eb702a6d72ce2872'
735 wrapped_wget_sha512
736
737 LFBFL_file_name="xhtml11.dtd"
738 LFBFL_a="https://www.w3.org/TR/xhtml11/DTD/xhtml11.dtd"
739 LFBFL_script_download_URL="${LFBFL_a}"
740 LFBFL_file_path="./${LFBFL_subdir3}/temp/${LFBFL_file_name}"
741 LFBFL_correct_sha512='aa08bb274fd8c4d33bbcaf8993b2357c4e6c03fbdc34b'
742 LFBFL_correct_sha512+='1c46bb98332e21db824a11de43da9c6388032149a148'
743 LFBFL_correct_sha512+='42992c6d92e728e275817b656d1c333ca7f5d04'
744 wrapped_wget_sha512
745
746 LFBFL_file_name="xhtml-lat1.ent"

```

```

747 LFBFL_a="https://www.w3.org/MarkUp/DTD/xhtml1-lat1.ent"
748 LFBFL_script_download_URL="${LFBFL_a}"
749 LFBFL_file_path="./${LFBFL_subdir3}/temp/${LFBFL_file_name}"
750 LFBFL_correct_sha512='3243f33c056e71ae995d51cd2418979a505875d53ec9b'
751 LFBFL_correct_sha512+='17310268232dfbda19f5a52794973db47e51058cbcb4'
752 LFBFL_correct_sha512+='4a86838fed4937e6adc29636e12741bdc93af04'
753 wrapped_wget_sha512
754
755 LFBFL_file_name="xhtml-special.ent"
756 LFBFL_a="https://www.w3.org/MarkUp/DTD/xhtml-special.ent"
757 LFBFL_script_download_URL="${LFBFL_a}"
758 LFBFL_file_path="./${LFBFL_subdir3}/temp/${LFBFL_file_name}"
759 LFBFL_correct_sha512='ec8e78745673044993b2d57242f834c94f1615a0df653'
760 LFBFL_correct_sha512+='5882b84c1df223f652ce536cc6b17eece23ab6dae518'
761 LFBFL_correct_sha512+='60a6e562b20f7ef5440004d56f9dbe4ea58913f'
762 wrapped_wget_sha512
763
764 LFBFL_file_name="xhtml-symbol.ent"
765 LFBFL_a="https://www.w3.org/MarkUp/DTD/xhtml-symbol.ent"
766 LFBFL_script_download_URL="${LFBFL_a}"
767 LFBFL_file_path="./${LFBFL_subdir3}/temp/${LFBFL_file_name}"
768 LFBFL_correct_sha512='47ca9edba10776c5ea8bba5c0e3ea8dc1a94b2830eada'
769 LFBFL_correct_sha512+='2ebf2bec1101ca05066ce09c0e06ecef1af7785c1179'
770 LFBFL_correct_sha512+='0a61c2efdc959d89610b7b4b084bb60af89cf72'
771 wrapped_wget_sha512
772
773 declare -r LFBFL_s_files_for_xmllint=$(
774     find . -type f -iregex ".*\\.\\(xml\\|xhtml\\)" "\
775     | relevant_find\
776     | sort
777 )
778 if [[ -n "${LFBFL_s_files_for_xmllint}" ]]; then
779     LFBFL_xmllint_use_downloaded_DTDs=""
780     grep_variable "${LFBFL_data_file_path}" xmllint_use_downloaded_DTDs\
781     --result-variable-prefix=LFBFL_
782
783     declare -a LFBFL_arr_files_for_xmllint
784     mapfile -t LFBFL_arr_files_for_xmllint\
785     <<< "${LFBFL_s_files_for_xmllint}"
786     readonly LFBFL_arr_files_for_xmllint
787     local LFBFL_xmllint_files_without_DTD=""
788     grep_variable_with_multiple_files "${LFBFL_data_file_path}" "\
789     xmllint_files_without_DTD\
790     --result-variable-prefix=LFBFL_
791     declare -a LFBFL_arr_xmllint_files_without_DTD
792     if [[ -n "${LFBFL_xmllint_files_without_DTD}" ]]; then

```

```

793     mapfile -t LFBFL_arr_xmllint_files_without_DTD\  

794     <<< "${LFBFL_xmllint_files_without_DTD}"  

795 fi  

796 for LFBFL_file_path in "${LFBFL_arr_xmllint_files_without_DTD[@]}"; do  

797     [[ LFBFL_i_verbose -eq 1 ]]\<br>
798     && printf "xmllint on %s\n" "${LFBFL_file_path}"  

799     # see https://gitlab.gnome.org/GNOME/libxml2/-/issues/1100  

800     # https://gitlab.gnome.org/GNOME/libxml2/-/work_items/1100  

801     # xmllint --pedantic --noout -- "${LFBFL_file_path}"  

802     xmllint --pedantic --noout "${LFBFL_file_path}"  

803 done  

804  

805 local LFBFL_file_path2  

806 for LFBFL_file_path in "${LFBFL_arr_files_for_xmllint[@]}"; do  

807     for LFBFL_file_path2 in "${LFBFL_arr_xmllint_files_without_DTD[@]}";  

808     do  

809         if [[ "${LFBFL_file_path}" == "${LFBFL_file_path2}" ]]; then  

810             LFBFL_file_path=""  

811         fi  

812     done  

813     if [[ "${LFBFL_file_path}" == "" ]]; then  

814         continue  

815     fi  

816     [[ LFBFL_i_verbose -eq 1 ]]\<br>
817     && printf "xmllint on %s\n" "${LFBFL_file_path}"  

818     if [[  

819         "${LFBFL_file_path}" == *.xhtml  

820         && "${LFBFL_xmllint_use_downloaded_DTDs}" == "true"  

821     ]]; then  

822         if grep --fixed-strings\  

823             "http://www.w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd\  

824             "${LFBFL_file_path}"  

825         then  

826             xmllint --pedantic --noout\  

827                 --dtdvalid "./${LFBFL_subdir3}/temp/xhtml1-strict.dtd\  

828                 "${LFBFL_file_path}"  

829         elif grep --fixed-strings\  

830             "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd\  

831             "${LFBFL_file_path}"  

832         then  

833             xmllint --pedantic --noout\  

834                 --dtdvalid "./${LFBFL_subdir3}/temp/xhtml1-transitional.dtd\  

835                 "${LFBFL_file_path}"  

836         elif grep --fixed-strings\  

837             "http://www.w3.org/TR/xhtml1/DTD/xhtml1-frameset.dtd\  

838             "${LFBFL_file_path}"

```

```

839         then
840             xmllint --pedantic --noout\
841                 --dtdvalid "${LFBFL_subdir3}/temp/xhtml11-frameset.dtd"\
842                 "${LFBFL_file_path}"
843         elif grep --fixed-strings\
844             "http://www.w3.org/TR/xhtml1/DTD/xhtml11.dtd"\
845             "${LFBFL_file_path}"
846         then
847             xmllint --pedantic --noout\
848                 --dtdvalid "${LFBFL_subdir3}/temp/xhtml11.dtd"\
849                 "${LFBFL_file_path}"
850         else
851             printf "Unknown XHTML DTD.\n"
852         fi
853     else
854         xmllint --pedantic --noout --valid "${LFBFL_file_path}"
855     fi
856 done
857 fi
858 # -----
859
860 # -----
861 # It is at the end that all the HTML files are generated and that
862 # we can check there are no mistakes.
863 printf "Running Nu W3C HTML CSS and SVG validator\n"
864 local LFBFL_upgrade_vnu_jar_time_interval_in_seconds=""
865 grep_variable "${LFBFL_data_file_path}"\
866     upgrade_vnu_jar_time_interval_in_seconds\
867     --result-variable-prefix=LFBFL_
868
869 if [[ "${LFBFL_upgrade_vnu_jar_time_interval_in_seconds}" == "wat" ]];
870 then
871     LFBFL_upgrade_vnu_jar_time_interval_in_seconds=${RANDOM}
872 fi
873
874 declare -i LFBFL_i_vnu_jar_ts
875 local LFBFL_vnu_jar_path=""
876 grep_variable "${LFBFL_data_file_path}" vnu_jar_path\
877     --result-variable-prefix=LFBFL_\
878     --replace-line-returns-by=""
879 if [[ -f "${LFBFL_vnu_jar_path}" ]]; then
880     LFBFL_i_vnu_jar_ts=$(stat --format %Y -- "${LFBFL_vnu_jar_path}")
881     LFBFL_i_current_ts=$(date +%s)
882     ((LFBFL_i_current_ts -= LFBFL_i_vnu_jar_ts))
883     ((
884         LFBFL_i_current_ts -= LFBFL_upgrade_vnu_jar_time_interval_in_seconds

```

```

885     ))
886     if [[ LFBFL_i_current_ts -gt 0 ]]; then
887         printf $'/!\\ATTENTION: Nu W3C validator is too old.\\/!\\n'
888         printf "Go get the latest version here:\\n"
889         printf "https://github.com/validator/validator/releases\\n"
890     fi
891     # vnu has false positives for xhtml.
892     local LFBFL_use_vnu_for_xhtml=""
893     grep_variable "${LFBFL_data_file_path}" use_vnu_for_xhtml\\
894     --result-variable-prefix=LFBFL_
895     local LFBFL_find_regexp
896     if [[ "${LFBFL_use_vnu_for_xhtml}" == "true" ]]; then
897         LFBFL_find_regexp=".*\\.\\(css\\|html\\|svg\\|xhtml\\)"
898     else
899         LFBFL_find_regexp=".*\\.\\(css\\|html\\|svg\\)"
900     fi
901     declare -r LFBFL_s_files_for_Nu=$(
902         find . -type f -iregex "${LFBFL_find_regexp}"\\
903         | relevant_find
904     )
905     if [[ -n "${LFBFL_s_files_for_Nu}" ]]; then
906         declare -a LFBFL_arr_files_for_Nu
907         mapfile -t LFBFL_arr_files_for_Nu <<< "${LFBFL_s_files_for_Nu}"
908         readonly LFBFL_arr_files_for_Nu
909         java -Xss128M -jar "${LFBFL_vnu_jar_path}" --exit-zero-always\\
910         --verbose -- "${LFBFL_arr_files_for_Nu[@]}"
911     fi
912 fi
913 # -----
914
915 if [[ LFBFL_i_upgrade_venvs -eq 1 ]]; then
916     touch -- "${LFBFL_upgrade_venvs_ts_file}"
917 fi
918 }
919
920 common_build_and_checks "$@"

```

3.10 build_and_checks_dependencies/common_options.lib.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,

```



```

8 # either version 3 of the License,
9 # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
24
25 get_where_was_i() {
26     # Auxiliary function needed below.
27     # See usages below if you want to reuse it.
28     # $1=offset
29     LFBFL_where_was_i="$0"
30     if [[ "${BASH_SOURCE[$1]}" != "" && "${BASH_SOURCE[$1]}" != "$0" ]]; then
31         LFBFL_where_was_i+=" ${BASH_SOURCE[$1]}"
32     fi
33     if [[ "${FUNCNAME[$1]}" != "" ]]; then
34         LFBFL_where_was_i+=" ${FUNCNAME[$1]}() "
35     fi
36     readonly LFBFL_where_was_i
37     # Comment out line above in case someone would use distinct
38     # offsets in the same function.
39 }
40
41 # RETURN traps handling
42 # Add the following lines at the start of a function.
43 # declare -a LFBFL_return_traps_stack
44 # init_return_trap
45
46 init_return_trap() {
47     local LFBFL_previous_return_trap
48     local LFBFL_previous_return_trap2
49     LFBFL_previous_return_trap=$(trap -p RETURN)
50     # shellcheck disable=SC2154,SC2309
51     if [[ LFBFL_i_verbose -eq 1 ]]; then
52         local LFBFL_where_was_i
53         get_where_was_i 2

```

```

54     printf "%s previous_return_trap is: %s.\n"\
55         "${LFBFL_where_was_i}"\
56         "${LFBFL_previous_return_trap}"
57 fi
58 if [[ -z "${LFBFL_previous_return_trap}" ]]; then
59     LFBFL_previous_return_trap="trap - RETURN"
60 fi
61 readonly LFBFL_previous_return_trap
62 declare -ir LFBFL_function_depth=$(( ${#FUNCNAME[@]} - 1 ) )
63 LFBFL_previous_return_trap2="${LFBFL_function_depth}:"
64 LFBFL_previous_return_trap2+="${LFBFL_previous_return_trap}"
65 readonly LFBFL_previous_return_trap2
66 LFBFL_return_traps_stack+="${LFBFL_previous_return_trap2}"
67 trap 'execute_return_traps' RETURN
68 }
69
70 execute_return_traps() {
71     if [[ "${FUNCNAME[1]}" == "init_return_trap" ]]; then
72         return
73     fi
74     # -----
75     # See https://lists.gnu.org/archive/html/help-bash/2026-03/msg00052.html
76     if [[ "${FUNCNAME[1]}" == "source" ]]; then
77         # Not Working
78         return
79     fi
80     if [[ ${LFBFL_i_no_return_traps:-0} -eq 1 ]]; then
81         return
82     fi
83     # -----
84     local LFBFL_some_return_trap
85     local LFBFL_where_was_i
86     get_where_was_i 2
87     declare -ir LFBFL_function_depth=$(( ${#FUNCNAME[@]} - 1 ) )
88     while [[ ${#LFBFL_return_traps_stack[@]} -gt 0 ]]; do
89         LFBFL_some_return_trap="${LFBFL_return_traps_stack[-1]}"
90         if [[ "${LFBFL_some_return_trap}" != "${LFBFL_function_depth}:" ]]; then
91             # We only treat the top of the stack that should correspond to the
92             # current function.
93             break
94         fi
95         LFBFL_some_return_trap=${LFBFL_some_return_trap#*:}
96         # shellcheck disable=SC2154,SC2309
97         if [[ LFBFL_i_verbose -eq 1 ]]; then
98             if [[ ${#LFBFL_return_traps_stack[@]} -gt 1 ]]; then
99                 printf "%s executing some return trap: %s.\n"\

```

```

100         "${LFBFL_where_was_i}"\
101         "${LFBFL_some_return_trap}"
102     else
103         printf "%s setting back to previous_return_trap: %s.\n"\
104         "${LFBFL_where_was_i}"\
105         "${LFBFL_some_return_trap}"
106     fi
107 fi
108 eval -- "${LFBFL_some_return_trap}"
109 unset 'LFBFL_return_traps_stack[-1]'
110 done
111 }
112
113
114 is_top_dirstack_directory(){
115     # Although "${DIRSTACK[0]}" may seem to be already a realpath,
116     # possible use of symbolic links makes this function necessary.
117     # https://lists.gnu.org/archive/html/help-bash/2026-03/msg00005.html
118     # $1=to_directory needed to be "realpathed" already
119     # but I removed this micro-optimization.
120     # A compiled language could have a "realpathed" property" on
121     # "path object/string" to optimize when possible.
122     if [[ -z "$1" ]]; then
123         return 0
124     fi
125     local LFBFL_real_path
126     LFBFL_real_path=$(realpath -- "${DIRSTACK[0]}")
127     readonly LFBFL_real_path
128     local LFBFL_real_path2
129     LFBFL_real_path2=$(realpath -- "$1")
130     readonly LFBFL_real_path2
131     [[ "${LFBFL_real_path}" == "${LFBFL_real_path2}" ]]
132 }
133
134 enhanced_pushd(){
135     # Auxiliary function needed below.
136     # See usages below if you want to reuse it.
137     # $1=to_directory (needed to be sanitized with realpath before call)
138     # $2=offset_for_where_was_i
139     # $3=error_message_intermediate_complement
140     # returns an error code whenever no pushd happened
141     # $1 can be any path now, see my comment on the micro-optimization in
142     # is_top_dirstack_directory() just above.
143     # shellcheck disable=SC2154,SC2309
144     [[ LFBFL_i_verbose -eq 1 ]]\
145     && printf "enhanced_pushd requested: %s.\n" "$1"

```

```

146 # Value 0 will always be overwritten, it is superfluous.
147 declare -gi i_enhanced_pushd_result=0
148 if [[ -z "$1" ]]; then
149     i_enhanced_pushd_result=110
150     # shellcheck disable=SC2248
151     return ${i_enhanced_pushd_result}
152 fi
153 local LFBFL_real_path
154 LFBFL_real_path=$(realpath -- "$1")
155 readonly LFBFL_real_path
156 # shellcheck disable=SC2154,SC2309
157 [[ LFBFL_i_verbose -eq 1 ]]\
158     && printf "enhanced_pushd passed validation 1.\n"
159 is_top_dirstack_directory "${LFBFL_real_path}" && {
160     i_enhanced_pushd_result=111
161     # shellcheck disable=SC2248
162     return ${i_enhanced_pushd_result}
163 }
164 # shellcheck disable=SC2154,SC2309
165 [[ LFBFL_i_verbose -eq 1 ]]\
166     && printf "enhanced_pushd passed validation 2.\n"
167
168 pushd -- "${LFBFL_real_path}" || {
169     i_enhanced_pushd_result=$?
170     local LFBFL_where_was_i
171     get_where_was_i "$2"
172     printf "%s %s%s no such directory.\n" "${LFBFL_where_was_i}" "$3"\
173         "${LFBFL_real_path}"
174     # shellcheck disable=SC2248
175     return ${i_enhanced_pushd_result}
176 }
177 # shellcheck disable=SC2154,SC2309
178 [[ LFBFL_i_verbose -eq 1 ]]\
179     && printf "enhanced_pushd executed.\n"
180 # shellcheck disable=SC2248
181 return ${i_enhanced_pushd_result}
182
183 enhanced_popd() {
184     # Auxiliary function needed below.
185     # See usages below if you want to reuse it.
186     # $1=to_directory
187     # $2=offset_for_where_was_i
188     # shellcheck disable=SC2154,SC2309
189     [[ LFBFL_i_verbose -eq 1 ]]\
190         && printf "enhanced_popd requested: %s.\n" "$1"
191     if [[ -z "$1" ]]; then

```

```

192     return 0
193 fi
194
195 declare -i LFBFL_i_popd_result
196 popd || {
197     LFBFL_i_popd_result=$?
198     readonly LFBFL_i_popd_result
199     local LFBFL_where_was_i
200     get_where_was_i "$2"
201     printf "%s popd failed.\n" "${LFBFL_where_was_i}"
202     # shellcheck disable=SC2248
203     return ${LFBFL_i_popd_result}
204 }
205 # shellcheck disable=SC2154,SC2309
206 [[ LFBFL_i_verbose -eq 1 ]] && printf "enhanced_popd executed.\n"
207 return 0
208 }
209
210 can_continue_after_enhanced_pushd() {
211     [[
212         i_enhanced_pushd_result -eq 0
213         || i_enhanced_pushd_result -eq 110
214         || i_enhanced_pushd_result -eq 111
215     ]]
216 }
217
218 # Main usage for the next functions relative to verbose mode:
219 # Add the two following lines at the start of a function.
220 #   declare -i LFBFL_i_verbose=0
221 #   get_verbose_option "$@"
222 # /\ You really need all of the two lines. /\
223 # Otherwise, the call to get_verbose_option may impact a function above;
224 # in case you didn't copy all of "$@" in nested function calls...
225 # /\ The same warning applies for other functions below. /\
226 # /\ I will not repeat it below. /\
227 # Use get_verbose_options_array, if needed.
228
229 get_verbose_options_array() {
230     # Use this constant with code like:
231     # "${LFBFL_VERBOSE_OPTIONS[LFBFL_i_verbose]}"
232     # It could be extended if there is more than one level of verboseness.
233     if [[ -n "${LFBFL_VERBOSE_OPTIONS}" ]]; then
234         return
235     fi
236
237     declare -agr LFBFL_VERBOSE_OPTIONS=(

```

```

238     ""
239     "--verbose"
240 )
241 }
242
243 get_some_flag() {
244     # $1=variable_name
245     # $2=some_flag_long_name
246     # $3=read_only 0 or 1 to make the variable readonly
247     # This command is to be called in another one with same arguments on top
248     # of the three previous.
249     # This test:
250     # if [[ "$*" == *--verbose* ]]; then
251     # is faster than below.
252     # But it is not bug free in a calling function,
253     # and even incompatible with the current function where
254     # the flag_long_name is a mandatory argument.
255     printf -v "$1" "%d" 0
256     declare -i LFBFL_i
257     local LFBFL_argument
258     for ((LFBFL_i = 4; LFBFL_i <= $#; ++LFBFL_i)); do
259         LFBFL_argument="${!LFBFL_i}"
260         if [[ "${LFBFL_argument}" == "$2" ]]; then
261             printf -v "$1" "%d" 1
262             break
263         fi
264     done
265     if [[ $3 -eq 1 ]]; then
266         readonly "$1"
267     fi
268 }
269
270 get_verbose_option() {
271     # This command is to be called in another one with same arguments.
272     # Options:
273     # --verbose
274     get_some_flag LFBFL_i_verbose --verbose 1 "$@"
275     # shellcheck disable=SC2154,SC2309
276     if [[ LFBFL_i_verbose -eq 1 ]]; then
277         local LFBFL_where_was_i
278         get_where_was_i 2
279         printf "%s %s\n" "${LFBFL_where_was_i}" "$*"
280     fi
281 }
282
283

```

```

284 get_some_option() {
285     # $1=variable_name
286     # $2=some_option_long_name
287     # $3=option_default_value_if_flag_without_option_value_or_empty_value
288     # $4=option_default_value_if_nothing
289     # $5=read_only 0 or 1 to make the variable readonly
290     # This command is to be called in another one with same arguments on top
291     # of the four previous.
292     # If you truly have a need to distinguish:
293     # option_default_value_if_flag_without_option_value --thing
294     # option_default_value_if_flag_with_empty_option_value --thing= or '='
295     # then think twice before modifying this function.
296     printf -v "$1" "%s" "$4"
297     declare -i LFBFL_i
298     local LFBFL_argument
299     for ((LFBFL_i = 6; LFBFL_i <= $#; ++LFBFL_i)); do
300         LFBFL_argument="${!LFBFL_i}"
301         if [[ "${LFBFL_argument}" == "$2" ]]; then
302             printf -v "$1" "%s" "$3"
303             break
304         fi
305         if [[ "${LFBFL_argument}" == "$2"=* ]]; then
306             printf -v "$1" "%s" "${LFBFL_argument#"${2}"="}"
307             printf -v "$1" "%s" "${!1:-$3}"
308             break
309         fi
310     done
311     if [[ $5 -eq 1 ]]; then
312         readonly "$1"
313     fi
314 }
315
316 keep_options() {
317     # $1=variable_name of array of options
318     # Other arguments: the options to keep.
319     declare -a LFBFL_array_of_filtered_options
320     declare -n LFBFL_array_of_options=$1
321     local LFBFL_some_argument
322     local LFBFL_some_argument2
323     for LFBFL_some_argument in "${LFBFL_array_of_options[@]"; do
324         for LFBFL_some_argument2 in "$@"; do
325             if [[
326                 "${LFBFL_some_argument}" == "${LFBFL_some_argument2}"
327                 || "${LFBFL_some_argument}" == "${LFBFL_some_argument2}"=*
328             ]]; then
329                 LFBFL_array_of_filtered_options+=("${LFBFL_some_argument}")

```

```

330         fi
331     done
332 done
333 LFBFL_array_of_options=("${LFBFL_array_of_filtered_options[@]}")
334 }
335
336
337 # Main usage for the next functions relative to work_directory:
338 # Add the five following lines at the start of a function.
339 #     local LFBFL_work_directory=""
340 #     get_work_directory_option "$@"
341 #     pushd_to_work_directory\
342 #     && trap 'popd_from_work_directory' RETURN
343 #     can_continue_after_enhanced_pushd || return 1
344 # Or:
345 #     local LFBFL_work_directory=""
346 #     get_work_directory_option "$@"
347 #     pushd_to_work_directory --trap-popd
348 #     can_continue_after_enhanced_pushd || return 1
349
350 get_work_directory_option() {
351     # This command is to be called in another one with same arguments.
352     # Options:
353     #     --work-directory=""
354     get_some_option LFBFL_work_directory --work-directory "." "." 0 "$@"
355     LFBFL_work_directory=$(realpath -- "${LFBFL_work_directory}")
356     readonly LFBFL_work_directory
357 }
358
359 pushd_to_work_directory() {
360     # Options:
361     #     --trap-popd
362     enhanced_pushd "${LFBFL_work_directory}" 3 " --work-directory="
363     if [[ i_enhanced_pushd_result -eq 0 ]]; then
364         declare -i LFBFL_i_trap_popd
365         get_some_flag LFBFL_i_trap_popd --trap-popd 1 "$@"
366         if [[ LFBFL_i_trap_popd -eq 1 ]]; then
367             declare -ir LFBFL_function_depth=$(( ${#FUNCNAME[@]} - 1 ))
368             local LFBFL_some_return_trap
369             LFBFL_some_return_trap="${LFBFL_function_depth}:"
370             LFBFL_some_return_trap+="popd_from_work_directory 4"
371             readonly LFBFL_some_return_trap
372             LFBFL_return_traps_stack+=("${LFBFL_some_return_trap}")
373         fi
374     fi
375     # shellcheck disable=SC2248

```



```

376     return ${i_enhanced_pushd_result}
377 }
378
379 popd_from_work_directory() {
380     # $1=offset for where_was_i
381     enhanced_popd "${LFBFL_work_directory}" "${1:-3}"
382 }
383
384 work_directory_is_top_dirstack_directory() {
385     is_top_dirstack_directory "${LFBFL_work_directory}"
386 }
387
388
389 get_offset_option() {
390     # This command is to be called in another one with same arguments on top
391     # of the default value.
392     # $1=option_default_value
393     # Options:
394     #     --offset=2
395     get_some_option LFBFL_i_offset --offset "$1" "$1" 1 "$@"
396 }
397
398 get_max_line_length_option() {
399     # This command is to be called in another one with same arguments.
400     # Its most useful feature is that it factorizes the default maximum line
401     # length of 70 characters.
402     # Options:
403     #     --max-line-length
404     get_some_option LFBFL_i_max_line_length --max-line-length 70 70 1 "$@"
405 }
406
407
408 # Functions relative to shell and bash options
409 # (See SHELLOPTS and BASHOPTS, set and shopt):
410 # - shell options usage, example with pipefail:
411 #     enhanced_set_shell_option pipefail\
412 #         && trap 'enhanced_unset_shell_option pipefail' RETURN
413 # or maybe:
414 #     enhanced_unset_shell_option pipefail\
415 #         && trap 'enhanced_set_shell_option pipefail' RETURN
416 # if you need to unset it in some function.
417 # or better if you use my RETURN traps handler:
418 #     enhanced_set_shell_option pipefail --trap-unset
419 #     enhanced_unset_shell_option pipefail --trap-set
420 # - bash options usage, example with globstar:
421 #     enhanced_set_bash_option globstar\

```

```

422 #         && trap 'enhanced_unset_bash_option globstar' RETURN
423 #     or maybe:
424 #         enhanced_unset_bash_option globstar\
425 #         && trap 'enhanced_set_bash_option globstar' RETURN
426 #     or better if you use my RETURN traps handler:
427 #         enhanced_set_bash_option globstar --trap-unset
428 #         enhanced_unset_bash_option globstar --trap-set
429
430 enhanced_set_shell_option(){
431     # $1=optname some shell option for set
432     # Options:
433     #     --offset=2
434     #     --trap-unset
435     declare -r LFBFL_result_name="i_enhanced_set_shell_option_$1_result"
436     declare -gi "${LFBFL_result_name}"=0
437     if [[ -o "$1" ]]; then
438         printf -v "${LFBFL_result_name}" "%d" 1
439         # shellcheck disable=SC2086
440         return ${!LFBFL_result_name}
441     fi
442     set -o "$1"
443     declare -i LFBFL_i_offset=2
444     get_offset_option 2 "$@"
445     # shellcheck disable=SC2154,SC2309
446     if [[ LFBFL_i_verbose -eq 1 ]]; then
447         local LFBFL_where_was_i
448         # shellcheck disable=SC2248
449         get_where_was_i ${LFBFL_i_offset}
450         printf "%s %s shell option activated.\n" "${LFBFL_where_was_i}" "$1"
451     fi
452     declare -i LFBFL_i_trap_unset
453     get_some_flag LFBFL_i_trap_unset --trap-unset 1 "$@"
454     if [[ LFBFL_i_trap_unset -eq 1 ]]; then
455         declare -ir LFBFL_function_depth=$(( ${#FUNCNAME[@]} - 1 ) )
456         local LFBFL_some_return_trap
457         LFBFL_some_return_trap="${LFBFL_function_depth}:"
458         LFBFL_some_return_trap+="enhanced_unset_shell_option '$1' --offset=3"
459         readonly LFBFL_some_return_trap
460         LFBFL_return_traps_stack+=("${LFBFL_some_return_trap}")
461     fi
462     # shellcheck disable=SC2086
463     return ${!LFBFL_result_name}
464 }
465
466 enhanced_unset_shell_option(){
467     # $1=optname some shell option for set

```

```

468 # Options:
469 #   --offset=2
470 #   --trap-set
471 declare -r LFBFL_result_name="i_enhanced_unset_shell_option_$1_result"
472 declare -gi "${LFBFL_result_name}"=0
473 if [[ ! -o "$1" ]]; then
474     printf -v "${LFBFL_result_name}" "%d" 1
475     # shellcheck disable=SC2086
476     return ${!LFBFL_result_name}
477 fi
478 set +o "$1"
479 declare -i LFBFL_i_offset=2
480 get_offset_option 2 "$@"
481 # shellcheck disable=SC2154,SC2309
482 if [[ LFBFL_i_verbose -eq 1 ]]; then
483     local LFBFL_where_was_i
484     # shellcheck disable=SC2248
485     get_where_was_i ${LFBFL_i_offset}
486     printf "%s %s shell option unactivated.\n" "${LFBFL_where_was_i}" "$1"
487 fi
488 declare -i LFBFL_i_trap_set
489 get_some_flag LFBFL_i_trap_set --trap-set 1 "$@"
490 if [[ LFBFL_i_trap_set -eq 1 ]]; then
491     declare -ir LFBFL_function_depth=$(( ${#FUNCNAME[@]} - 1 ))
492     local LFBFL_some_return_trap
493     LFBFL_some_return_trap="${LFBFL_function_depth}:"
494     LFBFL_some_return_trap+="enhanced_set_shell_option '$1' --offset=3"
495     readonly LFBFL_some_return_trap
496     LFBFL_return_traps_stack+=("${LFBFL_some_return_trap}")
497 fi
498 # shellcheck disable=SC2086
499 return ${!LFBFL_result_name}
500 }
501
502 enhanced_set_bash_option() {
503     # $1=optname some bash option for shopt
504     # Options:
505     #   --offset=2
506     #   --trap-unset
507     declare -r LFBFL_result_name="i_enhanced_set_bash_option_$1_result"
508     declare -gi "${LFBFL_result_name}"=0
509     # declare -r LFBFL_regexp="^(.*:)?$1(:.*)?$" funny but brainfucked
510     # if [[ "${BASHOPTS}" =~ ${LFBFL_regexp} ]]; then
511     if shopt -q "$1"; then
512         printf -v "${LFBFL_result_name}" "%d" 1
513         # shellcheck disable=SC2086

```

```

514     return ${!LFBFL_result_name}
515 fi
516 shopt -s "$1"
517 declare -i LFBFL_i_offset=2
518 get_offset_option 2 "$@"
519 # shellcheck disable=SC2154,SC2309
520 if [[ LFBFL_i_verbose -eq 1 ]]; then
521     local LFBFL_where_was_i
522     # shellcheck disable=SC2248
523     get_where_was_i ${LFBFL_i_offset}
524     printf "%s %s bash option activated.\n" "${LFBFL_where_was_i}" "$1"
525 fi
526 declare -i LFBFL_i_trap_unset
527 get_some_flag LFBFL_i_trap_unset --trap-unset 1 "$@"
528 if [[ LFBFL_i_trap_unset -eq 1 ]]; then
529     declare -ir LFBFL_function_depth=$(( ${#FUNCNAME[@]} - 1 ))
530     local LFBFL_some_return_trap
531     LFBFL_some_return_trap="${LFBFL_function_depth}:"
532     LFBFL_some_return_trap+="enhanced_unset_bash_option '$1' --offset=3"
533     readonly LFBFL_some_return_trap
534     LFBFL_return_traps_stack+="${LFBFL_some_return_trap}"
535 fi
536 # shellcheck disable=SC2086
537 return ${!LFBFL_result_name}
538 }
539
540 enhanced_unset_bash_option() {
541     # $1=optname some bash option for shopt
542     # Options:
543     #   --offset=2
544     #   --trap-set
545     declare -r LFBFL_result_name="i_enhanced_unset_bash_option_$1_result"
546     declare -gi "${LFBFL_result_name}"=0
547     if ! shopt -q "$1"; then
548         printf -v "${LFBFL_result_name}" "%d" 1
549         # shellcheck disable=SC2086
550         return ${!LFBFL_result_name}
551     fi
552     shopt -u "$1"
553     declare -i LFBFL_i_offset=2
554     get_offset_option 2 "$@"
555     # shellcheck disable=SC2154,SC2309
556     if [[ LFBFL_i_verbose -eq 1 ]]; then
557         local LFBFL_where_was_i
558         # shellcheck disable=SC2248
559         get_where_was_i ${LFBFL_i_offset}

```

```

560     printf "%s %s bash option unactivated.\n" "${LFBFL_where_was_i}" "$1"
561 fi
562 declare -i LFBFL_i_trap_set
563 get_some_flag LFBFL_i_trap_set --trap-set 1 "$@"
564 if [[ LFBFL_i_trap_set -eq 1 ]]; then
565     declare -ir LFBFL_function_depth=$(( ${#FUNCNAME[@]} - 1 ))
566     local LFBFL_some_return_trap
567     LFBFL_some_return_trap="${LFBFL_function_depth}:"
568     LFBFL_some_return_trap+="enhanced_set_bash_option '$1' --offset=3"
569     readonly LFBFL_some_return_trap
570     LFBFL_return_traps_stack+=("${LFBFL_some_return_trap}")
571 fi
572 # shellcheck disable=SC2086
573 return ${!LFBFL_result_name}
574 }

```

3.11 build_and_checks_dependencies/comparisons.lib.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023–2026 Laurent Frédéric Bernard François Lyaudet
24 # The file "comparisons.sh" was renamed to "comparisons.lib.sh".
25
26 # shellcheck source=common_options.lib.sh
27 source "../build_and_checks_dependencies/common_options.lib.sh"
28

```

```

29 equal() {
30     # Returns 1 if all the arguments strings are equal.
31     # Renvoie 1 dans $? si toutes les chaînes en arguments sont égales.
32     # J'ai rerepensé au 3-way-merge
33     # et à mon article sur le principe de première différence
34     # appliqué à la largeur modulaire, de clique ou de rang avec
35     # l'idée d'un principe de première différence ternaire.
36     declare -i LFBFL_i_first=1
37     local LFBFL_current
38     local LFBFL_argument
39     for LFBFL_argument in "$@"; do
40         if [[ LFBFL_i_first -eq 1 ]]; then
41             LFBFL_current="${LFBFL_argument}"
42             LFBFL_i_first=0
43             continue
44         fi
45         if [[ "${LFBFL_current}" != "${LFBFL_argument}" ]]; then
46             return 0
47         fi
48     done
49     return 1
50 }
51
52 some_distinct() {
53     ! equal "$@"
54 }
55
56 all_distinct() {
57     # Returns 1 if all the arguments strings are distinct.
58     declare -ir LFBFL_ij_max=$#
59     declare -i LFBFL_i
60     declare -i LFBFL_j
61     for ((LFBFL_i = 1; LFBFL_i < LFBFL_ij_max; ++LFBFL_i)); do
62         for ((LFBFL_j = LFBFL_i + 1; LFBFL_j <= LFBFL_ij_max; ++LFBFL_j)); do
63             [[ "${!LFBFL_i}" == "${!LFBFL_j}" ]] && return 0
64         done
65     done
66     return 1
67 }
68
69 all_distinct2() {
70     # Returns 1 if all the arguments strings are distinct.
71     local LFBFL_element
72     local LFBFL_previous_element
73     if [[ $# -le 1 ]]; then
74         return 1

```

```

75     fi
76     declare -r LFBFL_s_sorted_arguments=$(
77         printf "%s\n" "$@" \
78         | sort
79     )
80     declare -a LFBFL_arr_sorted_arguments
81     mapfile -t LFBFL_arr_sorted_arguments <<< "${LFBFL_s_sorted_arguments}"
82     declare -i LFBFL_i
83     declare -ir LFBFL_i_max=${#LFBFL_arr_sorted_arguments[@]}
84     LFBFL_previous_element=${LFBFL_arr_sorted_arguments[0]}
85     for ((LFBFL_i = 1; LFBFL_i < LFBFL_i_max; ++LFBFL_i)); do
86         LFBFL_element=${LFBFL_arr_sorted_arguments[${LFBFL_i}]}
87         if [[ "${LFBFL_previous_element}" == "${LFBFL_element}" ]]; then
88             return 0
89         fi
90         LFBFL_previous_element="${LFBFL_element}"
91     done
92     return 1
93 }
94
95 all_distinct3(){
96     # Returns 1 if all the arguments strings are distinct.
97     # all_distinct3 is slower than old all_distinct2 since a call to sort is
98     # needed:
99     # the manual of uniq says it doesn't detect non-adjacent repeated lines.
100    # A few weeks ago, when testing without sort, I had no bug...
101    # I may have tested all_distinct3 a a b and not all_distinct3 a b a
102    # There is a sort also in all_distinct2, but uniq could have an option to
103    # sort before "applying -d", or sort could have an option for printing
104    # duplicates only. It would complement -u option of sort.
105    # Both solutions would avoid one pipe and one more shell command call.
106    # Note that old all_distinct2 was faster with pipes and read -r commands,
107    # but read -r has small drawbacks. Using mapfile is a cleaner way to do
108    # it, since it handles arguments with spaces from scratch.
109    # Arguments with line-returns are still not handled.
110    # Use C, PHP or Python for example for that.
111    # Somehow Bash was made to push people to stop being lazy and do actual C
112    # code, even if it needs compiling something, adding a makefile, etc. XD
113    # Note that C code would be faster with all_distinct2 blueprint,
114    # that's the reason I kept all 3 versions, see the (asymptotic)
115    # complexity and simple algorithms ideas on this toy problem.
116    if [[ $# -le 1 ]]; then
117        return 1
118    fi
119    declare -r LFBFL_s_duplicated_arguments=$(
120        printf "%s\n" "$@" \

```

```

121         | sort\
122         | uniq --repeated
123     )
124     [[ -n "${LFBFL_s_duplicated_arguments}" ]]
125 }
126
127 some_equal() {
128     ! all_distinct "$@"
129 }
130
131 some_equal2() {
132     ! all_distinct2 "$@"
133 }
134
135 some_equal3() {
136     ! all_distinct3 "$@"
137 }
138
139 max() {
140     # Returns the maximum string among the arguments.
141     # Renvoie la chaîne la plus grande parmi celles proposées.
142     # $1=sort_command with the flags you want to be applied.
143     # $ max sort a b c
144     # c
145     if [[ $# -eq 0 ]]; then
146         return 1
147     fi
148     enhanced_set_shell_option pipefail\
149     && trap 'enhanced_unset_shell_option pipefail' RETURN
150     printf "%s\n" "${@:2}" \
151         | eval -- "$1 --reverse"\
152         | head --lines=1
153 }
154
155 min() {
156     # Returns the minimum string among the arguments.
157     # Renvoie la chaîne la plus petite parmi celles proposées.
158     # $1=sort_command with the flags you want to be applied.
159     # $ min sort a b c
160     # a
161     if [[ $# -eq 0 ]]; then
162         return 1
163     fi
164     enhanced_set_shell_option pipefail\
165     && trap 'enhanced_unset_shell_option pipefail' RETURN
166     printf "%s\n" "${@:2}" \

```



```

167         | eval -- "$1"\
168         | head --lines=1
169     }
170
171     is_substring() {
172         # $1=string
173         # $2=substring
174         declare -r LFBFL_var_1=$(
175             printf "%s" "$1"\
176             | sed --expression='s/\\/\\&/g' --expression="s/'/'/\\&/g"
177         )
178         declare -r LFBFL_var_2=$(
179             printf "%s" "$2"\
180             | sed --expression='s/\\/\\&/g' --expression="s/'/'/\\&/g"
181         )
182         local LFBFL_var_3="\$a = '${LFBFL_var_1}';"
183         LFBFL_var_3+=" \$b = preg_quote('${LFBFL_var_2}');"
184         LFBFL_var_3+=" \$c = '/'.addslashes(\$b, '/').'/'";
185         LFBFL_var_3+=" die(1 - preg_match(\$c, \$a));"
186         readonly LFBFL_var_3
187         php --run="\${LFBFL_var_3}"
188         return $?
189     }
190
191     is_subfile() {
192         # $1=file_path
193         # $2=sub_file_path
194         local LFBFL_var_1="\$a = file_get_contents('$1');"
195         LFBFL_var_1+=" \$b = preg_quote(file_get_contents('$2'));"
196         LFBFL_var_1+=" \$c = '/'.addslashes(\$b, '/').'/'";
197         LFBFL_var_1+=" die(1 - preg_match(\$c, \$a));"
198         readonly LFBFL_var_1
199         php --run="\${LFBFL_var_1}"
200         return $?
201     }
202
203     alias min_from_int_sort="min 'sort --numeric-sort'"
204     alias max_from_int_sort="max 'sort --numeric-sort'"

```

3.12 build_and_checks_dependencies/create_PDF.exec.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it

```

```

6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
24 # This file was renamed from "create_PDF.sh" to "create_PDF.exec.sh".
25
26 LFBFL_subdir="build_and_checks_dependencies"
27 # shellcheck source=common_options.lib.sh
28 source "${LFBFL_subdir}/common_options.lib.sh"
29 # shellcheck source=generate_from_template.lib.sh
30 source "${LFBFL_subdir}/generate_from_template.lib.sh"
31 # shellcheck source=lines_counts.lib.sh
32 source "${LFBFL_subdir}/lines_counts.lib.sh"
33 # shellcheck source=lines_filters.lib.sh
34 source "${LFBFL_subdir}/lines_filters.lib.sh"
35 # shellcheck source=lines_maps.lib.sh
36 source "${LFBFL_subdir}/lines_maps.lib.sh"
37 # shellcheck source=overwrite_if_not_equal.lib.sh
38 source "${LFBFL_subdir}/overwrite_if_not_equal.lib.sh"
39 # shellcheck source=strings_functions.lib.sh
40 source "${LFBFL_subdir}/strings_functions.lib.sh"
41
42 create_PDF() {
43     # Options:
44     #   --verbose
45     #   --work-directory=""
46     declare -i LFBFL_i_verbose=0
47     get_verbose_option "$@"
48     local LFBFL_work_directory=""
49     get_work_directory_option "$@"
50     declare -a LFBFL_return_traps_stack
51     init_return_trap

```

```

52 pushd_to_work_directory --trap-popd
53 can_continue_after_enhanced_pushd || return 1
54
55 enhanced_set_shell_option pipefail --trap-unset
56
57 declare -a LFBFL_common_options=("$@" )
58 keep_options LFBFL_common_options --verbose
59
60 local LFBFL_subdir2="build_and_checks_variables"
61 local LFBFL_data_file_path="${LFBFL_subdir2}/repository_data.txt"
62 local LFBFL_repository_name=""
63 grep_variable "${LFBFL_data_file_path}" repository_name\
64     --result-variable-prefix="LFBFL_"\
65     --replace-line-returns-by=" "
66
67 local LFBFL_repository_web_url=""
68 grep_variable "${LFBFL_data_file_path}" repository_web_url\
69     --result-variable-prefix="LFBFL_"\
70     --replace-line-returns-by=" "
71
72 local LFBFL_repository_git_url=""
73 grep_variable "${LFBFL_data_file_path}" repository_git_url\
74     --result-variable-prefix="LFBFL_"\
75     --replace-line-returns-by=" "
76
77 local LFBFL_abstract=""
78 grep_variable "${LFBFL_data_file_path}" abstract\
79     --result-variable-prefix="LFBFL_"
80
81 local LFBFL_acknowledgments=""
82 grep_variable "${LFBFL_data_file_path}" acknowledgments\
83     --result-variable-prefix="LFBFL_"
84
85 local LFBFL_author_email=""
86 grep_variable "${LFBFL_data_file_path}" author_email\
87     --result-variable-prefix="LFBFL_"\
88     --replace-line-returns-by=" "
89
90 local LFBFL_author_full_name=""
91 grep_variable "${LFBFL_data_file_path}" author_full_name\
92     --result-variable-prefix="LFBFL_"\
93     --replace-line-returns-by=" "
94
95 local LFBFL_author_website=""
96 grep_variable "${LFBFL_data_file_path}" author_website\
97     --result-variable-prefix="LFBFL_"\

```

```

98     --replace-line-returns-by=""
99
100 declare -i LFBFL_i_max_line_length
101 grep_variable "${LFBFL_data_file_path}" max_line_length\
102     --result-variable-prefix="LFBFL_i_"
103
104 declare -r LFBFL_current_date=$(date --iso-8601="date")
105
106 declare -r LFBFL_current_git_SHA1=$(git rev-parse HEAD)
107
108 declare -ir LFBFL_i_number_of_commits=$(
109     git shortlog\
110     | space_starting_lines\
111     | wc --lines
112 )
113
114 local LFBFL_redirect="/dev/stdout"
115 if [[ LFBFL_i_verbose -eq 0 ]]; then
116     LFBFL_redirect="/dev/null"
117 fi
118 {
119     code_lines_count_all "${LFBFL_common_options[@]}"
120     code_lines_count_not_empty "${LFBFL_common_options[@]}"
121     code_lines_count_empty "${LFBFL_common_options[@]}"
122 } &> "${LFBFL_redirect}"
123
124 local LFBFL_number_of_lines="${i_code_lines_count_all_result}"
125 LFBFL_number_of_lines+=" total lines,"
126 LFBFL_number_of_lines+=" ${i_code_lines_count_not_empty_result}"
127 LFBFL_number_of_lines+=" not empty lines,"
128 LFBFL_number_of_lines+=" ${i_code_lines_count_empty_result}"
129 LFBFL_number_of_lines+=" empty lines."
130 readonly LFBFL_number_of_lines
131
132 declare -r LFBFL_temp_path="${LFBFL_subdir2}/temp"
133
134 # see https://gitlab.com/OldManProgrammer/unix-tree/-/issues
135 # ?show=eyJpaWQiOiI0MyIsImZlbGxhcGF0aCI6Ik9sZE1hblByb2dyYW1t
136 # ZXIvdW5peC10cmVlIiwiaWQiOiJlE4NTE0NTgzOH0%3D
137 tree -a --gitignore\
138     -I "node_modules/"\
139     -I "__pycache__/"\
140     -I ".mypy_cache/"\
141     -I ".ruff_cache/"\
142     -I ".git/"\
143     | replace_non_ascii_spaces\

```

```

144     > "${LFBFL_temp_path}/current_tree_light.txt"
145
146 tree -a -DFh --gitignore\
147     -I "node_modules/"\
148     -I "__pycache__/"\
149     -I ".mypy_cache/"\
150     -I ".ruff_cache/"\
151     -I ".git/"\
152     | replace_non_ascii_spaces\
153     > "${LFBFL_temp_path}/current_tree.txt.temp"
154
155 local LFBFL_s_files_paths
156 # Remove line returns that are here to keep lines short.
157 LFBFL_s_files_paths=$(
158     sed --regextype=extended --null-data\
159         --expression='s/(.)\\n\\1/Mg'\
160         -- "${LFBFL_subdir2}/files_names_listing.txt"\
161         | grep --invert-match '^/'
162 )
163 readonly LFBFL_s_files_paths
164 declare -a LFBFL_arr_files_paths
165 if [[ -n "${LFBFL_s_files_paths}" ]]; then
166     mapfile -t LFBFL_arr_files_paths <<< "${LFBFL_s_files_paths}"
167 fi
168 readonly LFBFL_arr_files_paths
169
170 local LFBFL_temp_files_listing="${LFBFL_temp_path}/"
171 LFBFL_temp_files_listing+="files_listing.tex.sub.temp"
172 readonly LFBFL_temp_files_listing
173 : > "${LFBFL_temp_files_listing}"
174 local LFBFL_temp_files_listing2="${LFBFL_temp_path}/"
175 LFBFL_temp_files_listing2+="files_listing.html.sub.temp"
176 readonly LFBFL_temp_files_listing2
177 : > "${LFBFL_temp_files_listing2}"
178 # HTML <li> elements, hence "lis".
179 local LFBFL_temp_files_lis
180 LFBFL_temp_files_lis="${LFBFL_temp_path}/files_lis.html.sub.temp"
181 readonly LFBFL_temp_files_lis
182 : > "${LFBFL_temp_files_lis}"
183 # shellcheck disable=SC2248
184 get_split_score_simple 1 ${LFBFL_i_max_line_length} /
185 declare -r LFBFL_score_command="${get_split_score_result}"
186 declare -i LFBFL_i_score_command_properties
187 LFBFL_i_score_command_properties=${i_get_split_score_result2}
188 readonly LFBFL_i_score_command_properties
189 # shellcheck disable=SC2248

```

```

190 get_split_score_simple 1 ${LFBFL_i_max_line_length} ':'
191 declare -r LFBFL_score_command2="${get_split_score_result}"
192 declare -i LFBFL_i_score_command_properties2
193 LFBFL_i_score_command_properties2=${i_get_split_score_result2}
194 readonly LFBFL_i_score_command_properties2
195 declare -r LFBFL_suffix='%'
196 declare -i LFBFL_i=0
197 local LFBFL_cleaned_path1
198 local LFBFL_cleaned_path2
199 local LFBFL_new_lines
200 local LFBFL_new_lines2
201 local LFBFL_new_lines3
202 local LFBFL_file_path
203 local LFBFL_s_format
204 for LFBFL_file_path in "${LFBFL_arr_files_paths[@]"; do
205     printf "Listing file for tex/HTML : %s\n" "${LFBFL_file_path}"
206     # printf "Listing file for tex : %s\n" "${LFBFL_file_path}"
207     # LFBFL_base_file_name=$(basename -- "${LFBFL_file_path}")
208     LFBFL_cleaned_path1="${LFBFL_file_path//_/\_}"
209     LFBFL_cleaned_path2=$(
210         printf "%s" "${LFBFL_file_path}"\
211         | sed --expression='s/\:\/\/:/g;s/\./\/g'
212     )
213     LFBFL_new_lines=" ${LFBFL_cleaned_path1}"
214     if [[ ${#LFBFL_new_lines} -gt LFBFL_i_max_line_length ]]; then
215         # shellcheck disable=SC2248
216         repeated_split_last_line "${LFBFL_new_lines}"\
217             "\
218             ${LFBFL_i_max_line_length}\
219             "${LFBFL_suffix}"\
220             "${LFBFL_score_command}"\
221             ${LFBFL_i_score_command_properties}\
222             "\
223         LFBFL_new_lines=${repeated_split_last_line_result}
224     fi
225     LFBFL_new_lines2=" ${LFBFL_cleaned_path2}"
226     if [[ ${#LFBFL_new_lines2} -gt LFBFL_i_max_line_length ]]; then
227         # shellcheck disable=SC2248
228         repeated_split_last_line "${LFBFL_new_lines2}"\
229             "\
230             ${LFBFL_i_max_line_length}\
231             "${LFBFL_suffix}"\
232             "${LFBFL_score_command2}"\
233             ${LFBFL_i_score_command_properties2}
234         LFBFL_new_lines2=${repeated_split_last_line_result}
235     fi

```

```

236 LFBFL_new_lines3="${LFBFL_file_path}"
237 if [[ ${#LFBFL_new_lines3} -gt LFBFL_i_max_line_length ]]; then
238     # shellcheck disable=SC2248
239     repeated_split_last_line "${LFBFL_new_lines3}"\
240         "\
241         ${LFBFL_i_max_line_length}\
242         "${LFBFL_suffix}"\
243         "${LFBFL_score_command}"\
244         ${LFBFL_i_score_command_properties}
245     LFBFL_new_lines3=${repeated_split_last_line_result}
246 fi
247 LFBFL_s_format="\subsection{\n%s\n}\n\\label{\n%s\n}\n\n"
248 LFBFL_s_format+="\\VerbatimInput[numbers=left,xleftmargin=-5mm] "
249 LFBFL_s_format+="{\n%s\n}\n\n\n"
250 # shellcheck disable=SC2059
251 printf "${LFBFL_s_format}"\
252     "${LFBFL_new_lines}"\
253     "${LFBFL_new_lines2}"\
254     "${LFBFL_new_lines3}"\
255     >> "${LFBFL_temp_files_listing}"
256
257 # printf "Listing file for HTML : %s\n" "${LFBFL_file_path}"
258 ((++LFBFL_i))
259 LFBFL_new_lines="${LFBFL_file_path}"
260 if [[ ${#LFBFL_file_path} -gt LFBFL_i_max_line_length ]]; then
261     # shellcheck disable=SC2248
262     repeated_split_last_line "${LFBFL_new_lines}"\
263         "-->\
264         ${LFBFL_i_max_line_length}\
265         "<!--\
266         "${LFBFL_score_command}"\
267         ${LFBFL_i_score_command_properties}
268     LFBFL_new_lines=${repeated_split_last_line_result}
269 fi
270 {
271     LFBFL_s_format="<h3 id=\"subsection3.%s\">3.%s\n%s\n</h3>\n"
272     LFBFL_s_format+="<pre class=\"numbered_lines\">\n"
273     # shellcheck disable=SC2059
274     printf "${LFBFL_s_format}"\
275         "${LFBFL_i}"\
276         "${LFBFL_i}"\
277         "${LFBFL_new_lines}"
278     sed --expression='s/&/\&amp;/g;s/</\&lt;/g'\
279         < "${LFBFL_file_path}"
280     printf "</pre>\n\n\n"
281 } >> "${LFBFL_temp_files_listing2}"

```

```

282     LFBFL_s_format="          <li><a href=\"#subsection3.%s\">\n%s\n"
283     LFBFL_s_format+="          </a></li>\n"
284     # shellcheck disable=SC2059
285     printf "${LFBFL_s_format}" "${LFBFL_i}" "${LFBFL_new_lines}"\
286     >> "${LFBFL_temp_files_lis}"
287 done
288 overwrite_if_not_equal "${LFBFL_temp_path}/files_listing.tex.sub"\
289     "${LFBFL_temp_files_listing}"
290 # Example of generated content of files_listing.tex.sub:
291 # -----
292 # \subsection{
293 #   build\_and\_checks\_dependencies/licenses\_templates/%
294 # build\_licenses\_templates.exec.sh
295 # }
296 # \label{
297 #   build_and_checks_dependencies:licenses_templates:%
298 # build_licenses_templatesexecsh
299 # }
300 #
301 # \VerbatimInput[numbers=left,xleftmargin=-5mm]{
302 #   build_and_checks_dependencies/licenses_templates/%
303 #   build_licenses_templates.exec.sh
304 # }
305 # -----
306 sed --in-place --expression="s|\\n</pre>|</pre>|g"\
307     -- "${LFBFL_temp_files_listing2}"
308 overwrite_if_not_equal "${LFBFL_temp_path}/files_listing.html.sub"\
309     "${LFBFL_temp_files_listing2}"
310 # Example of generated content of files_listing.html.sub:
311 # -----
312 # <h3 id="subsection3.15">3.15
313 #   build_and_checks_dependencies/licenses_templates/<!--
314 #   -->build_licenses_templates.exec.sh
315 # </h3>
316 # ...
317 # <h3 id="subsection3.33">3.33
318 #   build_and_checks_variables/.gitignore
319 # </h3>
320 # <pre class="numbered_lines">
321 #   temp/
322 #   upgrade_venvs_ts
323 # </pre>
324 # -----
325 overwrite_if_not_equal "${LFBFL_temp_path}/files_lis.html.sub"\
326     "${LFBFL_temp_files_lis}"
327 # Example of generated content of files_lis.html.sub:

```



```

328 # -----
329 #      <li><a href="#subsection3.15">
330 # build_and_checks_dependencies/licenses_templates/
```

```

374 LFBFL_char="${LFBFL_prefix:${LFBFL_i_prefix_last_position}:1}"
375 # printf "LFBFL_char: %s\n" "${LFBFL_char}"
376 LFBFL_prefix=$(
377     printf "%s" "${LFBFL_prefix}"\
378     | sed --regex-extended --expression='s/[^ ]+$//g'
379 )
380 if [[ "${LFBFL_char}" == "L" ]]; then
381     LFBFL_prefix+=" "
382 else
383     LFBFL_prefix+="|"
384 fi
385 # printf "LFBFL_prefix: %s\n" "${LFBFL_prefix}"
386 LFBFL_file_name=$(
387     printf "%s" "${LFBFL_line}"\
388     | sed --regex-extended --expression='s|.* ([^ ]+)$|\1|g'
389 )
390 # printf "LFBFL_file_name: %s\n" "${LFBFL_file_name}"
391 LFBFL_i_keep_length=$(( ${#LFBFL_line} - ${#LFBFL_file_name} ))
392 LFBFL_line_start=${LFBFL_line:0:${LFBFL_i_keep_length}}
393 LFBFL_line_start=$(
394     printf "%s" "${LFBFL_line_start}"\
395     | sed --expression='s/ *$//g'
396 )
397 # printf "LFBFL_line_start: %s\n" "${LFBFL_line_start}"
398 LFBFL_new_lines="${LFBFL_prefix}${LFBFL_file_name}"
399 if [[ ${#LFBFL_new_lines} -gt LFBFL_i_max_line_length ]]; then
400     # shellcheck disable=SC2248
401     repeated_split_last_line "${LFBFL_new_lines}"\
402     "${LFBFL_prefix}"\
403     "${LFBFL_i_max_line_length}"\
404     ""\
405     ""\
406     ""
407     LFBFL_new_lines=${repeated_split_last_line_result}
408 fi
409 printf "%s\n%s\n" "${LFBFL_line_start}" "${LFBFL_new_lines}"\
410 > "${LFBFL_tree_path}.some_line.temp"
411 insert_file_at_token "${LFBFL_tree_path}"\
412 "${LFBFL_line}"\
413 "${LFBFL_tree_path}.some_line.temp"\
414 ""\
415 --quiet
416 done
417 rm --force -- "${LFBFL_tree_path}.some_line.temp"
418 done
419

```

```

420 overwrite_if_not_equal "${LFBFL_temp_path}/current_tree.txt"\
421     "${LFBFL_temp_path}/current_tree.txt.temp" --keep-temp --tree-mode
422
423 local LFBFL_tex_path_start
424 LFBFL_tex_path_start="${LFBFL_temp_path}/${LFBFL_repository_name}.tex"
425 readonly LFBFL_tex_path_start
426 local LFBFL_html_path_start
427 LFBFL_html_path_start="${LFBFL_temp_path}/${LFBFL_repository_name}.html"
428 readonly LFBFL_html_path_start
429
430 if [[ -f "${LFBFL_subdir2}/${LFBFL_repository_name}.tex.tpl" ]]; then
431     # If there is a template, we init the process from it.
432     cp -- "${LFBFL_subdir2}/${LFBFL_repository_name}.tex.tpl"\
433         "${LFBFL_tex_path_start}.1"
434 elif [[ -f "${LFBFL_subdir2}/${LFBFL_repository_name}.tex" ]]; then
435     # Otherwise if there is a tex file, we init the process from it.
436     cp -- "${LFBFL_subdir2}/${LFBFL_repository_name}.tex"\
437         "${LFBFL_tex_path_start}.1"
438 else
439     printf "Neither .tex.tpl, nor .tex in ./s/.\\n" "${LFBFL_subdir2}"
440 fi
441
442 # Same logic with repository HTML file.
443 if [[ -f "${LFBFL_subdir2}/${LFBFL_repository_name}.html.tpl" ]]; then
444     cp -- "${LFBFL_subdir2}/${LFBFL_repository_name}.html.tpl"\
445         "${LFBFL_html_path_start}.1"
446 elif [[ -f "${LFBFL_repository_name}.html" ]]; then
447     cp -- "${LFBFL_repository_name}.html" "${LFBFL_html_path_start}.1"
448 else
449     printf "Neither .html.tpl in ./s/, nor .html in ./\\.n"
450         "${LFBFL_subdir2}"
451 fi
452
453 # shellcheck disable=SC2001
454 printf "%s\\n" "${LFBFL_abstract}"\
455     | sed --expression='s/\\n/\\n/g'\
456     > "${LFBFL_temp_path}/abstract_temp"
457
458 # shellcheck disable=SC2001
459 printf "%s\\n" "${LFBFL_acknowledgments}"\
460     | sed --expression='s/\\n/\\n/g'\
461     > "${LFBFL_temp_path}/acknowledgments_temp"
462
463 # But the filling still occurs, in case the dev want to refill
464 # part of the tex/html file that he modified with @token@
465 # using some computed results.

```

```

466 # Tex filling:
467 if [[ -f "${LFBFL_tex_path_start}.1" ]]; then
468     sed --in-place\
469         --expression="s|@repository_name@|${LFBFL_repository_name}|g"\
470         --expression="s|@repository_web_url@|${LFBFL_repository_web_url}|g"\
471         --expression="s|@repository_git_url@|${LFBFL_repository_git_url}|g"\
472         --expression="s|@author_email@|${LFBFL_author_email}|g"\
473         --expression="s|@author_full_name@|${LFBFL_author_full_name}|g"\
474         --expression="s|@author_website@|${LFBFL_author_website}|g"\
475         --expression="s|@current_date@|${LFBFL_current_date}|g"\
476         --expression="s|@current_git_SHA1@|${LFBFL_current_git_SHA1}|g"\
477         --expression="s|@number_of_commits@|${LFBFL_i_number_of_commits}|g"\
478         --expression="s|@number_of_lines@|${LFBFL_number_of_lines}|g"\
479         -- "${LFBFL_tex_path_start}.1"
480
481     insert_file_at_token "${LFBFL_tex_path_start}.1"\
482         @abstract@\
483         "${LFBFL_temp_path}/abstract_temp"\
484         "${LFBFL_tex_path_start}.2"
485
486     insert_file_at_token "${LFBFL_tex_path_start}.2"\
487         @acknowledgments@\
488         "${LFBFL_temp_path}/acknowledgments_temp"\
489         "${LFBFL_tex_path_start}.3"
490
491     insert_file_at_token "${LFBFL_tex_path_start}.3"\
492         @current_tree_light@\
493         "${LFBFL_temp_path}/current_tree_light.txt"\
494         "${LFBFL_tex_path_start}.4"
495
496     insert_file_at_token "${LFBFL_tex_path_start}.4"\
497         @current_tree@\
498         "${LFBFL_temp_path}/current_tree.txt"\
499         "${LFBFL_tex_path_start}.5"
500
501     insert_file_at_token "${LFBFL_tex_path_start}.5"\
502         @dependencies_notes@\
503         "${LFBFL_temp_path}/dependencies_notes.tex.sub"\
504         "${LFBFL_tex_path_start}.6"
505
506     insert_file_at_token "${LFBFL_tex_path_start}.6"\
507         @files_listing_VerbatimInput@\
508         "${LFBFL_temp_path}/files_listing.tex.sub"\
509         "${LFBFL_tex_path_start}.7"
510
511     overwrite_if_not_equal\

```

```

512     "${LFBFL_subdir2}/${LFBFL_repository_name}.tex"\
513     "${LFBFL_tex_path_start}.7" --keep-temp
514 fi
515
516 # HTML filling:
517 declare -i LFBFL_i_HTML_updated=0
518 if [[ -f "${LFBFL_html_path_start}.1" ]]; then
519     sed --in-place\
520         --expression="s|@repository_name@|${LFBFL_repository_name}|g"\
521         --expression="s|@repository_web_url@|${LFBFL_repository_web_url}|g"\
522         --expression="s|@repository_git_url@|${LFBFL_repository_git_url}|g"\
523         --expression="s|@author_email@|${LFBFL_author_email}|g"\
524         --expression="s|@author_full_name@|${LFBFL_author_full_name}|g"\
525         --expression="s|@author_website@|${LFBFL_author_website}|g"\
526         --expression="s|@current_date@|${LFBFL_current_date}|g"\
527         --expression="s|@current_git_SHA1@|${LFBFL_current_git_SHA1}|g"\
528         --expression="s|@number_of_commits@|${LFBFL_i_number_of_commits}|g"\
529         --expression="s|@number_of_lines@|${LFBFL_number_of_lines}|g"\
530         -- "${LFBFL_html_path_start}.1"
531
532     insert_file_at_token "${LFBFL_html_path_start}.1"\
533         @abstract@\
534         "${LFBFL_temp_path}/abstract_temp"\
535         "${LFBFL_html_path_start}.2"
536
537     insert_file_at_token "${LFBFL_html_path_start}.2"\
538         @acknowledgments@\
539         "${LFBFL_temp_path}/acknowledgments_temp"\
540         "${LFBFL_html_path_start}.3"
541
542     insert_file_at_token "${LFBFL_html_path_start}.3"\
543         @files_lis@\
544         "${LFBFL_temp_path}/files_lis.html.sub"\
545         "${LFBFL_html_path_start}.4"
546
547     insert_file_at_token "${LFBFL_html_path_start}.4"\
548         @current_tree_light@\
549         "${LFBFL_temp_path}/current_tree_light.txt"\
550         "${LFBFL_html_path_start}.5"
551
552     insert_file_at_token "${LFBFL_html_path_start}.5"\
553         @current_tree@\
554         "${LFBFL_temp_path}/current_tree.txt"\
555         "${LFBFL_html_path_start}.6"
556
557     insert_file_at_token "${LFBFL_html_path_start}.6"\

```

```

558     @dependencies_notes@\
559     "${LFBFL_temp_path}/dependencies_notes.html.sub"\
560     "${LFBFL_html_path_start}.7"
561
562     insert_file_at_token "${LFBFL_html_path_start}.7"\
563     @files_listing_HTMLPreInput@\
564     "${LFBFL_temp_path}/files_listing.html.sub"\
565     "${LFBFL_html_path_start}.8"
566
567     overwrite_if_not_equal "${LFBFL_repository_name}.html"\
568     "${LFBFL_html_path_start}.8" --keep-temp
569     LFBFL_i_HTML_updated=$?
570 fi
571
572 # The HTML contains everything including listings with source code.
573 # If it doesn't get updated,
574 # then it is useless to recompute the PDF.
575 if [[ LFBFL_i_HTML_updated -eq 0 ]]; then
576     return
577 fi
578
579 local LFBFL_latex_command=""
580 grep_variable "${LFBFL_data_file_path}" latex_command\
581     --result-variable-prefix="LFBFL_"\
582     --replace-line-returns-by=""
583
584 case ${LFBFL_latex_command} in
585     pdflatex) : ;;
586     lualatex) : ;;
587     *) printf "Unsupported latex command" ; return 1 ;;
588 esac
589
590 local LFBFL_command
591 LFBFL_command="${LFBFL_latex_command}"
592 LFBFL_command+=" ' ${LFBFL_subdir2}/${LFBFL_repository_name}.tex' "
593 if [[ LFBFL_i_verbose -eq 0 ]]; then
594     LFBFL_command+=" > /dev/null"
595 fi
596 readonly LFBFL_command
597
598 for ((LFBFL_i = 0; LFBFL_i < 3; ++LFBFL_i)); do
599     eval -- "${LFBFL_command}"
600 done
601
602 LFBFL_files_to_temp=(\
603     "${LFBFL_repository_name}.aux"\

```

```

604     "${LFBFL_repository_name}.log"\
605     "${LFBFL_repository_name}.out"\
606     "${LFBFL_repository_name}.toc"
607 )
608 for LFBFL_file_name in "${LFBFL_files_to_temp[@]}"; do
609     mv -- "${LFBFL_file_name}" "${LFBFL_temp_path}/"
610 done
611 }
612
613 create_PDF "$@"

```

3.13 build_and_checks_dependencies/generate_from_template.lib.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023–2026 Laurent Frédéric Bernard François Lyaudet
24 # This file was renamed from "generate_from_template.sh" to
25 # "generate_from_template.lib.sh".
26
27 LFBFL_subdir="build_and_checks_dependencies"
28 # shellcheck source=lines_filters.lib.sh
29 source "${LFBFL_subdir}/lines_filters.lib.sh"
30 # shellcheck source=overwrite_if_not_equal.lib.sh
31 source "${LFBFL_subdir}/overwrite_if_not_equal.lib.sh"
32
33 generate_from_template_with_block_comments() {

```

```

34 # $1=base_file_path
35 # $2=target_file_path
36 # $3=enter_block_comment
37 # $4=exit_block_comment
38 local LFBFL_temp
39 LFBFL_temp="$2.generate_from_template_with_block_comments.temp"
40 readonly LFBFL_temp
41 {
42     printf "%s\n" "$3"
43     cat -- "$1"
44     printf "%s\n" "$4"
45 } > "${LFBFL_temp}"
46 overwrite_if_not_equal "$2" "${LFBFL_temp}"
47 }
48
49 generate_from_template_with_line_comments() {
50     # $1=base_file_path
51     # $2=target_file_path
52     # $3=line_comment_prefix
53     # $4=optional_post_processing
54     # $5=file_prefix
55     local LFBFL_temp
56     LFBFL_temp="$2.generate_from_template_with_line_comments.temp"
57     readonly LFBFL_temp
58     if [[ -n "$5" ]]; then
59         printf "%s\n" "$5" \
60             > "${LFBFL_temp}"
61     fi
62     sed --expression="s~^~$3~g" -- "$1" \
63         >> "${LFBFL_temp}"
64     if [[ -n "$4" ]]; then
65         eval -- "$4"
66     fi
67     overwrite_if_not_equal "$2" "${LFBFL_temp}"
68 }
69
70 split_file_in_two() {
71     # $1=file_path
72     # $2=token assume that token is the only thing on his line,
73     #     except for a possible indentation.
74     # $3=path_of_part1_of_file
75     # $4=path_of_part2_of_file
76     # We cannot add --line-regexp with --fixed-strings because of the
77     # possible indentation in file,
78     # instead we use grep_fixed_string_with_anchor.
79     declare -ir LFBFL_i_line_number=$(

```



```

80     grep_fixed_string_with_anchor "$1" "$2"\
81     --enforce-line-ends-with-fixed-string --line-number\
82     | head --lines=1\
83     | cut --delimiter=':' --fields=1
84 )
85 declare -ir LFBFL_i_line_count=$((ll_wc -l -n "$1")
86 declare -ir LFBFL_i_lines_after=$((
87     LFBFL_i_line_count - LFBFL_i_line_number
88 ))
89 head --lines="$((LFBFL_i_line_number - 1))" -- "$1"\
90     > "$3"
91 tail --lines="$ {LFBFL_i_lines_after}" -- "$1"\
92     > "$4"
93 }
94
95 insert_file_at_token() {
96     # $1=file_path
97     # $2=token assume that token is the only thing on his line,
98     #     except for a possible indentation.
99     # $3=path_of_file_to_insert
100    # $4=path_of_result_file
101    # Options:
102    #     $5=--quiet to suppress diff output in overwrite_if_not_equal
103    declare -r LFBFL_start_file_path="$1.insert_file_at_token1.temp"
104    declare -r LFBFL_end_file_path="$1.insert_file_at_token2.temp"
105    local LFBFL_result_file_path
106    if [[ -n "$4" ]]; then
107        LFBFL_result_file_path="$4"
108    else
109        LFBFL_result_file_path="$1.insert_file_at_token3.temp"
110    fi
111    readonly LFBFL_result_file_path
112    split_file_in_two "$1" "$2" "${LFBFL_start_file_path}"\
113        "${LFBFL_end_file_path}"
114    cat -- "${LFBFL_start_file_path}" "$3" "${LFBFL_end_file_path}"\
115        > "${LFBFL_result_file_path}"
116    rm -- "${LFBFL_start_file_path}" "${LFBFL_end_file_path}"
117    if [[ -z "$4" ]]; then
118        overwrite_if_not_equal "$1" "${LFBFL_result_file_path}" "$5"
119    fi
120 }

```

3.14 build_and_checks_dependencies/get_common_text_glob_patterns.lib.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.

```

```

3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
24 # This file was renamed from "get_common_text_glob_patterns.sh"
25 # to "get_common_text_glob_patterns.lib.sh".
26
27 get_COMMON_TEXT_PATHS_GLOB_PATTERNS() {
28     if [[ -n "${COMMON_TEXT_PATHS_GLOB_PATTERNS}" ]]; then
29         return
30     fi
31
32     declare -agr COMMON_TEXT_PATHS_GLOB_PATTERNS=(
33         '**/*.c'
34         '**/*.css'
35         '**/*.h'
36         '**/*.htm'
37         '**/*.html'
38         '**/*.ini'
39         '**/*.js'
40         '**/*.json'
41         '**/*.md'
42         '**/*.php'
43         '**/*.py'
44         '**/*.rs'
45         '**/*.rlib'
46         '**/*.sh'
47         '**/*.sql'
48         '**/*.sub'

```

```

49     '**/*.tex'
50     '**/*.toml'
51     '**/*.tpl'
52     '**/*.ts'
53     '**/*.txt'
54     '**/*.xml'
55     '**/*.yaml'
56     '**/COPYING'
57     '**/COPYING.LESSER'
58     '**/pre-commit'
59     '**/post-commit'
60     '**/.gitignore'
61     '**/py.typed'
62 )
63 }
64
65
66 get_COMMON_TEXT_FILES_GLOB_PATTERNS() {
67     if [[ -n "${COMMON_TEXT_FILES_GLOB_PATTERNS}" ]]; then
68         return
69     fi
70
71     declare -agr COMMON_TEXT_FILES_GLOB_PATTERNS=(
72         '*.c'
73         '*.css'
74         '*.h'
75         '*.htm'
76         '*.html'
77         '*.ini'
78         '*.js'
79         '*.json'
80         '*.md'
81         '*.php'
82         '*.py'
83         '*.rs'
84         '*.rlib'
85         '*.sh'
86         '*.sql'
87         '*.sub'
88         '*.tex'
89         '*.toml'
90         '*.tpl'
91         '*.ts'
92         '*.txt'
93         '*.xml'
94         '*.yaml'

```

```

95     'COPYING'
96     'COPYING.LESSER'
97     'pre-commit'
98     'post-commit'
99     '.gitignore'
100    'py.typed'
101  )
102  }

```

3.15 build_and_checks_dependencies/grammar_and_spelling_check.lib.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023–2026 Laurent Frédéric Bernard François Lyaudet
24 # 2026-03-22T15:30+01:00: This file was renamed from
25 # "grammar_and_spell_check.lib.sh"
26 # to
27 # "grammar_and_spelling_check.lib.sh".
28 # This file was renamed from "grammar_and_spell_check.sh"
29 # to "grammar_and_spell_check.lib.sh".
30
31 LFBFL_subdir="build_and_checks_dependencies"
32 # shellcheck source=common_options.lib.sh
33 source "${LFBFL_subdir}/common_options.lib.sh"
34 # shellcheck source=get_common_text_glob_patterns.lib.sh
35 source "${LFBFL_subdir}/get_common_text_glob_patterns.lib.sh"

```

```

36 # shellcheck source=lines_filters.lib.sh
37 source "${LFBFL_subdir}/lines_filters.lib.sh"
38
39 grammar_and_spelling_check() {
40     # $1=configuration_path build_and_checks_variables/repository_data.txt
41     # Options:
42     #     --verbose
43     #     --work-directory=""
44     declare -i LFBFL_i_verbose=0
45     get_verbose_option "$@"
46     local LFBFL_work_directory=""
47     get_work_directory_option "$@"
48     declare -a LFBFL_return_traps_stack
49     init_return_trap
50     pushd_to_work_directory --trap-popd
51     can_continue_after_enhanced_pushd || return 1
52
53     enhanced_set_shell_option pipefail --trap-unset
54
55     get_COMMON_TEXT_FILES_GLOB_PATTERNS
56     local LFBFL_grammar_and_spelling_checker_command=""
57     grep_variable "$1" grammar_and_spelling_checker_command\
58         --result-variable-prefix=LFBFL_\
59         --replace-line-returns-by=""
60     declare -r LFBFL_command="${LFBFL_grammar_and_spelling_checker_command}"
61     if [[ -z "${LFBFL_command}" ]]; then
62         if [[ LFBFL_i_verbose -eq 1 ]]; then
63             printf "grammar_and_spelling_check: No command in configuration.\n"
64         fi
65         return
66     fi
67     if [[ LFBFL_i_verbose -eq 1 ]]; then
68         printf "grammar_and_spelling_check: Command found: %s.\n" \
69             "${LFBFL_command}"
70     fi
71     local LFBFL_file_path
72     local LFBFL_s_files_paths
73     declare -a LFBFL_arr_files_paths
74     local LFBFL_pattern
75     local LFBFL_eval_string
76     for LFBFL_pattern in "${COMMON_TEXT_FILES_GLOB_PATTERNS[@]"; do
77         if [[ LFBFL_i_verbose -eq 1 ]]; then
78             printf "grammar_and_spelling_check: Iterating on pattern: %s.\n" \
79                 "${LFBFL_pattern}"
80         fi
81         LFBFL_s_files_paths=$(

```

```

82     find . -type f -name "${LFBFL_pattern}" -printf '%P\n'\
83     | relevant_find
84 )
85 if [[ -z "${LFBFL_s_files_paths}" ]]; then
86     [[ LFBFL_i_verbose -eq 1 ]]\
87     && printf "grammar_and_spelling_check: No file found.\n"
88     continue
89 fi
90 mapfile -t LFBFL_arr_files_paths <<< "${LFBFL_s_files_paths}"
91 for LFBFL_file_path in "${LFBFL_arr_files_paths[@]}"; do
92     LFBFL_eval_string="${LFBFL_command} ${LFBFL_file_path}"
93     eval -- "${LFBFL_eval_string}"
94 done
95 done
96 }

```

3.16 build_and_checks_dependencies/licenses_templates/build_licenses_templates.exec.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023–2026 Laurent Frédéric Bernard François Lyaudet
24 # This file was renamed from "build_licenses_templates.sh"
25 # to "build_licenses_templates.exec.sh".
26
27 LFBFL_subdir="build_and_checks_dependencies"
28 # shellcheck source=check_shell_scripts_beginnings.lib.sh

```

```

29 source "${LFBFL_subdir}/check_shell_scripts_beginnings.lib.sh"
30 # shellcheck source=common_options.lib.sh
31 source "${LFBFL_subdir}/common_options.lib.sh"
32 # shellcheck source=comparisons.lib.sh
33 source "${LFBFL_subdir}/comparisons.lib.sh"
34 # shellcheck source=generate_from_template.lib.sh
35 source "${LFBFL_subdir}/generate_from_template.lib.sh"
36 # shellcheck source=lines_filters.lib.sh
37 source "${LFBFL_subdir}/lines_filters.lib.sh"
38 # shellcheck source=overwrite_if_not_equal.lib.sh
39 source "${LFBFL_subdir}/overwrite_if_not_equal.lib.sh"
40
41 enhanced_set_bash_option extglob
42 # shellcheck source=repository_data.lib.sh
43 source "${LFBFL_subdir}/repository_data.lib.sh"
44 # shellcheck disable=SC2154,SC2309
45 [[ i_enhanced_set_bash_option_extglob_result -eq 0 ]]\
46   && enhanced_unset_bash_option extglob
47
48 build_licenses_templates() {
49   # Options:
50   #   --verbose
51   #   --work-directory=""
52   declare -i LFBFL_i_verbose=0
53   get_verbose_option "$@"
54   local LFBFL_work_directory=""
55   get_work_directory_option "$@"
56   declare -a LFBFL_return_traps_stack
57   init_return_trap
58
59   enhanced_set_shell_option pipefail --trap-unset
60
61   local LFBFL_s_format
62
63   # Source
64   local LFBFL_license_source_subdir
65   LFBFL_license_source_subdir="${LFBFL_subdir}/licenses_templates/"
66   readonly LFBFL_license_source_subdir
67   local LFBFL_source_license_prefix="${LFBFL_license_source_subdir}"
68   LFBFL_source_license_prefix+="license_file_header_"
69   readonly LFBFL_source_license_prefix
70   # Target
71   local LFBFL_license_target_subdir
72   LFBFL_license_target_subdir="${LFBFL_work_directory}/"
73   LFBFL_license_target_subdir="build_and_checks_variables/temp/"
74   readonly LFBFL_license_target_subdir

```

```

75 local LFBFL_target_license_prefix="${LFBFL_license_target_subdir}"
76 LFBFL_target_license_prefix+="license_file_header_"
77 readonly LFBFL_target_license_prefix
78
79 declare -ar LFBFL_licenses=(
80     "AGPLv3+"
81     "GPLv3+"
82     "LGPLv3+"
83 )
84
85 # -----
86 # Various language definitions for text file formats
87 declare -ar LFBFL_block_comment_languages=(
88     "c"
89     "py"
90     "xml"
91 )
92 declare -ar LFBFL_block_comment_enters=(
93     '/ * '
94     ' " " '
95     ' <!-- '
96 )
97 declare -ar LFBFL_block_comment_exits=(
98     ' * / '
99     ' " " '
100    ' --> '
101 )
102 equal "${#LFBFL_block_comment_languages[@]}" "\
103     "${#LFBFL_block_comment_enters[@]}" "\
104     "${#LFBFL_block_comment_exits[@]}"
105 declare -i LFBFL_i_equal_result=$?
106 if [[ LFBFL_i_equal_result -eq 0 ]]; then
107     printf $'/!\\Problem with the definitions of languages arrays 1/!\\n'
108     return 1
109 fi
110
111 declare -ar LFBFL_line_comment_languages=(
112     "rs"
113     "sh"
114     "sql"
115     "tex"
116 )
117 declare -ar LFBFL_line_comment_prefixes=(
118     '// '
119     '# '
120     '-- '

```



```

121     ' % '
122 )
123 equal "${#LFBFL_line_comment_languages[@]}"\
124     "${#LFBFL_line_comment_prefixes[@]}"
125 LFBFL_i_equal_result=$?
126 if [[ LFBFL_i_equal_result -eq 0 ]]; then
127     printf $'/!\Problem with the definitions of languages arrays 2/!\n'
128     return 1
129 fi
130 # -----
131
132 # -----
133 # We generate the license header templates adapted to various text
134 # files formats.
135 # Kamoulox do endfor, Jacques Beauregard XD
136 # (C'est toujours mieux que l'inverse :) !)
137 # for do endfor -> for do done (Fort Doux Donne).
138 local LFBFL_some_license
139 local LFBFL_license_prefix
140 local LFBFL_license_prefix2
141 local LFBFL_extension
142 local LFBFL_license_file_path
143 local LFBFL_enter_string
144 local LFBFL_exit_string
145 local LFBFL_temp2
146 local LFBFL_prefix_string
147 local LFBFL_intermediate_file_path
148 local LFBFL_file_prefix
149 declare -i LFBFL_i_generate_from_template_result
150 declare -i LFBFL_i
151 for LFBFL_some_license in "${LFBFL_licenses[@]"}; do
152     LFBFL_license_prefix="${LFBFL_source_license_prefix}"
153     LFBFL_license_prefix+="${LFBFL_some_license}"
154     LFBFL_license_prefix2="${LFBFL_target_license_prefix}"
155     LFBFL_license_prefix2+="${LFBFL_some_license}"
156     for (
157         LFBFL_i = 0;
158         LFBFL_i < ${#LFBFL_block_comment_languages[@]};
159         ++LFBFL_i
160     ); do
161         LFBFL_extension=${LFBFL_block_comment_languages[LFBFL_i]}
162         LFBFL_license_file_path="${LFBFL_license_prefix2}"
163         LFBFL_license_file_path+=".${LFBFL_extension}"
164         LFBFL_enter_string=${LFBFL_block_comment_enters[LFBFL_i]}
165         LFBFL_exit_string=${LFBFL_block_comment_exits[LFBFL_i]}
166         generate_from_template_with_block_comments\

```

```

167     "${LFBFL_license_prefix}.tpl"\
168     "${LFBFL_license_file_path}.tpl"\
169     "${LFBFL_enter_string}" "${LFBFL_exit_string}"
170 LFBFL_i_generate_from_template_result=$?
171 if [[ LFBFL_i_verbose -eq 1 ]]; then
172     if [[ LFBFL_i_generate_from_template_result -eq 1 ]]; then
173         printf "License template %s.tpl updated.\n"\
174             "${LFBFL_license_file_path}"
175     elif [[ LFBFL_i_generate_from_template_result -eq 2 ]]; then
176         printf "License template %s.tpl created.\n"\
177             "${LFBFL_license_file_path}"
178     fi
179 fi
180 done
181 LFBFL_temp2=".generate_from_template_with_line_comments.temp"
182 for (
183     LFBFL_i = 0;
184     LFBFL_i < ${#LFBFL_line_comment_languages[@]};
185     ++LFBFL_i
186 ); do
187     LFBFL_extension=${LFBFL_line_comment_languages[LFBFL_i]}
188     LFBFL_license_file_path="${LFBFL_license_prefix2}"
189     LFBFL_license_file_path+=".${LFBFL_extension}"
190     LFBFL_prefix_string=${LFBFL_line_comment_prefixes[LFBFL_i]}
191     LFBFL_intermediate_file_path="${LFBFL_license_file_path}.tpl"
192     LFBFL_intermediate_file_path+="${LFBFL_temp2}"
193     LFBFL_file_prefix=""
194     if [[ "${LFBFL_extension}" == "sh" ]]; then
195         LFBFL_file_prefix="${LFBFL_SHELL_SCRIPT_BEGINNING}"
196     fi
197     # The sed command is here to remove trailing spaces of previously
198     # empty lines after comment prefix is added to the line.
199     generate_from_template_with_line_comments\
200         "${LFBFL_license_prefix}.tpl"\
201         "${LFBFL_license_file_path}.tpl"\
202         "${LFBFL_prefix_string}"\
203         "sed -Ei -e 's/\s*$//g' '${LFBFL_intermediate_file_path}'"\
204         "${LFBFL_file_prefix}"
205     LFBFL_i_generate_from_template_result=$?
206     if [[ LFBFL_i_verbose -eq 1 ]]; then
207         if [[ LFBFL_i_generate_from_template_result -eq 1 ]]; then
208             printf "License template %s.tpl updated.\n"\
209                 "${LFBFL_license_file_path}"
210         elif [[ LFBFL_i_generate_from_template_result -eq 2 ]]; then
211             printf "License template %s.tpl created.\n"\
212                 "${LFBFL_license_file_path}"

```

```

213         fi
214     fi
215 done
216 done
217 # -----
218
219 # Now that base license templates generated languages license
220 # templates in work directory, we can go there.
221 pushd_to_work_directory --trap-popd
222 can_continue_after_enhanced_pushd || return 1
223
224 local LFBFL_data_file_path="build_and_checks_variables/"
225 LFBFL_data_file_path+="repository_data.txt"
226 readonly LFBFL_data_file_path
227 local LFBFL_repository_name=""
228 grep_variable "${LFBFL_data_file_path}" repository_name\
229     --result-variable-prefix="LFBFL_"\
230     --replace-line-returns-by=""
231 local LFBFL_license=""
232 grep_variable "${LFBFL_data_file_path}" license\
233     --result-variable-prefix="LFBFL_"
234 local LFBFL_license2=""
235 grep_variable "${LFBFL_data_file_path}" license2\
236     --result-variable-prefix="LFBFL_"
237 local LFBFL_author_full_name=""
238 grep_variable "${LFBFL_data_file_path}" author_full_name\
239     --result-variable-prefix="LFBFL_"\
240     --replace-line-returns-by=""
241
242 LFBFL_license_prefix="build_and_checks_variables/temp/"
243 LFBFL_license_prefix+="license_file_header_"
244 readonly LFBFL_license_prefix
245 LFBFL_license_prefix2="${LFBFL_license_prefix}${LFBFL_license}"
246 readonly LFBFL_license_prefix2
247 local LFBFL_license_prefix3="${LFBFL_license_prefix}${LFBFL_license2}"
248 readonly LFBFL_license_prefix3
249
250 # First year according to current state of git repository.
251 declare -ir LFBFL_i_first_year=$(
252     git log\
253     | grep 'Date:'\
254     | tail --lines=1\
255     | cut --delimiter=' ' --fields=8
256 )
257 # Last year according to current state of git repository.
258 declare -ir LFBFL_i_last_year=$(

```

```

259     git log\
260     | grep 'Date:'\
261     | head --lines=1\
262     | cut --delimiter=' ' --fields=8
263 )
264 local LFBFL_copyright_string
265 LFBFL_copyright_string="${LFBFL_i_first_year}-${LFBFL_i_last_year}"
266 LFBFL_copyright_string+="${LFBFL_author_full_name}"
267 readonly LFBFL_copyright_string
268
269 LFBFL_files_without_license_header=""
270 grep_variable_with_multiple_files "${LFBFL_data_file_path}"\
271     files_without_license_header\
272     --result-variable-prefix="LFBFL_"
273 declare -a LFBFL_arr_files_without_license_header
274 if [[ -n "${LFBFL_files_without_license_header}" ]]; then
275     mapfile -t LFBFL_arr_files_without_license_header\
276         <<< "${LFBFL_files_without_license_header}"
277 fi
278
279 prepare_filled_license_file_block() {
280     # $1=license_file_path
281     sed --expression="s/@repository_name@/${LFBFL_repository_name}/g"\
282         --expression="s/@copyright_string@/${LFBFL_copyright_string}/g"\
283         -- "$1.tpl"\
284         > "$1.temp"
285     overwrite_if_not_equal "$1" "$1.temp"
286     declare -ir LFBFL_i_result=$?
287     if [[ LFBFL_i_verbose -eq 1 ]]; then
288         if [[ LFBFL_i_result -eq 1 ]]; then
289             printf "License template %s updated.\n" "$1"
290         elif [[ LFBFL_i_result -eq 2 ]]; then
291             printf "License template %s created.\n" "$1"
292         fi
293     fi
294     head --lines=-1 -- "$1"\
295     | tail --lines=+2\
296     > "$1.temp"
297     # Strange world: tail --lines=-1 was working
298     # to exclude first line.
299     # I tested it months ago, and saw with my eyes the start and end
300     # block comments removed with:
301     # head --lines=-1 "$1" | tail --lines=-1.
302     # Now, man page says to use --lines=+2 instead.
303     # Welcome in the world where AI change your environment and your
304     # documentation on the fly...

```

```

305     }
306
307     declare -Ar LFBFL_all_block_comment_languages=(
308         ["c"]="c"
309         ["css"]="c"
310         ["html"]="xml"
311         ["php"]="c"
312         ["py"]="py"
313         ["js"]="c"
314         ["ts"]="c"
315         ["xml"]="xml"
316     )
317
318     local LFBFL_key
319     local LFBFL_dest
320     local LFBFL_license_file_path2
321     declare -i LFBFL_i_not_subfile
322     declare -i LFBFL_i_not_subfile2
323     local LFBFL_file_path
324     local LFBFL_file_path2
325     local LFBFL_s_files_paths
326     declare -a LFBFL_arr_files_paths
327     declare -i LFBFL_i_is_whitelisted
328     for LFBFL_key in "${!LFBFL_all_block_comment_languages[@]}"; do
329         LFBFL_dest=${LFBFL_all_block_comment_languages[${LFBFL_key}]}
330         LFBFL_license_file_path="${LFBFL_license_prefix2}.${LFBFL_dest}"
331         prepare_filled_license_file_block "${LFBFL_license_file_path}"
332         if [[ -n "${LFBFL_license2}" ]]; then
333             LFBFL_license_file_path2="${LFBFL_license_prefix3}"
334             LFBFL_license_file_path2+=".${LFBFL_dest}"
335             prepare_filled_license_file_block "${LFBFL_license_file_path2}"
336         fi
337
338         LFBFL_s_files_paths=(
339             find . -type f -iregex ".$*\.\.(${LFBFL_key})\|${LFBFL_key}\.tpl\)" \
340                 -printf '%P\n' \
341                 | relevant_find
342         )
343         if [[ -z "${LFBFL_s_files_paths}" ]]; then
344             if [[ LFBFL_i_verbose -eq 1 ]]; then
345                 LFBFL_s_format="build_licenses_templates: "
346                 LFBFL_s_format+="No file found with extension .%s or .%s.tpl.\n"
347                 # shellcheck disable=SC2059
348                 printf "${LFBFL_s_format}" "${LFBFL_key}" "${LFBFL_key}"
349             fi
350             continue

```

```

351     fi
352     mapfile -t LFBFL_arr_files_paths <<< "${LFBFL_s_files_paths}"
353     for LFBFL_file_path in "${LFBFL_arr_files_paths[@]};" do
354         LFBFL_i_is_whitelisted=0
355         for LFBFL_file_path2 in\
356             "${LFBFL_arr_files_without_license_header[@]}";
357         do
358             if [[ "${LFBFL_file_path}" == "${LFBFL_file_path2}" ]]; then
359                 LFBFL_i_is_whitelisted=1
360             fi
361         done
362         if [[ LFBFL_i_is_whitelisted -eq 1 ]]; then
363             continue
364         fi
365         is_subfile "${LFBFL_file_path}"\
366             "${LFBFL_license_file_path}.temp"
367         LFBFL_i_not_subfile=$?
368         LFBFL_i_not_subfile2=1
369         if [[ -n "${LFBFL_license2}" ]]; then
370             is_subfile "${LFBFL_file_path}"\
371                 "${LFBFL_license_file_path2}.temp"
372             LFBFL_i_not_subfile2=$?
373         fi
374         if [[ LFBFL_i_not_subfile -ge 1 && LFBFL_i_not_subfile2 -ge 1 ]];
375         then
376             printf "File %s has no/wrong license header?\n"\
377                 "${LFBFL_file_path}"
378         fi
379     done
380     rm -- "${LFBFL_license_file_path}.temp"
381     if [[ -n "${LFBFL_license2}" ]]; then
382         rm -- "${LFBFL_license_file_path2}.temp"
383     fi
384 done
385
386 prepare_filled_license_file_line() {
387     # $1=LFBFL_license_file_path
388     sed --expression="s/@repository_name@/${LFBFL_repository_name}/g"\
389         --expression="s/@copyright_string@/${LFBFL_copyright_string}/g"\
390         -- "${1.tpl}"\
391         > "${1.temp}"
392     overwrite_if_not_equal "$1" "${1.temp}"
393     declare -ir LFBFL_i_result=$?
394     if [[ LFBFL_i_verbose -eq 1 ]]; then
395         if [[ LFBFL_i_result -eq 1 ]]; then
396             printf "License template %s updated.\n" "$1"

```

```

397         elif [[ LFBFL_i_result -eq 2 ]]; then
398             printf "License template %s created.\n" "$1"
399         fi
400     fi
401 }
402
403 declare -Ar LFBFL_all_line_comment_languages=(
404     ["rlib"]="rs"
405     ["rs"]="rs"
406     ["sh"]="sh"
407     ["sql"]="sql"
408     ["tex"]="tex"
409     ["toml"]="sh"
410     ["yaml"]="sh"
411 )
412
413 for LFBFL_key in "${!LFBFL_all_line_comment_languages[@]}; do
414     LFBFL_dest=${LFBFL_all_line_comment_languages[${LFBFL_key}]}
415     LFBFL_license_file_path="${LFBFL_license_prefix2}.${LFBFL_dest}"
416     prepare_filled_license_file_line "${LFBFL_license_file_path}"
417     if [[ -n "${LFBFL_license2}" ]]; then
418         LFBFL_license_file_path2="${LFBFL_license_prefix3}"
419         LFBFL_license_file_path2+=".${LFBFL_dest}"
420         prepare_filled_license_file_line "${LFBFL_license_file_path2}"
421     fi
422
423     LFBFL_s_files_paths=$(
424         find . -type f -iregex ".*\.$({LFBFL_key})|${LFBFL_key}\.tpl\" \
425             -printf '%P\n' \
426             | relevant_find
427     )
428     if [[ -z "${LFBFL_s_files_paths}" ]]; then
429         if [[ LFBFL_i_verbose -eq 1 ]]; then
430             LFBFL_s_format="build_licenses_templates: "
431             LFBFL_s_format+="No file found with extension .%s or .%s.tpl.\n"
432             # shellcheck disable=SC2059
433             printf "${LFBFL_s_format}" "${LFBFL_key}" "${LFBFL_key}"
434         fi
435         continue
436     fi
437     mapfile -t LFBFL_arr_files_paths <<< "${LFBFL_s_files_paths}"
438     for LFBFL_file_path in "${LFBFL_arr_files_paths[@]}; do
439         LFBFL_i_is_whitelisted=0
440         for LFBFL_file_path2 in\
441             "${LFBFL_arr_files_without_license_header[@]};"
442         do

```

```

443         if [[ "${LFBFL_file_path}" == "${LFBFL_file_path2}" ]]; then
444             LFBFL_i_is_whitelisted=1
445         fi
446     done
447     if [[ LFBFL_i_is_whitelisted -eq 1 ]]; then
448         continue
449     fi
450     is_subfile "${LFBFL_file_path}" "${LFBFL_license_file_path}"
451     LFBFL_i_not_subfile=$?
452     LFBFL_i_not_subfile2=1
453     if [[ -n "${LFBFL_license2}" ]]; then
454         is_subfile "${LFBFL_file_path}" "${LFBFL_license_file_path2}"
455         LFBFL_i_not_subfile2=$?
456     fi
457     if [[ LFBFL_i_not_subfile -ge 1 && LFBFL_i_not_subfile2 -ge 1 ]];
458     then
459         printf "File %s has no/wrong license header?\n"\
460             "${LFBFL_file_path}"
461     fi
462 done
463 done
464 }
465
466 build_licenses_templates "$@"

```

3.17 build_and_checks_dependencies/licenses_templates/license_file_header_AGPLv3+.tpl

```

1  This file is part of @repository_name@.
2
3  @repository_name@ is free software:
4  you can redistribute it and/or modify it
5  under the terms of the GNU Affero General Public License
6  as published by the Free Software Foundation,
7  either version 3 of the License,
8  or (at your option) any later version.
9
10 @repository_name@ is distributed
11 in the hope that it will be useful,
12 but WITHOUT ANY WARRANTY;
13 without even the implied warranty of
14 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
15 See the GNU Affero General Public License for more details.
16
17 You should have received a copy of
18 the GNU Affero General Public License
19 along with @repository_name@.

```


20 If not, see <<https://www.gnu.org/licenses/>>.
21
22 ©Copyright @copyright_string@

3.18 build_and_checks_dependencies/licenses_templates/license_file_header_GPLv3+.tpl

1 This file is part of @repository_name@.
2
3 @repository_name@ is free software:
4 you can redistribute it and/or modify it
5 under the terms of the GNU General Public License
6 as published by the Free Software Foundation,
7 either version 3 of the License,
8 or (at your option) any later version.
9
10 @repository_name@ is distributed
11 in the hope that it will be useful,
12 but WITHOUT ANY WARRANTY;
13 without even the implied warranty of
14 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
15 See the GNU General Public License for more details.
16
17 You should have received a copy of
18 the GNU General Public License
19 along with @repository_name@.
20 If not, see <<https://www.gnu.org/licenses/>>.
21
22 ©Copyright @copyright_string@

3.19 build_and_checks_dependencies/licenses_templates/license_file_header_LGPLv3+.tpl

1 This file is part of @repository_name@.
2
3 @repository_name@ is free software:
4 you can redistribute it and/or modify it
5 under the terms of the GNU Lesser General Public License
6 as published by the Free Software Foundation,
7 either version 3 of the License,
8 or (at your option) any later version.
9
10 @repository_name@ is distributed
11 in the hope that it will be useful,
12 but WITHOUT ANY WARRANTY;
13 without even the implied warranty of
14 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
15 See the GNU Lesser General Public License for more details.

```

16
17 You should have received a copy of
18 the GNU Lesser General Public License
19 along with @repository_name@.
20 If not, see <https://www.gnu.org/licenses/>.
21
22 ©Copyright @copyright_string@

```

3.20 build_and_checks_dependencies/lines_counts.lib.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 ©Copyright 2023–2026 Laurent Frédéric Bernard François Lyaudet
24 # This file was renamed from "lines_counts.sh" to
25 # "lines_counts.lib.sh".
26
27 LFBFL_subdir="build_and_checks_dependencies"
28 # shellcheck source=common_options.lib.sh
29 source "${LFBFL_subdir}/common_options.lib.sh"
30 # shellcheck source=get_common_text_glob_patterns.lib.sh
31 source "${LFBFL_subdir}/get_common_text_glob_patterns.lib.sh"
32 # shellcheck source=lines_filters.lib.sh
33 source "${LFBFL_subdir}/lines_filters.lib.sh"
34
35 all_code_lines() {
36     # Options:

```

```

37 # --verbose
38 # --work-directory=""
39 declare -i LFBFL_i_verbose=0
40 get_verbose_option "$@"
41 local LFBFL_work_directory=""
42 get_work_directory_option "$@"
43 declare -a LFBFL_return_traps_stack
44 init_return_trap
45 pushd_to_work_directory --trap-popd
46 can_continue_after_enhanced_pushd || return 1
47
48 enhanced_set_shell_option pipefail --trap-unset
49
50 get_COMMON_TEXT_FILES_GLOB_PATTERNS
51 local LFBFL_pattern
52 for LFBFL_pattern in "${COMMON_TEXT_FILES_GLOB_PATTERNS[@]}; do
53     if [[ LFBFL_i_verbose -eq 1 ]]; then
54         printf "all_code_lines: Iterating on pattern: %s.\n\"
55             "${LFBFL_pattern}"
56     fi
57     find . -type f -name "${LFBFL_pattern}" -printf '%P\n' \
58         | tr '\n' '\0' \
59         | xargs -0 grep --invert-match --perl-regexp --with-filename \
60             -- 'a(?!a)a'
61 done
62 }
63
64 all_self_code_lines(){
65     # Options:
66     # --verbose
67     # --work-directory=""
68     declare -i LFBFL_i_verbose=0
69     get_verbose_option "$@"
70     local LFBFL_work_directory=""
71     get_work_directory_option "$@"
72     declare -a LFBFL_return_traps_stack
73     init_return_trap
74     pushd_to_work_directory --trap-popd
75     can_continue_after_enhanced_pushd || return 1
76
77     enhanced_set_shell_option pipefail --trap-unset
78
79     declare -a LFBFL_common_options=("$@")
80     keep_options LFBFL_common_options --verbose
81
82     # below and another lines, see SC2145 false positive

```

```

83     all_code_lines "${LFBFL_common_options[@]}" \
84         | relevant_grep\
85         | not_license_grep\
86         | not_main_tex_grep\
87         | not_main_html_grep
88 }
89
90 # shellcheck disable=SC2120
91 all_self_empty_code_lines() {
92     # Options:
93     #   --verbose
94     #   --work-directory=""
95     declare -i LFBFL_i_verbose=0
96     get_verbose_option "$@"
97     local LFBFL_work_directory=""
98     get_work_directory_option "$@"
99     declare -a LFBFL_return_traps_stack
100    init_return_trap
101    pushd_to_work_directory --trap-popd
102    can_continue_after_enhanced_pushd || return 1
103
104    enhanced_set_shell_option pipefail --trap-unset
105
106    declare -a LFBFL_common_options=("${$@}")
107    keep_options LFBFL_common_options --verbose
108
109    all_self_code_lines "${LFBFL_common_options[@]}" \
110        | empty_lines_after_file_name
111 }
112
113 # shellcheck disable=SC2120
114 all_self_not_empty_code_lines() {
115     # Options:
116     #   --verbose
117     #   --work-directory=""
118     declare -i LFBFL_i_verbose=0
119     get_verbose_option "$@"
120     local LFBFL_work_directory=""
121     get_work_directory_option "$@"
122     declare -a LFBFL_return_traps_stack
123     init_return_trap
124     pushd_to_work_directory --trap-popd
125     can_continue_after_enhanced_pushd || return 1
126
127     enhanced_set_shell_option pipefail --trap-unset
128

```

```

129 declare -a LFBFL_common_options=("$@")
130 keep_options LFBFL_common_options --verbose
131
132 all_self_code_lines "${LFBFL_common_options[@]}" \
133 | not_empty_lines_after_file_name
134 }
135
136 code_lines_count_all() {
137 # Options:
138 # --verbose
139 # --work-directory=""
140 declare -i LFBFL_i_verbose=0
141 get_verbose_option "$@"
142 local LFBFL_work_directory=""
143 get_work_directory_option "$@"
144 declare -a LFBFL_return_traps_stack
145 init_return_trap
146 pushd_to_work_directory --trap-popd
147 can_continue_after_enhanced_pushd || return 1
148
149 enhanced_set_shell_option pipefail --trap-unset
150
151 declare -gi i_code_lines_count_all_result
152 i_code_lines_count_all_result=$(
153 all_self_code_lines\
154 | wc --lines
155 )
156 # The printf is for command line use.
157 # A script should use the result value instead.
158 # shellcheck disable=SC2248
159 printf "%s\n" ${i_code_lines_count_all_result}
160 }
161
162 code_lines_count_empty() {
163 # Options:
164 # --verbose
165 # --work-directory=""
166 declare -i LFBFL_i_verbose=0
167 get_verbose_option "$@"
168 local LFBFL_work_directory=""
169 get_work_directory_option "$@"
170 declare -a LFBFL_return_traps_stack
171 init_return_trap
172 pushd_to_work_directory --trap-popd
173 can_continue_after_enhanced_pushd || return 1
174

```

```

175     enhanced_set_shell_option pipefail --trap-unset
176
177     declare -gi i_code_lines_count_empty_result
178     # shellcheck disable=SC2119
179     i_code_lines_count_empty_result=$(
180         all_self_empty_code_lines\
181         | wc --lines
182     )
183     # The printf is for command line use.
184     # A script should use the result value instead.
185     # shellcheck disable=SC2248
186     printf "%s\n" "${i_code_lines_count_empty_result}"
187 }
188
189 code_lines_count_not_empty() {
190     # Options:
191     #   --verbose
192     #   --work-directory=""
193     declare -i LFBFL_i_verbose=0
194     get_verbose_option "$@"
195     local LFBFL_work_directory=""
196     get_work_directory_option "$@"
197     declare -a LFBFL_return_traps_stack
198     init_return_trap
199     pushd_to_work_directory --trap-popd
200     can_continue_after_enhanced_pushd || return 1
201
202     enhanced_set_shell_option pipefail --trap-unset
203
204     declare -gi i_code_lines_count_not_empty_result
205     # shellcheck disable=SC2119
206     i_code_lines_count_not_empty_result=$(
207         all_self_not_empty_code_lines\
208         | wc --lines
209     )
210     # The printf is for command line use.
211     # A script should use the result value instead.
212     # shellcheck disable=SC2248
213     printf "%s\n" "${i_code_lines_count_not_empty_result}"
214 }

```

3.21 build_and_checks_dependencies/lines_filters.lib.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #

```

```

4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
24 # This file was renamed from "lines_filters.sh" to
25 # "lines_filters.lib.sh".
26
27 # The goal of this file is to have some common line filters
28 # for bash processing and pipes.
29 # As is the case for other .sh files in this repository,
30 # it can be copied somewhere in your home directory
31 # and sourced in your .bashrc.
32
33 # shellcheck source=common_options.lib.sh
34 source "./build_and_checks_dependencies/common_options.lib.sh"
35
36 ll_wc() {
37     # current options to wc:
38     # -c --bytes
39     # -m --chars
40     # -l --lines
41     # --files0-from # Incompatible with cat,
42     #                  # another thing intentional by ?
43     #                  # I don't see the meaning of "files0".
44     # -L --max-line-length
45     # -w --words
46     # --help
47     # --version
48     # New option by Laurent Lyaudet (and probably other before):
49     # -n --no-filenames display only number(s)

```

```

50 # I think I did that the first time many years ago (Teliae ?).
51 # Since then, they added it as ignored... (-n)
52 enhanced_set_shell_option pipefail\
53     && trap 'enhanced_unset_shell_option pipefail' RETURN
54 declare -a ll_wc_var_args=()
55 declare -i ll_wc_var_i_number_only=0
56 declare -i ll_wc_var_i=0
57 for ll_wc_var_arg in "$@"; do
58     # printf "%s\n" "${ll_wc_var_arg}"
59     if [[ "${ll_wc_var_arg}" == "-n" ]]; then
60         ll_wc_var_i_number_only=1
61     elif [[ "${ll_wc_var_arg}" == "--no-filenames" ]]; then
62         ll_wc_var_i_number_only=1
63     elif [[ ll_wc_var_i_number_only -eq 0 ]]; then
64         ll_wc_var_args[ll_wc_var_i]="${ll_wc_var_arg}"
65         ll_wc_var_i=$((ll_wc_var_i + 1))
66     elif [[ "${ll_wc_var_arg}" =~ -.* ]]; then
67         ll_wc_var_args[ll_wc_var_i]="${ll_wc_var_arg}"
68         ll_wc_var_i=$((ll_wc_var_i + 1))
69     fi
70 done
71 # typeset -p ll_wc_var_args
72 # printf "%s\n" "${ll_wc_var_i_number_only}"
73 if [[ ll_wc_var_i_number_only -gt 0 ]]; then
74     # Too simple code, only the base use case is handled now.
75     # Convenient but incomplete.
76     # With more time,
77     # the simpler would be to submit a patch to GNU coreutils,
78     # unless blockade from assholes.
79     # Otherwise, it may be more simply handled in PHP or Python
80     # (argparse, etc.).
81     # You'll need to start by improving cat first,
82     # with --files0-from handling.
83     # wc does not display file_name when stream...
84     # hence cat of last arg "${!#}"
85     cat -- "${!#}"\
86         | wc "${ll_wc_var_args[@]}"
87 else
88     # printf "normal\n"
89     wc "${ll_wc_var_args[@]}"
90 fi
91 }
92
93 # I submitted a patch for wc :).
94 # printf "https://domain/list-path/2024-05/msg00013.html" | \
95 #     sed --expression='s|domain|lists.gnu.org|' \

```



```

96 # --expression='s|list-path|archive/html/bug-coreutils|'
97 # I found another way to have a long URL fit on 70 characters.
98 # If it is merged, the following would be better:
99 # If --no-filenames option available,
100 # we redefine ll_wc command as an alias.
101 wc_help_text=$(wc --help)
102 if [[ "${wc_help_text}" == *" --no-filenames "*" ]]; then
103     alias ll_wc='wc'
104 fi
105
106 # Trace avant le (2e ?) renommage
107 # de wget_sha512.sh à wget_sha512.lib.sh.
108 # $ ll_wc wget_sha512.sh
109 # 41 189 1224 wget_sha512.sh
110 # $ ll_wc -n wget_sha512.sh
111 # 41 189 1224
112 # $ ll_wc -l wget_sha512.sh
113 # 41 wget_sha512.sh
114 # $ ll_wc -l -n wget_sha512.sh
115 # 41
116
117 in_place_grep() {
118     # Same arguments and options as grep.
119     declare -r LFBFL_temp="${!#}.in_place_grep.temp"
120     grep "$@" \
121         > "${LFBFL_temp}"
122     # declare -ir LFBFL_i_lines_before=$(ll_wc -l -n "${!#}")
123     # declare -ir LFBFL_i_lines_after=$(ll_wc -l -n "${LFBFL_temp}")
124     # printf "%s\n" "${LFBFL_i_lines_before}"
125     # printf "%s\n" "${LFBFL_i_lines_after}"
126     # if [[ LFBFL_i_lines_before -eq LFBFL_i_lines_after ]]; then
127     # Almost as fast (on large files) and correct in all cases :).
128     # Thanks Paul Eggert for the suggestion :).
129     # https://debbugs.gnu.org/cgi/bugreport.cgi?bug=80547
130     if cmp --silent -- "${LFBFL_temp}" "${!#}"; then
131         rm -- "${LFBFL_temp}"
132         return
133     fi
134     mv -- "${LFBFL_temp}" "${!#}"
135 }
136
137 grep_fixed_string_with_anchor() {
138     # $1=file_path
139     # $2=some_fixed_string
140     # Options:
141     # --enforce-line-starts-with-fixed-string

```

```

142 # --enforce-line-ends-with-fixed-string
143 # Apart from $1 and $2 and the options above,
144 # all other arguments are considered grep_options like --quiet
145 # for example.
146 # But note that --fixed-strings will be added below,
147 # you don't need to supply it.
148 declare -a LFBFL_grep_options=()
149 declare -a LFBFL_grep_options2=()
150 declare -i LFBFL_i=0
151 declare -i LFBFL_i_enforce_line_starts=0
152 declare -i LFBFL_i_enforce_line_ends=0
153 declare -i LFBFL_i_quiet=0
154 local LFBFL_argument
155 for LFBFL_argument in "$@"; do
156     ((++LFBFL_i))
157     if [[ LFBFL_i -lt 3 ]]; then
158         continue
159     fi
160     if [[
161         "${LFBFL_argument}" == "--enforce-line-starts-with-fixed-string"
162     ]]; then
163         LFBFL_i_enforce_line_starts=1
164         continue
165     fi
166     if [[
167         "${LFBFL_argument}" == "--enforce-line-ends-with-fixed-string"
168     ]]; then
169         LFBFL_i_enforce_line_ends=1
170         continue
171     fi
172     LFBFL_grep_options+=("${LFBFL_argument}")
173     if [[
174         "${LFBFL_argument}" == "-q"
175         || "${LFBFL_argument}" == "--quiet"
176     ]]; then
177         LFBFL_i_quiet=1
178         continue
179     fi
180     LFBFL_grep_options2+=("${LFBFL_argument}")
181 done
182
183 if [[
184     LFBFL_i_enforce_line_starts -eq 0
185     && LFBFL_i_enforce_line_ends -eq 0
186 ]]; then
187     grep "${LFBFL_grep_options[@]}" --fixed-strings -- "$2" "$1"

```

```

188     return
189 fi
190 declare -r LFBFL_s_lines=$(
191     grep "${LFBFL_grep_options2[@]}" --color=never --fixed-strings --\
192         "$2" "$1"
193 )
194 declare -i LFBFL_i_result=1
195 if [[ -z "${LFBFL_s_lines}" ]]; then
196     # shellcheck disable=SC2248
197     return ${LFBFL_i_result}
198 fi
199 declare -a LFBFL_arr_lines
200 mapfile -t LFBFL_arr_lines <<< "${LFBFL_s_lines}"
201 readonly LFBFL_arr_lines
202
203 declare -i LFBFL_i_fixed_string_length=${#2}
204 local LFBFL_some_line
205 local LFBFL_line_part
206 for LFBFL_some_line in "${LFBFL_arr_lines[@]"}; do
207     if [[ "${LFBFL_some_line}" == "$2" ]]; then
208         LFBFL_i_result=0
209         if [[ LFBFL_i_quiet -eq 1 ]]; then
210             break
211         fi
212         printf "%s\n" "${LFBFL_some_line}"
213         continue
214     fi
215     if [[
216         LFBFL_i_enforce_line_starts -eq 1
217         && LFBFL_i_enforce_line_ends -eq 1
218     ]]; then
219         continue
220     fi
221     if [[ LFBFL_i_enforce_line_starts -eq 1 ]]; then
222         LFBFL_line_part=${LFBFL_some_line:0:${LFBFL_i_fixed_string_length}}
223     fi
224     if [[ LFBFL_i_enforce_line_ends -eq 1 ]]; then
225         LFBFL_line_part=${LFBFL_some_line: -${LFBFL_i_fixed_string_length}}
226     fi
227     if [[ "${LFBFL_line_part}" == "$2" ]]; then
228         LFBFL_i_result=0
229         if [[ LFBFL_i_quiet -eq 1 ]]; then
230             break
231         fi
232         printf "%s\n" "${LFBFL_some_line}"
233     fi

```

```

234     done
235     # shellcheck disable=SC2248
236     return ${LFBFL_i_result}
237 }
238
239 grep_variable() {
240     # $1=file_path
241     # $2=variable_name
242     # Options :
243     #   --replace-line-returns-by=""
244     #   --result-variable-prefix="LFBFL_" for example
245     declare -r LFBFL_regexp="(?!<^$2=).*$"
246     # printf "%s\n" "${LFBFL_regexp}"
247     local LFBFL_variable_value
248     local LFBFL_s_replace
249     get_some_option LFBFL_s_replace --replace-line-returns-by ' ' $'\n' 1 "$@"
250     if [[ "${LFBFL_s_replace}" != $'\n' ]]; then
251         # sed -Ez -e...
252         LFBFL_variable_value=$(
253             grep --only-matching --perl-regexp -- "${LFBFL_regexp}" "$1" \
254             | sed --null-data --regexp-extended \
255                 --expression='s/\n/' "${LFBFL_s_replace}" /Mg'
256         )
257         # We remove the trailing replace string,
258         # since the intent is only to replace the intermediate \n.
259         if [[ -n "${LFBFL_s_replace}" ]]; then
260             LFBFL_variable_value=${LFBFL_variable_value%"${LFBFL_s_replace}"}
261         fi
262     else
263         LFBFL_variable_value=$(
264             grep --only-matching --perl-regexp -- "${LFBFL_regexp}" "$1"
265         )
266     fi
267     local LFBFL_prefix=""
268     get_some_option LFBFL_prefix --result-variable-prefix ' ' ' ' 1 "$@"
269     declare -r LFBFL_variable_name="${LFBFL_prefix}$2"
270     # printf "%s : %s\n" "${LFBFL_variable_name}" "${LFBFL_variable_value}"
271     # The declare line may be dropped by a local or declare
272     # in outer scope.
273     # declare -g "${LFBFL_variable_name}"
274     # So the assignment must be done on another line.
275     printf -v "${LFBFL_variable_name}" "%s" "${LFBFL_variable_value}"
276     # printf "%s\n" "${!LFBFL_variable_name}"
277 }
278
279 empty_lines() {

```

```

280     grep '^$'
281 }
282
283 not_empty_lines() {
284     grep --invert-match '^$'
285 }
286
287 space_starting_lines() {
288     grep '^ '
289 }
290
291 not_space_starting_lines() {
292     grep --invert-match '^ '
293 }
294
295 # Space starting or empty lines = spampty
296 spampty_lines() {
297     grep --extended-regexp '^ (|$)'
298 }
299
300 not_spampty_lines() {
301     grep '^ [^ ]'
302     # grep --extended-regexp --invert-match '^ (|$)'
303 }
304
305 all_space_lines() {
306     grep '^ [ ]+$'
307 }
308
309 not_all_space_lines() {
310     grep --invert-match '^ [ ]+$'
311 }
312
313 # All space or empty lines = asspampty
314 asspampty_lines() {
315     grep '^ [ ]*$'
316 }
317
318 not_asspampty_lines() {
319     grep '[^ ]'
320     # grep --invert-match '^ [ ]*$'
321 }
322
323 empty_lines_after_file_name() {
324     grep '^ [^:]\+:$'
325 }

```

```

326
327 not_empty_lines_after_file_name() {
328     grep --invert-match '^[^:]\+:$'
329 }
330
331 space_starting_lines_after_file_name() {
332     grep '^[^:]\+:'
333 }
334
335 not_space_starting_lines_after_file_name() {
336     grep --invert-match '^[^:]\+:'
337 }
338
339 spampty_lines_after_file_name() {
340     grep --extended-regexp '^[^:]\+:( |$)'
341 }
342
343 not_spampty_lines_after_file_name() {
344     # The two variants results differ on lines without filename before.
345     # Since the intent of the function is only on lines "blabla.sh:whatever",
346     # use the fastest one. I didn't do extensive testing and just assumed
347     # that the "positive" one is faster as usual when querying database.
348     # But there is no index here ;) XD.
349     grep '^[^:]\+:[^ ]'
350     # grep --extended-regexp --invert-match '^[^:]\+:( |$)'
351 }
352
353 all_space_lines_after_file_name() {
354     grep '^[^:]\+:[ ]\+$'
355 }
356
357 not_all_space_lines_after_file_name() {
358     grep --invert-match '^[^:]\+:[ ]\+$'
359 }
360
361 aspampty_lines_after_file_name() {
362     grep '^[^:]\+:[ ]*$'
363 }
364
365 not_aspampty_lines_after_file_name() {
366     grep --invert-match '^[^:]\+:[ ]*$'
367 }
368
369 # If you need to test the previous 20 functions,
370 # look at file spampty_data.txt in miscellaneous.
371 # And give a try at something like:

```

```

372 # cat -E <(cat miscellaneous/spamty_data.txt | empty_lines)
373 # -E = --show-ends :). Nice command :).
374
375 not_JS_dependencies_find() {
376     grep --extended-regexp --invert-match\
377         --regexp="(^|/)node_modules/"\
378         --regexp="(^|/)package-lock\.json$"
379 }
380
381 not_JS_dependencies_grep() {
382     grep --extended-regexp --invert-match\
383         --regexp="^([^:]+)/?node_modules/"\
384         --regexp="^([^:]+)/?package-lock\.json:"
385 }
386
387 not_dependencies_find() {
388     not_JS_dependencies_find
389 }
390
391 not_dependencies_grep() {
392     not_JS_dependencies_grep
393 }
394
395 not_php_cache_find() {
396     grep --extended-regexp --invert-match\
397         --regexp="(^|/)\.phpdoc/cache/"
398 }
399
400 not_php_cache_grep() {
401     grep --extended-regexp --invert-match\
402         --regexp="^([^:]+)/?\.phpdoc/cache/"
403 }
404
405 not_python_cache_find() {
406     grep --extended-regexp --invert-match\
407         --regexp="(^|/).__pycache__/"\
408         --regexp="(^|/)\.mypy_cache/"\
409         --regexp="(^|/)\.ruff_cache/"
410 }
411
412 not_python_cache_grep() {
413     grep --extended-regexp --invert-match\
414         --regexp="^([^:]+)/?__pycache__/"\
415         --regexp="^([^:]+)/?\.mypy_cache/"\
416         --regexp="^([^:]+)/?\.ruff_cache/"
417 }

```

```

418
419 not_cache_find() {
420     not_php_cache_find\
421     | not_python_cache_find
422 }
423
424 not_cache_grep() {
425     not_php_cache_grep\
426     | not_python_cache_grep
427 }
428
429 not_git_find() {
430     grep --extended-regexp --invert-match "(^|/)\.git/"
431 }
432
433 not_git_grep() {
434     grep --extended-regexp --invert-match "^([:]+/)?\.git/"
435 }
436
437 not_archive_find() {
438     grep --extended-regexp --invert-match "(\.gz|\.rar|\.tar|\.tgz|\.whl)$"
439 }
440
441 not_archive_grep() {
442     grep --extended-regexp --invert-match\
443     --regexp="^([:]* (\.gz|\.rar|\.tar|\.tgz|\.whl)):"
444 }
445
446 not_license_find() {
447     grep --extended-regexp --invert-match\
448     --regexp="( ^|/ ) COPYING$" \
449     --regexp="( ^|/ ) COPYING\ .LESSER$"
450 }
451
452 not_license_grep() {
453     grep --extended-regexp --invert-match\
454     --regexp="^( [^:] +/ ) ?COPYING:" \
455     --regexp="^( [^:] +/ ) ?COPYING\ .LESSER:"
456 }
457
458 not_main_tex_find() {
459     local LFBFL_repository_name=""
460     grep_variable build_and_checks_variables/repository_data.txt\
461     repository_name\
462     --result-variable-prefix="LFBFL_" \
463     --replace-line-returns-by=""

```



```

464     grep --extended-regexp --invert-match\
465         --regexp="(^|/){LFBFL_repository_name}\.tex$"
466 }
467
468 not_main_tex_grep() {
469     local LFBFL_repository_name=""
470     grep_variable build_and_checks_variables/repository_data.txt\
471         repository_name\
472         --result-variable-prefix="LFBFL_"\
473         --replace-line-returns-by=""
474     grep --extended-regexp --invert-match\
475         --regexp="^( [^:]+/ )?${LFBFL_repository_name}\.tex:"
476 }
477
478 not_main_html_find() {
479     local LFBFL_repository_name=""
480     grep_variable build_and_checks_variables/repository_data.txt\
481         repository_name\
482         --result-variable-prefix="LFBFL_"\
483         --replace-line-returns-by=""
484     grep --extended-regexp --invert-match\
485         --regexp="(^|/){LFBFL_repository_name}\.html$"
486 }
487
488 not_main_html_grep() {
489     local LFBFL_repository_name=""
490     grep_variable build_and_checks_variables/repository_data.txt\
491         repository_name\
492         --result-variable-prefix="LFBFL_"\
493         --replace-line-returns-by=""
494     grep --extended-regexp --invert-match\
495         --regexp="^( [^:]+/ )?${LFBFL_repository_name}\.html:"
496 }
497
498 not_temp_file_find() {
499     grep --extended-regexp --invert-match\
500         --regexp="(^|/)build_and_checks_variables/temp/"
501 }
502
503 not_temp_file_grep() {
504     grep --extended-regexp --invert-match\
505         --regexp="^( [^:]+/ )?build_and_checks_variables/temp/[^:]*:"
506 }
507
508 not_unchecked_builds_find() {
509     grep --extended-regexp --invert-match\

```

```

510     --regexp="(^|/)\.phpdoc/build/"
511 }
512
513 not_unchecked_builds_grep() {
514     grep --extended-regexp --invert-match\
515         --regexp="^([^\:]+/)?\.phpdoc/build/"
516 }
517
518 relevant_find() {
519     enhanced_set_shell_option pipefail\
520     && trap 'enhanced_unset_shell_option pipefail' RETURN
521     not_dependencies_find\
522     | not_cache_find\
523     | not_git_find\
524     | not_archive_find\
525     | not_temp_file_find\
526     | not_unchecked_builds_find
527 }
528
529 relevant_grep() {
530     enhanced_set_shell_option pipefail\
531     && trap 'enhanced_unset_shell_option pipefail' RETURN
532     not_dependencies_grep\
533     | not_cache_grep\
534     | not_git_grep\
535     | not_archive_grep\
536     | not_temp_file_grep\
537     | not_unchecked_builds_grep
538 }

```

3.22 build_and_checks_dependencies/lines_maps.lib.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of

```

```

15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
24 # This file was renamed from "lines_maps.sh" to "lines_maps.lib.sh".
25
26 # https://en.wikibooks.org/wiki/Unicode/Character\_reference/2000-2FFF
27 # Some invisible unicode characters that are a problem:
28 # 2000-200F 2028-202F 205F 2060-206F
29 # [
30 #   '2000', '2001', '2002', '2003', '2004', '2005', '2006', '2007',
31 #   '2008', '2009', '200A', '200B', '200C', '200D', '200E', '200F',
32 #   '2028', '2029', '202A', '202B', '202C', '202D', '202E', '202F',
33 #   '205F',
34 #   '2060', '2061', '2062', '2063', '2064', '2065', '2066', '2067',
35 #   '2068', '2069', '206A', '206B', '206C', '206D', '206E', '206F',
36 # ]
37 replace_non_ascii_spaces() {
38     sed\
39         --expression='s/\xc2\xa0/ /g'\
40         --expression='s/\xe2\x80\x80/ /g'\
41         --expression='s/\xe2\x80\x81/ /g'\
42         --expression='s/\xe2\x80\x82/ /g'\
43         --expression='s/\xe2\x80\x83/ /g'\
44         --expression='s/\xe2\x80\x84/ /g'\
45         --expression='s/\xe2\x80\x85/ /g'\
46         --expression='s/\xe2\x80\x86/ /g'\
47         --expression='s/\xe2\x80\x87/ /g'\
48         --expression='s/\xe2\x80\x88/ /g'\
49         --expression='s/\xe2\x80\x89/ /g'\
50         --expression='s/\xe2\x80\x8a/ /g'\
51         --expression='s/\xe2\x80\x8b/ /g'\
52         --expression='s/\xe2\x80\x8c/ /g'\
53         --expression='s/\xe2\x80\x8d/ /g'\
54         --expression='s/\xe2\x80\x8e/ /g'\
55         --expression='s/\xe2\x80\x8f/ /g'\
56         --expression='s/\xe2\x80\xa8/ /g'\
57         --expression='s/\xe2\x80\xa9/ /g'\
58         --expression='s/\xe2\x80\xaa/ /g'\
59         --expression='s/\xe2\x80\xab/ /g'\
60         --expression='s/\xe2\x80\xac/ /g'\

```

```

61     --expression=' s/\xe2\x80\xad/ /g' \
62     --expression=' s/\xe2\x80\xae/ /g' \
63     --expression=' s/\xe2\x80\xaf/ /g' \
64     --expression=' s/\xe2\x81\x9f/ /g' \
65     --expression=' s/\xe2\x81\xa0/ /g' \
66     --expression=' s/\xe2\x81\xa1/ /g' \
67     --expression=' s/\xe2\x81\xa2/ /g' \
68     --expression=' s/\xe2\x81\xa3/ /g' \
69     --expression=' s/\xe2\x81\xa4/ /g' \
70     --expression=' s/\xe2\x81\xa5/ /g' \
71     --expression=' s/\xe2\x81\xa6/ /g' \
72     --expression=' s/\xe2\x81\xa7/ /g' \
73     --expression=' s/\xe2\x81\xa8/ /g' \
74     --expression=' s/\xe2\x81\xa9/ /g' \
75     --expression=' s/\xe2\x81\xaa/ /g' \
76     --expression=' s/\xe2\x81\xab/ /g' \
77     --expression=' s/\xe2\x81\xac/ /g' \
78     --expression=' s/\xe2\x81\xad/ /g' \
79     --expression=' s/\xe2\x81\xae/ /g' \
80     --expression=' s/\xe2\x81\xaf/ /g' \
81 }

```

3.23 build_and_checks_dependencies/overwrite_if_not_equal.lib.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #

```

```

23 # ©Copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
24 # This file was renamed from "overwrite_if_not_equal.sh"
25 # to "overwrite_if_not_equal.lib.sh".
26
27 LFBFL_subdir="build_and_checks_dependencies"
28 # shellcheck source=common_options.lib.sh
29 source "${LFBFL_subdir}/common_options.lib.sh"
30
31 overwrite_if_not_equal() {
32     # $1=target_file_path
33     # $2=temp_file_path
34     # Options:
35     #   --keep-temp : keep the temporary file
36     #   --quiet : we even don't want the message of diff saying that
37     #               files are distinct
38     #   --tree-mode : when the two files are the output of tree command,
39     #               we ignore if all the differences are only on directories timestamps.
40     # Return 0 target was the same
41     #       1 target was different
42     #       2 target did not already exist
43     declare -i LFBFL_i_keep_temp
44     get_some_flag LFBFL_i_keep_temp --keep-temp 1 "$@"
45     declare -i LFBFL_i_quiet
46     get_some_flag LFBFL_i_quiet --quiet 1 "$@"
47     declare -i LFBFL_i_tree_mode
48     get_some_flag LFBFL_i_tree_mode --tree-mode 1 "$@"
49
50     if [[ ! -f "$1" ]]; then
51         if [[ LFBFL_i_keep_temp -eq 1 ]]; then
52             cp --preserve=mode,ownership,timestamps -- "$2" "$1"
53         else
54             mv -- "$2" "$1"
55         fi
56         return 2
57     fi
58     declare -i LFBFL_i_is_equal
59     if [[ LFBFL_i_tree_mode -eq 1 ]]; then
60         # Not setting pipefail since the result would still be incorrect.
61         # shellcheck disable=SC2312
62         diff -- "$1" "$2" \
63             | grep --extended-regexp "^(>|<)" \
64             | grep --invert-match "/"
65         LFBFL_i_is_equal=${PIPESTATUS[2]}
66         if [[ LFBFL_i_is_equal -eq 1 ]]; then
67             grep --only-matching --regexp="^[^ ]*/$" -- "$1" \
68                 > "overwrite_if_not_equal.file1.temp"

```

```

69     grep --only-matching --regexp="^[^ ]*/$" -- "$2"\
70     > "overwrite_if_not_equal.file2.temp"
71     if [[ LFBFL_i_quiet -eq 1 ]]; then
72         diff overwrite_if_not_equal.file1.temp\
73             overwrite_if_not_equal.file2.temp\
74             > /dev/null
75     else
76         diff overwrite_if_not_equal.file1.temp\
77             overwrite_if_not_equal.file2.temp
78     fi
79     LFBFL_i_is_equal=1- $?
80     rm overwrite_if_not_equal.file1.temp\
81         overwrite_if_not_equal.file2.temp
82 fi
83 else
84     if [[ LFBFL_i_quiet -eq 1 ]]; then
85         diff --brief -- "$1" "$2" > /dev/null
86     else
87         diff --brief -- "$1" "$2"
88     fi
89     LFBFL_i_is_equal=1- $?
90 fi
91 if [[ LFBFL_i_is_equal -eq 1 ]]; then
92     if [[ LFBFL_i_keep_temp -eq 0 ]]; then
93         rm -- "$2"
94     fi
95     return 0
96 fi
97 if [[ LFBFL_i_keep_temp -eq 1 ]]; then
98     cp --preserve=mode,ownership,timestamps -- "$2" "$1"
99 else
100     mv -- "$2" "$1"
101 fi
102 return 1
103 }

```

3.24 build_and_checks_dependencies/python_black_complement.lib.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,

```

```

9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
24 # This file was renamed from "python_black_complement.sh"
25 # to "python_black_complement.lib.sh".
26
27 # shellcheck source=common_options.lib.sh
28 source "./build_and_checks_dependencies/common_options.lib.sh"
29
30 # It was rejected to enhance black with this currently.
31 # https://github.com/psf/black/issues/2370
32 # And moreover, at some point, I saw the reverse rule
33 # in black or pylint to add an empty line...
34 # This regexp may give false positives,
35 # but that's not the end of the world.
36 check_no_empty_line_after_python_function_docstring() {
37     # Options:
38     #   --verbose
39     #   --work-directory=""
40     declare -i LFBFL_i_verbose=0
41     get_verbose_option "$@"
42     local LFBFL_work_directory=""
43     get_work_directory_option "$@"
44     declare -a LFBFL_return_traps_stack
45     init_return_trap
46     pushd_to_work_directory --trap-popd
47     can_continue_after_enhanced_pushd || return 1
48
49     enhanced_set_bash_option globstar --trap-unset
50
51     [[ LFBFL_i_verbose -eq 1 ]]\
52     && printf "Checking empty lines after Python function docstrings\n"
53     pcre2grep --multiline --\
54     '$^def ([^"]|"(?!")))*""([^\]|"(?!")))*""\n\n(?:\s*def)'\

```

```

55     **/*.py
56 }
57
58 python_black_complement() {
59     # Options:
60     #     --verbose
61     #     --work-directory=""
62     declare -i LFBFL_i_verbose=0
63     get_verbose_option "$@"
64     local LFBFL_work_directory=""
65     get_work_directory_option "$@"
66     declare -a LFBFL_return_traps_stack
67     init_return_trap
68     pushd_to_work_directory --trap-popd
69     can_continue_after_enhanced_pushd || return 1
70
71     declare -a LFBFL_common_options=("$@")
72     keep_options LFBFL_common_options --verbose
73
74     check_no_empty_line_after_python_function_docstring\
75         "${LFBFL_common_options[@]}"
76 }

```

3.25 build_and_checks_dependencies/python_isort_complement.lib.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.

```



```

22 #
23 # Copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
24 # This file was renamed from "python_isort_complement.sh"
25 # to "python_isort_complement.lib.sh".
26
27 LFBFL_subdir="build_and_checks_dependencies"
28 # shellcheck source=common_options.lib.sh
29 source "${LFBFL_subdir}/common_options.lib.sh"
30 # shellcheck source=lines_filters.lib.sh
31 source "${LFBFL_subdir}/lines_filters.lib.sh"
32 # shellcheck source=overwrite_if_not_equal.lib.sh
33 source "${LFBFL_subdir}/overwrite_if_not_equal.lib.sh"
34
35 check_collections_abc_place() {
36     # Options:
37     #   --verbose
38     #   --work-directory=""
39     # This function should be useless in a few months:
40     # https://github.com/PyCQA/isort/issues/2250
41     declare -i LFBFL_i_verbose=0
42     get_verbose_option "$@"
43     local LFBFL_work_directory=""
44     get_work_directory_option "$@"
45     declare -a LFBFL_return_traps_stack
46     init_return_trap
47     pushd_to_work_directory --trap-popd
48     can_continue_after_enhanced_pushd || return 1
49
50     [[ LFBFL_i_verbose -eq 1 ]]\
51     && printf\
52         "Checking that import of _collections_abc is at the right place.\n"
53
54     enhanced_set_shell_option pipefail --trap-unset
55
56     declare -r LFBFL_temp=".check_collections_abc_place.temp"
57     local LFBFL_file_path
58     declare -r LFBFL_s_files_paths=$(
59         find . -type f -name "*.py" -printf '%P\n'\
60         | relevant_find
61     )
62     if [[ -z "${LFBFL_s_files_paths}" ]]; then
63         [[ LFBFL_i_verbose -eq 1 ]]\
64         && printf "check_collections_abc_place: No file found.\n"
65         return
66     fi
67     declare -a LFBFL_arr_files_paths

```

```

68 mapfile -t LFBFL_arr_files_paths <<< "${LFBFL_s_files_paths}"
69 readonly LFBFL_arr_files_paths
70 for LFBFL_file_path in "${LFBFL_arr_files_paths[@]}; do
71     sed --regextype-extended --null-data\
72         --expression='s/\n(\nfrom _collections_abc[^\n]*)/\1\n/Mg'\
73         -- "${LFBFL_file_path}"\
74         > "${LFBFL_file_path}${LFBFL_temp}"
75     overwrite_if_not_equal "${LFBFL_file_path}"\
76         "${LFBFL_file_path}${LFBFL_temp}"
77 done
78 }
79
80 python_isort_complement() {
81     # Options:
82     #     --verbose
83     #     --work-directory=""
84     declare -i LFBFL_i_verbose=0
85     get_verbose_option "$@"
86     local LFBFL_work_directory=""
87     get_work_directory_option "$@"
88     declare -a LFBFL_return_traps_stack
89     init_return_trap
90     pushd_to_work_directory --trap-popd
91     can_continue_after_enhanced_pushd || return 1
92
93     declare -a LFBFL_common_options=("$@")
94     keep_options LFBFL_common_options --verbose
95
96     check_collections_abc_place "${LFBFL_common_options[@]}"
97 }

```

3.26 build_and_checks_dependencies/repository_data.lib.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;

```

```

14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
24
25 LFBFL_subdir="build_and_checks_dependencies"
26 # shellcheck source=common_options.lib.sh
27 source "${LFBFL_subdir}/common_options.lib.sh"
28 # shellcheck source=lines_filters.lib.sh
29 source "${LFBFL_subdir}/lines_filters.lib.sh"
30
31 # /\ You need to activate extglob before parsing this file. /\
32 # And I'm kind enough to activate it inside functions that need it below.
33
34 get_upgrade_venvs_time_interval_in_seconds() {
35     # $1=data_file_path
36     # Options:
37     #     --verbose
38     declare -i LFBFL_i_verbose=0
39     get_verbose_option "$@"
40     declare -a LFBFL_return_traps_stack
41     init_return_trap
42
43     enhanced_set_bash_option extglob --trap-unset
44
45     grep_variable "$1" \
46         upgrade_venvs_time_interval_in_seconds \
47         --result-variable-prefix="LFBFL_"
48
49     [[ LFBFL_i_verbose -eq 1 ]] \
50         && printf "You say \"%s\".\n" \
51             "${LFBFL_upgrade_venvs_time_interval_in_seconds}"
52
53     case ${LFBFL_upgrade_venvs_time_interval_in_seconds} in
54         +([0-9])) : ;;
55         wat) LFBFL_upgrade_venvs_time_interval_in_seconds=${RANDOM};;
56         watyouwant\?) LFBFL_upgrade_venvs_time_interval_in_seconds=${SRANDOM};;
57         *) printf "No wat for you?\n";; #TempsDeCerveauDisponible XD SC2249 ;)
58     esac
59

```

```

60     [[ LFBFL_i_verbos -eq 1 ]]\
61     && printf "I say \"%s\".\n\"
62         "${LFBFL_upgrade_venvs_time_interval_in_seconds}"
63 }
64
65 grep_variable_with_multiple_files(){
66     # $1=data_file_path
67     # $2=variable_name
68     # Options :
69     # --result-variable-prefix="LFBFL_" for example
70     local LFBFL_prefix=""
71     get_some_option LFBFL_prefix --result-variable-prefix ' ' ' ' 1 "$@"
72     grep_variable "$1" "$2" --result-variable-prefix="${LFBFL_prefix}"
73     declare -r LFBFL_variable_name="${LFBFL_prefix}$2"
74     declare -a LFBFL_arr
75     if [[ -z "${!LFBFL_variable_name}" ]]; then
76         return
77     fi
78     mapfile -t LFBFL_arr <<< "${!LFBFL_variable_name}"
79     local LFBFL_s=""
80     local LFBFL_file_path
81     local LFBFL_previous_file_path
82     for LFBFL_file_path in "${LFBFL_arr[@]}"; do
83         if [[
84             -n "${LFBFL_previous_file_path}"
85             && "${LFBFL_previous_file_path}" != */
86         ]]; then
87             LFBFL_s+=$'\n'
88         fi
89         LFBFL_s+="${LFBFL_file_path}"
90         LFBFL_previous_file_path="${LFBFL_file_path}"
91     done
92     printf -v "${LFBFL_variable_name}" "%s" "${LFBFL_s}"
93 }

```

3.27 build_and_checks_dependencies/shell_checks_complement.lib.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.

```

```

10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
24 # This file was renamed from "python_black_complement.sh"
25 # to "python_black_complement.lib.sh".
26
27 # shellcheck source=common_options.lib.sh
28 source "../build_and_checks_dependencies/common_options.lib.sh"
29
30 check_no_size_of_array_first_element() {
31     # Options:
32     #   --verbose
33     #   --work-directory=""
34     declare -i LFBFL_i_verbose=0
35     get_verbose_option "$@"
36     local LFBFL_work_directory=""
37     get_work_directory_option "$@"
38     declare -a LFBFL_return_traps_stack
39     init_return_trap
40     pushd_to_work_directory --trap-popd
41     can_continue_after_enhanced_pushd || return 1
42
43     enhanced_set_bash_option globstar --trap-unset
44
45     local LFBFL_s="Checking that shell scripts do not"
46     LFBFL_s+=" contain wrong array size expansion.\n"
47     # shellcheck disable=SC2059
48     [[ LFBFL_i_verbose -eq 1 ]] && printf "${LFBFL_s}"
49
50     pcre2grep --multiline -- '$\\$\\#{#(|.*_)arr_(?!.*\\[@\\])}' **/*.sh
51 }
52
53 check_no_misplaced_then() {
54     # Options:
55     #   --verbose

```

```

56 # --work-directory=""
57 # --max-line-length
58 declare -i LFBFL_i_verbose=0
59 get_verbose_option "$@"
60 local LFBFL_work_directory=""
61 get_work_directory_option "$@"
62 declare -a LFBFL_return_traps_stack
63 init_return_trap
64 pushd_to_work_directory --trap-popd
65 can_continue_after_enhanced_pushd || return 1
66
67 declare -i LFBFL_i_max_line_length
68 get_max_line_length_option "$@"
69 declare -i LFBFL_i_max_previous_line_length
70 LFBFL_i_max_previous_line_length=$((LFBFL_i_max_line_length - 5))
71
72 enhanced_set_bash_option globstar --trap-unset
73
74 [[ LFBFL_i_verbose -eq 1 ]]\
75     && printf\
76         "Checking that shell scripts do not contain misplaced 'then'.\n"
77
78 local LFBFL_regexp
79 LFBFL_regexp="^[^\n]{1,${LFBFL_i_max_previous_line_length}}"
80 LFBFL_regexp+="(?!<=\\|\\);[^\n]{0,${LFBFL_i_max_previous_line_length}})"
81 LFBFL_regexp+="(?!<!\s{0,${LFBFL_i_max_previous_line_length}}\\|\\);)"
82 LFBFL_regexp+="\n\s*then"
83 # pcre2grep --multiline --
84 # '^[^\n]{1,70}(?!<=\\|\\);[^\n]{0,70})'
85 # '(?!<!\s{0,70}\\|\\);)\n\s*then'
86 pcre2grep --multiline -- "${LFBFL_regexp}" **/*.sh
87 }
88
89 check_no_negation_before_bash_test() {
90     # Options:
91     # --verbose
92     # --work-directory=""
93     declare -i LFBFL_i_verbose=0
94     get_verbose_option "$@"
95     local LFBFL_work_directory=""
96     get_work_directory_option "$@"
97     declare -a LFBFL_return_traps_stack
98     init_return_trap
99     pushd_to_work_directory --trap-popd
100     can_continue_after_enhanced_pushd || return 1
101

```

```

102     enhanced_set_bash_option globstar --trap-unset
103
104     [[ LFBFL_i_verbose -eq 1 ]]\
105     && printf "Checking that shell scripts do not contain ! before [!.\\n"
106
107     pcre2grep --multiline -- '$!\\s*\\[\\[\\[' '**/*.sh
108 }
109
110 shell_checks_complement() {
111     # Options:
112     #   --verbose
113     #   --work-directory=""
114     declare -i LFBFL_i_verbose=0
115     get_verbose_option "$@"
116     local LFBFL_work_directory=""
117     get_work_directory_option "$@"
118     declare -a LFBFL_return_traps_stack
119     init_return_trap
120     pushd_to_work_directory --trap-popd
121     can_continue_after_enhanced_pushd || return 1
122
123     declare -a LFBFL_common_options=("$@")
124     keep_options LFBFL_common_options --verbose --max-line-length
125
126     check_no_size_of_array_first_element "${LFBFL_common_options[@]}"
127     check_no_misplaced_then "${LFBFL_common_options[@]}"
128     check_no_negation_before_bash_test "${LFBFL_common_options[@]}"
129 }

```

3.28 build_and_checks_dependencies/split_score.exec.php

```

1  #!/usr/bin/php
2  <?php
3
4  /**
5   This file is part of DevOrSysAdminScripts.
6
7   DevOrSysAdminScripts is free software:
8   you can redistribute it and/or modify it
9   under the terms of the GNU Lesser General Public License
10  as published by the Free Software Foundation,
11  either version 3 of the License,
12  or (at your option) any later version.
13
14  DevOrSysAdminScripts is distributed
15  in the hope that it will be useful,

```

```

16 but WITHOUT ANY WARRANTY;
17 without even the implied warranty of
18 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
19 See the GNU Lesser General Public License for more details.
20
21 You should have received a copy of
22 the GNU Lesser General Public License
23 along with DevOrSysAdminScripts.
24 If not, see <https://www.gnu.org/licenses/>.
25
26 ©Copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
27 2026-01-04T13:38+01:00: This file was renamed from
28 "split_line_at_most.exec.php"
29 to
30 "split_score.exec.php".
31 This file was renamed from
32 "call_split_score_after_before_or_before_after.exec.php" to
33 "split_line_at_most.exec.php".
34 This file was renamed from
35 "call_split_score_after_before_or_before_after.php" to
36 "call_split_score_after_before_or_before_after.exec.php".
37
38 @category Executable
39 @package DevOrSysAdminScripts
40 @author Laurent Lyaudet <laurent.lyaudet@gmail.com>
41 @copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
42 @license https://www.gnu.org/licenses/lgpl-3.0.html LGPLv3+
43 */
44
45 declare(strict_types=1);
46 declare(encoding='UTF-8');
47
48 require_once './build_and_checks_dependencies/split_score.lib.php';
49
50 /*
51 php -r\
52   '$require_once(\'./build_and_checks_dependencies/\
53   $split_score.lib.php\');'\
54   '$ echo(generate_split_score'\
55   $(true, 70, [\'/\']) (\'/\', 60, true));'
56 */
57
58 // phpcs:disable Generic.WhiteSpace.ArbitraryParenthesesSpacing
59 // The first cast "(int) $func..." is to avoid false
60 // positive errors on possible XSS if output is unescaped.
61 echo(

```



```

62     (int) generate_split_score(
63         (bool) $argv[1],
64         (int) $argv[2],
65         explode(',', $argv[3]),
66     )($argv[4], (int) $argv[5], (bool) $argv[6])
67 );
68 // phpcs:disable Generic.WhiteSpace.ArbitraryParenthesesSpacing
69 ?>

```

3.29 build_and_checks_dependencies/split_score.lib.php

```

1  <?php
2
3  /**
4   This file is part of DevOrSysAdminScripts.
5
6   DevOrSysAdminScripts is free software:
7   you can redistribute it and/or modify it
8   under the terms of the GNU Lesser General Public License
9   as published by the Free Software Foundation,
10  either version 3 of the License,
11  or (at your option) any later version.
12
13  DevOrSysAdminScripts is distributed
14  in the hope that it will be useful,
15  but WITHOUT ANY WARRANTY;
16  without even the implied warranty of
17  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
18  See the GNU Lesser General Public License for more details.
19
20  You should have received a copy of
21  the GNU Lesser General Public License
22  along with DevOrSysAdminScripts.
23  If not, see <https://www.gnu.org/licenses/>.
24
25  ©Copyright 2023–2026 Laurent Frédéric Bernard François Lyaudet
26  2026-01-04T13:38+01:00: This file was renamed from
27  "split_line_at_most.lib.php"
28  to
29  "split_score.lib.php".
30  This file was renamed from "split_line_at_most.php" to
31  "split_line_at_most.lib.php".
32
33  @category Library
34  @package DevOrSysAdminScripts
35  @author Laurent Lyaudet <laurent.lyaudet@gmail.com>

```

```

36  @copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
37  @license https://www.gnu.org/licenses/lgpl-3.0.html LGPLv3+
38  */
39
40  declare(strict_types=1);
41  declare(encoding='UTF-8');
42
43
44
45  /**
46   Given the 3 following arguments, this function returns a closure that can
47   be used to compute the split score given the current string
48   (hopefully matching a delimiter), the current cut/split position,
49   and if that split position is after or before the current string.
50
51   @param bool          $b_larger_after
52                       Score is larger when splitting after,
53                       previous name of this parameter was $b_after_before.
54   @param int           $i_max_length
55                       The maximum length allowed (goal length).
56   @param array<string> $a_delimiter_strings_domain
57                       An array of "delimiters".
58
59   @return \Closure {
60       The "split_score" closure to use repeatedly afterward.
61
62       @param string $s_delimiter_string The string tested to be a delimiter.
63       @param int    $i_cut_position     The offset of the cut in the string.
64       @param bool   $b_is_cut_after     Is the offset taken after the string?
65
66       @return int The split score.
67   }
68  */
69  function generate_split_score(
70      bool $b_larger_after,
71      int $i_max_length,
72      array $a_delimiter_strings_domain,
73  ) : Closure {
74      return function (
75          string $s_delimiter_string,
76          int $i_cut_position,
77          bool $b_is_cut_after,
78      ) use (
79          $b_larger_after,
80          $i_max_length,
81          $a_delimiter_strings_domain,

```

```

82 ) : int {
83     if(
84         !in_array(
85             $s_delimiter_string,
86             $a_delimiter_strings_domain,
87             true,
88         )
89     ){
90         // I do not handle regexps for the moment.
91         // I'm too brainfucked. I just want to finish this feature fast
92         // for HTML and Tex/PDF listings generation with HTML and Tex on
93         // at most 70 characters.
94         return 0;
95     }
96     if($b_is_cut_after === $b_larger_after){
97         // When $b_larger_after,
98         // always way better to cut after '/' than before it.
99         // When !$b_larger_after (aka larger_before),
100         // always way better to cut before '/' than after it.
101         return 1 + $i_max_length + $i_cut_position;
102     }
103     return 1 + $i_cut_position;
104 };
105 }//end generate_split_score()
106 ?>

```

3.30 build_and_checks_dependencies/strings_functions.lib.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of

```

```

19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
24 # I think I created a file strings_functions.sh or renamed to
25 # strings_functions.sh at some point, before committing.
26 # Hence, someone must have changed or reversed the name of this file
27 # to string_functions.sh at some point.
28 # This file was renamed from "string_functions.sh" to
29 # "strings_functions.lib.sh".
30
31 LFBFL_subdir="build_and_checks_dependencies"
32 # shellcheck source=get_common_text_glob_patterns.lib.sh
33 source "${LFBFL_subdir}/get_common_text_glob_patterns.lib.sh"
34 # shellcheck source=comparisons.lib.sh
35 source "${LFBFL_subdir}/comparisons.lib.sh"
36 # shellcheck source=too_long_code_lines.lib.sh
37 source "${LFBFL_subdir}/too_long_code_lines.lib.sh"
38
39 split_line_at() {
40     # $1=line
41     # $2=position : number of characters in split_line_at_result_beginning
42     declare -g split_line_at_result_beginning="${1:0:$2}"
43     declare -g split_line_at_result_end="${1:$2}"
44     # printf "%s\n" "$split_line_at_result_beginning"
45     # printf "%s\n" "$split_line_at_result_end"
46 }
47
48 #-----
49 #-----
50 # Properties for the score for a possible split/cut in the string between
51 # two characters.
52 #-----
53 # Some preliminary remarks:
54 # a) If the character before the split position is a forbidden previous
55 # character, the score is -1.
56 # (Usually, either we have no or one forbidden previous character that is
57 # a backslash.)
58 # b) If the previous character is not forbidden,
59 # and either the character before the position is among the delimiters,
60 # or the character after the position is among the delimiters,
61 # then the score is computed according to the delimiter found,
62 # the position, and the fact that the position is after or before the
63 # delimiter.
64 # c) If two consecutive delimiters are found in the string,

```

```

65 # the maximum score between the one after the first delimiter
66 # and before the second delimiter is taken for the score between the
67 # two delimiters.
68 # d) Otherwise, by default,
69 # the score for cutting/splitting at some position is 0.
70 # e) A substring is given by the goal length given for the resulting
71 # strings/lines after split.
72 # f) When some scores are equal,
73 # we split at the rightmost position with maximum score in the substring.
74 # g) Remark f) implies that below we do not need to consider strict
75 # inequalities for the score for the result.
76 # But if you look at split_line_at_most code,
77 # you will see a micro-optimization where distinguishing < and <= could
78 # have been interesting.
79 # h) The score function SF(position) which will dictate our choice for
80 # split/cut position is in reality
81 # SF1a(
82 #     position, previous_character, next_character, delimiters, forbiddens
83 # )
84 # but at the cost of expliciting its internal and adding verbosity,
85 # we can see that the score really depends on the following arguments
86 # SF1b(
87 #     position, matched_delimiter_before, matched_delimiter_after,
88 #     previous_character_is_forbidden
89 # )
90 # If it is needed,
91 # then matched_delimiter_before or matched_delimiter_after is NULL.
92 # Somehow previous_character can be seen as position.previous_character,
93 # and next_character can be seen as position.next_character.
94 # We can see that the previous or next character without
95 # knowing that it matches a delimiter is irrelevant.
96 # The fact that there is 1 or more delimiters may be interesting.
97 # The fact that there is 0 or more forbidden previous characters
98 # may be interesting, but we haven't integrated it in the split_score
99 # functions.
100 # SF1a when the previous character is not forbidden
101 # needs a score function SF2a with the following parameters
102 # SF2a(position, current_character, delimiter, is_after):
103 # SF1a(
104 #     position, previous_character, next_character, delimiters, forbiddens
105 # ) = max(
106 #     For all delimiter in delimiters,
107 #     SF2a(position, previous_character, delimiter, TRUE),
108 #     SF2a(position, next_character, delimiter, FALSE),
109 # )
110 # = max(

```

```

111 #       For all delimiter in delimiters,
112 #       For all couple C in {
113 #           (position.previous_character, TRUE),
114 #           (position.next_character, FALSE)
115 #       }
116 #       SF2a(position, C.1, delimiter, C.2),
117 #   )
118 #   Similarly,
119 #   SF1b(
120 #       position, matched_delimiter_before, matched_delimiter_after,
121 #       previous_character_is_forbidden
122 #   ) = max(
123 #       For all delimiter in delimiters,
124 #       SF2b(position, matched_delimiter_before, TRUE),
125 #       SF2b(position, matched_delimiter_after, FALSE),
126 #   )
127 #   where the score function SF2b has the following parameters
128 #   SF2b(cut_position, matched_delimiter, is_after).
129 #   We have also:
130 #   SF1b(
131 #       position, matched_delimiter_before, matched_delimiter_after,
132 #       previous_character_is_forbidden
133 #   ) = max(
134 #       For all delimiter in delimiters,
135 #       SF2c(position-1, matched_delimiter_before, TRUE),
136 #       SF2c(position, matched_delimiter_after, FALSE),
137 #   )
138 #   where the score function SF2c has the following parameters
139 #   SF2c(character_position, matched_delimiter, is_after).
140 #   current_character is only used to check if it is equal to the
141 #   delimiter, otherwise the score is zero;
142 #   but when expressing properties it makes sense to compare after
143 #   and before the same character position.
144 #   position, delimiter, and is_after may all three impact the score
145 #   once the current character matches the delimiter.
146 #   Position is an integer from 1 to goal length.
147 #   Cutting at position 0 would be stupid,
148 #   and moreover there would be no previous character.
149 #   Since we ask for a split, the current length is above goal length,
150 #   and there is a next character at the last considered position.
151 #   So, in search of properties that may have an impact on the algorithm,
152 #   we discard the characters to only keep matched delimiters.
153 #   Let us use p1 and p2 for position1 and position2,
154 #   mdb1 and mdb2 for matched_delimiter_before1, etc.,
155 #   mda1 and mda2 for matched_delimiter_after1, etc.,
156 #   pcif for previous_character_is_forbidden, etc.,

```

```

157 # md1 and md2 for matched_delimiter1, etc.,
158 # ia1 and ia2 for is_after1, etc.
159 #
160 # What we consider as properties are of 3 forms.
161 # The first form is like:
162 #   For all p1 in [1, goal_length], for all p2 in [1, goal_length],
163 #   for all mdb1 in delimiters union {NULL},
164 #   for all mdb2 in delimiters union {NULL},
165 #   for all mda1 in delimiters union {NULL},
166 #   for all mda2 in delimiters union {NULL},
167 #   RelationP(p1, p2) AND RelationM(mdb1, mdb2, mda1, mda2)
168 #   implies RelationS(
169 #       SF1b(p1, mdb1, mda1, false),
170 #       SF1b(p2, mdb2, mda2, false),
171 #   )
172 # There are many choices for RelationP, RelationM and RelationS.
173 # We can apply the without loss of generality argument only once when
174 # breaking symmetry between equivalent properties.
175 # Breaking symmetry on another relation that RelationS first
176 # is a challenge that we do not tackle.
177 # Indeed RelationS is the only relation where all variables appear.
178 # And breaking symmetry on RelationP would not allow to break symmetry
179 # on RelationM freely since some variables are correlated by the
180 # suffixes 1 or 2.
181 # But some choices for some relation may allow to break symmetry on
182 # another relation.
183 # Breaking symmetry on the result, there are only 2 choices for
184 # RelationS:
185 # RS= : SF1b(p1, mdb1, mda1, false) = SF1b(p2, mdb2, mda2, false),
186 # RS<= : SF1b(p1, mdb1, mda1, false) <= SF1b(p2, mdb2, mda2, false).
187 # But then there are 5+1 choices for RelationP:
188 # RP1 : p1 = p2,
189 # RP2 : p1 < p2,
190 # RP3 : p1 <= p2,
191 # RP4 : p1 > p2,
192 # RP5 : p1 >= p2,
193 # plus the choice that p1 and p2 are not necessarily related
194 # (empty RP or RPe).
195 # We can add RP6 : p1 = p2 - 1 and RP7 : p1 = p2 + 1, since it implies
196 # some equalities between matched delimiters.
197 # Note that p1 = p2 + i or p2 = p1 + i with i >= 2 brings no additional
198 # logical relations compared to p1 < p2 or p2 < p1;
199 # it only yields subslices of other properties and open a slightly silly
200 # door on infinity.
201 # If we have RS=, by symmetry we can consider only RP1, RP2, RP3 and RPe,
202 # and maybe RP6.

```

```

203 # Note that RSe or empty RS would have no interest at all.
204 # There are many choices for RelationM:
205 # mdb1 is NULL AND mdb2 is NULL AND mda1 is NULL AND mda2 is NULL is not
206 # interesting at all since both scores are 0 or -1.
207 # mdb1 is NULL AND mdb2 is NULL AND mda1 is NULL AND mda2 is not NULL
208 # implies that second score is always larger, that's not an additional
209 # property, that is a theorem.
210 # Hence, at least one of mdb1 or mda1, resp. mdb2 or mda2,
211 # must (have the possibility to) be non-NULL.
212 # If we start listing the remaining relations, we have:
213 # 1) mdb1 is NULL AND mdb2 is NULL AND mda1 is not NULL
214 #    AND mda2 is not NULL
215 #    RMA1A2
216 # 2) mdb1 is NULL AND mdb2 is NULL AND mda1 is not NULL
217 #    AND mda2 is not NULL
218 #    AND mda1 = mda2
219 #    RMA1A2=
220 # 3) mdb1 is NULL AND mdb2 is NULL AND mda1 is not NULL
221 #    AND mda2 is not NULL
222 #    AND mda1 != mda2 -> This case is not interesting (alone,
223 #    full analysis could combine it with some other case,
224 #    but it seems gratis combinatorial explosion without insight):
225 #    If we only know they are different, we cannot say anything on
226 #    properties related to delimiters that are different unless the score
227 #    doesn't depend on the delimiter, and that case is already handled by
228 #    1) that contains it. The same remark applies to some other choices.
229 #    The only thing that could be said would be if we had an order on
230 #    delimiters scores that are uniform for the position, or the score
231 #    before some delimiter would always be =, >=, <=, etc. the score
232 #    before or after another one. So it would only make sense with RPe,
233 #    and mda1 <= mda2 for example, but that would trivially imply RS<=.
234 #    It would end up with max(mda1, mdb1) <= max(mda2, mdb2) where max
235 #    ignores NULL value. You do not deduce or specify anything new here.
236 # 4) mdb1 is not NULL AND mdb2 is not NULL AND mda1 is NULL
237 #    AND mda2 is NULL
238 #    RMB1B2
239 # and so on. So if we use the short notation RM followed by A1, resp. A2,
240 # resp. B1, resp. B2, when mda1, resp. mda2, resp. mdb1, resp. mdb2,
241 # is not null, we have the following possibilities:
242 # RMA1A2, RMB1B2, RMA1B2, RMA2B1, all 4 with variant with = like RMA1A2=,
243 # RMA1A2B1, RMA1A2B2, RMA1B1B2, RMA2B1B2, all 4 (RMXXYYZZ) with variants
244 # with suffixes _1 (XX = YY), _2 (XX = ZZ), _3 (YY = ZZ),
245 # and _4 (XX = YY = ZZ)
246 # for equalities on the 1st, 2nd or 3rd couple or between the three
247 # variables by transitivity,
248 # RMALL where none is null, with suffixes A1A2 (A1 = A2), etc.

```



```

249 # RMALL_A1A2, RMALL_A1B1, RMALL_A1B2, RMALL_A2B1, RMALL_A2B2, RMALL_B1B2,
250 # for one edge;
251 # RMALL_A1A2B1, RMALL_A1A2B2, RMALL_A1B1B2, RMALL_A2B1B2, one triangle;
252 # RMALL_A1A2_B1B2, RMALL_A1B1_A2B2, RMALL_A1B2_A2B1, 2 disjoint edges;
253 # RMALL_ALL square with diagonals.
254 # So we see that we listed at least 39 possibilities only for RM.
255 # We did not list yet the possibilities where the variables not present
256 # in some equality can be NULL or not NULL, etc.
257 # We see 9 of them : RMe (40), and the following 8:
258 # RMA1A2+ = RMA1A2= OR RMA1A2B1_1 OR RMA1A2B2_1 OR RMALL_A1A2
259 # RMB1B2+ = RMB1B2= OR RMA1B1B2_3 OR RMA2B1B2_3 OR RMALL_B1B2
260 # RMA1B2+ = RMA1B2= OR RMA1A2B2_2 OR RMA1B1B2_2 OR RMALL_A1B2
261 # RMA2B1+ = RMA2B1= OR RMA1A2B1_3 OR RMA2B1B2_1 OR RMALL_A2B1
262 # RMA1A2B1+ = RMA1A2B1_4 OR RMALL_A1A2B1
263 # RMA1A2B2+ = RMA1A2B2_4 OR RMALL_A1A2B2
264 # RMA1B1B2+ = RMA1B1B2_4 OR RMALL_A1B1B2
265 # RMA2B1B2+ = RMA2B1B2_4 OR RMALL_A2B1B2
266 # We don't do complete analysis at the moment.
267 # If we wanted to filter out some possibilities,
268 # we would keep only the RM possibilities, among the 38,
269 # that are symmetric between 1 and 2:
270 # RMA1A2, RMB1B2, RMA1A2=, RMB1B2=,
271 # RMALL, RMALL_A1A2, RMALL_A2B2, RMALL_A1A2_B1B2, RMALL_A1B1_A2B2,
272 # RMALL_ALL. Still 10 possibilities.
273 # We have 1 (RS=) times 5 times 10 + 1 (RS<=) times 8 times 10 = 130
274 # combinations (life is too short ;) :) );
275 # if we keep 48 RM possibilities, there is 624 combinations,
276 # but we did not analyze totally which RM relations are useless.
277 #
278 # The second form is like:
279 #   For all p1 in [1, goal_length], for all p2 in [1, goal_length],
280 #   for all md1 in delimiters union {NULL},
281 #   for all md2 in delimiters union {NULL},
282 #   for all ial in {TRUE,FALSE}, for all ia2 in {TRUE,FALSE},
283 #   RelationP(p1, p2) AND RelationMM(md1, md2) AND RelationIA(ial, ia2)
284 #   implies RelationS(
285 #       SF2b(p1, md1, ial)
286 #       SF2b(p2, md2, ia2)
287 #   )
288 # The third form is like:
289 #   For all p1 in [1, goal_length], for all p2 in [1, goal_length],
290 #   for all md1 in delimiters union {NULL},
291 #   for all md2 in delimiters union {NULL},
292 #   for all ial in {TRUE,FALSE}, for all ia2 in {TRUE,FALSE},
293 #   RelationPP(p1, p2) AND RelationMM(md1, md2) AND RelationIA(ial, ia2)
294 #   implies RelationS(

```

```

295 #         SF2c(p1, md1, ia1)
296 #         SF2c(p2, md2, ia2)
297 #     )
298 # This time the combinatorics is much more pleasant :).
299 # As above, we have RS= and RS<=, RPe, RP1 to RP7;
300 # For RelationMM, assume that the possible delimiters correspond to
301 # integer numbers 1 to i; hence md1, resp. md2, can be seen as an integer
302 # in [0,i], either 0 for NULL or the delimiter index.
303 # Clearly, if md1 = k in [1,i] and md2 = l in [1,i], then the only
304 # information we can use is k = l or k != l.
305 # If we allow that md1 != 0 and md2 = 0,
306 # then both RS= and RS<= are false.
307 # Thus RMM= is not possible.
308 # If we allow that md1 = 0 and md2 != 0, then RS<= is always true,
309 # whilst RS= is false.
310 # Thus properties with RS<= can trivially be extended with
311 # RMM="allow-md1-0", not useful to explicit this for the moment.
312 # If both md1 = 0 and md2 = 0, then both scores are 0 and we also learn
313 # nothing more.
314 # Thus we can focus on: md1 and md2 are not NULL,
315 # and are equal RMM= or not RMM!=. It seems that a property with RMM!=
316 # could be extended to a property RMM=or!=/RMMNotNULL.
317 # and finally RIA0 to RIA8 where TRUE = 1, FALSE = 0 and the digit is
318 # 3 * ia1 + ia2, and both variables can be 2 if they can be either TRUE
319 # or FALSE. Wrong ! Not pleasant ! XD
320 # So for RIA, we keep either: empty RIAe (RIA8),
321 # ia1 = ia2 RIA= (RIA0 or RIA4),
322 # ia1 = ia2 = TRUE RIA=T (RIA4), ia1 = ia2 = FALSE RIA=F (RIA0),
323 # ia1 != ia2 RIA!= (RIA1 or RIA3), ia1 != ia2 = FALSE RIA!=T1 (RIA3),
324 # ia1 != ia2 = TRUE RIA!=T2 (RIA1),
325 # ia1 = TRUE (RIA5), ia1=FALSE (RIA2),
326 # ia2 = TRUE (RIA7), ia2=FALSE (RIA6),
327 # even less pleasant XD : 11 possibilities.
328 # In total, we have now 1 (RS=) times 5 times 2 times 11
329 # + 1 (RS<=) times 8 times 2 times 11 = 286
330 # combinations (life is even shorter ;) :).
331 # We only listed below properties of the third form.
332 # i) By the previous remark, there is a good chance that we missed some
333 # possible property.
334 # We hope we did found the properties that had a simple meaning,
335 # in particular related to the algorithm where either you
336 # loop on the string forward and keep last position with maximum score,
337 # or you loop backward and abort as soon as possible as soon you know
338 # that you found some position at the end that must have maximum score.
339 # j) These properties are "boolean" flags (integers that are powers of 2).
340 # We first put the exact integers,

```

```

341 # then wondered about switching everything to exponentiation 2**i,
342 # then we took the solution that minimizes the character length between
343 # [1-9][0-9]* and 2**i, then reverted to initial before committing.
344 # Most efficient interpreted code is what we did first,
345 # if there is no opcode cache for constants.
346 # Most safe code is when the language hides the details and handles
347 # families of flags,
348 # but beware if some flag goes into the database.
349 # Most readable code is a mix: 1 is easier to read than 2**0 ;) :P,
350 # or $(2<<0)...
351 # What I would love to see in many languages is a flag type, as a subtype
352 # of integers, flag32, flag64 for C for example.
353 # I think there is no such thing because sooner or later you play with
354 # pseudo-flags that are combination of flags, hence integers.
355 # But just for the declaration to let the type checker check that the
356 # integer is a power of 2: flag32 MY_FLAG = 4;
357 # Or better flag32 MY_FLAG = 2; as an equivalent of int32 MY_FLAG = 1<<2;
358 # Another fact is that practice makes perfect, so working with the powers
359 # of 2 written out in base 10 gets you accustomed to them.
360 # Safe code should be favored since (pre-)compilation optimizes it,
361 # but for this project, I prefer to keep the integers in decimal and
362 # check that it doubles when reading my listing, because I'm familiar
363 # with that and the powers of 2 doesn't go beyond what I can check fast
364 # enough in my brain.
365 # k) Some of the properties below are union of other properties,
366 # and are here to simplify not only code but understanding.
367 # split_score_properties_logical_closure() function below checks that
368 # all flags that are consequences of already activated flags are set.
369 # l) We use SSP_prefix for SPLIT_SCORE_PROPERTY_.
370 # Some of these remarks are repeated below in the corresponding functions,
371 # and some remarks are added just after the constants.
372 #-----
373 # Any score after a character that matches a delimiter
374 # is larger than or equal to
375 # any score before a character that matches a delimiter.
376 # RPPe RMMNotNull RIA!=T2 RS<=
377 declare -gir SSP_ALWAYS_LARGER_AFTER=1
378
379 # Any score before a character that matches a delimiter
380 # is larger than or equal to
381 # any score after a character that matches a delimiter.
382 # RPPe RMMNotNull RIA!=T1 RS<=
383 declare -gir SSP_ALWAYS_LARGER_BEFORE=2
384
385 # The score doesn't depend on the delimiter that is found.
386 # RPP1 RMMNotNull RIA= RS=

```

```

387 declare -gir SSP_DELIMITER_UNIFORM=4
388
389 # Whenever a character that matches a delimiter is found,
390 # the score after is equal to the score before.
391 # Or equivalently:
392 # For any delimiter, and for any character position,
393 # if the character at this position matches this delimiter,
394 # the score after the character
395 # is equal to
396 # the score before the character.
397 # RPP1 RMM= RIA!= RS=
398 declare -gir SSP_EQUAL_AFTER_OR_BEFORE=8
399 # declare -gir SSP_SAME_DELIMITER_AND_POSITION_EQUAL_AFTER_OR_BEFORE=
400
401 # Whenever a character that matches a delimiter is found,
402 # the score after is larger than or equal to the score before.
403 # Or equivalently:
404 # For any delimiter, and for any character position,
405 # if the character at this position matches this delimiter,
406 # the score after the character
407 # is larger than or equal to
408 # the score before the character.
409 # RPP1 RMM= RIA!=T2 RS<=
410 declare -gir SSP_LARGER_AFTER=16
411 # declare -gir SSP_SAME_DELIMITER_AND_POSITION_LARGER_AFTER=
412
413 # Whenever a character that matches a delimiter is found,
414 # the score before is larger than or equal to the score after.
415 # Or equivalently:
416 # For any delimiter, and for any character position,
417 # if the character at this position matches this delimiter,
418 # the score before the character
419 # is larger than or equal to
420 # the score after the character.
421 # RPP1 RMM= RIA!=T1 RS<=
422 declare -gir SSP_LARGER_BEFORE=32
423 # declare -gir SSP_SAME_DELIMITER_AND_POSITION_LARGER_BEFORE=
424
425 # The score after, resp. before, a character that matches a delimiter
426 # doesn't decrease when the position in the string increase.
427 # (RPP2 or RPP3) RMM= RIA= RS<=
428 declare -gir SSP_POSITION_NOT DECREASING=64
429
430 # The score after a character that matches a delimiter doesn't decrease
431 # when the position in the string increases.
432 # (RPP2 or RPP3) RMM= RIA=T RS<=

```

```

433 declare -gir SSP_POSITION_NOT_DECREASING_AFTER=128
434
435 # The score before a character that matches a delimiter doesn't decrease
436 # when the position in the string increases.
437 # (RPP2 or RPP3) RMM= RIA=F RS<=
438 declare -gir SSP_POSITION_NOT_DECREASING_BEFORE=256
439
440 # The score after, resp. before, a character that matches a delimiter
441 # doesn't depend on the position in the string.
442 # (RPP2 or RPP3) RMM= RIA= RS=
443 declare -gir SSP_POSITION_UNIFORM=512
444
445 # The score after a character that matches a delimiter doesn't depend
446 # on the position in the string.
447 # (RPP2 or RPP3) RMM= RIA=T RS=
448 declare -gir SSP_POSITION_UNIFORM_AFTER=1024
449
450 # The score before a character that matches a delimiter doesn't depend
451 # on the position in the string.
452 # (RPP2 or RPP3) RMM= RIA=F RS=
453 declare -gir SSP_POSITION_UNIFORM_BEFORE=2048
454
455 # For any delimiter,
456 # any score after a character that matches this delimiter
457 # is equal to
458 # any score before a character that matches this delimiter.
459 # RPPe RMM= RIA!= RS=
460 # <=> RPPe RMM= RIAe RS=
461 declare -gir SSP_SAME_DELIMITER_EQUAL_AFTER_OR_BEFORE=4096
462
463 # For any delimiter,
464 # any score after a character that matches this delimiter
465 # is larger than or equal to
466 # any score before a character that matches this delimiter.
467 # RPPe RMM= RIA!=T2 RS<=
468 declare -gir SSP_SAME_DELIMITER_LARGER_AFTER=8192
469
470 # For any delimiter,
471 # any score before a character that matches this delimiter
472 # is larger than or equal to
473 # any score after a character that matches this delimiter.
474 # RPPe RMM= RIA!=T1 RS<=
475 declare -gir SSP_SAME_DELIMITER_LARGER_BEFORE=16384
476
477 # For any character position,
478 # assuming that a character at this position matches some delimiter,

```

```

479 # the score after a character at this position that matches a delimiter
480 # is equal to
481 # the score before a character at this position that matches a delimiter.
482 # RPP1 RMMNotNull RIA!= RS=
483 declare -gir SSP_SAME_POSITION_EQUAL_AFTER_OR_BEFORE=32768
484
485 # For any character position,
486 # assuming that a character at this position matches some delimiter,
487 # the score after a character at this position that matches a delimiter
488 # is larger than or equal to
489 # the score before a character at this position that matches a delimiter.
490 # RPP1 RMMNotNull RIA!=T2 RS<=
491 declare -gir SSP_SAME_POSITION_LARGER_AFTER=65536
492
493 # For any character position,
494 # assuming that a character at this position matches some delimiter,
495 # the score before a character at this position that matches a delimiter
496 # is larger than or equal to
497 # the score after a character at this position that matches a delimiter.
498 # RPP1 RMMNotNull RIA!=T1 RS<=
499 declare -gir SSP_SAME_POSITION_LARGER_BEFORE=131072
500
501 # For all possible split/cut positions, the score is equal as long as
502 # at least one of the previous and next characters is a delimiter.
503 # Or equivalently:
504 # Any score after a character that matches a delimiter
505 # is equal to
506 # any score before a character that matches a delimiter.
507 # is_after doesn't change anything.
508 # So we cut on the last position adjacent to a delimiter without
509 # forbidden previous character (edge case, on last position).
510 # RPPe RMMNotNull RIAe RS=
511 declare -gir SSP_UNIFORM=262144
512 # declare -gir SSP_ALWAYS_EQUAL_AFTER_OR_BEFORE=1
513
514 #-----
515 # m) Note that a property telling that the score is always the same
516 # even if the current character isn't among delimiters is not needed,
517 # since, in that case, a null split score command will split at the goal
518 # length.
519 #-----
520 #-----
521
522 split_score_properties_logical_closure(){
523     # $1=split_score_properties
524     # Since this code is not performance critical,

```

```

525 # we followed lexicographic order on constants,
526 # instead of an order to minimize the operations.
527 # It is also safer to avoid forgetting some relation.
528 declare -i LFBFL_i_result=$((($1))
529 declare -i LFBFL_i_result_old=0
530 declare -i LFBFL_i_all_flags=$((
531     SSP_ALWAYS_LARGER_AFTER
532     | SSP_ALWAYS_LARGER_BEFORE
533     | SSP_DELIMITER_UNIFORM
534     | SSP_EQUAL_AFTER_OR_BEFORE
535     | SSP_LARGER_AFTER
536     | SSP_LARGER_BEFORE
537     | SSP_POSITION_NOT DECREASING
538     | SSP_POSITION_NOT DECREASING_AFTER
539     | SSP_POSITION_NOT DECREASING_BEFORE
540     | SSP_POSITION_UNIFORM
541     | SSP_POSITION_UNIFORM_AFTER
542     | SSP_POSITION_UNIFORM_BEFORE
543     | SSP_SAME_DELIMITER_EQUAL_AFTER_OR_BEFORE
544     | SSP_SAME_DELIMITER_LARGER_AFTER
545     | SSP_SAME_DELIMITER_LARGER_BEFORE
546     | SSP_SAME_POSITION_EQUAL_AFTER_OR_BEFORE
547     | SSP_SAME_POSITION_LARGER_AFTER
548     | SSP_SAME_POSITION_LARGER_BEFORE
549     | SSP_UNIFORM
550 ))
551 until [[ LFBFL_i_result_old -eq LFBFL_i_result ]]; do
552     LFBFL_i_result_old=$((LFBFL_i_result))
553     if ((LFBFL_i_result & SSP_ALWAYS_LARGER_AFTER)); then
554         LFBFL_i_result=$((
555             LFBFL_i_result
556             | SSP_LARGER_AFTER
557             | SSP_SAME_DELIMITER_LARGER_AFTER
558             | SSP_SAME_POSITION_LARGER_AFTER
559         ))
560     fi
561     if ((LFBFL_i_result & SSP_ALWAYS_LARGER_BEFORE)); then
562         LFBFL_i_result=$((
563             LFBFL_i_result
564             | SSP_LARGER_BEFORE
565             | SSP_SAME_DELIMITER_LARGER_BEFORE
566             | SSP_SAME_POSITION_LARGER_BEFORE
567         ))
568     fi
569     if ((LFBFL_i_result & SSP_POSITION_NOT DECREASING)); then
570         LFBFL_i_result=$((

```

```

571         LFBFL_i_result
572         | SSP_POSITION_NOT_DECREASING_AFTER
573         | SSP_POSITION_NOT_DECREASING_BEFORE
574     ))
575 fi
576 if ((LFBFL_i_result & SSP_POSITION_UNIFORM)); then
577     LFBFL_i_result=$((
578         LFBFL_i_result
579         | SSP_POSITION_UNIFORM_AFTER
580         | SSP_POSITION_UNIFORM_BEFORE
581         | SSP_POSITION_NOT_DECREASING
582         | SSP_POSITION_NOT_DECREASING_AFTER
583         | SSP_POSITION_NOT_DECREASING_BEFORE
584     ))
585 fi
586 if ((LFBFL_i_result & SSP_POSITION_UNIFORM_AFTER)); then
587     LFBFL_i_result=$((
588         LFBFL_i_result
589         | SSP_POSITION_NOT_DECREASING_AFTER
590     ))
591 fi
592 if ((LFBFL_i_result & SSP_POSITION_UNIFORM_BEFORE)); then
593     LFBFL_i_result=$((
594         LFBFL_i_result
595         | SSP_POSITION_NOT_DECREASING_BEFORE
596     ))
597 fi
598 if ((LFBFL_i_result & SSP_SAME_DELIMITER_EQUAL_AFTER_OR_BEFORE)); then
599     LFBFL_i_result=$((
600         LFBFL_i_result
601         | SSP_EQUAL_AFTER_OR_BEFORE
602         | SSP_LARGER_AFTER
603         | SSP_LARGER_BEFORE
604         | SSP_SAME_DELIMITER_LARGER_AFTER
605         | SSP_SAME_DELIMITER_LARGER_BEFORE
606     ))
607 fi
608 if ((LFBFL_i_result & SSP_SAME_DELIMITER_LARGER_AFTER)); then
609     LFBFL_i_result=$((
610         LFBFL_i_result
611         | SSP_LARGER_AFTER
612     ))
613 fi
614 if ((LFBFL_i_result & SSP_SAME_DELIMITER_LARGER_BEFORE)); then
615     LFBFL_i_result=$((
616         LFBFL_i_result

```



```

617         | SSP_LARGER_BEFORE
618     ))
619 fi
620 if ((LFBFL_i_result & SSP_SAME_POSITION_EQUAL_AFTER_OR_BEFORE)); then
621     LFBFL_i_result=$((
622         LFBFL_i_result
623         | SSP_DELIMITER_UNIFORM
624         | SSP_EQUAL_AFTER_OR_BEFORE
625         | SSP_LARGER_AFTER
626         | SSP_LARGER_BEFORE
627         | SSP_SAME_POSITION_LARGER_AFTER
628         | SSP_SAME_POSITION_LARGER_BEFORE
629     ))
630 fi
631 if ((LFBFL_i_result & SSP_SAME_POSITION_LARGER_AFTER)); then
632     LFBFL_i_result=$((
633         LFBFL_i_result
634         | SSP_LARGER_AFTER
635     ))
636 fi
637 if ((LFBFL_i_result & SSP_SAME_POSITION_LARGER_BEFORE)); then
638     LFBFL_i_result=$((
639         LFBFL_i_result
640         | SSP_LARGER_BEFORE
641     ))
642 fi
643 if ((LFBFL_i_result & SSP_UNIFORM)); then
644     LFBFL_i_result=$((LFBFL_i_all_flags))
645     break
646 fi
647 if ((LFBFL_i_result & SSP_ALWAYS_LARGER_AFTER))\
648 && ((
649     LFBFL_i_result & (
650         SSP_ALWAYS_LARGER_BEFORE
651         | SSP_EQUAL_AFTER_OR_BEFORE
652         | SSP_LARGER_BEFORE
653         | SSP_SAME_DELIMITER_EQUAL_AFTER_OR_BEFORE
654         | SSP_SAME_DELIMITER_LARGER_BEFORE
655         | SSP_SAME_POSITION_EQUAL_AFTER_OR_BEFORE
656         | SSP_SAME_POSITION_LARGER_BEFORE
657     )
658 )); then
659     LFBFL_i_result=$((LFBFL_i_all_flags))
660     break
661 fi
662 if ((LFBFL_i_result & SSP_ALWAYS_LARGER_BEFORE))\

```

```

663      && ( (
664          LFBFL_i_result & (
665              SSP_EQUAL_AFTER_OR_BEFORE
666              | SSP_LARGER_AFTER
667              | SSP_SAME_DELIMITER_EQUAL_AFTER_OR_BEFORE
668              | SSP_SAME_DELIMITER_LARGER_AFTER
669              | SSP_SAME_POSITION_EQUAL_AFTER_OR_BEFORE
670              | SSP_SAME_POSITION_LARGER_AFTER
671          )
672      ); then
673          LFBFL_i_result=$((LFBFL_i_all_flags))
674          break
675      fi
676      if ((LFBFL_i_result & SSP_DELIMITER_UNIFORM))\
677      && ((LFBFL_i_result & SSP_EQUAL_AFTER_OR_BEFORE)); then
678          LFBFL_i_result=$((
679              LFBFL_i_result
680              | SSP_SAME_POSITION_EQUAL_AFTER_OR_BEFORE
681          ))
682      fi
683      if ((LFBFL_i_result & SSP_DELIMITER_UNIFORM))\
684      && ((LFBFL_i_result & SSP_LARGER_AFTER)); then
685          LFBFL_i_result=$((
686              LFBFL_i_result
687              | SSP_SAME_POSITION_LARGER_AFTER
688          ))
689      fi
690      if ((LFBFL_i_result & SSP_DELIMITER_UNIFORM))\
691      && ((LFBFL_i_result & SSP_LARGER_BEFORE)); then
692          LFBFL_i_result=$((
693              LFBFL_i_result
694              | SSP_SAME_POSITION_LARGER_BEFORE
695          ))
696      fi
697      if ((LFBFL_i_result & SSP_DELIMITER_UNIFORM))\
698      && ((LFBFL_i_result & SSP_SAME_DELIMITER_EQUAL_AFTER_OR_BEFORE)); then
699          LFBFL_i_result=$((LFBFL_i_all_flags))
700          break
701      fi
702      if ((LFBFL_i_result & SSP_DELIMITER_UNIFORM))\
703      && ((LFBFL_i_result & SSP_SAME_DELIMITER_LARGER_AFTER)); then
704          LFBFL_i_result=$((
705              LFBFL_i_result
706              | SSP_ALWAYS_LARGER_AFTER
707          ))
708      fi

```

```

709     if ((LFBFL_i_result & SSP_DELIMITER_UNIFORM))\
710     && ((LFBFL_i_result & SSP_SAME_DELIMITER_LARGER_BEFORE)); then
711         LFBFL_i_result=$((
712             LFBFL_i_result
713             | SSP_ALWAYS_LARGER_BEFORE
714         ))
715     fi
716     if ((LFBFL_i_result & SSP_LARGER_AFTER))\
717     && ((LFBFL_i_result & SSP_LARGER_BEFORE)); then
718         LFBFL_i_result=$((
719             LFBFL_i_result
720             | SSP_EQUAL_AFTER_OR_BEFORE
721         ))
722     fi
723     if ((LFBFL_i_result & SSP_LARGER_AFTER))\
724     && ((
725         LFBFL_i_result & (
726             SSP_POSITION_UNIFORM
727             | SSP_POSITION_UNIFORM_AFTER
728         )
729     )); then
730         LFBFL_i_result=$((
731             LFBFL_i_result
732             | SSP_SAME_DELIMITER_LARGER_AFTER
733         ))
734     fi
735     if ((LFBFL_i_result & SSP_LARGER_BEFORE))\
736     && ((
737         LFBFL_i_result & (
738             SSP_POSITION_UNIFORM
739             | SSP_POSITION_UNIFORM_BEFORE
740         )
741     )); then
742         LFBFL_i_result=$((
743             LFBFL_i_result
744             | SSP_SAME_DELIMITER_LARGER_BEFORE
745         ))
746     fi
747     if ((LFBFL_i_result & SSP_POSITION_NOT_DECREASING_AFTER))\
748     && ((LFBFL_i_result & SSP_POSITION_NOT_DECREASING_BEFORE)); then
749         LFBFL_i_result=$((
750             LFBFL_i_result
751             | SSP_POSITION_NOT_DECREASING
752         ))
753     fi
754     if ((LFBFL_i_result & SSP_POSITION_UNIFORM))\

```

```

755    && ((LFBFL_i_result & SSP_EQUAL_AFTER_OR_BEFORE)); then
756        LFBFL_i_result=$((
757            LFBFL_i_result
758            | SSP_SAME_DELIMITER_EQUAL_AFTER_OR_BEFORE
759        ))
760    fi
761    if ((LFBFL_i_result & SSP_POSITION_UNIFORM))\
762    && ((LFBFL_i_result & SSP_SAME_POSITION_EQUAL_AFTER_OR_BEFORE)); then
763        LFBFL_i_result=$((LFBFL_i_all_flags))
764        break
765    fi
766    if ((LFBFL_i_result & SSP_POSITION_UNIFORM))\
767    && ((LFBFL_i_result & SSP_SAME_POSITION_LARGER_AFTER)); then
768        LFBFL_i_result=$((
769            LFBFL_i_result
770            | SSP_ALWAYS_LARGER_AFTER
771        ))
772    fi
773    if ((LFBFL_i_result & SSP_POSITION_UNIFORM))\
774    && ((LFBFL_i_result & SSP_SAME_POSITION_LARGER_BEFORE)); then
775        LFBFL_i_result=$((
776            LFBFL_i_result
777            | SSP_ALWAYS_LARGER_BEFORE
778        ))
779    fi
780    if ((LFBFL_i_result & SSP_POSITION_UNIFORM_AFTER))\
781    && ((LFBFL_i_result & SSP_POSITION_UNIFORM_BEFORE)); then
782        LFBFL_i_result=$((
783            LFBFL_i_result
784            | SSP_POSITION_UNIFORM
785        ))
786    fi
787    if ((LFBFL_i_result & SSP_POSITION_UNIFORM_AFTER))\
788    && ((LFBFL_i_result & SSP_SAME_POSITION_LARGER_AFTER)); then
789        LFBFL_i_result=$((
790            LFBFL_i_result
791            | SSP_ALWAYS_LARGER_AFTER
792        ))
793    fi
794    if ((LFBFL_i_result & SSP_POSITION_UNIFORM_BEFORE))\
795    && ((LFBFL_i_result & SSP_SAME_POSITION_LARGER_BEFORE)); then
796        LFBFL_i_result=$((
797            LFBFL_i_result
798            | SSP_ALWAYS_LARGER_BEFORE
799        ))
800    fi

```

```

801 if ((LFBFL_i_result & SSP_SAME_DELIMITER_EQUAL_AFTER_OR_BEFORE)) \
802 && ((
803     LFBFL_i_result & (
804         SSP_SAME_POSITION_EQUAL_AFTER_OR_BEFORE
805         | SSP_SAME_POSITION_LARGER_AFTER
806         | SSP_SAME_POSITION_LARGER_BEFORE
807     )
808 )); then
809     LFBFL_i_result=$((LFBFL_i_all_flags))
810     break
811 fi
812 if ((LFBFL_i_result & SSP_SAME_DELIMITER_LARGER_AFTER)) \
813 && ((
814     LFBFL_i_result & (
815         SSP_SAME_POSITION_EQUAL_AFTER_OR_BEFORE
816         | SSP_SAME_POSITION_LARGER_BEFORE
817     )
818 )); then
819     LFBFL_i_result=$((LFBFL_i_all_flags))
820     break
821 fi
822 if ((LFBFL_i_result & SSP_SAME_DELIMITER_LARGER_AFTER)) \
823 && ((LFBFL_i_result & SSP_SAME_POSITION_LARGER_AFTER)); then
824     LFBFL_i_result=$((
825         LFBFL_i_result
826         | SSP_ALWAYS_LARGER_AFTER
827     ))
828 fi
829 if ((LFBFL_i_result & SSP_SAME_DELIMITER_LARGER_BEFORE)) \
830 && ((
831     LFBFL_i_result & (
832         SSP_SAME_POSITION_EQUAL_AFTER_OR_BEFORE
833         | SSP_SAME_POSITION_LARGER_AFTER
834     )
835 )); then
836     LFBFL_i_result=$((LFBFL_i_all_flags))
837     break
838 fi
839 if ((LFBFL_i_result & SSP_SAME_DELIMITER_LARGER_BEFORE)) \
840 && ((LFBFL_i_result & SSP_SAME_POSITION_LARGER_BEFORE)); then
841     LFBFL_i_result=$((
842         LFBFL_i_result
843         | SSP_ALWAYS_LARGER_BEFORE
844     ))
845 fi
846 if ((LFBFL_i_result & SSP_SAME_POSITION_LARGER_AFTER)) \

```

```

847     && ((LFBFL_i_result & SSP_SAME_POSITION_LARGER_BEFORE)); then
848         LFBFL_i_result=$((
849             LFBFL_i_result
850             | SSP_SAME_POSITION_EQUAL_AFTER_OR_BEFORE
851         ))
852     fi
853 done
854 declare -gi i_split_score_properties_logical_closure_result=$((
855     LFBFL_i_result
856 ))
857 }
858
859 split_score_simple() {
860     # $1=larger_after (The name was "after_before" previously,
861     #                 the meaning was not modified.
862     #                 Remark not repeated below.)
863     # $2=delimiters_strings_domain concatenated characters/delimiters
864     # $3=delimiter_string a single character
865     # $4=is_cut_after
866     declare -gi i_split_score_result
867     if [[ "$2" != *$3* ]]; then
868         i_split_score_result=0
869         return
870     fi
871     if [[ "$4" == "$1" ]]; then
872         i_split_score_result=2
873         return
874     fi
875     i_split_score_result=1
876 }
877
878 get_split_score_simple() {
879     # $1=larger_after
880     # $2=max_length
881     # $3=delimiters_strings_domain
882     declare -g get_split_score_result="split_score_simple $1 '$3'"
883     declare -gi i_get_split_score_result2
884     # i_get_split_score_result2=$((11-$1*4))
885     # if [[ $1 -eq 1 ]]; then
886     #     i_get_split_score_result2=7
887     # else
888     #     i_get_split_score_result2=11
889     # fi
890     i_get_split_score_result2=$((
891         SSP_DELIMITER_UNIFORM
892         + SSP_POSITION_UNIFORM

```

```

893     + SSP_LARGER_BEFORE
894     + (
895         $1 * (
896             SSP_LARGER_AFTER
897             - SSP_LARGER_BEFORE
898         )
899     )
900 ))
901 # shellcheck disable=SC2248
902 split_score_properties_logical_closure ${i_get_split_score_result2}
903 i_get_split_score_result2=$((
904     i_split_score_properties_logical_closure_result
905 ))
906 }
907
908 get_split_score_exec() {
909     declare -g SPLIT_SCORE_EXEC="./build_and_checks_dependencies"
910     SPLIT_SCORE_EXEC+="/split_score.exec.php"
911 }
912
913 split_score() {
914     # $1=larger_after
915     # $2=max_length
916     # $3=delimiters_strings_domain concatenated characters/delimiters
917     # $4=delimiter_string a single character
918     # $5=cut_position
919     # $6=is_cut_after
920     get_split_score_exec
921     declare -r LFBFL_command="${SPLIT_SCORE_EXEC} $1 $2 '$3' '$4' $5 $6"
922     declare -gi i_split_score_result
923     i_split_score_result=$(eval -- "${LFBFL_command}")
924 }
925
926 # This function is currently not called,
927 # hence we need this shellcheck disable.
928 # shellcheck disable=SC2034
929 get_split_score() {
930     # $1=larger_after
931     # $1=max_length
932     # $2=delimiters_strings_domain
933     declare -g get_split_score_result="split_score $1 $2 '$3'"
934     declare -gi i_get_split_score_result2
935     # i_get_split_score_result2=$((9-$1*4))
936     i_get_split_score_result2=$((
937         SSP_DELIMITER_UNIFORM
938         + SSP_LARGER_BEFORE

```

```

939     + (
940         $1 * (
941             SSP_LARGER_AFTER
942             - SSP_LARGER_BEFORE
943         )
944     )
945 ))
946 # shellcheck disable=SC2248
947 split_score_properties_logical_closure ${i_get_split_score_result2}
948 i_get_split_score_result2=$((
949     i_split_score_properties_logical_closure_result
950 ))
951 }
952
953 split_line_at_most() {
954     # $1=line
955     # $2=max_length of beginning result string
956     # $3=split_score_command
957     # negative score means do not consider as a possible split
958     # $4=split_score_command_properties :
959     # These properties are flags.
960     # If someday some property is not a flag,
961     # then create split_score_command_properties2.
962     # Old values to get a simple idea without reading everything at the
963     # beginning of file:
964     # - null or 0 no property;
965     # - 1 split score doesn't depend on which delimiter matches;
966     # - 2 split score doesn't depend on the current position;
967     # - 4 any split score after is always larger
968     #   than any split score before;
969     # - 8 any split score before is always larger
970     #   than any split score after;
971     # $5=forbidden_previous_character
972     # $6=split_score_command_delimiter_strings_domain
973     # optimisation if small domain
974     # - this argument can be "null", then we will use $3 only instead,
975     #   in that case, only mono-character strings are considered,
976     # - this argument can be an array of characters,
977     #   optimize accordingly,
978     # - this argument can be an array of strings,
979     #   optimize accordingly,
980     # - this argument can be an array of regexps,
981     #   optimize accordingly.
982     # Not sure an array of regexps makes more sense than a single
983     # one. Maybe they could be both cases with corresponding
984     # optimizations. Same for a single character or substring.

```



```

985 #
986 # Note that we're always looking for the last position to split
987 # among the positions with maximum score;
988 # if some position gets a score from 2 delimiters,
989 # its score is always the maximum of the two corresponding scores.
990 declare -g split_line_at_most_result_start
991 declare -g split_line_at_most_result_end
992 declare -A LFBFL_positions
993 # printf "%s %s %s %s\n" "$1" "$2" "$3" "$4"
994 # For my use case in Bash scripts, I will need only an array of
995 # characters. See get_split_score().
996 if [[ -n "$6" ]]; then
997     printf '$split_line_at_most() $6 NOT IMPLEMENTED YET\n'
998 fi
999 if [[ $2 -ge ${#1} ]]; then
1000     split_line_at_most_result_start=$1
1001     split_line_at_most_result_end=""
1002     return
1003 fi
1004 # We know that ${#1} > $2, hence ${#1} - 1 >= $2
1005 # Edge cases:
1006 # There is always at least one character that is overlength,
1007 # but we need to look only at the score before that character that is
1008 # overlength, the score after that character is invalid,
1009 # whatever ${#1} - 1 = $2, or ${#1} - 1 > $2.
1010 # That first character that is overlength has index $2.
1011 # The cut position after that character has index $2 + 1.
1012 # Looping from character position going from 0 to $2, we need to drop
1013 # score before character 0 and drop score after character $2.
1014 # We do this with forbidden score -1.
1015 declare -ir LFBFL_i_max=$(( $2 ))
1016 declare -i LFBFL_i
1017 declare -i LFBFL_j
1018 local LFBFL_current_char
1019
1020 if [[ $2 -lt 2 ]]; then
1021     printf "split_line_at_most: max_length should be at least 2...\n"
1022     return
1023 fi
1024 if [[ -n "$5" && "$1" =~ ^"$5"*$ ]]; then
1025     for ((LFBFL_i = 2; LFBFL_i <= $2; LFBFL_i <= 1)); do
1026         :
1027     done
1028     ((LFBFL_i >= 1))
1029     split_line_at_most_result_start="${1:0:LFBFL_i}"
1030     split_line_at_most_result_end="${1:LFBFL_i}"

```

```

1031     return
1032 fi
1033
1034 # At the beginning, each position has score 0.
1035 LFBFL_positions["0"]="-1"
1036 for ((LFBFL_i = 1; LFBFL_i <= LFBFL_i_max; ++LFBFL_i)) do
1037     LFBFL_positions["${LFBFL_i}"]="0"
1038 done
1039 LFBFL_positions["${LFBFL_i}"]=" -1"
1040
1041 # If we have a forbidden previous character,
1042 # we mark the forbidden positions with -1.
1043 if [[ -n "$5" ]]; then
1044     for ((LFBFL_i = 0; LFBFL_i < LFBFL_i_max;)) do
1045         LFBFL_current_char="${1:${LFBFL_i}:1}"
1046         ((++LFBFL_i))
1047         if [[ "${LFBFL_current_char}" == "$5" ]]; then
1048             LFBFL_positions["${LFBFL_i}"]=" -1"
1049         fi
1050     done
1051 fi
1052
1053 declare -r LFBFL_sort_command="sort --numeric-sort"
1054
1055 update_position_score() {
1056     # $1=position
1057     # Returns 0 if updated, 1 otherwise
1058     # printf "%s|%s\n" "${i_split_score_result}" "$1"
1059     if [[ i_split_score_result -ge 1 ]]; then
1060         # printf "valid result"
1061         if [[ ${LFBFL_positions["$1"]} != "-1" ]]; then
1062             LFBFL_positions["$1"]=$(
1063                 max "${LFBFL_sort_command}"\
1064                     "${LFBFL_positions["$1"]}"\
1065                     "${i_split_score_result}"
1066             )
1067             return 0
1068         fi
1069     fi
1070     return 1
1071 }
1072
1073 local LFBFL_split_score_command=$3
1074 declare -i LFBFL_split_score_command_properties=$4
1075
1076 normal_or_position_uniform_call() {

```

```

1077     # $1=cut_position
1078     # $2=is_cut_after
1079     if ((LFBFL_split_score_command_properties & SSP_POSITION_UNIFORM));
1080     then
1081         eval --\
1082             "${LFBFL_split_score_command} '${LFBFL_current_char}' $2"
1083     else
1084         eval --\
1085             "${LFBFL_split_score_command} '${LFBFL_current_char}' $1 $2"
1086     fi
1087 }
1088
1089 if (($4 & SSP_DELIMITER_UNIFORM))\
1090 && (($4 & SSP_LARGER_AFTER))\
1091 && (($4 & SSP_POSITION_NOT DECREASING_AFTER)); then
1092     for ((LFBFL_i = LFBFL_i_max; LFBFL_i >= 0; --LFBFL_i)) do
1093         LFBFL_current_char="${1:${LFBFL_i}:1}"
1094         LFBFL_j=$((LFBFL_i + 1))
1095         # shellcheck disable=SC2248
1096         normal_or_position_uniform_call ${LFBFL_j} 1
1097         # shellcheck disable=SC2248
1098         if update_position_score ${LFBFL_j}
1099         then
1100             break
1101         fi
1102
1103         # shellcheck disable=SC2248
1104         normal_or_position_uniform_call ${LFBFL_i} 0
1105         # shellcheck disable=SC2248
1106         update_position_score ${LFBFL_i}
1107     done
1108 elif (($4 & SSP_DELIMITER_UNIFORM))\
1109 && (($4 & SSP_LARGER_BEFORE))\
1110 && (($4 & SSP_POSITION_NOT DECREASING_BEFORE)); then
1111     for ((LFBFL_i = LFBFL_i_max; LFBFL_i >= 0; --LFBFL_i)) do
1112         LFBFL_current_char="${1:${LFBFL_i}:1}"
1113         # We still need to break in second if, after computing score after,
1114         # because SSP_LARGER_BEFORE implies large inequality instead of
1115         # strict inequality.
1116         # And since the algorithm is to take the largest position with
1117         # maximum score, there is a possibility that we'll break on a found
1118         # score before but for splitting on a score after.
1119         LFBFL_j=$((LFBFL_i + 1))
1120         # shellcheck disable=SC2248
1121         normal_or_position_uniform_call ${LFBFL_j} 1
1122         # shellcheck disable=SC2248

```

```

1123     update_position_score ${LFBFL_j}
1124
1125     # shellcheck disable=SC2248
1126     normal_or_position_uniform_call ${LFBFL_i} 0
1127     # shellcheck disable=SC2248
1128     if update_position_score ${LFBFL_i}
1129     then
1130         break
1131     fi
1132 done
1133 else
1134     for ((LFBFL_i = 0; LFBFL_i <= LFBFL_i_max;)) do
1135         LFBFL_current_char="${1:${LFBFL_i}:1}"
1136         eval -- "$3 '${LFBFL_current_char}' ${LFBFL_i} 0"
1137         # shellcheck disable=SC2248
1138         update_position_score ${LFBFL_i}
1139         ((++LFBFL_i))
1140         eval -- "$3 '${LFBFL_current_char}' ${LFBFL_i} 1"
1141         # shellcheck disable=SC2248
1142         update_position_score ${LFBFL_i}
1143     done
1144 fi
1145 declare -ir LFBFL_i_max_score=$(
1146     max 'sort --numeric-sort' "${LFBFL_positions[@]}"
1147 )
1148 local LFBFL_value
1149 declare -i LFBFL_i_best_position
1150 for ((LFBFL_i = LFBFL_i_max; LFBFL_i >= 0; --LFBFL_i)) do
1151     if [[ LFBFL_i -eq 0 ]]; then
1152         printf $'/!\split_line_at_most bug: no split position found./!\n'
1153     fi
1154     local LFBFL_value=${LFBFL_positions[${LFBFL_i}]}
1155     # printf "%s %s\n" "${LFBFL_i} ${LFBFL_value}"
1156     if [[ "${LFBFL_value}" == "${LFBFL_i_max_score}" ]]; then
1157         LFBFL_i_best_position=$((LFBFL_i))
1158         break
1159     fi
1160 done
1161 # shellcheck disable=SC2248
1162 split_line_at "$1" ${LFBFL_i_best_position}
1163 split_line_at_most_result_start="${split_line_at_result_beginning}"
1164 split_line_at_most_result_end="${split_line_at_result_end}"
1165 # printf "%s\n" "$split_line_at_most_result_start"
1166 # printf "%s\n" "$split_line_at_most_result_end"
1167 }
1168

```

```

1169 split_last_line() {
1170     # $1=new_lines
1171     # $2=prefix
1172     # $3=max_length
1173     # $4=suffix
1174     # $5=split_score_command
1175     # $6=split_score_command_properties
1176     # $7=forbidden_previous_character ('\ ' usually)
1177     # Options:
1178     # --verbose
1179     # In general, a prefix/suffix can be a required line prefix/suffix
1180     # for all final lines like a comment prefix,
1181     # or it can be a continuation line prefix/suffix applied only
1182     # when splitting a line in 2 lines,
1183     # or it can be a prefix/suffix for the string made of all the lines.
1184     # Clearly, there is no gain to couple handling a prefix/suffix for
1185     # the string made of all the lines in this function.
1186     # Since we add a prefix/suffix when splitting,
1187     # it is easy to see that we do not need to distinguish between
1188     # required line prefix/suffix and continuation line prefix/suffix.
1189     # The $2 and $4 arguments are given as concatenation of the
1190     # required and continuation line prefixes/suffixes as needed by the
1191     # user.
1192     # Thus lines arguments should be given already prefixed
1193     # and suffixed.
1194     # This is logic, since it would be cumbersome to handle prefixing
1195     # or not already splitted lines in this function
1196     # (see repeated_split_last_line).
1197     # The given max_length is the goal.
1198     # This function adapts the effective max position for the split by
1199     # taking into account the length of the suffix.
1200     declare -i LFBFL_i_verbose=0
1201     get_verbose_option "$@"
1202     declare -a LFBFL_return_traps_stack
1203     init_return_trap
1204
1205     enhanced_set_shell_option pipefail --trap-unset
1206
1207     declare -g split_last_line_result="$1"
1208     declare -ir LFBFL_i_length2=$(( $3 - ${#4} ))
1209     get_overlength_regexp "$3"
1210
1211     # Testing if some line is too long.
1212     printf "%s" "$1" \
1213     | grep --quiet "${get_overlength_regexp_result}"
1214     if [[ ${PIPESTATUS[1]} -eq 1 ]]; then

```

```

1215     return
1216 fi
1217
1218 declare -r LFBFL_start=$(
1219     printf "%s" "$1"\
1220     | head --lines=-1
1221 )
1222 # printf "start: %s\n" "${LFBFL_start}"
1223 declare -r LFBFL_last_line=$(
1224     printf "%s" "$1"\
1225     | tail --lines=1
1226 )
1227 # printf "last_line: %s\n" "${LFBFL_last_line}"
1228 split_last_line_result=""
1229 if [[ -n "${LFBFL_start}" ]]; then
1230     split_last_line_result="${LFBFL_start}"
1231     # Last line-return of LFBFL_start seems dropped by $( ) and not ="${} ".
1232     # printf "%s %s\n" "${#split_last_line_result}"
1233     # "${split_last_line_result}"
1234     split_last_line_result+="${'\n'}"
1235     # something="${split_last_line_result}"
1236     # printf "%s %s\n" "${#something}" "${something}"
1237 fi
1238 if [[ -n "$5" ]]; then
1239     # shellcheck disable=SC2248
1240     split_line_at_most "${LFBFL_last_line}" ${LFBFL_i_length2}\
1241         "$5" "$6" "$7"
1242     split_last_line_result+="${split_line_at_most_result_start}"
1243     split_last_line_result+=" $4"
1244     split_last_line_result+="${'\n'}"
1245     split_last_line_result+="$2${split_line_at_most_result_end}"
1246 else
1247     split_last_line_result+="${LFBFL_last_line:0:${LFBFL_i_length2}}"
1248     split_last_line_result+=" $4"
1249     split_last_line_result+="${'\n'}"
1250     split_last_line_result+="$2${LFBFL_last_line:${LFBFL_i_length2}}"
1251 fi
1252 # printf "result: %s\n" "${split_last_line_result}"
1253 }
1254
1255 repeated_split_last_line() {
1256     # See split_last_line for the first arguments.
1257     # $8=final_suffix to handle when the end of the original string
1258     # is the suffix.
1259     declare -g repeated_split_last_line_result="$1"
1260     local LFBFL_result="$1x"

```

```

1261 until
1262     [[ "${LFBFL_result}" == "${repeated_split_last_line_result}" ]];
1263 do
1264     split_last_line "${repeated_split_last_line_result}" "$2" "$3"\
1265         "$4" "$5" "$6" "$7"
1266     LFBFL_result="${repeated_split_last_line_result}"
1267     repeated_split_last_line_result="${split_last_line_result}"
1268     # printf "%s\n" "${repeated_split_last_line_result}"
1269 done
1270 if [[ -n "$4" && -n "$8" ]]; then
1271     declare -ir LFBFL_i_offset=$((-${#4}))
1272     local LFBFL_lines_end
1273     LFBFL_lines_end="${repeated_split_last_line_result: ${LFBFL_i_offset}}"
1274     if [[ "${LFBFL_lines_end}" == "$4" ]]; then
1275         repeated_split_last_line_result+="$8"
1276     fi
1277 fi
1278 }

```

3.31 build_and_checks_dependencies/too_long_code_lines.lib.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023–2026 Laurent Frédéric Bernard François Lyaudet
24 # This file was renamed from "too_long_code_lines.sh"
25 # to "too_long_code_lines.lib.sh".

```

```

26
27 LFBFL_subdir="build_and_checks_dependencies"
28 # shellcheck source=common_options.lib.sh
29 source "${LFBFL_subdir}/common_options.lib.sh"
30 # shellcheck source=get_common_text_glob_patterns.lib.sh
31 source "${LFBFL_subdir}/get_common_text_glob_patterns.lib.sh"
32 # shellcheck source=lines_filters.lib.sh
33 source "${LFBFL_subdir}/lines_filters.lib.sh"
34
35 get_overlength_regexp() {
36     # $1=length
37     # Option:
38     #   --length-is-overlength
39     declare -i LFBFL_i_overlength=$1
40     declare -i LFBFL_i_length_is_overlength
41     get_some_flag LFBFL_i_length_is_overlength --length-is-overlength 1 "$@"
42     if [[ LFBFL_i_length_is_overlength -eq 0 ]]; then
43         ((++LFBFL_i_overlength))
44     fi
45     readonly LFBFL_i_overlength
46     declare -g get_overlength_regexp_result=".\\${LFBFL_i_overlength}\\\\"
47     # declare -g get_overlength_regexp_result="^\\.\\${LFBFL_i_overlength}\\\\"
48     # declare -g get_overlength_regexp_result=".\\${LFBFL_i_overlength}\\}\\\\"
49     # First one seems to be faster by a few percents when testing like this:
50     # time for ((i = 0; i < 1000; ++i)); do grep '.{70}' COPYING; done
51     # time for ((i = 0; i < 1000; ++i)); do grep '^.{70}' COPYING; done
52     # time for ((i = 0; i < 1000; ++i)); do grep '.{70}$' COPYING; done
53 }
54
55 too_long_code_lines() {
56     # Options:
57     #   --verbose
58     #   --work-directory=""
59     #   --max-line-length
60     declare -i LFBFL_i_verbose=0
61     get_verbose_option "$@"
62     local LFBFL_work_directory=""
63     get_work_directory_option "$@"
64     declare -a LFBFL_return_traps_stack
65     init_return_trap
66     pushd_to_work_directory --trap-popd
67     can_continue_after_enhanced_pushd || return 1
68
69     declare -i LFBFL_i_max_line_length
70     get_max_line_length_option "$@"
71

```



```

72 # shellcheck disable=SC2248
73 get_overlength_regex ${LFBFL_i_max_line_length}
74
75 enhanced_set_shell_option pipefail --trap-unset
76
77 get_COMMON_TEXT_FILES_GLOB_PATTERNS
78 local LFBFL_pattern
79 local LFBFL_long_line
80 local LFBFL_file_path
81 local LFBFL_line
82 local LFBFL_extension
83 local LFBFL_base_name
84 local LFBFL_s_long_lines
85 declare -a LFBFL_arr_long_lines
86 for LFBFL_pattern in "${COMMON_TEXT_FILES_GLOB_PATTERNS[@]}"; do
87     if [[ LFBFL_i_verbose -eq 1 ]]; then
88         printf "too_long_code_lines: Iterating on pattern: %s.\n\"
89             "${LFBFL_pattern}"
90     fi
91     # shellcheck disable=SC2248
92     LFBFL_s_long_lines=$(
93         find . -type f -name "${LFBFL_pattern}" -printf '%P\n' \
94             | relevant_find \
95             | not_license_find \
96             | tr '\n' '\0' \
97             | xargs -0 grep --line-number --with-filename \
98                 --regexp="${get_overlength_regex_result}" --
99     )
100     if [[ -z "${LFBFL_s_long_lines}" ]]; then
101         [[ LFBFL_i_verbose -eq 1 ]] \
102             && printf "too_long_code_lines: No file found with long lines.\n"
103         continue
104     fi
105     mapfile -t LFBFL_arr_long_lines <<< "${LFBFL_s_long_lines}"
106     for LFBFL_long_line in "${LFBFL_arr_long_lines[@]}"; do
107         LFBFL_file_path=${LFBFL_long_line%:*} # Drop long ':*' suffix
108         # Remove file_path and line_number
109         LFBFL_line=${LFBFL_long_line#*:} # Drop short '*:' prefix
110         LFBFL_line=${LFBFL_line#*:} # Drop short '*:' prefix
111         # LFBFL_line="${LFBFL_line%/\\}/" # Drop/Replace '/' suffix by ''
112         LFBFL_extension=${LFBFL_file_path##*.} # Drop long '*.' prefix
113         LFBFL_base_name=${LFBFL_file_path%.*} # Drop short '.*' suffix
114         if [[ "${LFBFL_extension}" == "html" ]]; then
115             if [[ -f "${LFBFL_base_name}.md" ]]; then
116                 continue
117             fi

```

```

118         if grep --quiet --fixed-strings -- "${LFBFL_line}"\
119             "./build_and_checks_variables/temp/files_listing.html.sub"
120         then
121             continue
122         fi
123         printf "%s\n" "${LFBFL_long_line}"
124     elif [[ "${LFBFL_extension}" == "md" ]]; then
125         if [[ ! -f "${LFBFL_base_name}.md.tpl" ]]; then
126             printf "%s\n" "${LFBFL_long_line}"
127         fi
128     else
129         printf "%s\n" "${LFBFL_long_line}"
130     fi
131 done
132 done
133 }

```

3.32 build_and_checks_dependencies/update_common_build_and_checks.exec.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023–2026 Laurent Frédéric Bernard François Lyaudet
24 # This file was renamed from "update_common_build_and_checks.sh"
25 # to "update_common_build_and_checks.exec.sh".
26
27 cd .. || exit

```

```

28 # shellcheck source=overwrite_if_not_equal.lib.sh
29 source "./build_and_checks_dependencies/overwrite_if_not_equal.lib.sh"
30 cd build_and_checks_dependencies || exit
31
32 update_common_build_and_checks() {
33     # Option:
34     #   --verbose
35     declare -i LFBFL_i_verbose=0
36     if [[ "$*" == *--verbose* ]]; then
37         printf "%s %s\n" "$0" "$*"
38         LFBFL_i_verbose=1
39     fi
40     readonly LFBFL_i_verbose
41
42     if [[ ! -o pipefail ]]; then
43         [[ LFBFL_i_verbose -eq 1 ]] && printf "pipefail option activated\n"
44         set -o pipefail
45         trap 'set +o pipefail' RETURN
46     fi
47
48     declare -r LFBFL_common_file_name="common_build_and_checks.exec.sh"
49     cp -- "${LFBFL_common_file_name}.tpl" \
50         "${LFBFL_common_file_name}.temp"
51
52     declare -ar LFBFL_files_names=(
53         "build_dependencies_notes.exec.php"
54         "build_dependencies_notes.lib.php"
55         "build_md_from_printable_md.exec.sh"
56         "check_shell_scripts_beginnings.lib.sh"
57         "check_shell_scripts_indentation.lib.sh"
58         "check_URLs.lib.sh"
59         "common_options.lib.sh"
60         "comparisons.lib.sh"
61         "create_PDF.exec.sh"
62         "generate_from_template.lib.sh"
63         "get_common_text_glob_patterns.lib.sh"
64         "grammar_and_spelling_check.lib.sh"
65         "licenses_templates/build_licenses_templates.exec.sh"
66         "licenses_templates/license_file_header_AGPLv3+.tpl"
67         "licenses_templates/license_file_header_GPLv3+.tpl"
68         "licenses_templates/license_file_header_LGPLv3+.tpl"
69         "lines_counts.lib.sh"
70         "lines_filters.lib.sh"
71         "lines_maps.lib.sh"
72         "overwrite_if_not_equal.lib.sh"
73         "python_black_complement.lib.sh"

```

```

74     "python_isort_complement.lib.sh"
75     "repository_data.lib.sh"
76     "shell_checks_complement.lib.sh"
77     "split_score.exec.php"
78     "split_score.lib.php"
79     "strings_functions.lib.sh"
80     "too_long_code_lines.lib.sh"
81     "update_or_check_files_names_listing.exec.sh"
82 )
83
84 local LFBFL_file_name
85 local LFBFL_file_sha512
86 local LFBFL_file_sha512_all
87 local LFBFL_base_file_name
88 for LFBFL_file_name in "${LFBFL_files_names[@]}"; do
89     LFBFL_file_sha512=$(
90         sha512sum "./${LFBFL_file_name}"\
91         | cut --delimiter=' ' --fields=1
92     )
93     LFBFL_file_sha512_all="LFBFL_correct_sha512="
94     LFBFL_file_sha512_all+="'${LFBFL_file_sha512:0:45}'\n"
95     LFBFL_file_sha512_all+="    LFBFL_correct_sha512\+="
96     LFBFL_file_sha512_all+="'${LFBFL_file_sha512:45:44}'\n"
97     LFBFL_file_sha512_all+="    LFBFL_correct_sha512\+="
98     LFBFL_file_sha512_all+="'${LFBFL_file_sha512:89}' "
99     LFBFL_base_file_name=$(basename -- "${LFBFL_file_name}")
100     sed --in-place\
101         "s|@sha512_${LFBFL_base_file_name}@|${LFBFL_file_sha512_all}|g"\
102         "./${LFBFL_common_file_name}.temp"
103 done
104
105 overwrite_if_not_equal "./${LFBFL_common_file_name}"\
106     "./${LFBFL_common_file_name}.temp"
107
108 declare -r LFBFL_main_file_name="build_and_checks.exec.sh"
109 cp "./${LFBFL_main_file_name}.tpl" "../${LFBFL_main_file_name}.temp"
110
111 LFBFL_file_sha512=$(
112     sha512sum "./${LFBFL_common_file_name}"\
113     | cut --delimiter=' ' --fields=1
114 )
115 LFBFL_file_sha512_all="local LFBFL_correct_sha512\n"
116 LFBFL_file_sha512_all+="    LFBFL_correct_sha512="
117 LFBFL_file_sha512_all+="'${LFBFL_file_sha512:0:45}'\n"
118 LFBFL_file_sha512_all+="    LFBFL_correct_sha512\+="
119 LFBFL_file_sha512_all+="'${LFBFL_file_sha512:45:44}'\n"

```

```

120 LFBFL_file_sha512_all+=" LFBFL_correct_sha512\+="
121 LFBFL_file_sha512_all+="'${LFBFL_file_sha512:89}' "
122 sed --in-place\
123     "s|@sha512_${LFBFL_common_file_name}@|${LFBFL_file_sha512_all}|g"\
124     "../${LFBFL_main_file_name}.temp"
125
126 overwrite_if_not_equal "../${LFBFL_main_file_name}"\
127     "../${LFBFL_main_file_name}.temp"
128 }
129
130 update_common_build_and_checks "$@"

```

3.33 build_and_checks_dependencies/update_or_check_files_names_listing.exec.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # Copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
24
25 # 2025-12-30T21:33+01:00: This file was moved from
26 # "../build_and_checks_dependencies/listings"
27 # to
28 # "../build_and_checks_dependencies".
29 # This file was renamed from "update_or_check_files_names_listing.sh"
30 # to "update_or_check_files_names_listing.exec.sh".
31 # This file was renamed from "update_or_check_file_names_listing.sh"
32 # to "update_or_check_files_names_listing.sh"?

```

```

33
34 LFBFL_subdir="build_and_checks_dependencies"
35 # shellcheck source=common_options.lib.sh
36 source "${LFBFL_subdir}/common_options.lib.sh"
37 # shellcheck source=lines_filters.lib.sh
38 source "${LFBFL_subdir}/lines_filters.lib.sh"
39 # shellcheck source=strings_functions.lib.sh
40 source "${LFBFL_subdir}/strings_functions.lib.sh"
41
42 update_or_check_files_names_listing() {
43     # Options:
44     #   --verbose
45     #   --work-directory=""
46     declare -i LFBFL_i_verbose=0
47     get_verbose_option "$@"
48     local LFBFL_work_directory=""
49     get_work_directory_option "$@"
50     declare -a LFBFL_return_traps_stack
51     init_return_trap
52     pushd_to_work_directory --trap-popd
53     can_continue_after_enhanced_pushd || return 1
54
55     declare -i LFBFL_i_write
56     get_some_flag LFBFL_i_write --write 1 "$@"
57     declare -i LFBFL_i_append
58     get_some_flag LFBFL_i_append --append 1 "$@"
59
60     enhanced_set_shell_option pipefail --trap-unset
61
62     LFBFL_subdir2="build_and_checks_variables"
63     declare -r LFBFL_listing="${LFBFL_subdir2}/files_names_listing.txt"
64     declare -r LFBFL_data_file_path="${LFBFL_subdir2}/repository_data.txt"
65
66     declare -i LFBFL_i_max_line_length
67     grep_variable "${LFBFL_data_file_path}" max_line_length\
68         --result-variable-prefix="LFBFL_i_"
69
70     if [[ LFBFL_i_write -eq 1 ]]; then
71         : > "${LFBFL_listing}"
72     fi
73     # Remove line returns that are here to keep lines short.
74     sed --regexp-extended --null-data --expression='s/(.)\\n\\1/Mg'\
75         -- "${LFBFL_listing}"\
76         > "${LFBFL_listing}.temp"
77     # shopt -s dotglob was needed at some point but I don't see why now.
78     # shellcheck disable=SC2248

```

```

79 get_split_score_simple 1 ${LFBFL_i_max_line_length} /
80 declare -r LFBFL_split_score_command="${get_split_score_result}"
81 declare -i LFBFL_i_split_score_command_properties
82 LFBFL_i_split_score_command_properties=${i_get_split_score_result2}
83 readonly LFBFL_i_split_score_command_properties
84 local LFBFL_suffix=\\ # instead of '\\' to avoid shellcheck SC1003
85 readonly LFBFL_suffix
86 # There is always a '$'\n' final suffix from >>.
87 # But when origin string ends with the suffix we must add something.
88 declare -r LFBFL_final_suffix='$'\n\\'
89
90 local LFBFL_s_files_paths
91 LFBFL_s_files_paths=$(
92     find . -type f -printf '%P\n'\
93     | relevant_find\
94     | sort
95 )
96 # printf "%s\n" "${LFBFL_s_files_paths}"
97 declare -a LFBFL_arr_files_paths
98 if [[ -n "${LFBFL_s_files_paths}" ]]; then
99     if [[ LFBFL_i_verbose -eq 1 ]]; then
100         printf\
101             "update_or_check_files_names_listing: Some files to process.\n"
102         fi
103         mapfile -t LFBFL_arr_files_paths <<< "${LFBFL_s_files_paths}"
104     fi
105     # printf "%s\n" "${LFBFL_arr_files_paths[@]}"
106
107     local LFBFL_file_path
108     local LFBFL_base_file_name
109     for LFBFL_file_path in "${LFBFL_arr_files_paths[@]}"; do
110         # if [[ LFBFL_i_verbose -eq 1 ]]; then
111             #     printf\
112             #         "update_or_check_files_names_listing: Maybe ignored file: %s\n"\
113             #         "${LFBFL_file_path}"
114             # fi
115         git check-ignore --quiet -- "${LFBFL_file_path}" && continue
116         LFBFL_base_file_name=$(basename -- "${LFBFL_file_path}")
117         [[ "${LFBFL_base_file_name}" != files_names_listing.txt* ]]\
118         || continue
119         if [[ "${LFBFL_base_file_name}" == *.md ]]; then
120             if [[ -f "${LFBFL_file_path}.tpl" ]]; then
121                 continue
122             fi
123         fi
124         if [[ LFBFL_i_verbose -eq 1 ]]; then

```

```

125     printf "update_or_check_files_names_listing: Non-ignored file: %s\n"\
126         "${LFBFL_file_path}"
127 fi
128 # shellcheck disable=SC2248
129 repeated_split_last_line "${LFBFL_file_path}"\
130     ""\
131     ${LFBFL_i_max_line_length}\
132     "${LFBFL_suffix}"\
133     "${LFBFL_split_score_command}"\
134     ${LFBFL_i_split_score_command_properties}\
135     ""\
136     "${LFBFL_final_suffix}"
137 if [[ LFBFL_i_write -eq 1 ]]; then
138     # shellcheck disable=SC2001
139     printf "%s\n" "${repeated_split_last_line_result}"\
140         >> "${LFBFL_listing}"
141     continue
142 fi
143 if ! grep_fixed_string_with_anchor "${LFBFL_listing}.temp"\
144     "${LFBFL_file_path}" --quiet --enforce-line-ends-with-fixed-string;
145 then
146     printf "The file %s is not listed in %s.\n"\
147         "${LFBFL_file_path}"\
148         "${LFBFL_listing}"
149     if [[ LFBFL_i_append -eq 1 ]]; then
150         # shellcheck disable=SC2001
151         printf "%s\n" "${repeated_split_last_line_result}"\
152             >> "${LFBFL_listing}"
153     fi
154 fi
155 done
156
157 LFBFL_s_files_paths=$(cat -- "${LFBFL_listing}.temp")
158 if [[ -n "${LFBFL_s_files_paths}" ]]; then
159     mapfile -t LFBFL_arr_files_paths <<< "${LFBFL_s_files_paths}"
160 fi
161
162 for LFBFL_file_path in "${LFBFL_arr_files_paths[@]}"; do
163     [[ "${LFBFL_file_path}" != '/'/* ]] || continue
164     if [[ ! -f "${LFBFL_file_path}" ]]; then
165         printf "The non-file %s is listed in %s.\n"\
166             "${LFBFL_file_path}"\
167             "${LFBFL_listing}"
168     fi
169 done
170

```



```

171 rm -- "${LFBFL_listing}.temp"
172
173 if [[ LFBFL_i_verbos -eq 1 ]]; then
174     cat -- "${LFBFL_listing}"
175 fi
176 }
177
178 update_or_check_files_names_listing "$@"

```

3.34 build_and_checks_variables/.gitignore

```

1 temp/
2 upgrade_venvs_ts

```

3.35 build_and_checks_variables/.bandit.ini

```

1 # FILE: .bandit
2 [bandit]

```

3.36 build_and_checks_variables/.bandit_baseline.json

```

1 {"results":[]}

```

3.37 build_and_checks_variables/black.toml

```

1 [tool.black]
2 line-length = 75

```

3.38 build_and_checks_variables/dependencies_data.json

```

1 [
2   { "dependency_name": "Bash", "URLs": [
3     "https://www.gnu.org/software/bash/",
4     "https://tiswww.case.edu/php/chet/bash/bashtop.html",
5     "https://savannah.gnu.org/projects/bash/"
6   ] },
7   { "dependency_name": "GNU coreutils", "URLs": [
8     "https://www.gnu.org/software/coreutils/",
9     "https://savannah.gnu.org/projects/coreutils/"
10  ] },
11  { "dependency_name": "utils coreutils", "URLs": [
12    "https://utils.github.io/coreutils/",
13    "https://github.com/utils/coreutils"
14  ] },
15  { "dependency_name": "diff (GNU diffutils)", "URLs": [
16    "https://www.gnu.org/software/diffutils/",

```

```

17         "https://savannah.gnu.org/projects/diffutils/"
18     ] },
19     { "dependency_name": "find, xargs (GNU findutils)", "URLs": [
20         "https://www.gnu.org/software/findutils/",
21         "https://savannah.gnu.org/projects/findutils/"
22     ] },
23     { "dependency_name": "grep (GNU grep)", "URLs": [
24         "https://www.gnu.org/software/grep/",
25         "https://savannah.gnu.org/projects/grep/"
26     ] },
27     { "dependency_name": "sed (GNU sed)", "URLs": [
28         "https://www.gnu.org/software/sed/",
29         "https://savannah.gnu.org/projects/sed/"
30     ] },
31     { "dependency_name": "ShellCheck", "URLs": [
32         "https://www.shellcheck.net/",
33         "https://github.com/koalaman/shellcheck"
34     ] },
35     { "dependency_name": "GNU Wget", "URLs": [
36         "https://www.gnu.org/software/wget/",
37         "https://savannah.gnu.org/projects/wget/"
38     ] },
39     { "dependency_name": "more of util-linux", "URLs": [
40         "https://www.kernel.org/pub/linux/utils/util-linux/",
41         "https://git.kernel.org/pub/scm/utils/util-linux/util-linux.git/",
42         {
43             "URL": "https://github.com/util-linux/util-linux",
44             "comment": "official?"
45         }
46     ] },
47     { "dependency_name": "pandoc", "URLs": [
48         "https://pandoc.org/",
49         "https://github.com/jgm/pandoc"
50     ] },
51     { "dependency_name": "pdftex/pdflatex", "URLs": [
52         "https://www.tug.org/applications/pdftex/",
53         "https://tug.org/texlive/svn/"
54     ] },
55     { "dependency_name": "tree", "URLs": [
56         "https://oldmanprogrammer.net/source.php?dir=projects/tree",
57         "https://gitlab.com/OldManProgrammer/unix-tree",
58         "https://github.com/Old-Man-Programmer/tree"
59     ] },
60     { "dependency_name": "git", "URLs": [
61         "https://git-scm.com/about",
62         "https://github.com/git/git"

```

```

63 ] },
64 { "dependency_name": "pylint", "URLs": [
65     "https://www.pylint.org/",
66     "https://pylint.readthedocs.io/en/stable/",
67     "https://github.com/pylint-dev/pylint",
68     "https://pypi.org/project/pylint/"
69 ] },
70 { "dependency_name": "notify-send", "URLs": [
71     "https://gitlab.gnome.org/GNOME/libnotify/",
72     "https://gnome.pages.gitlab.gnome.org/libnotify/"
73 ] },
74 { "dependency_name": "black", "URLs": [
75     "https://github.com/psf/black",
76     "https://black.readthedocs.io/en/stable/",
77     "https://pypi.org/project/black/"
78 ] },
79 { "dependency_name": "isort", "URLs": [
80     "https://pycqa.github.io/isort/",
81     "https://github.com/pycqa/isort/",
82     "https://pypi.org/project/isort/"
83 ] },
84 { "dependency_name": "mypy", "URLs": [
85     "https://mypy-lang.org/",
86     "https://mypy.readthedocs.io/en/stable/",
87     "https://github.com/python/mypy",
88     "https://pypi.org/project/mypy/"
89 ] },
90 { "dependency_name": "phpdoc (phpDocumentor)", "URLs": [
91     "https://phpdoc.org/",
92     "https://docs.phpdoc.org/",
93     "https://github.com/phpdocumentor/phpdocumentor"
94 ] },
95 { "dependency_name": "pip", "URLs": [
96     "https://pip.pypa.io/en/stable/",
97     "https://github.com/pypa/pip",
98     {
99         "URL": "https://pypi.org/project/pip/",
100         "comment": "(egg and chicken ;)"
101     }
102 ] },
103 { "dependency_name": "ruff", "URLs": [
104     "https://docs.astral.sh/ruff/",
105     "https://github.com/astral-sh/ruff",
106     "https://pypi.org/project/ruff/"
107 ] },
108 { "dependency_name": "xmllint (libxml2)", "URLs": [

```

```

109         "https://gitlab.gnome.org/GNOME/libxml2/-/wikis/home",
110         "https://gitlab.gnome.org/GNOME/libxml2"
111     ] },
112     { "dependency_name": "bandit", "URLs": [
113         "https://bandit.readthedocs.io/en/latest/",
114         "https://github.com/PyCQA/bandit",
115         "https://pypi.org/project/bandit/"
116     ] },
117     { "dependency_name": "phpcs (PHP_CodeSniffer)", "URLs": [
118         "https://github.com/PHPCSStandards/PHP_CodeSniffer",
119         "https://packagist.org/packages/squizlabs/php_codesniffer"
120     ] },
121     { "dependency_name": "phpmd", "URLs": [
122         "https://phpmd.org/",
123         "https://github.com/phpmd/phpmd",
124         "https://packagist.org/packages/phpmd/phpmd"
125     ] },
126     { "dependency_name": "php", "URLs": [
127         "https://www.php.net/",
128         "https://github.com/php/php-src"
129     ] },
130     { "dependency_name": "tex", "URLs": [
131         "https://ctan.org/tex-archive/systems/knuth/dist/tex"
132     ] },
133     { "dependency_name": "pcregrep, pcre2grep", "URLs": [
134         "https://www.pcre.org/",
135         "https://pcre2project.github.io/pcre2/",
136         "https://github.com/PCRE2Project/pcre1",
137         "https://github.com/PCRE2Project/pcre2",
138         "https://github.com/PCRE2Project/pcre2/blob/main/src/pcre2grep.c"
139     ] },
140     { "dependency_name": "python3", "URLs": [
141         "https://www.python.org/",
142         "https://docs.python.org/3/"
143     ] }
144 ]

```

3.39 build_and_checks_variables/dependencies_notes.txt

```

1 Bash can be found at the following URLs:
2 https://www.gnu.org/software/bash/
3 https://tiswww.case.edu/php/chet/bash/bashtop.html
4 https://savannah.gnu.org/projects/bash/
5
6 GNU coreutils can be found at the following URLs:
7 https://www.gnu.org/software/coreutils/

```

8 <https://savannah.gnu.org/projects/coreutils/>
9
10 utils coreutils can be found at the following URLs:
11 <https://uutils.github.io/coreutils/>
12 <https://github.com/uutils/coreutils>
13
14 diff (GNU diffutils) can be found at the following URLs:
15 <https://www.gnu.org/software/diffutils/>
16 <https://savannah.gnu.org/projects/diffutils/>
17
18 find, xargs (GNU findutils) can be found at the following URLs:
19 <https://www.gnu.org/software/findutils/>
20 <https://savannah.gnu.org/projects/findutils/>
21
22 grep (GNU grep) can be found at the following URLs:
23 <https://www.gnu.org/software/grep/>
24 <https://savannah.gnu.org/projects/grep/>
25
26 sed (GNU sed) can be found at the following URLs:
27 <https://www.gnu.org/software/sed/>
28 <https://savannah.gnu.org/projects/sed/>
29
30 ShellCheck can be found at the following URLs:
31 <https://www.shellcheck.net/>
32 <https://github.com/koalaman/shellcheck>
33
34 GNU Wget can be found at the following URLs:
35 <https://www.gnu.org/software/wget/>
36 <https://savannah.gnu.org/projects/wget/>
37
38 more of util-linux can be found at the following URLs:
39 <https://www.kernel.org/pub/linux/utils/util-linux/>
40 <https://git.kernel.org/pub/scm/utils/util-linux/util-linux.git/>
41 <https://github.com/util-linux/util-linux> official?
42
43 pandoc can be found at the following URLs:
44 <https://pandoc.org/>
45 <https://github.com/jgm/pandoc>
46
47 pdftex/pdflatex can be found at the following URLs:
48 <https://www.tug.org/applications/pdftex/>
49 <https://tug.org/texlive/svn/>
50
51 tree can be found at the following URLs:
52 <https://oldmanprogrammer.net/source.php?dir=projects/tree>
53 <https://gitlab.com/OldManProgrammer/unix-tree>

```

54 https://github.com/Old-Man-Programmer/tree
55
56 git can be found at the following URLs:
57 https://git-scm.com/about
58 https://github.com/git/git
59
60 pylint can be found at the following URLs:
61 https://www.pylint.org/
62 https://pylint.readthedocs.io/en/stable/
63 https://github.com/pylint-dev/pylint
64 https://pypi.org/project/pylint/
65
66 notify-send can be found at the following URLs:
67 https://gitlab.gnome.org/GNOME/libnotify/
68 https://gnome.pages.gitlab.gnome.org/libnotify/
69
70 black can be found at the following URLs:
71 https://github.com/psf/black
72 https://black.readthedocs.io/en/stable/
73 https://pypi.org/project/black/
74
75 isort can be found at the following URLs:
76 https://pycqa.github.io/isort/
77 https://github.com/pycqa/isort/
78 https://pypi.org/project/isort/
79
80 mypy can be found at the following URLs:
81 https://mypy-lang.org/
82 https://mypy.readthedocs.io/en/stable/
83 https://github.com/python/mypy
84 https://pypi.org/project/mypy/
85
86 phpdoc (phpDocumentor) can be found at the following URLs:
87 https://phpdoc.org/
88 https://docs.phpdoc.org/
89 https://github.com/phpdocumentor/phpdocumentor
90
91 pip can be found at the following URLs:
92 https://pip.pypa.io/en/stable/
93 https://github.com/pypa/pip
94 https://pypi.org/project/pip/ (egg and chicken ;) )
95
96 ruff can be found at the following URLs:
97 https://docs.astral.sh/ruff/
98 https://github.com/astral-sh/ruff
99 https://pypi.org/project/ruff/

```

```

100
101 xmllint (libxml2) can be found at the following URLs:
102 https://gitlab.gnome.org/GNOME/libxml2/-/wikis/home
103 https://gitlab.gnome.org/GNOME/libxml2
104
105 bandit can be found at the following URLs:
106 https://bandit.readthedocs.io/en/latest/
107 https://github.com/PyCQA/bandit
108 https://pypi.org/project/bandit/
109
110 phpcs (PHP_CodeSniffer) can be found at the following URLs:
111 https://github.com/PHPCSStandards/PHP_CodeSniffer
112 https://packagist.org/packages/squizlabs/php_codesniffer
113
114 phpmd can be found at the following URLs:
115 https://phpmd.org/
116 https://github.com/phpmd/phpmd
117 https://packagist.org/packages/phpmd/phpmd
118
119 php can be found at the following URLs:
120 https://www.php.net/
121 https://github.com/php/php-src
122
123 tex can be found at the following URL:
124 https://ctan.org/tex-archive/systems/knuth/dist/tex
125
126 pcregrep, pcre2grep can be found at the following URLs:
127 https://www.pcre.org/
128 https://pcre2project.github.io/pcre2/
129 https://github.com/PCRE2Project/pcre1
130 https://github.com/PCRE2Project/pcre2
131 https://github.com/PCRE2Project/pcre2/blob/main/src/pcre2grep.c
132
133 python3 can be found at the following URLs:
134 https://www.python.org/
135 https://docs.python.org/3/
136
137 If you see something that I missed regarding my dependencies,
138 please tell me/email me :).

```

3.40 build_and_checks_variables/DevOrSysAdminScripts.html.tpl

```

1 <!DOCTYPE html>
2 <html lang="en">
3 <!--
4 This file is part of DevOrSysAdminScripts.

```

```

5
6 DevOrSysAdminScripts is free software:
7 you can redistribute it and/or modify it
8 under the terms of the GNU Lesser General Public License
9 as published by the Free Software Foundation,
10 either version 3 of the License,
11 or (at your option) any later version.
12
13 DevOrSysAdminScripts is distributed
14 in the hope that it will be useful,
15 but WITHOUT ANY WARRANTY;
16 without even the implied warranty of
17 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
18 See the GNU Lesser General Public License for more details.
19
20 You should have received a copy of
21 the GNU Lesser General Public License
22 along with DevOrSysAdminScripts.
23 If not, see <https://www.gnu.org/licenses/>.
24
25 ©Copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
26 -->
27 <head>
28 <meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
29 <meta name="generator" content="DevOrSysAdminScripts">
30 <style>
31 .title{
32     margin: 2ex auto;
33     text-align: center;
34 }
35 .titlemain{
36     margin: 1ex 2ex 2ex 1ex;
37 }
38 .titlerest{
39     font-size: 1.17em;
40     margin: 0ex 2ex;
41 }
42 table{
43     border-collapse: collapse;
44 }
45 td{
46     padding: 0;
47 }
48 pre{
49     text-align: left;
50     margin-left: 0ex;

```



```

51     margin-right: auto;
52 }
53 pre.numbered_lines:before{
54     background: snow;
55     border-right: 1px black solid;
56     color: #010101;
57     content: attr(line-numbers);
58     float: left;
59     padding: 0 1ch;
60     text-align: right;
61 }
62 blockquote{
63     margin-left: 4ex;
64     margin-right: 4ex;
65     text-align: left;
66 }
67 ol.level1, ol.level2{
68     list-style-type: none;
69     /*
70     list-style-type: decimal;
71     Previous rule is shorter and more efficient if you need only level1.
72     But you don't have an accessible counter if you use decimal.
73     */
74 }
75 ol.level1{
76     counter-reset: level1;
77 }
78 ol.level2{
79     counter-reset: level2;
80 }
81 ol.level1 li:before{
82     content: counter(level1) ". ";
83     counter-increment: level1;
84 }
85 ol.level2 li:before{
86     content: counter(level1) "." counter(level2) " ";
87     counter-increment: level2;
88 }
89 </style>
90 <title>@repository_name@</title>
91 </head>
92 <body >
93 <table class="title">
94     <tr>
95         <td style="padding:1ex">
96             <h1 class="titlemain">@repository_name@</h1>

```

```

97         <h2 class="titlerest">
98             @author_full_name@
99             <br>
100             <a href="@author_website@">
101                 <span style="font-family:monospace">
102                     @author_website@
103                 </span>
104             </a>
105             <br>
106             <a href="mailto:@author_email@">
107                 <span style="font-family:monospace">
108                     @author_email@
109                 </span>
110             </a>
111         </h2>
112     </td>
113 </tr>
114 </table>
115
116 <blockquote class="abstract">
117     <span style="font-weight:bold">Abstract:</span>
118     @abstract@
119 </blockquote>
120 <p>Current version: @current_date@</p>
121 <p>Current number of commits: @number_of_commits@</p>
122 <p>Current git SHA1: @current_git_SHA1@</p>
123 <p>
124 Code lines: @number_of_lines@
125 </p>
126
127
128 <h2>Contents</h2>
129
130 <ol class="level1">
131     <li><a href="#section1">Files trees</a></li>
132     <li><a href="#section2">Notes on licenses and dependencies</a></li>
133     <li><a href="#section3">Listing of files</a><br>
134         <ol class="level2">
135             @files_lis@
136         </ol>
137     </li>
138 </ol>
139
140
141 <h2 id="section1">1 Files trees</h2>
142 <pre class="verbatim">

```

```

143 @current_tree_light@
144 </pre>
145 <pre class="verbatim">
146 @current_tree@
147 </pre>
148
149
150 <h2 id="section2">2 Notes on licenses and dependencies</h2>
151
152 <p>
153 This repository is dual licensed.
154 All the Bash scripts source code is covered by GPLv3+.
155 All the PHP scripts source code is covered by LGPLv3+.
156 All the Python scripts source code is covered by LGPLv3+.
157 </p>
158
159 <p>
160 The text of the licenses is available at:
161 <a href="https://www.gnu.org/licenses/"><span
162 style="font-family:monospace"
163 >https://www.gnu.org/licenses/</span></a>.
164 The git repository of this source code is also available at:
165 <a href="@repository_web_url@"><span
166 style="font-family:monospace"
167 >@repository_web_url@</span></a>.
168 Clone it with this URL:
169 <span style="font-family:monospace"
170 >@repository_git_url@</span>.
171 </p>
172
173 <div>
174 <p>
175 Here is a listing of the dependencies of the code in this repository:
176 </p>
177 <ul>
178 <li> The following dependencies are GPLv3+ licensed:<br>
179 basename, bash (and its builtins), cat, chmod, cp, cut, date, diff,
180 dirname, env, find, grep, head, mkdir, mv, realpath, rm, sed,
181 sha512sum, shellcheck, sort, tail, touch, wc, wget, xargs;
182 <li> The following dependencies are GPLv2+ licensed:<br>
183 more, pandoc, pdftex, pdflatex, tree;
184 <li> The following dependencies are GPLv2 licensed:<br>
185 git, pylint;
186 <li> The following dependencies are LGPLv2.1+ licensed:<br>
187 notify-send;
188 <li> The following dependencies are MIT licensed:<br>

```

```

189 black, isort, mypy, phpdoc, pip, ruff, xmllint;
190 <li> The following dependencies are Apache-2.0 licensed:<br>
191 bandit;
192 <li> The following dependencies are BSD-3-Clause licensed:<br>
193 phpcs, phpm;
194 <li> php is licensed under PHP License v3.01;
195 <li> tex is licensed under Knuth license;
196 <li> pcregrep, pcre2grep has a custom license from Cambridge
197 University, but PCRE2 has BSD-3-Clause WITH PCRE2-exception.
198 <li> python3 is licensed under PSF License Version 2 and the Zero-Clause
199 BSD license.
200 </ul>
201 </div>
202
203 <p>
204 Remark: Some commands listed under GPLv3+ are POSIX
205 and can have different implementations under another license;
206 for example, utils coreutils is MIT licensed,
207 whilst GNU coreutils is GPLv3+ licensed.
208 </p>
209
210 @dependencies_notes@
211
212
213 <h2 id="section3">3 Listing of files</h2>
214
215 @files_listing_HTMLPreInput@
216
217 <p>
218 @acknowledgments@
219 </p>
220
221 <script>
222 "use strict";
223 const pres = Array.from(
224   document.getElementsByClassName('numbered_lines')
225 );
226 pres.forEach(
227   (pre) => {
228     const nb = Array.from(pre.innerText.matchAll("\n")).length + 1;
229     let numbers = "";
230     for(let i = 1; i <= nb; ++i){
231       numbers += i.toString();
232       if(i < nb){ numbers += "\n "; }
233     }
234     pre.setAttribute('line-numbers', numbers);

```

```

235     }
236 );
237 </script>
238 </html>

```

3.41 build_and_checks_variables/DevOrSysAdminScripts.tex.tpl

```

1  % This file is part of DevOrSysAdminScripts.
2  %
3  % DevOrSysAdminScripts is free software:
4  % you can redistribute it and/or modify it
5  % under the terms of the GNU Lesser General Public License
6  % as published by the Free Software Foundation,
7  % either version 3 of the License,
8  % or (at your option) any later version.
9  %
10 % DevOrSysAdminScripts is distributed
11 % in the hope that it will be useful,
12 % but WITHOUT ANY WARRANTY;
13 % without even the implied warranty of
14 % MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
15 % See the GNU Lesser General Public License for more details.
16 %
17 % You should have received a copy of
18 % the GNU Lesser General Public License
19 % along with DevOrSysAdminScripts.
20 % If not, see <https://www.gnu.org/licenses/>.
21 %
22 % ©Copyright 2023–2026 Laurent Frédéric Bernard François Lyaudet
23
24 % 2025-12-29T17:08+01:00: This file was moved from
25 % "../latex"
26 % to
27 % "../build_and_checks_variables".
28
29 \documentclass{article}
30
31 \usepackage[utf8]{inputenc}
32 \usepackage[T1]{fontenc}
33 \usepackage{subfigure}
34 \usepackage{amsmath}
35 \usepackage{amssymb}
36 \usepackage{amsthm}
37 \usepackage[pdftex]{hyperref}
38 \usepackage{tikz}
39 \usepackage{caption}

```

```

40 \usepackage[round]{natbib}
41 \usepackage{fancyhdr}
42 \usepackage{amsfonts}
43 \usepackage{times}
44 \usepackage{ifpdf}
45 \usepackage{latexsym}
46 \usepackage{graphicx}
47 \usepackage{enumerate}
48 \usepackage{pmbboxdraw}
49 \usepackage{fancyvrb}
50 \usepackage[french,english]{babel}
51
52 % *** les environnements ***
53 %\theoremstyle{break}
54 \newtheorem{definition}{Definition}[section]
55 \newtheorem{proposition}[definition]{Proposition}
56 \newtheorem{theorem}[definition]{Theorem}
57 \newtheorem{lemma}[definition]{Lemma}
58 \newtheorem{corollary}[definition]{Corollary}
59 \newtheorem{remark}[definition]{Remark}
60 \newtheorem{openproblem}[definition]{Open problem}
61
62 \begin{document}
63
64 \author{
65   @author_full_name@\\
66   \url{@author_website@}\\
67   \href{mailto:@author_email@}{@author_email@}
68 }
69 \title{@repository_name@}
70
71 \maketitle
72 \begin{abstract}
73 @abstract@
74 \end{abstract}
75
76 Current version: @current_date@
77
78 Current number of commits: @number_of_commits@
79
80 Current git SHA1: @current_git_SHA1@
81
82 Code lines: @number_of_lines@
83
84 \tableofcontents
85 \newpage

```

```

86
87 \section{Files trees}
88 \label{section:trees}
89
90 \begin{verbatim}
91 @current_tree_light@
92 \end{verbatim}
93
94 \begin{verbatim}
95 @current_tree@
96 \end{verbatim}
97
98 \section{Notes on licenses and dependencies}
99 \label{section:notes_on}
100
101 This repository is dual licensed.
102 All the Bash scripts source code is covered by GPLv3+.
103 All the PHP scripts source code is covered by LGPLv3+.
104 All the Python scripts source code is covered by LGPLv3+.
105
106 The text of the licenses is available at:
107 \url{https://www.gnu.org/licenses/}.
108 The git repository of this source code is also available at:
109 \url{@repository_web_url@}.
110 Clone it with this URL:
111 \url{@repository_git_url@}.
112
113 Here is a listing of the dependencies of the code in this repository:
114 \begin{itemize}
115 \item The following dependencies are GPLv3+ licensed:\newline
116 basename, bash (and its builtins), cat, chmod, cp, cut, date, diff,
117 dirname, env, find, grep, head, mkdir, mv, realpath, rm, sed,
118 sha512sum, shellcheck, sort, tail, touch, wc, wget, xargs;
119 \item The following dependencies are GPLv2+ licensed:\newline
120 more, pandoc, pdftex, pdflatex, tree;
121 \item The following dependencies are GPLv2 licensed:\newline
122 git, pylint;
123 \item The following dependencies are LGPLv2.1+ licensed:\newline
124 notify-send;
125 \item The following dependencies are MIT licensed:\newline
126 black, isort, mypy, phpdoc, pip, ruff, xmllint;
127 \item The following dependencies are Apache-2.0 licensed:\newline
128 bandit;
129 \item The following dependencies are BSD-3-Clause licensed:\newline
130 phpcs, phpmd;
131 \item php is licensed under PHP License v3.01;

```

```

132 \item tex is licensed under Knuth license;
133 \item pcregrep, pcre2grep has a custom license from Cambridge
134 University, but PCRE2 has BSD-3-Clause WITH PCRE2-exception,
135 \item python3 is licensed under PSF License Version 2 and the Zero-Clause
136 BSD license.
137 \end{itemize}
138
139 Remark: Some commands listed under GPLv3+ are POSIX
140 and can have different implementations under another license;
141 for example, utils coreutils is MIT licensed,
142 whilst GNU coreutils is GPLv3+ licensed.
143
144 @dependencies_notes@
145
146 \section{Listing of files}
147 \label{section:listing}
148
149 @files_listing_VerbatimInput@
150
151 @acknowledgments@
152
153 \end{document}

```

3.42 build_and_checks_variables/files_names_listing.txt

```

1 // This file is part of DevOrSysAdminScripts.
2 //
3 // DevOrSysAdminScripts is free software:
4 // you can redistribute it and/or modify it under the terms
5 // of the GNU Lesser General Public License
6 // as published by the Free Software Foundation,
7 // either version 3 of the License,
8 // or (at your option) any later version.
9 //
10 // DevOrSysAdminScripts is distributed in the hope
11 // that it will be useful,
12 // but WITHOUT ANY WARRANTY;
13 // without even the implied warranty of
14 // MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
15 // See the GNU Lesser General Public License for more details.
16 //
17 // You should have received a copy of
18 // the GNU Lesser General Public License
19 // along with DevOrSysAdminScripts.
20 // If not, see <https://www.gnu.org/licenses/>.
21 //

```



```

22 // ©Copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
23 // 2024-10-31T21:37+01:00: This file was moved from
24 // "../build_and_checks_dependencies/listings"
25 // to
26 // "../build_and_checks_variables".
27 // Blasé20240517Résultat.txt
28 // Blasé20240517.sh
29 // Blasé20240518_2.txt
30 // Blasé20240518_3.txt
31 build_and_checks_dependencies/build_and_checks.exec.sh.tpl
32 build_and_checks_dependencies/build_dependencies_notes.exec.php
33 build_and_checks_dependencies/build_dependencies_notes.lib.php
34 build_and_checks_dependencies/build_md_from_printable_md.exec.sh
35 build_and_checks_dependencies/check_shell_scripts_beginnings.lib.sh
36 build_and_checks_dependencies/check_shell_scripts_indentation.lib.sh
37 build_and_checks_dependencies/check_URLs.lib.sh
38 build_and_checks_dependencies/common_build_and_checks.exec.sh
39 build_and_checks_dependencies/common_build_and_checks.exec.sh.tpl
40 build_and_checks_dependencies/common_options.lib.sh
41 build_and_checks_dependencies/comparisons.lib.sh
42 build_and_checks_dependencies/create_PDF.exec.sh
43 build_and_checks_dependencies/generate_from_template.lib.sh
44 build_and_checks_dependencies/get_common_text_glob_patterns.lib.sh
45 build_and_checks_dependencies/grammar_and_spelling_check.lib.sh
46 build_and_checks_dependencies/licenses_templates/\
47 build_licenses_templates.exec.sh
48 build_and_checks_dependencies/licenses_templates/\
49 license_file_header_AGPLv3+.tpl
50 build_and_checks_dependencies/licenses_templates/\
51 license_file_header_GPLv3+.tpl
52 build_and_checks_dependencies/licenses_templates/\
53 license_file_header_LGPLv3+.tpl
54 build_and_checks_dependencies/lines_counts.lib.sh
55 build_and_checks_dependencies/lines_filters.lib.sh
56 build_and_checks_dependencies/lines_maps.lib.sh
57 // build_and_checks_dependencies/listings/files_listing.tex.tpl
58 build_and_checks_dependencies/overwrite_if_not_equal.lib.sh
59 build_and_checks_dependencies/python_black_complement.lib.sh
60 build_and_checks_dependencies/python_isort_complement.lib.sh
61 build_and_checks_dependencies/repository_data.lib.sh
62 build_and_checks_dependencies/shell_checks_complement.lib.sh
63 build_and_checks_dependencies/split_score.exec.php
64 build_and_checks_dependencies/split_score.lib.php
65 build_and_checks_dependencies/strings_functions.lib.sh
66 build_and_checks_dependencies/too_long_code_lines.lib.sh
67 build_and_checks_dependencies/update_common_build_and_checks.exec.sh

```

```

68 build_and_checks_dependencies/\
69 update_or_check_files_names_listing.exec.sh
70 build_and_checks_variables/.gitignore
71 build_and_checks_variables/bandit.ini
72 build_and_checks_variables/bandit_baseline.json
73 build_and_checks_variables/black.toml
74 build_and_checks_variables/dependencies_data.json
75 build_and_checks_variables/dependencies_notes.txt
76 build_and_checks_variables/DevOrSysAdminScripts.html.tpl
77 // build_and_checks_variables/DevOrSysAdminScripts.tex
78 build_and_checks_variables/DevOrSysAdminScripts.tex.tpl
79 build_and_checks_variables/files_names_listing.txt
80 build_and_checks_variables/licenses_notes.txt
81 build_and_checks_variables/phpcs_ruleset.xml
82 build_and_checks_variables/phpmd_baseline.xml
83 build_and_checks_variables/pylintrc.toml
84 build_and_checks_variables/repository_data.txt
85 build_and_checks_variables/repository_data.txt.tpl
86 build_and_checks_variables/ruff.toml
87 build_and_checks_variables/shellcheck.ini
88 build_and_checks_variables/shellcheck_notes.txt
89 // build_and_checks_variables/upgrade_venvs_ts
90 build_and_checks.exec.sh
91 COPYING
92 COPYING.LESSER
93 // DevOrSysAdminScripts.html
94 // DevOrSysAdminScripts.pdf
95 // EncoreBlasé20240517-20240518.txt
96 git_helpers/git_checks.lib.sh
97 git_helpers/post-commit
98 git_helpers/post_commit_renaming_comment.lib.sh
99 git_helpers/pre-commit
100 IMAP_transfert.exec.py
101 LiensUtiles.txt
102 // Uncomment some files in miscellaneous to do some testing.
103 // miscellaneous/\
104 a_long_long_long_long_long_long_long_long_filename_so_that_you_can_se\
105 e_that_it_works.txt
106 miscellaneous/funny.sh
107 miscellaneous/spampty_data.txt
108 miscellaneous/string_escaping.html
109 miscellaneous/string_escaping.xhtml
110 // miscellaneous/\
111 yet_another_long_long_long_long_long_long_long_long_filename_so_that_\
112 you_can_see_that_it_works.txt
113 // README.html

```

```
114 // README.md
115 README.md.tpl
116 string_escaping.lib.php
117 unicode.lib.php
118 upgrade_build_and_checks.exec.sh
119 wget_sha512.lib.sh
```

3.43 build_and_checks_variables/licenses_notes.txt

```
1 This repository is dual licensed.
2 All the Bash scripts source code is covered by GPLv3+.
3 All the PHP scripts source code is covered by LGPLv3+.
4 All the Python scripts source code is covered by LGPLv3+.
5
6 Here is a listing of the dependencies of the code in this repository:
7 - The following dependencies are GPLv3+ licensed:
8 basename, bash (and its builtins), cat, chmod, cp, cut, date, diff,
9 dirname, env, find, grep, head, mkdir, mv, realpath, rm, sed,
10 sha512sum, shellcheck, sort, tail, touch, wc, wget, xargs;
11 - The following dependencies are GPLv2+ licensed:
12 more, pandoc, pdftex, pdflatex, tree;
13 - The following dependencies are GPLv2 licensed:
14 git, pylint;
15 - The following dependencies are LGPLv2.1+ licensed:
16 notify-send;
17 - The following dependencies are MIT licensed:
18 black, isort, mypy, phpdoc, pip, ruff, xmllint;
19 - The following dependencies are Apache-2.0 licensed:
20 bandit;
21 - The following dependencies are BSD-3-Clause licensed:
22 phpcs, phpmd;
23 - php is licensed under PHP License v3.01;
24 - tex is licensed under Knuth license;
25 - pcregrep, pcre2grep has a custom license from Cambridge University,
26 but PCRE2 has BSD-3-Clause WITH PCRE2-exception,
27 - python3 is licensed under PSF License Version 2 and the Zero-Clause BSD
28 license.
29
30 Remark: Some commands listed under GPLv3+ are POSIX
31 and can have different implementations under another license;
32 for example, utils coreutils is MIT licensed,
33 whilst GNU coreutils is GPLv3+ licensed.
```

3.44 build_and_checks_variables/phpcs_ruleset.xml

```
1 <?xml version="1.0"?>
2 <ruleset name="LFBFLCustomStandard" namespace="LFBFL\CS\CustomStandard">
3   <description>A custom coding standard</description>
4   <config name="tab_width" value="2"/>
5
6   <file>../</file>
7
8   <arg name="extensions" value="php"/>
9   <arg name="report" value="summary"/>
10  <arg name="colors"/>
11  <arg value="sp"/>
12
13  <!--
14  I added all the standards, then excluded all the rules that gave me
15  false positives or that seemed inappropriate when looking at the
16  documentation.
17  Some are bugs, some are conflicting with my own coding style.
18  You may delete an exclude and see what pops up to maybe understand
19  my choices.
20  -->
21
22  <rule ref="Generic">
23    <!-- You have to allow long or short or both syntaxes. -->
24    <exclude name="Generic.Arrays.DisallowShortArraySyntax"/>
25    <exclude name="Generic.Commenting.DocComment.ParamGroup"/>
26    <exclude name="Generic.Commenting.DocComment.TagsNotGrouped"/>
27    <exclude name="Generic.Commenting.DocComment.TagValueIndent"/>
28    <!-- Back to my habits at Teliae with always a closing tag. -->
29    <!-- <exclude name="Generic.PHP.ClosingPHPTag.NotFound"/> -->
30    <!--
31    Not standard in Unix/Linux world to keep files not ending with \n.
32    This is always an option of the code editors.
33    Since PHP doesn't output the final \n after ?>, it is ok.
34    -->
35    <exclude name="Generic.Files.EndFileNoNewline.Found"/>
36    <exclude name="Generic.Files.ExecutableFile.Executable"/>
37    <exclude name="Generic.Formatting.MultipleStatementAlignment"/>
38    <exclude
39      name="Generic.Functions.OpeningFunctionBraceBsdAllman.BraceOnSameLine"
40    />
41    <exclude
42      name="Generic.NamingConventions.CamelCapsFunctionName.NotCamelCaps"
43    />
44    <!-- Applies only to true, false and null. -->
```

```

45     <exclude name="Generic.PHP.LowerCaseConstant.Found"/>
46     <exclude name="Generic.PHP.UpperCaseConstant.Found"/>
47     <!-- const_bidule_HTML_truc would be better. Everything is prefix. -->
48     <exclude name="Generic.WhiteSpace.DisallowSpaceIndent.SpacesUsed"/>
49 </rule>
50 <rule ref="PEAR">
51     <exclude name="PEAR.Commenting.FileComment.MissingVersion"/>
52     <exclude name="PEAR.Commenting.FileComment.MissingLinkTag"/>
53     <!--
54     Look at the comment before generate_split_score.
55     PEAR and Squiz require to align the parameter names parts in the same
56     comment, and also the parameter comments parts in the same comment,
57     but with a long parameter name like $a_delimiter_strings_domain
58     and a line length limit at 75 characters, parameter comments parts
59     have only 24 characters left per line, which is ridiculous.
60     Our choice to put the parameter comments parts starting on another line
61     with same "indent" as parameter names parts is way better in those
62     cases. Alignment has always been a trap with short lines.
63     Since phpDocumentor handles the parameter comments parts correctly,
64     it is enough for me.
65     Worse is the handling of "nested doc block comment" for the Closure
66     returned by generate_split_score().
67     Our solution makes at least the source code readable.
68     Maybe one day the dev tools will handle it correctly.
69     -->
70     <exclude name="PEAR.Commenting.FunctionComment.DuplicateReturn"/>
71     <exclude name="PEAR.Commenting.FunctionComment.ExtraParamComment"/>
72     <exclude name="PEAR.Commenting.FunctionComment.MissingParamComment"/>
73     <exclude name="PEAR.Commenting.FunctionComment.SpacingAfterParamName"/>
74     <exclude name="PEAR.Commenting.FunctionComment.SpacingAfterParamType"/>
75     <exclude name="PEAR.ControlStructures.ControlSignature.Found"/>
76     <exclude name="PEAR.ControlStructures.MultiLineCondition.Alignment"/>
77     <exclude
78         name="PEAR.ControlStructures.MultiLineCondition.SpaceBeforeOpenBrace"
79     />
80     <exclude
81         name="PEAR.ControlStructures.MultiLineCondition.SpacingAfterOpenBrace"
82     />
83     <exclude
84         name="PEAR.ControlStructures.MultiLineCondition.StartWithBoolean"
85     />
86     <!--
87     Don't laugh when looking at the false positives of the two exclude
88     below ;) XD.
89     They don't check for multiline function declarations apparently.
90     -->

```

```

91     <exclude
92         name="PEAR.Functions.FunctionDeclaration.NewlineBeforeOpenBrace"
93     />
94     <exclude
95         name="PEAR.Functions.FunctionDeclaration.BraceOnSameLine"
96     />
97     <exclude
98         name="PEAR.NamingConventions.ValidFunctionName.FunctionNoCapital"
99     />
100    <exclude
101        name="PEAR.NamingConventions.ValidFunctionName.FunctionNameInvalid"
102    />
103 </rule>
104 <rule ref="PSR1">
105 </rule>
106 <rule ref="PSR2">
107     <!-- Back to my habits at Teliae with always a closing tag. -->
108     <exclude name="PSR2.Files.ClosingTag.NotAllowed"/>
109     <exclude
110 name="PSR2.ControlStructures.ControlStructureSpacing.SpacingAfterOpenBrace"
111     />
112 </rule>
113 <rule ref="PSR12">
114     <exclude
115 name="PSR12.ControlStructures.ControlStructureSpacing.FirstExpressionLine"
116     />
117     <exclude name="PSR12.Files.FileHeader.SpacingAfterDeclareBlock"/>
118     <!--
119     3 false positives, see:
120     https://github.com/PHPCSStandards/PHP_CodeSniffer/issues/1402
121     -->
122     <exclude
123         name="PSR12.Files.DeclareStatement.SpaceFoundAfterDirectiveValue"
124     />
125     <exclude
126         name="PSR12.Files.DeclareStatement.SpaceFoundBeforeDirectiveValue"
127     />
128     <exclude
129         name="PSR12.Files.DeclareStatement.SpaceFoundBeforeSemicolon"
130     />
131     <!-- and even a fourth and fifth false positives -->
132     <exclude
133         name="PSR12.Files.DeclareStatement.CloseBracketNotAligned"
134     />
135     <exclude
136         name="PSR12.Files.DeclareStatement.ExtraSpaceFoundAfterBracket"

```

```

137     />
138     <exclude name="PSR12.Classes.ClosingBrace.StatementAfter"/>
139     <exclude
140         name="PSR12.Functions.ReturnTypeDeclaration.SpaceBeforeColon"
141     />
142     <exclude name="PSR2.Namespaces.NamespaceDeclaration.BlankLineAfter"/>
143     <exclude name="PSR2.Namespaces.UseDeclaration.SpaceAfterLastUse"/>
144     <!-- I agree except for string concatenation. -->
145     <exclude name="PSR12.Operators.OperatorSpacing.NoSpaceBefore"/>
146     <exclude name="PSR12.Operators.OperatorSpacing.NoSpaceAfter"/>
147 </rule>
148 <rule ref="Squiz">
149     <exclude name="Squiz.Arrays.ArrayDeclaration.SingleLineNotAllowed"/>
150     <!--
151     It doesn't know the /* */ trick...
152     https://github.com/PHPCSStandards/PHP_CodeSniffer/issues/1403
153     -->
154     <exclude name="Squiz.Commenting.BlockComment.CloserSameLine"/>
155     <exclude name="Squiz.Commenting.BlockComment.FirstLineIndent"/>
156     <exclude name="Squiz.Commenting.BlockComment.LineIndent"/>
157     <exclude name="Squiz.Commenting.BlockComment.NoCapital"/>
158     <exclude name="Squiz.Commenting.BlockComment.NoEmptyLineAfter"/>
159     <exclude name="Squiz.Commenting.BlockComment.NoEmptyLineBefore"/>
160     <!-- Problem for doc block comment before namespace -->
161     <exclude name="Squiz.Commenting.BlockComment.WrongStart"/>
162     <exclude name="Squiz.Commenting.DocCommentAlignment.SpaceBeforeStar"/>
163     <exclude name="Squiz.Commenting.FileComment.CopyrightTagOrder"/>
164     <exclude name="Squiz.Commenting.FileComment.IncorrectAuthor"/>
165     <exclude name="Squiz.Commenting.FileComment.IncorrectCopyright"/>
166     <exclude name="Squiz.Commenting.FileComment.MissingSubpackageTag"/>
167     <exclude name="Squiz.Commenting.FileComment.PackageTagOrder"/>
168     <exclude name="Squiz.Commenting.FileComment.SpacingAfterOpen"/>
169     <exclude name="Squiz.Commenting.FileComment.SubpackageTagOrder"/>
170     <exclude name="Squiz.Commenting.FunctionComment.DuplicateReturn"/>
171     <exclude name="Squiz.Commenting.FunctionComment.ExtraParamComment"/>
172     <!-- asks for boolean instead of bool which is incorrect -->
173     <exclude
174         name="Squiz.Commenting.FunctionComment.IncorrectParamVarName"
175     />
176     <!-- asks for boolean instead of bool which is incorrect -->
177     <exclude name="Squiz.Commenting.FunctionComment.InvalidReturn"/>
178     <exclude name="Squiz.Commenting.FunctionComment.MissingParamComment"/>
179     <exclude name="Squiz.Commenting.FunctionComment.ParamCommentFullStop"/>
180     <exclude
181         name="Squiz.Commenting.FunctionComment.SpacingAfterParamName"
182     />

```

```

183     <exclude
184         name="Squiz.Commenting.FunctionComment.SpacingAfterParamType"
185     />
186     <!-- Problem for doc block comment before namespace -->
187     <exclude name="Squiz.Commenting.InlineComment.DocBlock"/>
188     <exclude name="Squiz.Commenting.InlineComment.NotCapital"/>
189     <!-- It doesn't know the /**/ trick... -->
190     <exclude name="Squiz.Commenting.InlineComment.NoSpaceBefore"/>
191     <exclude name="Squiz.Commenting.InlineComment.InvalidEndChar"/>
192     <exclude name="Squiz.Commenting.LongConditionClosingComment.Invalid"/>
193     <exclude name="Squiz.Commenting.PostStatementComment.Found"/>
194     <exclude
195         name="Squiz.ControlStructures.ControlSignature.SpaceAfterCloseBrace"
196     />
197     <exclude
198 name="Squiz.ControlStructures.ControlSignature.SpaceAfterCloseParenthesis"
199     />
200     <exclude
201         name="Squiz.ControlStructures.ControlSignature.SpaceAfterKeyword"
202     />
203     <exclude name="Squiz.Formatting.OperatorBracket.MissingBrackets"/>
204     <exclude name="Squiz.Functions.GlobalFunction.Found"/>
205     <exclude
206         name="Squiz.Functions.MultiLineFunctionDeclaration.BraceOnSameLine"
207     />
208     <exclude
209 name="Squiz.Functions.MultiLineFunctionDeclaration.NewlineBeforeOpenBrace"
210     />
211     <exclude
212         name="Squiz.NamingConventions.ValidFunctionName.NotCamelCaps"
213     />
214     <exclude
215         name="Squiz.NamingConventions.ValidVariableName.NotCamelCaps"
216     />
217     <exclude name="Squiz.Operators.ComparisonOperatorUsage.NotAllowed"/>
218     <exclude name="Squiz.Operators.ComparisonOperatorUsage.ImplicitTrue"/>
219     <exclude name="Squiz.PHP.CommentedOutCode"/>
220     <exclude name="Squiz.Strings.EchoedStrings.HasBracket"/>
221     <exclude name="Squiz.WhiteSpace.OperatorSpacing.NoSpaceBefore"/>
222     <exclude name="Squiz.WhiteSpace.OperatorSpacing.NoSpaceAfter"/>
223     <exclude name="Squiz.WhiteSpace.OperatorSpacing.SpacingBefore"/>
224     <exclude
225         name="Squiz.WhiteSpace.FunctionClosingBraceSpace.SpacingBeforeClose"
226     />
227 </rule>
228 <rule ref="Zend">

```



```

229     <!-- Back to my habits at Teliae with always a closing tag. -->
230     <exclude name="Zend.Files.ClosingTag.NotAllowed"/>
231     <exclude
232         name="Zend.NamingConventions.ValidVariableName.NotCamelCaps"
233     />
234 </rule>
235
236 <rule ref="Generic.Arrays.ArrayIndent">
237     <properties>
238         <property name="indent" value="2" />
239     </properties>
240 </rule>
241 <rule ref="Generic.Files.LineLength">
242     <properties>
243         <property name="lineLimit" value="75"/>
244         <property name="absoluteLineLimit" value="75"/>
245     </properties>
246 </rule>
247 <rule ref="Generic.Formatting.SpaceAfterNot">
248     <properties>
249         <property name="spacing" value="0" />
250     </properties>
251 </rule>
252 <rule ref="Generic.Functions.OpeningFunctionBraceKernighanRitchie">
253     <properties>
254         <property name="checkFunctions" value="true"/>
255         <property name="checkClosures" value="true"/>
256     </properties>
257 </rule>
258 <rule ref="Generic.Metrics.CyclomaticComplexity">
259     <properties>
260         <property name="complexity" value="40" />
261         <property name="absoluteComplexity" value="80" />
262     </properties>
263 </rule>
264 <rule ref="Generic.Strings.UnnecessaryStringConcat">
265     <properties>
266         <property name="allowMultiline" value="true" />
267     </properties>
268 </rule>
269 <rule ref="Generic.WhiteSpace.ArbitraryParenthesesSpacing">
270     <properties>
271         <property name="ignoreNewlines" value="true" />
272     </properties>
273 </rule>
274 <rule ref="Generic.WhiteSpace.ScopeIndent">

```

```

275     <properties>
276         <property name="ignoreIndentationTokens" type="array">
277             <element value="T_COMMENT"/>
278             <element value="T_DOC_COMMENT_OPEN_TAG"/>
279         </property>
280         <property name="indent" value="2"/>
281     </properties>
282 </rule>
283
284 <rule ref="PEAR.Functions.FunctionCallSignature">
285     <properties>
286         <property name="indent" value="2"/>
287     </properties>
288 </rule>
289 <rule ref="PEAR.Functions.FunctionDeclaration">
290     <properties>
291         <property name="indent" value="2"/>
292     </properties>
293 </rule>
294 <rule ref="PEAR.WhiteSpace.ScopeIndent">
295     <properties>
296         <property name="ignoreIndentationTokens" type="array">
297             <element value="T_COMMENT"/>
298             <element value="T_DOC_COMMENT_OPEN_TAG"/>
299         </property>
300         <property name="indent" value="2"/>
301     </properties>
302 </rule>
303
304 <rule ref="PSR2.Methods.FunctionCallSignature">
305     <properties>
306         <property name="indent" value="2"/>
307     </properties>
308 </rule>
309
310 <rule ref="PSR12.ControlStructures.ControlStructureSpacing">
311     <properties>
312         <property name="indent" value="2"/>
313     </properties>
314 </rule>
315
316 <rule ref="Squiz.Functions.MultiLineFunctionDeclaration">
317     <properties>
318         <property name="indent" value="2"/>
319     </properties>
320 </rule>

```

```

321 <rule ref="Squiz.Strings.ConcatenationSpacing">
322     <properties>
323         <property name="ignoreNewlines" value="true" />
324     </properties>
325 </rule>
326 <rule ref="Squiz.WhiteSpace.FunctionSpacing">
327     <properties>
328         <property name="spacing" value="3" />
329         <property name="spacingBeforeFirst" value="0" />
330         <property name="spacingAfterLast" value="0" />
331     </properties>
332 </rule>
333 </ruleset>

```

3.45 build_and_checks_variables/phpmd_baseline.xml

```

1 <?xml version="1.0"?>
2 <phpmd-baseline>
3     <violation rule="PHPMD\Rule\CyclomaticComplexity"
4         file="build_and_checks_dependencies/build_dependencies_notes.lib.php"
5     />
6     <violation rule="PHPMD\Rule\Design\NpathComplexity"
7         file="build_and_checks_dependencies/build_dependencies_notes.lib.php"
8     />
9     <violation rule="PHPMD\Rule\Design\LongMethod"
10        file="build_and_checks_dependencies/build_dependencies_notes.lib.php"
11    />
12    <violation rule="PHPMD\Rule\Controversial\CamelCaseParameterName"
13        file="build_and_checks_dependencies/build_dependencies_notes.lib.php"
14    />
15    <violation rule="PHPMD\Rule\Controversial\CamelCaseVariableName"
16        file="build_and_checks_dependencies/build_dependencies_notes.lib.php"
17    />
18    <violation rule="PHPMD\Rule\CleanCode\ElseExpression"
19        file="build_and_checks_dependencies/build_dependencies_notes.lib.php"
20    />
21    <violation rule="PHPMD\Rule\Naming\LongVariable"
22        file="build_and_checks_dependencies/build_dependencies_notes.lib.php"
23    />
24    <violation rule="PHPMD\Rule\Controversial\CamelCaseParameterName"
25        file="build_and_checks_dependencies/split_score.lib.php"
26    />
27    <violation rule="PHPMD\Rule\Naming\LongVariable"
28        file="build_and_checks_dependencies/split_score.lib.php"
29    />
30    <violation rule="PHPMD\Rule\Controversial\CamelCaseVariableName"

```

```

31     file="build_and_checks_dependencies/split_score.lib.php"
32 />
33 <violation rule="PHPMD\Rule\Controversial\CamelCaseParameterName"
34     file="string_escaping.lib.php"
35 />
36 <violation rule="PHPMD\Rule\Controversial\CamelCaseVariableName"
37     file="string_escaping.lib.php"
38 />
39 <violation rule="PHPMD\Rule\Design\LongMethod"
40     file="unicode.lib.php"
41 />
42 <violation rule="PHPMD\Rule\Controversial\CamelCaseParameterName"
43     file="unicode.lib.php"
44 />
45 <violation rule="PHPMD\Rule\Naming\LongVariable"
46     file="unicode.lib.php"
47 />
48 <violation rule="PHPMD\Rule\Controversial\CamelCaseVariableName"
49     file="unicode.lib.php"
50 />
51 <!-- https://github.com/phpmd/phpmd/issues/910 -->
52 <violation rule="PHPMD\Rule\CleanCode\MissingImport"
53     file="unicode.lib.php"
54 />
55 <violation rule="PHPMD\Rule\CyclomaticComplexity"
56     file="unicode.lib.php"
57 />
58 <violation rule="PHPMD\Rule\Design\NpathComplexity"
59     file="unicode.lib.php"
60 />
61 </phpmd-baseline>

```

3.46 build_and_checks_variables/pylintrc.toml

```

1 [tool.pylint.main]
2 exit-zero = true
3 ignore = ["node_modules"]
4 jobs = 0
5 [tool.pylint.basic]
6 # We use uppercase acronyms like HTML, IMAP, etc.
7 module-rgx = "^[_a-zA-Z0-9+]+$"
8 function-rgx = "^[_a-zA-Z0-9+]+$"
9 [tool.pylint."messages control"]
10 # Code like R0912 is better to order disables by category.
11 disable = [
12     "C1804", # use-implicit-booleaness-not-comparison-to-string

```

```

13 "I0011", # locally-disabled
14 "I0020", # suppressed-message
15 "R0912", # too-many-branches
16 "R0913", # too-many-arguments
17 "R0914", # too-many-locals
18 "R0915", # too-many-statements
19 "R0917", # too-many-positional-arguments
20 ]
21 enable = "all"
22 [tool.pylint.reports]
23 output-format = "colorized"

```

3.47 build_and_checks_variables/repository_data.txt

```

1 Look at grep_variable to understand the structure of this file.
2 Basically, it has almost no structure apart from some lines
3 starting with a "variable_name=".
4 Anything else is comments.
5
6 repository_name=DevOrSysAdminScripts
7 repository_web_url=https://github.com/LLyaudet/DevOrSysAdminScripts/
8 repository_git_url=git@github.com:LLyaudet/DevOrSysAdminScripts.git
9
10 abstract=Some "small" useful scripts
11 abstract=for enhancing development or system-administrators tasks
12
13 license=GPLv3+
14 license2=LGPLv3+
15
16 author_email=Laurent.Lyaudet@gmail.com
17 author_full_name=Laurent Frédéric Bernard François Lyaudet
18 author_last_name=Lyaudet
19 author_name=Laurent Lyaudet
20 author_website=https://lyaudet.eu/laurent/
21
22 acknowledgments=Merci Dieu !
23 acknowledgments=Merci Père ! Merci Seigneur ! Merci Saint Esprit !
24
25 Great day! Now I allow myself lines of 75 characters instead of 70 :).
26 I checked how many characters fit in the PDF file generated by tex with
27 default paper size,
28 when using verbatim environment with line numbers for source code listing.
29 With a screen capture in GIMP,
30 I mesured 197px between two-digits line numbers and the left border of
31 the page.
32 (It is less than 197px for three-digits or more line numbers.)

```

```

33 The same distance from the right border yields 75 characters allowed.
34 Since when printing the HTML file, the number of allowed characters in
35 <pre> tags is way larger, 75 is the right limit with the tools I use.
36
37 max_line_length=75
38
39 latex_command=pdflatex
40
41 grammar_and_spelling_checker_command=
42
43
44 Why one venv for each Python dependency ?
45 Because no language of my knowledge did it right to handle all
46 possible dependency conflicts.
47 So in case of such a conflict, one specialized venv can get you out
48 of any problem.
49 The best solution would have been to allow install of different
50 versions of the same package, and have a mechanism:
51 - default behavior, use the latest available version of a package among
52 those that satisfy the declared dependency constraints of the package
53 that has this dependency;
54 it requires that all dependency constraints are declared;
55 - custom behavior, check a dependency overload configuration file
56 with tree structure: if calling python package is A version 1.1.1
57 with dependency B itself with dependency C, use B 2.2.2 and C 3.3.3;
58 you could have along that another rule saying that when called
59 directly B 2.2.2 should use C 4.4.4;
60 and even more complicated:
61 if calling python package is A version 1.1.1 with dependency B and D
62 both themselves with dependency C, use B 2.2.2, D 0.1.0,
63 and C 3.3.3 for B, and C 4.4.4 for D;
64 once you've seen that it can never be more complicated than that once
65 the same version number guarantees that the code is the same,
66 you create a config language "à la CSS" for cascading dependencies ;)
67 XD fit into JSON the dumbest possible way and you stop bothering
68 about dependency conflicts for the rest of history of informatics.
69 {
70   "A":{
71     "1.1.1": {
72       "B": {
73         "2.2.2": {
74           "C": {
75             // Dumb, you did not found it by yourself? Failed exam.
76             "3.3.3" : {}
77           }
78         }
79       }
80     }
81   }
82 }

```

```

79         },
80         "D": {
81             "0.1.0": {
82                 "C": {
83                     // Dumb, you did not found it by yourself? Failed exam.
84                     "4.4.4" : {}
85                 }
86             }
87         }
88     },
89     "B": {
90         "2.2.2": {
91             "C": {
92                 // Dumb, you did not found it by yourself? Failed exam.
93                 "4.4.4" : {}
94             }
95         }
96     }
97 }
98
99 Wonderful someone rediscovered nested structures XD
100 Seriously so many engineers or computer scientists are dumb to cry.
101
102 bandit_venv=../venv_bandit
103 black_venv=../venv_black
104 isort_venv=../venv_isort
105 mypy_venv=../venv_mypy
106 pylint_venv=../venv_pylint
107 ruff_venv=../venv_ruff
108
109
110 upgrade_venvs can be auto or ask, any other value is interpreted
111 as ask.
112
113 upgrade_venvs=ask
114
115
116 time interval can be 0 to always upgrade or ask to upgrade,
117 or a number at most bash max int
118 https://superuser.com/questions/1030122/
119 what-is-the-maximum-value-of-a-numeric-bash-shell-variable
120 it should be enough to simulate never "upgrade or ask for upgrade"
121 unless you claim to live many billions years ;)
122 If it is wat, this is a random int XD (see RANDOM).
123 Note that the probability that it upgrades your dependencies is not
124 1/2, it increases over time, and is 1 after slightly

```

```

125 less than one day.
126 If it is watyouwant?, see SRANDOM XD.
127
128 upgrade_venvs_time_interval_in_seconds=wat
129
130
131 For the Nu HTML, CSS, and SVG checker.
132
133 vnu_jar_path=../jar_venv/vnu.jar
134
135 Not fully implemented yet, it will only warn that vnu jar was not
136 updated since some time.
137 "wat" works, but "watyouwant?" joke was not repeated ;).
138
139 upgrade_vnu_jar_time_interval_in_seconds=604800
140
141 use_vnu_for_xhtml=false
142
143 For xmllint_files_without_DTD and files_without_license_header,
144 each line is a file path, except if the line ends with a /,
145 then it is concatenated with the following line(s) to obtain a path.
146
147 xmllint_files_without_DTD=./build_and_checks_variables/phpcs_ruleset.xml
148 xmllint_files_without_DTD=./build_and_checks_variables/phpmd_baseline.xml
149
150 If you use Ubuntu/Debian, install w3c-sgml-lib instead of =true.
151 See https://gitlab.gnome.org/GNOME/libxml2/-/work\_items/1119
152
153 xmllint_use_downloaded_DTDs=false
154
155 files_without_license_header=build_and_checks_variables/phpcs_ruleset.xml
156 files_without_license_header=build_and_checks_variables/
157 files_without_license_header=phpmd_baseline.xml
158 files_without_license_header=README.html
159 files_without_license_header=miscellaneous/string_escaping.html
160 files_without_license_header=build_and_checks_variables/ruff.toml
161 files_without_license_header=build_and_checks_variables/black.toml
162 files_without_license_header=build_and_checks_variables/pylintsrc.toml

```

3.48 build_and_checks_variables/repository_data.txt.tpl

- 1 Look at grep_variable to understand the structure of this file.
- 2 Basically, it has almost no structure apart from some lines
- 3 starting with a "variable_name=".
- 4 Anything else is comments.
- 5 The goal of this template is to list all possible variables.


```
6
7 repository_name=
8 repository_web_url=
9 repository_git_url=
10
11 abstract=
12 abstract=
13
14 license=
15 license2=
16
17 author_email=
18 author_full_name=
19 author_last_name=
20 author_name=
21 author_website=
22
23 acknowledgments=
24 acknowledgments=
25
26 max_line_length=
27
28 latex_command=
29
30 grammar_and_spelling_checker_command=
31
32 bandit_venv=
33 black_venv=
34 isort_venv=
35 mypy_venv=
36 pylint_venv=
37 ruff_venv=
38
39 upgrade_venvs=
40
41 upgrade_venvs_time_interval_in_seconds=
42
43 vnu_jar_path=
44
45 upgrade_vnu_jar_time_interval_in_seconds=
46
47 use_vnu_for_xhtml=
48
49 npm_lint_directories=
50 npm_lint_directories=
51
```

```

52 xmllint_files_without_DTD=
53 xmllint_files_without_DTD=
54
55 xmllint_use_downloaded_DTDs=
56
57 files_without_license_header=
58 files_without_license_header=

```

3.49 build_and_checks_variables/ruff.toml

```

1  [lint]
2  select = [
3      "ALL",
4      "D211", # blank-line-before-class no...before-class-docstring!
5  ]
6  # ignore = ["D203", "D212", "D404"]
7  ignore = [
8      "C901", # complex-structure AKA give-me-toy-code
9      "D203", # (want-)?incorrect-blank-line-before-class
10     "D205", # missing-blank-line-after-summary So so cute|true ;) XD.
11     "D212", # multi-line-summary-first-line
12     "D404", # docstring-starts-with-this Shame! XD
13
14     # raw-string-in-exception may be useful for a real project
15     # with "dictionnaires" of errors made of constants.
16     "EM101",
17
18     # commented-out-code Of course git log is always faster...
19     # Note that if you're tired or someone else in your team is,
20     # it may catch some commit that lacked some review,
21     # or automated tests: "Last manual test succeeded, ah but when I
22     # debugged at some point I commented a part that was needed in
23     # another case."...
24     "ERA001",
25
26     "N802", # invalid-function-name IMAP, HTML, etc.
27     "PLR0912", # too-many-branches AKA ...
28     "PLR0913", # too-many-arguments AKA ...
29     "PLR0915", # too-many-statements AKA ...
30     # Not enough reading when young makes brain slow to read and
31     # understand lengthy functions.
32     # If the project is finished, you may play with AKA rules.
33 ]
34 [lint.per-file-ignores]
35 "build_and_checks_dependencies/licenses_templates/*.py" = [
36     "INP001" # implicit-namespace-package

```

```

37 ]
38 "IMAP_transfert.exec.py" = [
39     "T201", # print Use log instead in full applications.
40     "TRY003", # raise-vanilla-args
41 ]

```

3.50 build_and_checks_variables/shellcheck.ini

```

1 enable=all
2 check-sourced=true
3 external-sources=true
4 source-path="."
5 source-path="SCRIPTDIR"
6 source-path="./build_and_checks_dependencies"
7 source-path="./git_helpers"

```

3.51 build_and_checks_variables/shellcheck_notes.txt

```

1 A listing of the current suppressed warnings/errors from shellcheck,
2 and also some of the warnings that were suppressed in some previous
3 state of the git repository (in that case, we use X suffix, see SC2162X):
4 - SC1090 : Can't follow non-constant source.
5           Use a directive to specify location
6           # shellcheck source=bla/bli.sh
7           Only remaining cases are in common_build_and_checks
8           when sourcing some Python venv
9           source venv/bin/active
10 - SC1091 : Not following (file not found most of the time).
11           Only remaining cases are in common_build_and_checks
12           when sourcing some Python venv
13           source venv/bin/active
14 - SC1111 : Use of slanted double quotes (valid inside single quotes)
15           False positive, but may catch some problem.
16 - SC2001 : Replace some sed with bash builtin ${a//b/c}
17           False positive when c contains \n.
18 - SC2016 : Expressions don't expand in single quotes,
19           use double quotes for that.
20 - SC2034 : Unused variable
21           False positive for globals that are declared in functions
22           that are not currently called.
23           Somehow it can be used to detect dead code.
24 - SC2059 : Don't use variables in the printf format string.
25           Use printf '..%s..' "$foo".
26           False positive when using a variable to build the format string.
27           Usually because the format string is very long.
28 - SC2086 : Double quote to prevent globbing and word splitting.

```

```

29         False positive when returning integer variable
30         via an indirection like return ${!foo}.
31         See SC2248 below and the corresponding issue on GitHub.
32 - SC2119 : Use foo "$@" if function's $1 should mean script's $1.
33         False positive when passing arguments would yield
34         a wrong result.
35 - SC2120 : foo references arguments, but none are ever passed.
36         False positives when some arguments are meant for debug in CLI.
37 - SC2125 : Brace expansions and globs are literal.
38         False positive when assigning a variable declared with -i.
39         https://github.com/koalaman/shellcheck/issues/914
40 - SC2145 : Argument mixes string and array.
41         False positive when using "$@" line return and pipes.
42         https://github.com/koalaman/shellcheck/issues/3192
43         Example:
44             # shellcheck disable=SC2145
45             all_self_code_lines "$@"\
46             | empty_lines_after_file_name
47 - SC2154 : var is referenced but not assigned.
48         Very useful but false positive when I play with
49         variable variable names.
50 - SC2162X: read without -r will mangle backslashes.
51         False positive when read is used without variable:
52         https://github.com/koalaman/shellcheck/issues/623
53 - SC2248 : Prefer double quoting
54         False positive on returning integer values.
55         https://github.com/koalaman/shellcheck/issues/3405
56 - SC2309 : -eq treats this as a variable.
57         Use = to compare as string (or expand explicitly with $var).
58         Very useful but false positive when I play with
59         variable variable names.
60 - SC2312 : Some command is not invoked separately and thus its return
61         value is masked. Frequent with pipes.
62 - SCNNNNX: Use printf instead of echo.
63         https://github.com/koalaman/shellcheck/issues/3419
64
65 The command to check if there is anything else:
66 grep -r "shellcheck disable" . | grep -v -e '.git' -e "=SC1090$\\"
67 -e "=SC1091$" -e "=SC1090,SC1091$" -e "=SC1111$" -e "=SC2001$\\"
68 -e "=SC2016$" -e "=SC2034$" -e "=SC2059$" -e "=SC2086$" -e "=SC2119$\\"
69 -e "=SC2120$" -e "=SC2125$" -e "=SC2145$" -e "=SC2154$" -e "=SC2248$\\"
70 -e "=SC2309$" -e "=SC2312$" -e "=SC2154,SC2309$"

```

3.52 build_and_checks.exec.sh

```
1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
24 # The file "build_and_checks.exec.sh.tpl" was renamed from
25 # "build_and_checks.sh.tpl" to "build_and_checks.exec.sh.tpl".
26 # The file "build_and_checks.exec.sh" generated from the file
27 # "build_and_checks.sh.tpl" or "build_and_checks.exec.sh.tpl"
28 # was renamed from
29 # "build_and_checks.sh" to "build_and_checks.exec.sh".
30
31 build_and_checks() {
32     # $1=work_directory
33     # Options:
34     #   --check-download=y|keep (=keep to keep the downloaded files)
35     #   --verbose
36     local LFBFL_work_directory="."
37     if [[ -n "$1" ]]; then
38         LFBFL_work_directory="$1"
39     fi
40     readonly LFBFL_work_directory
41
42     local LFBFL_verbose=""
43     if [[ "$*" == *--verbose* ]]; then
44         printf "%s %s\n" "$0" "$*"

```

```

45     LFBFL_verbose="--verbose"
46 fi
47 readonly LFBFL_verbose
48
49 local LFBFL_check_download=""
50 if [[ "$*" == *--check-download=keep* ]]; then
51     LFBFL_check_download="--check-download=keep"
52 elif [[ "$*" == *--check-download=y* ]]; then
53     LFBFL_check_download="--check-download=y"
54 fi
55 readonly LFBFL_check_download
56
57 source ./wget_sha512.lib.sh
58
59 LFBFL_subdir="build_and_checks_dependencies"
60 mkdir --parents "${LFBFL_subdir}/licenses_templates"
61 local LFBFL_variables_directory
62 LFBFL_variables_directory="${LFBFL_work_directory}/"
63 LFBFL_variables_directory+="build_and_checks_variables"
64 readonly LFBFL_variables_directory
65 mkdir --parents -- "${LFBFL_variables_directory}/temp"
66 if [[ ! -f "${LFBFL_variables_directory}/.gitignore" ]]; then
67     printf "temp/\nupgrade_venvs_ts\n" \
68         > "${LFBFL_variables_directory}/.gitignore"
69 fi
70
71 local LFBFL_dependencies_URL
72 LFBFL_dependencies_URL="https://raw.githubusercontent.com/LLyaudet/"
73 LFBFL_dependencies_URL+="DevOrSysAdminScripts/main/${LFBFL_subdir}"
74 readonly LFBFL_dependencies_URL
75
76 declare -r LFBFL_common_file_name="common_build_and_checks.exec.sh"
77 local LFBFL_script_download_URL
78 LFBFL_script_download_URL="${LFBFL_dependencies_URL}/"
79 LFBFL_script_download_URL+="${LFBFL_common_file_name}"
80 readonly LFBFL_script_download_URL
81 declare -r LFBFL_file_path="./${LFBFL_subdir}/${LFBFL_common_file_name}"
82 local LFBFL_correct_sha512
83 LFBFL_correct_sha512='699cba6730b8441798da645fe7d3d65f201979e4e7603'
84 LFBFL_correct_sha512+='ce0fc6721b3d96c708e45ec63f5a0c5ac54338835a31'
85 LFBFL_correct_sha512+='e812e3e4c094bcb3d67d2dac9ab760b45810708'
86 wget_sha512 "${LFBFL_file_path}" \
87     "${LFBFL_script_download_URL}" \
88     "${LFBFL_correct_sha512}" \
89     "${LFBFL_verbose}" \
90     "${LFBFL_check_download}"

```

```

91  chmod +x "${LFBFL_file_path}"
92
93  "${LFBFL_file_path}" "${LFBFL_work_directory}"\
94    "${LFBFL_dependencies_URL}"\
95    "${LFBFL_verbose}"\
96    "${LFBFL_check_download}"
97 }
98
99 if [[ "$*" == *--fixed-point-build* ]]; then
100  printf -- "--fixed-point-build\n"
101  source ../build_and_checks_dependencies/lines_filters.lib.sh"
102  LFBFL_work_directory="."
103  if [[ -n "$1" ]]; then
104    LFBFL_work_directory="$1"
105  fi
106  LFBFL_variables_directory="${LFBFL_work_directory}/"
107  LFBFL_variables_directory+="build_and_checks_variables"
108  LFBFL_data_file_name="${LFBFL_variables_directory}/"
109  LFBFL_data_file_name+="repository_data.txt"
110  LFBFL_repository_name=""
111  grep_variable "${LFBFL_data_file_name}" repository_name\
112    --result-variable-prefix="LFBFL_"\
113    --replace-line-returns-by=""
114  # Touching the 3 following files first let us iterate
115  # upgrade_build_and_checks 2 times instead of 3 to reach
116  # a fixed point.
117  touch -- "${LFBFL_variables_directory}/${LFBFL_repository_name}.tex"
118  touch -- "${LFBFL_work_directory}/${LFBFL_repository_name}.pdf"
119  touch -- "${LFBFL_work_directory}/${LFBFL_repository_name}.html"
120  # The two iterations of build_and_checks needs to complete
121  # during the same minute to have a fixed point.
122  build_and_checks "$@"
123  # build_and_checks "$@" second iteration below
124  # Then calling this script without --fixed-point-build should not
125  # yield any new superficial modifications.
126 fi
127
128 build_and_checks "$@"

```

3.53 COPYING

```

1  GNU GENERAL PUBLIC LICENSE
2  Version 3, 29 June 2007
3
4  Copyright (C) 2007 Free Software Foundation, Inc. <https://fsf.org/>
5  Everyone is permitted to copy and distribute verbatim copies

```

6 of this license document, but changing it is not allowed.

7
8 Preamble

9
10 The GNU General Public License is a free, copyleft license for
11 software and other kinds of works.

12
13 The licenses for most software and other practical works are designed
14 to take away your freedom to share and change the works. By contrast,
15 the GNU General Public License is intended to guarantee your freedom to
16 share and change all versions of a program--to make sure it remains free
17 software for all its users. We, the Free Software Foundation, use the
18 GNU General Public License for most of our software; it applies also to
19 any other work released this way by its authors. You can apply it to
20 your programs, too.

21
22 When we speak of free software, we are referring to freedom, not
23 price. Our General Public Licenses are designed to make sure that you
24 have the freedom to distribute copies of free software (and charge for
25 them if you wish), that you receive source code or can get it if you
26 want it, that you can change the software or use pieces of it in new
27 free programs, and that you know you can do these things.

28
29 To protect your rights, we need to prevent others from denying you
30 these rights or asking you to surrender the rights. Therefore, you have
31 certain responsibilities if you distribute copies of the software, or if
32 you modify it: responsibilities to respect the freedom of others.

33
34 For example, if you distribute copies of such a program, whether
35 gratis or for a fee, you must pass on to the recipients the same
36 freedoms that you received. You must make sure that they, too, receive
37 or can get the source code. And you must show them these terms so they
38 know their rights.

39
40 Developers that use the GNU GPL protect your rights with two steps:
41 (1) assert copyright on the software, and (2) offer you this License
42 giving you legal permission to copy, distribute and/or modify it.

43
44 For the developers' and authors' protection, the GPL clearly explains
45 that there is no warranty for this free software. For both users' and
46 authors' sake, the GPL requires that modified versions be marked as
47 changed, so that their problems will not be attributed erroneously to
48 authors of previous versions.

49
50 Some devices are designed to deny users access to install or run
51 modified versions of the software inside them, although the manufacturer

52 can do so. This is fundamentally incompatible with the aim of
53 protecting users' freedom to change the software. The systematic
54 pattern of such abuse occurs in the area of products for individuals to
55 use, which is precisely where it is most unacceptable. Therefore, we
56 have designed this version of the GPL to prohibit the practice for those
57 products. If such problems arise substantially in other domains, we
58 stand ready to extend this provision to those domains in future versions
59 of the GPL, as needed to protect the freedom of users.

60
61 Finally, every program is threatened constantly by software patents.
62 States should not allow patents to restrict development and use of
63 software on general-purpose computers, but in those that do, we wish to
64 avoid the special danger that patents applied to a free program could
65 make it effectively proprietary. To prevent this, the GPL assures that
66 patents cannot be used to render the program non-free.

67
68 The precise terms and conditions for copying, distribution and
69 modification follow.

70 71 TERMS AND CONDITIONS

72 73 0. Definitions.

74
75 "This License" refers to version 3 of the GNU General Public License.

76
77 "Copyright" also means copyright-like laws that apply to other kinds of
78 works, such as semiconductor masks.

79
80 "The Program" refers to any copyrightable work licensed under this
81 License. Each licensee is addressed as "you". "Licensees" and
82 "recipients" may be individuals or organizations.

83
84 To "modify" a work means to copy from or adapt all or part of the work
85 in a fashion requiring copyright permission, other than the making of an
86 exact copy. The resulting work is called a "modified version" of the
87 earlier work or a work "based on" the earlier work.

88
89 A "covered work" means either the unmodified Program or a work based
90 on the Program.

91
92 To "propagate" a work means to do anything with it that, without
93 permission, would make you directly or secondarily liable for
94 infringement under applicable copyright law, except executing it on a
95 computer or modifying a private copy. Propagation includes copying,
96 distribution (with or without modification), making available to the
97 public, and in some countries other activities as well.

98

99 To "convey" a work means any kind of propagation that enables other
100 parties to make or receive copies. Mere interaction with a user through
101 a computer network, with no transfer of a copy, is not conveying.

102

103 An interactive user interface displays "Appropriate Legal Notices"
104 to the extent that it includes a convenient and prominently visible
105 feature that (1) displays an appropriate copyright notice, and (2)
106 tells the user that there is no warranty for the work (except to the
107 extent that warranties are provided), that licensees may convey the
108 work under this License, and how to view a copy of this License. If
109 the interface presents a list of user commands or options, such as a
110 menu, a prominent item in the list meets this criterion.

111

112 1. Source Code.

113

114 The "source code" for a work means the preferred form of the work
115 for making modifications to it. "Object code" means any non-source
116 form of a work.

117

118 A "Standard Interface" means an interface that either is an official
119 standard defined by a recognized standards body, or, in the case of
120 interfaces specified for a particular programming language, one that
121 is widely used among developers working in that language.

122

123 The "System Libraries" of an executable work include anything, other
124 than the work as a whole, that (a) is included in the normal form of
125 packaging a Major Component, but which is not part of that Major
126 Component, and (b) serves only to enable use of the work with that
127 Major Component, or to implement a Standard Interface for which an
128 implementation is available to the public in source code form. A
129 "Major Component", in this context, means a major essential component
130 (kernel, window system, and so on) of the specific operating system
131 (if any) on which the executable work runs, or a compiler used to
132 produce the work, or an object code interpreter used to run it.

133

134 The "Corresponding Source" for a work in object code form means all
135 the source code needed to generate, install, and (for an executable
136 work) run the object code and to modify the work, including scripts to
137 control those activities. However, it does not include the work's
138 System Libraries, or general-purpose tools or generally available free
139 programs which are used unmodified in performing those activities but
140 which are not part of the work. For example, Corresponding Source
141 includes interface definition files associated with source files for
142 the work, and the source code for shared libraries and dynamically
143 linked subprograms that the work is specifically designed to require,

144 such as by intimate data communication or control flow between those
145 subprograms and other parts of the work.

146
147 The Corresponding Source need not include anything that users
148 can regenerate automatically from other parts of the Corresponding
149 Source.

150
151 The Corresponding Source for a work in source code form is that
152 same work.

153 154 2. Basic Permissions.

155
156 All rights granted under this License are granted for the term of
157 copyright on the Program, and are irrevocable provided the stated
158 conditions are met. This License explicitly affirms your unlimited
159 permission to run the unmodified Program. The output from running a
160 covered work is covered by this License only if the output, given its
161 content, constitutes a covered work. This License acknowledges your
162 rights of fair use or other equivalent, as provided by copyright law.

163
164 You may make, run and propagate covered works that you do not
165 convey, without conditions so long as your license otherwise remains
166 in force. You may convey covered works to others for the sole purpose
167 of having them make modifications exclusively for you, or provide you
168 with facilities for running those works, provided that you comply with
169 the terms of this License in conveying all material for which you do
170 not control copyright. Those thus making or running the covered works
171 for you must do so exclusively on your behalf, under your direction
172 and control, on terms that prohibit them from making any copies of
173 your copyrighted material outside their relationship with you.

174
175 Conveying under any other circumstances is permitted solely under
176 the conditions stated below. Sublicensing is not allowed; section 10
177 makes it unnecessary.

178 179 3. Protecting Users' Legal Rights From Anti-Circumvention Law.

180
181 No covered work shall be deemed part of an effective technological
182 measure under any applicable law fulfilling obligations under article
183 11 of the WIPO copyright treaty adopted on 20 December 1996, or
184 similar laws prohibiting or restricting circumvention of such
185 measures.

186
187 When you convey a covered work, you waive any legal power to forbid
188 circumvention of technological measures to the extent such circumvention
189 is effected by exercising rights under this License with respect to

190 the covered work, and you disclaim any intention to limit operation or
191 modification of the work as a means of enforcing, against the work's
192 users, your or third parties' legal rights to forbid circumvention of
193 technological measures.

194

195 4. Conveying Verbatim Copies.

196

197 You may convey verbatim copies of the Program's source code as you
198 receive it, in any medium, provided that you conspicuously and
199 appropriately publish on each copy an appropriate copyright notice;
200 keep intact all notices stating that this License and any
201 non-permissive terms added in accord with section 7 apply to the code;
202 keep intact all notices of the absence of any warranty; and give all
203 recipients a copy of this License along with the Program.

204

205 You may charge any price or no price for each copy that you convey,
206 and you may offer support or warranty protection for a fee.

207

208 5. Conveying Modified Source Versions.

209

210 You may convey a work based on the Program, or the modifications to
211 produce it from the Program, in the form of source code under the
212 terms of section 4, provided that you also meet all of these conditions:

213

214 a) The work must carry prominent notices stating that you modified
215 it, and giving a relevant date.

216

217 b) The work must carry prominent notices stating that it is
218 released under this License and any conditions added under section
219 7. This requirement modifies the requirement in section 4 to
220 "keep intact all notices".

221

222 c) You must license the entire work, as a whole, under this
223 License to anyone who comes into possession of a copy. This
224 License will therefore apply, along with any applicable section 7
225 additional terms, to the whole of the work, and all its parts,
226 regardless of how they are packaged. This License gives no
227 permission to license the work in any other way, but it does not
228 invalidate such permission if you have separately received it.

229

230 d) If the work has interactive user interfaces, each must display
231 Appropriate Legal Notices; however, if the Program has interactive
232 interfaces that do not display Appropriate Legal Notices, your
233 work need not make them do so.

234

235 A compilation of a covered work with other separate and independent

236 works, which are not by their nature extensions of the covered work,
237 and which are not combined with it such as to form a larger program,
238 in or on a volume of a storage or distribution medium, is called an
239 "aggregate" if the compilation and its resulting copyright are not
240 used to limit the access or legal rights of the compilation's users
241 beyond what the individual works permit. Inclusion of a covered work
242 in an aggregate does not cause this License to apply to the other
243 parts of the aggregate.

244 245 6. Conveying Non-Source Forms.

246
247 You may convey a covered work in object code form under the terms
248 of sections 4 and 5, provided that you also convey the
249 machine-readable Corresponding Source under the terms of this License,
250 in one of these ways:

- 251
252 a) Convey the object code in, or embodied in, a physical product
253 (including a physical distribution medium), accompanied by the
254 Corresponding Source fixed on a durable physical medium
255 customarily used for software interchange.
- 256
257 b) Convey the object code in, or embodied in, a physical product
258 (including a physical distribution medium), accompanied by a
259 written offer, valid for at least three years and valid for as
260 long as you offer spare parts or customer support for that product
261 model, to give anyone who possesses the object code either (1) a
262 copy of the Corresponding Source for all the software in the
263 product that is covered by this License, on a durable physical
264 medium customarily used for software interchange, for a price no
265 more than your reasonable cost of physically performing this
266 conveying of source, or (2) access to copy the
267 Corresponding Source from a network server at no charge.
- 268
269 c) Convey individual copies of the object code with a copy of the
270 written offer to provide the Corresponding Source. This
271 alternative is allowed only occasionally and noncommercially, and
272 only if you received the object code with such an offer, in accord
273 with subsection 6b.
- 274
275 d) Convey the object code by offering access from a designated
276 place (gratis or for a charge), and offer equivalent access to the
277 Corresponding Source in the same way through the same place at no
278 further charge. You need not require recipients to copy the
279 Corresponding Source along with the object code. If the place to
280 copy the object code is a network server, the Corresponding Source
281 may be on a different server (operated by you or a third party)

282 that supports equivalent copying facilities, provided you maintain
283 clear directions next to the object code saying where to find the
284 Corresponding Source. Regardless of what server hosts the
285 Corresponding Source, you remain obligated to ensure that it is
286 available for as long as needed to satisfy these requirements.

287
288 e) Convey the object code using peer-to-peer transmission, provided
289 you inform other peers where the object code and Corresponding
290 Source of the work are being offered to the general public at no
291 charge under subsection 6d.

292
293 A separable portion of the object code, whose source code is excluded
294 from the Corresponding Source as a System Library, need not be
295 included in conveying the object code work.

296
297 A "User Product" is either (1) a "consumer product", which means any
298 tangible personal property which is normally used for personal, family,
299 or household purposes, or (2) anything designed or sold for incorporation
300 into a dwelling. In determining whether a product is a consumer product,
301 doubtful cases shall be resolved in favor of coverage. For a particular
302 product received by a particular user, "normally used" refers to a
303 typical or common use of that class of product, regardless of the status
304 of the particular user or of the way in which the particular user
305 actually uses, or expects or is expected to use, the product. A product
306 is a consumer product regardless of whether the product has substantial
307 commercial, industrial or non-consumer uses, unless such uses represent
308 the only significant mode of use of the product.

309
310 "Installation Information" for a User Product means any methods,
311 procedures, authorization keys, or other information required to install
312 and execute modified versions of a covered work in that User Product from
313 a modified version of its Corresponding Source. The information must
314 suffice to ensure that the continued functioning of the modified object
315 code is in no case prevented or interfered with solely because
316 modification has been made.

317
318 If you convey an object code work under this section in, or with, or
319 specifically for use in, a User Product, and the conveying occurs as
320 part of a transaction in which the right of possession and use of the
321 User Product is transferred to the recipient in perpetuity or for a
322 fixed term (regardless of how the transaction is characterized), the
323 Corresponding Source conveyed under this section must be accompanied
324 by the Installation Information. But this requirement does not apply
325 if neither you nor any third party retains the ability to install
326 modified object code on the User Product (for example, the work has
327 been installed in ROM).

328
329 The requirement to provide Installation Information does not include a
330 requirement to continue to provide support service, warranty, or updates
331 for a work that has been modified or installed by the recipient, or for
332 the User Product in which it has been modified or installed. Access to a
333 network may be denied when the modification itself materially and
334 adversely affects the operation of the network or violates the rules and
335 protocols for communication across the network.

336
337 Corresponding Source conveyed, and Installation Information provided,
338 in accord with this section must be in a format that is publicly
339 documented (and with an implementation available to the public in
340 source code form), and must require no special password or key for
341 unpacking, reading or copying.

342 343 7. Additional Terms.

344
345 "Additional permissions" are terms that supplement the terms of this
346 License by making exceptions from one or more of its conditions.
347 Additional permissions that are applicable to the entire Program shall
348 be treated as though they were included in this License, to the extent
349 that they are valid under applicable law. If additional permissions
350 apply only to part of the Program, that part may be used separately
351 under those permissions, but the entire Program remains governed by
352 this License without regard to the additional permissions.

353
354 When you convey a copy of a covered work, you may at your option
355 remove any additional permissions from that copy, or from any part of
356 it. (Additional permissions may be written to require their own
357 removal in certain cases when you modify the work.) You may place
358 additional permissions on material, added by you to a covered work,
359 for which you have or can give appropriate copyright permission.

360
361 Notwithstanding any other provision of this License, for material you
362 add to a covered work, you may (if authorized by the copyright holders of
363 that material) supplement the terms of this License with terms:

364
365 a) Disclaiming warranty or limiting liability differently from the
366 terms of sections 15 and 16 of this License; or

367
368 b) Requiring preservation of specified reasonable legal notices or
369 author attributions in that material or in the Appropriate Legal
370 Notices displayed by works containing it; or

371
372 c) Prohibiting misrepresentation of the origin of that material, or
373 requiring that modified versions of such material be marked in

374 reasonable ways as different from the original version; or
375
376 d) Limiting the use for publicity purposes of names of licensors or
377 authors of the material; or
378
379 e) Declining to grant rights under trademark law for use of some
380 trade names, trademarks, or service marks; or
381
382 f) Requiring indemnification of licensors and authors of that
383 material by anyone who conveys the material (or modified versions of
384 it) with contractual assumptions of liability to the recipient, for
385 any liability that these contractual assumptions directly impose on
386 those licensors and authors.

387
388 All other non-permissive additional terms are considered "further
389 restrictions" within the meaning of section 10. If the Program as you
390 received it, or any part of it, contains a notice stating that it is
391 governed by this License along with a term that is a further
392 restriction, you may remove that term. If a license document contains
393 a further restriction but permits relicensing or conveying under this
394 License, you may add to a covered work material governed by the terms
395 of that license document, provided that the further restriction does
396 not survive such relicensing or conveying.

397
398 If you add terms to a covered work in accord with this section, you
399 must place, in the relevant source files, a statement of the
400 additional terms that apply to those files, or a notice indicating
401 where to find the applicable terms.

402
403 Additional terms, permissive or non-permissive, may be stated in the
404 form of a separately written license, or stated as exceptions;
405 the above requirements apply either way.

406 407 8. Termination.

408
409 You may not propagate or modify a covered work except as expressly
410 provided under this License. Any attempt otherwise to propagate or
411 modify it is void, and will automatically terminate your rights under
412 this License (including any patent licenses granted under the third
413 paragraph of section 11).

414
415 However, if you cease all violation of this License, then your
416 license from a particular copyright holder is reinstated (a)
417 provisionally, unless and until the copyright holder explicitly and
418 finally terminates your license, and (b) permanently, if the copyright
419 holder fails to notify you of the violation by some reasonable means

420 prior to 60 days after the cessation.

421
422 Moreover, your license from a particular copyright holder is
423 reinstated permanently if the copyright holder notifies you of the
424 violation by some reasonable means, this is the first time you have
425 received notice of violation of this License (for any work) from that
426 copyright holder, and you cure the violation prior to 30 days after
427 your receipt of the notice.

428
429 Termination of your rights under this section does not terminate the
430 licenses of parties who have received copies or rights from you under
431 this License. If your rights have been terminated and not permanently
432 reinstated, you do not qualify to receive new licenses for the same
433 material under section 10.

434 435 9. Acceptance Not Required for Having Copies.

436
437 You are not required to accept this License in order to receive or
438 run a copy of the Program. Ancillary propagation of a covered work
439 occurring solely as a consequence of using peer-to-peer transmission
440 to receive a copy likewise does not require acceptance. However,
441 nothing other than this License grants you permission to propagate or
442 modify any covered work. These actions infringe copyright if you do
443 not accept this License. Therefore, by modifying or propagating a
444 covered work, you indicate your acceptance of this License to do so.

445 446 10. Automatic Licensing of Downstream Recipients.

447
448 Each time you convey a covered work, the recipient automatically
449 receives a license from the original licensors, to run, modify and
450 propagate that work, subject to this License. You are not responsible
451 for enforcing compliance by third parties with this License.

452
453 An "entity transaction" is a transaction transferring control of an
454 organization, or substantially all assets of one, or subdividing an
455 organization, or merging organizations. If propagation of a covered
456 work results from an entity transaction, each party to that
457 transaction who receives a copy of the work also receives whatever
458 licenses to the work the party's predecessor in interest had or could
459 give under the previous paragraph, plus a right to possession of the
460 Corresponding Source of the work from the predecessor in interest, if
461 the predecessor has it or can get it with reasonable efforts.

462
463 You may not impose any further restrictions on the exercise of the
464 rights granted or affirmed under this License. For example, you may
465 not impose a license fee, royalty, or other charge for exercise of

466 rights granted under this License, and you may not initiate litigation
467 (including a cross-claim or counterclaim in a lawsuit) alleging that
468 any patent claim is infringed by making, using, selling, offering for
469 sale, or importing the Program or any portion of it.

470

471 11. Patents.

472

473 A "contributor" is a copyright holder who authorizes use under this
474 License of the Program or a work on which the Program is based. The
475 work thus licensed is called the contributor's "contributor version".

476

477 A contributor's "essential patent claims" are all patent claims
478 owned or controlled by the contributor, whether already acquired or
479 hereafter acquired, that would be infringed by some manner, permitted
480 by this License, of making, using, or selling its contributor version,
481 but do not include claims that would be infringed only as a
482 consequence of further modification of the contributor version. For
483 purposes of this definition, "control" includes the right to grant
484 patent sublicenses in a manner consistent with the requirements of
485 this License.

486

487 Each contributor grants you a non-exclusive, worldwide, royalty-free
488 patent license under the contributor's essential patent claims, to
489 make, use, sell, offer for sale, import and otherwise run, modify and
490 propagate the contents of its contributor version.

491

492 In the following three paragraphs, a "patent license" is any express
493 agreement or commitment, however denominated, not to enforce a patent
494 (such as an express permission to practice a patent or covenant not to
495 sue for patent infringement). To "grant" such a patent license to a
496 party means to make such an agreement or commitment not to enforce a
497 patent against the party.

498

499 If you convey a covered work, knowingly relying on a patent license,
500 and the Corresponding Source of the work is not available for anyone
501 to copy, free of charge and under the terms of this License, through a
502 publicly available network server or other readily accessible means,
503 then you must either (1) cause the Corresponding Source to be so
504 available, or (2) arrange to deprive yourself of the benefit of the
505 patent license for this particular work, or (3) arrange, in a manner
506 consistent with the requirements of this License, to extend the patent
507 license to downstream recipients. "Knowingly relying" means you have
508 actual knowledge that, but for the patent license, your conveying the
509 covered work in a country, or your recipient's use of the covered work
510 in a country, would infringe one or more identifiable patents in that
511 country that you have reason to believe are valid.

512

513 If, pursuant to or in connection with a single transaction or
514 arrangement, you convey, or propagate by procuring conveyance of, a
515 covered work, and grant a patent license to some of the parties
516 receiving the covered work authorizing them to use, propagate, modify
517 or convey a specific copy of the covered work, then the patent license
518 you grant is automatically extended to all recipients of the covered
519 work and works based on it.

520

521 A patent license is "discriminatory" if it does not include within
522 the scope of its coverage, prohibits the exercise of, or is
523 conditioned on the non-exercise of one or more of the rights that are
524 specifically granted under this License. You may not convey a covered
525 work if you are a party to an arrangement with a third party that is
526 in the business of distributing software, under which you make payment
527 to the third party based on the extent of your activity of conveying
528 the work, and under which the third party grants, to any of the
529 parties who would receive the covered work from you, a discriminatory
530 patent license (a) in connection with copies of the covered work
531 conveyed by you (or copies made from those copies), or (b) primarily
532 for and in connection with specific products or compilations that
533 contain the covered work, unless you entered into that arrangement,
534 or that patent license was granted, prior to 28 March 2007.

535

536 Nothing in this License shall be construed as excluding or limiting
537 any implied license or other defenses to infringement that may
538 otherwise be available to you under applicable patent law.

539

540 12. No Surrender of Others' Freedom.

541

542 If conditions are imposed on you (whether by court order, agreement or
543 otherwise) that contradict the conditions of this License, they do not
544 excuse you from the conditions of this License. If you cannot convey a
545 covered work so as to satisfy simultaneously your obligations under this
546 License and any other pertinent obligations, then as a consequence you may
547 not convey it at all. For example, if you agree to terms that obligate you
548 to collect a royalty for further conveying from those to whom you convey
549 the Program, the only way you could satisfy both those terms and this
550 License would be to refrain entirely from conveying the Program.

551

552 13. Use with the GNU Affero General Public License.

553

554 Notwithstanding any other provision of this License, you have
555 permission to link or combine any covered work with a work licensed
556 under version 3 of the GNU Affero General Public License into a single
557 combined work, and to convey the resulting work. The terms of this

558 License will continue to apply to the part which is the covered work,
559 but the special requirements of the GNU Affero General Public License,
560 section 13, concerning interaction through a network will apply to the
561 combination as such.

562

563 14. Revised Versions of this License.

564

565 The Free Software Foundation may publish revised and/or new versions of
566 the GNU General Public License from time to time. Such new versions will
567 be similar in spirit to the present version, but may differ in detail to
568 address new problems or concerns.

569

570 Each version is given a distinguishing version number. If the
571 Program specifies that a certain numbered version of the GNU General
572 Public License "or any later version" applies to it, you have the
573 option of following the terms and conditions either of that numbered
574 version or of any later version published by the Free Software
575 Foundation. If the Program does not specify a version number of the
576 GNU General Public License, you may choose any version ever published
577 by the Free Software Foundation.

578

579 If the Program specifies that a proxy can decide which future
580 versions of the GNU General Public License can be used, that proxy's
581 public statement of acceptance of a version permanently authorizes you
582 to choose that version for the Program.

583

584 Later license versions may give you additional or different
585 permissions. However, no additional obligations are imposed on any
586 author or copyright holder as a result of your choosing to follow a
587 later version.

588

589 15. Disclaimer of Warranty.

590

591 THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY
592 APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT
593 HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY
594 OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO,
595 THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
596 PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM
597 IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF
598 ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

599

600 16. Limitation of Liability.

601

602 IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
603 WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS

604 THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY
605 GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE
606 USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF
607 DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD
608 PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS),
609 EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF
610 SUCH DAMAGES.

611

612 17. Interpretation of Sections 15 and 16.

613

614 If the disclaimer of warranty and limitation of liability provided
615 above cannot be given local legal effect according to their terms,
616 reviewing courts shall apply local law that most closely approximates
617 an absolute waiver of all civil liability in connection with the
618 Program, unless a warranty or assumption of liability accompanies a
619 copy of the Program in return for a fee.

620

621 END OF TERMS AND CONDITIONS

622

623 How to Apply These Terms to Your New Programs

624

625 If you develop a new program, and you want it to be of the greatest
626 possible use to the public, the best way to achieve this is to make it
627 free software which everyone can redistribute and change under these terms.

628

629 To do so, attach the following notices to the program. It is safest
630 to attach them to the start of each source file to most effectively
631 state the exclusion of warranty; and each file should have at least
632 the "copyright" line and a pointer to where the full notice is found.

633

634 <one line to give the program's name and a brief idea of what it does.>
635 Copyright (C) <year> <name of author>

636

637 This program is free software: you can redistribute it and/or modify
638 it under the terms of the GNU General Public License as published by
639 the Free Software Foundation, either version 3 of the License, or
640 (at your option) any later version.

641

642 This program is distributed in the hope that it will be useful,
643 but WITHOUT ANY WARRANTY; without even the implied warranty of
644 MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
645 GNU General Public License for more details.

646

647 You should have received a copy of the GNU General Public License
648 along with this program. If not, see <<https://www.gnu.org/licenses/>>.

649

650 Also add information on how to contact you by electronic and paper mail.
651
652 If the program does terminal interaction, make it output a short
653 notice like this when it starts in an interactive mode:
654
655 <program> Copyright (C) <year> <name of author>
656 This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
657 This is free software, and you are welcome to redistribute it
658 under certain conditions; type `show c' for details.
659
660 The hypothetical commands `show w' and `show c' should show the appropriate
661 parts of the General Public License. Of course, your program's commands
662 might be different; for a GUI interface, you would use an "about box".
663
664 You should also get your employer (if you work as a programmer) or school,
665 if any, to sign a "copyright disclaimer" for the program, if necessary.
666 For more information on this, and how to apply and follow the GNU GPL, see
667 <<https://www.gnu.org/licenses/>>.
668
669 The GNU General Public License does not permit incorporating your program
670 into proprietary programs. If your program is a subroutine library, you
671 may consider it more useful to permit linking proprietary applications with
672 the library. If this is what you want to do, use the GNU Lesser General
673 Public License instead of this License. But first, please read
674 <<https://www.gnu.org/licenses/why-not-lgpl.html>>.

3.54 COPYING.LESSER

1 GNU LESSER GENERAL PUBLIC LICENSE
2 Version 3, 29 June 2007
3
4 Copyright (C) 2007 Free Software Foundation, Inc. <<https://fsf.org/>>
5 Everyone is permitted to copy and distribute verbatim copies
6 of this license document, but changing it is not allowed.
7
8
9 This version of the GNU Lesser General Public License incorporates
10 the terms and conditions of version 3 of the GNU General Public
11 License, supplemented by the additional permissions listed below.
12
13 0. Additional Definitions.
14
15 As used herein, "this License" refers to version 3 of the GNU Lesser
16 General Public License, and the "GNU GPL" refers to version 3 of the GNU
17 General Public License.
18

19 "The Library" refers to a covered work governed by this License,
20 other than an Application or a Combined Work as defined below.

21
22 An "Application" is any work that makes use of an interface provided
23 by the Library, but which is not otherwise based on the Library.
24 Defining a subclass of a class defined by the Library is deemed a mode
25 of using an interface provided by the Library.

26
27 A "Combined Work" is a work produced by combining or linking an
28 Application with the Library. The particular version of the Library
29 with which the Combined Work was made is also called the "Linked
30 Version".

31
32 The "Minimal Corresponding Source" for a Combined Work means the
33 Corresponding Source for the Combined Work, excluding any source code
34 for portions of the Combined Work that, considered in isolation, are
35 based on the Application, and not on the Linked Version.

36
37 The "Corresponding Application Code" for a Combined Work means the
38 object code and/or source code for the Application, including any data
39 and utility programs needed for reproducing the Combined Work from the
40 Application, but excluding the System Libraries of the Combined Work.

41
42 1. Exception to Section 3 of the GNU GPL.

43
44 You may convey a covered work under sections 3 and 4 of this License
45 without being bound by section 3 of the GNU GPL.

46
47 2. Conveying Modified Versions.

48
49 If you modify a copy of the Library, and, in your modifications, a
50 facility refers to a function or data to be supplied by an Application
51 that uses the facility (other than as an argument passed when the
52 facility is invoked), then you may convey a copy of the modified
53 version:

54
55 a) under this License, provided that you make a good faith effort to
56 ensure that, in the event an Application does not supply the
57 function or data, the facility still operates, and performs
58 whatever part of its purpose remains meaningful, or

59
60 b) under the GNU GPL, with none of the additional permissions of
61 this License applicable to that copy.

62
63 3. Object Code Incorporating Material from Library Header Files.

64

65 The object code form of an Application may incorporate material from
66 a header file that is part of the Library. You may convey such object
67 code under terms of your choice, provided that, if the incorporated
68 material is not limited to numerical parameters, data structure
69 layouts and accessors, or small macros, inline functions and templates
70 (ten or fewer lines in length), you do both of the following:

71

- 72 a) Give prominent notice with each copy of the object code that the
- 73 Library is used in it and that the Library and its use are
- 74 covered by this License.
- 75
- 76 b) Accompany the object code with a copy of the GNU GPL and this license
- 77 document.
- 78

79 4. Combined Works.

80

81 You may convey a Combined Work under terms of your choice that,
82 taken together, effectively do not restrict modification of the
83 portions of the Library contained in the Combined Work and reverse
84 engineering for debugging such modifications, if you also do each of
85 the following:

86

- 87 a) Give prominent notice with each copy of the Combined Work that
- 88 the Library is used in it and that the Library and its use are
- 89 covered by this License.
- 90
- 91 b) Accompany the Combined Work with a copy of the GNU GPL and this license
- 92 document.
- 93
- 94 c) For a Combined Work that displays copyright notices during
- 95 execution, include the copyright notice for the Library among
- 96 these notices, as well as a reference directing the user to the
- 97 copies of the GNU GPL and this license document.
- 98
- 99 d) Do one of the following:

100

- 101 0) Convey the Minimal Corresponding Source under the terms of this
- 102 License, and the Corresponding Application Code in a form
- 103 suitable for, and under terms that permit, the user to
- 104 recombine or relink the Application with a modified version of
- 105 the Linked Version to produce a modified Combined Work, in the
- 106 manner specified by section 6 of the GNU GPL for conveying
- 107 Corresponding Source.
- 108
- 109 1) Use a suitable shared library mechanism for linking with the
- 110 Library. A suitable mechanism is one that (a) uses at run time

111 a copy of the Library already present on the user's computer
112 system, and (b) will operate properly with a modified version
113 of the Library that is interface-compatible with the Linked
114 Version.

115

116 e) Provide Installation Information, but only if you would otherwise
117 be required to provide such information under section 6 of the
118 GNU GPL, and only to the extent that such information is
119 necessary to install and execute a modified version of the
120 Combined Work produced by recombining or relinking the
121 Application with a modified version of the Linked Version. (If
122 you use option 4d0, the Installation Information must accompany
123 the Minimal Corresponding Source and Corresponding Application
124 Code. If you use option 4d1, you must provide the Installation
125 Information in the manner specified by section 6 of the GNU GPL
126 for conveying Corresponding Source.)

127

128 5. Combined Libraries.

129

130 You may place library facilities that are a work based on the
131 Library side by side in a single library together with other library
132 facilities that are not Applications and are not covered by this
133 License, and convey such a combined library under terms of your
134 choice, if you do both of the following:

135

136 a) Accompany the combined library with a copy of the same work based
137 on the Library, uncombined with any other library facilities,
138 conveyed under the terms of this License.

139

140 b) Give prominent notice with the combined library that part of it
141 is a work based on the Library, and explaining where to find the
142 accompanying uncombined form of the same work.

143

144 6. Revised Versions of the GNU Lesser General Public License.

145

146 The Free Software Foundation may publish revised and/or new versions
147 of the GNU Lesser General Public License from time to time. Such new
148 versions will be similar in spirit to the present version, but may
149 differ in detail to address new problems or concerns.

150

151 Each version is given a distinguishing version number. If the
152 Library as you received it specifies that a certain numbered version
153 of the GNU Lesser General Public License "or any later version"
154 applies to it, you have the option of following the terms and
155 conditions either of that published version or of any later version
156 published by the Free Software Foundation. If the Library as you

```

157 received it does not specify a version number of the GNU Lesser
158 General Public License, you may choose any version of the GNU Lesser
159 General Public License ever published by the Free Software Foundation.
160
161 If the Library as you received it specifies that a proxy can decide
162 whether future versions of the GNU Lesser General Public License shall
163 apply, that proxy's public statement of acceptance of any version is
164 permanent authorization for you to choose that version for the
165 Library.

```

3.55 git_helpers/git_checks.lib.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023–2026 Laurent Frédéric Bernard François Lyaudet
24 # 2024-05-31T01:57+02:00: This file was renamed from
25 # "git_checks.lib.sh"
26 # to
27 # "git_checks.lib.sh".
28 # 2024-05-31T01:57+02:00: This file was moved from
29 # "."
30 # to
31 # "./git_helpers".
32 # 2024-05-31T01:49+02:00: This file was renamed from
33 # "git_checks.lib.sh"
34 # to

```

```

35 # "git_checks.lib.sh".
36 # 2024-05-31T01:49+02:00: This file was moved from
37 # "."
38 # to
39 # "./git_helpers".
40 # This file was renamed from "git_checks.sh" to "git_checks.lib.sh".
41
42 check_files() {
43     # Checks used on Django projects.
44     # Use `git commit --no-verify` after check.
45     declare -r LFBFL_send_summary_1="ATTENTION : models modifiés"
46     declare -r LFBFL_send_body_1="Vérifiez si besoin de migrations."
47     local LFBFL_send_body_2="Pensez aussi aux contraintes d'unicités"
48     LFBFL_send_body_2+=" dès la création du modèle."
49     readonly LFBFL_send_body_2
50     declare -r LFBFL_send_summary_2="ATTENTION : serializers modifiés"
51     declare -r LFBFL_send_body_3=\
52 "Les nouveaux preloadings sont interdits : -> #Prefetch()."
53     declare -i LFBFL_i_error=0
54     git diff --cached --name-only\
55     > /tmp/DOSAS_django_git_check1.temp
56     if grep models /tmp/DOSAS_django_git_check1.temp;
57     then
58         notify-send "${LFBFL_send_summary_1}" "${LFBFL_send_body_1}"
59         notify-send "${LFBFL_send_summary_1}" "${LFBFL_send_body_2}"
60         LFBFL_i_error=1
61     fi
62     if grep serializer /tmp/DOSAS_django_git_check1.temp;
63     then
64         notify-send "${LFBFL_send_summary_2}" "${LFBFL_send_body_3}"
65         LFBFL_i_error=1
66     fi
67     rm /tmp/DOSAS_django_git_check1.temp
68     # shellcheck disable=SC2248
69     return ${LFBFL_i_error}
70 }
71
72
73 check_no_abusive_trailing_comma() {
74     # Useful for Python code, although it regularly yields
75     # false positives in Python code
76     # (but it is easy to distinguish by hand).
77     # Use `git commit --no-verify` after check.
78     declare -r LFBFL_send_summary_1="ATTENTION"
79     local LFBFL_send_body_1="Il semblerait que vous affectiez un tuple"
80     LFBFL_send_body_1+=" au lieu d'une autre valeur dans une variable."

```

```

81     readonly LFBFL_send_body_1
82     declare -i LFBFL_i_error=0
83     git diff --cached\
84         > /tmp/DOSAS_django_git_check2.temp
85     if grep --perl-regexp ' = .*,\s*$' /tmp/DOSAS_django_git_check2.temp;
86     then
87         notify-send "${LFBFL_send_summary_1}" "${LFBFL_send_body_1}"
88         LFBFL_i_error=1
89     fi
90     rm /tmp/DOSAS_django_git_check2.temp
91     # shellcheck disable=SC2248
92     return ${LFBFL_i_error}
93 }
94
95
96 check_black_code_formatting(){
97     # attention ça ne marche que sur les fichiers "stagés" avec git add
98     declare -r LFBFL_s_files_paths=$(
99         git diff --cached --name-only\
100         | grep '\.py$'
101     )
102     printf "%s\n" "${LFBFL_s_files_paths}"
103     declare -a LFBFL_arr_files_paths
104     mapfile -t LFBFL_arr_files_paths <<< "${LFBFL_s_files_paths}"
105     readonly LFBFL_arr_files_paths
106     declare -i LFBFL_i_error=0
107     local LFBFL_file_path
108     for LFBFL_file_path in "${LFBFL_arr_files_paths[@]}"; do
109         printf "Black will check formatting on file %s.\n" "${LFBFL_file_path}"
110         if ! black --check --diff -- "${LFBFL_file_path}";
111         then
112             LFBFL_i_error=1
113         fi
114     done
115     # shellcheck disable=SC2248
116     return ${LFBFL_i_error}
117 }

```

3.56 git_helpers/post-commit

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it under the terms
6  # of the GNU General Public License

```

```

7 # as published by the Free Software Foundation,
8 # either version 3 of the License,
9 # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed in the hope
12 # that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023-2024 Laurent Frédéric Bernard François Lyaudet
24 # 2024-05-31T01:49+02:00: This file was renamed from
25 # "post-commit"
26 # to
27 # "post-commit".
28 # 2024-05-31T01:49+02:00: This file was moved from
29 # "."
30 # to
31 # "./git_helpers".
32
33 LFBFL_some_directory="../DevOrSysAdminScripts"
34 declare -i LFBFL_i_pushd_result3
35 pushd "${LFBFL_some_directory}" || {
36     LFBFL_i_pushd_result3=$?
37     printf "post-commit pushd %s no such directory\n"\
38         "${LFBFL_some_directory}"
39     # shellcheck disable=SC2248
40     exit ${LFBFL_i_pushd_result3}
41 }
42 # shellcheck source=post_commit_renaming_comment.lib.sh
43 source "../git_helpers/post_commit_renaming_comment.lib.sh"
44 # shellcheck source=lines_filters.lib.sh
45 source "../build_and_checks_dependencies/lines_filters.lib.sh"
46 declare -i LFBFL_i_popd_result3
47 popd || {
48     LFBFL_i_popd_result3=$?
49     printf "post-commit no popd\n"
50     # shellcheck disable=SC2248
51     exit ${LFBFL_i_popd_result3}
52 }

```

```

53
54 LFBFL_data_file_name="build_and_checks_variables/repository_data.txt"
55 LFBFL_max_comment_line_length=""
56 if [[ -f "${LFBFL_data_file_name}" ]]; then
57     LFBFL_max_line_length=""
58     grep_variable "${LFBFL_data_file_name}" "max_line_length"\
59     --result-variable-prefix="LFBFL_"
60     LFBFL_max_comment_line_length="--max-comment-line-length="
61     LFBFL_max_comment_line_length+="${LFBFL_max_line_length}"
62 fi
63
64 commit_a_file_renamed_comment --verbose --log-directory-change\
65     "${LFBFL_max_comment_line_length}"
66 exit 0

```

3.57 git_helpers/post_commit_renaming_comment.lib.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023–2026 Laurent Frédéric Bernard François Lyaudet
24 # 2024-05-31T01:49+02:00: This file was renamed from
25 # "post_commit_renaming_comment.lib.sh"
26 # to
27 # "post_commit_renaming_comment.lib.sh".
28 # 2024-05-31T01:49+02:00: This file was moved from
29 # "."

```

```

30 # to
31 # "./git_helpers".
32 # This file was renamed from "post_commit_renaming_comment"
33 # to "post_commit_renaming_comment.lib.sh".
34 # (Before first commit it seems. But I had the old name in listing.)
35
36 LFBFL_this_file_path=$(realpath -- "${BASH_SOURCE[0]}")
37 LFBFL_this_file_directory=$(dirname -- "${LFBFL_this_file_path}")
38 LFBFL_some_directory="${LFBFL_this_file_directory}/../"
39 declare -i LFBFL_i_pushd_result2
40 pushd -- "${LFBFL_some_directory}" || {
41     LFBFL_i_pushd_result2=$?
42     printf\
43         "post_commit_renaming_comment.lib.sh pushd %s no such directory\n"\
44         "${LFBFL_some_directory}"
45     # shellcheck disable=SC2248
46     exit ${LFBFL_i_pushd_result2}
47 }
48 # shellcheck source=common_options.lib.sh
49 source "../build_and_checks_dependencies/common_options.lib.sh"
50 # shellcheck source=strings_functions.lib.sh
51 source "../build_and_checks_dependencies/strings_functions.lib.sh"
52 declare -i LFBFL_i_popd_result2
53 popd || {
54     LFBFL_i_popd_result2=$?
55     printf "post_commit_renaming_comment.lib.sh no popd\n"
56     # shellcheck disable=SC2248
57     exit ${LFBFL_i_popd_result2}
58 }
59
60 # Never forget that the worse security is the illusion of security
61 # (Kevin Mitnick). So, do not expect to have an accurate trackability
62 # of code history just because you use this post-commit hook or
63 # something else more evolved. This is useful but not a guarantee.
64 # This function will only handle the files that were only renamed in the
65 # preceding commit.
66 # It assumes that `diff` is the current default difference utility
67 # parametered with `git`. This point could be enhanced.
68 commit_a_file_renamed_comment() {
69     # Options:
70     # --verbose
71     # --log-directory-change
72     # --max-comment-line-length
73     declare -i LFBFL_i_verbose=0
74     get_verbose_option "$@"
75     declare -i LFBFL_i_log_directory_change

```

```

76 get_some_flag LFBFL_i_log_directory_change --log-directory-change 1 "$@"
77 declare -i LFBFL_i_max_comment_line_length
78 get_some_option LFBFL_i_max_comment_line_length\
79     --max-comment-line-length 70 70 1 "$@"
80 if [[ LFBFL_i_verbose -eq 1 ]]; then
81     LFBFL_s_format="LFBFL_i_log_directory_change: %s\n"
82     LFBFL_s_format+="LFBFL_i_max_comment_line_length: %s\n"
83     # shellcheck disable=SC2059,SC2248
84     printf "${LFBFL_s_format}"\
85         "${LFBFL_i_log_directory_change}"\
86         "${LFBFL_i_max_comment_line_length}"
87 fi
88 if [[ LFBFL_i_max_comment_line_length -lt 10 ]]; then
89     declare -r LFBFL_send_summary="Max comment line length below 10."
90     notify-send "${LFBFL_send_summary}" "${LFBFL_send_summary}"
91     if [[ LFBFL_i_verbose -eq 1 ]]; then
92         printf "Max comment line length below 10, aborting.\n"
93     fi
94     return
95 fi
96 local LFBFL_s_format
97 #-----
98
99 enhanced_set_shell_option pipefail\
100     && trap 'enhanced_unset_shell_option pipefail' RETURN
101
102 declare -r LFBFL_renaming_lines=$(
103     git log --max-count=1 --patch\
104     | grep --after-context=1 '^diff --git'
105 )
106 if [[ LFBFL_i_verbose -eq 1 ]]; then
107     printf "LFBFL_renaming_lines: %s\n" "${LFBFL_renaming_lines}"
108 fi
109
110 declare -a LFBFL_renaming_lines_array
111 mapfile -t LFBFL_renaming_lines_array <<< "${LFBFL_renaming_lines}"
112 readonly LFBFL_renaming_lines_array
113
114 declare -r LFBFL_timestamp=$(date --iso-8601="minute")
115 if [[ LFBFL_i_verbose -eq 1 ]]; then
116     printf "LFBFL_timestamp: %s\n" "${LFBFL_timestamp}"
117 fi
118 local LFBFL_split_score_command1
119 declare -i LFBFL_i_split_score_command_properties1
120 # shellcheck disable=SC2248
121 get_split_score_simple 1 "${LFBFL_i_max_comment_line_length}" _

```



```

122 LFBFL_split_score_command1="{get_split_score_result}"
123 LFBFL_i_split_score_command_properties1={i_get_split_score_result2}
124 readonly LFBFL_split_score_command1
125 readonly LFBFL_i_split_score_command_properties1
126 local LFBFL_split_score_command2
127 declare -i LFBFL_i_split_score_command_properties2
128 # shellcheck disable=SC2248
129 get_split_score_simple 1 ${LFBFL_i_max_comment_line_length} /
130 LFBFL_split_score_command2="{get_split_score_result}"
131 LFBFL_i_split_score_command_properties2={i_get_split_score_result2}
132 readonly LFBFL_split_score_command2
133 readonly LFBFL_i_split_score_command_properties2
134 declare -i LFBFL_i_renaming_happened=0
135 declare -i LFBFL_i
136 declare -i LFBFL_j
137 declare -r LFBFL_special_file_name="files_names_listing.txt"
138 local LFBFL_diff_line
139 local LFBFL_similarity_line
140 local LFBFL_old_file_path
141 local LFBFL_old_file_name
142 local LFBFL_old_file_directory
143 local LFBFL_new_file_path
144 local LFBFL_new_file_name
145 local LFBFL_new_file_directory
146 local LFBFL_useful_file_name
147 local LFBFL_extension
148 local LFBFL_comment_prefix
149 local LFBFL_comment_prefix2
150 local LFBFL_old_file_name2
151 local LFBFL_old_file_directory2
152 local LFBFL_new_file_name2
153 local LFBFL_new_file_directory2
154 local LFBFL_new_comment
155 declare -i LFBFL_i_copyright_line_number
156 declare -r LFBFL_send_summary_2="ATTENTION: No line with copyright"
157 declare -i LFBFL_i_line_count
158 declare -i LFBFL_i_lines_after
159 local LFBFL_temp_file_path
160 for ((LFBFL_i = 0; LFBFL_i < ${#LFBFL_renaming_lines_array[@]};)); do
161     LFBFL_diff_line="{LFBFL_renaming_lines_array[${LFBFL_i}]}"
162     LFBFL_i=$((LFBFL_i + 1))
163     LFBFL_similarity_line="{LFBFL_renaming_lines_array[${LFBFL_i}]}"
164     LFBFL_i=$((LFBFL_i + 1))
165     # We need to increment 3 times since grep adds "--" lines between.
166     LFBFL_i=$((LFBFL_i + 1))
167     if [[ LFBFL_i_verbose -eq 1 ]]; then

```

```

168     printf "LFBFL_diff_line: %s\nLFBFL_similarity_line: %s\n"\
169         "${LFBFL_diff_line}"\
170         "${LFBFL_similarity_line}"
171 fi
172 if [[ "${LFBFL_similarity_line:17:4}" != "100%" ]]; then
173     continue
174 fi
175
176 # Extract old file name from diff line. -----
177 LFBFL_old_file_path=$(
178     printf "%s" "${LFBFL_diff_line}"\
179     | cut --delimiter=' ' --fields=3
180 )
181 # It starts by "a/".
182 LFBFL_old_file_path=".${LFBFL_old_file_path:1}"
183 LFBFL_old_file_name=$(basename -- "${LFBFL_old_file_path}")
184 LFBFL_old_file_directory=$(dirname -- "${LFBFL_old_file_path}")
185 # Extract new file name from diff line. -----
186 LFBFL_new_file_path=$(
187     printf "%s" "${LFBFL_diff_line}"\
188     | cut --delimiter=' ' --fields=4
189 )
190 # It starts by "b/".
191 LFBFL_new_file_path=".${LFBFL_new_file_path:1}"
192 LFBFL_new_file_name=$(basename -- "${LFBFL_new_file_path}")
193 LFBFL_new_file_directory=$(dirname -- "${LFBFL_new_file_path}")
194 if [[ LFBFL_i_verbose -eq 1 ]]; then
195     LFBFL_s_format="LFBFL_old_file_path: %s\n"
196     LFBFL_s_format+="LFBFL_old_file_name: %s\n"
197     LFBFL_s_format+="LFBFL_old_file_directory: %s\n"
198     LFBFL_s_format+="LFBFL_new_file_path: %s\n"
199     LFBFL_s_format+="LFBFL_new_file_name: %s\n"
200     LFBFL_s_format+="LFBFL_new_file_directory: %s\n"
201     # shellcheck disable=SC2059
202     printf "${LFBFL_s_format}"\
203         "${LFBFL_old_file_path}"\
204         "${LFBFL_old_file_name}"\
205         "${LFBFL_old_file_directory}"\
206         "${LFBFL_new_file_path}"\
207         "${LFBFL_new_file_name}"\
208         "${LFBFL_new_file_directory}"
209 fi
210 # Extract "LFBFL_extension" with smart guessing for .tpl -----
211 # and set prefix for line with ©Copyright. -----
212 LFBFL_useful_file_name="${LFBFL_new_file_name}"
213 LFBFL_extension="${LFBFL_useful_file_name##*."}

```

```

214 if [[ LFBFL_i_verbose -eq 1 ]]; then
215     printf "LFBFL_useful_file_name: %s\nLFBFL_extension: %s\n" \
216         "${LFBFL_useful_file_name}" \
217         "${LFBFL_extension}"
218 fi
219 for ((LFBFL_j = 0; LFBFL_j < 3; ++LFBFL_j)); do
220     if [[ "${LFBFL_extension}" != "tpl" ]]; then
221         break
222     fi
223     LFBFL_useful_file_name="${LFBFL_useful_file_name:0:-4}"
224     LFBFL_extension="${LFBFL_useful_file_name##*}."
225     if [[ LFBFL_i_verbose -eq 1 ]]; then
226         printf "LFBFL_useful_file_name: %s\nLFBFL_extension: %s\n" \
227             "${LFBFL_useful_file_name}" \
228             "${LFBFL_extension}"
229     fi
230 done
231 LFBFL_comment_prefix=""
232 if [[
233     "${LFBFL_extension}" == "sh"
234     || "${LFBFL_extension}" == "toml"
235     || "${LFBFL_extension}" == "yaml"
236 ]]; then
237     LFBFL_comment_prefix="# "
238 fi
239 if [[ "${LFBFL_extension}" == "sql" ]]; then
240     LFBFL_comment_prefix="-- "
241 fi
242 if [[ "${LFBFL_extension}" == "tex" ]]; then
243     LFBFL_comment_prefix="% "
244 fi
245 if [[
246     "${LFBFL_useful_file_name}" == "${LFBFL_special_file_name}"
247     || "${LFBFL_extension}" == "rs"
248     || "${LFBFL_extension}" == "rlib"
249 ]]; then
250     LFBFL_comment_prefix="// "
251 fi
252 if [[ LFBFL_i_verbose -eq 1 ]]; then
253     printf "LFBFL_comment_prefix: %s\n" "${LFBFL_comment_prefix}"
254 fi
255 #-----
256 # Split if necessary old_file_name, new_file_name, etc. to have
257 # comment lines below max_comment_line_length.
258 LFBFL_comment_prefix2="${LFBFL_comment_prefix}"' "'

```

```

260 # -----
261 LFBFL_old_file_name2="${LFBFL_comment_prefix2}"
262 LFBFL_old_file_name2+="${LFBFL_old_file_name}"
263 # shellcheck disable=SC2248
264 repeated_split_last_line "${LFBFL_old_file_name2}"\
265     "${LFBFL_comment_prefix2}"\
266     "${LFBFL_i_max_comment_line_length}"\
267     '""\
268     "${LFBFL_split_score_command1}"\
269     "${LFBFL_i_split_score_command_properties1}"
270 LFBFL_old_file_name2="${repeated_split_last_line_result}"
271 # -----
272 LFBFL_old_file_directory2="${LFBFL_comment_prefix2}"
273 LFBFL_old_file_directory2+="${LFBFL_old_file_directory}"
274 # shellcheck disable=SC2248
275 repeated_split_last_line "${LFBFL_old_file_directory2}"\
276     "${LFBFL_comment_prefix2}"\
277     "${LFBFL_i_max_comment_line_length}"\
278     '""\
279     "${LFBFL_split_score_command2}"\
280     "${LFBFL_i_split_score_command_properties2}"
281 LFBFL_old_file_directory2="${repeated_split_last_line_result}"
282 # -----
283 LFBFL_new_file_name2="${LFBFL_comment_prefix2}"
284 LFBFL_new_file_name2+="${LFBFL_new_file_name}"
285 # shellcheck disable=SC2248
286 repeated_split_last_line "${LFBFL_new_file_name2}"\
287     "${LFBFL_comment_prefix2}"\
288     "${LFBFL_i_max_comment_line_length}"\
289     '""\
290     "${LFBFL_split_score_command1}"\
291     "${LFBFL_i_split_score_command_properties1}"
292 LFBFL_new_file_name2="${repeated_split_last_line_result}"
293 # -----
294 LFBFL_new_file_directory2="${LFBFL_comment_prefix2}"
295 LFBFL_new_file_directory2+="${LFBFL_new_file_directory}"
296 # shellcheck disable=SC2248
297 repeated_split_last_line "${LFBFL_new_file_directory2}"\
298     "${LFBFL_comment_prefix2}"\
299     "${LFBFL_i_max_comment_line_length}"\
300     '""\
301     "${LFBFL_split_score_command2}"\
302     "${LFBFL_i_split_score_command_properties2}"
303 LFBFL_new_file_directory2="${repeated_split_last_line_result}"
304 # Create new comments strings. -----
305 LFBFL_new_comment=""

```

```

306 if [[ "${LFBFL_new_file_name}" != "${LFBFL_old_file_name}" ]]; then
307     LFBFL_new_comment="${LFBFL_comment_prefix}"
308     LFBFL_new_comment+="${LFBFL_timestamp}"
309     LFBFL_new_comment+=": This file was renamed from"
310     LFBFL_new_comment+=$'\n'
311     LFBFL_new_comment+="${LFBFL_old_file_name2}"' "'
312     LFBFL_new_comment+=$'\n'
313     LFBFL_new_comment+="${LFBFL_comment_prefix}to"
314     LFBFL_new_comment+=$'\n'
315     LFBFL_new_comment+="${LFBFL_new_file_name2}"' ". '
316 fi
317 if [[
318     LFBFL_i_log_directory_change -eq 1
319     && "${LFBFL_new_file_directory}" != "${LFBFL_old_file_directory}"
320 ]];
321 then
322     if [[ "${LFBFL_new_file_name}" != "${LFBFL_old_file_name}" ]]; then
323         LFBFL_new_comment+=$'\n'
324         fi
325         LFBFL_new_comment+="${LFBFL_comment_prefix}"
326         LFBFL_new_comment+="${LFBFL_timestamp}"
327         LFBFL_new_comment+=": This file was moved from"
328         LFBFL_new_comment+=$'\n'
329         LFBFL_new_comment+="${LFBFL_old_file_directory2}"' "'
330         LFBFL_new_comment+=$'\n'
331         LFBFL_new_comment+="${LFBFL_comment_prefix}to"
332         LFBFL_new_comment+=$'\n'
333         LFBFL_new_comment+="${LFBFL_new_file_directory2}"' ". '
334     fi
335     if [[ LFBFL_i_verbose -eq 1 ]]; then
336         printf "LFBFL_new_comment: %s\n" "${LFBFL_new_comment}"
337     fi
338     # Find line with ©Copyright. -----
339     LFBFL_i_copyright_line_number=$(
340         grep --line-number -- '©Copyright' "${LFBFL_new_file_path}"\
341         | head --lines=1\
342         | cut --delimiter=':' --fields=1
343     )
344     if [[ LFBFL_i_verbose -eq 1 ]]; then
345         printf "LFBFL_i_copyright_line_number: %s\n"\
346             "${LFBFL_i_copyright_line_number}"
347     fi
348     if [[ LFBFL_i_copyright_line_number -eq 0 ]]; then
349         notify-send "${LFBFL_send_summary_2}"\
350             "${LFBFL_send_summary_2} for: ${LFBFL_new_comment}"
351         if [[ LFBFL_i_verbose -eq 1 ]]; then

```

```

352     printf "No copyright line. Skipping file.\n"
353     fi
354     continue
355 fi
356 # Get total number of lines. -----
357 LFBFL_i_line_count=$(
358     wc --lines\
359     < "${LFBFL_new_file_path}"
360 )
361 if [[ LFBFL_i_verbose -eq 1 ]]; then
362     printf "LFBFL_i_line_count: %s\n" "${LFBFL_i_line_count}"
363 fi
364 # Compute number of lines after. -----
365 LFBFL_i_lines_after=$((
366     LFBFL_i_line_count - LFBFL_i_copyright_line_number
367 ))
368 if [[ LFBFL_i_verbose -eq 1 ]]; then
369     printf "LFBFL_i_lines_after: %s\n" "${LFBFL_i_lines_after}"
370 fi
371 # Update file. -----
372 LFBFL_temp_file_path="${LFBFL_new_file_path}.LFBFL.temp"
373 {
374     head --lines="${LFBFL_i_copyright_line_number}"\
375         -- "${LFBFL_new_file_path}"
376     printf "%s\n" "${LFBFL_new_comment}"
377     tail --lines="${LFBFL_i_lines_after}" -- "${LFBFL_new_file_path}"
378 } >> "${LFBFL_temp_file_path}"
379 mv -- "${LFBFL_temp_file_path}" "${LFBFL_new_file_path}"
380 # Add file to stage. -----
381 git add -- "${LFBFL_new_file_path}"
382 LFBFL_i_renaming_happened=1
383 done
384 readonly LFBFL_i_renaming_happened
385 if [[ LFBFL_i_renaming_happened -eq 1 ]]; then
386     # Commit -----
387     local LFBFL_message="commit_a_file_renamed_comment()"
388     LFBFL_message+=" post-commit hook, ${LFBFL_timestamp}."
389     readonly LFBFL_message
390     printf "Commit message:\n%s\n" "${LFBFL_message}"
391     git commit --no-verify --message="${LFBFL_message}"
392 fi
393 }

```

3.58 git_helpers/pre-commit

```
1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it under the terms
6  # of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed in the hope
12 # that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023-2024 Laurent Frédéric Bernard François Lyaudet
24 # 2024-05-31T01:57+02:00: This file was renamed from
25 # "pre-commit"
26 # to
27 # "pre-commit".
28 # 2024-05-31T01:57+02:00: This file was moved from
29 # "."
30 # to
31 # "./git_helpers".
32
33 LFBFL_some_directory="../../DevOrSysAdminScripts"
34 declare -i LFBFL_i_pushd_result3
35 pushd "${LFBFL_some_directory}" || {
36     LFBFL_i_pushd_result3=$?
37     printf "pre-commit pushd %s no such directory\n"\
38         "${LFBFL_some_directory}"
39     # shellcheck disable=SC2248
40     exit ${LFBFL_i_pushd_result3}
41 }
42 # shellcheck source=git_checks.lib.sh
43 source "./git_helpers/git_checks.lib.sh"
44 declare -i LFBFL_i_popd_result3
```

```

45 popd || {
46     LFBFL_i_popd_result3=$?
47     printf "pre-commit no popd\n"
48     # shellcheck disable=SC2248
49     exit ${LFBFL_i_popd_result3}
50 }
51
52 declare -gi LFBFL_i_git_hook_error=0
53 if ! check_files; then
54     LFBFL_i_git_hook_error=1
55 fi
56 if ! check_no_abusive_trailing_comma; then
57     LFBFL_i_git_hook_error=1
58 fi
59 if ! check_black_code_formatting; then
60     LFBFL_i_git_hook_error=1
61 fi
62 readonly LFBFL_i_git_hook_error
63 # shellcheck disable=SC2248
64 exit ${LFBFL_i_git_hook_error}

```

3.59 IMAP_transfert.exec.py

```

1  """
2  This file is part of DevOrSysAdminScripts.
3
4  DevOrSysAdminScripts is free software:
5  you can redistribute it and/or modify it
6  under the terms of the GNU Lesser General Public License
7  as published by the Free Software Foundation,
8  either version 3 of the License,
9  or (at your option) any later version.
10
11  DevOrSysAdminScripts is distributed
12  in the hope that it will be useful,
13  but WITHOUT ANY WARRANTY;
14  without even the implied warranty of
15  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16  See the GNU Lesser General Public License for more details.
17
18  You should have received a copy of
19  the GNU Lesser General Public License
20  along with DevOrSysAdminScripts.
21  If not, see <https://www.gnu.org/licenses/>.
22
23  ©Copyright 2023–2026 Laurent Frédéric Bernard François Lyaudet

```



```

24 2026-05-12T12:06+02:00: This file was renamed from
25 "IMAP_transfert.py"
26 to
27 "IMAP_transfert.exec.py".
28
29 Pour transférer d'un compte IMAP à un autre
30 Penser à autoriser les apps moins sûres sur Gmail si nécessaire
31 """
32
33 import argparse
34 import email
35 import imaplib
36
37
38 class IMAPTransfertBadArgumentError(Exception):
39     """
40     A class to avoid a linter warning,
41     that needs an Error suffix to avoid another linter warning,
42     that needs a docstring to avoid another linter warning.
43     If you don't see its intent, try badminton.
44     """
45
46
47 class SurpriseError(Exception):
48     """
49     A class to avoid a linter warning,
50     that needs an Error suffix to avoid another linter warning,
51     that needs a docstring to avoid another linter warning.
52     If you don't see its intent after seeing its use, try volleyball.
53     But "Cheer up!", now you don't need "pass" XD.
54     """
55
56
57 def IMAP_transfert(
58     from_login: str,
59     from_password: str,
60     from_host: str,
61     from_port: int,
62     to_login: str,
63     to_password: str,
64     to_host: str,
65     to_port: int,
66     *,
67     to_new_folder: str = "",
68     verbose: bool = False,
69 ) -> None:

```

```

70     """
71     Transfert all emails from some IMAP account
72     to another IMAP account.
73     """
74     empty = ""
75     if from_login == "":
76         raise IMAPTransfertBadArgumentError("From login is empty.")
77     # if from_password == "":
78     if from_password == empty:
79         # https://github.com/PyCQA/bandit/issues/714
80         # Dumb
81         raise IMAPTransfertBadArgumentError("From password is empty.")
82     if from_host == "":
83         raise IMAPTransfertBadArgumentError("From host is empty.")
84     if from_port <= 0:
85         raise IMAPTransfertBadArgumentError(
86             "From port is not positive.",
87         )
88     if to_login == "":
89         raise IMAPTransfertBadArgumentError("To login is empty.")
90     if to_password == empty:
91         # And Dumber The infinite collection XD
92         raise IMAPTransfertBadArgumentError("To password is empty.")
93     if to_host == "":
94         raise IMAPTransfertBadArgumentError("To host is empty.")
95     if to_port <= 0:
96         raise IMAPTransfertBadArgumentError(
97             "To port is not positive.",
98         )
99     # pylint: disable=pointless-string-statement
100    """
101    Maybe one day Python will ship something like that in its standard
102    library:
103    https://www.php.net/manual/fr/function.filter-var.php
104    But now urlparse doesn't do any validation.
105    You may want to check that the hosts or other fields are not
106    "anything".
107    """
108
109    # pylint: disable=unreachable
110    raise SurpriseError(
111        "I haven't tested this version of my script... Ooooooh!\n"
112        "But I linted it without this exception ;). Aaaaaaaah!\n"
113        "XD XD XD\n"
114        "Untested Scream Horror Show (Soon on BrainfuckedFlix)",
115    )

```

```

116 # """
117 # I haven't tested any version with an empty to_new_folder...
118
119 if verbose:
120     print('Connecting to "from account".')
121 from_account = imaplib.IMAP4_SSL(host=from_host, port=from_port)
122 from_account.login(from_login, from_password)
123
124 if verbose:
125     print('Connecting to "to account".')
126 to_account = imaplib.IMAP4_SSL(host=to_host, port=to_port)
127 to_account.login(to_login, to_password)
128
129 if to_new_folder != "":
130     if verbose:
131         print('Creating new folder in "to account".')
132     to_account.create(to_new_folder)
133
134 if verbose:
135     print('Fetching all emails ids in "from account".')
136 from_account.select()
137 result, ids = from_account.uid("search", "all")
138 if verbose:
139     print(f'from_account.uid("search") result:{result} ids:{ids}')
140 ids = ids[0].decode().split()
141 if verbose:
142     print('Fetching and transferring each email in "from account".')
143 for my_id in ids:
144     result, raw_message = from_account.uid(
145         "fetch",
146         my_id,
147         "(RFC822)",
148     )
149     if verbose:
150         print(f'from_account.uid("fetch", {my_id}) result:{result}')
151     message = raw_message[0][1]
152     my_email = email.message_from_string(message.decode("utf-8"))
153     flags = imaplib.ParseFlags(raw_message[0][0])
154     # flags = " ".join(flags) mypy is unhappy but IMAP flags are
155     # ASCII strings, we give mypy what it wants.
156     flags_as_strs = [flag.decode("ascii") for flag in flags]
157     flags_str = " ".join(flags_as_strs)
158     # date = imaplib.Internaldate2tuple(raw_message[0][0])
159     date = '"" + my_email["date"] + ""'
160     if verbose:
161         print(

```

```

162         f'from_account.uid("fetch", {my_id})'
163         f" flags:{flags} date:{date}",
164     )
165     to_account.append(to_new_folder, flags_str, date, message)
166
167
168 def main() -> None:
169     """
170     Parse command-line arguments and
171     transfert all emails from some IMAP account
172     to another IMAP account.
173     """
174     parser = argparse.ArgumentParser(
175         description=(
176             "Transfert all emails from some IMAP account"
177             " to another IMAP account"
178         ),
179     )
180     parser.add_argument(
181         "from_login",
182         type=str,
183         help="Email account login of user one.",
184     )
185     parser.add_argument(
186         "from_password",
187         type=str,
188         help="Email account password of user one.",
189     )
190     parser.add_argument(
191         "to_login",
192         type=str,
193         help="Email account login of user two.",
194     )
195     parser.add_argument(
196         "to_password",
197         type=str,
198         help="Email account password of user two.",
199     )
200     parser.add_argument(
201         "--to_new_folder",
202         type=str,
203         default="",
204         help="Transfert emails into a new folder of this name.",
205     )
206     parser.add_argument(
207         "--from_host",

```

```

208         type=str,
209         default="imap.gmail.com",
210         help="Host of first email account",
211     )
212     parser.add_argument(
213         "--from_port",
214         type=int,
215         default=993,
216         help="Port on host of first email account",
217     )
218     parser.add_argument(
219         "--to_host",
220         type=str,
221         default="imap.gmail.com",
222         help="Host of second email account",
223     )
224     parser.add_argument(
225         "--to_port",
226         type=int,
227         default=993,
228         help="Port on host of second email account",
229     )
230     parser.add_argument(
231         "-v",
232         "--verbose",
233         action="store_true",
234         help="Print details of operations",
235     )
236
237     args = parser.parse_args()
238
239     if args.verbose:
240         print(
241             "-----\n"
242             "IMAP transfert:\n"
243             "-----\n"
244             "From account:\n"
245             f" - Login: {args.from_login}\n"
246             f" - Password: {args.from_password}\n"
247             f" - Host: {args.from_host}\n"
248             f" - Port: {args.from_port}\n"
249             "To account:\n"
250             f" - Login: {args.to_login}\n"
251             f" - Password: {args.to_password}\n"
252             f" - Host: {args.to_host}\n"
253             f" - Port: {args.to_port}\n"

```

```

254         "-----\n",
255     )
256     if args.to_new_folder is not None:
257         print(
258             f"Emails will go in folder {args.to_new_folder}"
259             " after it is created.",
260         )
261     try:
262         IMAP_transfert(
263             args.from_login,
264             args.from_password,
265             args.from_host,
266             args.from_port,
267             args.to_login,
268             args.to_password,
269             args.to_host,
270             args.to_port,
271             to_new_folder=args.to_new_folder,
272             verbose=args.verbose,
273         )
274     except (IMAPTransfertBadArgumentError, SurpriseError) as e:
275         print(e)
276
277
278 if __name__ == "__main__":
279     main()

```

3.60 LiensUtiles.txt

```

1  https://support.google.com/a/answer/9476255?hl=fr#zippy=%2C%C3%A9tape\
2  -configurez-le-service-de-migration-de-donn%C3%A9es
3  -----
4  https://stackoverflow.com/a/78413334/5796086
5  https://stackoverflow.com/questions/21612980/\
6  why-is-usr-bin-env-bash-superior-to-bin-bash/78413334
7  https://web.archive.org/web/20240501105801/https://stackoverflow.com\
8  /questions/21612980/why-is-usr-bin-env-bash-superior-to-bin-bash/\
9  78413334#78413334
10 -----
11 https://news.ycombinator.com/item?id=22214690
12 https://github.com/koalaman/shellcheck/issues/2005
13 https://opensource.stackexchange.com/questions/6271/\
14 calling-gpld-programs-from-a-shell-script
15 -----
16 https://pubs.opengroup.org/onlinepubs/9699919799/
17 When looking `man sed` GNU sed says to use POSIX -E instead of

```

```

18 -r or --regexp-extended for portability.
19 But the link above says that still now only -e, -f, -n are POSIX options
20 for sed.
21 For this reason we replaced all short option names by long option names
22 when possible, even for sed.

```

3.61 miscellaneous/funny.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # Copyright 2023–2026 Laurent Frédéric Bernard François Lyaudet
24
25 unprotected_funny() {
26     # Works in a script but not in shell if job control is active.
27     shopt -s lastpipe
28     declare -i LFBFL_i_result=0
29     local LFBFL_line
30     printf "hahaha\n" | while read -r LFBFL_line; do
31         if [[ "${LFBFL_line}" == "hahaha" ]]; then
32             LFBFL_i_result=1
33         fi
34     done
35     [[ LFBFL_i_result -eq 1 ]] && printf "I had a good laugh.\n"
36 }
37
38 protected_funny() {

```

```

39  # Always works regarding the echoes.
40  printf "hahaha\n" | while read -r LFBFL_line; do
41      unprotected_funny
42  done
43  }

```

3.62 miscellaneous/spamty_data.txt

```

1
2
3
4  a
5  a
6  empty.txt:
7  one_space.txt:
8  all_space.txt:
9  normal.txt:a
10 normal_again.txt: a

```

3.63 miscellaneous/string_escaping.html

```

1  <!DOCTYPE html>
2  <html lang="en">
3  <head>
4      <meta charset="utf-8">
5      <title>Truc</title>
6  </head>
7  <body>
8  <header id="title-block-header">
9  <h1 class="title">Truc</h1>
10 </header>
11 &lt;abc> &amp; &lt;de>
12 <p title="&<>'
13   abcd\\ machin">
14 This is some text
15 </p>
16
17 <pre>
18 "&lt;&amp;>'&quot;
19 abcd\\ machin"
20 This is some text
21 </pre>
22
23 <script>
24 let a = 'abcd & < > \\ \n  \"\' \u{00003c}/script>';
25 alert(a);

```



```

26 let b = "abcd & < > \\ \n  \"'\";
27 alert(b);
28 </script>
29
30 </body>
31 </html>

```

3.64 miscellaneous/string_escaping.xhtml

```

1 <!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
2   "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
3 <html xmlns="http://www.w3.org/1999/xhtml" xml:lang="fr" lang="fr">
4 <head>
5   <meta content="text/html; charset=UTF-8" http-equiv="Content-Type" />
6   <title>Truc</title>
7 </head>
8 <body>
9   <h1 class="title">Truc</h1>
10   &lt;abc> &amp; &lt;de>
11
12   <p title="&lt;&amp;>'&#10;
13     abcd\\ machin">
14     This is some text
15   </p>
16
17   <pre>
18     "&lt;&amp;>'&quot;
19     abcd\\ machin"
20     This is some text
21   </pre>
22
23   <script type="text/javascript">
24     let a = 'abcd &amp; &lt; > \\ \n  \"'\';
25     alert(a);
26     let b = "abcd &amp; &lt; > \\ \n  \"'\";
27     alert(b);
28   </script>
29
30 </body>
31 </html>

```

3.65 README.md.tpl

```

1 # DevOrSysAdminScripts
2
3 [[CodeFactor-badge]][CodeFactor-package-page]

```

```

4  [[Codacy-badge]][Codacy-package-page]
5  ![GitHub-top-language-badge]
6  ![GitHub-code-size-in-bytes-badge]
7  [[Security:bandit:badge]][Bandit-GitHub.com]
8  [[Code-style:black:badge]][Black-GitHub.com]
9  [[Imports:isort:badge]][Isort-GitHub.io]
10 [[Typecheck:mypy:badge]][Typecheck-mypy-lang.org]
11 [[Linting:pylint:badge]][Pylint-GitHub.com]
12 [[Linting:ruff:badge]][Ruff-GitHub.com]
13
14 |                               **Some "small" useful scripts**                               |
15 |:-----:|
16 | **for enhancing development or system-administrators tasks** |
17
18 Currently, the biggest part of this repository is in
19 a suite of shell scripts about build and checks that
20 I use in some of my other repositories.
21
22 I tried to follow some conventions for my bash code:
23
24 - I tried to encapsulate most of the code in functions.
25 - Unless used as return values, variables in functions are defined
26   as local variables (`local` keyword or `declare`)
27   with prefix "LFBFL_".
28 - When used as return values, variables in functions are defined
29   as global variables (`declare -g`) with prefix
30   "@function_name@_result_".
31 - Whenever a variable is no more modified after some point,
32   add the keyword `readonly` or use `declare -r`.
33 - Whenever a variable will only contain integer values (or boolean
34   values as 0 or 1), use `declare -i`.
35 - I named bash files with suffixes ".exec.sh" when the script can
36   be runned
37   (executable, abbreviation stops before a vowel).
38 - I named bash files with suffixes ".lib.sh" when the script contains
39   only functions definitions
40   (library, abbreviation stops before a vowel).
41 - But the files "pre-commit" and "post-commit" were not renamed,
42   since it is not possible to give them other names to use them as
43   pre-commit/post-commit hooks in `git`.
44 - When some ".exec.sh" code is encapsulated into functions,
45   either these functions can be reused and go in some ".lib.sh" file,
46   either they are truly specific to this script and they are kept
47   in ".exec.sh" file.
48 - When using `source` builtin, although any path/filename with a slash
49   will only be searched for from the current directory (tested),

```

```

50     we add the prefix "./", to make it explicit.
51 - We use mapfile instead of read -r most of the time, but with the
52   following exceptions: real use of read -r to read the command line of the
53   shell, comments (of course), and a file funny.sh where it is kind of
54   required to use read -r.
55 - We replaced all echo calls by printf calls to follow
56   "The Open Group Base Specifications" since at least 2 decades:
57   "New applications are encouraged to use printf instead of echo.",
58   <https://pubs.opengroup.org/onlinepubs/000095399/>.
59 - We used `'_?i_'` or `'_?j_'`, etc. in integer variables names in Bash
60   scripts.
61
62 [CodeFactor-badge]: https://www.codefactor.io/repository/github/llyaudet/DevOrSysAdminScripts/badge
63
64
65 [CodeFactor-package-page]: https://www.codefactor.io/repository/github/llyaudet/DevOrSysAdminScripts
66
67
68 [Codacy-badge]: https://app.codacy.com/project/badge/Grade/3dd6ef85e8db4460991d1ebc404b68dd
69
70
71 [Codacy-package-page]: https://app.codacy.com/gh/LLyaudet/DevOrSysAdminScripts/dashboard?utm\_source=gh&utm\_medium=referral&utm\_content=&utm\_campaign=Badge\_grade
72
73
74
75 [GitHub-top-language-badge]: https://img.shields.io/github/languages/top/llyaudet/DevOrSysAdminScripts
76
77
78 [GitHub-code-size-in-bytes-badge]: https://img.shields.io/github/languages/code-size/llyaudet/DevOrSysAdminScripts
79
80
81 [Security:bandit:badge]: https://img.shields.io/badge/security-bandit-yellow.svg
82
83
84 [Bandit-GitHub.com]: https://github.com/PyCQA/bandit
85
86
87 [Code-style:black:badge]: https://img.shields.io/badge/code%20style-black-000000.svg
88
89
90 [Black-GitHub.com]: https://github.com/psf/black
91
92
93 [Imports:isort:badge]: https://img.shields.io/badge/%20imports-isort-%231674b1?style=flat&labelColor=ef8336
94
95 [Isort-GitHub.io]: https://pycqa.github.io/isort/

```

```

96 [Typecheck:mypy:badge]: https://www.mypy-lang.org/static/\
97 mypy_badge.svg
98
99 [Typecheck-mypy-lang.org]: https://mypy-lang.org/
100
101 [Linting:pylint:badge]: https://img.shields.io/badge/\
102 linting-pylint-yellowgreen
103
104 [Pylint-GitHub.com]: https://github.com/pylint-dev/pylint
105
106 [Linting:ruff:badge]: https://img.shields.io/endpoint?url=\
107 https://raw.githubusercontent.com/astral-sh/ruff/main/assets/\
108 badge/v2.json
109
110 [Ruff-GitHub.com]: https://github.com/astral-sh/ruff

```

3.66 string_escaping.lib.php

```

1  <?php
2
3  /**
4   This file is part of DevOrSysAdminScripts.
5
6   DevOrSysAdminScripts is free software:
7   you can redistribute it and/or modify it
8   under the terms of the GNU Lesser General Public License
9   as published by the Free Software Foundation,
10  either version 3 of the License,
11  or (at your option) any later version.
12
13  DevOrSysAdminScripts is distributed
14  in the hope that it will be useful,
15  but WITHOUT ANY WARRANTY;
16  without even the implied warranty of
17  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
18  See the GNU Lesser General Public License for more details.
19
20  You should have received a copy of
21  the GNU Lesser General Public License
22  along with DevOrSysAdminScripts.
23  If not, see <https://www.gnu.org/licenses/>.
24
25  ©Copyright 2023–2026 Laurent Frédéric Bernard François Lyaudet
26
27  @category Library
28  @package DevOrSysAdminScripts

```

```

29 @author Laurent Lyaudet <laurent.lyaudet@gmail.com>
30 @copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
31 @license https://www.gnu.org/licenses/lgpl-3.0.html LGPLv3+
32 */
33
34 declare(strict_types=1);
35 declare(encoding='UTF-8');
36
37
38
39 /**
40 The namespace string_escaping is splitted into subnamespaces for each
41 language.
42 This subnamespace is for HTML (surprised?)...
43
44 @package DevOrSysAdminScripts
45 @subpackage string_escaping\HTML
46 */
47 namespace string_escaping\HTML {
48     /**
49      When you want that the string appears as is in HTML text block.
50
51      @param string $s_string The string you want to escape.
52
53      @return string The escaped string.
54     */
55     function escape_text(string $s_string) : string {
56         return str_replace(
57             [
58                 '&',
59                 '<',
60             ],
61             [
62                 '&',
63                 '<',
64             ],
65             $s_string,
66         );
67     } //end escape_text()
68
69
70
71     /**
72      When you want that the string appears as is in an HTML tag attribute
73      that starts and ends with double quotes: my_attribute="something".
74      Example: a title attribute.

```

```

75  /\ in double quotes /\ my_attribute='something' is not supported.
76
77  @param string $s_string The string you want to escape.
78
79  @return string The escaped string.
80  */
81  function escape_attribute(string $s_string) : string {
82      return str_replace(
83          ['"',
84           '"'],
85          $s_string,
86      );
87  } //end escape_attribute()
88
89
90
91  /**
92   When you want that the string appears verbatim inside HTML <pre> tags.
93
94   @param string $s_string The string you want to escape.
95
96   @return string The escaped string.
97   */
98   function escape_pre(string $s_string) : string {
99       return str_replace(
100          [
101              '&',
102              '<',
103          ],
104          [
105              '&amp;',
106              '&lt;',
107          ],
108          $s_string,
109      );
110  } //end escape_pre()
111  } //end namespace string_escaping\HTML
112
113
114
115
116  /**
117   The namespace string_escaping is splitted into subnamespaces for each
118   language.
119   This subnamespace is for XHTML (still surprised?)...
120

```

```

121 @package DevOrSysAdminScripts
122 @subpackage string_escaping\XHTML
123 */
124 namespace string_escaping\XHTML {
125     /**
126      * When you want that the string appears as is in XHTML text block.
127      *
128      * @param string $s_string The string you want to escape.
129      *
130      * @return string The escaped string.
131      */
132     function escape_text(string $s_string) : string {
133         return str_replace(
134             [
135                 '&',
136                 '<',
137             ],
138             [
139                 '&amp;',
140                 '&lt;',
141             ],
142             $s_string,
143         );
144     } //end escape_text()
145
146
147
148     /**
149      * When you want that the string appears as is in an XHTML tag attribute
150      * that starts and ends with double quotes: my_attribute="something".
151      * Example: a title attribute.
152      * /!\ in double quotes /!\ my_attribute='something' is not supported.
153      *
154      * @param string $s_string The string you want to escape.
155      *
156      * @return string The escaped string.
157      */
158     function escape_attribute(string $s_string) : string {
159         return str_replace(
160             [
161                 '&',
162                 '<',
163                 '"',
164                 "\n",
165             ],
166             [

```

```

167         '&';',
168         '<';',
169         '"';',
170         '#10;';',
171     ],
172     $s_string,
173 );
174 }//end escape_attribute()
175
176
177
178 /**
179  When you want that the string appears verbatim inside XHTML <pre> tags.
180
181  @param string $s_string The string you want to escape.
182
183  @return string The escaped string.
184  */
185 function escape_pre(string $s_string) : string {
186     return str_replace(
187         [
188             '&',
189             '<',
190         ],
191         [
192             '&';',
193             '<';',
194         ],
195         $s_string,
196     );
197 }//end escape_pre()
198 }//end namespace string_escaping\XHTML
199
200
201
202
203 /**
204  The namespace string_escaping is splitted into subnamespaces for each
205  language.
206  This subnamespace is for JS (you're hopeless?)...
207
208  @package DevOrSysAdminScripts
209  @subpackage string_escaping\JS
210  */
211 namespace string_escaping\JS {
212

```



```

213 use function string_escaping\XHTML\escape_text as XHTML_escape_text;
214
215
216
217 /**
218 When you want that the string can be put in a JS string definition.
219
220 @param string $s_string The string you want to escape.
221
222 @return string The escaped string.
223 */
224 function escape(string $s_string) : string {
225     return str_replace(
226         [
227             '\\',
228             '\n',
229             '"',
230             "'",
231         ],
232         [
233             '\\\\',
234             '\n',
235             '\\\\'',
236             '\\\\"',
237         ],
238         $s_string,
239     );
240 } //end escape()
241
242
243
244 /**
245 When you want that the string can be put in a JS string definition
246 to be included inside an HTML file <script> tag.
247
248 @param string $s_string The string you want to escape.
249
250 @return string The escaped string.
251 */
252 function escape_for_string_definition_inside_HTML(string $s_string)
253 : string {
254     return str_replace(
255         ['</script>', ],
256         ['\u{00003c}/script>', ],
257         escape($s_string),
258     );

```

```

259     }//end escape_for_string_definition_inside_XHTML()
260
261
262
263     /**
264     When you want that the string can be put in a JS string definition
265     to be included inside an XHTML file <script> tag.
266
267     @param string $s_string The string you want to escape.
268
269     @return string The escaped string.
270     */
271     function escape_for_string_definition_inside_XHTML(string $s_string)
272     : string {
273         return XHTML_escape_text(escape($s_string));
274     }//end escape_for_string_definition_inside_XHTML()
275 }//end namespace string_escaping\JS
276
277
278
279
280 /**
281 The namespace string_escaping is splitted into subnamespaces for each
282 language.
283 This subnamespace is for TeX.
284
285 @package DevOrSysAdminScripts
286 @subpackage string_escaping\TeX
287 */
288 namespace string_escaping\TeX {
289     /**
290     When you want that the string can be written to a TeX file inside a
291     part where TeX is in text mode.
292
293     @param string $s_string The string you want to escape.
294
295     @return string The escaped string.
296     */
297     function escape_text(string $s_string) : string {
298         // https://tex.stackexchange.com/a/34586/270015
299         return str_replace(
300             [
301                 '\\',
302                 '&',
303                 '%',
304                 '$',

```

```

305         '#',
306         '-',
307         '{',
308         '}',
309         '~',
310         '^',
311     ],
312     [
313         '\\textbackslash',
314         '\\&',
315         '\\%',
316         '\\$',
317         '\\#',
318         '\\_',
319         '\\{',
320         '\\}',
321         '\\textasciitilde',
322         '\\textasciicircum',
323     ],
324     $s_string,
325 );
326 }//end escape_text()
327 }//end namespace string_escaping\\TeX
328
329 /*
330 $ php
331 <?php
332 require_once('string_escaping.lib.php');
333 var_dump(string_escaping\\HTML\\escape_text("<&\\\"\\n'truc\\>"));
334 var_dump(string_escaping\\HTML\\escape_attribute("<&\\\"\\n'truc\\>"));
335 var_dump(string_escaping\\HTML\\escape_pre("<&\\\"\\n'truc\\>"));
336 var_dump(string_escaping\\XHTML\\escape_text("<&\\\"\\n'truc\\>"));
337 var_dump(string_escaping\\XHTML\\escape_attribute("<&\\\"\\n'truc\\>"));
338 var_dump(string_escaping\\XHTML\\escape_pre("<&\\\"\\n'truc\\>"));
339 var_dump(string_escaping\\JS\\escape("abcd & < > \\ \\n \\\"'"));
340 var_dump(string_escaping\\JS\\escape_for_string_definition_inside_HTML(
341     "abcd & < > \\ \\n \\\"' </script>"
342 ));
343 var_dump(string_escaping\\JS\\escape_for_string_definition_inside_XHTML(
344     "abcd & < > \\ \\n \\\"'"
345 ));
346 */
347 ?>

```

3.67 unicode.lib.php

```
1  <?php
2
3  /**
4   This file is part of DevOrSysAdminScripts.
5
6   DevOrSysAdminScripts is free software:
7   you can redistribute it and/or modify it
8   under the terms of the GNU Lesser General Public License
9   as published by the Free Software Foundation,
10  either version 3 of the License,
11  or (at your option) any later version.
12
13  DevOrSysAdminScripts is distributed
14  in the hope that it will be useful,
15  but WITHOUT ANY WARRANTY;
16  without even the implied warranty of
17  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
18  See the GNU Lesser General Public License for more details.
19
20  You should have received a copy of
21  the GNU Lesser General Public License
22  along with DevOrSysAdminScripts.
23  If not, see <https://www.gnu.org/licenses/>.
24
25  ©Copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
26  This file was renamed from "unicode.php" to "unicode.lib.php".
27
28  @category Library
29  @package DevOrSysAdminScripts
30  @author Laurent Lyaudet <laurent.lyaudet@gmail.com>
31  @copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
32  @license https://www.gnu.org/licenses/lgpl-3.0.html LGPLv3+
33  */
34
35  declare(strict_types=1);
36  declare(encoding='UTF-8');
37
38
39
40  /**
41   Converts an int to the byte-string corresponding to the UTF-8 encoding
42   of the Unicode code point of same integer value.
43   decimal_code_point is a slight abuse of language to say that you write the
44   code point in decimal notation in PHP code and you get the UTF-8.
```

```

45 If you provide the integer of the code point without using decimal
46 notation, it will also work.
47
48 @param int $i_code_point_in_decimal_notation The code point.
49
50 @throws Exception When the code point is outside of Unicode range.
51
52 @return string The corresponding UTF-8 character.
53 */
54 function decimal_code_point_to_UTF8(
55     int $i_code_point_in_decimal_notation
56 ) : string {
57     // var_dump($i_code_point_in_decimal_notation);
58     // 0xxxxxxx ASCII
59     if($i_code_point_in_decimal_notation < 128){
60         return chr($i_code_point_in_decimal_notation);
61     }
62     $i_continuation_base_value = 128;
63     // 110xxxxx 10xxxxxx
64     if($i_code_point_in_decimal_notation < 2048){ // 2**11
65         $i_first_byte_base_value = 192;
66         /*
67         $i_last_byte_significant_bits = (
68             $i_code_point_in_decimal_notation % 64 // 2**6
69         );
70         $i_first_byte_significant_bits = intdiv(
71             (
72                 $i_code_point_in_decimal_notation
73                 - $i_last_byte_significant_bits
74             ),
75             64, // 2**6
76         );
77         $s_result = chr(
78             $i_first_byte_base_value
79             + $i_first_byte_significant_bits
80         );
81         $s_result .= chr(
82             $i_continuation_base_value
83             + $i_last_byte_significant_bits
84         );
85         return $s_result;
86     */
87     return (
88         chr(
89             $i_first_byte_base_value
90             + ($i_code_point_in_decimal_notation >> 6)

```

```

91         )
92         .chr(
93             $i_continuation_base_value
94             + ($i_code_point_in_decimal_notation & 63)
95         )
96     );
97 }//end if($i_code_point_in_decimal_notation < 2048)
98 // 1110xxxx 10xxxxxx 10xxxxxx
99 if($i_code_point_in_decimal_notation < 65536){ // 2**16
100     $i_first_byte_base_value = 224;
101     /*
102     $arr_arr_data_per_byte_reverse = [
103         ['i_bits' => 6, 'i_base_value' => $i_continuation_base_value],
104         ['i_bits' => 6, 'i_base_value' => $i_continuation_base_value],
105         ['i_bits' => 4, 'i_base_value' => $i_first_byte_base_value],
106     ];
107     $i_rest = $i_code_point_in_decimal_notation;
108     $s_result = '';
109     foreach($arr_arr_data_per_byte_reverse as $arr_data){
110         // _Pragma unroll
111         // J'aurais pu "roller" les 4 cas des ifs.
112         // Mais pour les perfs, il faudrait tout unroller vu le nombre
113         // d'itérations. Et j'aimerais bien comparer du code unrollé
114         // aux 2 niveaux à la main avec celui unrollé par le compilateur
115         // sur les 2 niveaux. Je préjuge/présume qu'il unroll
116         // l'intérieur d'abord (pour ne pas refaire le même boulot)
117         // puis l'extérieur et qu'il oublie de réoptimiser l'intérieur
118         // en fonction de l'extérieur unrollé. Est-ce que j'ai raison ?
119         $i_significant_bits = $i_rest % (2**$arr_data['i_bits']);
120         $i_rest = intdiv(
121             $i_rest - $i_significant_bits,
122             2**$arr_data['i_bits'],
123         );
124         // .= or =.
125         // Below could have been a case of "=".
126         $s_result = (
127             chr($i_significant_bits + $arr_data['i_base_value'])
128             . $s_result
129         );
130     }//end foreach($arr_arr_data_per_byte_reverse as $arr_data)
131     return $s_result;
132 */
133     return (
134         chr(
135             $i_first_byte_base_value
136             + ($i_code_point_in_decimal_notation >> 12)

```

```

137     )
138     .chr(
139         $i_continuation_base_value
140         + (($i_code_point_in_decimal_notation >> 6) & 63)
141     )
142     .chr(
143         $i_continuation_base_value
144         + ($i_code_point_in_decimal_notation & 63)
145     )
146 );
147 }//end if($i_code_point_in_decimal_notation < 65536)
148 // 11110xxx 10xxxxxx 10xxxxxx 10xxxxxx
149 if($i_code_point_in_decimal_notation < 2097152){ // 2**21
150     $i_first_byte_base_value = 240;
151     /*
152     $arr_arr_data_per_byte_reverse = [
153         ['i_bits' => 6, 'i_base_value' => $i_continuation_base_value],
154         ['i_bits' => 6, 'i_base_value' => $i_continuation_base_value],
155         ['i_bits' => 6, 'i_base_value' => $i_continuation_base_value],
156         ['i_bits' => 3, 'i_base_value' => $i_first_byte_base_value],
157     ];
158     $i_rest = $i_code_point_in_decimal_notation;
159     $s_result = '';
160     foreach($arr_arr_data_per_byte_reverse as $arr_data){
161         // _Pragma unroll
162         $i_significant_bits = $i_rest % (2**$arr_data['i_bits']);
163         $i_rest = intdiv(
164             $i_rest - $i_significant_bits,
165             2**$arr_data['i_bits'],
166         );
167         // .= or =.
168         // Below could have been a case of "=".
169         $s_result = (
170             chr($i_significant_bits + $arr_data['i_base_value'])
171             . $s_result
172         );
173     }
174     return $s_result;
175 */
176     return (
177         chr(
178             $i_first_byte_base_value
179             + ($i_code_point_in_decimal_notation >> 18)
180         )
181         .chr(
182             $i_continuation_base_value

```

```

183         + (($i_code_point_in_decimal_notation >> 12) & 63)
184     )
185     .chr(
186         $i_continuation_base_value
187         + (($i_code_point_in_decimal_notation >> 6) & 63)
188     )
189     .chr(
190         $i_continuation_base_value
191         + ($i_code_point_in_decimal_notation & 63)
192     )
193 );
194 }//end if($i_code_point_in_decimal_notation < 2097152)
195 // phpcs:disable Squiz.Strings.DoubleQuoteUsage.NotRequired
196 throw new Exception(
197     "UTF-8 avec jusqu'à 6 octets a été abandonné il y a longtemps."
198     ." Autre anecdote \"débile\" : MySQL a de base UTF-8 avec jusqu'à"
199     ." 3 octets au lieu de 4 :face-palm:."
200     ." Du coup, ça peut donner quelques \"surprises\"."
201     ." Sinon, y'a aussi ASCII dans MySQL."
202     ." Et comme ça joue sur la mémoire et les performances,"
203     ." pourquoi ils n'ont pas fait ASCII, UTF-8-2, UTF-8-3, UTF-8-4 ?"
204     ." :) "
205 );
206 // phpcs:enable Squiz.Strings.DoubleQuoteUsage.NotRequired
207 }//end decimal_code_point_to_UTF8()
208
209
210
211 /**
212  Converts a string of hexadecimal digits to the byte-string corresponding
213  to the UTF-8 encoding of the Unicode code point of same integer value
214  that is denoted by the hexadecimal digits.
215
216  @param string $s_code_point_in_hexadecimal_notation The code point.
217
218  @throws Exception When the code point is outside of Unicode range.
219
220  @return string The corresponding UTF-8 character.
221  */
222 function hexa_code_point_to_UTF8(
223     string $s_code_point_in_hexadecimal_notation
224 ) : string {
225     $s_code_point_in_hexadecimal_notation = strtoupper(
226         $s_code_point_in_hexadecimal_notation
227     );
228     $i_code_point_in_decimal_notation = 0;

```



```

229     $i_ord_0 = ord('0');
230     $i_ord_A = ord('A');
231     $i_digit_offset = -$i_ord_0;
232     $i_letter_offset = 10 - $i_ord_A;
233     for(
234         $i = 0, $i_max = strlen($s_code_point_in_hexadecimal_notation);
235         $i < $i_max;
236         ++$i
237     ){
238         $s_hexa_digit = $s_code_point_in_hexadecimal_notation[$i];
239         $i_code_point_in_decimal_notation *= 16;
240         if(ctype_digit($s_hexa_digit)){
241             $i_code_point_in_decimal_notation += (
242                 ord($s_hexa_digit) + $i_digit_offset
243             );
244             continue;
245         }
246         if(ctype_xdigit($s_hexa_digit)){
247             $i_code_point_in_decimal_notation += (
248                 ord($s_hexa_digit) + $i_letter_offset
249             );
250             continue;
251         }
252         throw new Exception('Not an hexadecimal digit.');
```

253 }

```

254     return decimal_code_point_to_UTF8(
255         $i_code_point_in_decimal_notation
256     );
257 } //end hexa_code_point_to_UTF8()
258
259
260
261 /**
262  This function throws an exception with extended debug informations
263  if the input string is not valid ASCII.
264  Otherwise, it returns true.
265
266  @param string $s_string The input string.
267
268  @throws Exception When the input string is not valid ASCII.
269
270  @return bool
271  */
272 function check_string_is_valid_ASCII(string $s_string) : bool {
273     $i_offset_in_octets_from_string_start = 0;
274     $i_current_line_number = 1;
```

```

275     $i_offset_in_octets_from_line_start = -1;
276     for($i = 0, $i_max = strlen($s_string); $i < $i_max; ++$i){
277         $i_current_octet = ord($s_string[$i]);
278         $i_offset_in_octets_from_string_start = $i;
279         ++$i_offset_in_octets_from_line_start;
280         if($i_current_octet > 127){
281             throw new Exception(
282                 'Non-ASCII character found on line '
283                 . $i_current_line_number
284                 . ' ; the octet/character '
285                 . ($i_offset_in_octets_from_line_start + 1)
286                 . ' has value '
287                 . $i_current_octet
288                 . ' which is not ASCII.'
289                 . ' (Sequential position without line splitting:'
290                 . ' This is at octet/character '
291                 . ($i_offset_in_octets_from_string_start + 1)
292                 . '.)',
293             );
294         }
295         // if($s_string[$i] === "\n"){
296         if($i_current_octet === 10){
297             ++$i_current_line_number;
298             $i_offset_in_octets_from_line_start = -1;
299         }
300     } //for($i = 0, $i_max = strlen($s_string); $i < $i_max; ++$i)
301     return true;
302 } //end check_string_is_valid_ASCII()
303
304
305
306 /**
307  * This function throws an exception with extended debug informations
308  * if the content of the file with given file_path is not valid ASCII.
309  * Otherwise, it returns true.
310  *
311  * @param string $s_file_path The input file_path.
312  *
313  * @throws Exception When the input string is not valid ASCII.
314  *
315  * @return bool
316  */
317 function check_file_is_valid_ASCII(string $s_file_path) : bool {
318     $s_string = file_get_contents($s_file_path);
319     if($s_string === false){
320         throw new Exception('File ' . $s_file_path . ' not found.');
```

```

321     }
322     return check_string_is_valid_ASCII($s_string);
323 }//end check_file_is_valid_ASCII()
324
325
326
327 /**
328 This function throws an exception with extended debug informations
329 if the input string is not valid UTF-8.
330 Otherwise, it returns true.
331
332 @param string $s_string The input string.
333
334 @throws Exception When the input string is not valid UTF-8.
335
336 @return bool
337 */
338 function check_string_is_valid_UTF8(string $s_string) : bool {
339     $i_continuation_octet_needed = 0;
340     $i_offset_in_octets_from_string_start = 0;
341     $i_offset_in_characters_from_string_start = -1;
342     $i_character_start_position_from_string_start = 0;
343     $i_current_line_number = 1;
344     $i_offset_in_octets_from_line_start = -1;
345     $i_offset_in_characters_from_line_start = -1;
346     $i_character_start_position_from_line_start = -1;
347     for($i = 0, $i_max = strlen($s_string); $i < $i_max; ++$i){
348         $i_current_octet = ord($s_string[$i]);
349         $i_offset_in_octets_from_string_start = $i;
350         ++$i_offset_in_octets_from_line_start;
351         if($i_continuation_octet_needed > 0){
352             if($i_current_octet < 128 || $i_current_octet >= 192){
353                 throw new Exception(
354                     'Non-UTF8 character found on line '
355                     . $i_current_line_number
356                     . ' ; the octet '
357                     . ($i_offset_in_octets_from_line_start + 1)
358                     . ' , part of the character '
359                     . ($i_offset_in_characters_from_line_start + 1)
360                     . ' , has value '
361                     . $i_current_octet
362                     . ' which is not a continuation octet.'
363                     . ' This character starts at octet '
364                     . ($i_character_start_position_from_line_start + 1)
365                     . ' of the current line.'
366                     . ' (Sequential positions without line splitting:'

```

```

367         .' This is at character '
368         .($i_offset_in_characters_from_string_start + 1)
369         .' and octet '
370         .($i_offset_in_octets_from_string_start + 1)
371         .'.'
372         .' This character starts at octet '
373         .($i_character_start_position_from_string_start + 1)
374         .'.)',
375     );
376     }//end if($i_current_octet < 128 || $i_current_octet >= 192)
377     --$i_continuation_octet_needed;
378     continue;
379 }//end if($i_continuation_octet_needed > 0)
380
381 ++$i_offset_in_characters_from_string_start;
382 ++$i_offset_in_characters_from_line_start;
383 $i_character_start_position_from_string_start = (
384     $i_offset_in_octets_from_string_start
385 );
386 $i_character_start_position_from_line_start = (
387     $i_offset_in_octets_from_line_start
388 );
389 if($i_current_octet < 128){ // 0xxxxxxx ASCII
390     // if($s_string[$i] === "\n"){
391     if($i_current_octet === 10){
392         ++$i_current_line_number;
393         $i_offset_in_octets_from_line_start = -1;
394         $i_offset_in_characters_from_line_start = -1;
395     }
396     continue;
397 }
398 if($i_current_octet >= 128 && $i_current_octet < 192){
399     throw new Exception(
400         'Non-UTF8 character found on line '
401         .$i_current_line_number
402         .' ; the octet '
403         .($i_offset_in_octets_from_line_start + 1)
404         .' , part of the character '
405         .($i_offset_in_characters_from_line_start + 1)
406         .' , has value '
407         .$i_current_octet
408         .' which is a continuation octet.'
409         .' This character starts at octet '
410         .($i_character_start_position_from_line_start + 1)
411         .' of the current line.'
412         .' (Sequential positions without line splitting:'

```

```

413         .' This is at character '
414         .($i_offset_in_characters_from_string_start + 1)
415         .' and octet '
416         .($i_offset_in_octets_from_string_start + 1)
417         .'.'
418         .' This character starts at octet '
419         .($i_character_start_position_from_string_start + 1)
420         .'.'),
421     );
422 }//end if($i_current_octet >= 128 && $i_current_octet < 192)
423 if($i_current_octet >= 192 && $i_current_octet < 224){
424     // 110xxxxx 10xxxxxx
425     $i_continuation_octet_needed = 1;
426     continue;
427 }
428 if($i_current_octet >= 224 && $i_current_octet < 240){
429     // 1110xxxx 10xxxxxx 10xxxxxx
430     $i_continuation_octet_needed = 2;
431     continue;
432 }
433 if($i_current_octet >= 240 && $i_current_octet < 248){
434     // 11110xxx 10xxxxxx 10xxxxxx 10xxxxxx
435     $i_continuation_octet_needed = 3;
436     continue;
437 }
438 throw new Exception(
439     'Non-UTF8 character found on line '
440     . $i_current_line_number
441     .' ; the octet '
442     . ($i_offset_in_octets_from_line_start + 1)
443     .' , part of the character '
444     . ($i_offset_in_characters_from_line_start + 1)
445     .' , has value '
446     . $i_current_octet
447     .' which is invalid.'
448     .' This character starts at octet '
449     . ($i_character_start_position_from_line_start + 1)
450     .' of the current line.'
451     .' (Sequential positions without line splitting:'
452     .' This is at character '
453     . ($i_offset_in_characters_from_string_start + 1)
454     .' and octet '
455     . ($i_offset_in_octets_from_string_start + 1)
456     .'.'
457     .' This character starts at octet '
458     . ($i_character_start_position_from_string_start + 1)

```

```

459         '.'.),' ,
460     );
461     }//end for($i = 0, $i_max = strlen($s_string); $i < $i_max; ++$i)
462     return true;
463 }//end check_string_is_valid_UTF8()
464
465
466
467 /**
468  This function throws an exception with extended debug informations
469  if the content of the file with given file_path is not valid UTF-8.
470  Otherwise, it returns true.
471
472  @param string $s_file_path The input file_path.
473
474  @throws Exception When the input string is not valid UTF-8.
475
476  @return bool
477  */
478 function check_file_is_valid_UTF8(string $s_file_path) : bool {
479     $s_string = file_get_contents($s_file_path);
480     if($s_string === false){
481         throw new Exception('File '.$s_file_path.' not found.');
```

```

482     }
483     return check_string_is_valid_UTF8($s_string);
484 }//end check_file_is_valid_UTF8()
485
486
487
488 /*
489 ?>
490 <?php
491 require_once("./unicode.lib.php");
492 var_dump(hexa_code_point_to_UTF8("002B"));
493 var_dump(hexa_code_point_to_UTF8("00E6"));
494 var_dump(hexa_code_point_to_UTF8("1400"));
495 var_dump(hexa_code_point_to_UTF8("10111"));
496 // https://en.wikibooks.org/wiki/Unicode/Character_reference/2000-2FFF
497 // Some invisible unicode characters that are a problem:
498 // 2000-200F 2028-202F 205F 2060-206F
499 $arr = [
500     '2000', '2001', '2002', '2003', '2004', '2005', '2006', '2007',
501     '2008', '2009', '200A', '200B', '200C', '200D', '200E', '200F',
502     '2028', '2029', '202A', '202B', '202C', '202D', '202E', '202F',
503     '205F',
504     '2060', '2061', '2062', '2063', '2064', '2065', '2066', '2067',
```

```

505     '2068', '2069', '206A', '206B', '206C', '206D', '206E', '206F',
506 ];
507 $arr_s = [];
508 $arr_s2 = [];
509 $arr_s3 = [];
510 echo("sed\\\n");
511 foreach($arr as $s_hexa){
512     $s = hexa_code_point_to_UTF8($s_hexa);
513     $arr_s []= $s;
514     if(strlen($s) === 2){
515         $s2 = '\x'.bin2hex($s[0]).'\x'.bin2hex($s[1]);
516     }
517     if(strlen($s) === 3){
518         $s2 = '\x'.bin2hex($s[0]).'\x'.bin2hex($s[1])
519             .'\x'.bin2hex($s[2]);
520     }
521     $arr_s2 []= $s2;
522     $s3 = " --expression='s/\".$s2.\"/ /g'\\"";
523     $arr_s3 []= $s3;
524     echo($s3."\\n");
525 }
526 /*/
527 ?>

```

3.68 upgrade_build_and_checks.exec.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed
12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.

```

```

21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # Copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
24 # This file was renamed from "upgrade_build_and_checks.sh"
25 # to "upgrade_build_and_checks.exec.sh".
26
27 upgrade_build_and_checks() {
28     # Options:
29     #   --add-test-files
30     #   --check-download=y|keep (=keep to keep the downloaded files)
31     #   --fixed-point-build
32     #   --verbose
33     local LFBFL_verbose=""
34     if [[ "$*" == *--verbose* ]]; then
35         printf "%s %s\n" "$0" "$*"
36         LFBFL_verbose="--verbose"
37     fi
38     readonly LFBFL_verbose
39     local LFBFL_fixed_point_build=""
40     if [[ "$*" == *--fixed-point-build* ]]; then
41         LFBFL_fixed_point_build="--fixed-point-build"
42     fi
43     readonly LFBFL_fixed_point_build
44     local LFBFL_check_download=""
45     if [[ "$*" == *--check-download=keep* ]]; then
46         LFBFL_check_download="--check-download=keep"
47     elif [[ "$*" == *--check-download=y* ]]; then
48         LFBFL_check_download="--check-download=y"
49     fi
50     readonly LFBFL_check_download
51     declare -i LFBFL_add_test_files=0
52     if [[ "$*" == *--add-test-files* ]]; then
53         LFBFL_add_test_files=1
54     fi
55     readonly LFBFL_add_test_files
56     declare -i LFBFL_remove_test_files=0
57     if [[ "$*" == *--remove-test-files* ]]; then
58         LFBFL_remove_test_files=1
59     fi
60     readonly LFBFL_remove_test_files
61     (\
62         cd build_and_checks_dependencies/\
63         && ./update_common_build_and_checks.exec.sh "${LFBFL_verbose}"\
64     )
65
66     declare -i LFBFL_i

```



```

67 local LFBFL_file_path="miscellaneous/123456789012345678901234567890"
68 declare -i LFBFL_digit
69 if [[ LFBFL_add_test_files -eq 1 ]]; then
70     mkdir --parents -- --a/
71     {
72         printf "<?php\nfunction my_function(;;){\n\n}\n"
73         # shellcheck disable=SC2016
74         printf '$my_variable = "aaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaa'
75         printf 'aaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaa";\n'
76     } > --a.php
77     cp -- --a.php --a/
78     {
79         printf "from typing import Iterable\n"
80         printf "from _collections_abc import dict_items\n"
81         printf "\n"
82         printf "from python_none_objects import NoneIterable\n"
83         printf "\n"
84         printf "def my_function(my_argument : int) -> None:\n"
85         printf "    print(my_argument)\n"
86         printf "\n"
87         printf "my_function(\"abcd\")\n"
88         printf "\n"
89         printf "def my_function2(my_argument : int) -> None:\n"
90         printf "    \"\"\"Some comment.\"\"\"\n"
91         printf "    print(my_argument)\n"
92         printf "\n"
93         printf "def my_function3(my_argument : int) -> None:\n"
94         printf "    \"\"\"Some comment.\"\"\"\n"
95         printf "\n"
96         printf "    print(my_argument)\n"
97         printf "\n"
98         printf "def my_function4(my_argument : int):\n"
99         printf "    \"\"\"Some comment.\"\"\"\n"
100        printf "    def my_sub_function():\n"
101        printf "        print(my_argument)\n"
102        printf "    return my_sub_function\n"
103        printf "\n"
104        printf "def my_function5(my_argument : int):\n"
105        printf "    \"\"\"Some comment.\"\"\"\n"
106        printf "\n"
107        printf "    def my_sub_function():\n"
108        printf "        print(my_argument)\n"
109        printf "    return my_sub_function\n"
110        printf "\n"
111    } > --a.py
112 cat -- --a.py

```

```

113 cp -- --a.py --a/
114 {
115     printf "def my_function(;;):\n\n\n"
116     printf 'my_variable = "aaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaa'\n'
117     printf 'aaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaa";\n'
118 } > --a2.py
119 cat -- --a2.py
120 cp -- --a2.py --a/
121 {
122     # Error 0 is missing shell header.
123     printf "my_function(){\n"
124     printf "    # Error 1: Indentation is not correct.\n"
125     printf "    sed -e 's/a/b/g' \\\n"
126     printf "        -e 's/a/b/g' \"\$1\" # Indentation is correct.\n"
127     printf "    my_variable=\"%%s\\n\"\\n"
128     # shellcheck disable=SC2016
129     printf '    printf "{$my_variable}" # Error 2: shellcheck warning\n'
130     local LFBFL_ttp="ttp"
131     local LFBFL_URL="h${LFBFL_ttp}://example.com"
132     printf '    printf "%s" # Error 3: http -> https\n' "${LFBFL_URL}"
133     # shellcheck disable=SC2016
134     printf '    printf "{$#some_'
135     printf 'arr_1}" # Error 4: no_size_of_array_first_element\n'
136     # shellcheck disable=SC2016
137     printf '    printf "{$#'
138     printf 'arr_1}" # Error 5: no_size_of_array_first_element\n'
139     printf '    if !'
140     # shellcheck disable=SC2016
141     printf '    [[ $1 -eq 1 ]]; # Error 6: no_negation_before_bash_test\n'
142     printf '    then # Error 7: misplaced then\n'
143     printf '        my_variable="a"\n'
144     printf '    fi\n'
145     printf "\n"
146     # shellcheck disable=SC2016
147     printf '    if [[ $1 -eq 1 ]];\n'
148     printf '    then # Error 8: another case of misplaced then\n'
149     printf '        my_variable="a"\n'
150     printf '    fi\n'
151     printf '    my_variable="aaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaa'\n'
152     printf 'aaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaa" # Error 9 line too long.\n'
153     printf '}\n'
154 } > --a.sh
155 cp -- --a.sh --a/
156
157 # We add a file with space in it for tests.
158 touch "a b.sh"

```

```

159
160     # The following files cannot be committed,
161     # because the backslash in them breaks CodeFactor.io.
162     for ((LFBFL_i = 1; LFBFL_i < 90; ++LFBFL_i)); do
163         LFBFL_digit=$((LFBFL_i % 10))
164         LFBFL_file_path+="${LFBFL_digit}"
165         touch "${LFBFL_file_path}"
166         touch "${LFBFL_file_path}\\.\"
167     done
168 fi
169 ./build_and_checks.exec.sh ".\"
170     "${LFBFL_verbose}"\"
171     "${LFBFL_fixed_point_build}"\"
172     "${LFBFL_check_download}"\"
173 if [[ LFBFL_add_test_files -eq 1 ]]; then
174     cat -- --a.py
175     cat -- --a2.py
176 fi
177 if [[ LFBFL_remove_test_files -eq 1 ]]; then
178     rm --force --recursive -- --a/
179     rm --force -- --a.php --a.py --a2.py --a.sh
180     rm "a b.sh"
181     for ((LFBFL_i = 1; LFBFL_i < 90; ++LFBFL_i)); do
182         LFBFL_digit=$((LFBFL_i % 10))
183         LFBFL_file_path+="${LFBFL_digit}"
184         rm --force "${LFBFL_file_path}"
185         rm --force "${LFBFL_file_path}\\.\"
186     done
187 fi
188 }
189
190 upgrade_build_and_checks "$@"

```

3.69 wget_sha512.lib.sh

```

1  #!/usr/bin/env bash
2  # This file is part of DevOrSysAdminScripts.
3  #
4  # DevOrSysAdminScripts is free software:
5  # you can redistribute it and/or modify it
6  # under the terms of the GNU General Public License
7  # as published by the Free Software Foundation,
8  # either version 3 of the License,
9  # or (at your option) any later version.
10 #
11 # DevOrSysAdminScripts is distributed

```

```

12 # in the hope that it will be useful,
13 # but WITHOUT ANY WARRANTY;
14 # without even the implied warranty of
15 # MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
16 # See the GNU General Public License for more details.
17 #
18 # You should have received a copy of
19 # the GNU General Public License
20 # along with DevOrSysAdminScripts.
21 # If not, see <https://www.gnu.org/licenses/>.
22 #
23 # ©Copyright 2023-2026 Laurent Frédéric Bernard François Lyaudet
24 # This file was renamed from "wget_sha512.sh"
25 # to "wget_sha512.lib.sh".
26
27 wget_sha512() {
28     # $1=file_path
29     # $2=download_URL
30     # $3=correct_sha512
31     # Options:
32     #   --check-download=y|keep (=keep to keep the downloaded file)
33     #   --verbose
34     local LFBFL_verbose=""
35     if [[ "$*" == *--verbose* ]]; then
36         printf "%s wget_sha512 %s\n" "$0" "$*"
37         LFBFL_verbose="--verbose"
38     fi
39     readonly LFBFL_verbose
40     local LFBFL_check_download=""
41     if [[ "$*" == *--check-download=keep* ]]; then
42         LFBFL_check_download="keep"
43     elif [[ "$*" == *--check-download=y* ]]; then
44         LFBFL_check_download="y"
45     fi
46     readonly LFBFL_check_download
47     declare -i LFBFL_i_error=0
48
49     if [[ ! -f "$1" ]]; then
50         wget ${LFBFL_verbose:+"${LFBFL_verbose}"} --output-document="$1"\
51             -- "$2"
52     fi
53     declare -r LFBFL_present_sha512=$(
54         sha512sum -- "$1"\
55         | cut --fields=1 --delimiter=' '
56     )
57     if [[ "${LFBFL_present_sha512}" != "$3" ]]; then

```

```

58     printf "%s does not have correct sha512:\n - wanted %s\n - found %s\n"\
59         "$1" "$3" "${LFBFL_present_sha512}"
60     LFBFL_i_error=1
61 fi
62 if [[ -n "${LFBFL_check_download}" ]]; then
63     wget ${LFBFL_verbos:+"${LFBFL_verbos}"}\
64         --output-document="$1.wget_sha512.temp"\
65         -- "$2"
66     declare -r LFBFL_present_sha512_2=$(
67         sha512sum -- "$1.wget_sha512.temp"\
68         | cut --fields=1 --delimiter=' '
69     )
70     if [[ "${LFBFL_check_download}" != "keep" ]]; then
71         rm -- "$1.wget_sha512.temp"
72     fi
73     if [[ "${LFBFL_present_sha512_2}" != "$3" ]]; then
74         printf\
75             "%s does not have correct sha512:\n - wanted %s\n - found %s\n"\
76             "Online version of $1" "$3" "${LFBFL_present_sha512_2}"
77         LFBFL_i_error=1
78     fi
79 fi
80 # shellcheck disable=SC2248
81 return ${LFBFL_i_error}
82 }

```

Merci Dieu ! Merci Père ! Merci Seigneur ! Merci Saint Esprit !