

GraphTheorySymbol: L^AT_EX Commands with Symbols for Graph Theory

Laurent Frédéric Bernard François Lyaudet
Website:<https://lyaudet.eu/laurent/>
Email:Laurent.Lyaudet@gmail.com

v1.5.1 2026/09/13

Abstract

This documentation is for L^AT_EX package GraphTheorySymbol. It provides symbols used in graph theory. The adjacency and incidence symbols, and the meta-logical operators symbols were created by the author of this package.

Contents

1	Introduction	1
2	Usage	2
2.1	Memo or for the impatient	2
2.2	Detailed usage	6
2.2.1	General macros	6
2.2.2	Standard adjacency macros	6
2.2.3	Standard incidence macros	10
2.2.4	Monochrome adjacency macros	13
2.2.5	Monochrome incidence macros	17
2.2.6	Meta-logic macros	20
2.3	Good practices	22
3	Implementation	23
4	Acknowledgments	39
5	Support	39

1 Introduction

This documentation is for L^AT_EX package GraphTheorySymbol. It provides symbols used in graph theory. The adjacency and incidence symbols, and the meta-logical operators symbols were created by the author of this package.

This package is licenced under Lesser GNU General Public License version 3 or later (LGPLv3+). It means you are free do anything with it, but if you do improve the code of the symbols that we provide, please do share these improvements in a similar way. There is no restriction on other graph theory symbols/code, even if it would be a good fit for inclusion in this package. There is also no need to share in a similar way what you build with this package. The text of the licenses is available at:

<https://www.gnu.org/licenses/>.

The git repository of this source code is also available at:

<https://github.com/LLyaudet/GraphTheorySymbol/>.

Clone it with this URL:

[git@github.com:LLyaudet/GraphTheorySymbol.git](https://github.com/LLyaudet/GraphTheorySymbol.git).

This package is available on CTAN:

<https://ctan.org/pkg/graph-theory-symbol>.

This is our first $\text{\LaTeX}$ package. It may be that our macros are quite slow and that a document making extensive use of these macros will be slow to compile. If you know how to produce better $\text{\LaTeX}$ code, please submit a pull request on GitHub.

2 Usage

2.1 Memo or for the impatient

Add in your preamble: `\usepackage{graph-theory-symbol}`.

For clarity, below we only show long macro names and short macro names; see Detailed usage section for intermediate length macro names.

Long name	Short name	Result	In context
<code>\GTSadjacency/</code>	<code>\GTSa/</code>	$\circ$	$u \circ v$
<code>\GTSadjacencyRelation/</code>	<code>\GTSaR/</code>	$\circ$	$u \circ v$
<code>\GTSunadjacency/</code>	<code>\GTSu/</code>	$\circ$	$u \circ v$
<code>\GTSunadjacencyRelation/</code>	<code>\GTSuR/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyUp/</code>	<code>\GTSdAU/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyUpRelation/</code>	<code>\GTSdAUR/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyUp/</code>	<code>\GTSnDAU/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyUpRelation/</code>	<code>\GTSnDAUR/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyDown/</code>	<code>\GTSdAD/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyDownRelation/</code>	<code>\GTSdADR/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyDown/</code>	<code>\GTSnDAD/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyDownRelation/</code>	<code>\GTSnDADR/</code>	$\circ$	$u \circ v$
<code>\GTSincidence/</code>	<code>\GTSi/</code>	$\circ$	$v \circ e$
<code>\GTSincidenceRelation/</code>	<code>\GTSiR/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedIncidence/</code>	<code>\GTSnI/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedIncidenceRelation/</code>	<code>\GTSnIR/</code>	$\circ$	$v \circ e$
<code>\GTSoutIncidence/</code>	<code>\GTSOI/</code>	$\circ$	$v \circ e$
<code>\GTSoutIncidenceRelation/</code>	<code>\GTSOIR/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedOutIncidence/</code>	<code>\GTSnOI/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedOutIncidenceRelation/</code>	<code>\GTSnOIR/</code>	$\circ$	$v \circ e$
<code>\GTSinIncidence/</code>	<code>\GTSiI/</code>	$\circ$	$v \circ e$
<code>\GTSinIncidenceRelation/</code>	<code>\GTSiIR/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedInIncidence/</code>	<code>\GTSnII/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedInIncidenceRelation/</code>	<code>\GTSnIIR/</code>	$\circ$	$v \circ e$

Long name	Short name	Result	In context
\GTSadjacencyMonochrome/	\GTSaM/	$\emptyset$	$u \emptyset v$
\GTSadjacencyMonochromeRelation/	\GTSaMR/	$\emptyset$	$u \emptyset v$
\GTSunadjacencyMonochrome/	\GTSuM/	$\emptyset$	$u \emptyset v$
\GTSunadjacencyMonochromeRelation/	\GTSuMR/	$\emptyset$	$u \emptyset v$
\GTSdirectedAdjacencyUpMonochrome/	\GTSdAUM/	$\emptyset$	$u \emptyset v$
\GTSdirectedAdjacencyUpMonochromeRelation/	\GTSdAUMR/	$\emptyset$	$u \emptyset v$
\GTSnegatedDirectedAdjacencyUpMonochrome/	\GTSnDAUM/	$\emptyset$	$u \emptyset v$
\GTSnegatedDirectedAdjacencyUpMonochromeRelation/	\GTSnDAUMR/	$\emptyset$	$u \emptyset v$
\GTSdirectedAdjacencyDownMonochrome/	\GTSdADM/	$\emptyset$	$u \emptyset v$
\GTSdirectedAdjacencyDownMonochromeRelation/	\GTSdADM/	$\emptyset$	$u \emptyset v$
\GTSnegatedDirectedAdjacencyDownMonochrome/	\GTSnDADM/	$\emptyset$	$u \emptyset v$
\GTSnegatedDirectedAdjacencyDownMonochromeRelation/	\GTSnDADM/	$\emptyset$	$u \emptyset v$
\GTSincidenceMonochrome/	\GTSiM/	$\emptyset$	$v \emptyset e$
\GTSincidenceMonochromeRelation/	\GTSiMR/	$\emptyset$	$v \emptyset e$
\GTSnegatedIncidenceMonochrome/	\GTSnIM/	$\emptyset$	$v \emptyset e$
\GTSnegatedIncidenceMonochromeRelation/	\GTSnIMR/	$\emptyset$	$v \emptyset e$
\GTSoutIncidenceMonochrome/	\GTSoIM/	$\emptyset$	$v \emptyset e$
\GTSoutIncidenceMonochromeRelation/	\GTSoIMR/	$\emptyset$	$v \emptyset e$
\GTSnegatedOutIncidenceMonochrome/	\GTSnOIM/	$\emptyset$	$v \emptyset e$
\GTSnegatedOutIncidenceMonochromeRelation/	\GTSnOIMR/	$\emptyset$	$v \emptyset e$
\GTSinIncidenceMonochrome/	\GTSiIM/	$\emptyset$	$v \emptyset e$
\GTSinIncidenceMonochromeRelation/	\GTSiIMR/	$\emptyset$	$v \emptyset e$
\GTSnegatedInIncidenceMonochrome/	\GTSnIIM/	$\emptyset$	$v \emptyset e$
\GTSnegatedInIncidenceMonochromeRelation/	\GTSnIIMR/	$\emptyset$	$v \emptyset e$

\GTSsetMainColor{blue}			
Long name	Short name	Result	In context
\GTSadjacency/	\GTSa/		$u \circ v$
\GTSadjacencyRelation/	\GTSaR/		$u \circ v$
\GTSunadjacency/	\GTSu/		$u \circ v$
\GTSunadjacencyRelation/	\GTSuR/		$u \circ v$
\GTSdirectedAdjacencyUp/	\GTSdAU/		$u \circ v$
\GTSdirectedAdjacencyUpRelation/	\GTSdAUR/		$u \circ v$
\GTSnegatedDirectedAdjacencyUp/	\GTSnDAU/		$u \circ v$
\GTSnegatedDirectedAdjacencyUpRelation/	\GTSnDAUR/		$u \circ v$
\GTSdirectedAdjacencyDown/	\GTSdAD/		$u \circ v$
\GTSdirectedAdjacencyDownRelation/	\GTSdADR/		$u \circ v$
\GTSnegatedDirectedAdjacencyDown/	\GTSnDAD/		$u \circ v$
\GTSnegatedDirectedAdjacencyDownRelation/	\GTSnDADR/		$u \circ v$
\GTSincidence/	\GTSi/		$v \circ e$
\GTSincidenceRelation/	\GTSiR/		$v \circ e$
\GTSnegatedIncidence/	\GTSnI/		$v \circ e$
\GTSnegatedIncidenceRelation/	\GTSnIR/		$v \circ e$
\GTSoutIncidence/	\GTSOI/		$v \circ e$
\GTSoutIncidenceRelation/	\GTSOIR/		$v \circ e$
\GTSnegatedOutIncidence/	\GTSnOI/		$v \circ e$
\GTSnegatedOutIncidenceRelation/	\GTSnOIR/		$v \circ e$
\GTSinIncidence/	\GTSiI/		$v \circ e$
\GTSinIncidenceRelation/	\GTSiIR/		$v \circ e$
\GTSnegatedInIncidence/	\GTSnII/		$v \circ e$
\GTSnegatedInIncidenceRelation/	\GTSnIIR/		$v \circ e$

Long name	Short name	Result	In context
\GTSmetaNot/	\GTSmN/	$\neg$	$\neg$
\GTSmetaAnd/	\GTSmA/	$\wedge$	$\wedge$
\GTSmetaOr/	\GTSmO/	$\vee$	$\vee$

Implicit meta-and via concatenation, no space except around whole relations compositions, no parentheses via higher priority to meta-and, brackets when all possible adjacencies are specified between two vertices:

Tournament adjacency:

$\forall u, v, u \circ v$

Tournament adjacency with maybe some colored edge also, who knows?:

$\forall u, v, u \circ v$

Directed graph:

$\forall u, v, u \circ v$

Oriented graph:

$\forall u, v, u \circ v$

Prefix notation:

$\exists u, v, u \circ v$

$\exists v, e, v \circ e$

Apart from these symbol macros, versatile macros to call them all are available with options:
 $\backslash\text{GTSx}\text{a}[]$, $\backslash\text{GTSx}\text{adj}[]$, or $\backslash\text{GTSx}\text{adjacency}[]$ for adjacency symbols,
 $\backslash\text{GTSx}\text{i}[]$, $\backslash\text{GTSx}\text{inc}[]$, or $\backslash\text{GTSx}\text{incidence}[]$ for incidence symbols,
 $\backslash\text{GTSx}\text{ml}[]$, or $\backslash\text{GTSx}\text{metallogic}[]$ for meta-logic symbols,
 $\backslash\text{GTSx}[]\{\}$ for all symbols
 $(\backslash\text{GTSx}[]\{\text{a}\} = \backslash\text{GTSx}\text{a}[], \backslash\text{GTSx}[]\{\text{i}\} = \backslash\text{GTSx}\text{i}[], \backslash\text{GTSx}[]\{\text{m}\} = \backslash\text{GTSx}\text{ml}[])$.
See Detailed usage section for full syntax of these macros.

2.2 Detailed usage

First you need to add in your preamble: `\usepackage{graph-theory-symbol}`.

All symbols macros were designed with ease of use in mind: they are called with a trailing slash, they can be called in text mode or in math mode, a variant with relation spacing for math mode exists with suffix “relation”.

2.2.1 General macros

\GTS@newcommand This macro will enforce that the other macros are called with a trailing slash, avoiding problems with spaces after macro call.

Arguments:

`{\commandname}` The name of the command to create.

`{\commandcode}` The code of the command to create.

\GTS@newprotectedcommand This macro will enforce that the other macros are called with a trailing slash, avoiding problems with spaces after macro call.

Arguments:

`{\commandname}` The name of the command to create.

`{\commandcode}` The code of the command to create.

\GTSsetMainColor This macro will set the main color used in GraphTheorySymbol. This color has initial value “black”.

Argument:

`{\color}` The color that must be used by GraphTheorySymbol afterward.

\GTSsetSecondColor This macro will set the second color used in GraphTheorySymbol. This color has initial value “gray”.

Argument:

`{\color}` The color that must be used by GraphTheorySymbol afterward.

2.2.2 Standard adjacency macros

\GTS@a This macro will draw any of the adjacency symbols if the correct arguments are given. It is not expected to be used directly. See the macros derived from it and **\GTS@b**: **\GTSxadjacency**, **\GTSxadj**, and **\GTSxa**.

Arguments:

`{\mainColor}` If non-empty, this color will be used as main color.

`{\secondColor}` If non-empty, this color will be used as second color.

`{\drawSlash}` Non-empty implies that a negation will be drawn.

`{\drawUpArrow}` Non-empty implies that an up-arrow will be drawn.

`{\drawDownArrow}` Non-empty implies that a down-arrow will be drawn.

\GTS@b This macro builds on top of **\GTS@a** to handle mathematical relation spacing if sixth argument is not empty. It is not expected to be used directly. See the macros derived from it and **\GTS@a**: **\GTSxadjacency**, **\GTSxadj**, and **\GTSxa**.

Arguments:

`{\mainColor}` If non-empty, this color will be used as main color.

`{\secondColor}` If non-empty, this color will be used as second color.

$\{\langle drawSlash \rangle\}$ Non-empty implies that a negation will be drawn.
 $\{\langle drawUpArrow \rangle\}$ Non-empty implies that an up-arrow will be drawn.
 $\{\langle drawDownArrow \rangle\}$ Non-empty implies that a down-arrow will be drawn.
 $\{\langle relation \rangle\}$ Non-empty implies that relation spacing will be added.

\GTSxadjacency, \GTSxadj, \GTSxa Versatile macros for adjacency that can be given options.

Argument:

$[\langle optionsList \rangle]$ Sets the following options if not empty:
`mainColor=color1` or `mainC=color1` or `mColor=color1` or `mC=color1`,
`secondColor=color2` or `secondC=color2` or `sColor=color2` or `sC=color2`,
`monochrome` or `mono` or `mon` or `m` (equivalent to `mC=black,sC=black`),
`negated` or `not` or `n`,
`up` or `u`,
`down` or `d`,
`relation` or `rel` or `r`.

\GTSadjacency, \GTSadj, \GTSa This macro will draw an adjacency symbol. A first drawing didn't include the small dots in the middle of the two circles corresponding to the graph vertices. But it was too similar to “spoon” and multimap symbols, and could be confused with a graph with only two vertices and one edge. Hence, these dots were added and they have the nice property to remind of the classical textual notation of adjacency relation as $\text{Adj}(.,.)$.

`A.\GTSadjacency/A.`

or `A.\GTSadj/A.`

or `A.\GTSa/A.`

will yield $A.\circ A.$

`u \GTSadjacency/ v`

or `u \GTSadj/ v`

or `u \GTSa/ v`

will yield $u \circ v$.

`$u \GTSadjacency/ v$`

or `$u \GTSadj/ v$`

or `$u \GTSa/ v$`

will yield $u \circ v$.

\GTSadjacencyRelation, \GTSadjRel, \GTSaR This macro will draw an adjacency symbol.

`$u\GTSadjacencyRelation/v$`

or `$u\GTSadjRel/v$`

or `$u\GTSaR/v$`

will yield $u \circ v$.

\GTSunadjacency, \GTSunadj, \GTSu This macro will draw an unadjacency symbol.

`A.\GTSunadjacency/A.`

or `A.\GTSunadj/A.`

or `A.\GTSu/A.`

will yield $A.\circ A.$

`u \GTSunadjacency/ v`

`or u \GTSunadj/ v`
`or u \GTSu/ v`
 will yield $u \int v$.
`$u \GTSunadjacency/ v$`
`or $u \GTSunadj/ v$`
`or $u \GTSu/ v$`
 will yield $u \int v$.

`\GTSunadjacencyRelation, \GTSunadjRel, \GTSuR` This macro will draw an unadjacency symbol.

`$u \GTSunadjacencyRelation/ v$`
`or $u \GTSunadjRel/ v$`
`or $u \GTSuR/ v$`
 will yield $u \int v$.

`\GTSdirectedAdjacencyUp, \GTSdirAdjUp, \GTSdAU` This macro will draw a directed adjacency upward symbol. The operand on the left of the symbol should be considered the source of the arc; the operand on the right of the symbol should be considered the target of the arc.

`A. \GTSdirectedAdjacencyUp/ A.`
`or A. \GTSdirAdjUp/ A.`
`or A. \GTSdAU/ A.`
 will yield $A. \int A.$
`u \GTSdirectedAdjacencyUp/ v`
`or u \GTSdirAdjUp/ v`
`or u \GTSdAU/ v`
 will yield $u \int v$.
`$u \GTSdirectedAdjacencyUp/ v$`
`or $u \GTSdirAdjUp/ v$`
`or $u \GTSdAU/ v$`
 will yield $u \int v$.

`\GTSdirectedAdjacencyUpRelation, \GTSdirAdjUpRel, \GTSdAUR` This macro will draw a directed adjacency upward symbol with relation spacing in math mode.

`$u \GTSdirectedAdjacencyUpRelation/ v$`
`or $u \GTSdirAdjUpRel/ v$`
`or $u \GTSdAUR/ v$`
 will yield $u \int v$.

`\GTSnegatedDirectedAdjacencyUp, \GTSnegDirAdjUp, \GTSnDAU` This macro will draw a negated directed adjacency upward symbol.

`A. \GTSnegatedDirectedAdjacencyUp/ A.`
`or A. \GTSnegDirAdjUp/ A.`
`or A. \GTSnDAU/ A.`
 will yield $A. \int A.$
`u \GTSnegatedDirectedAdjacencyUp/ v`
`or u \GTSnegDirAdjUp/ v`
`or u \GTSnDAU/ v`

will yield $u \overset{\curvearrowright}{\sim} v$.
 $\$u \backslash\text{GTSnegatedDirectedAdjacencyUp}/ v\$$
or $\$u \backslash\text{GTSnegDirAdjUp}/ v\$$
or $\$u \backslash\text{GTSnDAU}/ v\$$
will yield $u \overset{\curvearrowright}{\sim} v$.

$\backslash\text{GTSnegatedDirectedAdjacencyUpRelation}$, $\backslash\text{GTSnegDirAdjUpRel}$, $\backslash\text{GTSnDAUR}$
This macro will draw a negated directed adjacency upward symbol with relation spacing in math mode.

$\$u \backslash\text{GTSnegatedDirectedAdjacencyUpRelation}/ v\$$
or $\$u \backslash\text{GTSnegDirAdjUpRel}/ v\$$
or $\$u \backslash\text{GTSnDAUR}/ v\$$
will yield $u \overset{\curvearrowright}{\sim} v$.

$\backslash\text{GTSdirectedAdjacencyDown}$, $\backslash\text{GTSdirAdjDown}$, $\backslash\text{GTSdAD}$ This macro will draw a directed adjacency downward symbol. The operand on the left of the symbol should be considered the target of the arc; the operand on the right of the symbol should be considered the source of the arc.

$A.\backslash\text{GTSdirectedAdjacencyDown}/ A.$
or $A.\backslash\text{GTSdirAdjDown}/ A.$
or $A.\backslash\text{GTSnDAD}/ A.$
will yield $A.\overset{\curvearrowright}{\sim} A.$
 $u \backslash\text{GTSdirectedAdjacencyDown}/ v$
or $u \backslash\text{GTSdirAdjDown}/ v$
or $u \backslash\text{GTSnDAD}/ v$
will yield $u \overset{\curvearrowright}{\sim} v$.
 $\$u \backslash\text{GTSdirectedAdjacencyDown}/ v\$$
or $\$u \backslash\text{GTSdirAdjDown}/ v\$$
or $\$u \backslash\text{GTSnDAD}/ v\$$
will yield $u \overset{\curvearrowright}{\sim} v$.

$\backslash\text{GTSdirectedAdjacencyDownRelation}$, $\backslash\text{GTSdirAdjDownRel}$, $\backslash\text{GTSdADR}$ This macro will draw a directed adjacency downward symbol with relation spacing in math mode.

$\$u \backslash\text{GTSdirectedAdjacencyDownRelation}/ v\$$
or $\$u \backslash\text{GTSdirAdjDownRel}/ v\$$
or $\$u \backslash\text{GTSdADR}/ v\$$
will yield $u \overset{\curvearrowright}{\sim} v$.

$\backslash\text{GTSnegatedDirectedAdjacencyDown}$, $\backslash\text{GTSnegDirAdjDown}$, $\backslash\text{GTSnDAD}$ This macro will draw a negated directed adjacency downward symbol.

$A.\backslash\text{GTSnegatedDirectedAdjacencyDown}/ A.$
or $A.\backslash\text{GTSnegDirAdjDown}/ A.$
or $A.\backslash\text{GTSnDAD}/ A.$
will yield $A.\overset{\curvearrowright}{\sim} A.$
 $u \backslash\text{GTSnegatedDirectedAdjacencyDown}/ v$
or $u \backslash\text{GTSnegDirAdjDown}/ v$
or $u \backslash\text{GTSnDAD}/ v$
will yield $u \overset{\curvearrowright}{\sim} v$.

`\GTSnegatedDirectedAdjacencyDown/ v$`
or `\GTSnegDirAdjDown/ v$`
or `\GTSnDAD/ v$`
will yield $u \nrightarrow v$.

`\GTSnegatedDirectedAdjacencyDownRelation, \GTSnegDirAdjDownRel, \GTSnDADR`
This macro will draw a negated directed adjacency downward symbol with relation spacing in math mode.

`\GTSnegatedDirectedAdjacencyDownRelation/v$`
or `\GTSnegDirAdjDownRel/v$`
or `\GTSnDADR/v$`
will yield $u \nrightarrow v$.

2.2.3 Standard incidence macros

`\GTS@i` This macro will draw any of the incidence symbols if the correct arguments are given. It is not expected to be used directly. See the macros derived from it and `\GTS@j`: `\GTSxincidence`, `\GTSxinc`, and `\GTSxi`. The operand on the left of the symbol should be considered the vertex to which the edge/the operand on the right of the symbol is incident.

Arguments:

`{\mainColor}` If non-empty, this color will be used as main color.
`{\secondColor}` If non-empty, this color will be used as second color.
`{\drawSlash}` Non-empty implies that a negation will be drawn.
`{\drawUpArrow}` Non-empty implies that an up-arrow will be drawn.
`{\drawDownArrow}` Non-empty implies that a down-arrow will be drawn.

`\GTS@j` This macro builds on top of `\GTS@i` to handle mathematical relation spacing if sixth argument is not empty. It is not expected to be used directly. See the macros derived from it and `\GTS@i`: `\GTSxincidence`, `\GTSxinc`, and `\GTSxi`.

Arguments:

`{\mainColor}` If non-empty, this color will be used as main color.
`{\secondColor}` If non-empty, this color will be used as second color.
`{\drawSlash}` Non-empty implies that a negation will be drawn.
`{\drawUpArrow}` Non-empty implies that an up-arrow will be drawn.
`{\drawDownArrow}` Non-empty implies that a down-arrow will be drawn.
`{\relation}` Non-empty implies that relation spacing will be added.

`\GTSxincidence, \GTSxinc, \GTSxi` Versatile macros for incidence that can be given options.

Argument:

`[\optionsList]` Sets the following options if not empty:
`mainColor=color1` or `mainC=color1` or `mColor=color1` or `mC=color1`,
`secondColor=color2` or `secondC=color2` or `sColor=color2` or `sC=color2`,
`monochrome` or `mono` or `mon` or `m` (equivalent to `mC=black,sC=black`),
`negated` or `not` or `n`,
`in` or `i`,
`out` or `o`,
`relation` or `rel` or `r`.

\GTSincidence, \GTSinc, \GTSi This macro will draw an incidence symbol. The operand on the left of the symbol should be considered the vertex to which the edge/the operand on the right of the symbol is incident.

A.\GTSincidence/A.

or **A.\GTSinc/A.**

or **A.\GTSi/A.**

will yield $A \downarrow A$.

v \GTSincidence/ e

or **v \GTSinc/ e**

or **v \GTSi/ e**

will yield $v \downarrow e$.

\$v \GTSincidence/ e\$

or **\$v \GTSinc/ e\$**

or **\$v \GTSi/ e\$**

will yield $v \downarrow e$.

\GTSincidenceRelation, \GTSincRel, \GTSiR This macro will draw an incidence symbol with relation spacing in math mode.

\$v\GTSincidenceRelation/e\$

or **\$v\GTSincRel/e\$**

or **\$v\GTSiR/e\$**

will yield $v \downarrow e$.

\GTSnegatedIncidence, \GTSnegInc, \GTSnI This macro will draw a negated incidence symbol.

A.\GTSnegatedIncidence/A.

or **A.\GTSnegInc/A.**

or **A.\GTSnI/A.**

will yield $A \not\downarrow A$.

v \GTSnegatedIncidence/ e

or **v \GTSnegInc/ e**

or **v \GTSnI/ e**

will yield $v \not\downarrow e$.

\$v \GTSnegatedIncidence/ e\$

or **\$v \GTSnegInc/ e\$**

or **\$v \GTSnI/ e\$**

will yield $v \not\downarrow e$.

\GTSnegatedIncidenceRelation, \GTSnegIncRel, \GTSnIR This macro will draw a negated incidence symbol with relation spacing in math mode.

\$v\GTSnegatedIncidenceRelation/e\$

or **\$v\GTSnegIncRel/e\$**

or **\$v\GTSnIR/e\$**

will yield $v \not\downarrow e$.

\GTSoutIncidence, \GTSoutInc, \GTSoI This macro will draw a directed incidence upward (out(ward) incidence) symbol. The operand on the left of the symbol should be considered the vertex to which the arc/the operand on the right of the symbol is incident.

$A.\backslash\text{GTSoutIncidence}/A.$
or $A.\backslash\text{GTSoutInc}/A.$
or $A.\backslash\text{GTSOI}/A.$
will yield $A.\overset{\circ}{\hookrightarrow}A.$
 $v\ \backslash\text{GTSoutIncidence}/\ e$
or $v\ \backslash\text{GTSoutInc}/\ e$
or $v\ \backslash\text{GTSOI}/\ e$
will yield $v\ \overset{\circ}{\hookrightarrow}e.$
 $\$v\ \backslash\text{GTSoutIncidence}/\ e\$$
or $\$v\ \backslash\text{GTSoutInc}/\ e\$$
or $\$v\ \backslash\text{GTSOI}/\ e\$$
will yield $v\overset{\circ}{\hookrightarrow}e.$

$\backslash\text{GTSoutIncidenceRelation}, \backslash\text{GTSoutIncRel}, \backslash\text{GTSOI}$ This macro will draw a directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.
 $\$v\backslash\text{GTSoutIncidenceRelation}/e\$$
or $\$v\backslash\text{GTSoutIncRel}/e\$$
or $\$v\backslash\text{GTSOI}/e\$$
will yield $v\overset{\circ}{\hookrightarrow}e.$

$\backslash\text{GTSnegatedOutIncidence}, \backslash\text{GTSnegOutInc}, \backslash\text{GTSnOI}$ This macro will draw a negated directed incidence upward (out(ward) incidence) symbol.
 $A.\backslash\text{GTSnegatedOutIncidence}/A.$
or $A.\backslash\text{GTSnegOutInc}/A.$
or $A.\backslash\text{GTSnOI}/A.$
will yield $A.\overset{\circ}{\nrightarrow}A.$
 $v\ \backslash\text{GTSnegatedOutIncidence}/\ e$
or $v\ \backslash\text{GTSnegOutInc}/\ e$
or $v\ \backslash\text{GTSnOI}/\ e$
will yield $v\ \overset{\circ}{\nrightarrow}e.$
 $\$v\ \backslash\text{GTSnegatedOutIncidence}/\ e\$$
or $\$v\ \backslash\text{GTSnegOutInc}/\ e\$$
or $\$v\ \backslash\text{GTSnOI}/\ e\$$
will yield $v\overset{\circ}{\nrightarrow}e.$

$\backslash\text{GTSnegatedOutIncidenceRelation}, \backslash\text{GTSnegOutIncRel}, \backslash\text{GTSnOIR}$ This macro will draw a negated directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.
 $\$v\backslash\text{GTSnegatedOutIncidenceRelation}/e\$$
or $\$v\backslash\text{GTSnegOutIncRel}/e\$$
or $\$v\backslash\text{GTSnOIR}/e\$$
will yield $v\overset{\circ}{\nrightarrow}e.$

$\backslash\text{GTSinIncidence}, \backslash\text{GTSinInc}, \backslash\text{GTSiI}$ This macro will draw a directed incidence downward (in(ward) incidence) symbol. The operand on the left of the symbol should be considered the vertex to which the arc/the operand on the right of the symbol is incident.
 $A.\backslash\text{GTSinIncidence}/A.$
or $A.\backslash\text{GTSinInc}/A.$

`or A.\GTSiI/A.`
 will yield $A.\mathrel{\mathcal{G}}A.$
`v \GTSinIncidence/ e`
`or v \GTSinInc/ e`
`or v \GTSiI/ e`
 will yield $v \mathrel{\mathcal{G}} e.$
`$v \GTSinIncidence/ e$`
`or $v \GTSinInc/ e$`
`or $v \GTSiI/ e$`
 will yield $v \mathrel{\mathcal{G}} e.$

`\GTSinIncidenceRelation`, `\GTSinIncRel`, `\GTSiIR` This macro will draw a directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.
`$v\GTSinIncidenceRelation/e$`
`or $v\GTSinIncRel/e$`
`or $v\GTSiIR/e$`
 will yield $v \mathrel{\mathcal{G}} e.$

`\GTSnegatedInIncidence`, `\GTSnegInInc`, `\GTSnII` This macro will draw a negated directed incidence downward (in(ward) incidence) symbol.
`A.\GTSnegatedInIncidence/A.`
`or A.\GTSnegInInc/A.`
`or A.\GTSnII/A.`
 will yield $A.\mathrel{\mathcal{G}}A.$
`v \GTSnegatedInIncidence/ e`
`or v \GTSnegInInc/ e`
`or v \GTSnII/ e`
 will yield $v \mathrel{\mathcal{G}} e.$
`$v \GTSnegatedInIncidence/ e$`
`or $v \GTSnegInInc/ e$`
`or $v \GTSnII/ e$`
 will yield $v \mathrel{\mathcal{G}} e.$

`\GTSnegatedInIncidenceRelation`, `\GTSnegInIncRel`, `\GTSnIIR` This macro will draw a negated directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.
`$v\GTSnegatedInIncidenceRelation/e$`
`or $v\GTSnegInIncRel/e$`
`or $v\GTSnIIR/e$`
 will yield $v \mathrel{\mathcal{G}} e.$

2.2.4 Monochrome adjacency macros

`\GTSadjacencyMonochrome`, `\GTSadjMono`, `\GTSadjMon`, `\GTSaM` This macro will draw a monochrome adjacency symbol.
`A.\GTSadjacencyMonochrome/A.`
`or A.\GTSadjMono/A.`
`or A.\GTSadjMon/A.`
`or A.\GTSaM/A.`

will yield $A \circ A$.
 $\text{u \GTSadjacencyMonochrome/ v}$
or $\text{u \GTSadjMono/ v}$
or $\text{u \GTSadjMon/ v}$
or $\text{u \GTSaM/ v}$
will yield $u \circ v$.
 $\text{\$u \GTSadjacencyMonochrome/ v\$}$
or $\text{\$u \GTSadjMono/ v\$}$
or $\text{\$u \GTSadjMon/ v\$}$
or $\text{\$u \GTSaM/ v\$}$
will yield $u \circ v$.

\GTSadjacencyMonochromeRelation, \GTSadjMonoRel, \GTSadjMonRel, \GT-SaMR This macro will draw a monochrome adjacency symbol with relation spacing in math mode.

$\text{\$u \GTSadjacencyMonochromeRelation/v\$}$
or $\text{\$u \GTSadjMonoRel/v\$}$
or $\text{\$u \GTSadjMonRel/v\$}$
or $\text{\$u \GTSaMR/v\$}$
will yield $u \circ v$.

\GTSunadjacencyMonochrome, \GTSunadjMono, \GTSunadjMon, \GTSuM This macro will draw a monochrome unadjacency symbol.

$\text{A. \GTSunadjacencyMonochrome/A.}$
or $\text{A. \GTSunadjMono/A.}$
or $\text{A. \GTSunadjMon/A.}$
or $\text{A. \GTSuM/A.}$
will yield $A \circ A$.
 $\text{u \GTSunadjacencyMonochrome/ v}$
or $\text{u \GTSunadjMono/ v}$
or $\text{u \GTSunadjMon/ v}$
or $\text{u \GTSuM/ v}$
will yield $u \circ v$.
 $\text{\$u \GTSunadjacencyMonochrome/ v\$}$
or $\text{\$u \GTSunadjMono/ v\$}$
or $\text{\$u \GTSunadjMon/ v\$}$
or $\text{\$u \GTSuM/ v\$}$
will yield $u \circ v$.

\GTSunadjacencyMonochromeRelation, \GTSunadjMonoRel, \GTSunadjMonRel, \GTSuMR This macro will draw a monochrome unadjacency symbol with relation spacing in math mode.

$\text{\$u \GTSunadjacencyMonochromeRelation/v\$}$
or $\text{\$u \GTSunadjMonoRel/v\$}$
or $\text{\$u \GTSunadjMonRel/v\$}$
or $\text{\$u \GTSuMR/v\$}$
will yield $u \circ v$.

\GTSdirectedAdjacencyUpMonochrome, \GTSdirAdjUpMono, \GTSdirAdjUpMon, \GTSdAUM This macro will draw a monochrome directed adjacency upward symbol. The operand on the left of the symbol should be considered the source of the arc; the operand on the right of the symbol should be considered the target of the arc.

A.\GTSdirectedAdjacencyUpMonochrome/A.
or A.\GTSdirAdjUpMono/A.
or A.\GTSdirAdjUpMon/A.
or A.\GTSdAUM/A.
will yield $A \circ A$.
u \GTSdirectedAdjacencyUpMonochrome/ v
or u \GTSdirAdjUpMono/ v
or u \GTSdirAdjUpMon/ v
or u \GTSdAUM/ v
will yield $u \circ v$.
\$u \GTSdirectedAdjacencyUpMonochrome/ v\$
or \$u \GTSdirAdjUpMono/ v\$
or \$u \GTSdirAdjUpMon/ v\$
or \$u \GTSdAUM/ v\$
will yield $u \circ v$.

\GTSdirectedAdjacencyUpMonochromeRelation, \GTSdirAdjUpMonoRel, \GTSdirAdjUpMonRel, \GTSdAUMR This macro will draw a monochrome directed adjacency upward symbol with relation spacing in math mode.

\$u\GTSdirectedAdjacencyUpMonochromeRelation/v\$
or \$u\GTSdirAdjUpMonoRel/v\$
or \$u\GTSdirAdjUpMonRel/v\$
or \$u\GTSdAUMR/v\$
will yield $u \circ v$.

\GTSnegatedDirectedAdjacencyUpMonochrome, \GTSnegDirAdjUpMono, \GTSnegDirAdjUpMon, \GTSnDAUM This macro will draw a monochrome negated directed adjacency upward symbol.

A.\GTSnegatedDirectedAdjacencyUpMonochrome/A.
or A.\GTSnegDirAdjUpMono/A.
or A.\GTSnegDirAdjUpMon/A.
or A.\GTSnDAUM/A.
will yield $A \circ A$.
u \GTSnegatedDirectedAdjacencyUpMonochrome/ v
or u \GTSnegDirAdjUpMono/ v
or u \GTSnegDirAdjUpMon/ v
or u \GTSnDAUM/ v
will yield $u \circ v$.
\$u \GTSnegatedDirectedAdjacencyUpMonochrome/ v\$
or \$u \GTSnegDirAdjUpMono/ v\$
or \$u \GTSnegDirAdjUpMon/ v\$
or \$u \GTSnDAUM/ v\$
will yield $u \circ v$.

\GTSnegatedDirectedAdjacencyUpMonochromeRelation, \GTSnegDirAdjUpMonoRel,

\GTSnegDirAdjUpMonRel, \GTSnDAUMR This macro will draw a monochrome negated directed adjacency upward symbol with relation spacing in math mode.

$\$u\backslash\text{GTSnegatedDirectedAdjacencyUpMonochromeRelation}/v\$$

or $\$u\backslash\text{GTSnegDirAdjUpMonoRel}/v\$$

or $\$u\backslash\text{GTSnegDirAdjUpMonRel}/v\$$

or $\$u\backslash\text{GTSnDAUMR}/v\$$

will yield $u \overset{\circ}{\rightharpoonup} v$.

\GTSdirectedAdjacencyDownMonochrome, \GTSdirAdjDownMono, \GTSdirAdjDownMon, \GTSdADM This macro will draw a monochrome directed adjacency downward symbol. The operand on the left of the symbol should be considered the target of the arc; the operand on the right of the symbol should be considered the source of the arc.

$A.\backslash\text{GTSdirectedAdjacencyDownMonochrome}/A.$

or $A.\backslash\text{GTSdirAdjDownMono}/A.$

or $A.\backslash\text{GTSdirAdjDownMon}/A.$

or $A.\backslash\text{GTSdADM}/A.$

will yield $A.\overset{\circ}{\rightharpoonup}A.$

$u \backslash\text{GTSdirectedAdjacencyDownMonochrome}/ v$

or $u \backslash\text{GTSdirAdjDownMono}/ v$

or $u \backslash\text{GTSdirAdjDownMon}/ v$

or $u \backslash\text{GTSdADM}/ v$

will yield $u \overset{\circ}{\rightharpoonup} v$.

$\$u \backslash\text{GTSdirectedAdjacencyDownMonochrome}/ v\$$

or $\$u \backslash\text{GTSdirAdjDownMono}/ v\$$

or $\$u \backslash\text{GTSdirAdjDownMon}/ v\$$

or $\$u \backslash\text{GTSdADM}/ v\$$

will yield $u \overset{\circ}{\rightharpoonup} v$.

\GTSdirectedAdjacencyDownMonochromeRelation, \GTSdirAdjDownMonoRel, \GTSdirAdjDownMonRel, \GTSdADMR This macro will draw a monochrome directed adjacency downward symbol with relation spacing in math mode.

$\$u\backslash\text{GTSdirectedAdjacencyDownMonochromeRelation}/v\$$

or $\$u\backslash\text{GTSdirAdjDownMonoRel}/v\$$

or $\$u\backslash\text{GTSdirAdjDownMonRel}/v\$$

or $\$u\backslash\text{GTSdADMR}/v\$$

will yield $u \overset{\circ}{\rightharpoonup} v$.

\GTSnegatedDirectedAdjacencyDownMonochrome, \GTSnegDirAdjDownMono, \GTSnegDirAdjDownMon, \GTSnDADM This macro will draw a monochrome negated directed adjacency downward symbol.

$A.\backslash\text{GTSnegatedDirectedAdjacencyDownMonochrome}/A.$

or $A.\backslash\text{GTSnegDirAdjDownMono}/A.$

or $A.\backslash\text{GTSnegDirAdjDownMon}/A.$

or $A.\backslash\text{GTSnDADM}/A.$

will yield $A.\overset{\circ}{\nrightarrow}A.$

$u \backslash\text{GTSnegatedDirectedAdjacencyDownMonochrome}/ v$

or $u \backslash\text{GTSnegDirAdjDownMono}/ v$

or $u \backslash\text{GTSnegDirAdjDownMon}/ v$

or $u \backslash\text{GTSnDADM}/ v$

will yield $u \overset{\circ}{\circ} v$.
`$u \GTSnegatedDirectedAdjacencyDownMonochrome/ v$`
or `$u \GTSnegDirAdjDownMono/ v$`
or `$u \GTSnegDirAdjDownMon/ v$`
or `$u \GTSnDADM/ v$`
will yield $u \overset{\circ}{\circ} v$.

`\GTSnegatedDirectedAdjacencyDownMonochromeRelation`, `\GTSnegDirAdjDownMonoRel`, `\GTSnegDirAdjDownMonRel`, `\GTSnDADMR` This macro will draw a monochrome negated directed adjacency downward symbol with relation spacing in math mode.
`$u \GTSnegatedDirectedAdjacencyDownMonochromeRelation/v$`
or `$u \GTSnegDirAdjDownMonoRel/v$`
or `$u \GTSnegDirAdjDownMonRel/v$`
or `$u \GTSnDADMR/v$`
will yield $u \overset{\circ}{\circ} v$.

2.2.5 Monochrome incidence macros

`\GTSincidenceMonochrome`, `\GTSincMono`, `\GTSincMon`, `\GTSiM` This macro will draw a monochrome incidence symbol. The operand on the left of the symbol should be considered the vertex to which the edge/the operand on the right of the symbol is incident.

`A.\GTSincidenceMonochrome/A.`
or `A.\GTSincMono/A.`
or `A.\GTSincMon/A.`
or `A.\GTSiM/A.`
will yield $A \downarrow A$.
`v \GTSincidenceMonochrome/ e`
or `v \GTSincMono/ e`
or `v \GTSincMon/ e`
or `v \GTSiM/ e`
will yield $v \downarrow e$.
`$v \GTSincidenceMonochrome/ e$`
or `$v \GTSincMono/ e$`
or `$v \GTSincMon/ e$`
or `$v \GTSiM/ e$`
will yield $v \downarrow e$.

`\GTSincidenceMonochromeRelation`, `\GTSincMonoRel`, `\GTSincMonRel`, `\GTSiMR` This macro will draw a monochrome incidence symbol with relation spacing in math mode.

`$v \GTSincidenceMonochromeRelation/e$`
or `$v \GTSincMonoRel/e$`
or `$v \GTSincMonRel/e$`
or `$v \GTSiMR/e$`
will yield $v \downarrow e$.

`\GTSnegatedIncidenceMonochrome`, `\GTSnegIncMono`, `\GTSnegIncMon`, `\GTSnIM` This macro will draw a monochrome negated incidence symbol.

`A.\GTSnegatedIncidenceMonochrome/A.`

`or A.\GTSnegIncMono/A.`
`or A.\GTSnegIncMon/A.`
`or A.\GTSnIM/A.`
will yield $A \not\bowtie A$.
`v \GTSnegatedIncidenceMonochrome/ e`
`or v \GTSnegIncMono/ e`
`or v \GTSnegIncMon/ e`
`or v \GTSnIM/ e`
will yield $v \not\bowtie e$.
`$v \GTSnegatedIncidenceMonochrome/ e$`
`or $v \GTSnegIncMono/ e$`
`or $v \GTSnegIncMon/ e$`
`or $v \GTSnIM/ e$`
will yield $v \not\bowtie e$.

`\GTSnegatedIncidenceMonochromeRelation, \GTSnegIncMonoRel, \GTSnegIncMonRel, \GTSnIMR` This macro will draw a monochrome negated incidence symbol with relation spacing in math mode.

`$v\GTSnegatedIncidenceMonochromeRelation/e$`
`or $v\GTSnegIncMonoRel/e$`
`or $v\GTSnegIncMonRel/e$`
`or $v\GTSnIMR/e$`
will yield $v \not\bowtie e$.

`\GTSoutIncidenceMonochrome, \GTSoutIncMono, \GTSoutIncMon, \GTSoIM` This macro will draw a monochrome directed incidence upward (out(ward) incidence) symbol. The operand on the left of the symbol should be considered the vertex to which the arc/the operand on the right of the symbol is incident.

`A.\GTSoutIncidenceMonochrome/A.`
`or A.\GTSoutIncMono/A.`
`or A.\GTSoutIncMon/A.`
`or A.\GTSoIM/A.`
will yield $A \not\bowtie A$.
`v \GTSoutIncidenceMonochrome/ e`
`or v \GTSoutIncMono/ e`
`or v \GTSoutIncMon/ e`
`or v \GTSoIM/ e`
will yield $v \not\bowtie e$.
`$v \GTSoutIncidenceMonochrome/ e$`
`or $v \GTSoutIncMono/ e$`
`or $v \GTSoutIncMon/ e$`
`or $v \GTSoIM/ e$`
will yield $v \not\bowtie e$.

`\GTSoutIncidenceMonochromeRelation, \GTSoutIncMonoRel, \GTSoutIncMonRel, \GTSoIMR` This macro will draw a monochrome directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

`$v\GTSoutIncidenceMonochromeRelation/e$`
`or $v\GTSoutIncMonoRel/e$`

or $\$v\backslash\text{GTSoutIncMonRel}/e\$$
or $\$v\backslash\text{GTSOIMR}/e\$$
will yield $v \overset{\curvearrowright}{\circ} e$.

$\backslash\text{GTSnegatedOutIncidenceMonochrome}$, $\backslash\text{GTSnegOutIncMono}$, $\backslash\text{GTSnegOutIncMon}$, $\backslash\text{GTSnOIM}$ This macro will draw a monochrome negated directed incidence upward (out(ward) incidence) symbol.

$A.\backslash\text{GTSnegatedOutIncidenceMonochrome}/A.$
or $A.\backslash\text{GTSnegOutIncMono}/A.$
or $A.\backslash\text{GTSnegOutIncMon}/A.$
or $A.\backslash\text{GTSnOIM}/A.$
will yield $A.\overset{\curvearrowright}{\circ}A.$
 $v \backslash\text{GTSnegatedOutIncidenceMonochrome}/ e$
or $v \backslash\text{GTSnegOutIncMono}/ e$
or $v \backslash\text{GTSnegOutIncMon}/ e$
or $v \backslash\text{GTSnOIM}/ e$
will yield $v \overset{\curvearrowright}{\circ} e$.
 $\$v \backslash\text{GTSnegatedOutIncidenceMonochrome}/ e\$$
or $\$v \backslash\text{GTSnegOutIncMono}/ e\$$
or $\$v \backslash\text{GTSnegOutIncMon}/ e\$$
or $\$v \backslash\text{GTSnOIM}/ e\$$
will yield $v \overset{\curvearrowright}{\circ} e$.

$\backslash\text{GTSnegatedOutIncidenceMonochromeRelation}$, $\backslash\text{GTSnegOutIncMonoRel}$, $\backslash\text{GTSnegOutIncMonRel}$, $\backslash\text{GTSnOIMR}$ This macro will draw a monochrome negated directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

$\$v\backslash\text{GTSnegatedOutIncidenceMonochromeRelation}/e\$$
or $\$v\backslash\text{GTSnegOutIncMonoRel}/e\$$
or $\$v\backslash\text{GTSnegOutIncMonRel}/e\$$
or $\$v\backslash\text{GTSnOIMR}/e\$$
will yield $v \overset{\curvearrowright}{\circ} e$.

$\backslash\text{GTSinIncidenceMonochrome}$, $\backslash\text{GTSinIncMono}$, $\backslash\text{GTSinIncMon}$, $\backslash\text{GTSiIM}$ This macro will draw a monochrome directed incidence downward (in(ward) incidence) symbol. The operand on the left of the symbol should be considered the vertex to which the arc/the operand on the right of the symbol is incident.

$A.\backslash\text{GTSinIncidenceMonochrome}/A.$
or $A.\backslash\text{GTSinIncMono}/A.$
or $A.\backslash\text{GTSinIncMon}/A.$
or $A.\backslash\text{GTSiIM}/A.$
will yield $A.\overset{\curvearrowleft}{\circ}A.$
 $v \backslash\text{GTSinIncidenceMonochrome}/ e$
or $v \backslash\text{GTSinIncMono}/ e$
or $v \backslash\text{GTSinIncMon}/ e$
or $v \backslash\text{GTSiIM}/ e$
will yield $v \overset{\curvearrowleft}{\circ} e$.
 $\$v \backslash\text{GTSinIncidenceMonochrome}/ e\$$
or $\$v \backslash\text{GTSinIncMono}/ e\$$
or $\$v \backslash\text{GTSinIncMon}/ e\$$

or $\$v \backslash \text{GTSiIM}/ e\$$
will yield $v \text{⋈} e$.

$\backslash \text{GTSinIncidenceMonochromeRelation}$, $\backslash \text{GTSinIncMonoRel}$, $\backslash \text{GTSinIncMonRel}$, $\backslash \text{GT-SiIMR}$ This macro will draw a monochrome directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.
 $\$v \backslash \text{GTSinIncidenceMonochromeRelation}/ e\$$
or $\$v \backslash \text{GTSinIncMonoRel}/ e\$$
or $\$v \backslash \text{GTSinIncMonRel}/ e\$$
or $\$v \backslash \text{GTSiIMR}/ e\$$
will yield $v \text{⋈} e$.

$\backslash \text{GTSnegatedInIncidenceMonochrome}$, $\backslash \text{GTSnegInIncMono}$, $\backslash \text{GTSnegInIncMon}$, $\backslash \text{GT-SnIIM}$ This macro will draw a monochrome negated directed incidence downward (in(ward) incidence) symbol.
 $A. \backslash \text{GTSnegatedInIncidenceMonochrome}/ A.$
or $A. \backslash \text{GTSnegInIncMono}/ A.$
or $A. \backslash \text{GTSnegInIncMon}/ A.$
or $A. \backslash \text{GTSnIIM}/ A.$
will yield $A. \text{⋈} A$.
 $v \backslash \text{GTSnegatedInIncidenceMonochrome}/ e$
or $v \backslash \text{GTSnegInIncMono}/ e$
or $v \backslash \text{GTSnegInIncMon}/ e$
or $v \backslash \text{GTSnIIM}/ e$
will yield $v \text{⋈} e$.
 $\$v \backslash \text{GTSnegatedInIncidenceMonochrome}/ e\$$
or $\$v \backslash \text{GTSnegInIncMono}/ e\$$
or $\$v \backslash \text{GTSnegInIncMon}/ e\$$
or $\$v \backslash \text{GTSnIIM}/ e\$$
will yield $v \text{⋈} e$.

$\backslash \text{GTSnegatedInIncidenceMonochromeRelation}$, $\backslash \text{GTSnegInIncMonoRel}$, $\backslash \text{GTSnegInIncMonRel}$, $\backslash \text{GTSnIIMR}$ This macro will draw a monochrome negated directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.
 $\$v \backslash \text{GTSnegatedInIncidenceMonochromeRelation}/ e\$$
or $\$v \backslash \text{GTSnegInIncMonoRel}/ e\$$
or $\$v \backslash \text{GTSnegInIncMonRel}/ e\$$
or $\$v \backslash \text{GTSnIIMR}/ e\$$
will yield $v \text{⋈} e$.

2.2.6 Meta-logic macros

$\backslash \text{GTSMetaNot}$, $\backslash \text{GTSMN}$ This macro will draw a meta-not or relation-not symbol.
 $A. \backslash \text{GTSMetaNot}/ A.$
or $A. \backslash \text{GTSMN}/ A.$
will yield $A. \text{⋈} A$.
 $u \backslash \text{GTSMetaNot}/ \backslash \text{GTSdAU}/ v$
or $u \backslash \text{GTSMN}/ \backslash \text{GTSdAU}/ v$
will yield $u \text{⋈} v$.

`$u \GTSmetaNot/ \GTSdAU/ v$`
or `$u \GTSmN/ \GTSdAU/ v$`
will yield $u \overset{m}{\neg} v$.

`\GTSmetaAnd, \GTSmA` This macro will draw a meta-and or relations-and symbol. This is your duty to check that all relations have same arity. It should be easy as long as you remain in the realm of graphs/2-structures/binary structures. We didn't use Tarski's notation, since square cup has taken the preemptive meaning of disjoint union. Similarly, doublewedge or other wedge symbols have taken various meanings, whilst we want an unambiguous symbol. Look at the discussion after all logical symbols for less trivial uses and recommendations.

`A.\GTSmetaAnd/A.`
or `A.\GTSmA/A.`
will yield $A \overset{m}{\wedge} A$.
`u \GTSdAD/\GTSmetaAnd/\GTSdAU/ v`
or `u \GTSdAD/\GTSmA/\GTSdAU/ v`
will yield $u \overset{m}{\wedge} v$.
`$u \GTSdAD/ \GTSmetaAnd/ \GTSdAU/ v$`
or `$u \GTSdAD/ \GTSmA/ \GTSdAU/ v$`
will yield $u \overset{m}{\wedge} v$.

`\GTSmetaAndRelation, \GTSmetaAndRel, \GTSmAR` This macro will draw a meta-and symbol with relation spacing in math mode.

`$u \GTSdAD/\GTSmetaAndRelation/\GTSdAU/ v$`
or `$u \GTSdAD/\GTSmetaAndRel/\GTSdAU/ v$`
or `$u \GTSdAD/\GTSmAR/\GTSdAU/ v$`
will yield $u \overset{m}{\wedge} v$.

`\GTSmetaOr, \GTSmO` This macro will draw a meta-or or relations-or symbol. This is your duty to check that all relations have same arity. It should be easy as long as you remain in the realm of graphs/2-structures/binary structures. We didn't use Tarski's notation, since square cup has taken the preemptive meaning of disjoint union. Similarly, doublewedge or other wedge symbols have taken various meanings, whilst we want an unambiguous symbol. Look at the discussion after all logical symbols for less trivial uses and recommendations.

`A.\GTSmetaOr/A.`
or `A.\GTSmO/A.`
will yield $A \overset{m}{\vee} A$.
`u \GTSdAD/\GTSmetaOr/\GTSdAU/ v`
or `u \GTSdAD/\GTSmO/\GTSdAU/ v`
will yield $u \overset{m}{\vee} v$.
`$u \GTSdAD/ \GTSmetaOr/ \GTSdAU/ v$`
or `$u \GTSdAD/ \GTSmO/ \GTSdAU/ v$`
will yield $u \overset{m}{\vee} v$.

`\GTSmetaOrRelation, \GTSmetaOrRel, \GTSmOR` This macro will draw a meta-or symbol with relation spacing in math mode.

`$u \GTSdAD/\GTSmetaOrRelation/\GTSdAU/ v$`
or `$u \GTSdAD/\GTSmetaOrRel/\GTSdAU/ v$`
or `$u \GTSdAD/\GTSmOR/\GTSdAU/ v$`
will yield $u \overset{m}{\vee} v$.

\GTSxmetallogic, \GTSxml Versatile macros for meta-logic symbols that can be given options.

Argument:

[*\optionsList*] Sets the following options if not empty:

not or **n**,

and or **a**,

or or **o**,

relation or **rel** or **r**.

Of course first three options are incompatible, and the fourth is compatible only with the second and third options.

\GTSx One macro to rule them all. Versatile macro for all symbols that can be given options, and a symbol type mandatory switch.

Argument:

[*\optionsList*] Sets the following options if not empty:

- If $\{\langle symbolType \rangle\}$ below is **a**, see **\GTSxa**:
`mainColor=color1` or `mainC=color1` or `mColor=color1` or `mC=color1`,
`secondColor=color2` or `secondC=color2` or `sColor=color2` or `sC=color2`,
`monochrome` or `mono` or `mon` or `m` (equivalent to `mC=black,sC=black`),
`negated` or `not` or `n`,
`up` or `u`,
`down` or `d`,
`relation` or `rel` or `r`.
- If $\{\langle symbolType \rangle\}$ below is **i**, see **\GTSxi**:
`mainColor=color1` or `mainC=color1` or `mColor=color1` or `mC=color1`,
`secondColor=color2` or `secondC=color2` or `sColor=color2` or `sC=color2`,
`monochrome` or `mono` or `mon` or `m` (equivalent to `mC=black,sC=black`),
`negated` or `not` or `n`,
`in` or `i`,
`out` or `o`,
`relation` or `rel` or `r`.
- If $\{\langle symbolType \rangle\}$ below is **m**, see **\GTSxml**:
`not` or `n`,
`and` or `a`,
`or` or `o`,
`relation` or `rel` or `r`.

$\{\langle symbolType \rangle\}$ a mandatory switch; it can take value **a** for adjacency, **i** for incidence, **m** for meta-logic.

2.3 Good practices

As is customary in algebra and logic, the conjunction/multiplication can be replaced by concatenation, and has higher priority than disjunction. So the following formulas are equivalent; we recommend using the shortest one:

Tournament adjacency:

$$\forall u, v, u \overset{m}{\underset{a}{\mathbin{\mathbb{V}}}} v$$


```

19 \@ifdefinable{#1}{\def#1/{#2}}
20 }}

```

This macro will enforce that the other macros are called with a trailing slash, avoiding problems with spaces after macro call.

Arguments:

$\langle commandname \rangle$ The name of the command to create.

$\langle commandcode \rangle$ The code of the command to create.

```

21 \@ifdefinable{\GTS@newprotectedcommand}{\def\GTS@newprotectedcommand#1#2{%
22 \ifdefinable{#1}{\protected\def#1/{#2}}
23 }}

```

This macro will set the main color used in GraphTheorySymbol. This color has initial value “black”.

Argument:

$\langle color \rangle$ The color that must be used by GraphTheorySymbol afterward.

```

24 \newcommand{\GTSsetMainColor}[1]{%
25 \edef\GTS@mainColorTemp{#1}%
26 \edef\GTS@mainColorBackup{\GTS@mainColor}%
27 \edef\GTS@mainColor{\GTS@mainColorTemp}%
28 }

```

This macro will set the second color used in GraphTheorySymbol. This color has initial value “gray”.

Argument:

$\langle color \rangle$ The color that must be used by GraphTheorySymbol afterward.

```

29 \newcommand{\GTSsetSecondColor}[1]{%
30 \edef\GTS@secondColorTemp{#1}%
31 \edef\GTS@secondColorBackup{\GTS@secondColor}%
32 \edef\GTS@secondColor{\GTS@secondColorTemp}%
33 }

```

This macro will draw any adjacency symbol given the correct parameters. Its use is purely technical. See the macros derived from it and $\backslash\text{GTS@b}$: $\backslash\text{GTSxadjacency}$, $\backslash\text{GTSxadj}$, and $\backslash\text{GTSxa}$.

Arguments:

$\langle mainColor \rangle$ If non-empty, this color will be used as main color.

$\langle secondColor \rangle$ If non-empty, this color will be used as second color.

$\langle drawSlash \rangle$ Non-empty implies that a negation will be drawn.

$\langle drawUpArrow \rangle$ Non-empty implies that an up-arrow will be drawn.

$\langle drawDownArrow \rangle$ Non-empty implies that a down-arrow will be drawn.

```

34 \newcommand{\GTS@a}[5]{%
35 \if#1\empty\else%
36 \GTSsetMainColor{#1}%
37 \fi%
38 \if#2\empty\else%
39 \GTSsetSecondColor{#2}%
40 \fi%
41 \text{\ensuremath{%
42 \raisebox{-0.32ex}{\scalebox{1.5}[1.5]{%
43 %
44 \raisebox{0.7ex}{\scalebox{0.7}[0.7]{%
45 $\mathcolor{\GTS@secondColor}{\circ}$%

```

```

46 }}%
47 \hspace{-0.39ex}%
48 \raisebox{1.05ex}{\scalebox{0.1}[0.1]{%
49 $\mathcolor{\GTS@secondColor}{\bullet}$%
50 }}%
51 \hspace{-0.12ex}%
52 \raisebox{0.11ex}{\scalebox{0.1}[0.73]{%
53 $\mathcolor{\GTS@mainColor}{\smallblacksquare}$%
54 }}%
55 \hspace{-0.40ex}%
56 \raisebox{-0.3ex}{\scalebox{0.7}[0.7]{%
57 $\mathcolor{\GTS@secondColor}{\circ}$%
58 }}%
59 \hspace{-0.39ex}%
60 \raisebox{0.05ex}{\scalebox{0.1}[0.1]{%
61 $\mathcolor{\GTS@secondColor}{\bullet}$%
62 }}%
63 \hspace{0.27ex}%
if GTS@drawUpArrow empty else
64 \if#4\empty\else%
65 \hspace{-0.65ex}%
66 \raisebox{-0.18ex}{\scalebox{0.5}[0.5]{%
67 \textcolor{\GTS@mainColor}{\textasciicircum}%
68 }}%
69 \fi%
if GTS@drawDownArrow empty else
70 \if#5\empty\else%
71 \hspace{-0.65ex}%
72 \raisebox{1.37ex}{\scalebox{0.5}[-0.5]{%
73 \textcolor{\GTS@mainColor}{\textasciicircum}%
74 }}%
75 \fi%
if GTS@drawSlash empty else
76 \if#3\empty\else%
77 \hspace{-0.65ex}%
78 \raisebox{0.25ex}{\scalebox{0.6}[0.6]{%
79 \textcolor{black}{/}%
80 }}%
81 \fi%
82 %
83 }}%
84 }%
85 \if#1\empty\else%
86 \GTSsetMainColor{\GTS@mainColorBackup}%
87 \fi%
88 \if#2\empty\else%
89 \GTSsetSecondColor{\GTS@secondColorBackup}%
90 \fi%
91 }

```

This macro will handle wrapping in mathematical relation spacing if needed. Its use is purely technical. See the macros derived from it and `\GTS@a`: `\GTSxadjacency`, `\GTSxadj`, and `\GTSxa`.

Arguments:

$\{\langle mainColor \rangle\}$ If non-empty, this color will be used as main color.
 $\{\langle secondColor \rangle\}$ If non-empty, this color will be used as second color.
 $\{\langle drawSlash \rangle\}$ Non-empty implies that a negation will be drawn.
 $\{\langle drawUpArrow \rangle\}$ Non-empty implies that an up-arrow will be drawn.
 $\{\langle drawDownArrow \rangle\}$ Non-empty implies that a down-arrow will be drawn.
 $\{\langle relation \rangle\}$ Non-empty implies that relation spacing will be added.

```

92 \newcommand{\GTS@b}[6]{%
93 \if#61%
94 \mathrel{\GTS@a{#1}{#2}{#3}{#4}{#5}}%
95 \else%
96 \GTS@a{#1}{#2}{#3}{#4}{#5}%
97 \fi%
98 }
```

Versatile macros for adjacency that can be given options.

Argument:

$[\langle optionsList \rangle]$ Sets the following options if not empty:

mainColor=color1 or mainC=color1 or mColor=color1 or mC=color1,
secondColor=color2 or secondC=color2 or sColor=color2 or sC=color2,
monochrome or mono or mon or m (equivalent to mC=black,sC=black),
negated or not or n,
up or u,
down or d,
relation or rel or r.

```

99 \define@key{GTSxa}{mainColor}{\def\GTS@@mainColor{#1}}
100 \define@key{GTSxa}{mainC}{\def\GTS@@mainColor{#1}}
101 \define@key{GTSxa}{mColor}{\def\GTS@@mainColor{#1}}
102 \define@key{GTSxa}{mC}{\def\GTS@@mainColor{#1}}
103 \define@key{GTSxa}{secondColor}{\def\GTS@@secondColor{#1}}
104 \define@key{GTSxa}{secondC}{\def\GTS@@secondColor{#1}}
105 \define@key{GTSxa}{sColor}{\def\GTS@@secondColor{#1}}
106 \define@key{GTSxa}{sC}{\def\GTS@@secondColor{#1}}
107 \define@key{GTSxa}{monochrome}[1]%
108 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
109 \define@key{GTSxa}{mono}[1]%
110 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
111 \define@key{GTSxa}{mon}[1]%
112 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
113 \define@key{GTSxa}{m}[1]%
114 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
115 \define@key{GTSxa}{negated}[1]{\def\GTS@@drawSlash{1}}
116 \define@key{GTSxa}{not}[1]{\def\GTS@@drawSlash{1}}
117 \define@key{GTSxa}{n}[1]{\def\GTS@@drawSlash{1}}
118 \define@key{GTSxa}{up}[1]{\def\GTS@@drawUpArrow{1}}
119 \define@key{GTSxa}{u}[1]{\def\GTS@@drawUpArrow{1}}
120 \define@key{GTSxa}{down}[1]{\def\GTS@@drawDownArrow{1}}
121 \define@key{GTSxa}{d}[1]{\def\GTS@@drawDownArrow{1}}
122 \define@key{GTSxa}{relation}[1]{\def\GTS@@relation{1}}
123 \define@key{GTSxa}{rel}[1]{\def\GTS@@relation{1}}
124 \define@key{GTSxa}{r}[1]{\def\GTS@@relation{1}}
125
```

```

126 \newcommand{\GTSxa}[1] [] {%
127 \def\GTS@@mainColor{%
128 \def\GTS@@secondColor{%
129 \def\GTS@@drawSlash{%
130 \def\GTS@@drawUpArrow{%
131 \def\GTS@@drawDownArrow{%
132 \def\GTS@@relation{%
133 \setkeys{GTSxa}{#1}%
134 \GTS@b{\GTS@@mainColor}{\GTS@@secondColor}{\GTS@@drawSlash}%
135 {\GTS@@drawUpArrow}{\GTS@@drawDownArrow}{\GTS@@relation}%
136 }
137
138 \newcommand{\GTSxadj}[1] [] {\GTSxa[#1]}
139
140 \newcommand{\GTSxadjacency}[1] [] {\GTSxa[#1]}

```

This macro will draw an adjacency symbol.

```

141 \GTS@newcommand{\GTSadjacency}{\GTS@a{}{}{}{}}
142 \GTS@newcommand{\GTSadj}{\GTS@a{}{}{}{}}
143 \GTS@newcommand{\GTSa}{\GTS@a{}{}{}{}}

```

This macro will draw an adjacency symbol with relation spacing in math mode.

```

144 \GTS@newcommand{\GTSadjacencyRelation}{\mathrel{\GTSa/}}
145 \GTS@newcommand{\GTSadjRel}{\mathrel{\GTSa/}}
146 \GTS@newcommand{\GTSaR}{\mathrel{\GTSa/}}

```

This macro will draw an unadjacency symbol.

```

147 \GTS@newcommand{\GTSunadjacency}{\GTS@a{}{}{1}{}}
148 \GTS@newcommand{\GTSunadj}{\GTS@a{}{}{1}{}}
149 \GTS@newcommand{\GTSu}{\GTS@a{}{}{1}{}}

```

This macro will draw an unadjacency symbol with relation spacing in math mode.

```

150 \GTS@newcommand{\GTSunadjacencyRelation}{\mathrel{\GTSu/}}
151 \GTS@newcommand{\GTSunadjRel}{\mathrel{\GTSu/}}
152 \GTS@newcommand{\GTSuR}{\mathrel{\GTSu/}}

```

This macro will draw a directed adjacency upward symbol. The operand on the left of the symbol should be considered the source of the arc; the operand on the right of the symbol should be considered the target of the arc.

```

153 \GTS@newcommand{\GTSdirectedAdjacencyUp}{\GTS@a{}{}{1}{}}
154 \GTS@newcommand{\GTSdirAdjUp}{\GTS@a{}{}{1}{}}
155 \GTS@newcommand{\GTSdAU}{\GTS@a{}{}{1}{}}

```

This macro will draw a directed adjacency upward symbol with relation spacing in math mode.

```

156 \GTS@newcommand{\GTSdirectedAdjacencyUpRelation}{\mathrel{\GTSdAU/}}
157 \GTS@newcommand{\GTSdirAdjUpRel}{\mathrel{\GTSdAU/}}
158 \GTS@newcommand{\GTSdAUR}{\mathrel{\GTSdAU/}}

```

This macro will draw a negated directed adjacency upward symbol.

```

159 \GTS@newcommand{\GTSnegatedDirectedAdjacencyUp}{\GTS@a{}{}{1}{1}{}}
160 \GTS@newcommand{\GTSnegDirAdjUp}{\GTS@a{}{}{1}{1}{}}
161 \GTS@newcommand{\GTSnDAU}{\GTS@a{}{}{1}{1}{}}

```

This macro will draw a negated directed adjacency upward symbol with relation spacing in math mode.

```

162 \GTS@newcommand{\GTSnegatedDirectedAdjacencyUpRelation}{%
163 \mathrel{\GTSnDAU/}%
164 }
165 \GTS@newcommand{\GTSnegDirAdjUpRel}{\mathrel{\GTSnDAU/}}
166 \GTS@newcommand{\GTSnDAUR}{\mathrel{\GTSnDAU/}}

```

This macro will draw a directed adjacency downward symbol. The operand on the left of the symbol should be considered the target of the arc; the operand on the right of the symbol should be considered the source of the arc.

```

167 \GTS@newcommand{\GTSdirectedAdjacencyDown}{\GTS@a{}{}{}{1}}
168 \GTS@newcommand{\GTSdirAdjDown}{\GTS@a{}{}{}{1}}
169 \GTS@newcommand{\GTSdAD}{\GTS@a{}{}{}{1}}

```

This macro will draw a directed adjacency downward symbol with relation spacing in math mode.

```

170 \GTS@newcommand{\GTSdirectedAdjacencyDownRelation}{\mathrel{\GTSdAD/}}
171 \GTS@newcommand{\GTSdirAdjDownRel}{\mathrel{\GTSdAD/}}
172 \GTS@newcommand{\GTSdADR}{\mathrel{\GTSdAD/}}

```

This macro will draw a negated directed adjacency downward symbol.

```

173 \GTS@newcommand{\GTSnegatedDirectedAdjacencyDown}{\GTS@a{}{}{1}{1}}
174 \GTS@newcommand{\GTSnegDirAdjDown}{\GTS@a{}{}{1}{1}}
175 \GTS@newcommand{\GTSnDAD}{\GTS@a{}{}{1}{1}}

```

This macro will draw a negated directed adjacency downward symbol with relation spacing in math mode.

```

176 \GTS@newcommand{\GTSnegatedDirectedAdjacencyDownRelation}{%
177 \mathrel{\GTSnDAD/}%
178 }
179 \GTS@newcommand{\GTSnegDirAdjDownRel}{\mathrel{\GTSnDAD/}}
180 \GTS@newcommand{\GTSnDADR}{\mathrel{\GTSnDAD/}}

```

This macro will draw any incidence symbol given the correct parameters. Its use is purely technical. See the macros derived from it and `\GTS@j: \GTSxincidence`, `\GTSxinc`, and `\GTSxi`. The operand on the left of the symbol should be considered the vertex to which the edge/the operand on the right of the symbol is incident.

Arguments:

`{\langle mainColor \rangle}` If non-empty, this color will be used as main color.
`{\langle secondColor \rangle}` If non-empty, this color will be used as second color.
`{\langle drawSlash \rangle}` Non-empty implies that a negation will be drawn.
`{\langle drawUpArrow \rangle}` Non-empty implies that an up-arrow will be drawn.
`{\langle drawDownArrow \rangle}` Non-empty implies that a down-arrow will be drawn.

```

181 \newcommand{\GTS@i}[5]{%
182 \if#1\empty\else%
183 \GTSsetMainColor{#1}%
184 \fi%
185 \if#2\empty\else%
186 \GTSsetSecondColor{#2}%
187 \fi%
188 \text{\ensuremath{%

```

```

189 \raisebox{-0.22ex}{\scalebox{2.05}[2.05]{%
190 %
191 \raisebox{-0.3ex}{\scalebox{0.7}[0.7]{%
192 $\mathcolor{\GTS@secondColor}{\circ}$%
193 }}%
194 \hspace{-0.39ex}%
195 \raisebox{0.05ex}{\scalebox{0.1}[0.1]{%
196 $\mathcolor{\GTS@secondColor}{\bullet}$%
197 }}%
198 \hspace{-0.12ex}%
199 \raisebox{0.11ex}{\scalebox{0.1}[0.73]{%
200 $\mathcolor{\GTS@secondColor}{\smallblacksquare}$%
201 }}%
202 \hspace{-0.18ex}%
203 \raisebox{0.15ex}{\scalebox{0.2}[0.2]{%
204 $\mathcolor{\GTS@mainColor}{\smallblacksquare}$%
205 }}%
206 \hspace{0.2ex}%
if GTS@drawUpArrow empty else
207 \if#4\empty\else%
208 \hspace{-0.65ex}%
209 \raisebox{-0.18ex}{\scalebox{0.5}[0.5]{%
210 \textcolor{\GTS@secondColor}{\textasciicircum}%
211 }}%
212 \fi%
if GTS@drawDownArrow empty else
213 \if#5\empty\else%
214 \hspace{-0.65ex}%
215 \raisebox{1.37ex}{\scalebox{0.5}[-0.5]{%
216 \textcolor{\GTS@secondColor}{\textasciicircum}%
217 }}%
218 \fi%
if GTS@drawSlash empty else
219 \if#3\empty\else%
220 \hspace{-0.65ex}%
221 \raisebox{0.1ex}{\scalebox{0.5}[0.5]{%
222 \textcolor{black}{/}%
223 }}%
224 \fi%
225 %
226 }%
227 }%
228 \if#1\empty\else%
229 \GTSsetMainColor{\GTS@mainColorBackup}%
230 \fi%
231 \if#2\empty\else%
232 \GTSsetSecondColor{\GTS@secondColorBackup}%
233 \fi%
234 }

```

This macro will handle wrapping in mathematical relation spacing if needed. Its use is purely technical. See the macros derived from it and `\GTS@i`: `\GTSxincidence`, `\GTSxinc`, and `\GTSxi`.

Arguments:

$\{\langle mainColor \rangle\}$ If non-empty, this color will be used as main color.
 $\{\langle secondColor \rangle\}$ If non-empty, this color will be used as second color.
 $\{\langle drawSlash \rangle\}$ Non-empty implies that a negation will be drawn.
 $\{\langle drawUpArrow \rangle\}$ Non-empty implies that an up-arrow will be drawn.
 $\{\langle drawDownArrow \rangle\}$ Non-empty implies that a down-arrow will be drawn.
 $\{\langle relation \rangle\}$ Non-empty implies that relation spacing will be added.

```
235 \newcommand{\GTS@j}[6]{%
236 \if#61%
237 \mathrel{\GTS@i{#1}{#2}{#3}{#4}{#5}}%
238 \else%
239 \GTS@i{#1}{#2}{#3}{#4}{#5}%
240 \fi%
241 }
```

Versatile macros for incidence that can be given options.

Argument:

$[\langle optionsList \rangle]$ Sets the following options if not empty:

mainColor=color1 or mainC=color1 or mColor=color1 or mC=color1,
secondColor=color2 or secondC=color2 or sColor=color2 or sC=color2,
monochrome or mono or mon or m (equivalent to mC=black,sC=black),
negated or not or n,
in or i,
out or o,
relation or rel or r.

```
242 \define@key{GTSxi}{mainColor}{\def\GTS@@mainColor{#1}}
243 \define@key{GTSxi}{mainC}{\def\GTS@@mainColor{#1}}
244 \define@key{GTSxi}{mColor}{\def\GTS@@mainColor{#1}}
245 \define@key{GTSxi}{mC}{\def\GTS@@mainColor{#1}}
246 \define@key{GTSxi}{secondColor}{\def\GTS@@secondColor{#1}}
247 \define@key{GTSxi}{secondC}{\def\GTS@@secondColor{#1}}
248 \define@key{GTSxi}{sColor}{\def\GTS@@secondColor{#1}}
249 \define@key{GTSxi}{sC}{\def\GTS@@secondColor{#1}}
250 \define@key{GTSxi}{monochrome}[1]%
251 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
252 \define@key{GTSxi}{mono}[1]%
253 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
254 \define@key{GTSxi}{mon}[1]%
255 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
256 \define@key{GTSxi}{m}[1]%
257 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
258 \define@key{GTSxi}{negated}[1]{\def\GTS@@drawSlash{1}}
259 \define@key{GTSxi}{not}[1]{\def\GTS@@drawSlash{1}}
260 \define@key{GTSxi}{n}[1]{\def\GTS@@drawSlash{1}}
261 \define@key{GTSxi}{out}[1]{\def\GTS@@drawUpArrow{1}}
262 \define@key{GTSxi}{o}[1]{\def\GTS@@drawUpArrow{1}}
263 \define@key{GTSxi}{in}[1]{\def\GTS@@drawDownArrow{1}}
264 \define@key{GTSxi}{i}[1]{\def\GTS@@drawDownArrow{1}}
265 \define@key{GTSxi}{relation}[1]{\def\GTS@@relation{1}}
266 \define@key{GTSxi}{rel}[1]{\def\GTS@@relation{1}}
267 \define@key{GTSxi}{r}[1]{\def\GTS@@relation{1}}
268
```

```

269 \newcommand{\GTSxi}[1] [] {%
270 \def\GTS@@mainColor{%
271 \def\GTS@@secondColor{%
272 \def\GTS@@drawSlash{%
273 \def\GTS@@drawUpArrow{%
274 \def\GTS@@drawDownArrow{%
275 \def\GTS@@relation{%
276 \setkeys{GTSxi}{#1}%
277 \GTS@j{\GTS@@mainColor}{\GTS@@secondColor}{\GTS@@drawSlash}%
278 {\GTS@@drawUpArrow}{\GTS@@drawDownArrow}{\GTS@@relation}%
279 }
280
281 \newcommand{\GTSxinc}[1] [] {\GTSxi[#1]}
282
283 \newcommand{\GTSxincidence}[1] [] {\GTSxi[#1]}

```

This macro will draw an incidence symbol. The operand on the left of the symbol should be considered the vertex to which the edge/the operand on the right of the symbol is incident.

```

284 \GTS@newcommand{\GTSincidence}{\GTS@i{}{}{}{}}
285 \GTS@newcommand{\GTSinc}{\GTS@i{}{}{}{}}
286 \GTS@newcommand{\GTSi}{\GTS@i{}{}{}{}}

```

This macro will draw an incidence symbol with relation spacing in math mode.

```

287 \GTS@newcommand{\GTSincidenceRelation}{\mathrel{\GTSi/}}
288 \GTS@newcommand{\GTSincRel}{\mathrel{\GTSi/}}
289 \GTS@newcommand{\GTSiR}{\mathrel{\GTSi/}}

```

This macro will draw a negated incidence symbol.

```

290 \GTS@newcommand{\GTSnegatedIncidence}{\GTS@i{}{}{1}{}}
291 \GTS@newcommand{\GTSnegInc}{\GTS@i{}{}{1}{}}
292 \GTS@newcommand{\GTSnI}{\GTS@i{}{}{1}{}}

```

This macro will draw a negated incidence symbol with relation spacing in math mode.

```

293 \GTS@newcommand{\GTSnegatedIncidenceRelation}{\mathrel{\GTSnI/}}
294 \GTS@newcommand{\GTSnegIncRel}{\mathrel{\GTSnI/}}
295 \GTS@newcommand{\GTSnIR}{\mathrel{\GTSnI/}}

```

This macro will draw a directed incidence upward (out(ward) incidence) symbol. The operand on the left of the symbol should be considered the vertex to which the arc/the operand on the right of the symbol is incident.

```

296 \GTS@newcommand{\GTSoutIncidence}{\GTS@i{}{}{1}{}}
297 \GTS@newcommand{\GTSoutInc}{\GTS@i{}{}{1}{}}
298 \GTS@newcommand{\GTSOI}{\GTS@i{}{}{1}{}}

```

This macro will draw a directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

```

299 \GTS@newcommand{\GTSoutIncidenceRelation}{\mathrel{\GTSOI/}}
300 \GTS@newcommand{\GTSoutIncRel}{\mathrel{\GTSOI/}}
301 \GTS@newcommand{\GTSOIR}{\mathrel{\GTSOI/}}

```

This macro will draw a negated directed incidence upward (out(ward) incidence) symbol.

```

302 \GTS@newcommand{\GTSnegatedOutIncidence}{\GTS@i{}{}{1}{1}{}}
303 \GTS@newcommand{\GTSnegOutInc}{\GTS@i{}{}{1}{1}{}}
304 \GTS@newcommand{\GTSnOI}{\GTS@i{}{}{1}{1}{}}

```

This macro will draw a negated directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

```
305 \GTS@newcommand{\GTSnegatedOutIncidenceRelation}{\mathrel{\GTSnOI/}}
306 \GTS@newcommand{\GTSnegOutIncRel}{\mathrel{\GTSnOI/}}
307 \GTS@newcommand{\GTSnOIR}{\mathrel{\GTSnOI/}}
```

This macro will draw a directed incidence downward (in(ward) incidence) symbol. The operand on the left of the symbol should be considered the vertex to which the arc/the operand on the right of the symbol is incident.

```
308 \GTS@newcommand{\GTSinIncidence}{\GTS@i{}{}{}{1}}
309 \GTS@newcommand{\GTSinInc}{\GTS@i{}{}{}{1}}
310 \GTS@newcommand{\GTSiI}{\GTS@i{}{}{}{1}}
```

This macro will draw a directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.

```
311 \GTS@newcommand{\GTSinIncidenceRelation}{\mathrel{\GTSiI/}}
312 \GTS@newcommand{\GTSinIncRel}{\mathrel{\GTSiI/}}
313 \GTS@newcommand{\GTSiIR}{\mathrel{\GTSiI/}}
```

This macro will draw a negated directed incidence downward (in(ward) incidence) symbol.

```
314 \GTS@newcommand{\GTSnegatedInIncidence}{\GTS@i{}{}{1}{1}}
315 \GTS@newcommand{\GTSnegInInc}{\GTS@i{}{}{1}{1}}
316 \GTS@newcommand{\GTSnII}{\GTS@i{}{}{1}{1}}
```

This macro will draw a negated directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.

```
317 \GTS@newcommand{\GTSnegatedInIncidenceRelation}{\mathrel{\GTSnII/}}
318 \GTS@newcommand{\GTSnegInIncRel}{\mathrel{\GTSnII/}}
319 \GTS@newcommand{\GTSnIIR}{\mathrel{\GTSnII/}}
```

This macro will draw a monochrome adjacency symbol.

```
320 \GTS@newcommand{\GTSadjacencyMonochrome}{\GTS@a{black}{black}{}{}{}}
321 \GTS@newcommand{\GTSadjMono}{\GTS@a{black}{black}{}{}{}}
322 \GTS@newcommand{\GTSadjMon}{\GTS@a{black}{black}{}{}{}}
323 \GTS@newcommand{\GTSaM}{\GTS@a{black}{black}{}{}{}}
```

This macro will draw a monochrome adjacency symbol with relation spacing in math mode.

```
324 \GTS@newcommand{\GTSadjacencyMonochromeRelation}{\mathrel{\GTSaM/}}
325 \GTS@newcommand{\GTSadjMonoRel}{\mathrel{\GTSaM/}}
326 \GTS@newcommand{\GTSadjMonRel}{\mathrel{\GTSaM/}}
327 \GTS@newcommand{\GTSaMR}{\mathrel{\GTSaM/}}
```

This macro will draw a monochrome unadjacency symbol.

```
328 \GTS@newcommand{\GTSunadjacencyMonochrome}{\GTS@a{black}{black}{1}{}{}}
329 \GTS@newcommand{\GTSunadjMono}{\GTS@a{black}{black}{1}{}{}}
330 \GTS@newcommand{\GTSunadjMon}{\GTS@a{black}{black}{1}{}{}}
331 \GTS@newcommand{\GTSuM}{\GTS@a{black}{black}{1}{}{}}
```

This macro will draw a monochrome unadjacency symbol with relation spacing in math mode.

```
332 \GTS@newcommand{\GTSunadjacencyMonochromeRelation}{\mathrel{\GTSuM/}}
333 \GTS@newcommand{\GTSunadjMonoRel}{\mathrel{\GTSuM/}}
334 \GTS@newcommand{\GTSunadjMonRel}{\mathrel{\GTSuM/}}
335 \GTS@newcommand{\GTSuMR}{\mathrel{\GTSuM/}}
```

This macro will draw a monochrome directed adjacency upward symbol. The operand on the left of the symbol should be considered the source of the arc; the operand on the right of the symbol should be considered the target of the arc.

```

336 \GTS@newcommand{\GTSdirectedAdjacencyUpMonochrome}{%
337 \GTS@a{black}{black}{-}{1}{-}}%
338 }
339 \GTS@newcommand{\GTSdirAdjUpMono}{\GTS@a{black}{black}{-}{1}{-}}
340 \GTS@newcommand{\GTSdirAdjUpMon}{\GTS@a{black}{black}{-}{1}{-}}
341 \GTS@newcommand{\GTSdAUM}{\GTS@a{black}{black}{-}{1}{-}}

```

This macro will draw a monochrome directed adjacency upward symbol with relation spacing in math mode.

```

342 \GTS@newcommand{\GTSdirectedAdjacencyUpMonochromeRelation}{%
343 \mathrel{\GTSdAUM/}}%
344 }
345 \GTS@newcommand{\GTSdirAdjUpMonoRel}{\mathrel{\GTSdAUM/}}
346 \GTS@newcommand{\GTSdirAdjUpMonRel}{\mathrel{\GTSdAUM/}}
347 \GTS@newcommand{\GTSdAUMR}{\mathrel{\GTSdAUM/}}

```

This macro will draw a monochrome negated directed adjacency upward symbol.

```

348 \GTS@newcommand{\GTSnegatedDirectedAdjacencyUpMonochrome}{%
349 \GTS@a{black}{black}{1}{1}{-}}%
350 }
351 \GTS@newcommand{\GTSnegDirAdjUpMono}{\GTS@a{black}{black}{1}{1}{-}}
352 \GTS@newcommand{\GTSnegDirAdjUpMon}{\GTS@a{black}{black}{1}{1}{-}}
353 \GTS@newcommand{\GTSnDAUM}{\GTS@a{black}{black}{1}{1}{-}}

```

This macro will draw a monochrome negated directed adjacency upward symbol with relation spacing in math mode.

```

354 \GTS@newcommand{\GTSnegatedDirectedAdjacencyUpMonochromeRelation}{%
355 \mathrel{\GTSnDAUM/}}%
356 }
357 \GTS@newcommand{\GTSnegDirAdjUpMonoRel}{\mathrel{\GTSnDAUM/}}
358 \GTS@newcommand{\GTSnegDirAdjUpMonRel}{\mathrel{\GTSnDAUM/}}
359 \GTS@newcommand{\GTSnDAUMR}{\mathrel{\GTSnDAUM/}}

```

This macro will draw a monochrome directed adjacency downward symbol. The operand on the left of the symbol should be considered the target of the arc; the operand on the right of the symbol should be considered the source of the arc.

```

360 \GTS@newcommand{\GTSdirectedAdjacencyDownMonochrome}{%
361 \GTS@a{black}{black}{-}{-}{1}}%
362 }
363 \GTS@newcommand{\GTSdirAdjDownMono}{\GTS@a{black}{black}{-}{-}{1}}
364 \GTS@newcommand{\GTSdirAdjDownMon}{\GTS@a{black}{black}{-}{-}{1}}
365 \GTS@newcommand{\GTSdADM}{\GTS@a{black}{black}{-}{-}{1}}

```

This macro will draw a monochrome directed adjacency downward symbol with relation spacing in math mode.

```

366 \GTS@newcommand{\GTSdirectedAdjacencyDownMonochromeRelation}{%
367 \mathrel{\GTSdADM/}}%
368 }
369 \GTS@newcommand{\GTSdirAdjDownMonoRel}{\mathrel{\GTSdADM/}}

```

```

370 \GTS@newcommand{\GTSdirAdjDownMonRel}{\mathrel{\GTSdADM/}}
371 \GTS@newcommand{\GTSdADMR}{\mathrel{\GTSdADM/}}

```

This macro will draw a monochrome negated directed adjacency downward symbol.

```

372 \GTS@newcommand{\GTSnegatedDirectedAdjacencyDownMonochrome}{%
373 \GTS@a{black}{black}{1}{1}%
374 }
375 \GTS@newcommand{\GTSnegDirAdjDownMono}{\GTS@a{black}{black}{1}{1}}
376 \GTS@newcommand{\GTSnegDirAdjDownMon}{\GTS@a{black}{black}{1}{1}}
377 \GTS@newcommand{\GTSnDADM}{\GTS@a{black}{black}{1}{1}}

```

This macro will draw a monochrome negated directed adjacency downward symbol with relation spacing in math mode.

```

378 \GTS@newcommand{\GTSnegatedDirectedAdjacencyDownMonochromeRelation}{%
379 \mathrel{\GTSnDADM/}%
380 }
381 \GTS@newcommand{\GTSnegDirAdjDownMonoRel}{\mathrel{\GTSnDADM/}}
382 \GTS@newcommand{\GTSnegDirAdjDownMonRel}{\mathrel{\GTSnDADM/}}
383 \GTS@newcommand{\GTSnDADMR}{\mathrel{\GTSnDADM/}}

```

This macro will draw a monochrome incidence symbol. The operand on the left of the symbol should be considered the vertex to which the edge/the operand on the right of the symbol is incident.

```

384 \GTS@newcommand{\GTSincidenceMonochrome}{\GTS@i{black}{black}{}}
385 \GTS@newcommand{\GTSincMono}{\GTS@i{black}{black}{}}
386 \GTS@newcommand{\GTSincMon}{\GTS@i{black}{black}{}}
387 \GTS@newcommand{\GTSiM}{\GTS@i{black}{black}{}}

```

This macro will draw a monochrome incidence symbol with relation spacing in math mode.

```

388 \GTS@newcommand{\GTSincidenceMonochromeRelation}{\mathrel{\GTSiM/}}
389 \GTS@newcommand{\GTSincMonoRel}{\mathrel{\GTSiM/}}
390 \GTS@newcommand{\GTSincMonRel}{\mathrel{\GTSiM/}}
391 \GTS@newcommand{\GTSiMR}{\mathrel{\GTSiM/}}

```

This macro will draw a monochrome negated incidence symbol.

```

392 \GTS@newcommand{\GTSnegatedIncidenceMonochrome}{%
393 \GTS@i{black}{black}{1}{1}%
394 }
395 \GTS@newcommand{\GTSnegIncMono}{\GTS@i{black}{black}{1}{1}}
396 \GTS@newcommand{\GTSnegIncMon}{\GTS@i{black}{black}{1}{1}}
397 \GTS@newcommand{\GTSnIM}{\GTS@i{black}{black}{1}{1}}

```

This macro will draw a monochrome negated incidence symbol with relation spacing in math mode.

```

398 \GTS@newcommand{\GTSnegatedIncidenceMonochromeRelation}{\mathrel{\GTSnIM/}}
399 \GTS@newcommand{\GTSnegIncMonoRel}{\mathrel{\GTSnIM/}}
400 \GTS@newcommand{\GTSnegIncMonRel}{\mathrel{\GTSnIM/}}
401 \GTS@newcommand{\GTSnIMR}{\mathrel{\GTSnIM/}}

```

This macro will draw a monochrome directed incidence upward (out(ward) incidence) symbol. The operand on the left of the symbol should be considered the vertex to which the arc/the operand on the right of the symbol is incident.

```

402 \GTS@newcommand{\GTSoutIncidenceMonochrome}{\GTS@i{black}{black}{}}{1}{}}
403 \GTS@newcommand{\GTSoutIncMono}{\GTS@i{black}{black}{}}{1}{}}
404 \GTS@newcommand{\GTSoutIncMon}{\GTS@i{black}{black}{}}{1}{}}
405 \GTS@newcommand{\GTSoIM}{\GTS@i{black}{black}{}}{1}{}}

```

This macro will draw a monochrome directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

```

406 \GTS@newcommand{\GTSoutIncidenceMonochromeRelation}{\mathrel{\GTSoIM/}}
407 \GTS@newcommand{\GTSoutIncMonoRel}{\mathrel{\GTSoIM/}}
408 \GTS@newcommand{\GTSoutIncMonRel}{\mathrel{\GTSoIM/}}
409 \GTS@newcommand{\GTSoIMR}{\mathrel{\GTSoIM/}}

```

This macro will draw a monochrome negated directed incidence upward (out(ward) incidence) symbol.

```

410 \GTS@newcommand{\GTSnegatedOutIncidenceMonochrome}{%
411 \GTS@i{black}{black}{1}{1}}%
412 }
413 \GTS@newcommand{\GTSnegOutIncMono}{\GTS@i{black}{black}{1}{1}}
414 \GTS@newcommand{\GTSnegOutIncMon}{\GTS@i{black}{black}{1}{1}}
415 \GTS@newcommand{\GTSnOIM}{\GTS@i{black}{black}{1}{1}}

```

This macro will draw a monochrome negated directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

```

416 \GTS@newcommand{\GTSnegatedOutIncidenceMonochromeRelation}{%
417 \mathrel{\GTSnOIM/}}%
418 }
419 \GTS@newcommand{\GTSnegOutIncMonoRel}{\mathrel{\GTSnOIM/}}
420 \GTS@newcommand{\GTSnegOutIncMonRel}{\mathrel{\GTSnOIM/}}
421 \GTS@newcommand{\GTSnOIMR}{\mathrel{\GTSnOIM/}}

```

This macro will draw a monochrome directed incidence downward (in(ward) incidence) symbol. The operand on the left of the symbol should be considered the vertex to which the arc/the operand on the right of the symbol is incident.

```

422 \GTS@newcommand{\GTSinIncidenceMonochrome}{\GTS@i{black}{black}{}}{1}}
423 \GTS@newcommand{\GTSinIncMono}{\GTS@i{black}{black}{}}{1}}
424 \GTS@newcommand{\GTSinIncMon}{\GTS@i{black}{black}{}}{1}}
425 \GTS@newcommand{\GTSiIM}{\GTS@i{black}{black}{}}{1}}

```

This macro will draw a monochrome directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.

```

426 \GTS@newcommand{\GTSinIncidenceMonochromeRelation}{\mathrel{\GTSiIM/}}
427 \GTS@newcommand{\GTSinIncMonoRel}{\mathrel{\GTSiIM/}}
428 \GTS@newcommand{\GTSinIncMonRel}{\mathrel{\GTSiIM/}}
429 \GTS@newcommand{\GTSiIMR}{\mathrel{\GTSiIM/}}

```

This macro will draw a monochrome negated directed incidence downward (in(ward) incidence) symbol.

```

430 \GTS@newcommand{\GTSnegatedInIncidenceMonochrome}{%
431 \GTS@i{black}{black}{1}{1}}%
432 }
433 \GTS@newcommand{\GTSnegInIncMono}{\GTS@i{black}{black}{1}{1}}
434 \GTS@newcommand{\GTSnegInIncMon}{\GTS@i{black}{black}{1}{1}}
435 \GTS@newcommand{\GTSnIIM}{\GTS@i{black}{black}{1}{1}}

```

This macro will draw a monochrome negated directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.

```

436 \GTS@newcommand{\GTSnegatedInIncidenceMonochromeRelation}{%
437 \mathrel{\GTSnIIM/}%
438 }
439 \GTS@newcommand{\GTSnegInIncMonoRel}{\mathrel{\GTSnIIM/}}
440 \GTS@newcommand{\GTSnegInIncMonRel}{\mathrel{\GTSnIIM/}}
441 \GTS@newcommand{\GTSnIIMR}{\mathrel{\GTSnIIM/}}

```

This macro will draw a meta-not or relation-not symbol.

```

442 \GTS@newprotectedcommand{\GTSmN}{%
443 \text{\ensuremath{%
444 \raisebox{-0.44ex}{\scalebox{1}[1]{%
445 \raisebox{0ex}{\scalebox{1}[1]{\not$}}}%
446 \hspace{-1.46ex}%
447 \raisebox{1.2ex}{\scalebox{0.7}[0.7]{m}}}%
448 \hspace{0.2ex}%
449 }}}%
450 }}%
451 }
452 \GTS@newcommand{\GTSmetaNot}{\GTSmN/}

```

This macro will draw a meta-and or relations-and symbol. This is your duty to check that all relations have same arity. It should be easy as long as you remain in the realm of graphs/2-structures/binary structures. We didn't use Tarski's notation, since square cup has taken the preemptive meaning of disjoint union. Similarly, doublewedge or other wedge symbols have taken various meanings, whilst we want an unambiguous symbol.

```

453 \GTS@newprotectedcommand{\GTSmA}{%
454 \text{\ensuremath{%
455 \raisebox{-0.44ex}{\scalebox{0.95}[0.95]{%
456 \raisebox{0ex}{\scalebox{1}[1]{\wedge$}}}%
457 \hspace{-1.46ex}%
458 \raisebox{1.5ex}{\scalebox{0.7}[0.7]{m}}}%
459 }}}%
460 }}%
461 }
462 \GTS@newcommand{\GTSmetaAnd}{\GTSmA/}

```

This macro will draw a meta-and symbol with relation spacing in math mode.

```

463 \GTS@newcommand{\GTSmetaAndRelation}{\mathrel{\GTSmA/}}
464 \GTS@newcommand{\GTSmetaAndRel}{\mathrel{\GTSmA/}}
465 \GTS@newcommand{\GTSmAR}{\mathrel{\GTSmA/}}

```

This macro will draw a meta-or or relations-or symbol. This is your duty to check that all relations have same arity. It should be easy as long as you remain in the realm of graphs/2-structures/binary structures ;). We didn't use Tarski's notation, since square cup has taken the preemptive meaning of disjoint union. Similarly, doublevee or other vee symbols have taken various meanings, whilst we want an unambiguous symbol.

```

466 \GTS@newprotectedcommand{\GTSmO}{%
467 \text{\ensuremath{%
468 \raisebox{-0.44ex}{\scalebox{0.95}[0.95]{%
469 \raisebox{0ex}{\scalebox{1}[1]{\vee$}}}%

```

```

470 \hspace{-1.46ex}%
471 \raisebox{1.5ex}{\scalebox{0.7}[0.7]{m}}%
472 }}%
473 }}%
474 }
475 \GTS@newcommand{\GTSmetaOr}{\GTSmO/}

```

This macro will draw a meta-or symbol with relation spacing in math mode.

```

476 \GTS@newcommand{\GTSmetaOrRelation}{\mathrel{\GTSmO/}}
477 \GTS@newcommand{\GTSmetaOrRel}{\mathrel{\GTSmO/}}
478 \GTS@newcommand{\GTSmOR}{\mathrel{\GTSmO/}}

```

Versatile macros for meta-logic symbols that can be given options.

Argument:

[*<optionsList>*] Sets the following options if not empty:

not or n,

and or a,

or or o,

relation or rel or r.

Of course first three options are incompatible, and the fourth is compatible only with the second and third options.

```

479 \define@key{GTSxml}{not}[1]{\def\GTS@@drawMetaNot{1}}
480 \define@key{GTSxml}{n}[1]{\def\GTS@@drawMetaNot{1}}
481 \define@key{GTSxml}{and}[1]{\def\GTS@@drawMetaAnd{1}}
482 \define@key{GTSxml}{a}[1]{\def\GTS@@drawMetaAnd{1}}
483 \define@key{GTSxml}{or}[1]{\def\GTS@@drawMetaOr{1}}
484 \define@key{GTSxml}{o}[1]{\def\GTS@@drawMetaOr{1}}
485 \define@key{GTSxml}{relation}[1]{\def\GTS@@relation{1}}
486 \define@key{GTSxml}{rel}[1]{\def\GTS@@relation{1}}
487 \define@key{GTSxml}{r}[1]{\def\GTS@@relation{1}}
488
489 \newcommand{\GTSxml}[1][]{%
490 \def\GTS@@drawMetaNot{}%
491 \def\GTS@@drawMetaAnd{}%
492 \def\GTS@@drawMetaOr{}%
493 \def\GTS@@relation{}%
494 \setkeys{GTSxml}{#1}%
495 \if\GTS@@drawMetaNot1%
496 \GTSmN/%
497 \else\if\GTS@@drawMetaAnd1%
498 \if\GTS@@relation{1}%
499 \GTSmAR/%
500 \else%
501 \GTSmA/%
502 \fi%
503 \else\if\GTS@@drawMetaOr1%
504 \if\GTS@@relation{1}%
505 \GTSmOR/%
506 \else%
507 \GTSmO/%
508 \fi%
509 \else%
510 Wrong call to \textbackslash{GTSxml}%

```

```

511 \fi%
512 \fi%
513 \fi%
514 }
515
516 \newcommand{\GTSxmetallogic}[1][\GTSxml[#1]]

```

One macro to rule them all. Versatile macro for all symbols that can be given options, and a symbol type mandatory switch.

Argument:

[*optionsList*] Sets the following options if not empty:

- If $\{\langle symbolType \rangle\}$ below is **a**, see `\GTSxa`:
`mainColor=color1` or `mainC=color1` or `mColor=color1` or `mC=color1`,
`secondColor=color2` or `secondC=color2` or `sColor=color2` or `sC=color2`,
`monochrome` or `mono` or `mon` or `m` (equivalent to `mC=black,sC=black`),
`negated` or `not` or `n`,
`up` or `u`,
`down` or `d`,
`relation` or `rel` or `r`.
- If $\{\langle symbolType \rangle\}$ below is **i**, see `\GTSxi`:
`mainColor=color1` or `mainC=color1` or `mColor=color1` or `mC=color1`,
`secondColor=color2` or `secondC=color2` or `sColor=color2` or `sC=color2`,
`monochrome` or `mono` or `mon` or `m` (equivalent to `mC=black,sC=black`),
`negated` or `not` or `n`,
`in` or `i`,
`out` or `o`,
`relation` or `rel` or `r`.
- If $\{\langle symbolType \rangle\}$ below is **m**, see `\GTSxml`:
`not` or `n`,
`and` or `a`,
`or` or `o`,
`relation` or `rel` or `r`.

$\{\langle symbolType \rangle\}$ a mandatory switch; it can take value **a** for adjacency, **i** for incidence, **m** for meta-logic.

```

517 \newcommand{\GTSx}[2][\GTSx%
518 \if#2a%
519 \GTSxa[#1]%
520 \else\if#2i%
521 \GTSxi[#1]%
522 \else\if#2m%
523 \GTSxml[#1]%
524 \else%
525 Wrong call to \textbackslash{}GTSx%
526 \fi%
527 \fi%
528 \fi%
529 }

```

```
530 \endinput
531 \</package>
```

4 Acknowledgments

Thank You God! Thank You Father! Thank You Jesus! Thank You Holy-Spirit!

5 Support

This package is gratis and free. But if you can star it on GitHub, it is a nice encouragement.

6 Change History

v0.1.0 – 2026-08-01	v1.3.0 – 2026-09-08
General: Initial version 1	General: New macros for monochrome symbols 1
v1.0.0 – 2026-08-26	
General: First public release 1	
v1.1.0 – 2026-08-29	v1.4.0 – 2026-09-12
General: Added a memo 1	General: New macros for symbols for logical operations on relations 1
v1.1.1 – 2026-08-30	
General: Small corrections and improvements 1	v1.5.0 – 2026-09-12
v1.2.0 – 2026-09-06	General: One macro to rule them all 1
General: CTAN URL, new macros for same set of symbols 1	
v1.2.1 – 2026-09-08	v1.5.1 – 2026-09-13
General: Smaller tests output 1	General: Use noprint option of doc package to avoid too big left margins, and use paragraph command instead . . 1

Index

G

\GTS@@drawDownArrow	120, 121, 131, 135, 263, 264, 274, 278
\GTS@@drawMetaAnd	481, 482, 491, 497
\GTS@@drawMetaNot	479, 480, 490, 495
\GTS@@drawMetaOr	483, 484, 492, 503
\GTS@@drawSlash	115, 116, 117, 129, 134, 258, 259, 260, 272, 277
\GTS@@drawUpArrow	118, 119, 130, 135, 261, 262, 273, 278
\GTS@@mainColor	99, 100, 101, 102, 108, 110, 112, 114, 127, 134, 242, 243, 244, 245, 251, 253, 255, 257, 270, 277
\GTS@@relation	122, 123, 124, 132, 135, 265, 266, 267, 275, 278, 485, 486, 487, 493, 498, 504
\GTS@@secondColor	103, 104, 105, 106, 108, 110, 112, 114, 128, 134, 246, 247, 248, 249, 251, 253, 255, 257, 271, 277
\GTS@a	6, 34, 94, 96, 141, 142, 143, 147, 148, 149, 153, 154, 155, 159, 160, 161, 167, 168, 169, 173, 174, 175, 320, 321, 322, 323, 328, 329, 330, 331, 337, 339, 340, 341, 349, 351, 352, 353, 361, 363, 364, 365, 373, 375, 376, 377
\GTS@b	6, 92, 134
\GTS@drawDownArrow	16

\GTS@drawSlash	14
\GTS@drawUpArrow	15
\GTS@i	10, 237, 239, 284, 285, 286, 290, 291, 292, 296, 297, 298, 302, 303, 304, 308, 309, 310, 314, 315, 316, 384, 385, 386, 387, 393, 395, 396, 397, 402, 403, 404, 405, 411, 413, 414, 415, 422, 423, 424, 425, 431, 433, 434, 435
\GTS@j	10, 277
\GTS@mainColor	10, 26, 27, 53, 67, 73, 204
\GTS@mainColorBackup	12, 26, 86, 229
\GTS@mainColorTemp	25, 27
\GTS@newcommand	6, 18, 141, 142, 143, 144, 145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155, 156, 157, 158, 159, 160, 161, 162, 165, 166, 167, 168, 169, 170, 171, 172, 173, 174, 175, 176, 179, 180, 284, 285, 286, 287, 288, 289, 290, 291, 292, 293, 294, 295, 296, 297, 298, 299, 300, 301, 302, 303, 304, 305, 306, 307, 308, 309, 310, 311, 312, 313, 314, 315, 316, 317, 318, 319, 320, 321, 322, 323, 324, 325, 326, 327, 328, 329, 330, 331, 332, 333, 334, 335, 336, 339, 340, 341, 342, 345, 346, 347, 348, 351, 352, 353, 354, 357, 358, 359, 360, 363, 364, 365, 366, 369, 370, 371, 372, 375, 376, 377, 378, 381, 382, 383, 384, 385, 386, 387, 388, 389, 390, 391, 392, 395, 396, 397, 398, 399, 400, 401, 402, 403, 404, 405, 406, 407, 408, 409, 410, 413, 414, 415, 416, 419, 420, 421, 422, 423, 424, 425, 426, 427, 428, 429, 430, 433, 434, 435, 436, 439, 440, 441, 452, 462, 463, 464, 465, 475, 476, 477, 478
\GTS@newprotectedcommand	6, 21, 442, 453, 466
\GTS@secondColor	11, 31, 32, 45, 49, 57, 61, 192, 196, 200, 210, 216
\GTS@secondColorBackup	13, 31, 89, 232
\GTS@secondColorTemp	30, 32
\GTSa	7, 141, 144, 145, 146
\GTSadj	7, 141
\GTSadjacency	7, 141
\GTSadjacencyMonochrome	13
\GTSadjacencyMonochromeRelation	14, 323, 324
\GTSadjacencyRelation	7, 144
\GTSadjMon	13
\GTSadjMono	13
\GTSadjMonoRel	14, 323
\GTSadjMonRel	14, 323
\GTSadjRel	7, 144
\GTSaM	13, 324, 325, 326, 327
\GTSaMR	14, 323
\GTSaR	7, 144
\GTSdAD	9, 170, 171, 172
\GTSdADM	16, 359, 367, 369, 370, 371
\GTSdADMR	16, 365
\GTSdADR	9, 169
\GTSdAU	8, 153, 156, 157, 158
\GTSdAUM	15, 335, 343, 345, 346, 347
\GTSdAUMR	15, 341
\GTSdAUR	8, 155
\GTSdirAdjDown	9
\GTSdirAdjDownMon	16, 359
\GTSdirAdjDownMono	16, 359

\GTSdirAdjDownMonoRel	16, 365
\GTSdirAdjDownMonRel	16, 365
\GTSdirAdjDownRel	9, 169
\GTSdirAdjUp	8, 153
\GTSdirAdjUpMon	15, 335
\GTSdirAdjUpMono	15, 335
\GTSdirAdjUpMonoRel	15, 341
\GTSdirAdjUpMonRel	15, 341
\GTSdirAdjUpRel	8, 155
\GTSdirectedAdjacencyDown	9
\GTSdirectedAdjacencyDownMonochrome	16, 359, 360
\GTSdirectedAdjacencyDownMonochromeRelation	16, 365, 366
\GTSdirectedAdjacencyDownRelation	9, 169, 170
\GTSdirectedAdjacencyUp	8, 153
\GTSdirectedAdjacencyUpMonochrome	15, 335, 336
\GTSdirectedAdjacencyUpMonochromeRelation	15, 341, 342
\GTSdirectedAdjacencyUpRelation	8, 155, 156
\GTSi	11, 287, 288, 289
\GTSiI	12, 311, 312, 313
\GTSiIM	19, 426, 427, 428, 429
\GTSiIMR	20, 425
\GTSiIR	13
\GTSiM	17, 388, 389, 390, 391
\GTSiMR	17, 387
\GTSinc	11
\GTSincidence	11
\GTSincidenceMonochrome	17
\GTSincidenceMonochromeRelation	17, 387, 388
\GTSincidenceRelation	11
\GTSincMon	17
\GTSincMono	17
\GTSincMonoRel	17, 387
\GTSincMonRel	17, 387
\GTSincRel	11
\GTSinInc	12
\GTSinIncidence	12
\GTSinIncidenceMonochrome	19
\GTSinIncidenceMonochromeRelation	20, 425, 426
\GTSinIncidenceRelation	13
\GTSinIncMon	19
\GTSinIncMono	19
\GTSinIncMonoRel	20, 425
\GTSinIncMonRel	20, 425
\GTSinIncRel	13
\GTSiR	11
\GTSmA	21, 463, 464, 465, 501
\GTSmAR	21, 499
\GTSmetaAnd	21
\GTSmetaAndRel	21

\GTSmetaAndRelation	21
\GTSmetaNot	20
\GTSmetaOr	21
\GTSmetaOrRel	21
\GTSmetaOrRelation	21
\GTSmN	20, 496
\GTSmO	21, 476, 477, 478, 507
\GTSmOR	21, 505
\GTSnDAD	9, 172, 177, 179, 180
\GTSnDADM	16, 371, 379, 381, 382, 383
\GTSnDADMR	17, 377
\GTSnDADR	10, 175
\GTSnDAU	8, 158, 163, 165, 166
\GTSnDAUM	15, 347, 355, 357, 358, 359
\GTSnDAUMR	16, 353
\GTSnDAUR	9, 161
\GTSnegatedDirectedAdjacencyDown	9, 172, 173
\GTSnegatedDirectedAdjacencyDownMonochrome	16, 371, 372
\GTSnegatedDirectedAdjacencyDownMonochromeRelation	17, 377, 378
\GTSnegatedDirectedAdjacencyDownRelation	10, 175, 176
\GTSnegatedDirectedAdjacencyUp	8, 158, 159
\GTSnegatedDirectedAdjacencyUpMonochrome	15, 347, 348
\GTSnegatedDirectedAdjacencyUpMonochromeRelation	16, 353, 354
\GTSnegatedDirectedAdjacencyUpRelation	9, 161, 162
\GTSnegatedIncidence	11
\GTSnegatedIncidenceMonochrome	17, 391, 392
\GTSnegatedIncidenceMonochromeRelation	18, 397, 398
\GTSnegatedIncidenceRelation	11, 292, 293
\GTSnegatedInIncidence	13
\GTSnegatedInIncidenceMonochrome	20, 429, 430
\GTSnegatedInIncidenceMonochromeRelation	20, 435, 436
\GTSnegatedInIncidenceRelation	13, 316, 317
\GTSnegatedOutIncidence	12
\GTSnegatedOutIncidenceMonochrome	19, 409, 410
\GTSnegatedOutIncidenceMonochromeRelation	19, 415, 416
\GTSnegatedOutIncidenceRelation	12, 304, 305
\GTSnegDirAdjDown	9, 172
\GTSnegDirAdjDownMon	16, 371
\GTSnegDirAdjDownMono	16, 371
\GTSnegDirAdjDownMonoRel	17, 377
\GTSnegDirAdjDownMonRel	17, 377
\GTSnegDirAdjDownRel	10, 175
\GTSnegDirAdjUp	8, 158
\GTSnegDirAdjUpMon	15, 347
\GTSnegDirAdjUpMono	15, 347
\GTSnegDirAdjUpMonoRel	16, 353
\GTSnegDirAdjUpMonRel	16, 353
\GTSnegDirAdjUpRel	9, 161
\GTSnegInc	11

\GTSnegIncMon	17, 391
\GTSnegIncMono	17, 391
\GTSnegIncMonoRel	18, 397
\GTSnegIncMonRel	18, 397
\GTSnegIncRel	11, 292
\GTSnegInInc	13
\GTSnegInIncMon	20, 429
\GTSnegInIncMono	20, 429
\GTSnegInIncMonoRel	20, 435
\GTSnegInIncMonRel	20, 435
\GTSnegInIncRel	13, 316
\GTSnegOutInc	12
\GTSnegOutIncMon	19, 409
\GTSnegOutIncMono	19, 409
\GTSnegOutIncMonoRel	19, 415
\GTSnegOutIncMonRel	19, 415
\GTSnegOutIncRel	12, 304
\GTSnI	11, 293, 294, 295
\GTSnII	13, 317, 318, 319
\GTSnIIM	20, 429 , 437, 439, 440, 441
\GTSnIIMR	20, 435
\GTSnIIR	13, 316
\GTSnIM	17, 391 , 398, 399, 400, 401
\GTSnIMR	18, 397
\GTSnIR	11, 292
\GTSnOI	12, 305, 306, 307
\GTSnOIM	19, 409 , 417, 419, 420, 421
\GTSnOIMR	19, 415
\GTSnOIR	12, 304
\GTSoI	11, 299, 300, 301
\GTSoIM	18, 406, 407, 408, 409
\GTSoIMR	18, 405
\GTSoIR	12
\GTSoutInc	11
\GTSoutIncidence	11
\GTSoutIncidenceMonochrome	18
\GTSoutIncidenceMonochromeRelation	18, 405 , 406
\GTSoutIncidenceRelation	12
\GTSoutIncMon	18
\GTSoutIncMono	18
\GTSoutIncMonoRel	18, 405
\GTSoutIncMonRel	18, 405
\GTSoutIncRel	12
\GTSsetMainColor	6, 24 , 36, 86, 183, 229
\GTSsetSecondColor	6, 29 , 39, 89, 186, 232
\GTSu	7, 147 , 150, 151, 152
\GTSuM	14, 332, 333, 334, 335
\GTSuMR	14, 331
\GTSunadj	7, 147

\GTSunadjacency	7, <u>147</u>
\GTSunadjacencyMonochrome	<u>14</u>
\GTSunadjacencyMonochromeRelation	<u>14</u> , <u>331</u> , <u>332</u>
\GTSunadjacencyRelation	<u>8</u> , <u>150</u>
\GTSunadjMon	<u>14</u>
\GTSunadjMono	<u>14</u>
\GTSunadjMonoRel	<u>14</u> , <u>331</u>
\GTSunadjMonRel	<u>14</u> , <u>331</u>
\GTSunadjRel	<u>8</u> , <u>150</u>
\GTSuR	<u>8</u> , <u>150</u>
\GTSx	<u>22</u>
\GTSxa	<u>7</u> , <u>99</u> , <u>519</u>
\GTSxadj	<u>7</u> , <u>99</u>
\GTSxadjacency	<u>7</u> , <u>99</u>
\GTSxi	<u>10</u> , <u>521</u>
\GTSxinc	<u>10</u>
\GTSxincidence	<u>10</u>
\GTSxmetallogic	<u>22</u>
\GTSxml	<u>22</u> , <u>523</u>