

GraphTheorySymbol:

A set of $\text{\LaTeX}$ commands to have symbols designed for
Graph Theory

Laurent Frédéric Bernard François Lyaudet
Email: Laurent.Lyaudet@gmail.com

v1.3.0 2026/09/08

Abstract

This documentation is for $\text{\LaTeX}$ package GraphTheorySymbol. It provides symbols used in graph theory. The adjacency and incidence symbols were created by the author of this package.

Contents

1	Introduction	1
2	Usage	2
2.1	Memo or for the impatient	2
2.2	Detailed usage	4
3	Implementation	14
4	Acknowledgments	24
5	Support	24

1 Introduction

This documentation is for $\text{\LaTeX}$ package GraphTheorySymbol. It provides symbols used in graph theory. The adjacency and incidence symbols were created by the author of this package.

This package is licenced under Lesser GNU General Public License version 3 or later (LGPLv3+). It means you are free do anything with it, but if you do improve the code of the symbols that we provide, please do share these improvements in a similar way. There is no restriction on other graph theory symbols/code, even if it would be a good fit for inclusion in this package. There is also no need to share in a similar way what you build with this package. The text of the licenses is available at:

<https://www.gnu.org/licenses/>.

The git repository of this source code is also available at:

<https://github.com/LLyaudet/GraphTheorySymbol/>.

Clone it with this URL:

[git@github.com:LLyaudet/GraphTheorySymbol.git](https://github.com:LLyaudet/GraphTheorySymbol.git).

This package is available on CTAN:

<https://ctan.org/pkg/graph-theory-symbol>.

This is our first $\text{\LaTeX}$ package. It may be that our macros are quite slow and that a document making extensive use of these macros will be slow to compile. If you know how to produce better $\text{\LaTeX}$ code, please submit a pull request on GitHub.

2 Usage

2.1 Memo or for the impatient

Add in your preamble: `\usepackage{graph-theory-symbol}`.

Long name	Short name	Result	In context
<code>\GTSadjacency/</code>	<code>\GTSa/</code>	$\circ$	$u \circ v$
<code>\GTSadjacencyRelation/</code>	<code>\GTSaR/</code>	$\circ$	$u \circ v$
<code>\GTSunadjacency/</code>	<code>\GTSu/</code>	$\circ$	$u \circ v$
<code>\GTSunadjacencyRelation/</code>	<code>\GTSuR/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyUp/</code>	<code>\GTSdAU/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyUpRelation/</code>	<code>\GTSdAUR/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyUp/</code>	<code>\GTSnDAU/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyUpRelation/</code>	<code>\GTSnDAUR/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyDown/</code>	<code>\GTSdAD/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyDownRelation/</code>	<code>\GTSdADR/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyDown/</code>	<code>\GTSnDAD/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyDownRelation/</code>	<code>\GTSnDADR/</code>	$\circ$	$u \circ v$
<code>\GTSincidence/</code>	<code>\GTSi/</code>	$\circ$	$v \circ e$
<code>\GTSincidenceRelation/</code>	<code>\GTSiR/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedIncidence/</code>	<code>\GTSnI/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedIncidenceRelation/</code>	<code>\GTSnIR/</code>	$\circ$	$v \circ e$
<code>\GTSoutIncidence/</code>	<code>\GTSOI/</code>	$\circ$	$v \circ e$
<code>\GTSoutIncidenceRelation/</code>	<code>\GTSOIR/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedOutIncidence/</code>	<code>\GTSnOI/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedOutIncidenceRelation/</code>	<code>\GTSnOIR/</code>	$\circ$	$v \circ e$
<code>\GTSinIncidence/</code>	<code>\GTSiI/</code>	$\circ$	$v \circ e$
<code>\GTSinIncidenceRelation/</code>	<code>\GTSiIR/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedInIncidence/</code>	<code>\GTSnII/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedInIncidenceRelation/</code>	<code>\GTSnIIR/</code>	$\circ$	$v \circ e$
Long name	Short name	Result	In context
<code>\GTSadjacencyMonochrome/</code>	<code>\GTSaM/</code>	$\circ$	$u \circ v$
<code>\GTSadjacencyMonochromeRelation/</code>	<code>\GTSaMR/</code>	$\circ$	$u \circ v$
<code>\GTSunadjacencyMonochrome/</code>	<code>\GTSuM/</code>	$\circ$	$u \circ v$
<code>\GTSunadjacencyMonochromeRelation/</code>	<code>\GTSuMR/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyUpMonochrome/</code>	<code>\GTSdAUM/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyUpMonochromeRelation/</code>	<code>\GTSdAUMR/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyUpMonochrome/</code>	<code>\GTSnDAUM/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyUpMonochromeRelation/</code>	<code>\GTSnDAUMR/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyDownMonochrome/</code>	<code>\GTSdADM/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyDownMonochromeRelation/</code>	<code>\GTSdADMR/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyDownMonochrome/</code>	<code>\GTSnDADM/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyDownMonochromeRelation/</code>	<code>\GTSnDADMR/</code>	$\circ$	$u \circ v$
<code>\GTSincidenceMonochrome/</code>	<code>\GTSiM/</code>	$\circ$	$v \circ e$
<code>\GTSincidenceMonochromeRelation/</code>	<code>\GTSiMR/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedIncidenceMonochrome/</code>	<code>\GTSnIM/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedIncidenceMonochromeRelation/</code>	<code>\GTSnIMR/</code>	$\circ$	$v \circ e$
<code>\GTSoutIncidenceMonochrome/</code>	<code>\GTSOIM/</code>	$\circ$	$v \circ e$
<code>\GTSoutIncidenceMonochromeRelation/</code>	<code>\GTSOIMR/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedOutIncidenceMonochrome/</code>	<code>\GTSnOIM/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedOutIncidenceMonochromeRelation/</code>	<code>\GTSnOIMR/</code>	$\circ$	$v \circ e$
<code>\GTSinIncidenceMonochrome/</code>	<code>\GTSiIM/</code>	$\circ$	$v \circ e$
<code>\GTSinIncidenceMonochromeRelation/</code>	<code>\GTSiIMR/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedInIncidenceMonochrome/</code>	<code>\GTSnIIM/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedInIncidenceMonochromeRelation/</code>	<code>\GTSnIIMR/</code>	$\circ$	$v \circ e$

\GTSsetMainColor{blue}			
Long name	Short name	Result	In context
\GTSadjacency/	\GTSa/		u v
\GTSadjacencyRelation/	\GTSaR/		u v
\GTSunadjacency/	\GTSu/		u v
\GTSunadjacencyRelation/	\GTSuR/		u v
\GTSdirectedAdjacencyUp/	\GTSdAU/		u v
\GTSdirectedAdjacencyUpRelation/	\GTSdAUR/		u v
\GTSnegatedDirectedAdjacencyUp/	\GTSnDAU/		u v
\GTSnegatedDirectedAdjacencyUpRelation/	\GTSnDAUR/		u v
\GTSdirectedAdjacencyDown/	\GTSdAD/		u v
\GTSdirectedAdjacencyDownRelation/	\GTSdADR/		u v
\GTSnegatedDirectedAdjacencyDown/	\GTSnDAD/		u v
\GTSnegatedDirectedAdjacencyDownRelation/	\GTSnDADR/		u v
\GTSincidence/	\GTSi/		v e
\GTSincidenceRelation/	\GTSiR/		v e
\GTSnegatedIncidence/	\GTSnI/		v e
\GTSnegatedIncidenceRelation/	\GTSnIR/		v e
\GTSoutIncidence/	\GTSOI/		v e
\GTSoutIncidenceRelation/	\GTSOIR/		v e
\GTSnegatedOutIncidence/	\GTSnOI/		v e
\GTSnegatedOutIncidenceRelation/	\GTSnOIR/		v e
\GTSinIncidence/	\GTSiI/		v e
\GTSinIncidenceRelation/	\GTSiIR/		v e
\GTSnegatedInIncidence/	\GTSnII/		v e
\GTSnegatedInIncidenceRelation/	\GTSnIIR/		v e

2.2 Detailed usage

First you need to add in your preamble: `\usepackage{graph-theory-symbol}`.

All symbols macros were designed with ease of use in mind: they are called with a trailing slash, they can be called in text mode or in math mode, a variant with relation spacing for math mode exists with suffix “relation”.

`\GTS@newcommand` This macro will enforce that the other macros are called with a trailing slash, avoiding problems with spaces after macro call.

Arguments:

`{\langle commandname \rangle}` The name of the command to create.

`{\langle commandcode \rangle}` The code of the command to create.

`\GTSsetMainColor` This macro will set the main color used in GraphTheorySymbol. This color has initial value “black”.

Argument:

`{\langle color \rangle}` The color that must be used by GraphTheorySymbol afterward.

`\GTSsetSecondColor` This macro will set the second color used in GraphTheorySymbol. This color has initial value “gray”.

Argument:

`{\langle color \rangle}` The color that must be used by GraphTheorySymbol afterward.

`\GTS@a` This macro will draw any of the adjacency symbols if the correct arguments are given. It is not expected to be used directly. See the macros derived from it and `\GTS@b`: `\GTSxadjacency`, `\GTSxadj`, and `\GTSxa`.

Arguments:

`{\langle mainColor \rangle}` If non-empty, this color will be used as main color.

`{\langle secondColor \rangle}` If non-empty, this color will be used as second color.

`{\langle drawSlash \rangle}` Non-empty implies that a negation will be drawn.

`{\langle drawUpArrow \rangle}` Non-empty implies that an up-arrow will be drawn.

`{\langle drawDownArrow \rangle}` Non-empty implies that a down-arrow will be drawn.

`\GTS@b` This macro builds on top of `\GTS@a` to handle mathematical relation spacing if sixth argument is not empty. It is not expected to be used directly. See the macros derived from it and `\GTS@a`: `\GTSxadjacency`, `\GTSxadj`, and `\GTSxa`.

Arguments:

`{\langle mainColor \rangle}` If non-empty, this color will be used as main color.

`{\langle secondColor \rangle}` If non-empty, this color will be used as second color.

`{\langle drawSlash \rangle}` Non-empty implies that a negation will be drawn.

`{\langle drawUpArrow \rangle}` Non-empty implies that an up-arrow will be drawn.

`{\langle drawDownArrow \rangle}` Non-empty implies that a down-arrow will be drawn.

`{\langle relation \rangle}` Non-empty implies that relation spacing will be added.

`\GTSxa` Versatile macros for adjacency that can be given options.

`\GTSxadj` Argument:

`\GTSxadjacency` `[\langle optionsList \rangle]` Sets the following options if not empty:
`mainColor=color1` or `mainC=color1` or `mColor=color1` or `mC=color1`,
`secondColor=color2` or `secondC=color2` or `sColor=color2` or `sC=color2`,
`monochrome` or `mono` or `mon` or `m` (equivalent to `mC=black,sC=black`),
`negated` or `not` or `n`,
`up` or `u`,
`down` or `d`,
`relation` or `rel` or `r`.

`\GTSadjacency` This macro will draw an adjacency symbol. A first drawing didn’t include the small dots in the middle of the two circles corresponding to the graph vertices. But it was too similar to “spoon” and multimap symbols, and could be confused with a graph with only two vertices and one edge. Hence, these dots were added and they have the nice property to remind of the classical textual notation of adjacency relation as `Adj(.,.)`.

`A.\GTSadjacency/A.`

or `A.\GTSadj/A.`

or `A.\GTSa/A.`

will yield $A \circ A$.

`u \GTSadjacency/ v`

`or u \GTSadj/ v`
`or u \GTSa/ v`
 will yield $u \overset{\circ}{\parallel} v$.
`$u \GTSadjacency/ v$`
`or $u \GTSadj/ v$`
`or $u \GTSa/ v$`
 will yield $u \overset{\circ}{\parallel} v$.

`\GTSadjacencyRelation` This macro will draw an adjacency symbol.
`\GTSadjRel $u\GTSadjacencyRelation/v$`
`\GTSaR or $u\GTSadjRel/v$`
`or $u\GTSaR/v$`
 will yield $u \overset{\circ}{\parallel} v$.

`\GTSunadjacency` This macro will draw an unadjacency symbol.
`\GTSunadj A.\GTSunadjacency/A.`
`\GTSu or A.\GTSunadj/A.`
`or A.\GTSu/A.`
 will yield $A \overset{\circ}{\parallel} A$.
`u \GTSunadjacency/ v`
`or u \GTSunadj/ v`
`or u \GTSu/ v`
 will yield $u \overset{\circ}{\parallel} v$.
`$u \GTSunadjacency/ v$`
`or $u \GTSunadj/ v$`
`or $u \GTSu/ v$`
 will yield $u \overset{\circ}{\parallel} v$.

`\GTSunadjacencyRelation` This macro will draw an unadjacency symbol.
`\GTSunadjRel $u\GTSunadjacencyRelation/v$`
`\GTSuR or $u\GTSunadjRel/v$`
`or $u\GTSuR/v$`
 will yield $u \overset{\circ}{\parallel} v$.

`\GTSdirectedAdjacencyUp` This macro will draw a directed adjacency upward symbol. The operand on the left
`\GTSdirAdjUp` of the symbol should be considered the source of the arc; the operand on the right of the
`\GTSdAU` symbol should be considered the target of the arc.
`A.\GTSdirectedAdjacencyUp/A.`
`or A.\GTSdirAdjUp/A.`
`or A.\GTSdAU/A.`
 will yield $A \overset{\circ}{\parallel} A$.
`u \GTSdirectedAdjacencyUp/ v`
`or u \GTSdirAdjUp/ v`
`or u \GTSdAU/ v`
 will yield $u \overset{\circ}{\parallel} v$.
`$u \GTSdirectedAdjacencyUp/ v$`
`or $u \GTSdirAdjUp/ v$`
`or $u \GTSdAU/ v$`
 will yield $u \overset{\circ}{\parallel} v$.

`\GTSdirectedAdjacencyUp-` This macro will draw a directed adjacency upward symbol with relation spacing in
`Relation` math mode.
`\GTSdirAdjUpRel $u\GTSdirectedAdjacencyUpRelation/v$`
`\GTSdAUR or $u\GTSdirAdjUpRel/v$`
`or $u\GTSdAUR/v$`
 will yield $u \overset{\circ}{\parallel} v$.

`\GTSnegatedDirected-` This macro will draw a negated directed adjacency upward symbol.
`AdjacencyUp` `A.\GTSnegatedDirectedAdjacencyUp/A.`
`\GTSnegDirAdjUp` `or A.\GTSnegDirAdjUp/A.`
`\GTSnDAU` `or A.\GTSnDAU/A.`
 will yield $A \overset{\circ}{\parallel} A$.
`u \GTSnegatedDirectedAdjacencyUp/ v`
`or u \GTSnegDirAdjUp/ v`

or `u \GTSnDAU/ v`
will yield $u \overset{\curvearrowright}{\sim} v$.
`\GTSnegatedDirectedAdjacencyUp/ v$`
or `\GTSnegDirAdjUp/ v$`
or `\GTSnDAU/ v$`
will yield $u \overset{\curvearrowright}{\sim} v$.

`\GTSnegatedDirectedAdjacencyUpRelation` This macro will draw a negated directed adjacency upward symbol with relation spacing in math mode.

`\GTSnegDirAdjUpRel $u\GTSnegatedDirectedAdjacencyUpRelation/v$`
`\GTSnDAUR` or `\GTSnegDirAdjUpRel/v$`
or `\GTSnDAUR/v$`
will yield $u \overset{\curvearrowright}{\sim} v$.

`\GTSdirectedAdjacencyDown` This macro will draw a directed adjacency downward symbol. The operand on the left of the symbol should be considered the target of the arc; the operand on the right of the symbol should be considered the source of the arc.

`A.\GTSdirectedAdjacencyDown/A.`
or `A.\GTSdirAdjDown/A.`
or `A.\GTSnDAD/A.`
will yield $A \overset{\curvearrowright}{\sim} A$.
`u \GTSdirectedAdjacencyDown/ v`
or `u \GTSdirAdjDown/ v`
or `u \GTSnDAD/ v`
will yield $u \overset{\curvearrowright}{\sim} v$.
`$u \GTSdirectedAdjacencyDown/ v$`
or `$u \GTSdirAdjDown/ v$`
or `$u \GTSnDAD/ v$`
will yield $u \overset{\curvearrowright}{\sim} v$.

`\GTSdirectedAdjacencyDownRelation` This macro will draw a directed adjacency downward symbol with relation spacing in math mode.

`\GTSdirAdjDownRel $u\GTSdirectedAdjacencyDownRelation/v$`
`\GTSdADR` or `\GTSdirAdjDownRel/v$`
or `\GTSdADR/v$`
will yield $u \overset{\curvearrowright}{\sim} v$.

`\GTSnegatedDirectedAdjacencyDown` This macro will draw a negated directed adjacency downward symbol.

`A.\GTSnegatedDirectedAdjacencyDown/A.`
`\GTSnegDirAdjDown` or `A.\GTSnegDirAdjDown/A.`
`\GTSnDAD` or `A.\GTSnDAD/A.`
will yield $A \overset{\curvearrowright}{\sim} A$.
`u \GTSnegatedDirectedAdjacencyDown/ v`
or `u \GTSnegDirAdjDown/ v`
or `u \GTSnDAD/ v`
will yield $u \overset{\curvearrowright}{\sim} v$.
`$u \GTSnegatedDirectedAdjacencyDown/ v$`
or `$u \GTSnegDirAdjDown/ v$`
or `$u \GTSnDAD/ v$`
will yield $u \overset{\curvearrowright}{\sim} v$.

`\GTSnegatedDirectedAdjacencyDownRelation` This macro will draw a negated directed adjacency downward symbol with relation spacing in math mode.

`\GTSnegDirAdjDownRel $u\GTSnegatedDirectedAdjacencyDownRelation/v$`
`\GTSnDADR` or `\GTSnegDirAdjDownRel/v$`
or `\GTSnDADR/v$`
will yield $u \overset{\curvearrowright}{\sim} v$.

`\GTS@i` This macro will draw any of the incidence symbols if the correct arguments are given. It is not expected to be used directly. See the macros derived from it and `\GTS@j`: `\GTSxincidence`, `\GTSxinc`, and `\GTSxi`. The operand on the left of the symbol should be considered the vertex to which the edge/the operand on the right of the symbol is incident.
Arguments:

`{\mainColor}` If non-empty, this color will be used as main color.
`{\secondColor}` If non-empty, this color will be used as second color.
`{\drawSlash}` Non-empty implies that a negation will be drawn.
`{\drawUpArrow}` Non-empty implies that an up-arrow will be drawn.
`{\drawDownArrow}` Non-empty implies that a down-arrow will be drawn.

`\GTS@j` This macro builds on top of `\GTS@i` to handle mathematical relation spacing if sixth argument is not empty. It is not expected to be used directly. See the macros derived from it and `\GTS@i`: `\GTSxincidence`, `\GTSxinc`, and `\GTSxi`.

Arguments:

`{\mainColor}` If non-empty, this color will be used as main color.
`{\secondColor}` If non-empty, this color will be used as second color.
`{\drawSlash}` Non-empty implies that a negation will be drawn.
`{\drawUpArrow}` Non-empty implies that an up-arrow will be drawn.
`{\drawDownArrow}` Non-empty implies that a down-arrow will be drawn.
`{\relation}` Non-empty implies that relation spacing will be added.

`\GTSxi` Versatile macros for incidence that can be given options.

`\GTSxinc` Argument:

`\GTSxincidence` [`\optionsList`] Sets the following options if not empty:
`mainColor=color1` or `mainC=color1` or `mColor=color1` or `mC=color1`,
`secondColor=color2` or `secondC=color2` or `sColor=color2` or `sC=color2`,
`monochrome` or `mono` or `mon` or `m` (equivalent to `mC=black,sC=black`),
`negated` or `not` or `n`,
`in` or `i`,
`out` or `o`,
`relation` or `rel` or `r`.

`\GTSincidence` This macro will draw an incidence symbol. The operand on the left of the symbol should be considered the vertex to which the edge/the operand on the right of the symbol is incident.

`\GTSi` `A.\GTSincidence/A.`
or `A.\GTSinc/A.`
or `A.\GTSi/A.`
will yield $A \downarrow A$.
`v \GTSincidence/ e`
or `v \GTSinc/ e`
or `v \GTSi/ e`
will yield $v \downarrow e$.
`$v \GTSincidence/ e$`
or `$v \GTSinc/ e$`
or `$v \GTSi/ e$`
will yield $v \downarrow e$.

`\GTSincidenceRelation` This macro will draw an incidence symbol with relation spacing in math mode.

`\GTSincRel` `$v\GTSincidenceRelation/e$`
`\GTSiR` or `$v\GTSincRel/e$`
or `$v\GTSiR/e$`
will yield $v \downarrow e$.

`\GTSnegatedIncidence` This macro will draw a negated incidence symbol.

`\GTSnegInc` `A.\GTSnegatedIncidence/A.`
`\GTSnI` or `A.\GTSnegInc/A.`
or `A.\GTSnI/A.`
will yield $A \not\downarrow A$.
`v \GTSnegatedIncidence/ e`
or `v \GTSnegInc/ e`
or `v \GTSnI/ e`
will yield $v \not\downarrow e$.
`$v \GTSnegatedIncidence/ e$`
or `$v \GTSnegInc/ e$`
or `$v \GTSnI/ e$`
will yield $v \not\downarrow e$.

`\GTSnegatedIncidence-` This macro will draw a negated incidence symbol with relation spacing in math mode.
`Relation` `$v\GTSnegatedIncidenceRelation/e$`
`\GTSnegIncRel` or `$v\GTSnegIncRel/e$`
`\GTSnIR` or `$v\GTSnIR/e$`
will yield $v \not\hookrightarrow e$.

`\GTSoutIncidence` This macro will draw a directed incidence upward (out(ward) incidence) symbol. The
`\GTSoutInc` operand on the left of the symbol should be considered the vertex to which the arc/the
`\GTSOI` operand on the right of the symbol is incident.
`A.\GTSoutIncidence/A.`
or `A.\GTSoutInc/A.`
or `A.\GTSOI/A.`
will yield $A.\overset{\uparrow}{\hookrightarrow}A.$
`v \GTSoutIncidence/ e`
or `v \GTSoutInc/ e`
or `v \GTSOI/ e`
will yield $v \overset{\uparrow}{\hookrightarrow} e.$
`$v \GTSoutIncidence/ e$`
or `$v \GTSoutInc/ e$`
or `$v \GTSOI/ e$`
will yield $v\overset{\uparrow}{\hookrightarrow}e.$

`\GTSoutIncidenceRelation` This macro will draw a directed incidence upward (out(ward) incidence) symbol with
`\GTSoutIncRel` relation spacing in math mode.
`\GTSOIR` `$v\GTSoutIncidenceRelation/e$`
or `$v\GTSoutIncRel/e$`
or `$v\GTSOIR/e$`
will yield $v \overset{\uparrow}{\hookrightarrow} e.$

`\GTSnegatedOutIncidence` This macro will draw a negated directed incidence upward (out(ward) incidence) symbol.
`\GTSnegOutInc` `A.\GTSnegatedOutIncidence/A.`
`\GTSnOI` or `A.\GTSnegOutInc/A.`
or `A.\GTSnOI/A.`
will yield $A.\not\overset{\uparrow}{\hookrightarrow}A.$
`v \GTSnegatedOutIncidence/ e`
or `v \GTSnegOutInc/ e`
or `v \GTSnOI/ e`
will yield $v \not\overset{\uparrow}{\hookrightarrow} e.$
`$v \GTSnegatedOutIncidence/ e$`
or `$v \GTSnegOutInc/ e$`
or `$v \GTSnOI/ e$`
will yield $v\not\overset{\uparrow}{\hookrightarrow}e.$

`\GTSnegatedOutIncidence-` This macro will draw a negated directed incidence upward (out(ward) incidence)
`Relation` symbol with relation spacing in math mode.
`\GTSnegOutIncRel` `$v\GTSnegatedOutIncidenceRelation/e$`
`\GTSnOIR` or `$v\GTSnegOutIncRel/e$`
or `$v\GTSnOIR/e$`
will yield $v \not\overset{\uparrow}{\hookrightarrow} e.$

`\GTSinIncidence` This macro will draw a directed incidence downward (in(ward) incidence) symbol. The
`\GTSinInc` operand on the left of the symbol should be considered the vertex to which the arc/the
`\GTSiI` operand on the right of the symbol is incident.
`A.\GTSinIncidence/A.`
or `A.\GTSinInc/A.`
or `A.\GTSiI/A.`
will yield $A.\overset{\downarrow}{\hookrightarrow}A.$
`v \GTSinIncidence/ e`
or `v \GTSinInc/ e`
or `v \GTSiI/ e`
will yield $v \overset{\downarrow}{\hookrightarrow} e.$
`$v \GTSinIncidence/ e$`
or `$v \GTSinInc/ e$`

or $\$v \backslash \text{GTSiI} / e\$$
will yield $v \overset{\circ}{\dashv} e$.

$\backslash \text{GTSinIncidenceRelation}$ This macro will draw a directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.

$\backslash \text{GTSinIncRel}$ $\$v \backslash \text{GTSinIncidenceRelation} / e\$$
or $\$v \backslash \text{GTSinIncRel} / e\$$
or $\$v \backslash \text{GTSiIR} / e\$$
will yield $v \overset{\circ}{\dashv} e$.

$\backslash \text{GTSnegatedInIncidence}$ This macro will draw a negated directed incidence downward (in(ward) incidence) symbol.

$\backslash \text{GTSnegInInc}$ $A. \backslash \text{GTSnegatedInIncidence} / A.$
or $A. \backslash \text{GTSnegInInc} / A.$
or $A. \backslash \text{GTSnII} / A.$
will yield $A. \overset{\circ}{\dashv} A.$
 $v \backslash \text{GTSnegatedInIncidence} / e$
or $v \backslash \text{GTSnegInInc} / e$
or $v \backslash \text{GTSnII} / e$
will yield $v \overset{\circ}{\dashv} e.$
 $\$v \backslash \text{GTSnegatedInIncidence} / e\$$
or $\$v \backslash \text{GTSnegInInc} / e\$$
or $\$v \backslash \text{GTSnII} / e\$$
will yield $v \overset{\circ}{\dashv} e.$

$\backslash \text{GTSnegatedInIncidence-Relation}$ This macro will draw a negated directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.

$\backslash \text{GTSnegInIncRel}$ $\$v \backslash \text{GTSnegatedInIncidenceRelation} / e\$$
 $\backslash \text{GTSnIIR}$ or $\$v \backslash \text{GTSnegInIncRel} / e\$$
or $\$v \backslash \text{GTSnIIR} / e\$$
will yield $v \overset{\circ}{\dashv} e.$

$\backslash \text{GTSadjacencyMonochrome}$ This macro will draw a monochrome adjacency symbol.

$\backslash \text{GTSadjMono}$ $A. \backslash \text{GTSadjacencyMonochrome} / A.$
 $\backslash \text{GTSadjMon}$ or $A. \backslash \text{GTSadjMono} / A.$
 $\backslash \text{GTSaM}$ or $A. \backslash \text{GTSadjMon} / A.$
or $A. \backslash \text{GTSaM} / A.$
will yield $A. \overset{\circ}{\circ} A.$
 $u \backslash \text{GTSadjacencyMonochrome} / v$
or $u \backslash \text{GTSadjMono} / v$
or $u \backslash \text{GTSadjMon} / v$
or $u \backslash \text{GTSaM} / v$
will yield $u \overset{\circ}{\circ} v.$
 $\$u \backslash \text{GTSadjacencyMonochrome} / v\$$
or $\$u \backslash \text{GTSadjMono} / v\$$
or $\$u \backslash \text{GTSadjMon} / v\$$
or $\$u \backslash \text{GTSaM} / v\$$
will yield $u \overset{\circ}{\circ} v.$

$\backslash \text{GTSadjacencyMonochrome-Relation}$ This macro will draw a monochrome adjacency symbol with relation spacing in math mode.

$\backslash \text{GTSadjMonoRel}$ $\$u \backslash \text{GTSadjacencyMonochromeRelation} / v\$$
 $\backslash \text{GTSadjMonRel}$ or $\$u \backslash \text{GTSadjMonoRel} / v\$$
 $\backslash \text{GTSaMR}$ or $\$u \backslash \text{GTSadjMonRel} / v\$$
or $\$u \backslash \text{GTSaMR} / v\$$
will yield $u \overset{\circ}{\circ} v.$

$\backslash \text{GTSunadjacencyMonochrome}$ This macro will draw a monochrome unadjacency symbol.

$\backslash \text{GTSunadjMono}$ $A. \backslash \text{GTSunadjacencyMonochrome} / A.$
 $\backslash \text{GTSunadjMon}$ or $A. \backslash \text{GTSunadjMono} / A.$
 $\backslash \text{GTSuM}$ or $A. \backslash \text{GTSunadjMon} / A.$
or $A. \backslash \text{GTSuM} / A.$
will yield $A. \overset{\circ}{\circ} A.$
 $u \backslash \text{GTSunadjacencyMonochrome} / v$

or u \GTSunadjMono/ v
 or u \GTSunadjMon/ v
 or u \GTSuM/ v
 will yield $u \overset{\circ}{\parallel} v$.
 \$u \GTSunadjacencyMonochrome/ v\$
 or \$u \GTSunadjMono/ v\$
 or \$u \GTSunadjMon/ v\$
 or \$u \GTSuM/ v\$
 will yield $u \overset{\circ}{\parallel} v$.

\GTSunadjacencyMonochrome- This macro will draw a monochrome unadjacency symbol with relation spacing in
 Relation math mode.

\GTSunadjMonoRel \$u\GTSunadjacencyMonochromeRelation/v\$
 \GTSunadjMonRel or \$u\GTSunadjMonoRel/v\$
 \GTSuMR or \$u\GTSunadjMonRel/v\$
 or \$u\GTSuMR/v\$
 will yield $u \overset{\circ}{\parallel} v$.

\GTSdirectedAdjacencyUp- This macro will draw a monochrome directed adjacency upward symbol. The operand
 Monochrome on the left of the symbol should be considered the source of the arc; the operand on the
 \GTSdirAdjUpMono right of the symbol should be considered the target of the arc.

\GTSdirAdjUpMon A.\GTSdirectedAdjacencyUpMonochrome/A.
 \GTSdAUM or A.\GTSdirAdjUpMono/A.
 or A.\GTSdirAdjUpMon/A.
 or A.\GTSdAUM/A.
 will yield $A \overset{\circ}{\parallel} A$.
 u \GTSdirectedAdjacencyUpMonochrome/ v
 or u \GTSdirAdjUpMono/ v
 or u \GTSdirAdjUpMon/ v
 or u \GTSdAUM/ v
 will yield $u \overset{\circ}{\parallel} v$.
 \$u \GTSdirectedAdjacencyUpMonochrome/ v\$
 or \$u \GTSdirAdjUpMono/ v\$
 or \$u \GTSdirAdjUpMon/ v\$
 or \$u \GTSdAUM/ v\$
 will yield $u \overset{\circ}{\parallel} v$.

\GTSdirectedAdjacencyUp- This macro will draw a monochrome directed adjacency upward symbol with relation
 MonochromeRelation spacing in math mode.

\GTSdirAdjUpMonoRel \$u\GTSdirectedAdjacencyUpMonochromeRelation/v\$
 \GTSdirAdjUpMonRel or \$u\GTSdirAdjUpMonoRel/v\$
 \GTSdAUMR or \$u\GTSdirAdjUpMonRel/v\$
 or \$u\GTSdAUMR/v\$
 will yield $u \overset{\circ}{\parallel} v$.

\GTSnegatedDirected- This macro will draw a monochrome negated directed adjacency upward symbol.

AdjacencyUpMonochrome A.\GTSnegatedDirectedAdjacencyUpMonochrome/A.
 \GTSnegDirAdjUpMono or A.\GTSnegDirAdjUpMono/A.
 \GTSnegDirAdjUpMon or A.\GTSnegDirAdjUpMon/A.
 \GTSnDAUM or A.\GTSnDAUM/A.
 will yield $A \overset{\circ}{\parallel} A$.
 u \GTSnegatedDirectedAdjacencyUpMonochrome/ v
 or u \GTSnegDirAdjUpMono/ v
 or u \GTSnegDirAdjUpMon/ v
 or u \GTSnDAUM/ v
 will yield $u \overset{\circ}{\parallel} v$.
 \$u \GTSnegatedDirectedAdjacencyUpMonochrome/ v\$
 or \$u \GTSnegDirAdjUpMono/ v\$
 or \$u \GTSnegDirAdjUpMon/ v\$
 or \$u \GTSnDAUM/ v\$
 will yield $u \overset{\circ}{\parallel} v$.

`\GTSnegatedDirected-` This macro will draw a monochrome negated directed adjacency upward symbol with
`AdjacencyUpMonochrome-` relation spacing in math mode.
`Relation` `\GTSnegatedDirectedAdjacencyUpMonochromeRelation/v$`
`\GTSnegDirAdjUpMonoRel` or `\GTSnegDirAdjUpMonoRel/v$`
`\GTSnegDirAdjUpMonRel` or `\GTSnegDirAdjUpMonRel/v$`
`\GTSnDAUMR` or `\GTSnDAUMR/v$`
will yield $u \overset{\circ}{\frown} v$.

`\GTSdirectedAdjacencyDown-` This macro will draw a monochrome directed adjacency downward symbol. The
`Monochrome` operand on the left of the symbol should be considered the target of the arc; the operand
`\GTSdirAdjDownMono` on the right of the symbol should be considered the source of the arc.
`\GTSdirAdjDownMon` `A.\GTSdirectedAdjacencyDownMonochrome/A.`
`\GTSdADM` or `A.\GTSdirAdjDownMono/A.`
or `A.\GTSdirAdjDownMon/A.`
or `A.\GTSdADM/A.`
will yield $A \overset{\circ}{\smile} A$.
`u \GTSdirectedAdjacencyDownMonochrome/ v`
or `u \GTSdirAdjDownMono/ v`
or `u \GTSdirAdjDownMon/ v`
or `u \GTSdADM/ v`
will yield $u \overset{\circ}{\smile} v$.
`$u \GTSdirectedAdjacencyDownMonochrome/ v$`
or `$u \GTSdirAdjDownMono/ v$`
or `$u \GTSdirAdjDownMon/ v$`
or `$u \GTSdADM/ v$`
will yield $u \overset{\circ}{\smile} v$.

`\GTSdirectedAdjacencyDown-` This macro will draw a monochrome directed adjacency downward symbol with
`MonochromeRelation` relation spacing in math mode.
`\GTSdirAdjDownMonoRel` `\GTSdirectedAdjacencyDownMonochromeRelation/v$`
`\GTSdirAdjDownMonRel` or `\GTSdirAdjDownMonoRel/v$`
`\GTSdADMR` or `\GTSdirAdjDownMonRel/v$`
or `\GTSdADMR/v$`
will yield $u \overset{\circ}{\smile} v$.

`\GTSnegatedDirected-` This macro will draw a monochrome negated directed adjacency downward symbol.
`AdjacencyDownMonochrome` `A.\GTSnegatedDirectedAdjacencyDownMonochrome/A.`
`\GTSnegDirAdjDownMono` or `A.\GTSnegDirAdjDownMono/A.`
`\GTSnegDirAdjDownMon` or `A.\GTSnegDirAdjDownMon/A.`
`\GTSnDADM` or `A.\GTSnDADM/A.`
will yield $A \overset{\circ}{\frown} A$.
`u \GTSnegatedDirectedAdjacencyDownMonochrome/ v`
or `u \GTSnegDirAdjDownMono/ v`
or `u \GTSnegDirAdjDownMon/ v`
or `u \GTSnDADM/ v`
will yield $u \overset{\circ}{\frown} v$.
`$u \GTSnegatedDirectedAdjacencyDownMonochrome/ v$`
or `$u \GTSnegDirAdjDownMono/ v$`
or `$u \GTSnegDirAdjDownMon/ v$`
or `$u \GTSnDADM/ v$`
will yield $u \overset{\circ}{\frown} v$.

`\GTSnegatedDirected-` This macro will draw a monochrome negated directed adjacency downward symbol
`AdjacencyDownMonochrome-` with relation spacing in math mode.
`Relation` `\GTSnegatedDirectedAdjacencyDownMonochromeRelation/v$`
`\GTSnegDirAdjDownMonoRel` or `\GTSnegDirAdjDownMonoRel/v$`
`\GTSnegDirAdjDownMonRel` or `\GTSnegDirAdjDownMonRel/v$`
`\GTSnDADMR` or `\GTSnDADMR/v$`
will yield $u \overset{\circ}{\frown} v$.

`\GTSincidenceMonochrome` This macro will draw a monochrome incidence symbol. The operand on the left of the
`\GTSincMono` symbol should be considered the vertex to which the edge/the operand on the right of the
`\GTSincMon` symbol is incident.
`\GTSiM` `A.\GTSincidenceMonochrome/A.`

or A.\GTSincMono/A.
 or A.\GTSincMon/A.
 or A.\GTSiM/A.
 will yield $A \downarrow A$.
 v \GTSincidenceMonochrome/ e
 or v \GTSincMono/ e
 or v \GTSincMon/ e
 or v \GTSiM/ e
 will yield $v \downarrow e$.
 \$v \GTSincidenceMonochrome/ e\$
 or \$v \GTSincMono/ e\$
 or \$v \GTSincMon/ e\$
 or \$v \GTSiM/ e\$
 will yield $v \downarrow e$.

\GTSincidenceMonochrome- This macro will draw a monochrome incidence symbol with relation spacing in math
 Relation mode.

\GTSincMonoRel \$v\GTSincidenceMonochromeRelation/e\$
 \GTSincMonRel or \$v\GTSincMonoRel/e\$
 \GTSiMR or \$v\GTSincMonRel/e\$
 or \$v\GTSiMR/e\$
 will yield $v \downarrow e$.

\GTSnegatedIncidence- This macro will draw a monochrome negated incidence symbol.

Monochrome A.\GTSnegatedIncidenceMonochrome/A.
 \GTSnegIncMono or A.\GTSnegIncMono/A.
 \GTSnegIncMon or A.\GTSnegIncMon/A.
 \GTSnIM or A.\GTSnIM/A.
 will yield $A \downarrow A$.
 v \GTSnegatedIncidenceMonochrome/ e
 or v \GTSnegIncMono/ e
 or v \GTSnegIncMon/ e
 or v \GTSnIM/ e
 will yield $v \downarrow e$.
 \$v \GTSnegatedIncidenceMonochrome/ e\$
 or \$v \GTSnegIncMono/ e\$
 or \$v \GTSnegIncMon/ e\$
 or \$v \GTSnIM/ e\$
 will yield $v \downarrow e$.

\GTSnegatedIncidence- This macro will draw a monochrome negated incidence symbol with relation spacing
 MonochromeRelation in math mode.

\GTSnegIncMonoRel \$v\GTSnegatedIncidenceMonochromeRelation/e\$
 \GTSnegIncMonRel or \$v\GTSnegIncMonoRel/e\$
 \GTSnIMR or \$v\GTSnegIncMonRel/e\$
 or \$v\GTSnIMR/e\$
 will yield $v \downarrow e$.

\GTSoutIncidenceMonochrome This macro will draw a monochrome directed incidence upward (out(ward) incidence)
 \GTSoutIncMono symbol. The operand on the left of the symbol should be considered the vertex to which
 \GTSoutIncMon the arc/the operand on the right of the symbol is incident.

\GTSoIM A.\GTSoutIncidenceMonochrome/A.
 or A.\GTSoutIncMono/A.
 or A.\GTSoutIncMon/A.
 or A.\GTSoIM/A.
 will yield $A \uparrow A$.
 v \GTSoutIncidenceMonochrome/ e
 or v \GTSoutIncMono/ e
 or v \GTSoutIncMon/ e
 or v \GTSoIM/ e
 will yield $v \uparrow e$.
 \$v \GTSoutIncidenceMonochrome/ e\$
 or \$v \GTSoutIncMono/ e\$

or $\$v \backslash \text{GTSoutIncMon}/ e\$$
or $\$v \backslash \text{GTSOIM}/ e\$$
will yield $v \uparrow e$.

$\backslash \text{GTSoutIncidenceMonochrome-}$ This macro will draw a monochrome directed incidence upward (out(ward) incidence)
Relation symbol with relation spacing in math mode.
 $\backslash \text{GTSoutIncMonoRel}$ $\$v \backslash \text{GTSoutIncidenceMonochromeRelation}/ e\$$
 $\backslash \text{GTSoutIncMonRel}$ or $\$v \backslash \text{GTSoutIncMonoRel}/ e\$$
 $\backslash \text{GTSOIMR}$ or $\$v \backslash \text{GTSoutIncMonRel}/ e\$$
or $\$v \backslash \text{GTSOIMR}/ e\$$
will yield $v \uparrow e$.

$\backslash \text{GTSnegatedOutIncidence-}$ This macro will draw a monochrome negated directed incidence upward (out(ward)
Monochrome incidence) symbol.
 $\backslash \text{GTSnegOutIncMono}$ $A. \backslash \text{GTSnegatedOutIncidenceMonochrome}/ A.$
 $\backslash \text{GTSnegOutIncMon}$ or $A. \backslash \text{GTSnegOutIncMono}/ A.$
 $\backslash \text{GTSnOIM}$ or $A. \backslash \text{GTSnegOutIncMon}/ A.$
or $A. \backslash \text{GTSnOIM}/ A.$
will yield $A. \uparrow A.$
 $v \backslash \text{GTSnegatedOutIncidenceMonochrome}/ e$
or $v \backslash \text{GTSnegOutIncMono}/ e$
or $v \backslash \text{GTSnegOutIncMon}/ e$
or $v \backslash \text{GTSnOIM}/ e$
will yield $v \uparrow e$.
 $\$v \backslash \text{GTSnegatedOutIncidenceMonochrome}/ e\$$
or $\$v \backslash \text{GTSnegOutIncMono}/ e\$$
or $\$v \backslash \text{GTSnegOutIncMon}/ e\$$
or $\$v \backslash \text{GTSnOIM}/ e\$$
will yield $v \uparrow e$.

$\backslash \text{GTSnegatedOutIncidence-}$ This macro will draw a monochrome negated directed incidence upward (out(ward)
MonochromeRelation incidence) symbol with relation spacing in math mode.
 $\backslash \text{GTSnegOutIncMonoRel}$ $\$v \backslash \text{GTSnegatedOutIncidenceMonochromeRelation}/ e\$$
 $\backslash \text{GTSnegOutIncMonRel}$ or $\$v \backslash \text{GTSnegOutIncMonoRel}/ e\$$
 $\backslash \text{GTSnOIMR}$ or $\$v \backslash \text{GTSnegOutIncMonRel}/ e\$$
or $\$v \backslash \text{GTSnOIMR}/ e\$$
will yield $v \uparrow e$.

$\backslash \text{GTSinIncidenceMonochrome}$ This macro will draw a monochrome directed incidence downward (in(ward) incidence)
 $\backslash \text{GTSinIncMono}$ symbol. The operand on the left of the symbol should be considered the vertex to which
 $\backslash \text{GTSinIncMon}$ the arc/the operand on the right of the symbol is incident.
 $\backslash \text{GTSiIM}$ $A. \backslash \text{GTSinIncidenceMonochrome}/ A.$
or $A. \backslash \text{GTSinIncMono}/ A.$
or $A. \backslash \text{GTSinIncMon}/ A.$
or $A. \backslash \text{GTSiIM}/ A.$
will yield $A. \downarrow A.$
 $v \backslash \text{GTSinIncidenceMonochrome}/ e$
or $v \backslash \text{GTSinIncMono}/ e$
or $v \backslash \text{GTSinIncMon}/ e$
or $v \backslash \text{GTSiIM}/ e$
will yield $v \downarrow e$.
 $\$v \backslash \text{GTSinIncidenceMonochrome}/ e\$$
or $\$v \backslash \text{GTSinIncMono}/ e\$$
or $\$v \backslash \text{GTSinIncMon}/ e\$$
or $\$v \backslash \text{GTSiIM}/ e\$$
will yield $v \downarrow e$.

$\backslash \text{GTSinIncidenceMonochrome-}$ This macro will draw a monochrome directed incidence downward (in(ward) incidence)
Relation symbol with relation spacing in math mode.
 $\backslash \text{GTSinIncMonoRel}$ $\$v \backslash \text{GTSinIncidenceMonochromeRelation}/ e\$$
 $\backslash \text{GTSinIncMonRel}$ or $\$v \backslash \text{GTSinIncMonoRel}/ e\$$
 $\backslash \text{GTSiIMR}$ or $\$v \backslash \text{GTSinIncMonRel}/ e\$$
or $\$v \backslash \text{GTSiIMR}/ e\$$
will yield $v \downarrow e$.

`\GTSnegatedInIncidence-` This macro will draw a monochrome negated directed incidence downward (in(ward)
`Monochrome` incidence) symbol.
`\GTSnegInIncMono` $A.\GTSnegatedInIncidenceMonochrome/A.$
`\GTSnegInIncMon` or $A.\GTSnegInIncMono/A.$
`\GTSnIIM` or $A.\GTSnegInIncMon/A.$
or $A.\GTSnIIM/A.$
will yield $A.\not\downarrow A.$
 $v.\GTSnegatedInIncidenceMonochrome/ e$
or $v.\GTSnegInIncMono/ e$
or $v.\GTSnegInIncMon/ e$
or $v.\GTSnIIM/ e$
will yield $v.\not\downarrow e.$
 $\$v.\GTSnegatedInIncidenceMonochrome/ e\$$
or $\$v.\GTSnegInIncMono/ e\$$
or $\$v.\GTSnegInIncMon/ e\$$
or $\$v.\GTSnIIM/ e\$$
will yield $v.\not\downarrow e.$

`\GTSnegatedInIncidence-` This macro will draw a monochrome negated directed incidence downward (in(ward)
`MonochromeRelation` incidence) symbol with relation spacing in math mode.
`\GTSnegInIncMonoRel` $\$v.\GTSnegatedInIncidenceMonochromeRelation/e\$$
`\GTSnegInIncMonRel` or $\$v.\GTSnegInIncMonoRel/e\$$
`\GTSnIIMR` or $\$v.\GTSnegInIncMonRel/e\$$
or $\$v.\GTSnIIMR/e\$$
will yield $v.\not\downarrow e.$

3 Implementation

```

1 \package
2 \RequirePackage{amsmath}
3 \RequirePackage{amssymb}
4 \RequirePackage{graphicx}
5 \RequirePackage{keyval}
6 \RequirePackage{fdsymbol}
7 \RequirePackage{lua-unicode-math}
8 \RequirePackage{xcolor}
9
10 \def\GTS@mainColor{black}
11 \def\GTS@secondColor{gray}
12 \def\GTS@mainColorBackup{black}
13 \def\GTS@secondColorBackup{gray}
14 \def\GTS@drawSlash{}
15 \def\GTS@drawUpArrow{}
16 \def\GTS@drawDownArrow{}
17
\GTS@newcommand This macro will enforce that the other macros are called with a trailing slash, avoiding
problems with spaces after macro call.
Arguments:
{\commandname} The name of the command to create.
{\commandcode} The code of the command to create.
18 \@ifdefinable{\GTS@newcommand}{\def\GTS@newcommand#1#2{%
19   \@ifdefinable{#1}{\def#1/{#2}}
20 }}
\GTSsetMainColor This macro will set the main color used in GraphTheorySymbol. This color has initial value
"black".
Argument:
{\color} The color that must be used by GraphTheorySymbol afterward.
21 \newcommand{\GTSsetMainColor}[1]{%
22 \edef\GTS@mainColorTemp{#1}%
23 \edef\GTS@mainColorBackup{\GTS@mainColor}%
24 \edef\GTS@mainColor{\GTS@mainColorTemp}%
25 }
```

`\GTSsetSecondColor` This macro will set the second color used in `GraphTheorySymbol`. This color has initial value “gray”.

Argument:
`{\color}` The color that must be used by `GraphTheorySymbol` afterward.

```

26 \newcommand{\GTSsetSecondColor}[1]{%
27 \edef\GTS@secondColorTemp{#1}%
28 \edef\GTS@secondColorBackup{\GTS@secondColor}%
29 \edef\GTS@secondColor{\GTS@secondColorTemp}%
30 }

```

`\GTS@a` This macro will draw any adjacency symbol given the correct parameters. Its use is purely technical. See the macros derived from it and `\GTS@b`: `\GTSxadjacency`, `\GTSxadj`, and `\GTSxa`.

Arguments:
`{\mainColor}` If non-empty, this color will be used as main color.
`{\secondColor}` If non-empty, this color will be used as second color.
`{\drawSlash}` Non-empty implies that a negation will be drawn.
`{\drawUpArrow}` Non-empty implies that an up-arrow will be drawn.
`{\drawDownArrow}` Non-empty implies that a down-arrow will be drawn.

```

31 \newcommand{\GTS@a}[5]{%
32 \if#1\empty\else%
33 \GTSsetMainColor{#1}%
34 \fi%
35 \if#2\empty\else%
36 \GTSsetSecondColor{#2}%
37 \fi%
38 \text{\ensuremath{%
39 \raisebox{-0.2ex}{\scalebox{1.5}[1.5]{%
40 %
41 \raisebox{0.7ex}{\scalebox{0.7}[0.7]{%
42 $\mathcolor{\GTS@secondColor}{\circ}$%
43 }}%
44 \hspace{-0.39ex}%
45 \raisebox{1.05ex}{\scalebox{0.1}[0.1]{%
46 $\mathcolor{\GTS@secondColor}{\bullet}$%
47 }}%
48 \hspace{-0.12ex}%
49 \raisebox{0.11ex}{\scalebox{0.1}[0.73]{%
50 $\mathcolor{\GTS@mainColor}{\smallblacksquare}$%
51 }}%
52 \hspace{-0.40ex}%
53 \raisebox{-0.3ex}{\scalebox{0.7}[0.7]{%
54 $\mathcolor{\GTS@secondColor}{\circ}$%
55 }}%
56 \hspace{-0.39ex}%
57 \raisebox{0.05ex}{\scalebox{0.1}[0.1]{%
58 $\mathcolor{\GTS@secondColor}{\bullet}$%
59 }}%
60 \hspace{0.27ex}%
61 \if#4\empty\else%
62 \hspace{-0.65ex}%
63 \raisebox{-0.18ex}{\scalebox{0.5}[0.5]{%
64 \textcolor{\GTS@mainColor}{\textasciicircum}%
65 }}%
66 \fi%
67 \if#5\empty\else%
68 \hspace{-0.65ex}%
69 \raisebox{1.37ex}{\scalebox{0.5}[-0.5]{%
70 \textcolor{\GTS@mainColor}{\textasciicircum}%
71 }}%
72 \fi%

```

```

if GTS@drawSlash empty else
73 \if#3\empty\else%
74 \hspace{-0.65ex}%
75 \raisebox{0.25ex}{\scalebox{0.6}[0.6]{%
76 \textcolor{black}{/}%
77 }}%
78 \fi%
79 %
80 }%
81 }%
82 \if#1\empty\else%
83 \GTSsetMainColor{\GTS@mainColorBackup}%
84 \fi%
85 \if#2\empty\else%
86 \GTSsetSecondColor{\GTS@secondColorBackup}%
87 \fi%
88 }

```

\GTS@b This macro will handle wrapping in mathematical relation spacing if needed. Its use is purely technical. See the macros derived from it and **\GTS@a**: **\GTSxadjacency**, **\GTSxadj**, and **\GTSxa**.

Arguments:

{\mainColor} If non-empty, this color will be used as main color.
{\secondColor} If non-empty, this color will be used as second color.
{\drawSlash} Non-empty implies that a negation will be drawn.
{\drawUpArrow} Non-empty implies that an up-arrow will be drawn.
{\drawDownArrow} Non-empty implies that a down-arrow will be drawn.
{\relation} Non-empty implies that relation spacing will be added.

```

89 \newcommand{\GTS@b}[6]{%
90 \if#61%
91 \mathrel{\GTS@a{#1}{#2}{#3}{#4}{#5}}%
92 \else%
93 \GTS@a{#1}{#2}{#3}{#4}{#5}%
94 \fi%
95 }

```

\GTSxa Versatile macros for adjacency that can be given options.

\GTSxadj Argument:

\GTSxadjacency [*\optionsList*] Sets the following options if not empty:
mainColor=color1 or mainC=color1 or mColor=color1 or mC=color1,
secondColor=color2 or secondC=color2 or sColor=color2 or sC=color2,
monochrome or mono or mon or m (equivalent to mC=black,sC=black),
negated or not or n,
up or u,
down or d,
relation or rel or r.

```

96 \define@key{\GTSxa}{mainColor}{\def\GTS@@mainColor{#1}}
97 \define@key{\GTSxa}{mainC}{\def\GTS@@mainColor{#1}}
98 \define@key{\GTSxa}{mColor}{\def\GTS@@mainColor{#1}}
99 \define@key{\GTSxa}{mC}{\def\GTS@@mainColor{#1}}
100 \define@key{\GTSxa}{secondColor}{\def\GTS@@secondColor{#1}}
101 \define@key{\GTSxa}{secondC}{\def\GTS@@secondColor{#1}}
102 \define@key{\GTSxa}{sColor}{\def\GTS@@secondColor{#1}}
103 \define@key{\GTSxa}{sC}{\def\GTS@@secondColor{#1}}
104 \define@key{\GTSxa}{monochrome}[1]%
105 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
106 \define@key{\GTSxa}{mono}[1]%
107 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
108 \define@key{\GTSxa}{mon}[1]%
109 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
110 \define@key{\GTSxa}{m}[1]%
111 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
112 \define@key{\GTSxa}{negated}[1]{\def\GTS@@drawSlash{1}}
113 \define@key{\GTSxa}{not}[1]{\def\GTS@@drawSlash{1}}

```

```

114 \define@key{GTSxa}{n}[1]{\def\GTS@@drawSlash{1}}
115 \define@key{GTSxa}{up}[1]{\def\GTS@@drawUpArrow{1}}
116 \define@key{GTSxa}{u}[1]{\def\GTS@@drawUpArrow{1}}
117 \define@key{GTSxa}{down}[1]{\def\GTS@@drawDownArrow{1}}
118 \define@key{GTSxa}{d}[1]{\def\GTS@@drawDownArrow{1}}
119 \define@key{GTSxa}{relation}[1]{\def\GTS@@relation{1}}
120 \define@key{GTSxa}{rel}[1]{\def\GTS@@relation{1}}
121 \define@key{GTSxa}{r}[1]{\def\GTS@@relation{1}}
122
123 \newcommand{\GTSxa}[1][]{\%
124 \def\GTS@@mainColor{}}\%
125 \def\GTS@@secondColor{}}\%
126 \def\GTS@@drawSlash{}}\%
127 \def\GTS@@drawUpArrow{}}\%
128 \def\GTS@@drawDownArrow{}}\%
129 \def\GTS@@relation{}}\%
130 \setkeys{GTSxa}{#1}}\%
131 \GTS@b{\GTS@@mainColor}{\GTS@@secondColor}{\GTS@@drawSlash}}\%
132 {\GTS@@drawUpArrow}{\GTS@@drawDownArrow}{\GTS@@relation}}\%
133 }
134
135 \newcommand{\GTSxadj}[1][]{\GTSxa[#1]}
136
137 \newcommand{\GTSxadjacency}[1][]{\GTSxa[#1]}

```

`\GTSadjacency` This macro will draw an adjacency symbol.

```

\GTSadj 138 \GTS@newcommand{\GTSadjacency}{\GTS@a{}}{\GTS@{}}{\GTS@{}}
\GTSa 139 \GTS@newcommand{\GTSadj}{\GTS@a{}}{\GTS@{}}{\GTS@{}}
140 \GTS@newcommand{\GTSa}{\GTS@a{}}{\GTS@{}}{\GTS@{}}

```

`\GTSadjacencyRelation` This macro will draw an adjacency symbol with relation spacing in math mode.

```

\GTSadjRel 141 \GTS@newcommand{\GTSadjacencyRelation}{\mathrel{\GTSa/}}
\GTSaR 142 \GTS@newcommand{\GTSadjRel}{\mathrel{\GTSa/}}
143 \GTS@newcommand{\GTSaR}{\mathrel{\GTSa/}}

```

`\GTSunadjacency` This macro will draw an unadjacency symbol.

```

\GTSunadj 144 \GTS@newcommand{\GTSunadjacency}{\GTS@a{}}{\GTS@{}}{\GTS@{}}
\GTSu 145 \GTS@newcommand{\GTSunadj}{\GTS@a{}}{\GTS@{}}{\GTS@{}}
146 \GTS@newcommand{\GTSu}{\GTS@a{}}{\GTS@{}}{\GTS@{}}

```

`\GTSunadjacencyRelation` This macro will draw an unadjacency symbol with relation spacing in math mode.

```

\GTSunadjRel 147 \GTS@newcommand{\GTSunadjacencyRelation}{\mathrel{\GTSu/}}
\GTSuR 148 \GTS@newcommand{\GTSunadjRel}{\mathrel{\GTSu/}}
149 \GTS@newcommand{\GTSuR}{\mathrel{\GTSu/}}

```

`\GTSdirectedAdjacencyUp` This macro will draw a directed adjacency upward symbol. The operand on the left of the symbol should be considered the source of the arc; the operand on the right of the symbol should be considered the target of the arc.

```

\GTSdAU 150 \GTS@newcommand{\GTSdirectedAdjacencyUp}{\GTS@a{}}{\GTS@{}}{\GTS@{}}
151 \GTS@newcommand{\GTSdirAdjUp}{\GTS@a{}}{\GTS@{}}{\GTS@{}}
152 \GTS@newcommand{\GTSdAU}{\GTS@a{}}{\GTS@{}}{\GTS@{}}

```

`\GTSdirectedAdjacencyUp-Relation` This macro will draw a directed adjacency upward symbol with relation spacing in math mode.

```

\GTSdirAdjUpRel 153 \GTS@newcommand{\GTSdirectedAdjacencyUpRelation}{\mathrel{\GTSdAU/}}
\GTSdAUR 154 \GTS@newcommand{\GTSdirAdjUpRel}{\mathrel{\GTSdAU/}}
155 \GTS@newcommand{\GTSdAUR}{\mathrel{\GTSdAU/}}

```

`\GTSnegatedDirected-` This macro will draw a negated directed adjacency upward symbol.

```

AdjacencyUp 156 \GTS@newcommand{\GTSnegatedDirectedAdjacencyUp}{\GTS@a{}}{\GTS@{}}{\GTS@{}}
\GTSnegDirAdjUp 157 \GTS@newcommand{\GTSnegDirAdjUp}{\GTS@a{}}{\GTS@{}}{\GTS@{}}
\GTSnDAU 158 \GTS@newcommand{\GTSnDAU}{\GTS@a{}}{\GTS@{}}{\GTS@{}}

```

`\GTSnegatedDirectedAdjacencyUpRelation` This macro will draw a negated directed adjacency upward symbol with relation spacing in math mode.

```

\GTSnegDirAdjUpRel 159 \GTS@newcommand{\GTSnegatedDirectedAdjacencyUpRelation}{%
\GTSnDAUR 160 \mathrel{\GTSnDAU/}%
161 }
162 \GTS@newcommand{\GTSnegDirAdjUpRel}{\mathrel{\GTSnDAU/}}
163 \GTS@newcommand{\GTSnDAUR}{\mathrel{\GTSnDAU/}}

```

`\GTSdirectedAdjacencyDown` This macro will draw a directed adjacency downward symbol. The operand on the left of the symbol should be considered the target of the arc; the operand on the right of the symbol should be considered the source of the arc.

```

\GTSdirAdjDown 164 \GTS@newcommand{\GTSdirectedAdjacencyDown}{\GTS@a{}{}{}{1}}
\GTSdAD 165 \GTS@newcommand{\GTSdirAdjDown}{\GTS@a{}{}{}{1}}
166 \GTS@newcommand{\GTSdAD}{\GTS@a{}{}{}{1}}

```

`\GTSdirectedAdjacencyDownRelation` This macro will draw a directed adjacency downward symbol with relation spacing in math mode.

```

\GTSdirAdjDownRel 167 \GTS@newcommand{\GTSdirectedAdjacencyDownRelation}{\mathrel{\GTSdAD/}}
\GTSdADR 168 \GTS@newcommand{\GTSdirAdjDownRel}{\mathrel{\GTSdAD/}}
169 \GTS@newcommand{\GTSdADR}{\mathrel{\GTSdAD/}}

```

`\GTSnegatedDirectedAdjacencyDown` This macro will draw a negated directed adjacency downward symbol.

```

AdjacencyDown 170 \GTS@newcommand{\GTSnegatedDirectedAdjacencyDown}{\GTS@a{}{}{1}{1}}
\GTSnegDirAdjDown 171 \GTS@newcommand{\GTSnegDirAdjDown}{\GTS@a{}{}{1}{1}}
\GTSnDAD 172 \GTS@newcommand{\GTSnDAD}{\GTS@a{}{}{1}{1}}

```

`\GTSnegatedDirectedAdjacencyDownRelation` This macro will draw a negated directed adjacency downward symbol with relation spacing in math mode.

```

\GTSnegDirAdjDownRel 173 \GTS@newcommand{\GTSnegatedDirectedAdjacencyDownRelation}{%
\GTSnDADR 174 \mathrel{\GTSnDAD/}%
175 }
176 \GTS@newcommand{\GTSnegDirAdjDownRel}{\mathrel{\GTSnDAD/}}
177 \GTS@newcommand{\GTSnDADR}{\mathrel{\GTSnDAD/}}

```

`\GTS@i` This macro will draw any incidence symbol given the correct parameters. Its use is purely technical. See the macros derived from it and `\GTS@j`: `\GTSxincidence`, `\GTSxinc`, and `\GTSxi`. The operand on the left of the symbol should be considered the vertex to which the edge/the operand on the right of the symbol is incident.

Arguments:

- `{\langle mainColor \rangle}` If non-empty, this color will be used as main color.
- `{\langle secondColor \rangle}` If non-empty, this color will be used as second color.
- `{\langle drawSlash \rangle}` Non-empty implies that a negation will be drawn.
- `{\langle drawUpArrow \rangle}` Non-empty implies that an up-arrow will be drawn.
- `{\langle drawDownArrow \rangle}` Non-empty implies that a down-arrow will be drawn.

```

178 \newcommand{\GTS@i}[5]{%
179 \if#1\empty\else%
180 \GTSsetMainColor{#1}%
181 \fi%
182 \if#2\empty\else%
183 \GTSsetSecondColor{#2}%
184 \fi%
185 \text{\ensuremath{%
186 \raisebox{0ex}{\scalebox{1.8}[1.8]{%
187 %
188 \raisebox{-0.3ex}{\scalebox{0.7}[0.7]{%
189 $\mathcolor{\GTS@secondColor}{\circ}$%
190 }}%
191 \hspace{-0.39ex}%
192 \raisebox{0.05ex}{\scalebox{0.1}[0.1]{%
193 $\mathcolor{\GTS@secondColor}{\bullet}$%
194 }}%
195 \hspace{-0.12ex}%
196 \raisebox{0.11ex}{\scalebox{0.1}[0.73]{%
197 $\mathcolor{\GTS@secondColor}{\smallblacksquare}$%

```

```

198 }}%
199 \hspace{-0.18ex}%
200 \raisebox{0.15ex}{\scalebox{0.2}[0.2]{%
201 $\mathcolor{\GTS@mainColor}{\smallblacksquare}$%
202 }}%
203 \hspace{0.2ex}%
if GTS@drawUpArrow empty else
204 \if#4\empty\else%
205 \hspace{-0.65ex}%
206 \raisebox{-0.18ex}{\scalebox{0.5}[0.5]{%
207 \textcolor{\GTS@secondColor}{\textasciicircum}%
208 }}%
209 \fi%
if GTS@drawDownArrow empty else
210 \if#5\empty\else%
211 \hspace{-0.65ex}%
212 \raisebox{1.37ex}{\scalebox{0.5}[-0.5]{%
213 \textcolor{\GTS@secondColor}{\textasciicircum}%
214 }}%
215 \fi%
if GTS@drawSlash empty else
216 \if#3\empty\else%
217 \hspace{-0.65ex}%
218 \raisebox{0.1ex}{\scalebox{0.5}[0.5]{%
219 \textcolor{black}{/}%
220 }}%
221 \fi%
222 %
223 }}%
224 }}%
225 \if#1\empty\else%
226 \GTSsetMainColor{\GTS@mainColorBackup}%
227 \fi%
228 \if#2\empty\else%
229 \GTSsetSecondColor{\GTS@secondColorBackup}%
230 \fi%
231 }

```

\GTS@j This macro will handle wrapping in mathematical relation spacing if needed. Its use is purely technical. See the macros derived from it and **\GTS@i**: **\GTSxincidence**, **\GTSxinc**, and **\GTSxi**.

Arguments:

- {\langle mainColor \rangle}** If non-empty, this color will be used as main color.
- {\langle secondColor \rangle}** If non-empty, this color will be used as second color.
- {\langle drawSlash \rangle}** Non-empty implies that a negation will be drawn.
- {\langle drawUpArrow \rangle}** Non-empty implies that an up-arrow will be drawn.
- {\langle drawDownArrow \rangle}** Non-empty implies that a down-arrow will be drawn.
- {\langle relation \rangle}** Non-empty implies that relation spacing will be added.

```

232 \newcommand{\GTS@j}[6]{%
233 \if#61%
234 \mathrel{\GTS@i{#1}{#2}{#3}{#4}{#5}}%
235 \else%
236 \GTS@i{#1}{#2}{#3}{#4}{#5}%
237 \fi%
238 }

```

\GTSxi Versatile macros for incidence that can be given options.

\GTSxinc Argument:

\GTSxincidence [*optionsList*] Sets the following options if not empty:
 mainColor=color1 or mainC=color1 or mColor=color1 or mC=color1,
 secondColor=color2 or secondC=color2 or sColor=color2 or sC=color2,
 monochrome or mono or mon or m (equivalent to mC=black,sC=black),
 negated or not or n,

in or i,
out or o,
relation or rel or r.

```

239 \define@key{GTSxi}{mainColor}{\def\GTS@@mainColor{#1}}
240 \define@key{GTSxi}{mainC}{\def\GTS@@mainColor{#1}}
241 \define@key{GTSxi}{mColor}{\def\GTS@@mainColor{#1}}
242 \define@key{GTSxi}{mC}{\def\GTS@@mainColor{#1}}
243 \define@key{GTSxi}{secondColor}{\def\GTS@@secondColor{#1}}
244 \define@key{GTSxi}{secondC}{\def\GTS@@secondColor{#1}}
245 \define@key{GTSxi}{sColor}{\def\GTS@@secondColor{#1}}
246 \define@key{GTSxi}{sC}{\def\GTS@@secondColor{#1}}
247 \define@key{GTSxi}{monochrome}[1]%
248 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
249 \define@key{GTSxi}{mono}[1]%
250 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
251 \define@key{GTSxi}{mon}[1]%
252 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
253 \define@key{GTSxi}{m}[1]%
254 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
255 \define@key{GTSxi}{negated}[1]{\def\GTS@@drawSlash{1}}
256 \define@key{GTSxi}{not}[1]{\def\GTS@@drawSlash{1}}
257 \define@key{GTSxi}{n}[1]{\def\GTS@@drawSlash{1}}
258 \define@key{GTSxi}{out}[1]{\def\GTS@@drawUpArrow{1}}
259 \define@key{GTSxi}{o}[1]{\def\GTS@@drawUpArrow{1}}
260 \define@key{GTSxi}{in}[1]{\def\GTS@@drawDownArrow{1}}
261 \define@key{GTSxi}{i}[1]{\def\GTS@@drawDownArrow{1}}
262 \define@key{GTSxi}{relation}[1]{\def\GTS@@relation{1}}
263 \define@key{GTSxi}{rel}[1]{\def\GTS@@relation{1}}
264 \define@key{GTSxi}{r}[1]{\def\GTS@@relation{1}}
265
266 \newcommand{\GTSxi}[1][]{\%
267 \def\GTS@@mainColor{}%
268 \def\GTS@@secondColor{}%
269 \def\GTS@@drawSlash{}%
270 \def\GTS@@drawUpArrow{}%
271 \def\GTS@@drawDownArrow{}%
272 \def\GTS@@relation{}%
273 \setkeys{GTSxi}{#1}%
274 \GTS@j{\GTS@@mainColor}{\GTS@@secondColor}{\GTS@@drawSlash}%
275 {\GTS@@drawUpArrow}{\GTS@@drawDownArrow}{\GTS@@relation}%
276 }
277
278 \newcommand{\GTSxinc}[1][]{\GTSxi[#1]}
279
280 \newcommand{\GTSxincidence}[1][]{\GTSxi[#1]}

```

\GTSincidence This macro will draw an incidence symbol. The operand on the left of the symbol should be considered the vertex to which the edge/the operand on the right of the symbol is incident.

```

\GTSinc 281 \GTS@newcommand{\GTSincidence}{\GTS@i{}{}{}{}}
\GTSi    282 \GTS@newcommand{\GTSinc}{\GTS@i{}{}{}{}}
          283 \GTS@newcommand{\GTSi}{\GTS@i{}{}{}{}}

```

\GTSincidenceRelation This macro will draw an incidence symbol with relation spacing in math mode.

```

\GTSincRel 284 \GTS@newcommand{\GTSincidenceRelation}{\mathrel{\GTSi/}}
\GTSiR      285 \GTS@newcommand{\GTSincRel}{\mathrel{\GTSi/}}
          286 \GTS@newcommand{\GTSiR}{\mathrel{\GTSi/}}

```

\GTSnegatedIncidence This macro will draw a negated incidence symbol.

```

\GTSnegInc 287 \GTS@newcommand{\GTSnegatedIncidence}{\GTS@i{}{}{1}{}{}}
\GTSnI      288 \GTS@newcommand{\GTSnegInc}{\GTS@i{}{}{1}{}{}}
          289 \GTS@newcommand{\GTSnI}{\GTS@i{}{}{1}{}{}}

```

\GTSnegatedIncidenceRelation This macro will draw a negated incidence symbol with relation spacing in math mode.

```

Relation 290 \GTS@newcommand{\GTSnegatedIncidenceRelation}{\mathrel{\GTSnI/}}
\GTSnegIncRel 291 \GTS@newcommand{\GTSnegIncRel}{\mathrel{\GTSnI/}}
\GTSnIR    292 \GTS@newcommand{\GTSnIR}{\mathrel{\GTSnI/}}

```

`\GTSoutIncidence` This macro will draw a directed incidence upward (out(ward) incidence) symbol. The
`\GTSoutInc` operand on the left of the symbol should be considered the vertex to which the arc/the
`\GTSOI` operand on the right of the symbol is incident.
293 `\GTS@newcommand{\GTSoutIncidence}{\GTS@i{}{}{}{1}{}}`
294 `\GTS@newcommand{\GTSoutInc}{\GTS@i{}{}{}{1}{}}`
295 `\GTS@newcommand{\GTSOI}{\GTS@i{}{}{}{1}{}}`

`\GTSoutIncidenceRelation` This macro will draw a directed incidence upward (out(ward) incidence) symbol with relation
`\GTSoutIncRel` spacing in math mode.
`\GTSOIR` 296 `\GTS@newcommand{\GTSoutIncidenceRelation}{\mathrel{\GTSOI/}}`
297 `\GTS@newcommand{\GTSoutIncRel}{\mathrel{\GTSOI/}}`
298 `\GTS@newcommand{\GTSOIR}{\mathrel{\GTSOI/}}`

`\GTSnegatedOutIncidence` This macro will draw a negated directed incidence upward (out(ward) incidence) symbol.
`\GTSnegOutInc` 299 `\GTS@newcommand{\GTSnegatedOutIncidence}{\GTS@i{}{}{1}{1}{}}`
`\GTSnOI` 300 `\GTS@newcommand{\GTSnegOutInc}{\GTS@i{}{}{1}{1}{}}`
301 `\GTS@newcommand{\GTSnOI}{\GTS@i{}{}{1}{1}{}}`

`\GTSnegatedOutIncidence-` This macro will draw a negated directed incidence upward (out(ward) incidence) symbol
`Relation` with relation spacing in math mode.
`\GTSnegOutIncRel` 302 `\GTS@newcommand{\GTSnegatedOutIncidenceRelation}{\mathrel{\GTSnOI/}}`
`\GTSnOIR` 303 `\GTS@newcommand{\GTSnegOutIncRel}{\mathrel{\GTSnOI/}}`
304 `\GTS@newcommand{\GTSnOIR}{\mathrel{\GTSnOI/}}`

`\GTSinIncidence` This macro will draw a directed incidence downward (in(ward) incidence) symbol. The
`\GTSinInc` operand on the left of the symbol should be considered the vertex to which the arc/the
`\GTSiI` operand on the right of the symbol is incident.
305 `\GTS@newcommand{\GTSinIncidence}{\GTS@i{}{}{}{1}{}}`
306 `\GTS@newcommand{\GTSinInc}{\GTS@i{}{}{}{1}{}}`
307 `\GTS@newcommand{\GTSiI}{\GTS@i{}{}{}{1}{}}`

`\GTSinIncidenceRelation` This macro will draw a directed incidence downward (in(ward) incidence) symbol with re-
`\GTSinIncRel` lation spacing in math mode.
`\GTSiIR` 308 `\GTS@newcommand{\GTSinIncidenceRelation}{\mathrel{\GTSiI/}}`
309 `\GTS@newcommand{\GTSinIncRel}{\mathrel{\GTSiI/}}`
310 `\GTS@newcommand{\GTSiIR}{\mathrel{\GTSiI/}}`

`\GTSnegatedInIncidence` This macro will draw a negated directed incidence downward (in(ward) incidence) symbol.
`\GTSnegInInc` 311 `\GTS@newcommand{\GTSnegatedInIncidence}{\GTS@i{}{}{1}{1}{}}`
`\GTSnII` 312 `\GTS@newcommand{\GTSnegInInc}{\GTS@i{}{}{1}{1}{}}`
313 `\GTS@newcommand{\GTSnII}{\GTS@i{}{}{1}{1}{}}`

`\GTSnegatedInIncidence-` This macro will draw a negated directed incidence downward (in(ward) incidence) symbol
`Relation` with relation spacing in math mode.
`\GTSnegInIncRel` 314 `\GTS@newcommand{\GTSnegatedInIncidenceRelation}{\mathrel{\GTSnII/}}`
`\GTSnIIR` 315 `\GTS@newcommand{\GTSnegInIncRel}{\mathrel{\GTSnII/}}`
316 `\GTS@newcommand{\GTSnIIR}{\mathrel{\GTSnII/}}`

`\GTSadjacencyMonochrome` This macro will draw a monochrome adjacency symbol.
`\GTSadjMono` 317 `\GTS@newcommand{\GTSadjacencyMonochrome}{\GTS@a{black}{black}{}}{}}{}}`
`\GTSadjMon` 318 `\GTS@newcommand{\GTSadjMono}{\GTS@a{black}{black}{}}{}}{}}`
`\GTSaM` 319 `\GTS@newcommand{\GTSadjMon}{\GTS@a{black}{black}{}}{}}{}}`
320 `\GTS@newcommand{\GTSaM}{\GTS@a{black}{black}{}}{}}{}}`

`\GTSadjacencyMonochrome-` This macro will draw a monochrome adjacency symbol with relation spacing in math mode.
`Relation` 321 `\GTS@newcommand{\GTSadjacencyMonochromeRelation}{\mathrel{\GTSaM/}}`
`\GTSadjMonoRel` 322 `\GTS@newcommand{\GTSadjMonoRel}{\mathrel{\GTSaM/}}`
`\GTSadjMonRel` 323 `\GTS@newcommand{\GTSadjMonRel}{\mathrel{\GTSaM/}}`
`\GTSaMR` 324 `\GTS@newcommand{\GTSaMR}{\mathrel{\GTSaM/}}`

`\GTSunadjacencyMonochrome` This macro will draw a monochrome unadjacency symbol.
`\GTSunadjMono` 325 `\GTS@newcommand{\GTSunadjacencyMonochrome}{\GTS@a{black}{black}{1}{}}{}}{}}`
`\GTSunadjMon` 326 `\GTS@newcommand{\GTSunadjMono}{\GTS@a{black}{black}{1}{}}{}}{}}`
`\GTSuM` 327 `\GTS@newcommand{\GTSunadjMon}{\GTS@a{black}{black}{1}{}}{}}{}}`
328 `\GTS@newcommand{\GTSuM}{\GTS@a{black}{black}{1}{}}{}}{}}`

`\GTSunadjacencyMonochrome-` This macro will draw a monochrome unadjacency symbol with relation spacing in math mode.
`Relation`

`\GTSunadjMonoRel` 329 `\GTS@newcommand{\GTSunadjacencyMonochromeRelation}{\mathrel{\GTSuM/}}`
`\GTSunadjMonRel` 330 `\GTS@newcommand{\GTSunadjMonoRel}{\mathrel{\GTSuM/}}`
`\GTSuMR` 331 `\GTS@newcommand{\GTSunadjMonRel}{\mathrel{\GTSuM/}}`
332 `\GTS@newcommand{\GTSuMR}{\mathrel{\GTSuM/}}`

`\GTSdirectedAdjacencyUp-` This macro will draw a monochrome directed adjacency upward symbol. The operand on the left of the symbol should be considered the source of the arc; the operand on the right
`Monochrome` of the symbol should be considered the target of the arc.
`\GTSdirAdjUpMono`
`\GTSdirAdjUpMon` 333 `\GTS@newcommand{\GTSdirectedAdjacencyUpMonochrome}{%`
`\GTSdAUM` 334 `\GTS@a{black}{black}{1}{1}{}`
335 `}`
336 `\GTS@newcommand{\GTSdirAdjUpMono}{\GTS@a{black}{black}{1}{1}{}}`
337 `\GTS@newcommand{\GTSdirAdjUpMon}{\GTS@a{black}{black}{1}{1}{}}`
338 `\GTS@newcommand{\GTSdAUM}{\GTS@a{black}{black}{1}{1}{}}`

`\GTSdirectedAdjacencyUp-` This macro will draw a monochrome directed adjacency upward symbol with relation spacing
`MonochromeRelation` in math mode.
`\GTSdirAdjUpMonoRel` 339 `\GTS@newcommand{\GTSdirectedAdjacencyUpMonochromeRelation}{%`
`\GTSdirAdjUpMonRel` 340 `\mathrel{\GTSdAUM/}}`
`\GTSdAUMR` 341 `}`
342 `\GTS@newcommand{\GTSdirAdjUpMonoRel}{\mathrel{\GTSdAUM/}}`
343 `\GTS@newcommand{\GTSdirAdjUpMonRel}{\mathrel{\GTSdAUM/}}`
344 `\GTS@newcommand{\GTSdAUMR}{\mathrel{\GTSdAUM/}}`

`\GTSnegatedDirected-` This macro will draw a monochrome negated directed adjacency upward symbol.
`AdjacencyUpMonochrome`
`\GTSnegDirAdjUpMono` 345 `\GTS@newcommand{\GTSnegatedDirectedAdjacencyUpMonochrome}{%`
`\GTSnegDirAdjUpMon` 346 `\GTS@a{black}{black}{1}{1}{}`
347 `}`
`\GTSnDAUM` 348 `\GTS@newcommand{\GTSnegDirAdjUpMono}{\GTS@a{black}{black}{1}{1}{}}`
349 `\GTS@newcommand{\GTSnegDirAdjUpMon}{\GTS@a{black}{black}{1}{1}{}}`
350 `\GTS@newcommand{\GTSnDAUM}{\GTS@a{black}{black}{1}{1}{}}`

`\GTSnegatedDirected-` This macro will draw a monochrome negated directed adjacency upward symbol with relation
`AdjacencyUpMonochrome-` spacing in math mode.
`Relation`
`\GTSnegDirAdjUpMonRel` 351 `\GTS@newcommand{\GTSnegatedDirectedAdjacencyUpMonochromeRelation}{%`
`\GTSnegDirAdjUpMonoRel` 352 `\mathrel{\GTSnDAUM/}}`
353 `}`
`\GTSnDAUMR` 354 `\GTS@newcommand{\GTSnegDirAdjUpMonoRel}{\mathrel{\GTSnDAUM/}}`
355 `\GTS@newcommand{\GTSnegDirAdjUpMonRel}{\mathrel{\GTSnDAUM/}}`
356 `\GTS@newcommand{\GTSnDAUMR}{\mathrel{\GTSnDAUM/}}`

`\GTSdirectedAdjacencyDown-` This macro will draw a monochrome directed adjacency downward symbol. The operand on
`Monochrome` the left of the symbol should be considered the target of the arc; the operand on the right
`\GTSdirAdjDownMono` of the symbol should be considered the source of the arc.
`\GTSdirAdjDownMon`
`\GTSdADM` 357 `\GTS@newcommand{\GTSdirectedAdjacencyDownMonochrome}{%`
358 `\GTS@a{black}{black}{1}{1}{}`
359 `}`
360 `\GTS@newcommand{\GTSdirAdjDownMono}{\GTS@a{black}{black}{1}{1}{}}`
361 `\GTS@newcommand{\GTSdirAdjDownMon}{\GTS@a{black}{black}{1}{1}{}}`
362 `\GTS@newcommand{\GTSdADM}{\GTS@a{black}{black}{1}{1}{}}`

`\GTSdirectedAdjacencyDown-` This macro will draw a monochrome directed adjacency downward symbol with relation
`MonochromeRelation` spacing in math mode.
`\GTSdirAdjDownMonoRel` 363 `\GTS@newcommand{\GTSdirectedAdjacencyDownMonochromeRelation}{%`
`\GTSdirAdjDownMonRel` 364 `\mathrel{\GTSdADM/}}`
`\GTSdADMR` 365 `}`
366 `\GTS@newcommand{\GTSdirAdjDownMonoRel}{\mathrel{\GTSdADM/}}`
367 `\GTS@newcommand{\GTSdirAdjDownMonRel}{\mathrel{\GTSdADM/}}`
368 `\GTS@newcommand{\GTSdADMR}{\mathrel{\GTSdADM/}}`

`\GTSnegatedDirected-` This macro will draw a monochrome negated directed adjacency downward symbol.
`AdjacencyDownMonochrome`
`\GTSnegDirAdjDownMono` 369 `\GTS@newcommand{\GTSnegatedDirectedAdjacencyDownMonochrome}{%`
`\GTSnegDirAdjDownMon`
`\GTSnDADM`

```

370 \GTS@a{black}{black}{1}{1}%
371 }
372 \GTS@newcommand{\GTSnegDirAdjDownMono}{\GTS@a{black}{black}{1}{1}}
373 \GTS@newcommand{\GTSnegDirAdjDownMon}{\GTS@a{black}{black}{1}{1}}
374 \GTS@newcommand{\GTSnDADM}{\GTS@a{black}{black}{1}{1}}

\GTSnegatedDirected- This macro will draw a monochrome negated directed adjacency downward symbol with
AdjacencyDownMonochrome- relation spacing in math mode.
    Relation 375 \GTS@newcommand{\GTSnegatedDirectedAdjacencyDownMonochromeRelation}{%
\GTSnegDirAdjDownMonoRel 376 \mathrel{\GTSnDADM}/}%
\GTSnegDirAdjDownMonRel 377 }
    \GTSnDADMR 378 \GTS@newcommand{\GTSnegDirAdjDownMonoRel}{\mathrel{\GTSnDADM}}
379 \GTS@newcommand{\GTSnegDirAdjDownMonRel}{\mathrel{\GTSnDADM}}
380 \GTS@newcommand{\GTSnDADMR}{\mathrel{\GTSnDADM}}

\GTSincidenceMonochrome This macro will draw a monochrome incidence symbol. The operand on the left of the
\GTSincMono symbol should be considered the vertex to which the edge/the operand on the right of the
\GTSincMon symbol is incident.
    \GTSiM 381 \GTS@newcommand{\GTSincidenceMonochrome}{\GTS@i{black}{black}{}}{}{}
382 \GTS@newcommand{\GTSincMono}{\GTS@i{black}{black}{}}{}{}
383 \GTS@newcommand{\GTSincMon}{\GTS@i{black}{black}{}}{}{}
384 \GTS@newcommand{\GTSiM}{\GTS@i{black}{black}{}}{}{}

\GTSincidenceMonochrome- This macro will draw a monochrome incidence symbol with relation spacing in math mode.
    Relation 385 \GTS@newcommand{\GTSincidenceMonochromeRelation}{\mathrel{\GTSiM}/}
\GTSincMonoRel 386 \GTS@newcommand{\GTSincMonoRel}{\mathrel{\GTSiM}}
\GTSincMonRel 387 \GTS@newcommand{\GTSincMonRel}{\mathrel{\GTSiM}}
\GTSiMR 388 \GTS@newcommand{\GTSiMR}{\mathrel{\GTSiM}}

\GTSnegatedIncidence- This macro will draw a monochrome negated incidence symbol.
    Monochrome 389 \GTS@newcommand{\GTSnegatedIncidenceMonochrome}{%
\GTSnegIncMono 390 \GTS@i{black}{black}{1}{1}}%
\GTSnegIncMon 391 }
    \GTSnIM 392 \GTS@newcommand{\GTSnegIncMono}{\GTS@i{black}{black}{1}{1}}
393 \GTS@newcommand{\GTSnegIncMon}{\GTS@i{black}{black}{1}{1}}
394 \GTS@newcommand{\GTSnIM}{\GTS@i{black}{black}{1}{1}}

\GTSnegatedIncidence- This macro will draw a monochrome negated incidence symbol with relation spacing in math
MonochromeRelation mode.
    \GTSnegIncMonoRel 395 \GTS@newcommand{\GTSnegatedIncidenceMonochromeRelation}{\mathrel{\GTSnIM}/}
\GTSnegIncMonRel 396 \GTS@newcommand{\GTSnegIncMonRel}{\mathrel{\GTSnIM}}
\GTSnIMR 397 \GTS@newcommand{\GTSnegIncMonRel}{\mathrel{\GTSnIM}}
398 \GTS@newcommand{\GTSnIMR}{\mathrel{\GTSnIM}}

\GTSoutIncidenceMonochrome This macro will draw a monochrome directed incidence upward (out(ward) incidence) sym-
\GTSoutIncMono bol. The operand on the left of the symbol should be considered the vertex to which the
\GTSoutIncMon arc/the operand on the right of the symbol is incident.
    \GTSoIM 399 \GTS@newcommand{\GTSoutIncidenceMonochrome}{\GTS@i{black}{black}{}}{1}{}
400 \GTS@newcommand{\GTSoutIncMono}{\GTS@i{black}{black}{}}{1}{}
401 \GTS@newcommand{\GTSoutIncMon}{\GTS@i{black}{black}{}}{1}{}
402 \GTS@newcommand{\GTSoIM}{\GTS@i{black}{black}{}}{1}{}

\GTSoutIncidenceMonochrome- This macro will draw a monochrome directed incidence upward (out(ward) incidence) symbol
    Relation with relation spacing in math mode.
\GTSoutIncMonoRel 403 \GTS@newcommand{\GTSoutIncidenceMonochromeRelation}{\mathrel{\GTSoIM}/}
\GTSoutIncMonRel 404 \GTS@newcommand{\GTSoutIncMonoRel}{\mathrel{\GTSoIM}}
\GTSoIMR 405 \GTS@newcommand{\GTSoutIncMonRel}{\mathrel{\GTSoIM}}
406 \GTS@newcommand{\GTSoIMR}{\mathrel{\GTSoIM}}

\GTSnegatedOutIncidence- This macro will draw a monochrome negated directed incidence upward (out(ward) inci-
    Monochrome dence) symbol.
\GTSnegOutIncMono 407 \GTS@newcommand{\GTSnegatedOutIncidenceMonochrome}{%
\GTSnegOutIncMon 408 \GTS@i{black}{black}{1}{1}}%
\GTSnOIM 409 }

```

```

410 \GTS@newcommand{\GTSnegOutIncMono}{\GTS@i{black}{black}{1}{1}{}}
411 \GTS@newcommand{\GTSnegOutIncMon}{\GTS@i{black}{black}{1}{1}{}}
412 \GTS@newcommand{\GTSnOIM}{\GTS@i{black}{black}{1}{1}{}}

```

`\GTSnegatedOutIncidence-` This macro will draw a monochrome negated directed incidence upward (out(ward) inci-
`MonochromeRelation` dence) symbol with relation spacing in math mode.

```

\GTSnegOutIncMonoRel 413 \GTS@newcommand{\GTSnegatedOutIncidenceMonochromeRelation}{%
\GTSnegOutIncMonRel 414 \mathrel{\GTSnOIM}/}%
\GTSnOIMR 415 }
416 \GTS@newcommand{\GTSnegOutIncMonoRel}{\mathrel{\GTSnOIM/}}
417 \GTS@newcommand{\GTSnegOutIncMonRel}{\mathrel{\GTSnOIM/}}
418 \GTS@newcommand{\GTSnOIMR}{\mathrel{\GTSnOIM/}}

```

`\GTSinIncidenceMonochrome` This macro will draw a monochrome directed incidence downward (in(ward) incidence) sym-
`\GTSinIncMono` bol. The operand on the left of the symbol should be considered the vertex to which the
`\GTSinIncMon` arc/the operand on the right of the symbol is incident.

```

\GTSiIM 419 \GTS@newcommand{\GTSinIncidenceMonochrome}{\GTS@i{black}{black}{}}{\{1}}
420 \GTS@newcommand{\GTSinIncMono}{\GTS@i{black}{black}{}}{\{1}}
421 \GTS@newcommand{\GTSinIncMon}{\GTS@i{black}{black}{}}{\{1}}
422 \GTS@newcommand{\GTSiIM}{\GTS@i{black}{black}{}}{\{1}}

```

`\GTSinIncidenceMonochrome-` This macro will draw a monochrome directed incidence downward (in(ward) incidence) sym-
`Relation` bol with relation spacing in math mode.

```

\GTSinIncMonoRel 423 \GTS@newcommand{\GTSinIncidenceMonochromeRelation}{\mathrel{\GTSiIM/}}
\GTSinIncMonRel 424 \GTS@newcommand{\GTSinIncMonoRel}{\mathrel{\GTSiIM/}}
\GTSiIMR 425 \GTS@newcommand{\GTSinIncMonRel}{\mathrel{\GTSiIM/}}
426 \GTS@newcommand{\GTSiIMR}{\mathrel{\GTSiIM/}}

```

`\GTSnegatedInIncidence-` This macro will draw a monochrome negated directed incidence downward (in(ward) inci-
`Monochrome` dence) symbol.

```

\GTSnegInIncMono 427 \GTS@newcommand{\GTSnegatedInIncidenceMonochrome}{%
\GTSnegInIncMon 428 \GTS@i{black}{black}{1}{1}{}}
\GTSnIIM 429 }
430 \GTS@newcommand{\GTSnegInIncMono}{\GTS@i{black}{black}{1}{1}{}}
431 \GTS@newcommand{\GTSnegInIncMon}{\GTS@i{black}{black}{1}{1}{}}
432 \GTS@newcommand{\GTSnIIM}{\GTS@i{black}{black}{1}{1}{}}

```

`\GTSnegatedInIncidence-` This macro will draw a monochrome negated directed incidence downward (in(ward) inci-
`MonochromeRelation` dence) symbol with relation spacing in math mode.

```

\GTSnegInIncMonoRel 433 \GTS@newcommand{\GTSnegatedInIncidenceMonochromeRelation}{%
\GTSnegInIncMonRel 434 \mathrel{\GTSnIIM}/}%
\GTSnIIMR 435 }
436 \GTS@newcommand{\GTSnegInIncMonoRel}{\mathrel{\GTSnIIM/}}
437 \GTS@newcommand{\GTSnegInIncMonRel}{\mathrel{\GTSnIIM/}}
438 \GTS@newcommand{\GTSnIIMR}{\mathrel{\GTSnIIM/}}

```

```

439 \endinput
440 </package>

```

4 Acknowledgments

Thank You God! Thank You Father! Thank You Jesus! Thank You Holy-Spirit!

5 Support

This package is gratis and free. But if you can star it on GitHub, it is a nice encouragement.

6 Change History

v0.1.0 – 2026-08-01

v1.0.0 – 2026-08-26

General: Initial version 1 General: First public release 1

v1.1.0 – 2026-08-29	same set of symbols	1
General: Added a memo	1	
v1.1.1 – 2026-08-30	v1.2.1 – 2026-09-08	
General: Small corrections and improvements	General: smaller tests output	1
1	v1.3.0 – 2026-09-08	
v1.2.0 – 2026-09-06	General: new macros for monochrome symbols	1
General: CTAN URL, new macros for		

Index

D

`\define@key` 96, 97, 98, 99, 100, 101, 102, 103, 104, 106, 108, 110, 112, 113, 114, 115, 116, 117, 118, 119, 120, 121, 239, 240, 241, 242, 243, 244, 245, 246, 247, 249, 251, 253, 255, 256, 257, 258, 259, 260, 261, 262, 263, 264

G

`\GTS@@drawDownArrow` 117, 118, 128, 132, 260, 261, 271, 275
`\GTS@@drawSlash` 112, 113, 114, 126, 131, 255, 256, 257, 269, 274
`\GTS@@drawUpArrow` 115, 116, 127, 132, 258, 259, 270, 275
`\GTS@mainColor` 96, 97, 98, 99, 105, 107, 109, 111, 124, 131, 239, 240, 241, 242, 248, 250, 252, 254, 267, 274
`\GTS@@relation` 119, 120, 121, 129, 132, 262, 263, 264, 272, 275
`\GTS@secondColor` . 100, 101, 102, 103, 105, 107, 109, 111, 125, 131, 243, 244, 245, 246, 248, 250, 252, 254, 268, 274
`\GTS@a` . 4, 31, 91, 93, 138, 139, 140, 144, 145, 146, 150, 151, 152, 156, 157, 158, 164, 165, 166, 170, 171, 172, 317, 318, 319, 320, 325, 326, 327, 328, 334, 336, 337, 338, 346, 348, 349, 350, 358, 360, 361, 362, 370, 372, 373, 374
`\GTS@b` 4, 89, 131
`\GTS@drawDownArrow` 16
`\GTS@drawSlash` 14
`\GTS@drawUpArrow` 15
`\GTS@i` . . 6, 234, 236, 281, 282, 283, 287, 288, 289, 293, 294, 295, 299, 300, 301, 305, 306, 307, 311, 312, 313, 381, 382, 383, 384, 390, 392, 393, 394, 399, 400, 401, 402, 408, 410, 411, 412, 419, 420, 421, 422, 428, 430, 431, 432
`\GTS@j` 7, 274
`\GTS@mainColor` 10, 23, 24, 50, 64, 70, 201
`\GTS@mainColorBackup` 12, 23, 83, 226
`\GTS@mainColorTemp` 22, 24
`\GTS@newcommand` . . 4, 18, 138, 139, 140, 141, 142, 143, 144, 145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155, 156, 157, 158, 159, 162, 163, 164, 165, 166, 167, 168, 169, 170, 171, 172, 173, 176, 177, 281, 282, 283, 284, 285, 286, 287, 288, 289, 290, 291, 292, 293, 294, 295, 296, 297, 298, 299, 300, 301, 302, 303, 304, 305, 306, 307, 308, 309, 310, 311, 312, 313, 314, 315, 316, 317, 318, 319, 320, 321, 322, 323, 324, 325, 326, 327, 328, 329, 330, 331, 332, 333, 336, 337, 338, 339, 342, 343, 344, 345, 348, 349, 350, 351, 354, 355, 356, 357, 360, 361, 362, 363, 366, 367, 368, 369, 372, 373, 374, 375, 378, 379, 380, 381, 382, 383, 384, 385, 386, 387, 388, 389, 392, 393, 394, 395, 396, 397, 398, 399, 400, 401, 402, 403, 404, 405, 406, 407, 410, 411, 412, 413, 416, 417, 418, 419, 420, 421, 422, 423, 424, 425, 426, 427, 430, 431, 432, 433, 436, 437, 438
`\GTS@secondColor` 11, 28, 29, 42, 46, 54, 58, 189, 193, 197, 207, 213
`\GTS@secondColorBackup` 13, 28, 86, 229
`\GTS@secondColorTemp` 27, 29
`\GTSa` 4, 138, 141, 142, 143
`\GTSadj` 4, 138
`\GTSadjacency` 4, 138
`\GTSadjacencyMonochrome` 9
`\GTSadjacencyMonochromeRelation` 9, 320, 321
`\GTSadjacencyRelation` 5, 141
`\GTSadjMon` 9
`\GTSadjMono` 9
`\GTSadjMonoRel` 9, 320

\GTSadjMonRel	9, <u>320</u>
\GTSadjRel	5, <u>141</u>
\GTSaM	9, <u>321</u> , <u>322</u> , <u>323</u> , <u>324</u>
\GTSaMR	9, <u>320</u>
\GTSaR	5, <u>141</u>
\GTSdAD	6, <u>167</u> , <u>168</u> , <u>169</u>
\GTSdADM	11, <u>356</u> , <u>364</u> , <u>366</u> , <u>367</u> , <u>368</u>
\GTSdADMR	11, <u>362</u>
\GTSdADR	6, <u>166</u>
\GTSdAU	5, <u>150</u> , <u>153</u> , <u>154</u> , <u>155</u>
\GTSdAUM	10, <u>332</u> , <u>340</u> , <u>342</u> , <u>343</u> , <u>344</u>
\GTSdAUMR	10, <u>338</u>
\GTSdAUR	5, <u>152</u>
\GTSdirAdjDown	6
\GTSdirAdjDownMon	11, <u>356</u>
\GTSdirAdjDownMono	11, <u>356</u>
\GTSdirAdjDownMonoRel	11, <u>362</u>
\GTSdirAdjDownMonRel	11, <u>362</u>
\GTSdirAdjDownRel	6, <u>166</u>
\GTSdirAdjUp	5, <u>150</u>
\GTSdirAdjUpMon	10, <u>332</u>
\GTSdirAdjUpMono	10, <u>332</u>
\GTSdirAdjUpMonoRel	10, <u>338</u>
\GTSdirAdjUpMonRel	10, <u>338</u>
\GTSdirAdjUpRel	5, <u>152</u>
\GTSdirectedAdjacencyDown	6
\GTSdirectedAdjacencyDownMonochrome	11, <u>356</u> , <u>357</u>
\GTSdirectedAdjacencyDownMonochromeRelation	11, <u>362</u> , <u>363</u>
\GTSdirectedAdjacencyDownRelation	6, <u>166</u> , <u>167</u>
\GTSdirectedAdjacencyUp	5, <u>150</u>
\GTSdirectedAdjacencyUpMonochrome	10, <u>332</u> , <u>333</u>
\GTSdirectedAdjacencyUpMonochromeRelation	10, <u>338</u> , <u>339</u>
\GTSdirectedAdjacencyUpRelation	5, <u>152</u> , <u>153</u>
\GTSi	7, <u>284</u> , <u>285</u> , <u>286</u>
\GTSiI	8, <u>308</u> , <u>309</u> , <u>310</u>
\GTSiIM	13, <u>423</u> , <u>424</u> , <u>425</u> , <u>426</u>
\GTSiIMR	13, <u>422</u>
\GTSiIR	9
\GTSiM	11, <u>385</u> , <u>386</u> , <u>387</u> , <u>388</u>
\GTSiMR	12, <u>384</u>
\GTSinc	7
\GTSincidence	7
\GTSincidenceMonochrome	11
\GTSincidenceMonochromeRelation	12, <u>384</u> , <u>385</u>
\GTSincidenceRelation	7
\GTSincMon	11
\GTSincMono	11
\GTSincMonoRel	12, <u>384</u>
\GTSincMonRel	12, <u>384</u>
\GTSincRel	7
\GTSinInc	8
\GTSinIncidence	8
\GTSinIncidenceMonochrome	13
\GTSinIncidenceMonochromeRelation	13, <u>422</u> , <u>423</u>
\GTSinIncidenceRelation	9
\GTSinIncMon	13
\GTSinIncMono	13
\GTSinIncMonoRel	13, <u>422</u>
\GTSinIncMonRel	13, <u>422</u>
\GTSinIncRel	9
\GTSiR	7

\GTSnDAD	6, <u>169</u> , 174, 176, 177
\GTSnDADM	11, <u>368</u> , 376, 378, 379, 380
\GTSnDADMR	11, <u>374</u>
\GTSnDADR	6, <u>172</u>
\GTSnDAU	5, <u>155</u> , 160, 162, 163
\GTSnDAUM	10, <u>344</u> , 352, 354, 355, 356
\GTSnDAUMR	11, <u>350</u>
\GTSnDAUR	6, <u>158</u>
\GTSnegatedDirectedAdjacencyDown	6, <u>169</u> , 170
\GTSnegatedDirectedAdjacencyDownMonochrome	11, <u>368</u> , 369
\GTSnegatedDirectedAdjacencyDownMonochromeRelation	11, <u>374</u> , 375
\GTSnegatedDirectedAdjacencyDownRelation	6, <u>172</u> , 173
\GTSnegatedDirectedAdjacencyUp	5, <u>155</u> , 156
\GTSnegatedDirectedAdjacencyUpMonochrome	10, <u>344</u> , 345
\GTSnegatedDirectedAdjacencyUpMonochromeRelation	11, <u>350</u> , 351
\GTSnegatedDirectedAdjacencyUpRelation	6, <u>158</u> , 159
\GTSnegatedIncidence	7
\GTSnegatedIncidenceMonochrome	12, <u>388</u> , 389
\GTSnegatedIncidenceMonochromeRelation	12, <u>394</u> , 395
\GTSnegatedIncidenceRelation	8, <u>289</u> , 290
\GTSnegatedInIncidence	9
\GTSnegatedInIncidenceMonochrome	14, <u>426</u> , 427
\GTSnegatedInIncidenceMonochromeRelation	14, <u>432</u> , 433
\GTSnegatedInIncidenceRelation	9, <u>313</u> , 314
\GTSnegatedOutIncidence	8
\GTSnegatedOutIncidenceMonochrome	13, <u>406</u> , 407
\GTSnegatedOutIncidenceMonochromeRelation	13, <u>412</u> , 413
\GTSnegatedOutIncidenceRelation	8, <u>301</u> , 302
\GTSnegDirAdjDown	6, <u>169</u>
\GTSnegDirAdjDownMon	11, <u>368</u>
\GTSnegDirAdjDownMono	11, <u>368</u>
\GTSnegDirAdjDownMonoRel	11, <u>374</u>
\GTSnegDirAdjDownMonRel	11, <u>374</u>
\GTSnegDirAdjDownRel	6, <u>172</u>
\GTSnegDirAdjUp	5, <u>155</u>
\GTSnegDirAdjUpMon	10, <u>344</u>
\GTSnegDirAdjUpMono	10, <u>344</u>
\GTSnegDirAdjUpMonoRel	11, <u>350</u>
\GTSnegDirAdjUpMonRel	11, <u>350</u>
\GTSnegDirAdjUpRel	6, <u>158</u>
\GTSnegInc	7
\GTSnegIncMon	12, <u>388</u>
\GTSnegIncMono	12, <u>388</u>
\GTSnegIncMonoRel	12, <u>394</u>
\GTSnegIncMonRel	12, <u>394</u>
\GTSnegIncRel	8, <u>289</u>
\GTSnegInInc	9
\GTSnegInIncMon	14, <u>426</u>
\GTSnegInIncMono	14, <u>426</u>
\GTSnegInIncMonoRel	14, <u>432</u>
\GTSnegInIncMonRel	14, <u>432</u>
\GTSnegInIncRel	9, <u>313</u>
\GTSnegOutInc	8
\GTSnegOutIncMon	13, <u>406</u>
\GTSnegOutIncMono	13, <u>406</u>
\GTSnegOutIncMonoRel	13, <u>412</u>
\GTSnegOutIncMonRel	13, <u>412</u>
\GTSnegOutIncRel	8, <u>301</u>
\GTSnI	7, 290, 291, 292
\GTSnII	9, 314, 315, 316
\GTSnIIM	14, <u>426</u> , 434, 436, 437, 438

\GTSnIIMR	14, 432
\GTSnIIR	9, 313
\GTSnIM	12, 388 , 395, 396, 397, 398
\GTSnIMR	12, 394
\GTSnIR	8, 289
\GTSnOI	8, 302, 303, 304
\GTSnOIM	13, 406 , 414, 416, 417, 418
\GTSnOIMR	13, 412
\GTSnOIR	8, 301
\GTSOI	8, 296, 297, 298
\GTSOIM	12, 403, 404, 405, 406
\GTSOIMR	13, 402
\GTSOIR	8
\GTSoutInc	8
\GTSoutIncidence	8
\GTSoutIncidenceMonochrome	12
\GTSoutIncidenceMonochromeRelation	13, 402 , 403
\GTSoutIncidenceRelation	8
\GTSoutIncMon	12
\GTSoutIncMono	12
\GTSoutIncMonoRel	13, 402
\GTSoutIncMonRel	13, 402
\GTSoutIncRel	8
\GTSsetMainColor	4, 21 , 33, 83, 180, 226
\GTSsetSecondColor	4, 26 , 36, 86, 183, 229
\GTSu	5, 144 , 147, 148, 149
\GTSuM	9, 329, 330, 331, 332
\GTSuMR	10, 328
\GTSunadj	5, 144
\GTSunadjacency	5, 144
\GTSunadjacencyMonochrome	9
\GTSunadjacencyMonochromeRelation	10, 328 , 329
\GTSunadjacencyRelation	5, 147
\GTSunadjMon	9
\GTSunadjMono	9
\GTSunadjMonoRel	10, 328
\GTSunadjMonRel	10, 328
\GTSunadjRel	5, 147
\GTSuR	5, 147
\GTSxa	4, 96
\GTSxadj	4, 96
\GTSxadjacency	4, 96
\GTSxi	7
\GTSxinc	7
\GTSxincidence	7

S

\setkeys	130, 273
----------	----------