

GraphTheorySymbol: L^AT_EX Commands with Symbols for Graph Theory

Laurent Frédéric Bernard François Lyaudet

Website:<https://lyaudet.eu/laurent/>

Email:Laurent.Lyaudet@gmail.com

v1.7.0 2026/09/21

Abstract

This documentation is for L^AT_EX package GraphTheorySymbol. It provides symbols used in graph theory. The adjacency and incidence symbols, and the meta-logical operators symbols were created by the author of this package.

Contents

1	Introduction	1
2	Usage	3
2.1	Memo or for the impatient	3
2.2	Detailed usage	6
2.2.1	General macros	6
2.2.2	Standard adjacency macros	6
2.2.3	Standard incidence macros	9
2.2.4	Monochrome adjacency macros	12
2.2.5	Monochrome incidence macros	15
2.2.6	Meta-logic macros	17
2.3	Good practices	19
3	Implementation	19
4	Acknowledgments	33
5	FAQ	33
6	Support	33
7	Change History	33

1 Introduction

This documentation is for L^AT_EX package GraphTheorySymbol. It provides symbols used in graph theory. The adjacency and incidence symbols, and the meta-logical operators symbols were created by the author of this package.

This package is licenced under Lesser GNU General Public License version 3 or later (LGPLv3+). It means you are free do anything with it, but if you do improve the code of the symbols that we provide, please do share these improvements in a similar way. There is no restriction on other graph theory symbols/code, even if it would be a good fit for inclusion in this package. There is also no need to share in a similar way what you build with this package. The text of the licenses is available at: <https://www.gnu.org/licenses/>.

The git repository of this source code is also available at: <https://github.com/LLyaudet/GraphTheorySymbol/>.

Clone it with this URL:

[git@github.com:LLyaudet/GraphTheorySymbol.git](https://github.com:LLyaudet/GraphTheorySymbol.git).

This package is available on CTAN:

<https://ctan.org/pkg/graph-theory-symbol>.

This is our first $\text{\LaTeX}$ package. It may be that our macros are quite slow and that a document making extensive use of these macros will be slow to compile. If you know how to produce better $\text{\LaTeX}$ code, please submit a pull request on GitHub.

2 Usage

2.1 Memo or for the impatient

Add in your preamble: `\usepackage{graph-theory-symbol}`.

For clarity, below we only show long macro names and short macro names; see Detailed usage section for intermediate length macro names.

Long name	Short name	Result	In context
<code>\GTSadjacency/</code>	<code>\GTSa/</code>	$\mathbb{I}$	$u \mathbb{I} v$
<code>\GTSadjacencyRelation/</code>	<code>\GTSaR/</code>	$\mathbb{I}$	$u \mathbb{I} v$
<code>\GTSunadjacency/</code>	<code>\GTSu/</code>	$\mathbb{J}$	$u \mathbb{J} v$
<code>\GTSunadjacencyRelation/</code>	<code>\GTSuR/</code>	$\mathbb{J}$	$u \mathbb{J} v$
<code>\GTSdirectedAdjacencyUp/</code>	<code>\GTSdAU/</code>	$\mathbb{I}$	$u \mathbb{I} v$
<code>\GTSdirectedAdjacencyUpRelation/</code>	<code>\GTSdAUR/</code>	$\mathbb{I}$	$u \mathbb{I} v$
<code>\GTSnegatedDirectedAdjacencyUp/</code>	<code>\GTSnDAU/</code>	$\mathbb{J}$	$u \mathbb{J} v$
<code>\GTSnegatedDirectedAdjacencyUpRelation/</code>	<code>\GTSnDAUR/</code>	$\mathbb{J}$	$u \mathbb{J} v$
<code>\GTSdirectedAdjacencyDown/</code>	<code>\GTSdAD/</code>	$\mathbb{I}$	$u \mathbb{I} v$
<code>\GTSdirectedAdjacencyDownRelation/</code>	<code>\GTSdADR/</code>	$\mathbb{I}$	$u \mathbb{I} v$
<code>\GTSnegatedDirectedAdjacencyDown/</code>	<code>\GTSnDAD/</code>	$\mathbb{J}$	$u \mathbb{J} v$
<code>\GTSnegatedDirectedAdjacencyDownRelation/</code>	<code>\GTSnDADR/</code>	$\mathbb{J}$	$u \mathbb{J} v$
<code>\GTSincidence/</code>	<code>\GTSi/</code>	$\mathbb{I}$	$v \mathbb{I} e$
<code>\GTSincidenceRelation/</code>	<code>\GTSiR/</code>	$\mathbb{I}$	$v \mathbb{I} e$
<code>\GTSnegatedIncidence/</code>	<code>\GTSnI/</code>	$\mathbb{J}$	$v \mathbb{J} e$
<code>\GTSnegatedIncidenceRelation/</code>	<code>\GTSnIR/</code>	$\mathbb{J}$	$v \mathbb{J} e$
<code>\GTSoutIncidence/</code>	<code>\GTSoI/</code>	$\mathbb{I}$	$v \mathbb{I} e$
<code>\GTSoutIncidenceRelation/</code>	<code>\GTSoIR/</code>	$\mathbb{I}$	$v \mathbb{I} e$
<code>\GTSnegatedOutIncidence/</code>	<code>\GTSnOI/</code>	$\mathbb{J}$	$v \mathbb{J} e$
<code>\GTSnegatedOutIncidenceRelation/</code>	<code>\GTSnOIR/</code>	$\mathbb{J}$	$v \mathbb{J} e$
<code>\GTSinIncidence/</code>	<code>\GTSiI/</code>	$\mathbb{I}$	$v \mathbb{I} e$
<code>\GTSinIncidenceRelation/</code>	<code>\GTSiIR/</code>	$\mathbb{I}$	$v \mathbb{I} e$
<code>\GTSnegatedInIncidence/</code>	<code>\GTSnII/</code>	$\mathbb{J}$	$v \mathbb{J} e$
<code>\GTSnegatedInIncidenceRelation/</code>	<code>\GTSnIIR/</code>	$\mathbb{J}$	$v \mathbb{J} e$

Long name	Short name	Result	In context
<code>\GTSadjacencyMonochrome/</code>	<code>\GTSaM/</code>	$\mathbb{I}$	$u \mathbb{I} v$
<code>\GTSadjacencyMonochromeRelation/</code>	<code>\GTSaMR/</code>	$\mathbb{I}$	$u \mathbb{I} v$
<code>\GTSunadjacencyMonochrome/</code>	<code>\GTSuM/</code>	$\mathbb{J}$	$u \mathbb{J} v$
<code>\GTSunadjacencyMonochromeRelation/</code>	<code>\GTSuMR/</code>	$\mathbb{J}$	$u \mathbb{J} v$
<code>\GTSdirectedAdjacencyUpMonochrome/</code>	<code>\GTSdAUM/</code>	$\mathbb{I}$	$u \mathbb{I} v$
<code>\GTSdirectedAdjacencyUpMonochromeRelation/</code>	<code>\GTSdAUMR/</code>	$\mathbb{I}$	$u \mathbb{I} v$
<code>\GTSnegatedDirectedAdjacencyUpMonochrome/</code>	<code>\GTSnDAUM/</code>	$\mathbb{J}$	$u \mathbb{J} v$
<code>\GTSnegatedDirectedAdjacencyUpMonochromeRelation/</code>	<code>\GTSnDAUMR/</code>	$\mathbb{J}$	$u \mathbb{J} v$
<code>\GTSdirectedAdjacencyDownMonochrome/</code>	<code>\GTSdADM/</code>	$\mathbb{I}$	$u \mathbb{I} v$
<code>\GTSdirectedAdjacencyDownMonochromeRelation/</code>	<code>\GTSdADM/</code>	$\mathbb{I}$	$u \mathbb{I} v$
<code>\GTSnegatedDirectedAdjacencyDownMonochrome/</code>	<code>\GTSnDADM/</code>	$\mathbb{J}$	$u \mathbb{J} v$
<code>\GTSnegatedDirectedAdjacencyDownMonochromeRelation/</code>	<code>\GTSnDADM/</code>	$\mathbb{J}$	$u \mathbb{J} v$
<code>\GTSincidenceMonochrome/</code>	<code>\GTSiM/</code>	$\mathbb{I}$	$v \mathbb{I} e$
<code>\GTSincidenceMonochromeRelation/</code>	<code>\GTSiMR/</code>	$\mathbb{I}$	$v \mathbb{I} e$
<code>\GTSnegatedIncidenceMonochrome/</code>	<code>\GTSnIM/</code>	$\mathbb{J}$	$v \mathbb{J} e$
<code>\GTSnegatedIncidenceMonochromeRelation/</code>	<code>\GTSnIMR/</code>	$\mathbb{J}$	$v \mathbb{J} e$
<code>\GTSoutIncidenceMonochrome/</code>	<code>\GTSoIM/</code>	$\mathbb{I}$	$v \mathbb{I} e$
<code>\GTSoutIncidenceMonochromeRelation/</code>	<code>\GTSoIMR/</code>	$\mathbb{I}$	$v \mathbb{I} e$
<code>\GTSnegatedOutIncidenceMonochrome/</code>	<code>\GTSnOIM/</code>	$\mathbb{J}$	$v \mathbb{J} e$
<code>\GTSnegatedOutIncidenceMonochromeRelation/</code>	<code>\GTSnOIMR/</code>	$\mathbb{J}$	$v \mathbb{J} e$
<code>\GTSinIncidenceMonochrome/</code>	<code>\GTSiIM/</code>	$\mathbb{I}$	$v \mathbb{I} e$
<code>\GTSinIncidenceMonochromeRelation/</code>	<code>\GTSiIMR/</code>	$\mathbb{I}$	$v \mathbb{I} e$
<code>\GTSnegatedInIncidenceMonochrome/</code>	<code>\GTSnIIM/</code>	$\mathbb{J}$	$v \mathbb{J} e$
<code>\GTSnegatedInIncidenceMonochromeRelation/</code>	<code>\GTSnIIMR/</code>	$\mathbb{J}$	$v \mathbb{J} e$

<code>\GTSsetMainColor{blue}</code>			
Long name	Short name	Result	In context
<code>\GTSadjacency/</code>	<code>\GTSa/</code>		$u \overset{\circ}{\sim} v$
<code>\GTSadjacencyRelation/</code>	<code>\GTSaR/</code>		$u \overset{\circ}{\sim} v$
<code>\GTSunadjacency/</code>	<code>\GTSu/</code>		$u \overset{\circ}{\sim} v$
<code>\GTSunadjacencyRelation/</code>	<code>\GTSuR/</code>		$u \overset{\circ}{\sim} v$
<code>\GTSdirectedAdjacencyUp/</code>	<code>\GTSdAU/</code>		$u \overset{\circ}{\sim} v$
<code>\GTSdirectedAdjacencyUpRelation/</code>	<code>\GTSdAUR/</code>		$u \overset{\circ}{\sim} v$
<code>\GTSnegatedDirectedAdjacencyUp/</code>	<code>\GTSnDAU/</code>		$u \overset{\circ}{\sim} v$
<code>\GTSnegatedDirectedAdjacencyUpRelation/</code>	<code>\GTSnDAUR/</code>		$u \overset{\circ}{\sim} v$
<code>\GTSdirectedAdjacencyDown/</code>	<code>\GTSdAD/</code>		$u \overset{\circ}{\sim} v$
<code>\GTSdirectedAdjacencyDownRelation/</code>	<code>\GTSdADR/</code>		$u \overset{\circ}{\sim} v$
<code>\GTSnegatedDirectedAdjacencyDown/</code>	<code>\GTSnDAD/</code>		$u \overset{\circ}{\sim} v$
<code>\GTSnegatedDirectedAdjacencyDownRelation/</code>	<code>\GTSnDADR/</code>		$u \overset{\circ}{\sim} v$
<code>\GTSincidence/</code>	<code>\GTSi/</code>		$v \overset{\circ}{\sim} e$
<code>\GTSincidenceRelation/</code>	<code>\GTSiR/</code>		$v \overset{\circ}{\sim} e$
<code>\GTSnegatedIncidence/</code>	<code>\GTSnI/</code>		$v \overset{\circ}{\sim} e$
<code>\GTSnegatedIncidenceRelation/</code>	<code>\GTSnIR/</code>		$v \overset{\circ}{\sim} e$
<code>\GTSoutIncidence/</code>	<code>\GTSOI/</code>		$v \overset{\circ}{\sim} e$
<code>\GTSoutIncidenceRelation/</code>	<code>\GTSOIR/</code>		$v \overset{\circ}{\sim} e$
<code>\GTSnegatedOutIncidence/</code>	<code>\GTSnOI/</code>		$v \overset{\circ}{\sim} e$
<code>\GTSnegatedOutIncidenceRelation/</code>	<code>\GTSnOIR/</code>		$v \overset{\circ}{\sim} e$
<code>\GTSinIncidence/</code>	<code>\GTSiI/</code>		$v \overset{\circ}{\sim} e$
<code>\GTSinIncidenceRelation/</code>	<code>\GTSiIR/</code>		$v \overset{\circ}{\sim} e$
<code>\GTSnegatedInIncidence/</code>	<code>\GTSnII/</code>		$v \overset{\circ}{\sim} e$
<code>\GTSnegatedInIncidenceRelation/</code>	<code>\GTSnIIR/</code>		$v \overset{\circ}{\sim} e$

Long name	Short name	Result	In context
<code>\GTSmetaNot/</code>	<code>\GTSmN/</code>	$\neg$	$\neg \overset{\circ}{\sim}$
<code>\GTSmetaAnd/</code>	<code>\GTSmA/</code>	$\wedge$	$\overset{\circ}{\sim} \wedge \overset{\circ}{\sim}$
<code>\GTSmetaOr/</code>	<code>\GTSmO/</code>	$\vee$	$\overset{\circ}{\sim} \vee \overset{\circ}{\sim}$

Meta-logic can be used for compound adjacency types, etc.

Implicit meta-and via concatenation, no space except around whole relations compositions, no parentheses via higher priority to meta-and, brackets when all possible adjacencies are specified between two vertices:

Tournament adjacency:

$\forall u, v, u \overset{\circ}{\sim} \overset{\circ}{\sim} v$.

Tournament adjacency with maybe some colored edge also, who knows?:

$\forall u, v, u \overset{\circ}{\sim} \overset{\circ}{\sim} v$.

Directed graph:

$\forall u, v, u \overset{\circ}{\sim} \overset{\circ}{\sim} \overset{\circ}{\sim} \overset{\circ}{\sim} v$.

Oriented graph:

$\forall u, v, u \overset{\circ}{\sim} \overset{\circ}{\sim} \overset{\circ}{\sim} v$.

Tournament adjacency:

$\overset{\circ}{\sim} \overset{\circ}{\sim}$ is obtained with `\mathrel{\{\GTSdAD/\GTSnDAU/\GTSmO/\GTSnDAD/\GTSdAU/\}}`.

Tournament adjacency with maybe some colored edge also, who knows?:

$\overset{\circ}{\sim} \overset{\circ}{\sim}$ is obtained with `\mathrel{\{\GTSdAD/\GTSnDAU/\GTSmO/\GTSnDAD/\GTSdAU/\}}`.

Directed graph:

$\overset{\circ}{\sim} \overset{\circ}{\sim} \overset{\circ}{\sim} \overset{\circ}{\sim}$ is obtained with

`\mathrel{\{\GTSdAD/\GTSnDAU/\GTSmO/\GTSnDAD/\GTSdAU/\GTSmO/\GTSdAD/\GTSdAU/\GTSmO/\GTSnDAD/\GTSnDAU/\}}`.

Oriented graph:

$\overset{\circ}{\sim} \overset{\circ}{\sim} \overset{\circ}{\sim}$ is obtained with

`\mathrel{\{\GTSdAD/\GTSnDAU/\GTSmO/\GTSnDAD/\GTSdAU/\GTSmO/\GTSnDAD/\GTSnDAU/\}}`.

Prefix notation:

$\exists u, v, u \overset{\circ}{\sim} \overset{\circ}{\sim} v \Leftrightarrow \exists u, v, u \overset{\circ}{\sim} \overset{\circ}{\sim} v$.

$\exists v, e, v \overset{\circ}{\sim} \overset{\circ}{\sim} e \Leftrightarrow \exists v, e, v \overset{\circ}{\sim} \overset{\circ}{\sim} e$.

$\overset{\circ}{\sim} \overset{\circ}{\sim}$ is obtained with

`\mathrel{\{\GTSmO/\GTSxa[mC=red,d]\GTSxa[mC=green,d]\GTSxa[mC=blue,u]\}}`.

$\mathrel{\mathop{\mathbb{V}}\limits^{\textcolor{red}{\text{r}}}\textcolor{green}{\text{g}}\textcolor{blue}{\text{b}}}}$ is obtained with
`\mathrel{\{\GTSm0/\GTSxi[mC=red,i]\GTSxi[mC=green,i]\GTSxi[mC=blue,o]\}}.`

Apart from these symbol macros, versatile macros to call them all are available with options:
`\GTSxa[]`, `\GTSxadj[]`, or `\GTSxadjacency[]` for adjacency symbols,
`\GTSxi[]`, `\GTSxinc[]`, or `\GTSxincidence[]` for incidence symbols,
`\GTSxml[]`, or `\GTSxmetallogic[]` for meta-logic symbols,
`\GTSx[]{} for all symbols`
 $(\GTSx[]\{a\} = \GTSxa[], \GTSx[]\{i\} = \GTSxi[], \GTSx[]\{m\} = \GTSxml[]).$
 See Detailed usage section for full syntax of these macros.

2.2 Detailed usage

First you need to add in your preamble: `\usepackage{graph-theory-symbol}`.

All symbols macros were designed with ease of use in mind: they are called with a trailing slash, they can be called in text mode or in math mode, a variant with relation spacing for math mode exists with suffix “relation”.

2.2.1 General macros

\GTS@newcommand This macro will enforce that the other macros are called with a trailing slash, avoiding problems with spaces after macro call.

Arguments:

`{<commandname>}` The name of the command to create.

`{<commandcode>}` The code of the command to create.

\GTS@newprotectedcommand This macro will enforce that the other macros are called with a trailing slash, avoiding problems with spaces after macro call.

Arguments:

`{<commandname>}` The name of the command to create.

`{<commandcode>}` The code of the command to create.

\GTSsetMainColor This macro will set the main color used in GraphTheorySymbol. This color has initial value “black”.

Argument:

`{<color>}` The color that must be used by GraphTheorySymbol afterward.

\GTSsetSecondColor This macro will set the second color used in GraphTheorySymbol. This color has initial value “gray”.

Argument:

`{<color>}` The color that must be used by GraphTheorySymbol afterward.

2.2.2 Standard adjacency macros

\GTS@a This macro will draw any of the adjacency symbols if the correct arguments are given. It is not expected to be used directly. See the macros derived from it and **\GTS@b**: **\GTSxadjacency**, **\GTSxadj**, and **\GTSxa**.

Arguments:

`{<mainColor>}` If non-empty, this color will be used as main color.

`{<secondColor>}` If non-empty, this color will be used as second color.

`{<drawSlash>}` Non-empty implies that a negation will be drawn.

`{<drawUpArrow>}` Non-empty implies that an up-arrow will be drawn.

`{<drawDownArrow>}` Non-empty implies that a down-arrow will be drawn.

\GTS@b This macro builds on top of **\GTS@a** to handle mathematical relation spacing if sixth argument is not empty. It is not expected to be used directly. See the macros derived from it and **\GTS@a**: **\GTSxadjacency**, **\GTSxadj**, and **\GTSxa**.

Arguments:

`{<mainColor>}` If non-empty, this color will be used as main color.

`{<secondColor>}` If non-empty, this color will be used as second color.

`{<drawSlash>}` Non-empty implies that a negation will be drawn.

`{<drawUpArrow>}` Non-empty implies that an up-arrow will be drawn.

`{<drawDownArrow>}` Non-empty implies that a down-arrow will be drawn.

`{<relation>}` Non-empty implies that relation spacing will be added.

\GTSxadjacency, **\GTSxadj**, **\GTSxa** Versatile macros for adjacency that can be given options.

Argument:

`[<optionsList>]` Sets the following options if not empty:

`mainColor=color1` or `mainC=color1` or `mColor=color1` or `mC=color1`,

`secondColor=color2` or `secondC=color2` or `sColor=color2` or `sC=color2`,

`monochrome` or `mono` or `mon` or `m` (equivalent to `mC=black,sC=black`),

`negated` or `not` or `n`,

up or u,
down or d,
relation or rel or r.

\GTSadjacency, \GTSadj, \GTSa This macro will draw an adjacency symbol. A first drawing didn't include the small dots in the middle of the two circles corresponding to the graph vertices. But it was too similar to “spoon” and multimap symbols, and could be confused with a graph with only two vertices and one edge. Hence, these dots were added and they have the nice property to remind of the classical textual notation of adjacency relation as Adj(.,.).

A.\GTSadjacency/A.
or A.\GTSadj/A.
or A.\GTSa/A.
will yield $A \circ A$.
u \GTSadjacency/ v
or u \GTSadj/ v
or u \GTSa/ v
will yield $u \circ v$.
\$u \GTSadjacency/ v\$
or \$u \GTSadj/ v\$
or \$u \GTSa/ v\$
will yield $u \circ v$.

\GTSadjacencyRelation, \GTSadjRel, \GTSaR This macro will draw an adjacency symbol.
\$u\GTSadjacencyRelation/v\$
or \$u\GTSadjRel/v\$
or \$u\GTSaR/v\$
will yield $u \circ v$.

\GTSunadjacency, \GTSunadj, \GTSu This macro will draw an unadjacency symbol.
A.\GTSunadjacency/A.
or A.\GTSunadj/A.
or A.\GTSu/A.
will yield $A \circ A$.
u \GTSunadjacency/ v
or u \GTSunadj/ v
or u \GTSu/ v
will yield $u \circ v$.
\$u \GTSunadjacency/ v\$
or \$u \GTSunadj/ v\$
or \$u \GTSu/ v\$
will yield $u \circ v$.

\GTSunadjacencyRelation, \GTSunadjRel, \GTSuR This macro will draw an unadjacency symbol.
\$u\GTSunadjacencyRelation/v\$
or \$u\GTSunadjRel/v\$
or \$u\GTSuR/v\$
will yield $u \circ v$.

\GTSdirectedAdjacencyUp, \GTSdirAdjUp, \GTSdAU This macro will draw a directed adjacency upward symbol. The operand on the left of the symbol should be considered the source of the arc; the operand on the right of the symbol should be considered the target of the arc.

A.\GTSdirectedAdjacencyUp/A.
or A.\GTSdirAdjUp/A.
or A.\GTSdAU/A.
will yield $A \circ A$.
u \GTSdirectedAdjacencyUp/ v
or u \GTSdirAdjUp/ v
or u \GTSdAU/ v
will yield $u \circ v$.

`\GTSdirectedAdjacencyUp/ v$`
or `\GTSdirAdjUp/ v$`
or `\GTSdAU/ v$`
will yield $u \overset{\circ}{\rightharpoonup} v$.

`\GTSdirectedAdjacencyUpRelation, \GTSdirAdjUpRel, \GTSdAUR` This macro will draw a directed adjacency upward symbol with relation spacing in math mode.
`\GTSdirectedAdjacencyUpRelation/v$`
or `\GTSdirAdjUpRel/v$`
or `\GTSdAUR/v$`
will yield $u \overset{\circ}{\rightharpoonup} v$.

`\GTSnegatedDirectedAdjacencyUp, \GTSnegDirAdjUp, \GTSnDAU` This macro will draw a negated directed adjacency upward symbol.
`A.\GTSnegatedDirectedAdjacencyUp/A.`
or `A.\GTSnegDirAdjUp/A.`
or `A.\GTSnDAU/A.`
will yield $A \overset{\circ}{\nrightarrow} A$.
`u \GTSnegatedDirectedAdjacencyUp/ v`
or `u \GTSnegDirAdjUp/ v`
or `u \GTSnDAU/ v`
will yield $u \overset{\circ}{\nrightarrow} v$.
`$u \GTSnegatedDirectedAdjacencyUp/ v$`
or `$u \GTSnegDirAdjUp/ v$`
or `$u \GTSnDAU/ v$`
will yield $u \overset{\circ}{\nrightarrow} v$.

`\GTSnegatedDirectedAdjacencyUpRelation, \GTSnegDirAdjUpRel, \GTSnDAUR` This macro will draw a negated directed adjacency upward symbol with relation spacing in math mode.
`$u\GTSnegatedDirectedAdjacencyUpRelation/v$`
or `$u\GTSnegDirAdjUpRel/v$`
or `$u\GTSnDAUR/v$`
will yield $u \overset{\circ}{\nrightarrow} v$.

`\GTSdirectedAdjacencyDown, \GTSdirAdjDown, \GTSdAD` This macro will draw a directed adjacency downward symbol. The operand on the left of the symbol should be considered the target of the arc; the operand on the right of the symbol should be considered the source of the arc.
`A.\GTSdirectedAdjacencyDown/A.`
or `A.\GTSdirAdjDown/A.`
or `A.\GTSnDAD/A.`
will yield $A \overset{\circ}{\searrow} A$.
`u \GTSdirectedAdjacencyDown/ v`
or `u \GTSdirAdjDown/ v`
or `u \GTSnDAD/ v`
will yield $u \overset{\circ}{\searrow} v$.
`$u \GTSdirectedAdjacencyDown/ v$`
or `$u \GTSdirAdjDown/ v$`
or `$u \GTSnDAD/ v$`
will yield $u \overset{\circ}{\searrow} v$.

`\GTSdirectedAdjacencyDownRelation, \GTSdirAdjDownRel, \GTSdADR` This macro will draw a directed adjacency downward symbol with relation spacing in math mode.
`$u\GTSdirectedAdjacencyDownRelation/v$`
or `$u\GTSdirAdjDownRel/v$`
or `$u\GTSdADR/v$`
will yield $u \overset{\circ}{\searrow} v$.

`\GTSnegatedDirectedAdjacencyDown, \GTSnegDirAdjDown, \GTSnDAD` This macro will draw a negated directed adjacency downward symbol.
`A.\GTSnegatedDirectedAdjacencyDown/A.`

`or A.\GTSnegDirAdjDown/A.`
`or A.\GTSnDAD/A.`
 will yield $A \not\sim A$.
`u \GTSnegatedDirectedAdjacencyDown/ v`
`or u \GTSnegDirAdjDown/ v`
`or u \GTSnDAD/ v`
 will yield $u \not\sim v$.
`$u \GTSnegatedDirectedAdjacencyDown/ v$`
`or $u \GTSnegDirAdjDown/ v$`
`or $u \GTSnDAD/ v$`
 will yield $u \not\sim v$.

`\GTSnegatedDirectedAdjacencyDownRelation, \GTSnegDirAdjDownRel, \GTSnDADR`
 This macro will draw a negated directed adjacency downward symbol with relation spacing in math mode.

`$u\GTSnegatedDirectedAdjacencyDownRelation/v$`
`or $u\GTSnegDirAdjDownRel/v$`
`or $u\GTSnDADR/v$`
 will yield $u \not\sim v$.

2.2.3 Standard incidence macros

`\GTS@i` This macro will draw any of the incidence symbols if the correct arguments are given. It is not expected to be used directly. See the macros derived from it and `\GTS@j: \GTSxincidence, \GTSxinc, and \GTSxi`. The operand on the left of the symbol should be considered the vertex to which the edge/the operand on the right of the symbol is incident.

Arguments:

`{\langle mainColor \rangle}` If non-empty, this color will be used as main color.
`{\langle secondColor \rangle}` If non-empty, this color will be used as second color.
`{\langle drawSlash \rangle}` Non-empty implies that a negation will be drawn.
`{\langle drawUpArrow \rangle}` Non-empty implies that an up-arrow will be drawn.
`{\langle drawDownArrow \rangle}` Non-empty implies that a down-arrow will be drawn.

`\GTS@j` This macro builds on top of `\GTS@i` to handle mathematical relation spacing if sixth argument is not empty. It is not expected to be used directly. See the macros derived from it and `\GTS@i: \GTSxincidence, \GTSxinc, and \GTSxi`.

Arguments:

`{\langle mainColor \rangle}` If non-empty, this color will be used as main color.
`{\langle secondColor \rangle}` If non-empty, this color will be used as second color.
`{\langle drawSlash \rangle}` Non-empty implies that a negation will be drawn.
`{\langle drawUpArrow \rangle}` Non-empty implies that an up-arrow will be drawn.
`{\langle drawDownArrow \rangle}` Non-empty implies that a down-arrow will be drawn.
`{\langle relation \rangle}` Non-empty implies that relation spacing will be added.

`\GTSxincidence, \GTSxinc, \GTSxi` Versatile macros for incidence that can be given options.

Argument:

`[\langle optionsList \rangle]` Sets the following options if not empty:
`mainColor=color1 or mainC=color1 or mColor=color1 or mC=color1,`
`secondColor=color2 or secondC=color2 or sColor=color2 or sC=color2,`
`monochrome or mono or mon or m (equivalent to mC=black,sC=black),`
`negated or not or n,`
`in or i,`
`out or o,`
`relation or rel or r.`

`\GTSincidence, \GTSinc, \GTSi` This macro will draw an incidence symbol. The operand on the left of the symbol should be considered the vertex to which the edge/the operand on the right of the symbol is incident.

`A.\GTSincidence/A.`
`or A.\GTSinc/A.`

or $A.\backslash\text{GTSi}/A.$
will yield $A.\downarrow A.$
 $v \backslash\text{GTSincidence}/ e$
or $v \backslash\text{GTSinc}/ e$
or $v \backslash\text{GTSi}/ e$
will yield $v \downarrow e.$
 $\$v \backslash\text{GTSincidence}/ e\$$
or $\$v \backslash\text{GTSinc}/ e\$$
or $\$v \backslash\text{GTSi}/ e\$$
will yield $v \downarrow e.$

$\backslash\text{GTSincidenceRelation}$, $\backslash\text{GTSincRel}$, $\backslash\text{GTSiR}$ This macro will draw an incidence symbol with relation spacing in math mode.
 $\$v\backslash\text{GTSincidenceRelation}/e\$$
or $\$v\backslash\text{GTSincRel}/e\$$
or $\$v\backslash\text{GTSiR}/e\$$
will yield $v \downarrow e.$

$\backslash\text{GTSnegatedIncidence}$, $\backslash\text{GTSnegInc}$, $\backslash\text{GTSnI}$ This macro will draw a negated incidence symbol.
 $A.\backslash\text{GTSnegatedIncidence}/A.$
or $A.\backslash\text{GTSnegInc}/A.$
or $A.\backslash\text{GTSnI}/A.$
will yield $A.\not\downarrow A.$
 $v \backslash\text{GTSnegatedIncidence}/ e$
or $v \backslash\text{GTSnegInc}/ e$
or $v \backslash\text{GTSnI}/ e$
will yield $v \not\downarrow e.$
 $\$v \backslash\text{GTSnegatedIncidence}/ e\$$
or $\$v \backslash\text{GTSnegInc}/ e\$$
or $\$v \backslash\text{GTSnI}/ e\$$
will yield $v \not\downarrow e.$

$\backslash\text{GTSnegatedIncidenceRelation}$, $\backslash\text{GTSnegIncRel}$, $\backslash\text{GTSnIR}$ This macro will draw a negated incidence symbol with relation spacing in math mode.
 $\$v\backslash\text{GTSnegatedIncidenceRelation}/e\$$
or $\$v\backslash\text{GTSnegIncRel}/e\$$
or $\$v\backslash\text{GTSnIR}/e\$$
will yield $v \not\downarrow e.$

$\backslash\text{GTSoutIncidence}$, $\backslash\text{GTSoutInc}$, $\backslash\text{GTSOI}$ This macro will draw a directed incidence upward (out(ward) incidence) symbol. The operand on the left of the symbol should be considered the vertex to which the arc/the operand on the right of the symbol is incident.
 $A.\backslash\text{GTSoutIncidence}/A.$
or $A.\backslash\text{GTSoutInc}/A.$
or $A.\backslash\text{GTSOI}/A.$
will yield $A.\uparrow A.$
 $v \backslash\text{GTSoutIncidence}/ e$
or $v \backslash\text{GTSoutInc}/ e$
or $v \backslash\text{GTSOI}/ e$
will yield $v \uparrow e.$
 $\$v \backslash\text{GTSoutIncidence}/ e\$$
or $\$v \backslash\text{GTSoutInc}/ e\$$
or $\$v \backslash\text{GTSOI}/ e\$$
will yield $v \uparrow e.$

$\backslash\text{GTSoutIncidenceRelation}$, $\backslash\text{GTSoutIncRel}$, $\backslash\text{GTSOIR}$ This macro will draw a directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.
 $\$v\backslash\text{GTSoutIncidenceRelation}/e\$$
or $\$v\backslash\text{GTSoutIncRel}/e\$$

or $\$v\backslash\text{GTS}\text{OIR}/e\$$
will yield $v \nrightarrow e$.

$\backslash\text{GTSnegatedOutIncidence}$, $\backslash\text{GTSnegOutInc}$, $\backslash\text{GTSnOI}$ This macro will draw a negated directed incidence upward (out(ward) incidence) symbol.

$A.\backslash\text{GTSnegatedOutIncidence}/A.$
or $A.\backslash\text{GTSnegOutInc}/A.$
or $A.\backslash\text{GTSnOI}/A.$
will yield $A.\nrightarrow A.$
 $v \backslash\text{GTSnegatedOutIncidence}/ e$
or $v \backslash\text{GTSnegOutInc}/ e$
or $v \backslash\text{GTSnOI}/ e$
will yield $v \nrightarrow e$.
 $\$v \backslash\text{GTSnegatedOutIncidence}/ e\$$
or $\$v \backslash\text{GTSnegOutInc}/ e\$$
or $\$v \backslash\text{GTSnOI}/ e\$$
will yield $v \nrightarrow e$.

$\backslash\text{GTSnegatedOutIncidenceRelation}$, $\backslash\text{GTSnegOutIncRel}$, $\backslash\text{GTSnOIR}$ This macro will draw a negated directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

$\$v\backslash\text{GTSnegatedOutIncidenceRelation}/e\$$
or $\$v\backslash\text{GTSnegOutIncRel}/e\$$
or $\$v\backslash\text{GTSnOIR}/e\$$
will yield $v \nrightarrow e$.

$\backslash\text{GTSinIncidence}$, $\backslash\text{GTSinInc}$, $\backslash\text{GTSiI}$ This macro will draw a directed incidence downward (in(ward) incidence) symbol. The operand on the left of the symbol should be considered the vertex to which the arc/the operand on the right of the symbol is incident.

$A.\backslash\text{GTSinIncidence}/A.$
or $A.\backslash\text{GTSinInc}/A.$
or $A.\backslash\text{GTSiI}/A.$
will yield $A.\rightarrow A.$
 $v \backslash\text{GTSinIncidence}/ e$
or $v \backslash\text{GTSinInc}/ e$
or $v \backslash\text{GTSiI}/ e$
will yield $v \rightarrow e$.
 $\$v \backslash\text{GTSinIncidence}/ e\$$
or $\$v \backslash\text{GTSinInc}/ e\$$
or $\$v \backslash\text{GTSiI}/ e\$$
will yield $v \rightarrow e$.

$\backslash\text{GTSinIncidenceRelation}$, $\backslash\text{GTSinIncRel}$, $\backslash\text{GTSiIR}$ This macro will draw a directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.

$\$v\backslash\text{GTSinIncidenceRelation}/e\$$
or $\$v\backslash\text{GTSinIncRel}/e\$$
or $\$v\backslash\text{GTSiIR}/e\$$
will yield $v \rightarrow e$.

$\backslash\text{GTSnegatedInIncidence}$, $\backslash\text{GTSnegInInc}$, $\backslash\text{GTSnII}$ This macro will draw a negated directed incidence downward (in(ward) incidence) symbol.

$A.\backslash\text{GTSnegatedInIncidence}/A.$
or $A.\backslash\text{GTSnegInInc}/A.$
or $A.\backslash\text{GTSnII}/A.$
will yield $A.\nrightarrow A.$
 $v \backslash\text{GTSnegatedInIncidence}/ e$
or $v \backslash\text{GTSnegInInc}/ e$
or $v \backslash\text{GTSnII}/ e$
will yield $v \nrightarrow e$.
 $\$v \backslash\text{GTSnegatedInIncidence}/ e\$$

or $\$v \backslash\text{GTSnegInInc}/ e\$$
or $\$v \backslash\text{GTSnII}/ e\$$
will yield $v \not\bowtie e$.

$\backslash\text{GTSnegatedInIncidenceRelation}$, $\backslash\text{GTSnegInIncRel}$, $\backslash\text{GTSnIIR}$ This macro will draw a negated directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.
 $\$v\backslash\text{GTSnegatedInIncidenceRelation}/e\$$
or $\$v\backslash\text{GTSnegInIncRel}/e\$$
or $\$v\backslash\text{GTSnIIR}/e\$$
will yield $v \not\bowtie e$.

2.2.4 Monochrome adjacency macros

$\backslash\text{GTSadjacencyMonochrome}$, $\backslash\text{GTSadjMono}$, $\backslash\text{GTSadjMon}$, $\backslash\text{GTSaM}$ This macro will draw a monochrome adjacency symbol.

$A.\backslash\text{GTSadjacencyMonochrome}/A.$
or $A.\backslash\text{GTSadjMono}/A.$
or $A.\backslash\text{GTSadjMon}/A.$
or $A.\backslash\text{GTSaM}/A.$
will yield $A.\circ A.$
 $u \backslash\text{GTSadjacencyMonochrome}/ v$
or $u \backslash\text{GTSadjMono}/ v$
or $u \backslash\text{GTSadjMon}/ v$
or $u \backslash\text{GTSaM}/ v$
will yield $u \circ v$.
 $\$u \backslash\text{GTSadjacencyMonochrome}/ v\$$
or $\$u \backslash\text{GTSadjMono}/ v\$$
or $\$u \backslash\text{GTSadjMon}/ v\$$
or $\$u \backslash\text{GTSaM}/ v\$$
will yield $u \circ v$.

$\backslash\text{GTSadjacencyMonochromeRelation}$, $\backslash\text{GTSadjMonoRel}$, $\backslash\text{GTSadjMonRel}$, $\backslash\text{GTSaMR}$ This macro will draw a monochrome adjacency symbol with relation spacing in math mode.

$\$u\backslash\text{GTSadjacencyMonochromeRelation}/v\$$
or $\$u\backslash\text{GTSadjMonoRel}/v\$$
or $\$u\backslash\text{GTSadjMonRel}/v\$$
or $\$u\backslash\text{GTSaMR}/v\$$
will yield $u \circ v$.

$\backslash\text{GTSunadjacencyMonochrome}$, $\backslash\text{GTSunadjMono}$, $\backslash\text{GTSunadjMon}$, $\backslash\text{GTSuM}$ This macro will draw a monochrome unadjacency symbol.

$A.\backslash\text{GTSunadjacencyMonochrome}/A.$
or $A.\backslash\text{GTSunadjMono}/A.$
or $A.\backslash\text{GTSunadjMon}/A.$
or $A.\backslash\text{GTSuM}/A.$
will yield $A.\circ A.$
 $u \backslash\text{GTSunadjacencyMonochrome}/ v$
or $u \backslash\text{GTSunadjMono}/ v$
or $u \backslash\text{GTSunadjMon}/ v$
or $u \backslash\text{GTSuM}/ v$
will yield $u \circ v$.
 $\$u \backslash\text{GTSunadjacencyMonochrome}/ v\$$
or $\$u \backslash\text{GTSunadjMono}/ v\$$
or $\$u \backslash\text{GTSunadjMon}/ v\$$
or $\$u \backslash\text{GTSuM}/ v\$$
will yield $u \circ v$.

$\backslash\text{GTSunadjacencyMonochromeRelation}$, $\backslash\text{GTSunadjMonoRel}$, $\backslash\text{GTSunadjMonRel}$, $\backslash\text{GTSuMR}$ This macro will draw a monochrome unadjacency symbol with relation spacing in math mode.
 $\$u\backslash\text{GTSunadjacencyMonochromeRelation}/v\$$

or $\$u\backslash\text{GTSunadjMonoRel}/v\$$
or $\$u\backslash\text{GTSunadjMonRel}/v\$$
or $\$u\backslash\text{GTSuMR}/v\$$
will yield $u \overset{\circ}{\circ} v$.

$\backslash\text{GTSdirectedAdjacencyUpMonochrome}$, $\backslash\text{GTSdirAdjUpMono}$, $\backslash\text{GTSdirAdjUpMon}$, $\backslash\text{GTSdAUM}$ This macro will draw a monochrome directed adjacency upward symbol. The operand on the left of the symbol should be considered the source of the arc; the operand on the right of the symbol should be considered the target of the arc.
 $\text{A}.\backslash\text{GTSdirectedAdjacencyUpMonochrome}/\text{A}$.
or **$\text{A}.\backslash\text{GTSdirAdjUpMono}/\text{A}$.**
or **$\text{A}.\backslash\text{GTSdirAdjUpMon}/\text{A}$.**
or **$\text{A}.\backslash\text{GTSdAUM}/\text{A}$.**
will yield $\text{A}.\overset{\circ}{\circ}\text{A}$.
 $u \backslash\text{GTSdirectedAdjacencyUpMonochrome}/ v$
or **$u \backslash\text{GTSdirAdjUpMono}/ v$**
or **$u \backslash\text{GTSdirAdjUpMon}/ v$**
or **$u \backslash\text{GTSdAUM}/ v$**
will yield $u \overset{\circ}{\circ} v$.
 $\$u \backslash\text{GTSdirectedAdjacencyUpMonochrome}/ v\$$
or **$\$u \backslash\text{GTSdirAdjUpMono}/ v\$$**
or **$\$u \backslash\text{GTSdirAdjUpMon}/ v\$$**
or **$\$u \backslash\text{GTSdAUM}/ v\$$**
will yield $u \overset{\circ}{\circ} v$.

$\backslash\text{GTSdirectedAdjacencyUpMonochromeRelation}$, $\backslash\text{GTSdirAdjUpMonoRel}$, $\backslash\text{GTSdirAdjUpMonRel}$, $\backslash\text{GTSdAUMR}$ This macro will draw a monochrome directed adjacency upward symbol with relation spacing in math mode.
 $\$u\backslash\text{GTSdirectedAdjacencyUpMonochromeRelation}/v\$$
or **$\$u\backslash\text{GTSdirAdjUpMonoRel}/v\$$**
or **$\$u\backslash\text{GTSdirAdjUpMonRel}/v\$$**
or **$\$u\backslash\text{GTSdAUMR}/v\$$**
will yield $u \overset{\circ}{\circ} v$.

$\backslash\text{GTSnegatedDirectedAdjacencyUpMonochrome}$, $\backslash\text{GTSnegDirAdjUpMono}$, $\backslash\text{GTSnegDirAdjUpMon}$, $\backslash\text{GTSnDAUM}$ This macro will draw a monochrome negated directed adjacency upward symbol.
 $\text{A}.\backslash\text{GTSnegatedDirectedAdjacencyUpMonochrome}/\text{A}$.
or **$\text{A}.\backslash\text{GTSnegDirAdjUpMono}/\text{A}$.**
or **$\text{A}.\backslash\text{GTSnegDirAdjUpMon}/\text{A}$.**
or **$\text{A}.\backslash\text{GTSnDAUM}/\text{A}$.**
will yield $\text{A}.\overset{\circ}{\circ}\text{A}$.
 $u \backslash\text{GTSnegatedDirectedAdjacencyUpMonochrome}/ v$
or **$u \backslash\text{GTSnegDirAdjUpMono}/ v$**
or **$u \backslash\text{GTSnegDirAdjUpMon}/ v$**
or **$u \backslash\text{GTSnDAUM}/ v$**
will yield $u \overset{\circ}{\circ} v$.
 $\$u \backslash\text{GTSnegatedDirectedAdjacencyUpMonochrome}/ v\$$
or **$\$u \backslash\text{GTSnegDirAdjUpMono}/ v\$$**
or **$\$u \backslash\text{GTSnegDirAdjUpMon}/ v\$$**
or **$\$u \backslash\text{GTSnDAUM}/ v\$$**
will yield $u \overset{\circ}{\circ} v$.

$\backslash\text{GTSnegatedDirectedAdjacencyUpMonochromeRelation}$, $\backslash\text{GTSnegDirAdjUpMonoRel}$, $\backslash\text{GTSnegDirAdjUpMonRel}$, $\backslash\text{GTSnDAUMR}$ This macro will draw a monochrome negated directed adjacency upward symbol with relation spacing in math mode.
 $\$u\backslash\text{GTSnegatedDirectedAdjacencyUpMonochromeRelation}/v\$$
or **$\$u\backslash\text{GTSnegDirAdjUpMonoRel}/v\$$**
or **$\$u\backslash\text{GTSnegDirAdjUpMonRel}/v\$$**

or $\$u\backslash\text{GTSnDAUMR}/v\$$
will yield $u \stackrel{\circ}{\circ} v$.

$\backslash\text{GTSdirectedAdjacencyDownMonochrome}$, $\backslash\text{GTSdirAdjDownMono}$, $\backslash\text{GTSdirAdjDownMon}$, $\backslash\text{GTSdADM}$ This macro will draw a monochrome directed adjacency downward symbol. The operand on the left of the symbol should be considered the target of the arc; the operand on the right of the symbol should be considered the source of the arc.

$A.\backslash\text{GTSdirectedAdjacencyDownMonochrome}/A.$

or $A.\backslash\text{GTSdirAdjDownMono}/A.$

or $A.\backslash\text{GTSdirAdjDownMon}/A.$

or $A.\backslash\text{GTSdADM}/A.$

will yield $A.\stackrel{\circ}{\circ}A.$

$u \backslash\text{GTSdirectedAdjacencyDownMonochrome}/ v$

or $u \backslash\text{GTSdirAdjDownMono}/ v$

or $u \backslash\text{GTSdirAdjDownMon}/ v$

or $u \backslash\text{GTSdADM}/ v$

will yield $u \stackrel{\circ}{\circ} v$.

$\$u \backslash\text{GTSdirectedAdjacencyDownMonochrome}/ v\$$

or $\$u \backslash\text{GTSdirAdjDownMono}/ v\$$

or $\$u \backslash\text{GTSdirAdjDownMon}/ v\$$

or $\$u \backslash\text{GTSdADM}/ v\$$

will yield $u \stackrel{\circ}{\circ} v$.

$\backslash\text{GTSdirectedAdjacencyDownMonochromeRelation}$, $\backslash\text{GTSdirAdjDownMonoRel}$, $\backslash\text{GTSdirAdjDownMonRel}$, $\backslash\text{GTSdADMR}$ This macro will draw a monochrome directed adjacency downward symbol with relation spacing in math mode.

$\$u\backslash\text{GTSdirectedAdjacencyDownMonochromeRelation}/v\$$

or $\$u\backslash\text{GTSdirAdjDownMonoRel}/v\$$

or $\$u\backslash\text{GTSdirAdjDownMonRel}/v\$$

or $\$u\backslash\text{GTSdADMR}/v\$$

will yield $u \stackrel{\circ}{\circ} v$.

$\backslash\text{GTSnegatedDirectedAdjacencyDownMonochrome}$, $\backslash\text{GTSnegDirAdjDownMono}$, $\backslash\text{GTSnegDirAdjDownMon}$, $\backslash\text{GTSnDADM}$ This macro will draw a monochrome negated directed adjacency downward symbol.

$A.\backslash\text{GTSnegatedDirectedAdjacencyDownMonochrome}/A.$

or $A.\backslash\text{GTSnegDirAdjDownMono}/A.$

or $A.\backslash\text{GTSnegDirAdjDownMon}/A.$

or $A.\backslash\text{GTSnDADM}/A.$

will yield $A.\stackrel{\circ}{\circ}A.$

$u \backslash\text{GTSnegatedDirectedAdjacencyDownMonochrome}/ v$

or $u \backslash\text{GTSnegDirAdjDownMono}/ v$

or $u \backslash\text{GTSnegDirAdjDownMon}/ v$

or $u \backslash\text{GTSnDADM}/ v$

will yield $u \stackrel{\circ}{\circ} v$.

$\$u \backslash\text{GTSnegatedDirectedAdjacencyDownMonochrome}/ v\$$

or $\$u \backslash\text{GTSnegDirAdjDownMono}/ v\$$

or $\$u \backslash\text{GTSnegDirAdjDownMon}/ v\$$

or $\$u \backslash\text{GTSnDADM}/ v\$$

will yield $u \stackrel{\circ}{\circ} v$.

$\backslash\text{GTSnegatedDirectedAdjacencyDownMonochromeRelation}$, $\backslash\text{GTSnegDirAdjDownMonoRel}$, $\backslash\text{GTSnegDirAdjDownMonRel}$, $\backslash\text{GTSnDADMR}$ This macro will draw a monochrome negated directed adjacency downward symbol with relation spacing in math mode.

$\$u\backslash\text{GTSnegatedDirectedAdjacencyDownMonochromeRelation}/v\$$

or $\$u\backslash\text{GTSnegDirAdjDownMonoRel}/v\$$

or $\$u\backslash\text{GTSnegDirAdjDownMonRel}/v\$$

or $\$u\backslash\text{GTSnDADMR}/v\$$

will yield $u \stackrel{\circ}{\circ} v$.

2.2.5 Monochrome incidence macros

\GTSincidenceMonochrome, \GTSincMono, \GTSincMon, \GTSiM This macro will draw a monochrome incidence symbol. The operand on the left of the symbol should be considered the vertex to which the edge/the operand on the right of the symbol is incident.

A.\GTSincidenceMonochrome/A.

or **A.\GTSincMono/A.**

or **A.\GTSincMon/A.**

or **A.\GTSiM/A.**

will yield $A \downarrow A$.

v \GTSincidenceMonochrome/ e

or **v \GTSincMono/ e**

or **v \GTSincMon/ e**

or **v \GTSiM/ e**

will yield $v \downarrow e$.

\$v \GTSincidenceMonochrome/ e\$

or **\$v \GTSincMono/ e\$**

or **\$v \GTSincMon/ e\$**

or **\$v \GTSiM/ e\$**

will yield $v \downarrow e$.

\GTSincidenceMonochromeRelation, \GTSincMonoRel, \GTSincMonRel, \GTSiMR

This macro will draw a monochrome incidence symbol with relation spacing in math mode.

\$v\GTSincidenceMonochromeRelation/e\$

or **\$v\GTSincMonoRel/e\$**

or **\$v\GTSincMonRel/e\$**

or **\$v\GTSiMR/e\$**

will yield $v \downarrow e$.

\GTSnegatedIncidenceMonochrome, \GTSnegIncMono, \GTSnegIncMon, \GTSnIM

This macro will draw a monochrome negated incidence symbol.

A.\GTSnegatedIncidenceMonochrome/A.

or **A.\GTSnegIncMono/A.**

or **A.\GTSnegIncMon/A.**

or **A.\GTSnIM/A.**

will yield $A \not\downarrow A$.

v \GTSnegatedIncidenceMonochrome/ e

or **v \GTSnegIncMono/ e**

or **v \GTSnegIncMon/ e**

or **v \GTSnIM/ e**

will yield $v \not\downarrow e$.

\$v \GTSnegatedIncidenceMonochrome/ e\$

or **\$v \GTSnegIncMono/ e\$**

or **\$v \GTSnegIncMon/ e\$**

or **\$v \GTSnIM/ e\$**

will yield $v \not\downarrow e$.

\GTSnegatedIncidenceMonochromeRelation, \GTSnegIncMonoRel, \GTSnegIncMon-

Rel, \GTSnIMR This macro will draw a monochrome negated incidence symbol with relation spacing in math mode.

\$v\GTSnegatedIncidenceMonochromeRelation/e\$

or **\$v\GTSnegIncMonoRel/e\$**

or **\$v\GTSnegIncMonRel/e\$**

or **\$v\GTSnIMR/e\$**

will yield $v \not\downarrow e$.

\GTSoutIncidenceMonochrome, \GTSoutIncMono, \GTSoutIncMon, \GTSoIM This

macro will draw a monochrome directed incidence upward (out(ward) incidence) symbol. The operand on the left of the symbol should be considered the vertex to which the arc/the operand on the right of the symbol is incident.

A.\GTSoutIncidenceMonochrome/A.

`or A.\GTSoutIncMono/A.`
`or A.\GTSoutIncMon/A.`
`or A.\GTSOIM/A.`
 will yield $A \downarrow A$.
`v \GTSoutIncidenceMonochrome/ e`
`or v \GTSoutIncMono/ e`
`or v \GTSoutIncMon/ e`
`or v \GTSOIM/ e`
 will yield $v \downarrow e$.
`$v \GTSoutIncidenceMonochrome/ e$`
`or $v \GTSoutIncMono/ e$`
`or $v \GTSoutIncMon/ e$`
`or $v \GTSOIM/ e$`
 will yield $v \downarrow e$.

`\GTSoutIncidenceMonochromeRelation, \GTSoutIncMonoRel, \GTSoutIncMonRel, \GTSOIMR` This macro will draw a monochrome directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.
`$v \GTSoutIncidenceMonochromeRelation/e$`
`or $v \GTSoutIncMonoRel/e$`
`or $v \GTSoutIncMonRel/e$`
`or $v \GTSOIMR/e$`
 will yield $v \downarrow e$.

`\GTSnegatedOutIncidenceMonochrome, \GTSnegOutIncMono, \GTSnegOutIncMon, \GTSnOIM` This macro will draw a monochrome negated directed incidence upward (out(ward) incidence) symbol.
`A.\GTSnegatedOutIncidenceMonochrome/A.`
`or A.\GTSnegOutIncMono/A.`
`or A.\GTSnegOutIncMon/A.`
`or A.\GTSnOIM/A.`
 will yield $A \uparrow A$.
`v \GTSnegatedOutIncidenceMonochrome/ e`
`or v \GTSnegOutIncMono/ e`
`or v \GTSnegOutIncMon/ e`
`or v \GTSnOIM/ e`
 will yield $v \uparrow e$.
`$v \GTSnegatedOutIncidenceMonochrome/ e$`
`or $v \GTSnegOutIncMono/ e$`
`or $v \GTSnegOutIncMon/ e$`
`or $v \GTSnOIM/ e$`
 will yield $v \uparrow e$.

`\GTSnegatedOutIncidenceMonochromeRelation, \GTSnegOutIncMonoRel, \GTSnegOutIncMonRel, \GTSnOIMR` This macro will draw a monochrome negated directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.
`$v \GTSnegatedOutIncidenceMonochromeRelation/e$`
`or $v \GTSnegOutIncMonoRel/e$`
`or $v \GTSnegOutIncMonRel/e$`
`or $v \GTSnOIMR/e$`
 will yield $v \uparrow e$.

`\GTSinIncidenceMonochrome, \GTSinIncMono, \GTSinIncMon, \GTSiIM` This macro will draw a monochrome directed incidence downward (in(ward) incidence) symbol. The operand on the left of the symbol should be considered the vertex to which the arc/the operand on the right of the symbol is incident.
`A.\GTSinIncidenceMonochrome/A.`
`or A.\GTSinIncMono/A.`
`or A.\GTSinIncMon/A.`
`or A.\GTSiIM/A.`

will yield $A \Downarrow A$.
 $v \backslash \text{GTSinIncidenceMonochrome} / e$
or $v \backslash \text{GTSinIncMono} / e$
or $v \backslash \text{GTSinIncMon} / e$
or $v \backslash \text{GTSiIM} / e$
will yield $v \Downarrow e$.
 $\$v \backslash \text{GTSinIncidenceMonochrome} / e\$$
or $\$v \backslash \text{GTSinIncMono} / e\$$
or $\$v \backslash \text{GTSinIncMon} / e\$$
or $\$v \backslash \text{GTSiIM} / e\$$
will yield $v \Downarrow e$.

$\backslash \text{GTSinIncidenceMonochromeRelation}$, $\backslash \text{GTSinIncMonoRel}$, $\backslash \text{GTSinIncMonRel}$, $\backslash \text{GTSiIMR}$ This macro will draw a monochrome directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.
 $\$v \backslash \text{GTSinIncidenceMonochromeRelation} / e\$$
or $\$v \backslash \text{GTSinIncMonoRel} / e\$$
or $\$v \backslash \text{GTSinIncMonRel} / e\$$
or $\$v \backslash \text{GTSiIMR} / e\$$
will yield $v \Downarrow e$.

$\backslash \text{GTSnegatedInIncidenceMonochrome}$, $\backslash \text{GTSnegInIncMono}$, $\backslash \text{GTSnegInIncMon}$, $\backslash \text{GTSniIM}$ This macro will draw a monochrome negated directed incidence downward (in(ward) incidence) symbol.
 $A. \backslash \text{GTSnegatedInIncidenceMonochrome} / A.$
or $A. \backslash \text{GTSnegInIncMono} / A.$
or $A. \backslash \text{GTSnegInIncMon} / A.$
or $A. \backslash \text{GTSniIM} / A.$
will yield $A \Downarrow A$.
 $v \backslash \text{GTSnegatedInIncidenceMonochrome} / e$
or $v \backslash \text{GTSnegInIncMono} / e$
or $v \backslash \text{GTSnegInIncMon} / e$
or $v \backslash \text{GTSniIM} / e$
will yield $v \Downarrow e$.
 $\$v \backslash \text{GTSnegatedInIncidenceMonochrome} / e\$$
or $\$v \backslash \text{GTSnegInIncMono} / e\$$
or $\$v \backslash \text{GTSnegInIncMon} / e\$$
or $\$v \backslash \text{GTSniIM} / e\$$
will yield $v \Downarrow e$.

$\backslash \text{GTSnegatedInIncidenceMonochromeRelation}$, $\backslash \text{GTSnegInIncMonoRel}$, $\backslash \text{GTSnegInIncMonRel}$, $\backslash \text{GTSniIMR}$ This macro will draw a monochrome negated directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.
 $\$v \backslash \text{GTSnegatedInIncidenceMonochromeRelation} / e\$$
or $\$v \backslash \text{GTSnegInIncMonoRel} / e\$$
or $\$v \backslash \text{GTSnegInIncMonRel} / e\$$
or $\$v \backslash \text{GTSniIMR} / e\$$
will yield $v \Downarrow e$.

2.2.6 Meta-logic macros

$\backslash \text{GTSMetaNot}$, $\backslash \text{GTSMN}$ This macro will draw a meta-not or relation-not symbol.
 $A. \backslash \text{GTSMetaNot} / A.$
or $A. \backslash \text{GTSMN} / A.$
will yield $A \Downarrow A$.
 $u \backslash \text{GTSMetaNot} / \backslash \text{GTSdAU} / v$
or $u \backslash \text{GTSMN} / \backslash \text{GTSdAU} / v$
will yield $u \Downarrow v$.
 $\$u \backslash \text{GTSMetaNot} / \backslash \text{GTSdAU} / v\$$
or $\$u \backslash \text{GTSMN} / \backslash \text{GTSdAU} / v\$$
will yield $u \Downarrow v$.

\GTSMetaAnd, \GTSMa This macro will draw a meta-and or relations-and symbol. This is your duty to check that all relations have same arity. It should be easy as long as you remain in the realm of graphs/2-structures/binary structures. We didn't use Tarski's notation, since square cup has taken the preemptive meaning of disjoint union. Similarly, doublewedge or other wedge symbols have taken various meanings, whilst we want an unambiguous symbol.

Look at the discussion after all logical symbols for less trivial uses and recommendations.

A.\GTSMetaAnd/A.

or A.\GTSMa/A.

will yield $A.\bigwedge A$.

u \GTSDAD/\GTSMetaAnd/\GTSdAU/ v

or u \GTSDAD/\GTSMa/\GTSdAU/ v

will yield $u \bigwedge^m v$.

\$u \GTSDAD/ \GTSMetaAnd/ \GTSdAU/ v\$

or \$u \GTSDAD/ \GTSMa/ \GTSdAU/ v\$

will yield $u \bigwedge^m v$.

\GTSMetaAndRelation, \GTSMetaAndRel, \GTSMAR This macro will draw a meta-and symbol with relation spacing in math mode.

\$u \GTSDAD/\GTSMetaAndRelation/\GTSdAU/ v\$

or \$u \GTSDAD/\GTSMetaAndRel/\GTSdAU/ v\$

or \$u \GTSDAD/\GTSMAR/\GTSdAU/ v\$

will yield $u \bigwedge^m v$.

\GTSMetaOr, \GTSMo This macro will draw a meta-or or relations-or symbol. This is your duty to check that all relations have same arity. It should be easy as long as you remain in the realm of graphs/2-structures/binary structures. We didn't use Tarski's notation, since square cup has taken the preemptive meaning of disjoint union. Similarly, doublewedge or other wedge symbols have taken various meanings, whilst we want an unambiguous symbol.

Look at the discussion after all logical symbols for less trivial uses and recommendations.

A.\GTSMetaOr/A.

or A.\GTSMo/A.

will yield $A.\bigvee A$.

u \GTSDAD/\GTSMetaOr/\GTSdAU/ v

or u \GTSDAD/\GTSMo/\GTSdAU/ v

will yield $u \bigvee^m v$.

\$u \GTSDAD/ \GTSMetaOr/ \GTSdAU/ v\$

or \$u \GTSDAD/ \GTSMo/ \GTSdAU/ v\$

will yield $u \bigvee^m v$.

\GTSMetaOrRelation, \GTSMetaOrRel, \GTSMOR This macro will draw a meta-or symbol with relation spacing in math mode.

\$u \GTSDAD/\GTSMetaOrRelation/\GTSdAU/ v\$

or \$u \GTSDAD/\GTSMetaOrRel/\GTSdAU/ v\$

or \$u \GTSDAD/\GTSMOR/\GTSdAU/ v\$

will yield $u \bigvee^m v$.

\GTSxmetallogic, \GTSxml Versatile macros for meta-logic symbols that can be given options.

Argument:

[*<optionsList>*] Sets the following options if not empty:

not or n,

and or a,

or or o,

relation or rel or r.

Of course first three options are incompatible, and the fourth is compatible only with the second and third options.

\GTSx One macro to rule them all. Versatile macro for all symbols that can be given options, and a symbol type mandatory switch.

Argument:

[*optionsList*] Sets the following options if not empty:

- If $\{\langle symbolType \rangle\}$ below is a, see `\GTSxa`:
mainColor=color1 or mainC=color1 or mColor=color1 or mC=color1,
secondColor=color2 or secondC=color2 or sColor=color2 or sC=color2,
monochrome or mono or mon or m (equivalent to mC=black,sC=black),
negated or not or n,
up or u,
down or d,
relation or rel or r.
- If $\{\langle symbolType \rangle\}$ below is i, see `\GTSxi`:
mainColor=color1 or mainC=color1 or mColor=color1 or mC=color1,
secondColor=color2 or secondC=color2 or sColor=color2 or sC=color2,
monochrome or mono or mon or m (equivalent to mC=black,sC=black),
negated or not or n,
in or i,
out or o,
relation or rel or r.
- If $\{\langle symbolType \rangle\}$ below is m, see `\GTSxml`:
not or n,
and or a,
or or o,
relation or rel or r.

$\{\langle symbolType \rangle\}$ a mandatory switch; it can take value **a** for adjacency, **i** for incidence, **m** for meta-logic.

2.3 Good practices

As is customary in algebra and logic, the conjunction/multiplication can be replaced by concatenation, and has higher priority than disjunction. So the following formulas are equivalent; we recommend using the shortest one:

Tournament adjacency:

$$\forall u, v, u \text{ --- } \bigvee^m \text{ --- } v$$

is preferred over

$$\forall u, v, u \text{ } \begin{array}{c} \textcircled{\text{m}} \\ \text{ } \end{array} \wedge \begin{array}{c} \textcircled{\text{m}} \\ \text{ } \end{array} \vee \begin{array}{c} \textcircled{\text{m}} \\ \text{ } \end{array} \wedge \begin{array}{c} \textcircled{\text{m}} \\ \text{ } \end{array} v,$$
$$\text{or } \forall u, v, u \left(\bigotimes_{\wedge}^m \bigotimes \right) \bigvee \left(\bigotimes_{\wedge}^m \bigotimes \right) v,$$

or even $\forall u, v, ((u \overset{\circ}{\wedge} v) \wedge (u \overset{\circ}{\vee} v)) \vee ((u \overset{\circ}{\vee} v) \wedge (u \overset{\circ}{\wedge} v))$.

Note the use of macros without Relation suffix above, and adding a single `\mathrel{}` around the composition of all relations:

$$\backslash\mathrm{mathrel}\{\backslash\mathrm{GTSdAD}/\backslash\mathrm{GTSnDAU}/\backslash\mathrm{GTSmO}/\backslash\mathrm{GTSnDAD}/\backslash\mathrm{GTSdAU}/\}.$$

This is the spacing practice that we recommend, although for very long compositions, it may be quite unreadable, and then spacing everything with Relation could/should be preferred.

We also recommend using brackets when the composition reflects all of the adjacencies between two vertices:

Tournament adjacency:

$$\forall u, v, u \left[\begin{array}{c} \textcircled{\text{u}} \textcircled{\text{u}}^{\text{m}} \textcircled{\text{u}} \\ \textcircled{\text{u}} \textcircled{\text{u}} \textcircled{\text{u}} \end{array} \right] v.$$

Tournament adjacency with maybe some colored edge also, who knows?:

$$\forall u, v, u \text{ --- } \nabla^m \text{ --- } v.$$

Directed graph:

[illegible]

Oriented graph:

$$\forall u, v, u \left[\begin{array}{c} \textcircled{\bullet} \textcircled{\bullet} \overset{\text{m}}{\underset{\text{V}}{\downarrow}} \textcircled{\bullet} \textcircled{\bullet} \overset{\text{m}}{\underset{\text{V}}{\downarrow}} \textcircled{\bullet} \textcircled{\bullet} \\ \textcircled{\bullet} \end{array} \right] v.$$

Finally, we recommend prefix notation without “big” symbol for a sequence of consecutive ors or ands (with parentheses if needed):

$$\exists u, v, u \left[\bigvee_{\text{m}} \begin{array}{ccc} \text{red} & \text{green} & \text{blue} \end{array} \right] v.$$
$$\exists v, e, v \left[\overset{\text{m}}{\underset{\text{V}}{\text{V}}} \text{ (with red, green, blue nodes)} \right] e.$$

3 Implementation

```

1 \*package)
2 \RequirePackage{amsmath}
3 \RequirePackage{amssymb}
4 \RequirePackage{graphicx}
5 \RequirePackage{keyval}
6 \RequirePackage{fdsymbol}
7 \RequirePackage{lua-unicode-math}
8 \RequirePackage{xcolor}
9
10 \def\GTS@mainColor{black}
11 \def\GTS@secondColor{gray}
12 \def\GTS@mainColorBackup{black}
13 \def\GTS@secondColorBackup{gray}
14 \def\GTS@drawSlash{}
15 \def\GTS@drawUpArrow{}
16 \def\GTS@drawDownArrow{}
17

```

\GTS@newcommand This macro will enforce that the other macros are called with a trailing slash, avoiding problems with spaces after macro call.

Arguments:

{*<commandname>*} The name of the command to create.

{*<commandcode>*} The code of the command to create.

```

18 \ifdefinable{\GTS@newcommand}{\def\GTS@newcommand#1#2{%
19   \ifdefinable{#1}{\def#1/{#2}}
20 }}

```

\GTS@newprotectedcommand This macro will enforce that the other macros are called with a trailing slash, avoiding problems with spaces after macro call.

Arguments:

{*<commandname>*} The name of the command to create.

{*<commandcode>*} The code of the command to create.

```

21 \ifdefinable{\GTS@newprotectedcommand}{\def\GTS@newprotectedcommand#1#2{%
22   \ifdefinable{#1}{\protected\def#1/{#2}}
23 }}

```

\GTSsetMainColor This macro will set the main color used in GraphTheorySymbol. This color has initial value “black”.

Argument:

{*<color>*} The color that must be used by GraphTheorySymbol afterward.

```

24 \newcommand{\GTSsetMainColor}[1]{%
25 \edef\GTS@mainColorTemp{#1}%
26 \edef\GTS@mainColorBackup{\GTS@mainColor}%
27 \edef\GTS@mainColor{\GTS@mainColorTemp}%
28 }

```

\GTSsetSecondColor This macro will set the second color used in GraphTheorySymbol. This color has initial value “gray”.

Argument:

{*<color>*} The color that must be used by GraphTheorySymbol afterward.

```

29 \newcommand{\GTSsetSecondColor}[1]{%
30 \edef\GTS@secondColorTemp{#1}%
31 \edef\GTS@secondColorBackup{\GTS@secondColor}%
32 \edef\GTS@secondColor{\GTS@secondColorTemp}%
33 }

```

\GTS@a This macro will draw any adjacency symbol given the correct parameters. Its use is purely technical. See the macros derived from it and **\GTS@b**: **\GTSxadjacency**, **\GTSxadj**, and **\GTSxa**.

Arguments:

{*<mainColor>*} If non-empty, this color will be used as main color.

{*<secondColor>*} If non-empty, this color will be used as second color.

{*<drawSlash>*} Non-empty implies that a negation will be drawn.

{*<drawUpArrow>*} Non-empty implies that an up-arrow will be drawn.

{*<drawDownArrow>*} Non-empty implies that a down-arrow will be drawn.

```

34 \newcommand{\GTS@a}[5]{%
35 \if#1\empty\else%
36 \GTSsetMainColor{#1}%
37 \fi%
38 \if#2\empty\else%
39 \GTSsetSecondColor{#2}%
40 \fi%
41 \text{\ensuremath{%
42 \raisebox{-0.32ex}{\scalebox{1.5}[1.5]{%
43 %
44 \raisebox{0.7ex}{\scalebox{0.7}[0.7]{%
45 $\mathcolor{\GTS@secondColor}{\circ}$%
46 }}%
47 \hspace{-0.39ex}%
48 \raisebox{1.05ex}{\scalebox{0.1}[0.1]{%
49 $\mathcolor{\GTS@secondColor}{\bullet}$%
50 }}%
51 \hspace{-0.12ex}%
52 \raisebox{0.11ex}{\scalebox{0.1}[0.73]{%
53 $\mathcolor{\GTS@mainColor}{\smallblacksquare}$%
54 }}%
55 \hspace{-0.40ex}%
56 \raisebox{-0.3ex}{\scalebox{0.7}[0.7]{%
57 $\mathcolor{\GTS@secondColor}{\circ}$%
58 }}%
59 \hspace{-0.39ex}%
60 \raisebox{0.05ex}{\scalebox{0.1}[0.1]{%
61 $\mathcolor{\GTS@secondColor}{\bullet}$%
62 }}%
63 \hspace{0.27ex}%
if GTS@drawUpArrow empty else
64 \if#4\empty\else%
65 \hspace{-0.65ex}%
66 \raisebox{-0.18ex}{\scalebox{0.5}[0.5]{%
67 \textcolor{\GTS@mainColor}{\textasciicircum}%
68 }}%
69 \fi%
if GTS@drawDownArrow empty else
70 \if#5\empty\else%
71 \hspace{-0.65ex}%
72 \raisebox{1.37ex}{\scalebox{0.5}[-0.5]{%
73 \textcolor{\GTS@mainColor}{\textasciicircum}%
74 }}%
75 \fi%
if GTS@drawSlash empty else
76 \if#3\empty\else%
77 \hspace{-0.65ex}%
78 \raisebox{0.25ex}{\scalebox{0.6}[0.6]{%
79 \textcolor{black}{/}%
80 }}%
81 \fi%
82 %
83 }}%
84 }}%
85 \if#1\empty\else%
86 \GTSsetMainColor{\GTS@mainColorBackup}%
87 \fi%
88 \if#2\empty\else%
89 \GTSsetSecondColor{\GTS@secondColorBackup}%
90 \fi%
91 }

```

\GTS@b This macro will handle wrapping in mathematical relation spacing if needed. Its use is purely technical. See the macros derived from it and \GTS@a: \GTSxadjacency, \GTSxadj, and

`\GTSxa.`

Arguments:

`{\mainColor}` If non-empty, this color will be used as main color.
`{\secondColor}` If non-empty, this color will be used as second color.
`{\drawSlash}` Non-empty implies that a negation will be drawn.
`{\drawUpArrow}` Non-empty implies that an up-arrow will be drawn.
`{\drawDownArrow}` Non-empty implies that a down-arrow will be drawn.
`{\relation}` Non-empty implies that relation spacing will be added.

```
92 \newcommand{\GTS@b}[6]{%
93 \if#61%
94 \mathrel{\GTS@a{#1}{#2}{#3}{#4}{#5}}%
95 \else%
96 \GTS@a{#1}{#2}{#3}{#4}{#5}%
97 \fi%
98 }
```

`\GTSxadjacency`, `\GTSxadj`, `\GTSxa` Versatile macros for adjacency that can be given options.

Argument:

`[\optionsList]` Sets the following options if not empty:

`mainColor=color1` or `mainC=color1` or `mColor=color1` or `mC=color1`,
`secondColor=color2` or `secondC=color2` or `sColor=color2` or `sC=color2`,
`monochrome` or `mono` or `mon` or `m` (equivalent to `mC=black,sC=black`),
`negated` or `not` or `n`,
`up` or `u`,
`down` or `d`,
`relation` or `rel` or `r`.

```
99 \define@key{GTSxa}{mainColor}{\def\GTS@@mainColor{#1}}
100 \define@key{GTSxa}{mainC}{\def\GTS@@mainColor{#1}}
101 \define@key{GTSxa}{mColor}{\def\GTS@@mainColor{#1}}
102 \define@key{GTSxa}{mC}{\def\GTS@@mainColor{#1}}
103 \define@key{GTSxa}{secondColor}{\def\GTS@@secondColor{#1}}
104 \define@key{GTSxa}{secondC}{\def\GTS@@secondColor{#1}}
105 \define@key{GTSxa}{sColor}{\def\GTS@@secondColor{#1}}
106 \define@key{GTSxa}{sC}{\def\GTS@@secondColor{#1}}
107 \define@key{GTSxa}{monochrome}[1]%
108 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
109 \define@key{GTSxa}{mono}[1]%
110 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
111 \define@key{GTSxa}{mon}[1]%
112 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
113 \define@key{GTSxa}{m}[1]%
114 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
115 \define@key{GTSxa}{negated}[1]{\def\GTS@@drawSlash{1}}
116 \define@key{GTSxa}{not}[1]{\def\GTS@@drawSlash{1}}
117 \define@key{GTSxa}{n}[1]{\def\GTS@@drawSlash{1}}
118 \define@key{GTSxa}{up}[1]{\def\GTS@@drawUpArrow{1}}
119 \define@key{GTSxa}{u}[1]{\def\GTS@@drawUpArrow{1}}
120 \define@key{GTSxa}{down}[1]{\def\GTS@@drawDownArrow{1}}
121 \define@key{GTSxa}{d}[1]{\def\GTS@@drawDownArrow{1}}
122 \define@key{GTSxa}{relation}[1]{\def\GTS@@relation{1}}
123 \define@key{GTSxa}{rel}[1]{\def\GTS@@relation{1}}
124 \define@key{GTSxa}{r}[1]{\def\GTS@@relation{1}}
125
126 \newcommand{\GTSxa}[1][]{%
127 \def\GTS@@mainColor{}%
128 \def\GTS@@secondColor{}%
129 \def\GTS@@drawSlash{}%
130 \def\GTS@@drawUpArrow{}%
131 \def\GTS@@drawDownArrow{}%
132 \def\GTS@@relation{}%
133 \setkeys{GTSxa}{#1}%
134 \GTS@b{\GTS@@mainColor}{\GTS@@secondColor}{\GTS@@drawSlash}%
135 {\GTS@@drawUpArrow}{\GTS@@drawDownArrow}{\GTS@@relation}%
136 }
137
```

138 `\newcommand{\GTSxadj}[1][\GTSxa[#1]]`

139

140 `\newcommand{\GTSxadjacency}[1][\GTSxa[#1]]`

\GTSadjacency, \GTSadj, \GTSa This macro will draw an adjacency symbol.

141 `\GTS@newcommand{\GTSadjacency}{\GTS@a{}{}{}{}}{}`

142 `\GTS@newcommand{\GTSadj}{\GTS@a{}{}{}{}}{}`

143 `\GTS@newcommand{\GTSa}{\GTS@a{}{}{}{}}{}`

\GTSadjacencyRelation, \GTSadjRel, \GTSaR This macro will draw an adjacency symbol with relation spacing in math mode.

144 `\GTS@newcommand{\GTSadjacencyRelation}{\mathrel{\GTSa/}}`

145 `\GTS@newcommand{\GTSadjRel}{\mathrel{\GTSa/}}`

146 `\GTS@newcommand{\GTSaR}{\mathrel{\GTSa/}}`

\GTSunadjacency, \GTSunadj, \GTSu This macro will draw an unadjacency symbol.

147 `\GTS@newcommand{\GTSunadjacency}{\GTS@a{}{}{1}{}{}}`

148 `\GTS@newcommand{\GTSunadj}{\GTS@a{}{}{1}{}{}}`

149 `\GTS@newcommand{\GTSu}{\GTS@a{}{}{1}{}{}}`

\GTSunadjacencyRelation, \GTSunadjRel, \GTSuR This macro will draw an unadjacency symbol with relation spacing in math mode.

150 `\GTS@newcommand{\GTSunadjacencyRelation}{\mathrel{\GTSu/}}`

151 `\GTS@newcommand{\GTSunadjRel}{\mathrel{\GTSu/}}`

152 `\GTS@newcommand{\GTSuR}{\mathrel{\GTSu/}}`

\GTSdirectedAdjacencyUp, \GTSdirAdjUp, \GTSdAU This macro will draw a directed adjacency upward symbol. The operand on the left of the symbol should be considered the source of the arc; the operand on the right of the symbol should be considered the target of the arc.

153 `\GTS@newcommand{\GTSdirectedAdjacencyUp}{\GTS@a{}{}{1}{}{}}`

154 `\GTS@newcommand{\GTSdirAdjUp}{\GTS@a{}{}{1}{}{}}`

155 `\GTS@newcommand{\GTSdAU}{\GTS@a{}{}{1}{}{}}`

\GTSdirectedAdjacencyUpRelation, \GTSdirAdjUpRel, \GTSdAUR This macro will draw a directed adjacency upward symbol with relation spacing in math mode.

156 `\GTS@newcommand{\GTSdirectedAdjacencyUpRelation}{\mathrel{\GTSdAU/}}`

157 `\GTS@newcommand{\GTSdirAdjUpRel}{\mathrel{\GTSdAU/}}`

158 `\GTS@newcommand{\GTSdAUR}{\mathrel{\GTSdAU/}}`

\GTSnegatedDirectedAdjacencyUp, \GTSnegDirAdjUp, \GTSnDAU This macro will draw a negated directed adjacency upward symbol.

159 `\GTS@newcommand{\GTSnegatedDirectedAdjacencyUp}{\GTS@a{}{}{1}{1}{}{}}`

160 `\GTS@newcommand{\GTSnegDirAdjUp}{\GTS@a{}{}{1}{1}{}{}}`

161 `\GTS@newcommand{\GTSnDAU}{\GTS@a{}{}{1}{1}{}{}}`

\GTSnegatedDirectedAdjacencyUpRelation, \GTSnegDirAdjUpRel, \GTSnDAUR This macro will draw a negated directed adjacency upward symbol with relation spacing in math mode.

162 `\GTS@newcommand{\GTSnegatedDirectedAdjacencyUpRelation}{\%`

163 `\mathrel{\GTSnDAU/}}%`

164 }

165 `\GTS@newcommand{\GTSnegDirAdjUpRel}{\mathrel{\GTSnDAU/}}`

166 `\GTS@newcommand{\GTSnDAUR}{\mathrel{\GTSnDAU/}}`

\GTSdirectedAdjacencyDown, \GTSdirAdjDown, \GTSdAD This macro will draw a directed adjacency downward symbol. The operand on the left of the symbol should be considered the target of the arc; the operand on the right of the symbol should be considered the source of the arc.

167 `\GTS@newcommand{\GTSdirectedAdjacencyDown}{\GTS@a{}{}{}{1}{}{}}`

168 `\GTS@newcommand{\GTSdirAdjDown}{\GTS@a{}{}{}{1}{}{}}`

169 `\GTS@newcommand{\GTSdAD}{\GTS@a{}{}{}{1}{}{}}`

\GTSdirectedAdjacencyDownRelation, \GTSdirAdjDownRel, \GTSdADR This macro will draw a directed adjacency downward symbol with relation spacing in math mode.

170 `\GTS@newcommand{\GTSdirectedAdjacencyDownRelation}{\mathrel{\GTSdAD/}}`

171 `\GTS@newcommand{\GTSdirAdjDownRel}{\mathrel{\GTSdAD/}}`

172 `\GTS@newcommand{\GTSdADR}{\mathrel{\GTSdAD/}}`

\GTSnegatedDirectedAdjacencyDown, \GTSnegDirAdjDown, \GTSnDAD This macro will draw a negated directed adjacency downward symbol.

```
173 \GTS@newcommand{\GTSnegatedDirectedAdjacencyDown}{\GTS@a{}}{1}{1}{1}
174 \GTS@newcommand{\GTSnegDirAdjDown}{\GTS@a{}}{1}{1}{1}
175 \GTS@newcommand{\GTSnDAD}{\GTS@a{}}{1}{1}{1}
```

\GTSnegatedDirectedAdjacencyDownRelation, \GTSnegDirAdjDownRel, \GTSnDADR This macro will draw a negated directed adjacency downward symbol with relation spacing in math mode.

```
176 \GTS@newcommand{\GTSnegatedDirectedAdjacencyDownRelation}{%
177 \mathrel{\GTSnDAD}/}%
178 }
179 \GTS@newcommand{\GTSnegDirAdjDownRel}{\mathrel{\GTSnDAD}/}%
180 \GTS@newcommand{\GTSnDADR}{\mathrel{\GTSnDAD}/}%

```

\GTS@i This macro will draw any incidence symbol given the correct parameters. Its use is purely technical. See the macros derived from it and **\GTS@j**: **\GTSxincidence**, **\GTSxinc**, and **\GTSxi**. The operand on the left of the symbol should be considered the vertex to which the edge/the operand on the right of the symbol is incident.

Arguments:

{<mainColor>} If non-empty, this color will be used as main color.
{<secondColor>} If non-empty, this color will be used as second color.
{<drawSlash>} Non-empty implies that a negation will be drawn.
{<drawUpArrow>} Non-empty implies that an up-arrow will be drawn.
{<drawDownArrow>} Non-empty implies that a down-arrow will be drawn.

```
181 \newcommand{\GTS@i}[5]{%
182 \if#1\empty\else%
183 \GTSsetMainColor{#1}%
184 \fi%
185 \if#2\empty\else%
186 \GTSsetSecondColor{#2}%
187 \fi%
188 \text{\ensuremath{%
189 \raisebox{-0.22ex}{\scalebox{2.05}[2.05]{%
190 %
191 \raisebox{-0.3ex}{\scalebox{0.7}[0.7]{%
192 $\mathcolor{\GTS@secondColor}{\circ}$%
193 }}%
194 \hspace{-0.39ex}%
195 \raisebox{0.05ex}{\scalebox{0.1}[0.1]{%
196 $\mathcolor{\GTS@secondColor}{\bullet}$%
197 }}%
198 \hspace{-0.12ex}%
199 \raisebox{0.11ex}{\scalebox{0.1}[0.73]{%
200 $\mathcolor{\GTS@secondColor}{\smallblacksquare}$%
201 }}%
202 \hspace{-0.18ex}%
203 \raisebox{0.15ex}{\scalebox{0.2}[0.2]{%
204 $\mathcolor{\GTS@mainColor}{\smallblacksquare}$%
205 }}%
206 \hspace{0.2ex}%
if GTS@drawUpArrow empty else
207 \if#4\empty\else%
208 \hspace{-0.65ex}%
209 \raisebox{-0.18ex}{\scalebox{0.5}[0.5]{%
210 \textcolor{\GTS@secondColor}{\textasciicircum}%
211 }}%
212 \fi%
if GTS@drawDownArrow empty else
213 \if#5\empty\else%
214 \hspace{-0.65ex}%
215 \raisebox{1.37ex}{\scalebox{0.5}[-0.5]{%
216 \textcolor{\GTS@secondColor}{\textasciicircum}%

```

```

217 } }%
218 \fi%
if GTS@drawSlash empty else
219 \if#3\empty\else%
220 \hspace{-0.65ex}%
221 \raisebox{0.1ex}{\scalebox{0.5}[0.5]{%
222 \textcolor{black}{/}%
223 } }%
224 \fi%
225 %
226 } }%
227 } }%
228 \if#1\empty\else%
229 \GTSsetMainColor{\GTS@mainColorBackup}%
230 \fi%
231 \if#2\empty\else%
232 \GTSsetSecondColor{\GTS@secondColorBackup}%
233 \fi%
234 }

```

\GTS@j This macro will handle wrapping in mathematical relation spacing if needed. Its use is purely technical. See the macros derived from it and **\GTS@i**: **\GTSxincidence**, **\GTSxinc**, and **\GTSxi**. Arguments:

{<mainColor>} If non-empty, this color will be used as main color.
{<secondColor>} If non-empty, this color will be used as second color.
{<drawSlash>} Non-empty implies that a negation will be drawn.
{<drawUpArrow>} Non-empty implies that an up-arrow will be drawn.
{<drawDownArrow>} Non-empty implies that a down-arrow will be drawn.
{<relation>} Non-empty implies that relation spacing will be added.

```

235 \newcommand{\GTS@j}[6]{%
236 \if#61%
237 \mathrel{\GTS@i{#1}{#2}{#3}{#4}{#5}}%
238 \else%
239 \GTS@i{#1}{#2}{#3}{#4}{#5}%
240 \fi%
241 }

```

\GTSxincidence, **\GTSxinc**, **\GTSxi** Versatile macros for incidence that can be given options. Argument:

[*<optionsList>*] Sets the following options if not empty:

mainColor=color1 or **mainC=**color1 or **mColor=**color1 or **mC=**color1,
secondColor=color2 or **secondC=**color2 or **sColor=**color2 or **sC=**color2,
monochrome or **mono** or **mon** or **m** (equivalent to **mC=black**, **sC=black**),
negated or **not** or **n**,
in or **i**,
out or **o**,
relation or **rel** or **r**.

```

242 \define@key{GTSxi}{mainColor}{\def\GTS@@mainColor{#1}}
243 \define@key{GTSxi}{mainC}{\def\GTS@@mainColor{#1}}
244 \define@key{GTSxi}{mColor}{\def\GTS@@mainColor{#1}}
245 \define@key{GTSxi}{mC}{\def\GTS@@mainColor{#1}}
246 \define@key{GTSxi}{secondColor}{\def\GTS@@secondColor{#1}}
247 \define@key{GTSxi}{secondC}{\def\GTS@@secondColor{#1}}
248 \define@key{GTSxi}{sColor}{\def\GTS@@secondColor{#1}}
249 \define@key{GTSxi}{sC}{\def\GTS@@secondColor{#1}}
250 \define@key{GTSxi}{monochrome}[1]%
251 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
252 \define@key{GTSxi}{mono}[1]%
253 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
254 \define@key{GTSxi}{mon}[1]%
255 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
256 \define@key{GTSxi}{m}[1]%
257 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
258 \define@key{GTSxi}{negated}[1]{\def\GTS@@drawSlash{1}}

```

```

259 \define@key{GTSxi}{not}[1]{\def\GTS@@drawSlash{1}}
260 \define@key{GTSxi}{n}[1]{\def\GTS@@drawSlash{1}}
261 \define@key{GTSxi}{out}[1]{\def\GTS@@drawUpArrow{1}}
262 \define@key{GTSxi}{o}[1]{\def\GTS@@drawUpArrow{1}}
263 \define@key{GTSxi}{in}[1]{\def\GTS@@drawDownArrow{1}}
264 \define@key{GTSxi}{i}[1]{\def\GTS@@drawDownArrow{1}}
265 \define@key{GTSxi}{relation}[1]{\def\GTS@@relation{1}}
266 \define@key{GTSxi}{rel}[1]{\def\GTS@@relation{1}}
267 \define@key{GTSxi}{r}[1]{\def\GTS@@relation{1}}
268
269 \newcommand{\GTSxi}[1][]{\%
270 \def\GTS@@mainColor{}%
271 \def\GTS@@secondColor{}%
272 \def\GTS@@drawSlash{}%
273 \def\GTS@@drawUpArrow{}%
274 \def\GTS@@drawDownArrow{}%
275 \def\GTS@@relation{}%
276 \setkeys{GTSxi}{#1}%
277 \GTS@j{\GTS@@mainColor}{\GTS@@secondColor}{\GTS@@drawSlash}%
278 {\GTS@@drawUpArrow}{\GTS@@drawDownArrow}{\GTS@@relation}%
279 }
280
281 \newcommand{\GTSxinc}[1][]{\GTSxi[#1]}
282
283 \newcommand{\GTSxincidence}[1][]{\GTSxi[#1]}

```

\GTSincidence, \GTSinc, \GTSi This macro will draw an incidence symbol. The operand on the left of the symbol should be considered the vertex to which the edge/the operand on the right of the symbol is incident.

```

284 \GTS@newcommand{\GTSincidence}{\GTS@i{}{}{}{}}
285 \GTS@newcommand{\GTSinc}{\GTS@i{}{}{}{}}
286 \GTS@newcommand{\GTSi}{\GTS@i{}{}{}{}}

```

\GTSincidenceRelation, \GTSincRel, \GTSiR This macro will draw an incidence symbol with relation spacing in math mode.

```

287 \GTS@newcommand{\GTSincidenceRelation}{\mathrel{\GTSi/}}
288 \GTS@newcommand{\GTSincRel}{\mathrel{\GTSi/}}
289 \GTS@newcommand{\GTSiR}{\mathrel{\GTSi/}}

```

\GTSnegatedIncidence, \GTSnegInc, \GTSnI This macro will draw a negated incidence symbol.

```

290 \GTS@newcommand{\GTSnegatedIncidence}{\GTS@i{}{}{1}{}{}}
291 \GTS@newcommand{\GTSnegInc}{\GTS@i{}{}{1}{}{}}
292 \GTS@newcommand{\GTSnI}{\GTS@i{}{}{1}{}{}}

```

\GTSnegatedIncidenceRelation, \GTSnegIncRel, \GTSnIR This macro will draw a negated incidence symbol with relation spacing in math mode.

```

293 \GTS@newcommand{\GTSnegatedIncidenceRelation}{\mathrel{\GTSnI/}}
294 \GTS@newcommand{\GTSnegIncRel}{\mathrel{\GTSnI/}}
295 \GTS@newcommand{\GTSnIR}{\mathrel{\GTSnI/}}

```

\GTSoutIncidence, \GTSoutInc, \GTSoI This macro will draw a directed incidence upward (out(ward) incidence) symbol. The operand on the left of the symbol should be considered the vertex to which the arc/the operand on the right of the symbol is incident.

```

296 \GTS@newcommand{\GTSoutIncidence}{\GTS@i{}{}{1}{}{}}
297 \GTS@newcommand{\GTSoutInc}{\GTS@i{}{}{1}{}{}}
298 \GTS@newcommand{\GTSoI}{\GTS@i{}{}{1}{}{}}

```

\GTSoutIncidenceRelation, \GTSoutIncRel, \GTSoIR This macro will draw a directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

```

299 \GTS@newcommand{\GTSoutIncidenceRelation}{\mathrel{\GTSoI/}}
300 \GTS@newcommand{\GTSoutIncRel}{\mathrel{\GTSoI/}}
301 \GTS@newcommand{\GTSoIR}{\mathrel{\GTSoI/}}

```

\GTSnegatedOutIncidence, \GTSnegOutInc, \GTSnOI This macro will draw a negated directed incidence upward (out(ward) incidence) symbol.

```
302 \GTS@newcommand{\GTSnegatedOutIncidence}{\GTS@i{}{}{1}{1}}
303 \GTS@newcommand{\GTSnegOutInc}{\GTS@i{}{}{1}{1}}
304 \GTS@newcommand{\GTSnOI}{\GTS@i{}{}{1}{1}}
```

\GTSnegatedOutIncidenceRelation, \GTSnegOutIncRel, \GTSnOIR This macro will draw a negated directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

```
305 \GTS@newcommand{\GTSnegatedOutIncidenceRelation}{\mathrel{\GTSnOI/}}
306 \GTS@newcommand{\GTSnegOutIncRel}{\mathrel{\GTSnOI/}}
307 \GTS@newcommand{\GTSnOIR}{\mathrel{\GTSnOI/}}
```

\GTSinIncidence, \GTSinInc, \GTSiI This macro will draw a directed incidence downward (in(ward) incidence) symbol. The operand on the left of the symbol should be considered the vertex to which the arc/the operand on the right of the symbol is incident.

```
308 \GTS@newcommand{\GTSinIncidence}{\GTS@i{}{}{}{1}}
309 \GTS@newcommand{\GTSinInc}{\GTS@i{}{}{}{1}}
310 \GTS@newcommand{\GTSiI}{\GTS@i{}{}{}{1}}
```

\GTSinIncidenceRelation, \GTSinIncRel, \GTSiIR This macro will draw a directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.

```
311 \GTS@newcommand{\GTSinIncidenceRelation}{\mathrel{\GTSiI/}}
312 \GTS@newcommand{\GTSinIncRel}{\mathrel{\GTSiI/}}
313 \GTS@newcommand{\GTSiIR}{\mathrel{\GTSiI/}}
```

\GTSnegatedInIncidence, \GTSnegInInc, \GTSnII This macro will draw a negated directed incidence downward (in(ward) incidence) symbol.

```
314 \GTS@newcommand{\GTSnegatedInIncidence}{\GTS@i{}{}{1}{1}}
315 \GTS@newcommand{\GTSnegInInc}{\GTS@i{}{}{1}{1}}
316 \GTS@newcommand{\GTSnII}{\GTS@i{}{}{1}{1}}
```

\GTSnegatedInIncidenceRelation, \GTSnegInIncRel, \GTSnIIR This macro will draw a negated directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.

```
317 \GTS@newcommand{\GTSnegatedInIncidenceRelation}{\mathrel{\GTSnII/}}
318 \GTS@newcommand{\GTSnegInIncRel}{\mathrel{\GTSnII/}}
319 \GTS@newcommand{\GTSnIIR}{\mathrel{\GTSnII/}}
```

\GTSadjacencyMonochrome, \GTSadjMono, \GTSadjMon, \GTSaM This macro will draw a monochrome adjacency symbol.

```
320 \GTS@newcommand{\GTSadjacencyMonochrome}{\GTS@a{black}{black}{}{}}
321 \GTS@newcommand{\GTSadjMono}{\GTS@a{black}{black}{}{}}
322 \GTS@newcommand{\GTSadjMon}{\GTS@a{black}{black}{}{}}
323 \GTS@newcommand{\GTSaM}{\GTS@a{black}{black}{}{}}
```

\GTSadjacencyMonochromeRelation, \GTSadjMonoRel, \GTSadjMonRel, \GTSaMR This macro will draw a monochrome adjacency symbol with relation spacing in math mode.

```
324 \GTS@newcommand{\GTSadjacencyMonochromeRelation}{\mathrel{\GTSaM/}}
325 \GTS@newcommand{\GTSadjMonoRel}{\mathrel{\GTSaM/}}
326 \GTS@newcommand{\GTSadjMonRel}{\mathrel{\GTSaM/}}
327 \GTS@newcommand{\GTSaMR}{\mathrel{\GTSaM/}}
```

\GTSunadjacencyMonochrome, \GTSunadjMono, \GTSunadjMon, \GTSuM This macro will draw a monochrome unadjacency symbol.

```
328 \GTS@newcommand{\GTSunadjacencyMonochrome}{\GTS@a{black}{black}{1}{}}
329 \GTS@newcommand{\GTSunadjMono}{\GTS@a{black}{black}{1}{}}
330 \GTS@newcommand{\GTSunadjMon}{\GTS@a{black}{black}{1}{}}
331 \GTS@newcommand{\GTSuM}{\GTS@a{black}{black}{1}{}}
```

\GTSunadjacencyMonochromeRelation, \GTSunadjMonoRel, \GTSunadjMonRel, \GTSuMR This macro will draw a monochrome unadjacency symbol with relation spacing in math mode.

```
332 \GTS@newcommand{\GTSunadjacencyMonochromeRelation}{\mathrel{\GTSuM/}}
333 \GTS@newcommand{\GTSunadjMonoRel}{\mathrel{\GTSuM/}}
334 \GTS@newcommand{\GTSunadjMonRel}{\mathrel{\GTSuM/}}
335 \GTS@newcommand{\GTSuMR}{\mathrel{\GTSuM/}}
```

\GTSdirectedAdjacencyUpMonochrome, \GTSdirAdjUpMono, \GTSdirAdjUpMon, \GTSdAUM This macro will draw a monochrome directed adjacency upward symbol. The operand on the left of the symbol should be considered the source of the arc; the operand on the right of the symbol should be considered the target of the arc.

```
336 \GTS@newcommand{\GTSdirectedAdjacencyUpMonochrome}{%
337 \GTS@a{black}{black}{1}{1}}%
338 }
339 \GTS@newcommand{\GTSdirAdjUpMono}{\GTS@a{black}{black}{1}{1}}
340 \GTS@newcommand{\GTSdirAdjUpMon}{\GTS@a{black}{black}{1}{1}}
341 \GTS@newcommand{\GTSdAUM}{\GTS@a{black}{black}{1}{1}}
```

\GTSdirectedAdjacencyUpMonochromeRelation, \GTSdirAdjUpMonoRel, \GTSdirAdjUpMonRel, \GTSdAUMR This macro will draw a monochrome directed adjacency upward symbol with relation spacing in math mode.

```
342 \GTS@newcommand{\GTSdirectedAdjacencyUpMonochromeRelation}{%
343 \mathrel{\GTSdAUM/}}%
344 }
345 \GTS@newcommand{\GTSdirAdjUpMonoRel}{\mathrel{\GTSdAUM/}}
346 \GTS@newcommand{\GTSdirAdjUpMonRel}{\mathrel{\GTSdAUM/}}
347 \GTS@newcommand{\GTSdAUMR}{\mathrel{\GTSdAUM/}}
```

\GTSnegatedDirectedAdjacencyUpMonochrome, \GTSnegDirAdjUpMono, \GTSnegDirAdjUpMon, \GTSnDAUM This macro will draw a monochrome negated directed adjacency upward symbol.

```
348 \GTS@newcommand{\GTSnegatedDirectedAdjacencyUpMonochrome}{%
349 \GTS@a{black}{black}{1}{1}}%
350 }
351 \GTS@newcommand{\GTSnegDirAdjUpMono}{\GTS@a{black}{black}{1}{1}}
352 \GTS@newcommand{\GTSnegDirAdjUpMon}{\GTS@a{black}{black}{1}{1}}
353 \GTS@newcommand{\GTSnDAUM}{\GTS@a{black}{black}{1}{1}}
```

\GTSnegatedDirectedAdjacencyUpMonochromeRelation, \GTSnegDirAdjUpMonoRel, \GTSnegDirAdjUpMonRel, \GTSnDAUMR This macro will draw a monochrome negated directed adjacency upward symbol with relation spacing in math mode.

```
354 \GTS@newcommand{\GTSnegatedDirectedAdjacencyUpMonochromeRelation}{%
355 \mathrel{\GTSnDAUM/}}%
356 }
357 \GTS@newcommand{\GTSnegDirAdjUpMonoRel}{\mathrel{\GTSnDAUM/}}
358 \GTS@newcommand{\GTSnegDirAdjUpMonRel}{\mathrel{\GTSnDAUM/}}
359 \GTS@newcommand{\GTSnDAUMR}{\mathrel{\GTSnDAUM/}}
```

\GTSdirectedAdjacencyDownMonochrome, \GTSdirAdjDownMono, \GTSdirAdjDownMon, \GTSdADM This macro will draw a monochrome directed adjacency downward symbol. The operand on the left of the symbol should be considered the target of the arc; the operand on the right of the symbol should be considered the source of the arc.

```
360 \GTS@newcommand{\GTSdirectedAdjacencyDownMonochrome}{%
361 \GTS@a{black}{black}{1}{1}}%
362 }
363 \GTS@newcommand{\GTSdirAdjDownMono}{\GTS@a{black}{black}{1}{1}}
364 \GTS@newcommand{\GTSdirAdjDownMon}{\GTS@a{black}{black}{1}{1}}
365 \GTS@newcommand{\GTSdADM}{\GTS@a{black}{black}{1}{1}}
```

\GTSdirectedAdjacencyDownMonochromeRelation, \GTSdirAdjDownMonoRel, \GTSdirAdjDownMonRel, \GTSdADMR This macro will draw a monochrome directed adjacency downward symbol with relation spacing in math mode.

```
366 \GTS@newcommand{\GTSdirectedAdjacencyDownMonochromeRelation}{%
367 \mathrel{\GTSdADM/}}%
368 }
369 \GTS@newcommand{\GTSdirAdjDownMonoRel}{\mathrel{\GTSdADM/}}
370 \GTS@newcommand{\GTSdirAdjDownMonRel}{\mathrel{\GTSdADM/}}
371 \GTS@newcommand{\GTSdADMR}{\mathrel{\GTSdADM/}}
```

\GTSnegatedDirectedAdjacencyDownMonochrome, \GTSnegDirAdjDownMono, \GT-SnegDirAdjDownMon, \GTSnDADM This macro will draw a monochrome negated directed adjacency downward symbol.

```
372 \GTS@newcommand{\GTSnegatedDirectedAdjacencyDownMonochrome}{%
373 \GTS@a{black}{black}{1}{1}}%
374 }
375 \GTS@newcommand{\GTSnegDirAdjDownMono}{\GTS@a{black}{black}{1}{1}}
376 \GTS@newcommand{\GTSnegDirAdjDownMon}{\GTS@a{black}{black}{1}{1}}
377 \GTS@newcommand{\GTSnDADM}{\GTS@a{black}{black}{1}{1}}
```

\GTSnegatedDirectedAdjacencyDownMonochromeRelation, \GTSnegDirAdjDownMonoRel, \GTSnegDirAdjDownMonRel, \GTSnDADMR This macro will draw a monochrome negated directed adjacency downward symbol with relation spacing in math mode.

```
378 \GTS@newcommand{\GTSnegatedDirectedAdjacencyDownMonochromeRelation}{%
379 \mathrel{\GTSnDADM/}}%
380 }
381 \GTS@newcommand{\GTSnegDirAdjDownMonoRel}{\mathrel{\GTSnDADM/}}
382 \GTS@newcommand{\GTSnegDirAdjDownMonRel}{\mathrel{\GTSnDADM/}}
383 \GTS@newcommand{\GTSnDADMR}{\mathrel{\GTSnDADM/}}
```

\GTSincidenceMonochrome, \GTSincMono, \GTSincMon, \GTSiM This macro will draw a monochrome incidence symbol. The operand on the left of the symbol should be considered the vertex to which the edge/the operand on the right of the symbol is incident.

```
384 \GTS@newcommand{\GTSincidenceMonochrome}{\GTS@i{black}{black}{1}{1}}
385 \GTS@newcommand{\GTSincMono}{\GTS@i{black}{black}{1}{1}}
386 \GTS@newcommand{\GTSincMon}{\GTS@i{black}{black}{1}{1}}
387 \GTS@newcommand{\GTSiM}{\GTS@i{black}{black}{1}{1}}
```

\GTSincidenceMonochromeRelation, \GTSincMonoRel, \GTSincMonRel, \GTSiMR This macro will draw a monochrome incidence symbol with relation spacing in math mode.

```
388 \GTS@newcommand{\GTSincidenceMonochromeRelation}{\mathrel{\GTSiM/}}
389 \GTS@newcommand{\GTSincMonoRel}{\mathrel{\GTSiM/}}
390 \GTS@newcommand{\GTSincMonRel}{\mathrel{\GTSiM/}}
391 \GTS@newcommand{\GTSiMR}{\mathrel{\GTSiM/}}
```

\GTSnegatedIncidenceMonochrome, \GTSnegIncMono, \GTSnegIncMon, \GTSnIM This macro will draw a monochrome negated incidence symbol.

```
392 \GTS@newcommand{\GTSnegatedIncidenceMonochrome}{%
393 \GTS@i{black}{black}{1}{1}}%
394 }
395 \GTS@newcommand{\GTSnegIncMono}{\GTS@i{black}{black}{1}{1}}
396 \GTS@newcommand{\GTSnegIncMon}{\GTS@i{black}{black}{1}{1}}
397 \GTS@newcommand{\GTSnIM}{\GTS@i{black}{black}{1}{1}}
```

\GTSnegatedIncidenceMonochromeRelation, \GTSnegIncMonoRel, \GTSnegIncMon-Rel, \GTSnIMR This macro will draw a monochrome negated incidence symbol with relation spacing in math mode.

```
398 \GTS@newcommand{\GTSnegatedIncidenceMonochromeRelation}{\mathrel{\GTSnIM/}}
399 \GTS@newcommand{\GTSnegIncMonoRel}{\mathrel{\GTSnIM/}}
400 \GTS@newcommand{\GTSnegIncMonRel}{\mathrel{\GTSnIM/}}
401 \GTS@newcommand{\GTSnIMR}{\mathrel{\GTSnIM/}}
```

\GTSoutIncidenceMonochrome, \GTSoutIncMono, \GTSoutIncMon, \GTSoIM This macro will draw a monochrome directed incidence upward (out(ward) incidence) symbol. The operand on the left of the symbol should be considered the vertex to which the arc/the operand on the right of the symbol is incident.

```
402 \GTS@newcommand{\GTSoutIncidenceMonochrome}{\GTS@i{black}{black}{1}{1}}
403 \GTS@newcommand{\GTSoutIncMono}{\GTS@i{black}{black}{1}{1}}
404 \GTS@newcommand{\GTSoutIncMon}{\GTS@i{black}{black}{1}{1}}
405 \GTS@newcommand{\GTSoIM}{\GTS@i{black}{black}{1}{1}}
```

\GTSoutIncidenceMonochromeRelation, \GTSoutIncMonoRel, \GTSoutIncMonRel, \GT-SoIMR This macro will draw a monochrome directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

```

406 \GTS@newcommand{\GTSoutIncidenceMonochromeRelation}{\mathrel{\GTSoIM/}}
407 \GTS@newcommand{\GTSoutIncMonoRel}{\mathrel{\GTSoIM/}}
408 \GTS@newcommand{\GTSoutIncMonRel}{\mathrel{\GTSoIM/}}
409 \GTS@newcommand{\GTSoIMR}{\mathrel{\GTSoIM/}}

```

\GTSnegatedOutIncidenceMonochrome, \GTSnegOutIncMono, \GTSnegOutIncMon, \GTSnOIM This macro will draw a monochrome negated directed incidence upward (out(ward) incidence) symbol.

```

410 \GTS@newcommand{\GTSnegatedOutIncidenceMonochrome}{%
411 \GTS@i{black}{black}{1}{1}{1}}%
412 }
413 \GTS@newcommand{\GTSnegOutIncMono}{\GTS@i{black}{black}{1}{1}{1}}
414 \GTS@newcommand{\GTSnegOutIncMon}{\GTS@i{black}{black}{1}{1}{1}}
415 \GTS@newcommand{\GTSnOIM}{\GTS@i{black}{black}{1}{1}{1}}

```

\GTSnegatedOutIncidenceMonochromeRelation, \GTSnegOutIncMonoRel, \GTSnegOutIncMonRel, \GTSnOIMR This macro will draw a monochrome negated directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

```

416 \GTS@newcommand{\GTSnegatedOutIncidenceMonochromeRelation}{%
417 \mathrel{\GTSnOIM/}}%
418 }
419 \GTS@newcommand{\GTSnegOutIncMonoRel}{\mathrel{\GTSnOIM/}}
420 \GTS@newcommand{\GTSnegOutIncMonRel}{\mathrel{\GTSnOIM/}}
421 \GTS@newcommand{\GTSnOIMR}{\mathrel{\GTSnOIM/}}

```

\GTSinIncidenceMonochrome, \GTSinIncMono, \GTSinIncMon, \GTSiIM This macro will draw a monochrome directed incidence downward (in(ward) incidence) symbol. The operand on the left of the symbol should be considered the vertex to which the arc/the operand on the right of the symbol is incident.

```

422 \GTS@newcommand{\GTSinIncidenceMonochrome}{\GTS@i{black}{black}{-}{-}{1}}
423 \GTS@newcommand{\GTSinIncMono}{\GTS@i{black}{black}{-}{-}{1}}
424 \GTS@newcommand{\GTSinIncMon}{\GTS@i{black}{black}{-}{-}{1}}
425 \GTS@newcommand{\GTSiIM}{\GTS@i{black}{black}{-}{-}{1}}

```

\GTSinIncidenceMonochromeRelation, \GTSinIncMonoRel, \GTSinIncMonRel, \GTSiIMR This macro will draw a monochrome directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.

```

426 \GTS@newcommand{\GTSinIncidenceMonochromeRelation}{\mathrel{\GTSiIM/}}
427 \GTS@newcommand{\GTSinIncMonoRel}{\mathrel{\GTSiIM/}}
428 \GTS@newcommand{\GTSinIncMonRel}{\mathrel{\GTSiIM/}}
429 \GTS@newcommand{\GTSiIMR}{\mathrel{\GTSiIM/}}

```

\GTSnegatedInIncidenceMonochrome, \GTSnegInIncMono, \GTSnegInIncMon, \GTSnIIM This macro will draw a monochrome negated directed incidence downward (in(ward) incidence) symbol.

```

430 \GTS@newcommand{\GTSnegatedInIncidenceMonochrome}{%
431 \GTS@i{black}{black}{1}{1}{1}}%
432 }
433 \GTS@newcommand{\GTSnegInIncMono}{\GTS@i{black}{black}{1}{1}{1}}
434 \GTS@newcommand{\GTSnegInIncMon}{\GTS@i{black}{black}{1}{1}{1}}
435 \GTS@newcommand{\GTSnIIM}{\GTS@i{black}{black}{1}{1}{1}}

```

\GTSnegatedInIncidenceMonochromeRelation, \GTSnegInIncMonoRel, \GTSnegInIncMonRel, \GTSnIIMR This macro will draw a monochrome negated directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.

```

436 \GTS@newcommand{\GTSnegatedInIncidenceMonochromeRelation}{%
437 \mathrel{\GTSnIIM/}}%
438 }
439 \GTS@newcommand{\GTSnegInIncMonoRel}{\mathrel{\GTSnIIM/}}
440 \GTS@newcommand{\GTSnegInIncMonRel}{\mathrel{\GTSnIIM/}}
441 \GTS@newcommand{\GTSnIIMR}{\mathrel{\GTSnIIM/}}

```

\GTSmetaNot, \GTSmN This macro will draw a meta-not or relation-not symbol.

```

442 \GTS@newprotectedcommand{\GTSmN}{%

```

```

443 \text{\ensuremath{%
444 \raisebox{-0.44ex}{\scalebox{1}[1]{%
445 \raisebox{0ex}{\scalebox{1}[1]{\not$}}}%
446 \hspace{-1.46ex}%
447 \raisebox{1.2ex}{\scalebox{0.7}[0.7]{m}}}%
448 \hspace{0.2ex}%
449 }}%
450 }}%
451 }
452 \GTS@newcommand{\GTSmetaNot}{\GTSmN/}

```

\GTSmetaAnd, \GTSmA This macro will draw a meta-and or relations-and symbol. This is your duty to check that all relations have same arity. It should be easy as long as you remain in the realm of graphs/2-structures/binary structures. We didn't use Tarski's notation, since square cup has taken the preemptive meaning of disjoint union. Similarly, doublewedge or other wedge symbols have taken various meanings, whilst we want an unambiguous symbol.

```

453 \GTS@newprotectedcommand{\GTSmA}{%
454 \text{\ensuremath{%
455 \raisebox{-0.44ex}{\scalebox{0.95}[0.95]{%
456 \raisebox{0ex}{\scalebox{1}[1]{\wedge$}}}%
457 \hspace{-1.46ex}%
458 \raisebox{1.5ex}{\scalebox{0.7}[0.7]{m}}}%
459 }}%
460 }}%
461 }
462 \GTS@newcommand{\GTSmetaAnd}{\GTSmA/}

```

\GTSmetaAndRelation, \GTSmetaAndRel, \GTSmAR This macro will draw a meta-and symbol with relation spacing in math mode.

```

463 \GTS@newcommand{\GTSmetaAndRelation}{\mathrel{\GTSmA/}}
464 \GTS@newcommand{\GTSmetaAndRel}{\mathrel{\GTSmA/}}
465 \GTS@newcommand{\GTSmAR}{\mathrel{\GTSmA/}}

```

\GTSmetaOr, \GTSmO This macro will draw a meta-or or relations-or symbol. This is your duty to check that all relations have same arity. It should be easy as long as you remain in the realm of graphs/2-structures/binary structures ;). We didn't use Tarski's notation, since square cup has taken the preemptive meaning of disjoint union. Similarly, doublevee or other vee symbols have taken various meanings, whilst we want an unambiguous symbol.

```

466 \GTS@newprotectedcommand{\GTSmO}{%
467 \text{\ensuremath{%
468 \raisebox{-0.44ex}{\scalebox{0.95}[0.95]{%
469 \raisebox{0ex}{\scalebox{1}[1]{\vee$}}}%
470 \hspace{-1.46ex}%
471 \raisebox{1.5ex}{\scalebox{0.7}[0.7]{m}}}%
472 }}%
473 }}%
474 }
475 \GTS@newcommand{\GTSmetaOr}{\GTSmO/}

```

\GTSmetaOrRelation, \GTSmetaOrRel, \GTSmOR This macro will draw a meta-or symbol with relation spacing in math mode.

```

476 \GTS@newcommand{\GTSmetaOrRelation}{\mathrel{\GTSmO/}}
477 \GTS@newcommand{\GTSmetaOrRel}{\mathrel{\GTSmO/}}
478 \GTS@newcommand{\GTSmOR}{\mathrel{\GTSmO/}}

```

\GTSxmetallogic, \GTSxml Versatile macros for meta-logic symbols that can be given options.

Argument:

[*\langle optionsList \rangle*] Sets the following options if not empty:

not or **n**,

and or **a**,

or or **o**,

relation or **rel** or **r**.

Of course first three options are incompatible, and the fourth is compatible only with the second and third options.

```

479 \define@key{GTSxml}{not}[1]{\def\GTS@@drawMetaNot{1}}
480 \define@key{GTSxml}{n}[1]{\def\GTS@@drawMetaNot{1}}
481 \define@key{GTSxml}{and}[1]{\def\GTS@@drawMetaAnd{1}}
482 \define@key{GTSxml}{a}[1]{\def\GTS@@drawMetaAnd{1}}
483 \define@key{GTSxml}{or}[1]{\def\GTS@@drawMetaOr{1}}
484 \define@key{GTSxml}{o}[1]{\def\GTS@@drawMetaOr{1}}
485 \define@key{GTSxml}{relation}[1]{\def\GTS@@relation{1}}
486 \define@key{GTSxml}{rel}[1]{\def\GTS@@relation{1}}
487 \define@key{GTSxml}{r}[1]{\def\GTS@@relation{1}}
488
489 \newcommand{\GTSxml}[1][]{\%
490 \def\GTS@@drawMetaNot{}%
491 \def\GTS@@drawMetaAnd{}%
492 \def\GTS@@drawMetaOr{}%
493 \def\GTS@@relation{}%
494 \setkeys{GTSxml}{#1}%
495 \if\GTS@@drawMetaNot1%
496 \GTSmN/%
497 \else\if\GTS@@drawMetaAnd1%
498 \if\GTS@@relation{1}%
499 \GTSmAR/%
500 \else%
501 \GTSmA/%
502 \fi%
503 \else\if\GTS@@drawMetaOr1%
504 \if\GTS@@relation{1}%
505 \GTSmOR/%
506 \else%
507 \GTSmO/%
508 \fi%
509 \else%
510 Wrong call to \textbackslash{GTSxml}%
511 \fi%
512 \fi%
513 \fi%
514 }
515
516 \newcommand{\GTSxmetallogic}[1][]{\GTSxml[#1]}

```

\GTSx One macro to rule them all. Versatile macro for all symbols that can be given options, and a symbol type mandatory switch.

Argument:

[*(optionsList)*] Sets the following options if not empty:

- If $\{\langle symbolType \rangle\}$ below is a, see \GTSxa:
mainColor=color1 or mainC=color1 or mColor=color1 or mC=color1,
secondColor=color2 or secondC=color2 or sColor=color2 or sC=color2,
monochrome or mono or mon or m (equivalent to mC=black,sC=black),
negated or not or n,
up or u,
down or d,
relation or rel or r.
- If $\{\langle symbolType \rangle\}$ below is i, see \GTSxi:
mainColor=color1 or mainC=color1 or mColor=color1 or mC=color1,
secondColor=color2 or secondC=color2 or sColor=color2 or sC=color2,
monochrome or mono or mon or m (equivalent to mC=black,sC=black),
negated or not or n,
in or i,
out or o,
relation or rel or r.
- If $\{\langle symbolType \rangle\}$ below is m, see \GTSxml:
not or n,

and or a,
or or o,
relation or rel or r.

`{(symbolType)}` a mandatory switch; it can take value `a` for adjacency, `i` for incidence, `m` for meta-logic.

```
517 \newcommand{\GTSx}[2][\]{%
518 \if#2a%
519 \GTSxa[#1]%
520 \else\if#2i%
521 \GTSxi[#1]%
522 \else\if#2m%
523 \GTSxmi[#1]%
524 \else%
525 Wrong call to \textbackslash{\GTSx}%
526 \fi%
527 \fi%
528 \fi%
529 }

530 \endinput
531 \</package>
```

4 Acknowledgments

Thank You God! Thank You Father! Thank You Jesus! Thank You Holy-Spirit!

5 FAQ

Question: Why GraphTheorySymbol instead of GraphTheorySymbols? GraphTheorySymbol does contain many symbols.

Answer: Because I followed one common usage on CTAN.

Here is the list of all current packages with the word "symbol" in their name:

actuarialsymbol, adfsymbols, compact-symbols, cookingsymbols, FdSymbol, jpnedumathsymbols, KKsymbols, listofsymbols, losymbol, maths-symbols, mdsymbol, MnSymbol, open-everyday-symbols, qsymbols, SVRsymbols, symbolindex, The Comprehensive LaTeX Symbol List, tikz-cookingsymbols, tikzsymbols.

7 "symbol" plus GraphTheorySymbol 8, 12 "symbols".

"symb" abbreviation, "sym", "sy" and "s" are also quite common;

oPlotSymbl did it its own way ;) XD.

Because of the goal of GraphTheorySymbol, I was mainly looking at packages like FdSymbol, mdsymbol, MnSymbol, and The Comprehensive LaTeX Symbol List before creating my package; hence I followed this apparent majority, instead of listening to my thought that Symbols would be better.

After the package was uploaded to CTAN for a version update, this question came again, but CTAN admins were reluctant to change the package name afterward.

Otherwise, it is a matter of hours to modify and upload GraphTheorySymbols with version 2.0.0 to CTAN.

6 Support

This package is gratis and free. But if you can star it on GitHub, it is a nice encouragement.

7 Change History

v0.1.0 – 2026-08-01	v1.1.1 – 2026-08-30
General: Initial version 1	General: Small corrections and improvements 1
v1.0.0 – 2026-08-26	
General: First public release 1	v1.2.0 – 2026-09-06
v1.1.0 – 2026-08-29	General: CTAN URL, new macros for same
General: Added a memo 1	set of symbols 1

v1.2.1 – 2026-09-08	paragraph command instead	1
General: Smaller tests output		1
v1.3.0 – 2026-09-08	General: Add A4, USLetter, and Book variants of PDFs.	1
General: New macros for monochrome symbols		1
v1.4.0 – 2026-09-12	General: Add verbatim code for compound adjacency in memo.	1
General: New macros for symbols for logical operations on relations		1
v1.5.0 – 2026-09-12	General: Rename test(.tex, etc.) to graph-theory-symbol-test(.tex, etc.).	1
General: One macro to rule them all		1
v1.5.1 – 2026-09-13	v1.7.0 – 2026-09-21	
General: Use noprint option of doc package to avoid too big left margins, and use	General: Add FAQ section.	1

Index

G

<code>\GTS@@drawDownArrow</code>	120, 121, 131, 135, 263, 264, 274, 278
<code>\GTS@@drawMetaAnd</code>	481, 482, 491, 497
<code>\GTS@@drawMetaNot</code>	479, 480, 490, 495
<code>\GTS@@drawMetaOr</code>	483, 484, 492, 503
<code>\GTS@@drawSlash</code>	115, 116, 117, 129, 134, 258, 259, 260, 272, 277
<code>\GTS@@drawUpArrow</code>	118, 119, 130, 135, 261, 262, 273, 278
<code>\GTS@@mainColor</code> 99, 100, 101, 102, 108, 110, 112, 114, 127, 134, 242, 243, 244, 245, 251, 253, 255, 257, 270, 277	
<code>\GTS@@relation</code>	122, 123, 124, 132, 135, 265, 266, 267, 275, 278, 485, 486, 487, 493, 498, 504
<code>\GTS@@secondColor</code> . 103, 104, 105, 106, 108, 110, 112, 114, 128, 134, 246, 247, 248, 249, 251, 253, 255, 257, 271, 277	
<code>\GTS@a</code> . 6, 34, 94, 96, 141, 142, 143, 147, 148, 149, 153, 154, 155, 159, 160, 161, 167, 168, 169, 173, 174, 175, 320, 321, 322, 323, 328, 329, 330, 331, 337, 339, 340, 341, 349, 351, 352, 353, 361, 363, 364, 365, 373, 375, 376, 377	
<code>\GTS@b</code>	6, 92, 134
<code>\GTS@drawDownArrow</code>	16
<code>\GTS@drawSlash</code>	14
<code>\GTS@drawUpArrow</code>	15
<code>\GTS@i</code> 9, 181, 237, 239, 284, 285, 286, 290, 291, 292, 296, 297, 298, 302, 303, 304, 308, 309, 310, 314, 315, 316, 384, 385, 386, 387, 393, 395, 396, 397, 402, 403, 404, 405, 411, 413, 414, 415, 422, 423, 424, 425, 431, 433, 434, 435	
<code>\GTS@j</code>	9, 235, 277
<code>\GTS@mainColor</code>	10, 26, 27, 53, 67, 73, 204
<code>\GTS@mainColorBackup</code>	12, 26, 86, 229
<code>\GTS@mainColorTemp</code>	25, 27
<code>\GTS@newcommand</code> . . 6, 18, 141, 142, 143, 144, 145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155, 156, 157, 158, 159, 160, 161, 162, 165, 166, 167, 168, 169, 170, 171, 172, 173, 174, 175, 176, 179, 180, 284, 285, 286, 287, 288, 289, 290, 291, 292, 293, 294, 295, 296, 297, 298, 299, 300, 301, 302, 303, 304, 305, 306, 307, 308, 309, 310, 311, 312, 313, 314, 315, 316, 317, 318, 319, 320, 321, 322, 323, 324, 325, 326, 327, 328, 329, 330, 331, 332, 333, 334, 335, 336, 339, 340, 341, 342, 345, 346, 347, 348, 351, 352, 353, 354, 357, 358, 359, 360, 363, 364, 365, 366, 369, 370, 371, 372, 375, 376, 377, 378, 381, 382, 383, 384, 385, 386, 387, 388, 389, 390, 391, 392, 395, 396, 397, 398, 399, 400, 401, 402, 403, 404, 405, 406, 407, 408, 409, 410, 413, 414, 415, 416, 419, 420, 421, 422, 423, 424, 425, 426, 427, 428, 429, 430, 433, 434, 435, 436, 439, 440, 441, 452, 462, 463, 464, 465, 475, 476, 477, 478	
<code>\GTS@newprotectedcommand</code>	6, 21, 442, 453, 466
<code>\GTS@secondColor</code>	11, 31, 32, 45, 49, 57, 61, 192, 196, 200, 210, 216
<code>\GTS@secondColorBackup</code>	13, 31, 89, 232
<code>\GTS@secondColorTemp</code>	30, 32
<code>\GTSa</code>	7, 141, 144, 145, 146
<code>\GTSadj</code>	7, 141
<code>\GTSadjacency</code>	7, 141
<code>\GTSadjacencyMonochrome</code>	12, 320
<code>\GTSadjacencyMonochromeRelation</code>	12, 324

\GTSadjacencyRelation	7, 144
\GTSadjMon	12 , 320
\GTSadjMono	12 , 320
\GTSadjMonoRel	12 , 324
\GTSadjMonRel	12 , 324
\GTSadjRel	7, 144
\GTSaM	12 , 320 , 324 , 325 , 326 , 327
\GTSaMR	12 , 324
\GTSaR	7, 144
\GTSdAD	8, 167 , 170 , 171 , 172
\GTSdADM	14 , 360 , 367 , 369 , 370 , 371
\GTSdADMR	14 , 366
\GTSdADR	8, 170
\GTSdAU	7, 153 , 156 , 157 , 158
\GTSdAUM	13 , 336 , 343 , 345 , 346 , 347
\GTSdAUMR	13 , 342
\GTSdAUR	8, 156
\GTSdirAdjDown	8, 167
\GTSdirAdjDownMon	14 , 360
\GTSdirAdjDownMono	14 , 360
\GTSdirAdjDownMonoRel	14 , 366
\GTSdirAdjDownMonRel	14 , 366
\GTSdirAdjDownRel	8, 170
\GTSdirAdjUp	7, 153
\GTSdirAdjUpMon	13 , 336
\GTSdirAdjUpMono	13 , 336
\GTSdirAdjUpMonoRel	13 , 342
\GTSdirAdjUpMonRel	13 , 342
\GTSdirAdjUpRel	8, 156
\GTSdirectedAdjacencyDown	8, 167
\GTSdirectedAdjacencyDownMonochrome	14 , 360
\GTSdirectedAdjacencyDownMonochromeRelation	14 , 366
\GTSdirectedAdjacencyDownRelation	8, 170
\GTSdirectedAdjacencyUp	7, 153
\GTSdirectedAdjacencyUpMonochrome	13 , 336
\GTSdirectedAdjacencyUpMonochromeRelation	13 , 342
\GTSdirectedAdjacencyUpRelation	8, 156
\GTSi	9, 284 , 287 , 288 , 289
\GTSiI	11 , 308 , 311 , 312 , 313
\GTSiIM	16 , 422 , 426 , 427 , 428 , 429
\GTSiIMR	17 , 426
\GTSiIR	11 , 311
\GTSiM	15 , 384 , 388 , 389 , 390 , 391
\GTSiMR	15 , 388
\GTSinc	9, 284
\GTSincidence	9, 284
\GTSincidenceMonochrome	15 , 384
\GTSincidenceMonochromeRelation	15 , 388
\GTSincidenceRelation	10 , 287
\GTSincMon	15 , 384
\GTSincMono	15 , 384
\GTSincMonoRel	15 , 388
\GTSincMonRel	15 , 388
\GTSincRel	10 , 287
\GTSinInc	11 , 308
\GTSinIncidence	11 , 308
\GTSinIncidenceMonochrome	16 , 422
\GTSinIncidenceMonochromeRelation	17 , 426
\GTSinIncidenceRelation	11 , 311
\GTSinIncMon	16 , 422
\GTSinIncMono	16 , 422

\GTSinIncMonoRel	17, 426
\GTSinIncMonRel	17, 426
\GTSinIncRel	11, 311
\GTSiR	10, 287
\GTSmA	18, 453 , 463, 464, 465, 501
\GTSmAR	18, 463 , 499
\GTSmetaAnd	18, 453
\GTSmetaAndRel	18, 463
\GTSmetaAndRelation	18, 463
\GTSmetaNot	17, 442
\GTSmetaOr	18, 466
\GTSmetaOrRel	18, 476
\GTSmetaOrRelation	18, 476
\GTSmN	17, 442 , 496
\GTSmO	18, 466 , 476, 477, 478, 507
\GTSmOR	18, 476 , 505
\GTSnDAD	8, 173 , 177, 179, 180
\GTSnDADM	14, 372 , 379, 381, 382, 383
\GTSnDADMR	14, 378
\GTSnDADR	9, 176
\GTSnDAU	8, 159 , 163, 165, 166
\GTSnDAUM	13, 348 , 355, 357, 358, 359
\GTSnDAUMR	13, 354
\GTSnDAUR	8, 162
\GTSnegatedDirectedAdjacencyDown	8, 173
\GTSnegatedDirectedAdjacencyDownMonochrome	14, 372
\GTSnegatedDirectedAdjacencyDownMonochromeRelation	14, 378
\GTSnegatedDirectedAdjacencyDownRelation	9, 176
\GTSnegatedDirectedAdjacencyUp	8, 159
\GTSnegatedDirectedAdjacencyUpMonochrome	13, 348
\GTSnegatedDirectedAdjacencyUpMonochromeRelation	13, 354
\GTSnegatedDirectedAdjacencyUpRelation	8, 162
\GTSnegatedIncidence	10, 290
\GTSnegatedIncidenceMonochrome	15, 392
\GTSnegatedIncidenceMonochromeRelation	15, 398
\GTSnegatedIncidenceRelation	10, 293
\GTSnegatedInIncidence	11, 314
\GTSnegatedInIncidenceMonochrome	17, 430
\GTSnegatedInIncidenceMonochromeRelation	17, 436
\GTSnegatedInIncidenceRelation	12, 317
\GTSnegatedOutIncidence	11, 302
\GTSnegatedOutIncidenceMonochrome	16, 410
\GTSnegatedOutIncidenceMonochromeRelation	16, 416
\GTSnegatedOutIncidenceRelation	11, 305
\GTSnegDirAdjDown	8, 173
\GTSnegDirAdjDownMon	14, 372
\GTSnegDirAdjDownMono	14, 372
\GTSnegDirAdjDownMonoRel	14, 378
\GTSnegDirAdjDownMonRel	14, 378
\GTSnegDirAdjDownRel	9, 176
\GTSnegDirAdjUp	8, 159
\GTSnegDirAdjUpMon	13, 348
\GTSnegDirAdjUpMono	13, 348
\GTSnegDirAdjUpMonoRel	13, 354
\GTSnegDirAdjUpMonRel	13, 354
\GTSnegDirAdjUpRel	8, 162
\GTSnegInc	10, 290
\GTSnegIncMon	15, 392
\GTSnegIncMono	15, 392
\GTSnegIncMonoRel	15, 398
\GTSnegIncMonRel	15, 398

\GTSnegIncRel	10, <u>293</u>
\GTSnegInInc	11, <u>314</u>
\GTSnegInIncMon	17, <u>430</u>
\GTSnegInIncMono	17, <u>430</u>
\GTSnegInIncMonoRel	17, <u>436</u>
\GTSnegInIncMonRel	17, <u>436</u>
\GTSnegInIncRel	12, <u>317</u>
\GTSnegOutInc	11, <u>302</u>
\GTSnegOutIncMon	16, <u>410</u>
\GTSnegOutIncMono	16, <u>410</u>
\GTSnegOutIncMonoRel	16, <u>416</u>
\GTSnegOutIncMonRel	16, <u>416</u>
\GTSnegOutIncRel	11, <u>305</u>
\GTSnI	10, <u>290</u> , <u>293</u> , <u>294</u> , <u>295</u>
\GTSnII	11, <u>314</u> , <u>317</u> , <u>318</u> , <u>319</u>
\GTSnIIM	17, <u>430</u> , <u>437</u> , <u>439</u> , <u>440</u> , <u>441</u>
\GTSnIIMR	17, <u>436</u>
\GTSnIIR	12, <u>317</u>
\GTSnIM	15, <u>392</u> , <u>398</u> , <u>399</u> , <u>400</u> , <u>401</u>
\GTSnIMR	15, <u>398</u>
\GTSnIR	10, <u>293</u>
\GTSnOI	11, <u>302</u> , <u>305</u> , <u>306</u> , <u>307</u>
\GTSnOIM	16, <u>410</u> , <u>417</u> , <u>419</u> , <u>420</u> , <u>421</u>
\GTSnOIMR	16, <u>416</u>
\GTSnOIR	11, <u>305</u>
\GTSoI	10, <u>296</u> , <u>299</u> , <u>300</u> , <u>301</u>
\GTSoIM	15, <u>402</u> , <u>406</u> , <u>407</u> , <u>408</u> , <u>409</u>
\GTSoIMR	16, <u>406</u>
\GTSoIR	10, <u>299</u>
\GTSoutInc	10, <u>296</u>
\GTSoutIncidence	10, <u>296</u>
\GTSoutIncidenceMonochrome	15, <u>402</u>
\GTSoutIncidenceMonochromeRelation	16, <u>406</u>
\GTSoutIncidenceRelation	10, <u>299</u>
\GTSoutIncMon	15, <u>402</u>
\GTSoutIncMono	15, <u>402</u>
\GTSoutIncMonoRel	16, <u>406</u>
\GTSoutIncMonRel	16, <u>406</u>
\GTSoutIncRel	10, <u>299</u>
\GTSsetMainColor	6, <u>24</u> , <u>36</u> , <u>86</u> , <u>183</u> , <u>229</u>
\GTSsetSecondColor	6, <u>29</u> , <u>39</u> , <u>89</u> , <u>186</u> , <u>232</u>
\GTSu	7, <u>147</u> , <u>150</u> , <u>151</u> , <u>152</u>
\GTSuM	12, <u>328</u> , <u>332</u> , <u>333</u> , <u>334</u> , <u>335</u>
\GTSuMR	12, <u>332</u>
\GTSunadj	7, <u>147</u>
\GTSunadjacency	7, <u>147</u>
\GTSunadjacencyMonochrome	12, <u>328</u>
\GTSunadjacencyMonochromeRelation	12, <u>332</u>
\GTSunadjacencyRelation	7, <u>150</u>
\GTSunadjMon	12, <u>328</u>
\GTSunadjMono	12, <u>328</u>
\GTSunadjMonoRel	12, <u>332</u>
\GTSunadjMonRel	12, <u>332</u>
\GTSunadjRel	7, <u>150</u>
\GTSuR	7, <u>150</u>
\GTSx	18, <u>517</u>
\GTSxa	6, <u>99</u> , <u>519</u>
\GTSxadj	6, <u>99</u>
\GTSxadjacency	6, <u>99</u>
\GTSxi	9, <u>242</u> , <u>521</u>
\GTSxinc	9, <u>242</u>

\GTSxincidence	9, 242
\GTSxmetallogic	18, 479
\GTSxml	18, 479 , 523