

GraphTheorySymbol: $\text{\LaTeX}$ Commands with Symbols for Graph Theory

Laurent Frédéric Bernard François Lyaudet

Website: <https://lyaudet.eu/laurent/>

Email: Laurent.Lyaudet@gmail.com

v1.8.0 2026/09/28

Abstract

This documentation is for $\text{\LaTeX}$ package GraphTheorySymbol. It provides symbols used in graph theory. The adjacency and incidence symbols, and the meta-logical operators symbols were created by the author of this package.

Contents

1	Introduction	3
2	Usage	4
2.1	Memo or for the impatient	4
2.2	Detailed usage	7
2.2.1	General macros	7
2.2.2	Standard adjacency macros	7
2.2.3	Standard incidence macros	11
2.2.4	Monochrome adjacency macros	15
2.2.5	Monochrome incidence macros	19
2.2.6	Meta-logic macros	24
2.3	Good practices	25
3	Implementation	26
4	Acknowledgments	38
5	FAQ	39
6	Support	39
7	Change History	39

1 Introduction

This documentation is for $\text{\LaTeX}$ package GraphTheorySymbol. It provides symbols used in graph theory. The adjacency and incidence symbols, and the meta-logical operators symbols were created by the author of this package.

This package is licenced under Lesser GNU General Public License version 3 or later (LGPLv3+). It means you are free do anything with it, but if you do improve the code of the symbols that we provide, please do share these improvements in a similar way. There is no restriction on other graph theory symbols/code, even if it would be a good fit for inclusion in this package. There is also no need to share in a similar way what you build with this package. The text of the licenses is available at:

<https://www.gnu.org/licenses/>.

The git repository of this source code is also available at:

<https://github.com/LLyaudet/GraphTheorySymbol/>.

Clone it with this URL:

[git@github.com:LLyaudet/GraphTheorySymbol.git](https://github.com/LLyaudet/GraphTheorySymbol.git).

This package is available on CTAN:

<https://ctan.org/pkg/graph-theory-symbol>.

This is our first $\text{\LaTeX}$ package. It may be that our macros are quite slow and that a document making extensive use of these macros will be slow to compile. If you know how to produce better $\text{\LaTeX}$ code, please submit a pull request on GitHub.

2 Usage

2.1 Memo or for the impatient

Add in your preamble: `\usepackage{graph-theory-symbol}`.

For clarity, below we only show long macro names and short macro names; see Detailed usage section for intermediate length macro names.

Long name	Short name	Result	In context
<code>\GTSadjacency/</code>	<code>\GTSa/</code>	$\circ$	$u \circ v$
<code>\GTSadjacencyRelation/</code>	<code>\GTSaR/</code>	$\circ$	$u \circ v$
<code>\GTSunadjacency/</code>	<code>\GTSu/</code>	$\circ$	$u \circ v$
<code>\GTSunadjacencyRelation/</code>	<code>\GTSuR/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyUp/</code>	<code>\GTSdAU/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyUpRelation/</code>	<code>\GTSdAUR/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyUp/</code>	<code>\GTSnDAU/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyUpRelation/</code>	<code>\GTSnDAUR/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyDown/</code>	<code>\GTSdAD/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyDownRelation/</code>	<code>\GTSdADR/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyDown/</code>	<code>\GTSnDAD/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyDownRelation/</code>	<code>\GTSnDADR/</code>	$\circ$	$u \circ v$
<code>\GTSincidence/</code>	<code>\GTSi/</code>	$\circ$	$v \circ e$
<code>\GTSincidenceRelation/</code>	<code>\GTSiR/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedIncidence/</code>	<code>\GTSnI/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedIncidenceRelation/</code>	<code>\GTSnIR/</code>	$\circ$	$v \circ e$
<code>\GTSoutIncidence/</code>	<code>\GTSOI/</code>	$\circ$	$v \circ e$
<code>\GTSoutIncidenceRelation/</code>	<code>\GTSOIR/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedOutIncidence/</code>	<code>\GTSnOI/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedOutIncidenceRelation/</code>	<code>\GTSnOIR/</code>	$\circ$	$v \circ e$
<code>\GTSinIncidence/</code>	<code>\GTSiI/</code>	$\circ$	$v \circ e$
<code>\GTSinIncidenceRelation/</code>	<code>\GTSiIR/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedInIncidence/</code>	<code>\GTSnII/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedInIncidenceRelation/</code>	<code>\GTSnIIR/</code>	$\circ$	$v \circ e$

Long name	Short name	Result	In context
<code>\GTSadjacencyMonochrome/</code>	<code>\GTSaM/</code>	$\circ$	$u \circ v$
<code>\GTSadjacencyMonochromeRelation/</code>	<code>\GTSaMR/</code>	$\circ$	$u \circ v$
<code>\GTSunadjacencyMonochrome/</code>	<code>\GTSuM/</code>	$\circ$	$u \circ v$
<code>\GTSunadjacencyMonochromeRelation/</code>	<code>\GTSuMR/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyUpMonochrome/</code>	<code>\GTSdAUM/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyUpMonochromeRelation/</code>	<code>\GTSdAUMR/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyUpMonochrome/</code>	<code>\GTSnDAUM/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyUpMonochromeRelation/</code>	<code>\GTSnDAUMR/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyDownMonochrome/</code>	<code>\GTSdADM/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyDownMonochromeRelation/</code>	<code>\GTSdADM/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyDownMonochrome/</code>	<code>\GTSnDADM/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyDownMonochromeRelation/</code>	<code>\GTSnDADM/</code>	$\circ$	$u \circ v$
<code>\GTSincidenceMonochrome/</code>	<code>\GTSiM/</code>	$\circ$	$v \circ e$
<code>\GTSincidenceMonochromeRelation/</code>	<code>\GTSiMR/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedIncidenceMonochrome/</code>	<code>\GTSnIM/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedIncidenceMonochromeRelation/</code>	<code>\GTSnIMR/</code>	$\circ$	$v \circ e$
<code>\GTSoutIncidenceMonochrome/</code>	<code>\GTSOIM/</code>	$\circ$	$v \circ e$
<code>\GTSoutIncidenceMonochromeRelation/</code>	<code>\GTSOIMR/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedOutIncidenceMonochrome/</code>	<code>\GTSnOIM/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedOutIncidenceMonochromeRelation/</code>	<code>\GTSnOIMR/</code>	$\circ$	$v \circ e$
<code>\GTSinIncidenceMonochrome/</code>	<code>\GTSiIM/</code>	$\circ$	$v \circ e$
<code>\GTSinIncidenceMonochromeRelation/</code>	<code>\GTSiIMR/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedInIncidenceMonochrome/</code>	<code>\GTSnIIM/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedInIncidenceMonochromeRelation/</code>	<code>\GTSnIIMR/</code>	$\circ$	$v \circ e$

<code>\GTSsetMainColor{blue}</code>			
Long name	Short name	Result	In context
<code>\GTSadjacency/</code>	<code>\GTSa/</code>		$u \overset{\circ}{\sim} v$
<code>\GTSadjacencyRelation/</code>	<code>\GTSaR/</code>		$u \overset{\circ}{\sim} v$
<code>\GTSunadjacency/</code>	<code>\GTSu/</code>		$u \overset{\circ}{\sim} v$
<code>\GTSunadjacencyRelation/</code>	<code>\GTSuR/</code>		$u \overset{\circ}{\sim} v$
<code>\GTSdirectedAdjacencyUp/</code>	<code>\GTSdAU/</code>		$u \overset{\circ}{\sim} v$
<code>\GTSdirectedAdjacencyUpRelation/</code>	<code>\GTSdAUR/</code>		$u \overset{\circ}{\sim} v$
<code>\GTSnegatedDirectedAdjacencyUp/</code>	<code>\GTSnDAU/</code>		$u \overset{\circ}{\sim} v$
<code>\GTSnegatedDirectedAdjacencyUpRelation/</code>	<code>\GTSnDAUR/</code>		$u \overset{\circ}{\sim} v$
<code>\GTSdirectedAdjacencyDown/</code>	<code>\GTSdAD/</code>		$u \overset{\circ}{\sim} v$
<code>\GTSdirectedAdjacencyDownRelation/</code>	<code>\GTSdADR/</code>		$u \overset{\circ}{\sim} v$
<code>\GTSnegatedDirectedAdjacencyDown/</code>	<code>\GTSnDAD/</code>		$u \overset{\circ}{\sim} v$
<code>\GTSnegatedDirectedAdjacencyDownRelation/</code>	<code>\GTSnDADR/</code>		$u \overset{\circ}{\sim} v$
<code>\GTSincidence/</code>	<code>\GTSi/</code>		$v \overset{\circ}{\sim} e$
<code>\GTSincidenceRelation/</code>	<code>\GTSiR/</code>		$v \overset{\circ}{\sim} e$
<code>\GTSnegatedIncidence/</code>	<code>\GTSnI/</code>		$v \overset{\circ}{\sim} e$
<code>\GTSnegatedIncidenceRelation/</code>	<code>\GTSnIR/</code>		$v \overset{\circ}{\sim} e$
<code>\GTSoutIncidence/</code>	<code>\GTSOI/</code>		$v \overset{\circ}{\sim} e$
<code>\GTSoutIncidenceRelation/</code>	<code>\GTSOIR/</code>		$v \overset{\circ}{\sim} e$
<code>\GTSnegatedOutIncidence/</code>	<code>\GTSnOI/</code>		$v \overset{\circ}{\sim} e$
<code>\GTSnegatedOutIncidenceRelation/</code>	<code>\GTSnOIR/</code>		$v \overset{\circ}{\sim} e$
<code>\GTSinIncidence/</code>	<code>\GTSiI/</code>		$v \overset{\circ}{\sim} e$
<code>\GTSinIncidenceRelation/</code>	<code>\GTSiIR/</code>		$v \overset{\circ}{\sim} e$
<code>\GTSnegatedInIncidence/</code>	<code>\GTSnII/</code>		$v \overset{\circ}{\sim} e$
<code>\GTSnegatedInIncidenceRelation/</code>	<code>\GTSnIIR/</code>		$v \overset{\circ}{\sim} e$

Long name	Short name	Result	In context
<code>\GTSmetaNot/</code>	<code>\GTSmN/</code>	$\neg$	$\neg \overset{\circ}{\sim}$
<code>\GTSmetaAnd/</code>	<code>\GTSmA/</code>	$\wedge$	$\overset{\circ}{\sim} \wedge \overset{\circ}{\sim}$
<code>\GTSmetaOr/</code>	<code>\GTSmO/</code>	$\vee$	$\overset{\circ}{\sim} \vee \overset{\circ}{\sim}$

Meta-logic can be used for compound adjacency types, etc.

Implicit meta-and via concatenation, no space except around whole relations compositions, no parentheses via higher priority to meta-and, brackets when all possible adjacencies are specified between two vertices:

Tournament adjacency:

$\forall u, v, u \overset{\circ}{\sim} \overset{\circ}{\sim} v$.

Tournament adjacency with maybe some colored edge also, who knows?:

$\forall u, v, u \overset{\circ}{\sim} \overset{\circ}{\sim} v$.

Directed graph:

$\forall u, v, u \overset{\circ}{\sim} \overset{\circ}{\sim} \overset{\circ}{\sim} \overset{\circ}{\sim} v$.

Oriented graph:

$\forall u, v, u \overset{\circ}{\sim} \overset{\circ}{\sim} \overset{\circ}{\sim} v$.

Tournament adjacency:

$\overset{\circ}{\sim} \overset{\circ}{\sim}$ is obtained with `\mathrel{\{\GTSdAD/\GTSnDAU/\GTSmO/\GTSnDAD/\GTSdAU/\}}`.

Tournament adjacency with maybe some colored edge also, who knows?:

$\overset{\circ}{\sim} \overset{\circ}{\sim}$ is obtained with `\mathrel{\{\GTSdAD/\GTSnDAU/\GTSmO/\GTSnDAD/\GTSdAU/\}}`.

Directed graph:

$\overset{\circ}{\sim} \overset{\circ}{\sim} \overset{\circ}{\sim} \overset{\circ}{\sim}$ is obtained with

`\mathrel{\{\GTSdAD/\GTSnDAU/\GTSmO/\GTSnDAD/\GTSdAU/\GTSmO/\GTSdAD/\GTSdAU/\GTSmO/\GTSnDAD/\GTSnDAU/\}}`.

Oriented graph:

$\overset{\circ}{\sim} \overset{\circ}{\sim} \overset{\circ}{\sim}$ is obtained with

`\mathrel{\{\GTSdAD/\GTSnDAU/\GTSmO/\GTSnDAD/\GTSdAU/\GTSmO/\GTSnDAD/\GTSnDAU/\}}`.

Prefix notation:

$\exists u, v, u \overset{\circ}{\sim} \overset{\circ}{\sim} v \Leftrightarrow \exists u, v, u \overset{\circ}{\sim} \overset{\circ}{\sim} v$.

$\exists v, e, v \overset{\circ}{\sim} \overset{\circ}{\sim} e \Leftrightarrow \exists v, e, v \overset{\circ}{\sim} \overset{\circ}{\sim} e$.

$\overset{\circ}{\sim} \overset{\circ}{\sim}$ is obtained with

`\mathrel{\{\GTSmO/\GTSxa[mC=red,d]\GTSxa[mC=green,d]\GTSxa[mC=blue,u]\}}`.

$\mathrel{\mathop{\mathbb{V}}\limits^{\text{red}}\text{green}\text{blue}}]$ is obtained with
`\mathrel{\{\GTSm0/\GTSxi[mC=red,i]\GTSxi[mC=green,i]\GTSxi[mC=blue,o]\}}.`

Apart from these symbol macros, versatile macros to call them all are available with options:
`\GTSxa[]`, `\GTSxadj[]`, or `\GTSxadjacency[]` for adjacency symbols,
`\GTSxi[]`, `\GTSxinc[]`, or `\GTSxincidence[]` for incidence symbols,
`\GTSxml[]`, or `\GTSxmetallogic[]` for meta-logic symbols,
`\GTSx[]{} for all symbols`
`(\GTSx[]{a} = \GTSxa[], \GTSx[]{i} = \GTSxi[], \GTSx[]{m} = \GTSxml[]).`
 See Detailed usage section for full syntax of these macros.

2.2 Detailed usage

First you need to add in your preamble: `\usepackage{graph-theory-symbol}`.

All symbols macros were designed with ease of use in mind: they are called with a trailing slash, they can be called in text mode or in math mode, a variant with relation spacing for math mode exists with suffix “relation”.

For completeness, we also documented macros with an at sign, but as usual, you should not (have to) use them directly.

2.2.1 General macros

\GTS@newcommand This macro will enforce that the other macros are called with a trailing slash, avoiding problems with spaces after macro call.

Arguments:

`{\langle commandname \rangle}` The name of the command to create.

`{\langle commandcode \rangle}` The code of the command to create.

See its [implementation](#) on page 26.

\GTS@newprotectedcommand This macro will enforce that the other macros are called with a trailing slash, avoiding problems with spaces after macro call.

Arguments:

`{\langle commandname \rangle}` The name of the command to create.

`{\langle commandcode \rangle}` The code of the command to create.

See its [implementation](#) on page 26.

\GTSsetMainColor

This macro will set the main color used in GraphTheorySymbol. This color has initial value “black”.

Argument:

`{\langle color \rangle}` The color that must be used by GraphTheorySymbol afterward.

See its [implementation](#) on page 26.

\GTSsetSecondColor

This macro will set the second color used in GraphTheorySymbol. This color has initial value “gray”.

Argument:

`{\langle color \rangle}` The color that must be used by GraphTheorySymbol afterward.

See its [implementation](#) on page 26.

2.2.2 Standard adjacency macros

\GTS@a This macro will draw any of the adjacency symbols if the correct arguments are given. It is not expected to be used directly.

See the macros derived from it and **\GTS@b**: **\GTSxadjacency**, **\GTSxadj**, and **\GTSxa**.

Arguments:

`{\langle mainColor \rangle}` If non-empty, this color will be used as main color.

`{\langle secondColor \rangle}` If non-empty, this color will be used as second color.

`{\langle drawSlash \rangle}` Non-empty implies that a negation will be drawn.

`{\langle drawUpArrow \rangle}` Non-empty implies that an up-arrow will be drawn.

`{\langle drawDownArrow \rangle}` Non-empty implies that a down-arrow will be drawn.

See its [implementation](#) on page 27.

\GTS@b This macro builds on top of **\GTS@a** to handle mathematical relation spacing if sixth argument is not empty. It is not expected to be used directly.

See the macros derived from it and **\GTS@a**: **\GTSxadjacency**, **\GTSxadj**, and **\GTSxa**.

Arguments:

`{\langle mainColor \rangle}` If non-empty, this color will be used as main color.

`{\langle secondColor \rangle}` If non-empty, this color will be used as second color.

`{\langle drawSlash \rangle}` Non-empty implies that a negation will be drawn.

`{\langle drawUpArrow \rangle}` Non-empty implies that an up-arrow will be drawn.

`{\langle drawDownArrow \rangle}` Non-empty implies that a down-arrow will be drawn.

`{\langle relation \rangle}` Non-empty implies that relation spacing will be added.

See its [implementation](#) on page 28.

\GTSxadjacency, \GTSxadj, \GTSxa Versatile macros for adjacency that can be given options.

Argument:

[*optionsList*] Sets the following options if not empty:

mainColor=color1 or mainC=color1 or mColor=color1 or mC=color1,

secondColor=color2 or secondC=color2 or sColor=color2 or sC=color2,

monochrome or mono or mon or m (equivalent to mC=black,sC=black),

negated or not or n,

up or u,

down or d,

relation or rel or r.

See their [implementations](#) on page 28.

\GTSadjacency, \GTSadj, \GTSa These macros will draw an adjacency symbol. A first drawing didn't include the small dots in the middle of the two circles corresponding to the graph vertices. But it was too similar to “spoon” and multimap symbols, and could be confused with a graph with only two vertices and one edge. Hence, these dots were added and they have the nice property to remind of the classical textual notation of adjacency relation as Adj(.,.).

$A.\text{GTSadjacency}/A.$

or $A.\text{GTSadj}/A.$

or $A.\text{GTSa}/A.$

will yield $A.\overset{\circ}{\circ}A.$

$u\text{GTSadjacency}/v$

or $u\text{GTSadj}/v$

or $u\text{GTSa}/v$

will yield $u\overset{\circ}{\circ}v$

$\$u\text{GTSadjacency}/v\$$

or $\$u\text{GTSadj}/v\$$

or $\$u\text{GTSa}/v\$$

will yield $u\overset{\circ}{\circ}v$

See their [implementations](#) on page 28.

\GTSadjacencyRelation, \GTSadjRel, \GTSaR

These macros will draw an adjacency symbol with relation spacing in math mode.

$\$u\text{GTSadjacencyRelation}/v\$$

or $\$u\text{GTSadjRel}/v\$$

or $\$u\text{GTSaR}/v\$$

will yield $u\overset{\circ}{\circ}v$

See their [implementations](#) on page 28.

\GTSunadjacency, \GTSunadj, \GTSu These macros will draw an unadjacency symbol.

$A.\text{GTSunadjacency}/A.$

or $A.\text{GTSunadj}/A.$

or $A.\text{GTSu}/A.$

will yield $A.\overset{\circ}{\circ}A.$

$u\text{GTSunadjacency}/v$

or $u\text{GTSunadj}/v$

or $u\text{GTSu}/v$

will yield $u\overset{\circ}{\circ}v$

$\$u\text{GTSunadjacency}/v\$$

or $\$u \backslash \text{GTSunadj}/ v\$$

or $\$u \backslash \text{GTSu}/ v\$$

will yield $u \overset{\circ}{\parallel} v$.

See their [implementations](#) on page 29.

$\backslash \text{GTSunadjacencyRelation}$, $\backslash \text{GTSunadjRel}$, $\backslash \text{GTSuR}$

These macros will draw an unadjacency symbol with relation spacing in math mode.

$\$u \backslash \text{GTSunadjacencyRelation}/ v\$$

or $\$u \backslash \text{GTSunadjRel}/ v\$$

or $\$u \backslash \text{GTSuR}/ v\$$

will yield $u \overset{\circ}{\parallel} v$.

See their [implementations](#) on page 29.

$\backslash \text{GTSdirectedAdjacencyUp}$, $\backslash \text{GTSdirAdjUp}$, $\backslash \text{GTSdAU}$

These macros will draw a directed adjacency upward symbol.

The operand on the left of the symbol should be considered the source of the arc; the operand on the right of the symbol should be considered the target of the arc.

$A. \backslash \text{GTSdirectedAdjacencyUp}/ A.$

or $A. \backslash \text{GTSdirAdjUp}/ A.$

or $A. \backslash \text{GTSdAU}/ A.$

will yield $A. \overset{\circ}{\parallel} A.$.

$u \backslash \text{GTSdirectedAdjacencyUp}/ v$

or $u \backslash \text{GTSdirAdjUp}/ v$

or $u \backslash \text{GTSdAU}/ v$

will yield $u \overset{\circ}{\parallel} v$.

$\$u \backslash \text{GTSdirectedAdjacencyUp}/ v\$$

or $\$u \backslash \text{GTSdirAdjUp}/ v\$$

or $\$u \backslash \text{GTSdAU}/ v\$$

will yield $u \overset{\circ}{\parallel} v$.

See their [implementations](#) on page 29.

$\backslash \text{GTSdirectedAdjacencyUpRelation}$, $\backslash \text{GTSdirAdjUpRel}$, $\backslash \text{GTSdAUR}$

These macros will draw a directed adjacency upward symbol with relation spacing in math mode.

$\$u \backslash \text{GTSdirectedAdjacencyUpRelation}/ v\$$

or $\$u \backslash \text{GTSdirAdjUpRel}/ v\$$

or $\$u \backslash \text{GTSdAUR}/ v\$$

will yield $u \overset{\circ}{\parallel} v$.

See their [implementations](#) on page 29.

$\backslash \text{GTSnegatedDirectedAdjacencyUp}$, $\backslash \text{GTSnegDirAdjUp}$, $\backslash \text{GTSnDAU}$

These macros will draw a negated directed adjacency upward symbol.

$A. \backslash \text{GTSnegatedDirectedAdjacencyUp}/ A.$

or $A. \backslash \text{GTSnegDirAdjUp}/ A.$

or $A. \backslash \text{GTSnDAU}/ A.$

will yield $A. \overset{\circ}{\nparallel} A.$.

$u \backslash \text{GTSnegatedDirectedAdjacencyUp}/ v$

or $u \backslash \text{GTSnegDirAdjUp}/ v$

or $\boxed{u \ \backslash\text{GTSnDAU}/ \ v}$

will yield $\boxed{u \ \overset{\circ}{\curvearrowright} v}$.

$\boxed{\$u \ \backslash\text{GTSnegatedDirectedAdjacencyUp}/ \ v\$}$

or $\boxed{\$u \ \backslash\text{GTSnegDirAdjUp}/ \ v\$}$

or $\boxed{\$u \ \backslash\text{GTSnDAU}/ \ v\$}$

will yield $\boxed{u \ \overset{\circ}{\curvearrowright} v}$.

See their [implementations](#) on page 29.

$\backslash\text{GTSnegatedDirectedAdjacencyUpRelation}$, $\backslash\text{GTSnegDirAdjUpRel}$, $\backslash\text{GTSnDAUR}$

These macros will draw a negated directed adjacency upward symbol with relation spacing in math mode.

$\boxed{\$u \ \backslash\text{GTSnegatedDirectedAdjacencyUpRelation}/v\$}$

or $\boxed{\$u \ \backslash\text{GTSnegDirAdjUpRel}/v\$}$

or $\boxed{\$u \ \backslash\text{GTSnDAUR}/v\$}$

will yield $\boxed{u \ \overset{\circ}{\curvearrowright} v}$.

See their [implementations](#) on page 29.

$\backslash\text{GTSdirectedAdjacencyDown}$, $\backslash\text{GTSdirAdjDown}$, $\backslash\text{GTSdAD}$

These macros will draw a directed adjacency downward symbol.

The operand on the left of the symbol should be considered the target of the arc; the operand on the right of the symbol should be considered the source of the arc.

$\boxed{A.\backslash\text{GTSdirectedAdjacencyDown}/A.}$

or $\boxed{A.\backslash\text{GTSdirAdjDown}/A.}$

or $\boxed{A.\backslash\text{GTSdAD}/A.}$

will yield $\boxed{A.\overset{\circ}{\curvearrowright}A.}$.

$\boxed{u \ \backslash\text{GTSdirectedAdjacencyDown}/ \ v}$

or $\boxed{u \ \backslash\text{GTSdirAdjDown}/ \ v}$

or $\boxed{u \ \backslash\text{GTSdAD}/ \ v}$

will yield $\boxed{u \ \overset{\circ}{\curvearrowright} v}$.

$\boxed{\$u \ \backslash\text{GTSdirectedAdjacencyDown}/ \ v\$}$

or $\boxed{\$u \ \backslash\text{GTSdirAdjDown}/ \ v\$}$

or $\boxed{\$u \ \backslash\text{GTSdAD}/ \ v\$}$

will yield $\boxed{u \ \overset{\circ}{\curvearrowright} v}$.

See their [implementations](#) on page 29.

$\backslash\text{GTSdirectedAdjacencyDownRelation}$, $\backslash\text{GTSdirAdjDownRel}$, $\backslash\text{GTSdADR}$

These macros will draw a directed adjacency downward symbol with relation spacing in math mode.

$\boxed{\$u \ \backslash\text{GTSdirectedAdjacencyDownRelation}/v\$}$

or $\boxed{\$u \ \backslash\text{GTSdirAdjDownRel}/v\$}$

or $\boxed{\$u \ \backslash\text{GTSdADR}/v\$}$

will yield $\boxed{u \ \overset{\circ}{\curvearrowright} v}$.

See their [implementations](#) on page 29.

$\backslash\text{GTSnegatedDirectedAdjacencyDown}$, $\backslash\text{GTSnegDirAdjDown}$, $\backslash\text{GTSnDAD}$

These macros will draw a negated directed adjacency downward symbol.

$\boxed{A.\backslash\text{GTSnegatedDirectedAdjacencyDown}/A.}$

or $\boxed{A.\backslash\text{GTSnegDirAdjDown}/A.}$

or $\boxed{A.\backslash\text{GTSnDAD}/A.}$

will yield $A \not\sim A$.

`u \GTSnegatedDirectedAdjacencyDown/ v`

or `u \GTSnegDirAdjDown/ v`

or `u \GTSnDAD/ v`

will yield $u \not\sim v$.

`$u \GTSnegatedDirectedAdjacencyDown/ v$`

or `$u \GTSnegDirAdjDown/ v$`

or `$u \GTSnDAD/ v$`

will yield $u \not\sim v$.

See their [implementations](#) on page 29.

`\GTSnegatedDirectedAdjacencyDownRelation`, `\GTSnegDirAdjDownRel`, `\GTSnDADR`

These macros will draw a negated directed adjacency downward symbol with relation spacing in math mode.

`$u \GTSnegatedDirectedAdjacencyDownRelation/ v$`

or `$u \GTSnegDirAdjDownRel/ v$`

or `$u \GTSnDADR/ v$`

will yield $u \not\sim v$.

See their [implementations](#) on page 30.

2.2.3 Standard incidence macros

`\GTS@i` This macro will draw any of the incidence symbols if the correct arguments are given. It is not expected to be used directly.

See the macros derived from it and `\GTS@j`: `\GTSxincidence`, `\GTSxinc`, and `\GTSxi`.

The operand on the left of the symbol should be considered the vertex to which the edge/the operand on the right of the symbol is incident.

Arguments:

`{\mainColor}` If non-empty, this color will be used as main color.

`{\secondColor}` If non-empty, this color will be used as second color.

`{\drawSlash}` Non-empty implies that a negation will be drawn.

`{\drawUpArrow}` Non-empty implies that an up-arrow will be drawn.

`{\drawDownArrow}` Non-empty implies that a down-arrow will be drawn.

See its [implementation](#) on page 30.

`\GTS@j` This macro builds on top of `\GTS@i` to handle mathematical relation spacing if sixth argument is not empty. It is not expected to be used directly.

See the macros derived from it and `\GTS@i`: `\GTSxincidence`, `\GTSxinc`, and `\GTSxi`.

Arguments:

`{\mainColor}` If non-empty, this color will be used as main color.

`{\secondColor}` If non-empty, this color will be used as second color.

`{\drawSlash}` Non-empty implies that a negation will be drawn.

`{\drawUpArrow}` Non-empty implies that an up-arrow will be drawn.

`{\drawDownArrow}` Non-empty implies that a down-arrow will be drawn.

`{\relation}` Non-empty implies that relation spacing will be added.

See its [implementation](#) on page 31.

`\GTSxincidence`, `\GTSxinc`, `\GTSxi` Versatile macros for incidence that can be given options.

Argument:

`[\optionsList]` Sets the following options if not empty:

`mainColor=color1` or `mainC=color1` or `mColor=color1` or `mC=color1`,
`secondColor=color2` or `secondC=color2` or `sColor=color2` or `sC=color2`,
`monochrome` or `mono` or `mon` or `m` (equivalent to `mC=black,sC=black`),
`negated` or `not` or `n`,

in or i,
out or o,
relation or rel or r.
See their [implementations](#) on page 31.

\GTSincidence, \GTSinc, \GTSi These macros will draw an incidence symbol.
The operand on the left of the symbol should be considered the vertex to which the edge/the operand on the right of the symbol is incident.

`A.\GTSincidence/A.`

or `A.\GTSinc/A.`

or `A.\GTSi/A.`

will yield $A \circ A.$

`v \GTSincidence/ e`

or `v \GTSinc/ e`

or `v \GTSi/ e`

will yield $v \circ e.$

`$v \GTSincidence/ e$`

or `$v \GTSinc/ e$`

or `$v \GTSi/ e$`

will yield $v \circ e.$

See their [implementations](#) on page 31.

\GTSincidenceRelation, \GTSincRel, \GTSiR

These macros will draw an incidence symbol with relation spacing in math mode.

`$v\GTSincidenceRelation/e$`

or `$v\GTSincRel/e$`

or `$v\GTSiR/e$`

will yield $v \circ e.$

See their [implementations](#) on page 32.

\GTSnegatedIncidence, \GTSnegInc, \GTSnI

These macros will draw a negated incidence symbol.

`A.\GTSnegatedIncidence/A.`

or `A.\GTSnegInc/A.`

or `A.\GTSnI/A.`

will yield $A \not\circ A.$

`v \GTSnegatedIncidence/ e`

or `v \GTSnegInc/ e`

or `v \GTSnI/ e`

will yield $v \not\circ e.$

`$v \GTSnegatedIncidence/ e$`

or `$v \GTSnegInc/ e$`

or `$v \GTSnI/ e$`

will yield $v \not\circ e.$

See their [implementations](#) on page 32.

\GTSnegatedIncidenceRelation, \GTSnegIncRel, \GTSnIR

These macros will draw a negated incidence symbol with relation spacing in math mode.

`$v\GTSnegatedIncidenceRelation/e$`

or `$v\GTSnegIncRel/e$`

or `$v\GTSnIR/e$`

will yield $v \not\vdash e$.

See their [implementations](#) on page 32.

`\GTSoutIncidence`, `\GTSoutInc`, `\GTSoI`

These macros will draw a directed incidence upward (out(ward) incidence) symbol.

The operand on the left of the symbol should be considered the vertex to which the arc/the operand on the right of the symbol is incident.

`A.\GTSoutIncidence/A.`

or `A.\GTSoutInc/A.`

or `A.\GTSoI/A.`

will yield $A \vdash A$.

`v \GTSoutIncidence/ e`

or `v \GTSoutInc/ e`

or `v \GTSoI/ e`

will yield $v \vdash e$.

`$v \GTSoutIncidence/ e$`

or `$v \GTSoutInc/ e$`

or `$v \GTSoI/ e$`

will yield $v \vdash e$.

See their [implementations](#) on page 32.

`\GTSoutIncidenceRelation`, `\GTSoutIncRel`, `\GTSoIR` These macros will draw a directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

`$v\GTSoutIncidenceRelation/e$`

or `$v\GTSoutIncRel/e$`

or `$v\GTSoIR/e$`

will yield $v \not\vdash e$.

See their [implementations](#) on page 32.

`\GTSnegatedOutIncidence`, `\GTSnegOutInc`, `\GTSnOI`

These macros will draw a negated directed incidence upward (out(ward) incidence) symbol.

`A.\GTSnegatedOutIncidence/A.`

or `A.\GTSnegOutInc/A.`

or `A.\GTSnOI/A.`

will yield $A \not\vdash A$.

`v \GTSnegatedOutIncidence/ e`

or `v \GTSnegOutInc/ e`

or `v \GTSnOI/ e`

will yield $v \not\vdash e$.

`$v \GTSnegatedOutIncidence/ e$`

or `$v \GTSnegOutInc/ e$`

or `$v \GTSnOI/ e$`

will yield $v \not\vdash e$.

See their [implementations](#) on page 32.

\GTSnegatedOutIncidenceRelation, \GTSnegOutIncRel, \GTSnOIR These macros will draw a negated directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

$\$v\backslash\text{GTSnegatedOutIncidenceRelation}/e\$$

or $\$v\backslash\text{GTSnegOutIncRel}/e\$$

or $\$v\backslash\text{GTSnOIR}/e\$$

will yield $v \nrightarrow e$.

See their [implementations](#) on page 32.

\GTSinIncidence, \GTSinInc, \GTSiI

These macros will draw a directed incidence downward (in(ward) incidence) symbol.

The operand on the left of the symbol should be considered the vertex to which the arc/the operand on the right of the symbol is incident.

$A.\backslash\text{GTSinIncidence}/A.$

or $A.\backslash\text{GTSinInc}/A.$

or $A.\backslash\text{GTSiI}/A.$

will yield $A.\downarrow A.$

$v \backslash\text{GTSinIncidence}/ e$

or $v \backslash\text{GTSinInc}/ e$

or $v \backslash\text{GTSiI}/ e$

will yield $v \downarrow e$.

$\$v \backslash\text{GTSinIncidence}/ e\$$

or $\$v \backslash\text{GTSinInc}/ e\$$

or $\$v \backslash\text{GTSiI}/ e\$$

will yield $v \downarrow e$.

See their [implementations](#) on page 32.

\GTSinIncidenceRelation, \GTSinIncRel, \GTSiIR These macros will draw a directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.

$\$v\backslash\text{GTSinIncidenceRelation}/e\$$

or $\$v\backslash\text{GTSinIncRel}/e\$$

or $\$v\backslash\text{GTSiIR}/e\$$

will yield $v \downarrow e$.

See their [implementations](#) on page 32.

\GTSnegatedInIncidence, \GTSnegInInc, \GTSnII

These macros will draw a negated directed incidence downward (in(ward) incidence) symbol.

$A.\backslash\text{GTSnegatedInIncidence}/A.$

or $A.\backslash\text{GTSnegInInc}/A.$

or $A.\backslash\text{GTSnII}/A.$

will yield $A.\nrightarrow A.$

$v \backslash\text{GTSnegatedInIncidence}/ e$

or $v \backslash\text{GTSnegInInc}/ e$

or $v \backslash\text{GTSnII}/ e$

will yield $v \nrightarrow e$.

$\$v \backslash\text{GTSnegatedInIncidence}/ e\$$

or $A.\backslash\text{GTSunadjMono}/A.$

or $A.\backslash\text{GTSunadjMon}/A.$

or $A.\backslash\text{GTSuM}/A.$

will yield $A.\overset{\circ}{\circ}A.$

$u\backslash\text{GTSunadjacencyMonochrome}/v$

or $u\backslash\text{GTSunadjMono}/v$

or $u\backslash\text{GTSunadjMon}/v$

or $u\backslash\text{GTSuM}/v$

will yield $u\overset{\circ}{\circ}v$.

$\$u\backslash\text{GTSunadjacencyMonochrome}/v\$$

or $\$u\backslash\text{GTSunadjMono}/v\$$

or $\$u\backslash\text{GTSunadjMon}/v\$$

or $\$u\backslash\text{GTSuM}/v\$$

will yield $u\overset{\circ}{\circ}v$.

See their [implementations](#) on page 33.

$\backslash\text{GTSunadjacencyMonochromeRelation}$, $\backslash\text{GTSunadjMonoRel}$, $\backslash\text{GTSunadjMonRel}$,
 $\backslash\text{GTSuMR}$

These macros will draw a monochrome unadjacency symbol with relation spacing in math mode.

$\$u\backslash\text{GTSunadjacencyMonochromeRelation}/v\$$

or $\$u\backslash\text{GTSunadjMonoRel}/v\$$

or $\$u\backslash\text{GTSunadjMonRel}/v\$$

or $\$u\backslash\text{GTSuMR}/v\$$

will yield $u\overset{\circ}{\circ}v$.

See their [implementations](#) on page 33.

$\backslash\text{GTSdirectedAdjacencyUpMonochrome}$, $\backslash\text{GTSdirAdjUpMono}$, $\backslash\text{GTSdirAdjUpMon}$,
 $\backslash\text{GTSdAUM}$

These macros will draw a monochrome directed adjacency upward symbol.

The operand on the left of the symbol should be considered the source of the arc; the operand on the right of the symbol should be considered the target of the arc.

$A.\backslash\text{GTSdirectedAdjacencyUpMonochrome}/A.$

or $A.\backslash\text{GTSdirAdjUpMono}/A.$

or $A.\backslash\text{GTSdirAdjUpMon}/A.$

or $A.\backslash\text{GTSdAUM}/A.$

will yield $A.\overset{\circ}{\circ}A.$

$u\backslash\text{GTSdirectedAdjacencyUpMonochrome}/v$

or $u\backslash\text{GTSdirAdjUpMono}/v$

or $u\backslash\text{GTSdirAdjUpMon}/v$

or $u\backslash\text{GTSdAUM}/v$

will yield $u\overset{\circ}{\circ}v$.

$\$u\backslash\text{GTSdirectedAdjacencyUpMonochrome}/v\$$

or $\$u\backslash\text{GTSdirAdjUpMono}/v\$$

or $\$u\backslash\text{GTSdirAdjUpMon}/v\$$

or $\$u\backslash\text{GTSdAUM}/v\$$

will yield $u \circ v$.

See their [implementations](#) on page 33.

\GTSdirectedAdjacencyUpMonochromeRelation, \GTSdirAdjUpMonoRel, \GTSdirAdjUpMonRel, \GTSdAUMR These macros will draw a monochrome directed adjacency upward symbol with relation spacing in math mode.

$\$u\backslash\text{GTSdirectedAdjacencyUpMonochromeRelation}/v\$$

or $\$u\backslash\text{GTSdirAdjUpMonoRel}/v\$$

or $\$u\backslash\text{GTSdirAdjUpMonRel}/v\$$

or $\$u\backslash\text{GTSdAUMR}/v\$$

will yield $u \circ v$.

See their [implementations](#) on page 33.

\GTSnegatedDirectedAdjacencyUpMonochrome, \GTSnegDirAdjUpMono, \GTSnDAUM

These macros will draw a monochrome negated directed adjacency upward symbol.

$A.\backslash\text{GTSnegatedDirectedAdjacencyUpMonochrome}/A.$

or $A.\backslash\text{GTSnegDirAdjUpMono}/A.$

or $A.\backslash\text{GTSnegDirAdjUpMon}/A.$

or $A.\backslash\text{GTSnDAUM}/A.$

will yield $A \circ A$.

$u \backslash\text{GTSnegatedDirectedAdjacencyUpMonochrome}/ v$

or $u \backslash\text{GTSnegDirAdjUpMono}/ v$

or $u \backslash\text{GTSnegDirAdjUpMon}/ v$

or $u \backslash\text{GTSnDAUM}/ v$

will yield $u \circ v$.

$\$u \backslash\text{GTSnegatedDirectedAdjacencyUpMonochrome}/ v\$$

or $\$u \backslash\text{GTSnegDirAdjUpMono}/ v\$$

or $\$u \backslash\text{GTSnegDirAdjUpMon}/ v\$$

or $\$u \backslash\text{GTSnDAUM}/ v\$$

will yield $u \circ v$.

See their [implementations](#) on page 34.

\GTSnegatedDirectedAdjacencyUpMonochromeRelation, \GTSnegDirAdjUpMonoRel, \GTSnegDirAdjUpMonRel, \GTSnDAUMR These macros will draw a monochrome negated directed adjacency upward symbol with relation spacing in math mode.

$\$u\backslash\text{GTSnegatedDirectedAdjacencyUpMonochromeRelation}/v\$$

or $\$u\backslash\text{GTSnegDirAdjUpMonoRel}/v\$$

or $\$u\backslash\text{GTSnegDirAdjUpMonRel}/v\$$

or $\$u\backslash\text{GTSnDAUMR}/v\$$

will yield $u \circ v$.

See their [implementations](#) on page 34.

\GTSdirectedAdjacencyDownMonochrome, \GTSdirAdjDownMono, \GTSdirAdjDownMon, \GTSdADM

These macros will draw a monochrome directed adjacency downward symbol.

The operand on the left of the symbol should be considered the target of the arc; the operand on the right of the symbol should be considered the source of the arc.

`A.\GTSdirectedAdjacencyDownMonochrome/A.`

or `A.\GTSdirAdjDownMono/A.`

or `A.\GTSdirAdjDownMon/A.`

or `A.\GTSdADM/A.`

will yield $A \circ A.$

`u \GTSdirectedAdjacencyDownMonochrome/ v`

or `u \GTSdirAdjDownMono/ v`

or `u \GTSdirAdjDownMon/ v`

or `u \GTSdADM/ v`

will yield $u \circ v.$

`$u \GTSdirectedAdjacencyDownMonochrome/ v$`

or `$u \GTSdirAdjDownMono/ v$`

or `$u \GTSdirAdjDownMon/ v$`

or `$u \GTSdADM/ v$`

will yield $u \circ v.$

See their [implementations](#) on page 34.

`\GTSdirectedAdjacencyDownMonochromeRelation`, `\GTSdirAdjDownMonoRel`, `\GTSdirAdjDownMonRel`, `\GTSdADMR` These macros will draw a monochrome directed adjacency downward symbol with relation spacing in math mode.

`$u\GTSdirectedAdjacencyDownMonochromeRelation/v$`

or `$u\GTSdirAdjDownMonoRel/v$`

or `$u\GTSdirAdjDownMonRel/v$`

or `$u\GTSdADMR/v$`

will yield $u \circ v.$

See their [implementations](#) on page 34.

`\GTSnegatedDirectedAdjacencyDownMonochrome`, `\GTSnegDirAdjDownMono`, `\GTSnegDirAdjDownMon`, `\GTSnDADM`

These macros will draw a monochrome negated directed adjacency downward symbol.

`A.\GTSnegatedDirectedAdjacencyDownMonochrome/A.`

or `A.\GTSnegDirAdjDownMono/A.`

or `A.\GTSnegDirAdjDownMon/A.`

or `A.\GTSnDADM/A.`

will yield $A \circ A.$

`u \GTSnegatedDirectedAdjacencyDownMonochrome/ v`

or `u \GTSnegDirAdjDownMono/ v`

or `u \GTSnegDirAdjDownMon/ v`

or `u \GTSnDADM/ v`

will yield $u \circ v.$

`$u \GTSnegatedDirectedAdjacencyDownMonochrome/ v$`

or `$u \GTSnegDirAdjDownMono/ v$`

or `$u \GTSnegDirAdjDownMon/ v$`

or `$u \GTSnDADM/ v$`

will yield $u \circ v.$

See their [implementations](#) on page 34.

`\GTSnegatedDirectedAdjacencyDownMonochromeRelation`, `\GTSnegDirAdjDownMonoRel`, `\GTSnegDirAdjDownMonRel`, `\GTSnDADMR` These macros will draw a monochrome negated directed adjacency downward symbol with relation spacing in math mode.

`\$u\GTSnegatedDirectedAdjacencyDownMonochromeRelation/v\$`
 or `\$u\GTSnegDirAdjDownMonoRel/v\$`
 or `\$u\GTSnegDirAdjDownMonRel/v\$`
 or `\$u\GTSnDADMR/v\$`
 will yield $u \nrightarrow v$.

See their [implementations](#) on page 35.

2.2.5 Monochrome incidence macros

`\GTSincidenceMonochrome`, `\GTSincMono`, `\GTSincMon`, `\GTSiM`

These macros will draw a monochrome incidence symbol.

The operand on the left of the symbol should be considered the vertex to which the edge/the operand on the right of the symbol is incident.

`A.\GTSincidenceMonochrome/A.`
 or `A.\GTSincMono/A.`
 or `A.\GTSincMon/A.`
 or `A.\GTSiM/A.`
 will yield $A \downarrow A$.

`v \GTSincidenceMonochrome/ e`
 or `v \GTSincMono/ e`
 or `v \GTSincMon/ e`
 or `v \GTSiM/ e`
 will yield $v \downarrow e$.

`\$v \GTSincidenceMonochrome/ e\$`
 or `\$v \GTSincMono/ e\$`
 or `\$v \GTSincMon/ e\$`
 or `\$v \GTSiM/ e\$`
 will yield $v \downarrow e$.

See their [implementations](#) on page 35.

`\GTSincidenceMonochromeRelation`, `\GTSincMonoRel`, `\GTSincMonRel`, `\GTSiMR`

These macros will draw a monochrome incidence symbol with relation spacing in math mode.

`\$v\GTSincidenceMonochromeRelation/e\$`
 or `\$v\GTSincMonoRel/e\$`
 or `\$v\GTSincMonRel/e\$`
 or `\$v\GTSiMR/e\$`
 will yield $v \downarrow e$.

See their [implementations](#) on page 35.

`\GTSnegatedIncidenceMonochrome`, `\GTSnegIncMono`, `\GTSnegIncMon`, `\GTSnIM`

These macros will draw a monochrome negated incidence symbol.

`A.\GTSnegatedIncidenceMonochrome/A.`
 or `A.\GTSnegIncMono/A.`
 or `A.\GTSnegIncMon/A.`

or `A.\GTSnIM/A.`

will yield $A \not\bowtie A$.

`v \GTSnegatedIncidenceMonochrome/ e`

or `v \GTSnegIncMono/ e`

or `v \GTSnegIncMon/ e`

or `v \GTSnIM/ e`

will yield $v \not\bowtie e$.

`$v \GTSnegatedIncidenceMonochrome/ e$`

or `$v \GTSnegIncMono/ e$`

or `$v \GTSnegIncMon/ e$`

or `$v \GTSnIM/ e$`

will yield $v \not\bowtie e$.

See their [implementations](#) on page 35.

`\GTSnegatedIncidenceMonochromeRelation`, `\GTSnegIncMonoRel`, `\GTSnegIncMonRel`, `\GTSnIMR`

These macros will draw a monochrome negated incidence symbol with relation spacing in math mode.

`$v\GTSnegatedIncidenceMonochromeRelation/e$`

or `$v\GTSnegIncMonoRel/e$`

or `$v\GTSnegIncMonRel/e$`

or `$v\GTSnIMR/e$`

will yield $v \not\bowtie e$.

See their [implementations](#) on page 35.

`\GTSoutIncidenceMonochrome`, `\GTSoutIncMono`, `\GTSoutIncMon`, `\GTSoIM`

These macros will draw a monochrome directed incidence upward (out(ward) incidence) symbol.

The operand on the left of the symbol should be considered the vertex to which the arc/the operand on the right of the symbol is incident.

`A.\GTSoutIncidenceMonochrome/A.`

or `A.\GTSoutIncMono/A.`

or `A.\GTSoutIncMon/A.`

or `A.\GTSoIM/A.`

will yield $A \not\bowtie A$.

`v \GTSoutIncidenceMonochrome/ e`

or `v \GTSoutIncMono/ e`

or `v \GTSoutIncMon/ e`

or `v \GTSoIM/ e`

will yield $v \not\bowtie e$.

`$v \GTSoutIncidenceMonochrome/ e$`

or `$v \GTSoutIncMono/ e$`

or `$v \GTSoutIncMon/ e$`

or `$v \GTSoIM/ e$`

will yield $v \not\bowtie e$.

See their [implementations](#) on page 35.

`\GTSoutIncidenceMonochromeRelation`, `\GTSoutIncMonoRel`, `\GTSoutIncMonRel`, `\GTSoIMR` These macros will draw a monochrome directed incidence upward (out(ward) incidence)

symbol with relation spacing in math mode.

`$v\GTSoutIncidenceMonochromeRelation/e$`

or `$v\GTSoutIncMonoRel/e$`

or `$v\GTSoutIncMonRel/e$`

or `$v\GTSoIMR/e$`

will yield $v \nmid e$.

See their [implementations](#) on page 35.

\GTSnegatedOutIncidenceMonochrome, \GTSnegOutIncMono, \GTSnegOutIncMon, \GTSnOIM

These macros will draw a monochrome negated directed incidence upward (out(ward) incidence) symbol.

`A.\GTSnegatedOutIncidenceMonochrome/A.`

or `A.\GTSnegOutIncMono/A.`

or `A.\GTSnegOutIncMon/A.`

or `A.\GTSnOIM/A.`

will yield $A.\nrightarrow A.$

`v \GTSnegatedOutIncidenceMonochrome/ e`

or `v \GTSnegOutIncMono/ e`

or `v \GTSnegOutIncMon/ e`

or `v \GTSnOIM/ e`

will yield $v \nrightarrow e$

`$v \GTSnegatedOutIncidenceMonochrome/ e$`

or `$v \GTSnegOutIncMono/ e$`

or `$v \GTSnegOutIncMon/ e$`

or `$v \GTSnOIM/ e$`

will yield $v \nrightarrow e$

See their [implementations](#) on page 36.

\GTSnegatedOutIncidenceMonochromeRelation, \GTSnegOutIncMonoRel,

\GTSnegOutIncMonRel, \GTSnOIMR These macros will draw a monochrome negated directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

`$v\GTSnegatedOutIncidenceMonochromeRelation/e$`

or `$v\GTSnegOutIncMonoRel/e$`

or `$v\GTSnegOutIncMonRel/e$`

or `$v\GTSnOIMR/e$`

will yield $v \nrightarrow e$

See their [implementations](#) on page 36.

\GTSinIncidenceMonochrome, \GTSinIncMono, \GTSinIncMon, \GTSiIM

These macros will draw a monochrome directed incidence downward (in(ward) incidence) symbol.

The operand on the left of the symbol should be considered the vertex to which the arc/the operand on the right of the symbol is incident.

`A.\GTSinIncidenceMonochrome/A.`

or `A.\GTSinIncMono/A.`

or `A.\GTSinIncMon/A.`

or `A.\GTSiIM/A.`

will yield $A.\rightarrow A.$

`v \GTSinIncidenceMonochrome/ e`

or `v \GTSinIncMono/ e`

or `v \GTSinIncMon/ e`

or `v \GTSiIM/ e`

will yield $v \rightarrow e$

`$v \GTSinIncidenceMonochrome/ e$`

or $\$v \backslash \text{GTSinIncMono}/ e\$$
or $\$v \backslash \text{GTSinIncMon}/ e\$$
or $\$v \backslash \text{GTSiIM}/ e\$$

will yield $v \Downarrow e$.

See their [implementations](#) on page 36.

$\backslash \text{GTSinIncidenceMonochromeRelation}$, $\backslash \text{GTSinIncMonoRel}$, $\backslash \text{GTSinIncMonRel}$, $\backslash \text{GTS-iIMR}$ These macros will draw a monochrome directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.

$\$v \backslash \text{GTSinIncidenceMonochromeRelation}/ e\$$
or $\$v \backslash \text{GTSinIncMonoRel}/ e\$$
or $\$v \backslash \text{GTSinIncMonRel}/ e\$$
or $\$v \backslash \text{GTSiIMR}/ e\$$

will yield $v \Downarrow e$.

See their [implementations](#) on page 36.

$\backslash \text{GTSnegatedInIncidenceMonochrome}$, $\backslash \text{GTSnegInIncMono}$, $\backslash \text{GTSnegInIncMon}$, $\backslash \text{GTS-nIIM}$

These macros will draw a monochrome negated directed incidence downward (in(ward) incidence) symbol.

$A. \backslash \text{GTSnegatedInIncidenceMonochrome}/ A.$
or $A. \backslash \text{GTSnegInIncMono}/ A.$
or $A. \backslash \text{GTSnegInIncMon}/ A.$
or $A. \backslash \text{GTSnIIM}/ A.$

will yield $A. \Downarrow A.$.

$v \backslash \text{GTSnegatedInIncidenceMonochrome}/ e$
or $v \backslash \text{GTSnegInIncMono}/ e$
or $v \backslash \text{GTSnegInIncMon}/ e$
or $v \backslash \text{GTSnIIM}/ e$

will yield $v \Downarrow e$.

$\$v \backslash \text{GTSnegatedInIncidenceMonochrome}/ e\$$
or $\$v \backslash \text{GTSnegInIncMono}/ e\$$
or $\$v \backslash \text{GTSnegInIncMon}/ e\$$
or $\$v \backslash \text{GTSnIIM}/ e\$$

will yield $v \Downarrow e$.

See their [implementations](#) on page 36.

$\backslash \text{GTSnegatedInIncidenceMonochromeRelation}$, $\backslash \text{GTSnegInIncMonoRel}$, $\backslash \text{GTSnegInIncMonRel}$, $\backslash \text{GTSnIIMR}$ These macros will draw a monochrome negated directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.

$\$v \backslash \text{GTSnegatedInIncidenceMonochromeRelation}/ e\$$
or $\$v \backslash \text{GTSnegInIncMonoRel}/ e\$$
or $\$v \backslash \text{GTSnegInIncMonRel}/ e\$$
or $\$v \backslash \text{GTSnIIMR}/ e\$$

will yield $v \Downarrow e$.

See their [implementations](#) on page 36.

2.2.6 Meta-logic macros

\GTSmetaNot, \GTSMN These macros will draw a meta-not or relation-not symbol.

$A.\text{\GTSmetaNot}/A.$

or $A.\text{\GTSMN}/A.$

will yield $A.\text{\textcircled{\tiny{N}}}A.$

$u \text{\GTSmetaNot}/\text{\GTSdAU}/ v$

or $u \text{\GTSMN}/\text{\GTSdAU}/ v$

will yield $u \text{\textcircled{\tiny{N}}} v.$

$\$u \text{\GTSmetaNot}/ \text{\GTSdAU}/ v\$$

or $\$u \text{\GTSMN}/ \text{\GTSdAU}/ v\$$

will yield $u\text{\textcircled{\tiny{N}}}v.$

See their [implementations](#) on page 36.

\GTSmetaAnd, \GTSMa These macros will draw a meta-and or relations-and symbol. This is your duty to check that all relations have same arity. It should be easy as long as you remain in the realm of graphs/2-structures/binary structures. We didn't use Tarski's notation, since square cup has taken the preemptive meaning of disjoint union. Similarly, doublewedge or other wedge symbols have taken various meanings, whilst we want an unambiguous symbol.

Look at the discussion after all logical symbols for less trivial uses and recommendations.

$A.\text{\GTSmetaAnd}/A.$

or $A.\text{\GTSMa}/A.$

will yield $A.\text{\textcircled{\tiny{A}}}A.$

$u \text{\GTSdAD}/\text{\GTSmetaAnd}/\text{\GTSdAU}/ v$

or $u \text{\GTSdAD}/\text{\GTSMa}/\text{\GTSdAU}/ v$

will yield $u \text{\textcircled{\tiny{A}}} v.$

$\$u \text{\GTSdAD}/ \text{\GTSmetaAnd}/ \text{\GTSdAU}/ v\$$

or $\$u \text{\GTSdAD}/ \text{\GTSMa}/ \text{\GTSdAU}/ v\$$

will yield $u\text{\textcircled{\tiny{A}}}v.$

See their [implementations](#) on page 37.

\GTSmetaAndRelation, \GTSmetaAndRel, \GTSMaR

These macros will draw a meta-and symbol with relation spacing in math mode.

$\$u \text{\GTSdAD}/\text{\GTSmetaAndRelation}/\text{\GTSdAU}/ v\$$

or $\$u \text{\GTSdAD}/\text{\GTSmetaAndRel}/\text{\GTSdAU}/ v\$$

or $\$u \text{\GTSdAD}/\text{\GTSMaR}/\text{\GTSdAU}/ v\$$

will yield $u\text{\textcircled{\tiny{A}}}v.$

See their [implementations](#) on page 37.

\GTSmetaOr, \GTSMo These macros will draw a meta-or or relations-or symbol. This is your duty to check that all relations have same arity. It should be easy as long as you remain in the realm of graphs/2-structures/binary structures. We didn't use Tarski's notation, since square cup has taken the preemptive meaning of disjoint union. Similarly, doublewedge or other wedge symbols have taken various meanings, whilst we want an unambiguous symbol.

Look at the discussion after all logical symbols for less trivial uses and recommendations.

$A.\text{\GTSmetaOr}/A.$

or $A.\text{\GTSMo}/A.$

will yield $A.\text{\textcircled{\tiny{O}}}A.$

$u \text{\GTSdAD}/\text{\GTSmetaOr}/\text{\GTSdAU}/ v$

or $u \text{\GTSdAD}/\text{\GTSMo}/\text{\GTSdAU}/ v$

will yield $u \text{\textcircled{\tiny{O}}} v.$

$\$u \text{\GTSdAD}/ \text{\GTSmetaOr}/ \text{\GTSdAU}/ v\$$

or $\$u \text{\GTSdAD}/ \text{\GTSMo}/ \text{\GTSdAU}/ v\$$

will yield $u\text{\textcircled{\tiny{O}}}v.$

See their [implementations](#) on page 37.

\GTSmetaOrRelation, \GTSmetaOrRel, \GTSMoR

These macros will draw a meta-or symbol with relation spacing in math mode.

$\$u \text{\GTSdAD}/\text{\GTSmetaOrRelation}/\text{\GTSdAU}/ v\$$

or $\$u \text{\GTSdAD}/\text{\GTSmetaOrRel}/\text{\GTSdAU}/ v\$$

or $\$u \text{\GTSdAD}/\text{\GTSMoR}/\text{\GTSdAU}/ v\$$

will yield $u \mathrel{\mathbb{V}} v$.

See their [implementations](#) on page 37.

\GTSxmetallogic, \GTSxml Versatile macros for meta-logic symbols that can be given options.

Argument:

[*\langle optionsList \rangle*] Sets the following options if not empty:

not or **n**,
and or **a**,
or or **o**,
relation or **rel** or **r**.

Of course first three options are incompatible, and the fourth is compatible only with the second and third options.

See their [implementations](#) on page 38.

\GTSx One macro to rule them all.

Versatile macro for all symbols that can be given options, and a symbol type mandatory switch.

Argument:

[*\langle optionsList \rangle*] Sets the following options if not empty:

- If $\{\langle symbolType \rangle\}$ below is **a**, see **\GTSxa**:
mainColor=color1 or **mainC=**color1 or **mColor=**color1 or **mC=**color1,
secondColor=color2 or **secondC=**color2 or **sColor=**color2 or **sC=**color2,
monochrome or **mono** or **mon** or **m** (equivalent to **mC=black,sC=black**),
negated or **not** or **n**,
up or **u**,
down or **d**,
relation or **rel** or **r**.
- If $\{\langle symbolType \rangle\}$ below is **i**, see **\GTSxi**:
mainColor=color1 or **mainC=**color1 or **mColor=**color1 or **mC=**color1,
secondColor=color2 or **secondC=**color2 or **sColor=**color2 or **sC=**color2,
monochrome or **mono** or **mon** or **m** (equivalent to **mC=black,sC=black**),
negated or **not** or **n**,
in or **i**,
out or **o**,
relation or **rel** or **r**.
- If $\{\langle symbolType \rangle\}$ below is **m**, see **\GTSxml**:
not or **n**,
and or **a**,
or or **o**,
relation or **rel** or **r**.

$\{\langle symbolType \rangle\}$ a mandatory switch; it can take value **a** for adjacency, **i** for incidence, **m** for meta-logic.

See its [implementation](#) on page 38.

2.3 Good practices

As is customary in algebra and logic, the conjunction/multiplication can be replaced by concatenation, and has higher priority than disjunction. So the following formulas are equivalent; we recommend using the shortest one:

Tournament adjacency:

$\forall u, v, u \mathrel{\mathbb{V}} v$

is preferred over

$\forall u, v, u \mathrel{\mathbb{V}} v$

or $\forall u, v, u \mathrel{\mathbb{V}} v$

or even $\forall u, v, ((u \mathrel{\mathbb{V}} v) \wedge (u \mathrel{\mathbb{V}} v)) \vee ((u \mathrel{\mathbb{V}} v) \wedge (u \mathrel{\mathbb{V}} v))$.

Note the use of macros without Relation suffix above, and adding a single **\mathrel{}** around the composition of all relations:

\mathrel{\{\GTSdAD/\GTSnDAU/\GTSmO/\GTSnDAD/\GTSdAU\}}.

This is the spacing practice that we recommend, although for very long compositions, it may be quite unreadable, and then spacing everything with Relation could/should be preferred.

We also recommend using brackets when the composition reflects all of the adjacencies between two vertices:

Tournament adjacency:

$\forall u, v, u \overset{\text{m}}{\underset{\text{m}}{\text{V}}} v.$

Tournament adjacency with maybe some colored edge also, who knows?:

$\forall u, v, u \overset{\text{m}}{\underset{\text{m}}{\text{V}}} v.$

Directed graph:

$\forall u, v, u \overset{\text{m}}{\underset{\text{m}}{\text{V}}} \overset{\text{m}}{\underset{\text{m}}{\text{V}}} v.$

Oriented graph:

$\forall u, v, u \overset{\text{m}}{\underset{\text{m}}{\text{V}}} \overset{\text{m}}{\underset{\text{m}}{\text{V}}} v.$

Finally, we recommend prefix notation without “big” symbol for a sequence of consecutive ors or ands (with parentheses if needed):

$\exists u, v, u \overset{\text{m}}{\underset{\text{m}}{\text{V}}} v.$

$\exists v, e, v \overset{\text{m}}{\underset{\text{m}}{\text{V}}} e.$

3 Implementation

Below, we try to avoid repeating each macro description, and we give a hyperlink plus a page number reference of its description, after macro name(s). But if the description is only one sentence, we do repeat it here, because it makes no sense to have to go back and forth in the text for only one sentence.

```

1 \*package
2 \RequirePackage{amsmath}
3 \RequirePackage{amssymb}
4 \RequirePackage{graphicx}
5 \RequirePackage{keyval}
6 \RequirePackage{fdsymbol}
7 \RequirePackage{lua-unicode-math}
8 \RequirePackage{xcolor}
9
10 \def\GTS@mainColor{black}
11 \def\GTS@secondColor{gray}
12 \def\GTS@mainColorBackup{black}
13 \def\GTS@secondColorBackup{gray}
14 \def\GTS@drawSlash{}
15 \def\GTS@drawUpArrow{}
16 \def\GTS@drawDownArrow{}
17

```

\GTS@newcommand See its [description](#) on page 7.

```

18 \@ifdefinable{\GTS@newcommand}{\def\GTS@newcommand#1#2{%
19   \@ifdefinable{#1}{\def#1/{#2}}
20 }}

```

\GTS@newprotectedcommand See its [description](#) on page 7.

```

21 \@ifdefinable{\GTS@newprotectedcommand}{\def\GTS@newprotectedcommand#1#2{%
22   \@ifdefinable{#1}{\protected\def#1/{#2}}
23 }}

```

\GTSsetMainColor See its [description](#) on page 7.

```

24 \newcommand{\GTSsetMainColor}[1]{%
25 \edef\GTS@mainColorTemp{#1}%
26 \edef\GTS@mainColorBackup{\GTS@mainColor}%
27 \edef\GTS@mainColor{\GTS@mainColorTemp}%
28 }

```

\GTSsetSecondColor See its [description](#) on page 7.

```

29 \newcommand{\GTSsetSecondColor}[1]{%
30 \edef\GTS@secondColorTemp{#1}%
31 \edef\GTS@secondColorBackup{\GTS@secondColor}%
32 \edef\GTS@secondColor{\GTS@secondColorTemp}%
33 }

```

`\GTS@a` See its [description](#) on page 7.

```

34 \newcommand{\GTS@a}[5]{%
35 \if#1\empty\else%
36 \GTSsetMainColor{#1}%
37 \fi%
38 \if#2\empty\else%
39 \GTSsetSecondColor{#2}%
40 \fi%
41 \text{\ensuremath{%
42 \raisebox{-0.32ex}{\scalebox{1.5}[1.5]{%
43 %
44 \raisebox{0.7ex}{\scalebox{0.7}[0.7]{%
45 $\mathcolor{\GTS@secondColor}{\circ}$%
46 }}%
47 \hspace{-0.39ex}%
48 \raisebox{1.05ex}{\scalebox{0.1}[0.1]{%
49 $\mathcolor{\GTS@secondColor}{\bullet}$%
50 }}%
51 \hspace{-0.12ex}%
52 \raisebox{0.11ex}{\scalebox{0.1}[0.73]{%
53 $\mathcolor{\GTS@mainColor}{\smallblacksquare}$%
54 }}%
55 \hspace{-0.40ex}%
56 \raisebox{-0.3ex}{\scalebox{0.7}[0.7]{%
57 $\mathcolor{\GTS@secondColor}{\circ}$%
58 }}%
59 \hspace{-0.39ex}%
60 \raisebox{0.05ex}{\scalebox{0.1}[0.1]{%
61 $\mathcolor{\GTS@secondColor}{\bullet}$%
62 }}%
63 \hspace{0.27ex}%
if GTS@drawUpArrow empty else
64 \if#4\empty\else%
65 \hspace{-0.65ex}%
66 \raisebox{-0.18ex}{\scalebox{0.5}[0.5]{%
67 \textcolor{\GTS@mainColor}{\textasciicircum}%
68 }}%
69 \fi%
if GTS@drawDownArrow empty else
70 \if#5\empty\else%
71 \hspace{-0.65ex}%
72 \raisebox{1.37ex}{\scalebox{0.5}[-0.5]{%
73 \textcolor{\GTS@mainColor}{\textasciicircum}%
74 }}%
75 \fi%
if GTS@drawSlash empty else
76 \if#3\empty\else%
77 \hspace{-0.65ex}%
78 \raisebox{0.25ex}{\scalebox{0.6}[0.6]{%
79 \textcolor{black}{/}%
80 }}%
81 \fi%
82 %
83 }}%
84 }}%
85 \if#1\empty\else%
86 \GTSsetMainColor{\GTS@mainColorBackup}%
87 \fi%
88 \if#2\empty\else%
89 \GTSsetSecondColor{\GTS@secondColorBackup}%
90 \fi%
91 }

```

`\GTS@b` See its [description](#) on page 7.

```

92 \newcommand{\GTS@b}[6]{%
93 \if#61%
94 \mathrel{\GTS@a{#1}{#2}{#3}{#4}{#5}}%
95 \else%
96 \GTS@a{#1}{#2}{#3}{#4}{#5}%
97 \fi%
98 }

```

`\GTSxadjacency`, `\GTSxadj`, `\GTSxa` See their [description](#) on page 8.

```

99 \define@key{GTSxa}{mainColor}{\def\GTS@@mainColor{#1}}
100 \define@key{GTSxa}{mainC}{\def\GTS@@mainColor{#1}}
101 \define@key{GTSxa}{mColor}{\def\GTS@@mainColor{#1}}
102 \define@key{GTSxa}{mC}{\def\GTS@@mainColor{#1}}
103 \define@key{GTSxa}{secondColor}{\def\GTS@@secondColor{#1}}
104 \define@key{GTSxa}{secondC}{\def\GTS@@secondColor{#1}}
105 \define@key{GTSxa}{sColor}{\def\GTS@@secondColor{#1}}
106 \define@key{GTSxa}{sC}{\def\GTS@@secondColor{#1}}
107 \define@key{GTSxa}{monochrome}[1]%
108 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
109 \define@key{GTSxa}{mono}[1]%
110 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
111 \define@key{GTSxa}{mon}[1]%
112 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
113 \define@key{GTSxa}{m}[1]%
114 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
115 \define@key{GTSxa}{negated}[1]{\def\GTS@@drawSlash{1}}
116 \define@key{GTSxa}{not}[1]{\def\GTS@@drawSlash{1}}
117 \define@key{GTSxa}{n}[1]{\def\GTS@@drawSlash{1}}
118 \define@key{GTSxa}{up}[1]{\def\GTS@@drawUpArrow{1}}
119 \define@key{GTSxa}{u}[1]{\def\GTS@@drawUpArrow{1}}
120 \define@key{GTSxa}{down}[1]{\def\GTS@@drawDownArrow{1}}
121 \define@key{GTSxa}{d}[1]{\def\GTS@@drawDownArrow{1}}
122 \define@key{GTSxa}{relation}[1]{\def\GTS@@relation{1}}
123 \define@key{GTSxa}{rel}[1]{\def\GTS@@relation{1}}
124 \define@key{GTSxa}{r}[1]{\def\GTS@@relation{1}}
125
126 \newcommand{\GTSxa}[1][ ]{%
127 \def\GTS@@mainColor{}%
128 \def\GTS@@secondColor{}%
129 \def\GTS@@drawSlash{}%
130 \def\GTS@@drawUpArrow{}%
131 \def\GTS@@drawDownArrow{}%
132 \def\GTS@@relation{}%
133 \setkeys{GTSxa}{#1}%
134 \GTS@b{\GTS@@mainColor}{\GTS@@secondColor}{\GTS@@drawSlash}%
135 {\GTS@@drawUpArrow}{\GTS@@drawDownArrow}{\GTS@@relation}%
136 }
137
138 \newcommand{\GTSxadj}[1][ ]{\GTSxa[#1]}
139
140 \newcommand{\GTSxadjacency}[1][ ]{\GTSxa[#1]}

```

`\GTSadjacency`, `\GTSadj`, `\GTSa` These macros will draw an adjacency symbol.
See their [description](#) and usage examples on page 8.

```

141 \GTS@newcommand{\GTSadjacency}{\GTS@a{}{}{}{}}
142 \GTS@newcommand{\GTSadj}{\GTS@a{}{}{}{}}
143 \GTS@newcommand{\GTSa}{\GTS@a{}{}{}{}}

```

`\GTSadjacencyRelation`, `\GTSadjRel`, `\GTSaR`

These macros will draw an adjacency symbol with relation spacing in math mode.
See their [description](#) and usage examples on page 8.

```

144 \GTS@newcommand{\GTSadjacencyRelation}{\mathrel{\GTSa/}}
145 \GTS@newcommand{\GTSadjRel}{\mathrel{\GTSa/}}
146 \GTS@newcommand{\GTSaR}{\mathrel{\GTSa/}}

```

\GTSunadjacency, \GTSunadj, \GTSu These macros will draw an unadjacency symbol. See their [description](#) and usage examples on page 8.

```
147 \GTS@newcommand{\GTSunadjacency}{\GTS@a{}}{1}{1}{}{}
148 \GTS@newcommand{\GTSunadj}{\GTS@a{}}{1}{1}{}{}
149 \GTS@newcommand{\GTSu}{\GTS@a{}}{1}{1}{}{}
```

\GTSunadjacencyRelation, \GTSunadjRel, \GTSuR

These macros will draw an unadjacency symbol with relation spacing in math mode. See their [description](#) and usage examples on page 9.

```
150 \GTS@newcommand{\GTSunadjacencyRelation}{\mathrel{\GTSu/}}
151 \GTS@newcommand{\GTSunadjRel}{\mathrel{\GTSu/}}
152 \GTS@newcommand{\GTSuR}{\mathrel{\GTSu/}}
```

\GTSdirectedAdjacencyUp, \GTSdirAdjUp, \GTSdAU

These macros will draw a directed adjacency upward symbol. See their [description](#) and usage examples on page 9.

```
153 \GTS@newcommand{\GTSdirectedAdjacencyUp}{\GTS@a{}}{1}{1}{}{}
154 \GTS@newcommand{\GTSdirAdjUp}{\GTS@a{}}{1}{1}{}{}
155 \GTS@newcommand{\GTSdAU}{\GTS@a{}}{1}{1}{}{}
```

\GTSdirectedAdjacencyUpRelation, \GTSdirAdjUpRel, \GTSdAUR

These macros will draw a directed adjacency upward symbol with relation spacing in math mode. See their [description](#) and usage examples on page 9.

```
156 \GTS@newcommand{\GTSdirectedAdjacencyUpRelation}{\mathrel{\GTSdAU/}}
157 \GTS@newcommand{\GTSdirAdjUpRel}{\mathrel{\GTSdAU/}}
158 \GTS@newcommand{\GTSdAUR}{\mathrel{\GTSdAU/}}
```

\GTSnegatedDirectedAdjacencyUp, \GTSnegDirAdjUp, \GTSnDAU

These macros will draw a negated directed adjacency upward symbol. See their [description](#) and usage examples on page 9.

```
159 \GTS@newcommand{\GTSnegatedDirectedAdjacencyUp}{\GTS@a{}}{1}{1}{1}{}{}
160 \GTS@newcommand{\GTSnegDirAdjUp}{\GTS@a{}}{1}{1}{1}{}{}
161 \GTS@newcommand{\GTSnDAU}{\GTS@a{}}{1}{1}{1}{}{}
```

\GTSnegatedDirectedAdjacencyUpRelation, \GTSnegDirAdjUpRel, \GTSnDAUR

These macros will draw a negated directed adjacency upward symbol with relation spacing in math mode. See their [description](#) and usage examples on page 10.

```
162 \GTS@newcommand{\GTSnegatedDirectedAdjacencyUpRelation}{%
163 \mathrel{\GTSnDAU/}}%
164 }
165 \GTS@newcommand{\GTSnegDirAdjUpRel}{\mathrel{\GTSnDAU/}}
166 \GTS@newcommand{\GTSnDAUR}{\mathrel{\GTSnDAU/}}
```

\GTSdirectedAdjacencyDown, \GTSdirAdjDown, \GTSdAD

These macros will draw a directed adjacency downward symbol. See their [description](#) and usage examples on page 10.

```
167 \GTS@newcommand{\GTSdirectedAdjacencyDown}{\GTS@a{}}{1}{1}{}{}
168 \GTS@newcommand{\GTSdirAdjDown}{\GTS@a{}}{1}{1}{}{}
169 \GTS@newcommand{\GTSdAD}{\GTS@a{}}{1}{1}{}{}
```

\GTSdirectedAdjacencyDownRelation, \GTSdirAdjDownRel, \GTSdADR

These macros will draw a directed adjacency downward symbol with relation spacing in math mode. See their [description](#) and usage examples on page 10.

```
170 \GTS@newcommand{\GTSdirectedAdjacencyDownRelation}{\mathrel{\GTSdAD/}}
171 \GTS@newcommand{\GTSdirAdjDownRel}{\mathrel{\GTSdAD/}}
172 \GTS@newcommand{\GTSdADR}{\mathrel{\GTSdAD/}}
```

\GTSnegatedDirectedAdjacencyDown, \GTSnegDirAdjDown, \GTSnDAD

These macros will draw a negated directed adjacency downward symbol. See their [description](#) and usage examples on page 10.

```
173 \GTS@newcommand{\GTSnegatedDirectedAdjacencyDown}{\GTS@a{}}{1}{1}{1}{}{}
174 \GTS@newcommand{\GTSnegDirAdjDown}{\GTS@a{}}{1}{1}{1}{}{}
175 \GTS@newcommand{\GTSnDAD}{\GTS@a{}}{1}{1}{1}{}{}
```

`\GTSnegatedDirectedAdjacencyDownRelation`, `\GTSnegDirAdjDownRel`,
`\GTSnDADR`

These macros will draw a negated directed adjacency downward symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 11.

```
176 \GTS@newcommand{\GTSnegatedDirectedAdjacencyDownRelation}{%
177 \mathrel{\GTSnDAD/}}%
178 }
179 \GTS@newcommand{\GTSnegDirAdjDownRel}{\mathrel{\GTSnDAD/}}
180 \GTS@newcommand{\GTSnDADR}{\mathrel{\GTSnDAD/}}
```

`\GTS@i` See its [description](#) on page 11.

```
181 \newcommand{\GTS@i}[5]{%
182 \if#1\empty\else%
183 \GTSsetMainColor{#1}%
184 \fi%
185 \if#2\empty\else%
186 \GTSsetSecondColor{#2}%
187 \fi%
188 \text{\ensuremath{%
189 \raisebox{-0.22ex}{\scalebox{2.05}[2.05]{%
190 %
191 \raisebox{-0.3ex}{\scalebox{0.7}[0.7]{%
192 $\mathcolor{\GTS@secondColor}{\circ}$%
193 }}%
194 \hspace{-0.39ex}%
195 \raisebox{0.05ex}{\scalebox{0.1}[0.1]{%
196 $\mathcolor{\GTS@secondColor}{\bullet}$%
197 }}%
198 \hspace{-0.12ex}%
199 \raisebox{0.11ex}{\scalebox{0.1}[0.73]{%
200 $\mathcolor{\GTS@secondColor}{\smallblacksquare}$%
201 }}%
202 \hspace{-0.18ex}%
203 \raisebox{0.15ex}{\scalebox{0.2}[0.2]{%
204 $\mathcolor{\GTS@mainColor}{\smallblacksquare}$%
205 }}%
206 \hspace{0.2ex}%
if GTS@drawUpArrow empty else
207 \if#4\empty\else%
208 \hspace{-0.65ex}%
209 \raisebox{-0.18ex}{\scalebox{0.5}[0.5]{%
210 \textcolor{\GTS@secondColor}{\textasciicircum}%
211 }}%
212 \fi%
if GTS@drawDownArrow empty else
213 \if#5\empty\else%
214 \hspace{-0.65ex}%
215 \raisebox{1.37ex}{\scalebox{0.5}[-0.5]{%
216 \textcolor{\GTS@secondColor}{\textasciicircum}%
217 }}%
218 \fi%
if GTS@drawSlash empty else
219 \if#3\empty\else%
220 \hspace{-0.65ex}%
221 \raisebox{0.1ex}{\scalebox{0.5}[0.5]{%
222 \textcolor{black}{/}%
223 }}%
224 \fi%
225 %
226 }}%
227 }}%
228 \if#1\empty\else%
229 \GTSsetMainColor{\GTS@mainColorBackup}%
```

```

230 \fi%
231 \if#2\empty\else%
232 \GTSsetSecondColor{\GTS@secondColorBackup}%
233 \fi%
234 }

```

\GTS@j See its [description](#) on page 11.

```

235 \newcommand{\GTS@j}[6]{%
236 \if#61%
237 \mathrel{\GTS@i{#1}{#2}{#3}{#4}{#5}}%
238 \else%
239 \GTS@i{#1}{#2}{#3}{#4}{#5}%
240 \fi%
241 }

```

\GTSxincidence, \GTSxinc, \GTSxi See their [description](#) on page 11.

```

242 \define@key{GTSxi}{mainColor}{\def\GTS@mainColor{#1}}
243 \define@key{GTSxi}{mainC}{\def\GTS@mainColor{#1}}
244 \define@key{GTSxi}{mColor}{\def\GTS@mainColor{#1}}
245 \define@key{GTSxi}{mC}{\def\GTS@mainColor{#1}}
246 \define@key{GTSxi}{secondColor}{\def\GTS@secondColor{#1}}
247 \define@key{GTSxi}{secondC}{\def\GTS@secondColor{#1}}
248 \define@key{GTSxi}{sColor}{\def\GTS@secondColor{#1}}
249 \define@key{GTSxi}{sC}{\def\GTS@secondColor{#1}}
250 \define@key{GTSxi}{monochrome}[1]%
251 {\def\GTS@mainColor{black}\def\GTS@secondColor{black}}
252 \define@key{GTSxi}{mono}[1]%
253 {\def\GTS@mainColor{black}\def\GTS@secondColor{black}}
254 \define@key{GTSxi}{mon}[1]%
255 {\def\GTS@mainColor{black}\def\GTS@secondColor{black}}
256 \define@key{GTSxi}{m}[1]%
257 {\def\GTS@mainColor{black}\def\GTS@secondColor{black}}
258 \define@key{GTSxi}{negated}[1]{\def\GTS@drawSlash{1}}
259 \define@key{GTSxi}{not}[1]{\def\GTS@drawSlash{1}}
260 \define@key{GTSxi}{n}[1]{\def\GTS@drawSlash{1}}
261 \define@key{GTSxi}{out}[1]{\def\GTS@drawUpArrow{1}}
262 \define@key{GTSxi}{o}[1]{\def\GTS@drawUpArrow{1}}
263 \define@key{GTSxi}{in}[1]{\def\GTS@drawDownArrow{1}}
264 \define@key{GTSxi}{i}[1]{\def\GTS@drawDownArrow{1}}
265 \define@key{GTSxi}{relation}[1]{\def\GTS@relation{1}}
266 \define@key{GTSxi}{rel}[1]{\def\GTS@relation{1}}
267 \define@key{GTSxi}{r}[1]{\def\GTS@relation{1}}
268
269 \newcommand{\GTSxi}[1][]{%
270 \def\GTS@mainColor{}%
271 \def\GTS@secondColor{}%
272 \def\GTS@drawSlash{}%
273 \def\GTS@drawUpArrow{}%
274 \def\GTS@drawDownArrow{}%
275 \def\GTS@relation{}%
276 \setkeys{GTSxi}{#1}%
277 \GTS@j{\GTS@mainColor}{\GTS@secondColor}{\GTS@drawSlash}%
278 {\GTS@drawUpArrow}{\GTS@drawDownArrow}{\GTS@relation}%
279 }
280
281 \newcommand{\GTSxinc}[1][]{\GTSxi{#1}}
282
283 \newcommand{\GTSxincidence}[1][]{\GTSxi{#1}}

```

\GTSincidence, \GTSinc, \GTSi These macros will draw an incidence symbol.
See their [description](#) and usage examples on page 12.

```

284 \GTS@newcommand{\GTSincidence}{\GTS@i{}{}{}{}}
285 \GTS@newcommand{\GTSinc}{\GTS@i{}{}{}{}}
286 \GTS@newcommand{\GTSi}{\GTS@i{}{}{}{}}

```

\GTSincidenceRelation, \GTSincRel, \GTSiR

These macros will draw an incidence symbol with relation spacing in math mode.
See their [description](#) and usage examples on page 12.

```
287 \GTS@newcommand{\GTSincidenceRelation}{\mathrel{\GTSi/}}
288 \GTS@newcommand{\GTSincRel}{\mathrel{\GTSi/}}
289 \GTS@newcommand{\GTSiR}{\mathrel{\GTSi/}}
```

\GTSnegatedIncidence, \GTSnegInc, \GTSnI These macros will draw a negated incidence symbol.

See their [description](#) and usage examples on page 12.

```
290 \GTS@newcommand{\GTSnegatedIncidence}{\GTS@i{}{}{1}{}{}}
291 \GTS@newcommand{\GTSnegInc}{\GTS@i{}{}{1}{}{}}
292 \GTS@newcommand{\GTSnI}{\GTS@i{}{}{1}{}{}}
```

\GTSnegatedIncidenceRelation, \GTSnegIncRel, \GTSnIR

These macros will draw a negated incidence symbol with relation spacing in math mode.
See their [description](#) and usage examples on page 12.

```
293 \GTS@newcommand{\GTSnegatedIncidenceRelation}{\mathrel{\GTSnI/}}
294 \GTS@newcommand{\GTSnegIncRel}{\mathrel{\GTSnI/}}
295 \GTS@newcommand{\GTSnIR}{\mathrel{\GTSnI/}}
```

\GTSoutIncidence, \GTSoutInc, \GTSoI

These macros will draw a directed incidence upward (out(ward) incidence) symbol.
See their [description](#) and usage examples on page 13.

```
296 \GTS@newcommand{\GTSoutIncidence}{\GTS@i{}{}{1}{}{}}
297 \GTS@newcommand{\GTSoutInc}{\GTS@i{}{}{1}{}{}}
298 \GTS@newcommand{\GTSoI}{\GTS@i{}{}{1}{}{}}
```

\GTSoutIncidenceRelation, \GTSoutIncRel, \GTSoIR These macros will draw a directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 13.

```
299 \GTS@newcommand{\GTSoutIncidenceRelation}{\mathrel{\GTSoI/}}
300 \GTS@newcommand{\GTSoutIncRel}{\mathrel{\GTSoI/}}
301 \GTS@newcommand{\GTSoIR}{\mathrel{\GTSoI/}}
```

\GTSnegatedOutIncidence, \GTSnegOutInc, \GTSnOI

These macros will draw a negated directed incidence upward (out(ward) incidence) symbol.
See their [description](#) and usage examples on page 13.

```
302 \GTS@newcommand{\GTSnegatedOutIncidence}{\GTS@i{}{}{1}{1}{}{}}
303 \GTS@newcommand{\GTSnegOutInc}{\GTS@i{}{}{1}{1}{}{}}
304 \GTS@newcommand{\GTSnOI}{\GTS@i{}{}{1}{1}{}{}}
```

\GTSnegatedOutIncidenceRelation, \GTSnegOutIncRel, \GTSnOIR These macros will draw a negated directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 14.

```
305 \GTS@newcommand{\GTSnegatedOutIncidenceRelation}{\mathrel{\GTSnOI/}}
306 \GTS@newcommand{\GTSnegOutIncRel}{\mathrel{\GTSnOI/}}
307 \GTS@newcommand{\GTSnOIR}{\mathrel{\GTSnOI/}}
```

\GTSinIncidence, \GTSinInc, \GTSiI

These macros will draw a directed incidence downward (in(ward) incidence) symbol.
See their [description](#) and usage examples on page 14.

```
308 \GTS@newcommand{\GTSinIncidence}{\GTS@i{}{}{}{1}}
309 \GTS@newcommand{\GTSinInc}{\GTS@i{}{}{}{1}}
310 \GTS@newcommand{\GTSiI}{\GTS@i{}{}{}{1}}
```

\GTSinIncidenceRelation, \GTSinIncRel, \GTSiIR These macros will draw a directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 14.

```
311 \GTS@newcommand{\GTSinIncidenceRelation}{\mathrel{\GTSiI/}}
312 \GTS@newcommand{\GTSinIncRel}{\mathrel{\GTSiI/}}
313 \GTS@newcommand{\GTSiIR}{\mathrel{\GTSiI/}}
```

\GTSnegatedInIncidence, \GTSnegInInc, \GTSnII

These macros will draw a negated directed incidence downward (in(ward) incidence) symbol. See their [description](#) and usage examples on page 14.

```
314 \GTS@newcommand{\GTSnegatedInIncidence}{\GTS@i{}{}{1}{}{1}}
315 \GTS@newcommand{\GTSnegInInc}{\GTS@i{}{}{1}{}{1}}
316 \GTS@newcommand{\GTSnII}{\GTS@i{}{}{1}{}{1}}
```

\GTSnegatedInIncidenceRelation, \GTSnegInIncRel, \GTSnIIR These macros will draw a negated directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode. See their [description](#) and usage examples on page 15.

```
317 \GTS@newcommand{\GTSnegatedInIncidenceRelation}{\mathrel{\GTSnII/}}
318 \GTS@newcommand{\GTSnegInIncRel}{\mathrel{\GTSnII/}}
319 \GTS@newcommand{\GTSnIIR}{\mathrel{\GTSnII/}}
```

\GTSadjacencyMonochrome, \GTSadjMono, \GTSadjMon, \GTSaM

These macros will draw a monochrome adjacency symbol. See their [description](#) and usage examples on page 15.

```
320 \GTS@newcommand{\GTSadjacencyMonochrome}{\GTS@a{black}{black}{}{}{}}
321 \GTS@newcommand{\GTSadjMono}{\GTS@a{black}{black}{}{}{}}
322 \GTS@newcommand{\GTSadjMon}{\GTS@a{black}{black}{}{}{}}
323 \GTS@newcommand{\GTSaM}{\GTS@a{black}{black}{}{}{}}
```

\GTSadjacencyMonochromeRelation, \GTSadjMonoRel, \GTSadjMonRel, \GTSaMR

These macros will draw a monochrome adjacency symbol with relation spacing in math mode. See their [description](#) and usage examples on page 15.

```
324 \GTS@newcommand{\GTSadjacencyMonochromeRelation}{\mathrel{\GTSaM/}}
325 \GTS@newcommand{\GTSadjMonoRel}{\mathrel{\GTSaM/}}
326 \GTS@newcommand{\GTSadjMonRel}{\mathrel{\GTSaM/}}
327 \GTS@newcommand{\GTSaMR}{\mathrel{\GTSaM/}}
```

\GTSunadjacencyMonochrome, \GTSunadjMono, \GTSunadjMon, \GTSuM

These macros will draw a monochrome unadjacency symbol. See their [description](#) and usage examples on page 15.

```
328 \GTS@newcommand{\GTSunadjacencyMonochrome}{\GTS@a{black}{black}{1}{}{}}
329 \GTS@newcommand{\GTSunadjMono}{\GTS@a{black}{black}{1}{}{}}
330 \GTS@newcommand{\GTSunadjMon}{\GTS@a{black}{black}{1}{}{}}
331 \GTS@newcommand{\GTSuM}{\GTS@a{black}{black}{1}{}{}}
```

\GTSunadjacencyMonochromeRelation, \GTSunadjMonoRel, \GTSunadjMonRel, \GTSuMR

These macros will draw a monochrome unadjacency symbol with relation spacing in math mode. See their [description](#) and usage examples on page 16.

```
332 \GTS@newcommand{\GTSunadjacencyMonochromeRelation}{\mathrel{\GTSuM/}}
333 \GTS@newcommand{\GTSunadjMonoRel}{\mathrel{\GTSuM/}}
334 \GTS@newcommand{\GTSunadjMonRel}{\mathrel{\GTSuM/}}
335 \GTS@newcommand{\GTSuMR}{\mathrel{\GTSuM/}}
```

\GTSdirectedAdjacencyUpMonochrome, \GTSdirAdjUpMono, \GTSdirAdjUpMon, \GTSdAUM These macros will draw a monochrome directed adjacency upward symbol. See their [description](#) and usage examples on page 16.

```
336 \GTS@newcommand{\GTSdirectedAdjacencyUpMonochrome}{%
337 \GTS@a{black}{black}{}{1}{}%
338 }
339 \GTS@newcommand{\GTSdirAdjUpMono}{\GTS@a{black}{black}{}{1}{}{}}
340 \GTS@newcommand{\GTSdirAdjUpMon}{\GTS@a{black}{black}{}{1}{}{}}
341 \GTS@newcommand{\GTSdAUM}{\GTS@a{black}{black}{}{1}{}{}}
```

\GTSdirectedAdjacencyUpMonochromeRelation, \GTSdirAdjUpMonoRel, \GTSdirAdjUpMonRel, \GTSdAUMR

These macros will draw a monochrome directed adjacency upward symbol with relation spacing in math mode. See their [description](#) and usage examples on page 17.

```
342 \GTS@newcommand{\GTSdirectedAdjacencyUpMonochromeRelation}{%
```

```
343 \mathrel{\GTSdAUM/}%
```

```
344 }
```

```
345 \GTS@newcommand{\GTSdirAdjUpMonoRel}{\mathrel{\GTSdAUM/}}
```

```
346 \GTS@newcommand{\GTSdirAdjUpMonRel}{\mathrel{\GTSdAUM/}}
```

```
347 \GTS@newcommand{\GTSdAUMR}{\mathrel{\GTSdAUM/}}
```

\GTSnegatedDirectedAdjacencyUpMonochrome, \GTSnegDirAdjUpMono, \GTSnegDirAdjUpMon, \GTSnDAUM

These macros will draw a monochrome negated directed adjacency upward symbol.

See their [description](#) and usage examples on page 17.

```
348 \GTS@newcommand{\GTSnegatedDirectedAdjacencyUpMonochrome}{%
```

```
349 \GTS@a{black}{black}{1}{1}{1}}%
```

```
350 }
```

```
351 \GTS@newcommand{\GTSnegDirAdjUpMono}{\GTS@a{black}{black}{1}{1}{1}}
```

```
352 \GTS@newcommand{\GTSnegDirAdjUpMon}{\GTS@a{black}{black}{1}{1}{1}}
```

```
353 \GTS@newcommand{\GTSnDAUM}{\GTS@a{black}{black}{1}{1}{1}}
```

\GTSnegatedDirectedAdjacencyUpMonochromeRelation, \GTSnegDirAdjUpMonoRel, \GTSnegDirAdjUpMonRel, \GTSnDAUMR These macros will draw a monochrome negated directed adjacency upward symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 17.

```
354 \GTS@newcommand{\GTSnegatedDirectedAdjacencyUpMonochromeRelation}{%
```

```
355 \mathrel{\GTSnDAUM/}%
```

```
356 }
```

```
357 \GTS@newcommand{\GTSnegDirAdjUpMonoRel}{\mathrel{\GTSnDAUM/}}
```

```
358 \GTS@newcommand{\GTSnegDirAdjUpMonRel}{\mathrel{\GTSnDAUM/}}
```

```
359 \GTS@newcommand{\GTSnDAUMR}{\mathrel{\GTSnDAUM/}}
```

\GTSdirectedAdjacencyDownMonochrome, \GTSdirAdjDownMono, \GTSdirAdjDownMon, \GTSdADM

These macros will draw a monochrome directed adjacency downward symbol.

See their [description](#) and usage examples on page 17.

```
360 \GTS@newcommand{\GTSdirectedAdjacencyDownMonochrome}{%
```

```
361 \GTS@a{black}{black}{1}{1}{1}}%
```

```
362 }
```

```
363 \GTS@newcommand{\GTSdirAdjDownMono}{\GTS@a{black}{black}{1}{1}{1}}
```

```
364 \GTS@newcommand{\GTSdirAdjDownMon}{\GTS@a{black}{black}{1}{1}{1}}
```

```
365 \GTS@newcommand{\GTSdADM}{\GTS@a{black}{black}{1}{1}{1}}
```

\GTSdirectedAdjacencyDownMonochromeRelation, \GTSdirAdjDownMonoRel, \GTSdirAdjDownMonRel, \GTSdADMR These macros will draw a monochrome directed adjacency downward symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 18.

```
366 \GTS@newcommand{\GTSdirectedAdjacencyDownMonochromeRelation}{%
```

```
367 \mathrel{\GTSdADM/}%
```

```
368 }
```

```
369 \GTS@newcommand{\GTSdirAdjDownMonoRel}{\mathrel{\GTSdADM/}}
```

```
370 \GTS@newcommand{\GTSdirAdjDownMonRel}{\mathrel{\GTSdADM/}}
```

```
371 \GTS@newcommand{\GTSdADMR}{\mathrel{\GTSdADM/}}
```

\GTSnegatedDirectedAdjacencyDownMonochrome, \GTSnegDirAdjDownMono, \GTSnegDirAdjDownMon, \GTSnDADM

These macros will draw a monochrome negated directed adjacency downward symbol.

See their [description](#) and usage examples on page 18.

```
372 \GTS@newcommand{\GTSnegatedDirectedAdjacencyDownMonochrome}{%
```

```
373 \GTS@a{black}{black}{1}{1}{1}}%
```

```
374 }
```

```
375 \GTS@newcommand{\GTSnegDirAdjDownMono}{\GTS@a{black}{black}{1}{1}{1}}
```

```
376 \GTS@newcommand{\GTSnegDirAdjDownMon}{\GTS@a{black}{black}{1}{1}{1}}
```

```
377 \GTS@newcommand{\GTSnDADM}{\GTS@a{black}{black}{1}{1}{1}}
```

\GTSnegatedDirectedAdjacencyDownMonochromeRelation, \GTSnegDirAdjDownMonoRel, \GTSnegDirAdjDownMonRel, \GTSnDADMR These macros will draw a monochrome negated directed adjacency downward symbol with relation spacing

in math mode.

See their [description](#) and usage examples on page 19.

```
378 \GTS@newcommand{\GTSnegatedDirectedAdjacencyDownMonochromeRelation}{%
379 \mathrel{\GTSnDADM/}%
380 }
381 \GTS@newcommand{\GTSnegDirAdjDownMonoRel}{\mathrel{\GTSnDADM/}}
382 \GTS@newcommand{\GTSnegDirAdjDownMonRel}{\mathrel{\GTSnDADM/}}
383 \GTS@newcommand{\GTSnDADMR}{\mathrel{\GTSnDADM/}}
```

\GTSincidenceMonochrome, \GTSincMono, \GTSincMon, \GTSiM

These macros will draw a monochrome incidence symbol.

See their [description](#) and usage examples on page 19.

```
384 \GTS@newcommand{\GTSincidenceMonochrome}{\GTS@i{black}{black}{}}{}{}
385 \GTS@newcommand{\GTSincMono}{\GTS@i{black}{black}{}}{}{}
386 \GTS@newcommand{\GTSincMon}{\GTS@i{black}{black}{}}{}{}
387 \GTS@newcommand{\GTSiM}{\GTS@i{black}{black}{}}{}{}%
```

\GTSincidenceMonochromeRelation, \GTSincMonoRel, \GTSincMonRel, \GTSiMR

These macros will draw a monochrome incidence symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 19.

```
388 \GTS@newcommand{\GTSincidenceMonochromeRelation}{\mathrel{\GTSiM/}}
389 \GTS@newcommand{\GTSincMonoRel}{\mathrel{\GTSiM/}}
390 \GTS@newcommand{\GTSincMonRel}{\mathrel{\GTSiM/}}
391 \GTS@newcommand{\GTSiMR}{\mathrel{\GTSiM/}}
```

\GTSnegatedIncidenceMonochrome, \GTSnegIncMono, \GTSnegIncMon, \GTSnIM

These macros will draw a monochrome negated incidence symbol.

See their [description](#) and usage examples on page 19.

```
392 \GTS@newcommand{\GTSnegatedIncidenceMonochrome}{%
393 \GTS@i{black}{black}{1}}{}{}
394 }
395 \GTS@newcommand{\GTSnegIncMono}{\GTS@i{black}{black}{1}}{}{}
396 \GTS@newcommand{\GTSnegIncMon}{\GTS@i{black}{black}{1}}{}{}
397 \GTS@newcommand{\GTSnIM}{\GTS@i{black}{black}{1}}{}{}%
```

\GTSnegatedIncidenceMonochromeRelation, \GTSnegIncMonoRel, \GTSnegIncMonRel, \GTSnIMR

These macros will draw a monochrome negated incidence symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 20.

```
398 \GTS@newcommand{\GTSnegatedIncidenceMonochromeRelation}{\mathrel{\GTSnIM/}}
399 \GTS@newcommand{\GTSnegIncMonoRel}{\mathrel{\GTSnIM/}}
400 \GTS@newcommand{\GTSnegIncMonRel}{\mathrel{\GTSnIM/}}
401 \GTS@newcommand{\GTSnIMR}{\mathrel{\GTSnIM/}}
```

\GTSoutIncidenceMonochrome, \GTSoutIncMono, \GTSoutIncMon, \GTSoIM

These macros will draw a monochrome directed incidence upward (out(ward) incidence) symbol.

See their [description](#) and usage examples on page 20.

```
402 \GTS@newcommand{\GTSoutIncidenceMonochrome}{\GTS@i{black}{black}{}}{1}{}
403 \GTS@newcommand{\GTSoutIncMono}{\GTS@i{black}{black}{}}{1}{}
404 \GTS@newcommand{\GTSoutIncMon}{\GTS@i{black}{black}{}}{1}{}
405 \GTS@newcommand{\GTSoIM}{\GTS@i{black}{black}{}}{1}{}%
```

\GTSoutIncidenceMonochromeRelation, \GTSoutIncMonoRel, \GTSoutIncMonRel, \GTSoIMR

These macros will draw a monochrome directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 20.

```
406 \GTS@newcommand{\GTSoutIncidenceMonochromeRelation}{\mathrel{\GTSoIM/}}
407 \GTS@newcommand{\GTSoutIncMonoRel}{\mathrel{\GTSoIM/}}
408 \GTS@newcommand{\GTSoutIncMonRel}{\mathrel{\GTSoIM/}}
409 \GTS@newcommand{\GTSoIMR}{\mathrel{\GTSoIM/}}
```

\GTSnegatedOutIncidenceMonochrome, \GTSnegOutIncMono, \GTSnegOutIncMon, \GTSnOIM

These macros will draw a monochrome negated directed incidence upward (out(ward) incidence) symbol.

See their [description](#) and usage examples on page 22.

```
410 \GTS@newcommand{\GTSnegatedOutIncidenceMonochrome}{%
411 \GTS@i{black}{black}{1}{1}{}}%
412 }
413 \GTS@newcommand{\GTSnegOutIncMono}{\GTS@i{black}{black}{1}{1}{}}
414 \GTS@newcommand{\GTSnegOutIncMonRel}{\GTS@i{black}{black}{1}{1}{}}
415 \GTS@newcommand{\GTSnOIM}{\GTS@i{black}{black}{1}{1}{}}
```

\GTSnegatedOutIncidenceMonochromeRelation, \GTSnegOutIncMonoRel, \GTSnegOutIncMonRel, \GTSnOIMR These macros will draw a monochrome negated directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 22.

```
416 \GTS@newcommand{\GTSnegatedOutIncidenceMonochromeRelation}{%
417 \mathrel{\GTSnOIM/}}%
418 }
419 \GTS@newcommand{\GTSnegOutIncMonoRel}{\mathrel{\GTSnOIM/}}
420 \GTS@newcommand{\GTSnegOutIncMonRel}{\mathrel{\GTSnOIM/}}
421 \GTS@newcommand{\GTSnOIMR}{\mathrel{\GTSnOIM/}}
```

\GTSinIncidenceMonochrome, \GTSinIncMono, \GTSinIncMon, \GTSiIM

These macros will draw a monochrome directed incidence downward (in(ward) incidence) symbol.

See their [description](#) and usage examples on page 22.

```
422 \GTS@newcommand{\GTSinIncidenceMonochrome}{\GTS@i{black}{black}{}}{1}}
423 \GTS@newcommand{\GTSinIncMono}{\GTS@i{black}{black}{}}{1}}
424 \GTS@newcommand{\GTSinIncMon}{\GTS@i{black}{black}{}}{1}}
425 \GTS@newcommand{\GTSiIM}{\GTS@i{black}{black}{}}{1}}
```

\GTSinIncidenceMonochromeRelation, \GTSinIncMonoRel, \GTSinIncMonRel, \GTS-iIMR These macros will draw a monochrome directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 23.

```
426 \GTS@newcommand{\GTSinIncidenceMonochromeRelation}{\mathrel{\GTSiIM/}}
427 \GTS@newcommand{\GTSinIncMonoRel}{\mathrel{\GTSiIM/}}
428 \GTS@newcommand{\GTSinIncMonRel}{\mathrel{\GTSiIM/}}
429 \GTS@newcommand{\GTS-iIMR}{\mathrel{\GTSiIM/}}
```

\GTSnegatedInIncidenceMonochrome, \GTSnegInIncMono, \GTSnegInIncMon, \GTS-nIIM These macros will draw a monochrome negated directed incidence downward (in(ward) incidence) symbol.

See their [description](#) and usage examples on page 23.

```
430 \GTS@newcommand{\GTSnegatedInIncidenceMonochrome}{%
431 \GTS@i{black}{black}{1}{1}{}}%
432 }
433 \GTS@newcommand{\GTSnegInIncMono}{\GTS@i{black}{black}{1}{1}{}}
434 \GTS@newcommand{\GTSnegInIncMon}{\GTS@i{black}{black}{1}{1}{}}
435 \GTS@newcommand{\GTSnIIM}{\GTS@i{black}{black}{1}{1}{}}
```

\GTSnegatedInIncidenceMonochromeRelation, \GTSnegInIncMonoRel, \GTSnegInIncMonRel, \GTSnIIMR

These macros will draw a monochrome negated directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 23.

```
436 \GTS@newcommand{\GTSnegatedInIncidenceMonochromeRelation}{%
437 \mathrel{\GTSnIIM/}}%
438 }
439 \GTS@newcommand{\GTSnegInIncMonoRel}{\mathrel{\GTSnIIM/}}
440 \GTS@newcommand{\GTSnegInIncMonRel}{\mathrel{\GTSnIIM/}}
441 \GTS@newcommand{\GTSnIIMR}{\mathrel{\GTSnIIM/}}
```

\GTSmetaNot, \GTSmN These macros will draw a meta-not or relation-not symbol.

See their [description](#) and usage examples on page 24.

```

442 \GTS@newprotectedcommand{\GTSmN}{%
443 \text{\ensuremath{%
444 \raisebox{-0.44ex}{\scalebox{1}[1]{%
445 \raisebox{0ex}{\scalebox{1}[1]{\not$}}}%
446 \hspace{-1.46ex}%
447 \raisebox{1.2ex}{\scalebox{0.7}[0.7]{m}}}%
448 \hspace{0.2ex}%
449 }}}%
450 }}%
451 }
452 \GTS@newcommand{\GTSmetaNot}{\GTSmN/}

```

\GTSmetaAnd, \GTSmA These macros will draw a meta-and or relations-and symbol. See their [description](#) and usage examples on page 24.

```

453 \GTS@newprotectedcommand{\GTSmA}{%
454 \text{\ensuremath{%
455 \raisebox{-0.44ex}{\scalebox{0.95}[0.95]{%
456 \raisebox{0ex}{\scalebox{1}[1]{\wedge$}}}%
457 \hspace{-1.46ex}%
458 \raisebox{1.5ex}{\scalebox{0.7}[0.7]{m}}}%
459 }}}%
460 }}%
461 }
462 \GTS@newcommand{\GTSmetaAnd}{\GTSmA/}

```

\GTSmetaAndRelation, \GTSmetaAndRel, \GTSmAR

These macros will draw a meta-and symbol with relation spacing in math mode. See their [description](#) and usage examples on page 24.

```

463 \GTS@newcommand{\GTSmetaAndRelation}{\mathrel{\GTSmA/}}
464 \GTS@newcommand{\GTSmetaAndRel}{\mathrel{\GTSmA/}}
465 \GTS@newcommand{\GTSmAR}{\mathrel{\GTSmA/}}

```

\GTSmetaOr, \GTSmO These macros will draw a meta-or or relations-or symbol. This is your duty to check that all relations have same arity. It should be easy as long as you remain in the realm of graphs/2-structures/binary structures ;). We didn't use Tarski's notation, since square cup has taken the preemptive meaning of disjoint union. Similarly, doublevee or other vee symbols have taken various meanings, whilst we want an unambiguous symbol.

See their [description](#) and usage examples on page 24.

```

466 \GTS@newprotectedcommand{\GTSmO}{%
467 \text{\ensuremath{%
468 \raisebox{-0.44ex}{\scalebox{0.95}[0.95]{%
469 \raisebox{0ex}{\scalebox{1}[1]{\vee$}}}%
470 \hspace{-1.46ex}%
471 \raisebox{1.5ex}{\scalebox{0.7}[0.7]{m}}}%
472 }}}%
473 }}%
474 }
475 \GTS@newcommand{\GTSmetaOr}{\GTSmO/}

```

\GTSmetaOrRelation, \GTSmetaOrRel, \GTSmOR

These macros will draw a meta-or symbol with relation spacing in math mode. See their [description](#) and usage examples on page 24.

```

476 \GTS@newcommand{\GTSmetaOrRelation}{\mathrel{\GTSmO/}}
477 \GTS@newcommand{\GTSmetaOrRel}{\mathrel{\GTSmO/}}
478 \GTS@newcommand{\GTSmOR}{\mathrel{\GTSmO/}}

```

`\GTSxmetallogic`, `\GTSxml` See their [description](#) on page 25.

```

479 \define@key{GTSxml}{not}[1]{\def\GTS@@drawMetaNot{1}}
480 \define@key{GTSxml}{n}[1]{\def\GTS@@drawMetaNot{1}}
481 \define@key{GTSxml}{and}[1]{\def\GTS@@drawMetaAnd{1}}
482 \define@key{GTSxml}{a}[1]{\def\GTS@@drawMetaAnd{1}}
483 \define@key{GTSxml}{or}[1]{\def\GTS@@drawMetaOr{1}}
484 \define@key{GTSxml}{o}[1]{\def\GTS@@drawMetaOr{1}}
485 \define@key{GTSxml}{relation}[1]{\def\GTS@@relation{1}}
486 \define@key{GTSxml}{rel}[1]{\def\GTS@@relation{1}}
487 \define@key{GTSxml}{r}[1]{\def\GTS@@relation{1}}
488
489 \newcommand{\GTSxml}[1][]{%
490 \def\GTS@@drawMetaNot{}%
491 \def\GTS@@drawMetaAnd{}%
492 \def\GTS@@drawMetaOr{}%
493 \def\GTS@@relation{}%
494 \setkeys{GTSxml}{#1}%
495 \if\GTS@@drawMetaNot1%
496 \GTSmN/%
497 \else\if\GTS@@drawMetaAnd1%
498 \if\GTS@@relation{1}%
499 \GTSmAR/%
500 \else%
501 \GTSmA/%
502 \fi%
503 \else\if\GTS@@drawMetaOr1%
504 \if\GTS@@relation{1}%
505 \GTSmOR/%
506 \else%
507 \GTSmO/%
508 \fi%
509 \else%
510 Wrong call to \textbackslash{GTSxml}%
511 \fi%
512 \fi%
513 \fi%
514 }
515
516 \newcommand{\GTSxmetallogic}[1][]{\GTSxml[#1]}

```

`\GTSx` See its [description](#) on page 25.

```

517 \newcommand{\GTSx}[2][]{%
518 \if#2a%
519 \GTSxa[#1]%
520 \else\if#2i%
521 \GTSxi[#1]%
522 \else\if#2m%
523 \GTSxm[#1]%
524 \else%
525 Wrong call to \textbackslash{GTSx}%
526 \fi%
527 \fi%
528 \fi%
529 }

530 \endinput
531 \</package>

```

4 Acknowledgments

Thank You God! Thank You Father! Thank You Jesus! Thank You Holy-Spirit!

5 FAQ

Question: Why GraphTheorySymbol instead of GraphTheorySymbols? GraphTheorySymbol does contain many symbols.

Answer: Because I followed one common usage on CTAN.

Here is the list of all current packages with the word "symbol" in their name:

actuarialsymbol, adfsymbols, compact-symbols, cookingsymbols, FdSymbol, jpnedumathsymbols, KKsymbols, listofsymbols, losymbol, maths-symbols, mdsymbol, MnSymbol, open-everyday-symbols, qsymbols, SVRsymbols, symbolindex, The Comprehensive LaTeX Symbol List, tikz-cookingsymbols, tikzsymbols.

7 "symbol" plus GraphTheorySymbol 8, 12 "symbols".

"symb" abbreviation, "sym", "sy" and "s" are also quite common;

oPlotSymb did it its own way ;) XD.

Because of the goal of GraphTheorySymbol, I was mainly looking at packages like FdSymbol, mdsymbol, MnSymbol, and The Comprehensive LaTeX Symbol List before creating my package; hence I followed this apparent majority, instead of listening to my thought that Symbols would be better.

After the package was uploaded to CTAN for a version update, this question came again, but CTAN admins were reluctant to change the package name afterward.

Otherwise, it is a matter of hours to modify and upload GraphTheorySymbols with version 2.0.0 to CTAN.

6 Support

This package is gratis and free. But if you can star it on GitHub, it is a nice encouragement.

7 Change History

v0.1.0 – 2026-08-01		avoid too big left margins, and use	
General: Initial version	1	paragraph command instead	1
v1.0.0 – 2026-08-26		v1.5.2 – 2026-09-14	
General: First public release	1	General: Add A4, USLetter, and Book	
v1.1.0 – 2026-08-29		variants of PDFs.	1
General: Added a memo	1	v1.6.0 – 2026-09-18	
v1.1.1 – 2026-08-30		General: Add verbatim code for compound	
General: Small corrections and improvements	1	adjacency in memo.	1
v1.2.0 – 2026-09-06		v1.6.1 – 2026-09-19	
General: CTAN URL, new macros for same		General: Rename test(.tex, etc.) to	
set of symbols	1	graph-theory-symbol-test(.tex, etc.).	1
v1.2.1 – 2026-09-08		v1.7.0 – 2026-09-21	
General: Smaller tests output	1	General: Add FAQ section. Minors spacing	
v1.3.0 – 2026-09-08		and newpage corrections. Put table of	
General: New macros for monochrome		contents and Introduction on their own	
symbols	1	page. Use tcolorbox for more visible	
v1.4.0 – 2026-09-12		examples. Disclaimer for documentation	
General: New macros for symbols for logical		of macros with an at sign.	1
operations on relations	1	v1.8.0 – 2026-09-28	
v1.5.0 – 2026-09-12		General: Forward and backward hyperlinks	
General: One macro to rule them all	1	between macros descriptions and	
v1.5.1 – 2026-09-13		implementations.	1
General: Use noprint option of doc package to			

Index

G

\GTS@@drawDownArrow	120, 121, 131, 135, 263, 264, 274, 278
\GTS@@drawMetaAnd	481, 482, 491, 497
\GTS@@drawMetaNot	479, 480, 490, 495
\GTS@@drawMetaOr	483, 484, 492, 503
\GTS@@drawSlash	115, 116, 117, 129, 134, 258, 259, 260, 272, 277
\GTS@@drawUpArrow	118, 119, 130, 135, 261, 262, 273, 278

\GTS@@mainColor 99, 100, 101, 102, 108, 110, 112, 114, 127, 134, 242, 243, 244, 245, 251, 253, 255,
257, 270, 277
\GTS@@relation 122, 123, 124, 132, 135, 265, 266, 267, 275, 278, 485, 486, 487, 493, 498, 504
\GTS@@secondColor . 103, 104, 105, 106, 108, 110, 112, 114, 128, 134, 246, 247, 248, 249, 251, 253,
255, 257, 271, 277
\GTS@a . 7, 34, 94, 96, 141, 142, 143, 147, 148, 149, 153, 154, 155, 159, 160, 161, 167, 168, 169, 173,
174, 175, 320, 321, 322, 323, 328, 329, 330, 331, 337, 339, 340, 341, 349, 351, 352, 353, 361,
363, 364, 365, 373, 375, 376, 377
\GTS@b 7, 92, 134
\GTS@drawDownArrow 16
\GTS@drawSlash 14
\GTS@drawUpArrow 15
\GTS@i . 11, 181, 237, 239, 284, 285, 286, 290, 291, 292, 296, 297, 298, 302, 303, 304, 308, 309, 310,
314, 315, 316, 384, 385, 386, 387, 393, 395, 396, 397, 402, 403, 404, 405, 411, 413, 414, 415,
422, 423, 424, 425, 431, 433, 434, 435
\GTS@j 11, 235, 277
\GTS@mainColor 10, 26, 27, 53, 67, 73, 204
\GTS@mainColorBackup 12, 26, 86, 229
\GTS@mainColorTemp 25, 27
\GTS@newcommand . . 7, 18, 141, 142, 143, 144, 145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155,
156, 157, 158, 159, 160, 161, 162, 165, 166, 167, 168, 169, 170, 171, 172, 173, 174, 175, 176,
179, 180, 284, 285, 286, 287, 288, 289, 290, 291, 292, 293, 294, 295, 296, 297, 298, 299, 300,
301, 302, 303, 304, 305, 306, 307, 308, 309, 310, 311, 312, 313, 314, 315, 316, 317, 318, 319,
320, 321, 322, 323, 324, 325, 326, 327, 328, 329, 330, 331, 332, 333, 334, 335, 336, 339, 340,
341, 342, 345, 346, 347, 348, 351, 352, 353, 354, 357, 358, 359, 360, 363, 364, 365, 366, 369,
370, 371, 372, 375, 376, 377, 378, 381, 382, 383, 384, 385, 386, 387, 388, 389, 390, 391, 392,
395, 396, 397, 398, 399, 400, 401, 402, 403, 404, 405, 406, 407, 408, 409, 410, 413, 414, 415,
416, 419, 420, 421, 422, 423, 424, 425, 426, 427, 428, 429, 430, 433, 434, 435, 436, 439, 440,
441, 452, 462, 463, 464, 465, 475, 476, 477, 478
\GTS@newprotectedcommand 7, 21, 442, 453, 466
\GTS@secondColor 11, 31, 32, 45, 49, 57, 61, 192, 196, 200, 210, 216
\GTS@secondColorBackup 13, 31, 89, 232
\GTS@secondColorTemp 30, 32
\GTSa 8, 141, 144, 145, 146
\GTSadj 8, 141
\GTSadjacency 8, 141
\GTSadjacencyMonochrome 15, 320
\GTSadjacencyMonochromeRelation 15, 324
\GTSadjacencyRelation 8, 144
\GTSadjMon 15, 320
\GTSadjMono 15, 320
\GTSadjMonoRel 15, 324
\GTSadjMonRel 15, 324
\GTSadjRel 8, 144
\GTSaM 15, 320, 324, 325, 326, 327
\GTSaMR 15, 324
\GTSaR 8, 144
\GTSdAD 10, 167, 170, 171, 172
\GTSdADM 17, 360, 367, 369, 370, 371
\GTSdADMR 18, 366
\GTSdADR 10, 170
\GTSdAU 9, 153, 156, 157, 158
\GTSdAUM 16, 336, 343, 345, 346, 347
\GTSdAUMR 17, 342
\GTSdAUR 9, 156
\GTSdirAdjDown 10, 167
\GTSdirAdjDown\-Mon 17
\GTSdirAdjDownMon 360
\GTSdirAdjDownMono 17, 360
\GTSdirAdjDownMonoRel 18, 366
\GTSdirAdjDownMonRel 18, 366

\GTSdirAdjDownRel	10, 170
\GTSdirAdjUp	9, 153
\GTSdirAdjUpMon	16, 336
\GTSdirAdjUpMono	16, 336
\GTSdirAdjUpMonoRel	17, 342
\GTSdirAdjUpMonRel	17, 342
\GTSdirAdjUpRel	9, 156
\GTSdirectedAdjacencyDown	10, 167
\GTSdirectedAdjacencyDownMonochrome	17, 360
\GTSdirectedAdjacencyDownMonochromeRelation	18, 366
\GTSdirectedAdjacencyDownRelation	10, 170
\GTSdirectedAdjacencyUp	9, 153
\GTSdirectedAdjacencyUpMonochrome	16, 336
\GTSdirectedAdjacencyUpMonochromeRelation	17, 342
\GTSdirectedAdjacencyUpRelation	9, 156
\GTSi	12, 284, 287, 288, 289
\GTSiI	14, 308, 311, 312, 313
\GTSiIM	22, 422, 426, 427, 428, 429
\GTSiIMR	23, 426
\GTSiIR	14, 311
\GTSiM	19, 384, 388, 389, 390, 391
\GTSiMR	19, 388
\GTSinc	12, 284
\GTSincidence	12, 284
\GTSincidenceMonochrome	19, 384
\GTSincidenceMonochromeRelation	19, 388
\GTSincidenceRelation	12, 287
\GTSincMon	19, 384
\GTSincMono	19, 384
\GTSincMonoRel	19, 388
\GTSincMonRel	19, 388
\GTSincRel	12, 287
\GTSinInc	14, 308
\GTSinIncidence	14, 308
\GTSinIncidenceMonochrome	22, 422
\GTSinIncidenceMonochromeRelation	23, 426
\GTSinIncidenceRelation	14, 311
\GTSinIncMon	22, 422
\GTSinIncMono	22, 422
\GTSinIncMonoRel	23, 426
\GTSinIncMonRel	23, 426
\GTSinIncRel	14, 311
\GTSiR	12, 287
\GTSmA	24, 453, 463, 464, 465, 501
\GTSmAR	24, 463, 499
\GTSmetaAnd	24, 453
\GTSmetaAndRel	24, 463
\GTSmetaAndRelation	24, 463
\GTSmetaNot	24, 442
\GTSmetaOr	24, 466
\GTSmetaOrRel	24, 476
\GTSmetaOrRelation	24, 476
\GTSmN	24, 442, 496
\GTSmO	24, 466, 476, 477, 478, 507
\GTSmOR	24, 476, 505
\GTSnDAD	10, 173, 177, 179, 180
\GTSnDADM	18, 372, 379, 381, 382, 383
\GTSnDADMR	19, 378
\GTSnDADR	11, 176
\GTSnDAU	9, 159, 163, 165, 166
\GTSnDAUM	17, 348, 355, 357, 358, 359

\GTSnDAUMR	17, 354
\GTSnDAUR	10, 162
\GTSnegatedDirectedAdjacencyDown	10, 173
\GTSnegatedDirectedAdjacencyDownMonochrome	18, 372
\GTSnegatedDirectedAdjacencyDownMonochromeRelation	19, 378
\GTSnegatedDirectedAdjacencyDownRelation	11, 176
\GTSnegatedDirectedAdjacencyUp	9, 159
\GTSnegatedDirectedAdjacencyUpMonochrome	17, 348
\GTSnegatedDirectedAdjacencyUpMonochromeRelation	17, 354
\GTSnegatedDirectedAdjacencyUpRelation	10, 162
\GTSnegatedIncidence	12, 290
\GTSnegatedIncidenceMonochrome	19, 392
\GTSnegatedIncidenceMonochromeRelation	20, 398
\GTSnegatedIncidenceRelation	12, 293
\GTSnegatedInIncidence	14, 314
\GTSnegatedInIncidenceMonochrome	23, 430
\GTSnegatedInIncidenceMonochromeRelation	23, 436
\GTSnegatedInIncidenceRelation	15, 317
\GTSnegatedOutIncidence	13, 302
\GTSnegatedOutIncidenceMonochrome	22, 410
\GTSnegatedOutIncidenceMonochromeRelation	22, 416
\GTSnegatedOutIncidenceRelation	14, 305
\GTSnegDirAdjDown	10, 173
\GTSnegDirAdjDownMon	18, 372
\GTSnegDirAdjDownMono	18, 372
\GTSnegDirAdjDownMonoRel	19, 378
\GTSnegDirAdjDownMonRel	19, 378
\GTSnegDirAdjDownRel	11, 176
\GTSnegDirAdjUp	9, 159
\GTSnegDirAdjUpMon	17, 348
\GTSnegDirAdjUpMono	17, 348
\GTSnegDirAdjUpMonoRel	17, 354
\GTSnegDirAdjUpMonRel	17, 354
\GTSnegDirAdjUpRel	10, 162
\GTSnegInc	12, 290
\GTSnegIncMon	19, 392
\GTSnegIncMono	19, 392
\GTSnegIncMonoRel	20, 398
\GTSnegIncMonRel	20, 398
\GTSnegIncRel	12, 293
\GTSnegInInc	14, 314
\GTSnegInIncMon	23, 430
\GTSnegInIncMono	23, 430
\GTSnegInIncMonoRel	23, 436
\GTSnegInIncMonRel	23, 436
\GTSnegInIncRel	15, 317
\GTSnegOutInc	13, 302
\GTSnegOutIncMon	22, 410
\GTSnegOutIncMono	22, 410
\GTSnegOutIncMonoRel	22, 416
\GTSnegOutIncMonRel	22, 416
\GTSnegOutIncRel	14, 305
\GTSnI	12, 290, 293, 294, 295
\GTSnII	14, 314, 317, 318, 319
\GTSnIIM	23, 430, 437, 439, 440, 441
\GTSnIIMR	23, 436
\GTSnIIR	15, 317
\GTSnIM	19, 392, 398, 399, 400, 401
\GTSnIMR	20, 398
\GTSnIR	12, 293
\GTSnOI	13, 302, 305, 306, 307

\GTSnOIM	22, 410 , 417 , 419 , 420 , 421
\GTSnOIMR	22, 416
\GTSnOIR	14, 305
\GTSoI	13, 296 , 299 , 300 , 301
\GTSoIM	20, 402 , 406 , 407 , 408 , 409
\GTSoIMR	20, 406
\GTSoIR	13, 299
\GTSoutInc	13, 296
\GTSoutIncidence	13, 296
\GTSoutIncidenceMonochrome	20, 402
\GTSoutIncidenceMonochromeRelation	20, 406
\GTSoutIncidenceRelation	13, 299
\GTSoutIncMon	20, 402
\GTSoutIncMono	20, 402
\GTSoutIncMonoRel	20, 406
\GTSoutIncMonRel	20, 406
\GTSoutIncRel	13, 299
\GTSsetMainColor	7, 24 , 36 , 86 , 183 , 229
\GTSsetSecondColor	7, 29 , 39 , 89 , 186 , 232
\GTSu	8, 147 , 150 , 151 , 152
\GTSuM	15, 328 , 332 , 333 , 334 , 335
\GTSuMR	16, 332
\GTSunadj	8, 147
\GTSunadjacency	8, 147
\GTSunadjacencyMonochrome	15, 328
\GTSunadjacencyMonochromeRelation	16, 332
\GTSunadjacencyRelation	9, 150
\GTSunadjMon	15, 328
\GTSunadjMono	15, 328
\GTSunadjMonoRel	16, 332
\GTSunadjMonRel	16, 332
\GTSunadjRel	9, 150
\GTSuR	9, 150
\GTSx	25, 517
\GTSxa	8, 99 , 519
\GTSxadj	8, 99
\GTSxadjacency	8, 99
\GTSxi	11, 242 , 521
\GTSxinc	11, 242
\GTSxincidence	11, 242
\GTSxmetallogic	25, 479
\GTSxml	25, 479 , 523