

GraphTheorySymbol: L^AT_EX Commands with Symbols for Graph Theory

Laurent Frédéric Bernard François Lyaudet

Website: <https://lyaudet.eu/laurent/>

Email: Laurent.Lyaudet@gmail.com

v1.8.0 2026/09/28

Abstract

This documentation is for L^AT_EX package GraphTheorySymbol. It provides symbols used in graph theory. The adjacency and incidence symbols, and the meta-logical operators symbols were created by the author of this package.

Contents

1	Introduction	3
2	Usage	4
2.1	Memo or for the impatient	4
2.2	Detailed usage	7
2.2.1	General macros	7
2.2.2	Standard adjacency macros	7
2.2.3	Standard incidence macros	11
2.2.4	Monochrome adjacency macros	15
2.2.5	Monochrome incidence macros	20
2.2.6	Meta-logic macros	24
2.3	Good practices	26
3	Implementation	26
4	Acknowledgments	39
5	FAQ	40
6	Support	40
7	Change History	40

1 Introduction

This documentation is for $\text{\LaTeX}$ package GraphTheorySymbol. It provides symbols used in graph theory. The adjacency and incidence symbols, and the meta-logical operators symbols were created by the author of this package.

This package is licenced under Lesser GNU General Public License version 3 or later (LGPLv3+). It means you are free do anything with it, but if you do improve the code of the symbols that we provide, please do share these improvements in a similar way. There is no restriction on other graph theory symbols/code, even if it would be a good fit for inclusion in this package. There is also no need to share in a similar way what you build with this package. The text of the licenses is available at:

<https://www.gnu.org/licenses/>.

The git repository of this source code is also available at:

<https://github.com/LLyaudet/GraphTheorySymbol/>.

Clone it with this URL:

[git@github.com:LLyaudet/GraphTheorySymbol.git](https://github.com/LLyaudet/GraphTheorySymbol.git).

This package is available on CTAN:

<https://ctan.org/pkg/graph-theory-symbol>.

This is our first $\text{\LaTeX}$ package. It may be that our macros are quite slow and that a document making extensive use of these macros will be slow to compile. If you know how to produce better $\text{\LaTeX}$ code, please submit a pull request on GitHub.

2 Usage

2.1 Memo or for the impatient

Add in your preamble: `\usepackage{graph-theory-symbol}`.

For clarity, below we only show long macro names and short macro names; see Detailed usage section for intermediate length macro names.

Long name	Short name	Result	In context
<code>\GTSadjacency/</code>	<code>\GTSa/</code>	$\circ$	$u \circ v$
<code>\GTSadjacencyRelation/</code>	<code>\GTSaR/</code>	$\circ$	$u \circ v$
<code>\GTSunadjacency/</code>	<code>\GTSu/</code>	$\circ$	$u \circ v$
<code>\GTSunadjacencyRelation/</code>	<code>\GTSuR/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyUp/</code>	<code>\GTSdAU/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyUpRelation/</code>	<code>\GTSdAUR/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyUp/</code>	<code>\GTSnDAU/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyUpRelation/</code>	<code>\GTSnDAUR/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyDown/</code>	<code>\GTSdAD/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyDownRelation/</code>	<code>\GTSdADR/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyDown/</code>	<code>\GTSnDAD/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyDownRelation/</code>	<code>\GTSnDADR/</code>	$\circ$	$u \circ v$
<code>\GTSincidence/</code>	<code>\GTSi/</code>	$\circ$	$v \circ e$
<code>\GTSincidenceRelation/</code>	<code>\GTSiR/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedIncidence/</code>	<code>\GTSnI/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedIncidenceRelation/</code>	<code>\GTSnIR/</code>	$\circ$	$v \circ e$
<code>\GTSoutIncidence/</code>	<code>\GTSOI/</code>	$\circ$	$v \circ e$
<code>\GTSoutIncidenceRelation/</code>	<code>\GTSOIR/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedOutIncidence/</code>	<code>\GTSnOI/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedOutIncidenceRelation/</code>	<code>\GTSnOIR/</code>	$\circ$	$v \circ e$
<code>\GTSinIncidence/</code>	<code>\GTSiI/</code>	$\circ$	$v \circ e$
<code>\GTSinIncidenceRelation/</code>	<code>\GTSiIR/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedInIncidence/</code>	<code>\GTSnII/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedInIncidenceRelation/</code>	<code>\GTSnIIR/</code>	$\circ$	$v \circ e$
Long name	Short name	Result	In context
<code>\GTSadjacencyMonochrome/</code>	<code>\GTSaM/</code>	$\circ$	$u \circ v$
<code>\GTSadjacencyMonochromeRelation/</code>	<code>\GTSaMR/</code>	$\circ$	$u \circ v$
<code>\GTSunadjacencyMonochrome/</code>	<code>\GTSuM/</code>	$\circ$	$u \circ v$
<code>\GTSunadjacencyMonochromeRelation/</code>	<code>\GTSuMR/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyUpMonochrome/</code>	<code>\GTSdAUM/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyUpMonochromeRelation/</code>	<code>\GTSdAUMR/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyUpMonochrome/</code>	<code>\GTSnDAUM/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyUpMonochromeRelation/</code>	<code>\GTSnDAUMR/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyDownMonochrome/</code>	<code>\GTSdADM/</code>	$\circ$	$u \circ v$
<code>\GTSdirectedAdjacencyDownMonochromeRelation/</code>	<code>\GTSdADMR/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyDownMonochrome/</code>	<code>\GTSnDADM/</code>	$\circ$	$u \circ v$
<code>\GTSnegatedDirectedAdjacencyDownMonochromeRelation/</code>	<code>\GTSnDADMR/</code>	$\circ$	$u \circ v$
<code>\GTSincidenceMonochrome/</code>	<code>\GTSiM/</code>	$\circ$	$v \circ e$
<code>\GTSincidenceMonochromeRelation/</code>	<code>\GTSiMR/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedIncidenceMonochrome/</code>	<code>\GTSnIM/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedIncidenceMonochromeRelation/</code>	<code>\GTSnIMR/</code>	$\circ$	$v \circ e$
<code>\GTSoutIncidenceMonochrome/</code>	<code>\GTSOIM/</code>	$\circ$	$v \circ e$
<code>\GTSoutIncidenceMonochromeRelation/</code>	<code>\GTSOIMR/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedOutIncidenceMonochrome/</code>	<code>\GTSnOIM/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedOutIncidenceMonochromeRelation/</code>	<code>\GTSnOIMR/</code>	$\circ$	$v \circ e$
<code>\GTSinIncidenceMonochrome/</code>	<code>\GTSiIM/</code>	$\circ$	$v \circ e$
<code>\GTSinIncidenceMonochromeRelation/</code>	<code>\GTSiIMR/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedInIncidenceMonochrome/</code>	<code>\GTSnIIM/</code>	$\circ$	$v \circ e$
<code>\GTSnegatedInIncidenceMonochromeRelation/</code>	<code>\GTSnIIMR/</code>	$\circ$	$v \circ e$

<code>\GTSsetMainColor{blue}</code>			
Long name	Short name	Result	In context
<code>\GTSadjacency/</code>	<code>\GTSa/</code>		$u \overset{b}{\rightarrow} v$
<code>\GTSadjacencyRelation/</code>	<code>\GTSaR/</code>		$u \overset{b}{\rightarrow} v$
<code>\GTSunadjacency/</code>	<code>\GTSu/</code>		$u \overset{b}{\rightarrow} v$
<code>\GTSunadjacencyRelation/</code>	<code>\GTSuR/</code>		$u \overset{b}{\rightarrow} v$
<code>\GTSdirectedAdjacencyUp/</code>	<code>\GTSdAU/</code>		$u \overset{b}{\rightarrow} v$
<code>\GTSdirectedAdjacencyUpRelation/</code>	<code>\GTSdAUR/</code>		$u \overset{b}{\rightarrow} v$
<code>\GTSnegatedDirectedAdjacencyUp/</code>	<code>\GTSnDAU/</code>		$u \overset{b}{\rightarrow} v$
<code>\GTSnegatedDirectedAdjacencyUpRelation/</code>	<code>\GTSnDAUR/</code>		$u \overset{b}{\rightarrow} v$
<code>\GTSdirectedAdjacencyDown/</code>	<code>\GTSdAD/</code>		$u \overset{b}{\rightarrow} v$
<code>\GTSdirectedAdjacencyDownRelation/</code>	<code>\GTSdADR/</code>		$u \overset{b}{\rightarrow} v$
<code>\GTSnegatedDirectedAdjacencyDown/</code>	<code>\GTSnDAD/</code>		$u \overset{b}{\rightarrow} v$
<code>\GTSnegatedDirectedAdjacencyDownRelation/</code>	<code>\GTSnDADR/</code>		$u \overset{b}{\rightarrow} v$
<code>\GTSincidence/</code>	<code>\GTSi/</code>		$v \overset{b}{\leftarrow} e$
<code>\GTSincidenceRelation/</code>	<code>\GTSiR/</code>		$v \overset{b}{\leftarrow} e$
<code>\GTSnegatedIncidence/</code>	<code>\GTSnI/</code>		$v \overset{b}{\leftarrow} e$
<code>\GTSnegatedIncidenceRelation/</code>	<code>\GTSnIR/</code>		$v \overset{b}{\leftarrow} e$
<code>\GTSoutIncidence/</code>	<code>\GTSOI/</code>		$v \overset{b}{\leftarrow} e$
<code>\GTSoutIncidenceRelation/</code>	<code>\GTSOIR/</code>		$v \overset{b}{\leftarrow} e$
<code>\GTSnegatedOutIncidence/</code>	<code>\GTSnOI/</code>		$v \overset{b}{\leftarrow} e$
<code>\GTSnegatedOutIncidenceRelation/</code>	<code>\GTSnOIR/</code>		$v \overset{b}{\leftarrow} e$
<code>\GTSinIncidence/</code>	<code>\GTSiI/</code>		$v \overset{b}{\leftarrow} e$
<code>\GTSinIncidenceRelation/</code>	<code>\GTSiIR/</code>		$v \overset{b}{\leftarrow} e$
<code>\GTSnegatedInIncidence/</code>	<code>\GTSnII/</code>		$v \overset{b}{\leftarrow} e$
<code>\GTSnegatedInIncidenceRelation/</code>	<code>\GTSnIIR/</code>		$v \overset{b}{\leftarrow} e$

Long name	Short name	Result	In context
<code>\GTSmetaNot/</code>	<code>\GTSmN/</code>		$\overset{m}{\neg}$
<code>\GTSmetaAnd/</code>	<code>\GTSmA/</code>		$\overset{m}{\wedge}$
<code>\GTSmetaOr/</code>	<code>\GTSmO/</code>		$\overset{m}{\vee}$

Meta-logic can be used for compound adjacency types, etc.

Implicit meta-and via concatenation, no space except around whole relations compositions, no parentheses via higher priority to meta-and, brackets when all possible adjacencies are specified between two vertices:

Tournament adjacency:

$\forall u, v, u \overset{m}{\vee} v.$

Tournament adjacency with maybe some colored edge also, who knows?:

$\forall u, v, u \overset{m}{\vee} v.$

Directed graph:

$\forall u, v, u \overset{m}{\vee} v.$

Oriented graph:

$\forall u, v, u \overset{m}{\vee} v.$

Tournament adjacency:

$\overset{m}{\vee}$ is obtained with `\mathrel{\{[\GTSdAD/\GTSnDAU/\GTSmO/\GTSnDAD/\GTSdAU/]}`.

Tournament adjacency with maybe some colored edge also, who knows?:

$\overset{m}{\vee}$ is obtained with `\mathrel{\{\GTSdAD/\GTSnDAU/\GTSmO/\GTSnDAD/\GTSdAU/}}`.

Directed graph:

$\overset{m}{\vee}$ is obtained with

`\mathrel{\{[\GTSdAD/\GTSnDAU/\GTSmO/\GTSnDAD/\GTSdAU/\GTSmO/\GTSdAD/\GTSdAU/\GTSmO/\GTSnDAD/\GTSnDAU/]}`.

Oriented graph:

$\overset{m}{\vee}$ is obtained with

`\mathrel{\{[\GTSdAD/\GTSnDAU/\GTSmO/\GTSnDAD/\GTSdAU/\GTSmO/\GTSnDAD/\GTSnDAU/]}`.

Prefix notation:

$\exists u, v, u \text{ [}\overset{\text{m}}{\underset{\text{m}}{\underset{\text{m}}{\text{V}}}}\text{]} v \Leftrightarrow \exists u, v, u \text{ [}\overset{\text{m}}{\underset{\text{m}}{\underset{\text{m}}{\text{V}}}}\text{]} v.$

$\exists v, e, v \text{ [}\overset{\text{m}}{\underset{\text{m}}{\underset{\text{m}}{\text{V}}}}\text{]} e \Leftrightarrow \exists v, e, v \text{ [}\overset{\text{m}}{\underset{\text{m}}{\underset{\text{m}}{\text{V}}}}\text{]} e.$

$\text{[}\overset{\text{m}}{\underset{\text{m}}{\underset{\text{m}}{\text{V}}}}\text{]}$ is obtained with

`\mathrel{\{\[ \GTSm0/\GTSxa[mC=red,d]\GTSxa[mC=green,d]\GTSxa[mC=blue,u]\}}}`.

$\text{[}\overset{\text{m}}{\underset{\text{m}}{\underset{\text{m}}{\text{V}}}}\text{]}$ is obtained with

`\mathrel{\{\[ \GTSm0/\GTSxi[mC=red,i]\GTSxi[mC=green,i]\GTSxi[mC=blue,o]\}}}`.

Apart from these symbol macros, versatile macros to call them all are available with options:

`\GTSxa[]`, `\GTSxadj[]`, or `\GTSxadjacency[]` for adjacency symbols,

`\GTSxi[]`, `\GTSxinc[]`, or `\GTSxincidence[]` for incidence symbols,

`\GTSxml[]`, or `\GTSxmetallogic[]` for meta-logic symbols,

`\GTSx[]{} for all symbols`

`(\GTSx[]\{a\} = \GTSxa[], \GTSx[]\{i\} = \GTSxi[], \GTSx[]\{m\} = \GTSxml[])`.

See Detailed usage section for full syntax of these macros.

2.2 Detailed usage

First you need to add in your preamble: `\usepackage{graph-theory-symbol}`.

All symbols macros were designed with ease of use in mind: they are called with a trailing slash, they can be called in text mode or in math mode, a variant with relation spacing for math mode exists with suffix “relation”.

For completeness, we also documented macros with an at sign, but as usual, you should not (have to) use them directly.

2.2.1 General macros

\GTS@newcommand This macro will enforce that the other macros are called with a trailing slash, avoiding problems with spaces after macro call.

Arguments:

`{\commandname}` The name of the command to create.

`{\commandcode}` The code of the command to create.

See its [implementation](#) on page 27.

\GTS@newprotectedcommand This macro will enforce that the other macros are called with a trailing slash, avoiding problems with spaces after macro call.

Arguments:

`{\commandname}` The name of the command to create.

`{\commandcode}` The code of the command to create.

See its [implementation](#) on page 27.

\GTSsetMainColor

This macro will set the main color used in GraphTheorySymbol. This color has initial value “black”.

Argument:

`{\color}` The color that must be used by GraphTheorySymbol afterward.

See its [implementation](#) on page 27.

\GTSsetSecondColor

This macro will set the second color used in GraphTheorySymbol. This color has initial value “gray”.

Argument:

`{\color}` The color that must be used by GraphTheorySymbol afterward.

See its [implementation](#) on page 27.

2.2.2 Standard adjacency macros

\GTS@a This macro will draw any of the adjacency symbols if the correct arguments are given. It is not expected to be used directly.

See the macros derived from it and **\GTS@b**: `\GTSxadjacency`, `\GTSxadj`, and `\GTSxa`.

Arguments:

`{\mainColor}` If non-empty, this color will be used as main color.

`{\secondColor}` If non-empty, this color will be used as second color.

`{\drawSlash}` Non-empty implies that a negation will be drawn.

`{\drawUpArrow}` Non-empty implies that an up-arrow will be drawn.

`{\drawDownArrow}` Non-empty implies that a down-arrow will be drawn.

See its [implementation](#) on page 27.

\GTS@b This macro builds on top of **\GTS@a** to handle mathematical relation spacing if sixth argument is not empty. It is not expected to be used directly.

See the macros derived from it and **\GTS@a**: `\GTSxadjacency`, `\GTSxadj`, and `\GTSxa`.

Arguments:

`{\mainColor}` If non-empty, this color will be used as main color.

`{\secondColor}` If non-empty, this color will be used as second color.

`{\drawSlash}` Non-empty implies that a negation will be drawn.

$\{\langle drawUpArrow \rangle\}$ Non-empty implies that an up-arrow will be drawn.
 $\{\langle drawDownArrow \rangle\}$ Non-empty implies that a down-arrow will be drawn.
 $\{\langle relation \rangle\}$ Non-empty implies that relation spacing will be added.
See its [implementation](#) on page 28.

$\backslash\text{GTSxadjacency}$, $\backslash\text{GTSxadj}$, $\backslash\text{GTSxa}$ Versatile macros for adjacency that can be given options.

Argument:

$[\langle optionsList \rangle]$ Sets the following options if not empty:

$\text{mainColor}=\text{color1}$ or $\text{mainC}=\text{color1}$ or $\text{mColor}=\text{color1}$ or $\text{mC}=\text{color1}$,
 $\text{secondColor}=\text{color2}$ or $\text{secondC}=\text{color2}$ or $\text{sColor}=\text{color2}$ or $\text{sC}=\text{color2}$,
 monochrome or mono or mon or m (equivalent to $\text{mC}=\text{black}$, $\text{sC}=\text{black}$),
 negated or not or n ,
 up or u ,
 down or d ,
 relation or rel or r .

See their [implementations](#) on page 28.

$\backslash\text{GTSadjacency}$, $\backslash\text{GTSadj}$, $\backslash\text{GTSa}$ These macros will draw an adjacency symbol. A first drawing didn't include the small dots in the middle of the two circles corresponding to the graph vertices. But it was too similar to “spoon” and multimap symbols, and could be confused with a graph with only two vertices and one edge. Hence, these dots were added and they have the nice property to remind of the classical textual notation of adjacency relation as $\text{Adj}(.,.)$.

$\boxed{\text{A}.\backslash\text{GTSadjacency}/\text{A}.}$

or $\boxed{\text{A}.\backslash\text{GTSadj}/\text{A}.}$

or $\boxed{\text{A}.\backslash\text{GTSa}/\text{A}.}$

will yield $\boxed{\text{A}.\circ\text{A}.}$

$\boxed{\text{u} \backslash\text{GTSadjacency}/ \text{v}}$

or $\boxed{\text{u} \backslash\text{GTSadj}/ \text{v}}$

or $\boxed{\text{u} \backslash\text{GTSa}/ \text{v}}$

will yield $\boxed{\text{u} \circ \text{v}.}$

$\boxed{\$u \backslash\text{GTSadjacency}/ v\$}$

or $\boxed{\$u \backslash\text{GTSadj}/ v\$}$

or $\boxed{\$u \backslash\text{GTSa}/ v\$}$

will yield $\boxed{u \circ v}.$

See their [implementations](#) on page 29.

$\backslash\text{GTSadjacencyRelation}$, $\backslash\text{GTSadjRel}$, $\backslash\text{GTSaR}$

These macros will draw an adjacency symbol with relation spacing in math mode.

$\boxed{\$u\backslash\text{GTSadjacencyRelation}/v\$}$

or $\boxed{\$u\backslash\text{GTSadjRel}/v\$}$

or $\boxed{\$u\backslash\text{GTSaR}/v\$}$

will yield $\boxed{u \circ v}.$

See their [implementations](#) on page 29.

$\backslash\text{GTSunadjacency}$, $\backslash\text{GTSunadj}$, $\backslash\text{GTSu}$ These macros will draw an unadjacency symbol.

$\boxed{\text{A}.\backslash\text{GTSunadjacency}/\text{A}.}$

or $\boxed{\text{A}.\backslash\text{GTSunadj}/\text{A}.}$

or $\boxed{\text{A}.\backslash\text{GTSu}/\text{A}.}$

will yield $A \circ A$.

`u \GTSunadjacency/ v`

or `u \GTSunadj/ v`

or `u \GTSu/ v`

will yield $u \circ v$.

`$u \GTSunadjacency/ v$`

or `$u \GTSunadj/ v$`

or `$u \GTSu/ v$`

will yield $u \circ v$.

See their [implementations](#) on page 29.

`\GTSunadjacencyRelation`, `\GTSunadjRel`, `\GTSuR`

These macros will draw an unadjacency symbol with relation spacing in math mode.

`$u \GTSunadjacencyRelation/v$`

or `$u \GTSunadjRel/v$`

or `$u \GTSuR/v$`

will yield $u \circ v$.

See their [implementations](#) on page 29.

`\GTSdirectedAdjacencyUp`, `\GTSdirAdjUp`, `\GTSdAU`

These macros will draw a directed adjacency upward symbol.

The operand on the left of the symbol should be considered the source of the arc; the operand on the right of the symbol should be considered the target of the arc.

`A.\GTSdirectedAdjacencyUp/A.`

or `A.\GTSdirAdjUp/A.`

or `A.\GTSdAU/A.`

will yield $A \circ A$.

`u \GTSdirectedAdjacencyUp/ v`

or `u \GTSdirAdjUp/ v`

or `u \GTSdAU/ v`

will yield $u \circ v$.

`$u \GTSdirectedAdjacencyUp/ v$`

or `$u \GTSdirAdjUp/ v$`

or `$u \GTSdAU/ v$`

will yield $u \circ v$.

See their [implementations](#) on page 29.

`\GTSdirectedAdjacencyUpRelation`, `\GTSdirAdjUpRel`, `\GTSdAUR`

These macros will draw a directed adjacency upward symbol with relation spacing in math mode.

`$u \GTSdirectedAdjacencyUpRelation/v$`

or `$u \GTSdirAdjUpRel/v$`

or `$u \GTSdAUR/v$`

will yield $u \circ v$.

See their [implementations](#) on page 30.

\GTSnegatedDirectedAdjacencyUp, \GTSnegDirAdjUp, \GTSnDAU

These macros will draw a negated directed adjacency upward symbol.

$A.\text{\GTSnegatedDirectedAdjacencyUp}/A.$

or $A.\text{\GTSnegDirAdjUp}/A.$

or $A.\text{\GTSnDAU}/A.$

will yield $A.\overset{\circ}{\rightharpoonup}A.$

$u\text{\GTSnegatedDirectedAdjacencyUp}/v$

or $u\text{\GTSnegDirAdjUp}/v$

or $u\text{\GTSnDAU}/v$

will yield $u\overset{\circ}{\rightharpoonup}v$

$\$u\text{\GTSnegatedDirectedAdjacencyUp}/v\$$

or $\$u\text{\GTSnegDirAdjUp}/v\$$

or $\$u\text{\GTSnDAU}/v\$$

will yield $u\overset{\circ}{\rightharpoonup}v$

See their [implementations](#) on page 30.

\GTSnegatedDirectedAdjacencyUpRelation, \GTSnegDirAdjUpRel, \GTSnDAUR These macros will draw a negated directed adjacency upward symbol with relation spacing in math mode.

$\$u\text{\GTSnegatedDirectedAdjacencyUpRelation}/v\$$

or $\$u\text{\GTSnegDirAdjUpRel}/v\$$

or $\$u\text{\GTSnDAUR}/v\$$

will yield $u\overset{\circ}{\rightharpoonup}v$

See their [implementations](#) on page 30.

\GTSdirectedAdjacencyDown, \GTSdirAdjDown, \GTSdAD

These macros will draw a directed adjacency downward symbol.

The operand on the left of the symbol should be considered the target of the arc; the operand on the right of the symbol should be considered the source of the arc.

$A.\text{\GTSdirectedAdjacencyDown}/A.$

or $A.\text{\GTSdirAdjDown}/A.$

or $A.\text{\GTSdAD}/A.$

will yield $A.\overset{\circ}{\searrow}A.$

$u\text{\GTSdirectedAdjacencyDown}/v$

or $u\text{\GTSdirAdjDown}/v$

or $u\text{\GTSdAD}/v$

will yield $u\overset{\circ}{\searrow}v$

$\$u\text{\GTSdirectedAdjacencyDown}/v\$$

or $\$u\text{\GTSdirAdjDown}/v\$$

or $\$u\text{\GTSdAD}/v\$$

will yield $u\overset{\circ}{\searrow}v$

See their [implementations](#) on page 30.

\GTSdirectedAdjacencyDownRelation, \GTSdirAdjDownRel, \GTSdADR

These macros will draw a directed adjacency downward symbol with relation spacing in math mode.

`\$u\GTSdirectedAdjacencyDownRelation/v\$`

or `\$u\GTSdirAdjDownRel/v\$`

or `\$u\GTSdADR/v\$`

will yield $u \Downarrow v$.

See their [implementations](#) on page 30.

\GTSnegatedDirectedAdjacencyDown, \GTSnegDirAdjDown, \GTSnDAD

These macros will draw a negated directed adjacency downward symbol.

`A.\GTSnegatedDirectedAdjacencyDown/A.`

or `A.\GTSnegDirAdjDown/A.`

or `A.\GTSnDAD/A.`

will yield $A \nDownarrow A$.

`u \GTSnegatedDirectedAdjacencyDown/ v`

or `u \GTSnegDirAdjDown/ v`

or `u \GTSnDAD/ v`

will yield $u \nDownarrow v$.

`\$u \GTSnegatedDirectedAdjacencyDown/ v\$`

or `\$u \GTSnegDirAdjDown/ v\$`

or `\$u \GTSnDAD/ v\$`

will yield $u \nDownarrow v$.

See their [implementations](#) on page 30.

\GTSnegatedDirectedAdjacencyDownRelation, \GTSnegDirAdjDownRel, \GTSnDADR

These macros will draw a negated directed adjacency downward symbol with relation spacing in math mode.

`\$u\GTSnegatedDirectedAdjacencyDownRelation/v\$`

or `\$u\GTSnegDirAdjDownRel/v\$`

or `\$u\GTSnDADR/v\$`

will yield $u \nDownarrow v$.

See their [implementations](#) on page 30.

2.2.3 Standard incidence macros

\GTS@i This macro will draw any of the incidence symbols if the correct arguments are given. It is not expected to be used directly.

See the macros derived from it and `\GTS@j`: `\GTSxincidence`, `\GTSxinc`, and `\GTSxi`.

The operand on the left of the symbol should be considered the vertex to which the edge/the operand on the right of the symbol is incident.

Arguments:

`\{<mainColor>\}` If non-empty, this color will be used as main color.

`\{<secondColor>\}` If non-empty, this color will be used as second color.

`\{<drawSlash>\}` Non-empty implies that a negation will be drawn.

`\{<drawUpArrow>\}` Non-empty implies that an up-arrow will be drawn.

`\{<drawDownArrow>\}` Non-empty implies that a down-arrow will be drawn.

See its [implementation](#) on page 30.

\GTS@j This macro builds on top of **\GTS@i** to handle mathematical relation spacing if sixth argument is not empty. It is not expected to be used directly.

See the macros derived from it and **\GTS@i**: **\GTSxincidence**, **\GTSxinc**, and **\GTSxi**.

Arguments:

{<mainColor>} If non-empty, this color will be used as main color.

{<secondColor>} If non-empty, this color will be used as second color.

{<drawSlash>} Non-empty implies that a negation will be drawn.

{<drawUpArrow>} Non-empty implies that an up-arrow will be drawn.

{<drawDownArrow>} Non-empty implies that a down-arrow will be drawn.

{<relation>} Non-empty implies that relation spacing will be added.

See its [implementation](#) on page 31.

\GTSxincidence, **\GTSxinc**, **\GTSxi** Versatile macros for incidence that can be given options.

Argument:

[<optionsList>] Sets the following options if not empty:

mainColor=color1 or **mainC=**color1 or **mColor=**color1 or **mC=**color1,

secondColor=color2 or **secondC=**color2 or **sColor=**color2 or **sC=**color2,

monochrome or **mono** or **mon** or **m** (equivalent to **mC=black,sC=black**),

negated or **not** or **n**,

in or **i**,

out or **o**,

relation or **rel** or **r**.

See their [implementations](#) on page 32.

\GTSincidence, **\GTSinc**, **\GTSi** These macros will draw an incidence symbol.

The operand on the left of the symbol should be considered the vertex to which the edge/the operand on the right of the symbol is incident.

A.\GTSincidence/A.

or **A.\GTSinc/A.**

or **A.\GTSi/A.**

will yield **A.⊥A.**

v \GTSincidence/ e

or **v \GTSinc/ e**

or **v \GTSi/ e**

will yield **v ⊥ e**

\$v \GTSincidence/ e\$

or **\$v \GTSinc/ e\$**

or **\$v \GTSi/ e\$**

will yield **$v \perp e$**

See their [implementations](#) on page 32.

\GTSincidenceRelation, **\GTSincRel**, **\GTSiR**

These macros will draw an incidence symbol with relation spacing in math mode.

\$v\GTSincidenceRelation/e\$

or **\$v\GTSincRel/e\$**

or **\$v\GTSiR/e\$**

will yield **$v \perp e$**

See their [implementations](#) on page 32.

\GTSnegatedIncidence, **\GTSnegInc**, **\GTSnI**

These macros will draw a negated incidence symbol.

`A.\GTSnegatedIncidence/A.`

or `A.\GTSnegInc/A.`

or `A.\GTSnI/A.`

will yield $A \not\vdash A$.

`v \GTSnegatedIncidence/ e`

or `v \GTSnegInc/ e`

or `v \GTSnI/ e`

will yield $v \not\vdash e$.

`$v \GTSnegatedIncidence/ e$`

or `$v \GTSnegInc/ e$`

or `$v \GTSnI/ e$`

will yield $v \not\vdash e$.

See their [implementations](#) on page 32.

`\GTSnegatedIncidenceRelation`, `\GTSnegIncRel`, `\GTSnIR`

These macros will draw a negated incidence symbol with relation spacing in math mode.

`$v\GTSnegatedIncidenceRelation/e$`

or `$v\GTSnegIncRel/e$`

or `$v\GTSnIR/e$`

will yield $v \not\vdash e$.

See their [implementations](#) on page 33.

`\GTSoutIncidence`, `\GTSoutInc`, `\GTSoI`

These macros will draw a directed incidence upward (out(ward) incidence) symbol.

The operand on the left of the symbol should be considered the vertex to which the arc/the operand on the right of the symbol is incident.

`A.\GTSoutIncidence/A.`

or `A.\GTSoutInc/A.`

or `A.\GTSoI/A.`

will yield $A \vdash A$.

`v \GTSoutIncidence/ e`

or `v \GTSoutInc/ e`

or `v \GTSoI/ e`

will yield $v \vdash e$.

`$v \GTSoutIncidence/ e$`

or `$v \GTSoutInc/ e$`

or `$v \GTSoI/ e$`

will yield $v \vdash e$.

See their [implementations](#) on page 33.

`\GTSoutIncidenceRelation`, `\GTSoutIncRel`, `\GTSoIR` These macros will draw a directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

`$v\GTSoutIncidenceRelation/e$`

or $\$v\backslash\text{GTSoutIncRel}/e\$$

or $\$v\backslash\text{GTSoIR}/e\$$

will yield $v \nrightarrow e$.

See their [implementations](#) on page 33.

$\backslash\text{GTSnegatedOutIncidence}$, $\backslash\text{GTSnegOutInc}$, $\backslash\text{GTSnOI}$

These macros will draw a negated directed incidence upward (out(ward) incidence) symbol.

$A.\backslash\text{GTSnegatedOutIncidence}/A.$

or $A.\backslash\text{GTSnegOutInc}/A.$

or $A.\backslash\text{GTSnOI}/A.$

will yield $A.\nrightarrow A.$

$v \backslash\text{GTSnegatedOutIncidence}/ e$

or $v \backslash\text{GTSnegOutInc}/ e$

or $v \backslash\text{GTSnOI}/ e$

will yield $v \nrightarrow e$.

$\$v \backslash\text{GTSnegatedOutIncidence}/ e\$$

or $\$v \backslash\text{GTSnegOutInc}/ e\$$

or $\$v \backslash\text{GTSnOI}/ e\$$

will yield $v \nrightarrow e$.

See their [implementations](#) on page 33.

$\backslash\text{GTSnegatedOutIncidenceRelation}$, $\backslash\text{GTSnegOutIncRel}$, $\backslash\text{GTSnOIR}$ These macros will draw a negated directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

$\$v\backslash\text{GTSnegatedOutIncidenceRelation}/e\$$

or $\$v\backslash\text{GTSnegOutIncRel}/e\$$

or $\$v\backslash\text{GTSnOIR}/e\$$

will yield $v \nrightarrow e$.

See their [implementations](#) on page 33.

$\backslash\text{GTSinIncidence}$, $\backslash\text{GTSinInc}$, $\backslash\text{GTSiI}$

These macros will draw a directed incidence downward (in(ward) incidence) symbol.

The operand on the left of the symbol should be considered the vertex to which the arc/the operand on the right of the symbol is incident.

$A.\backslash\text{GTSinIncidence}/A.$

or $A.\backslash\text{GTSinInc}/A.$

or $A.\backslash\text{GTSiI}/A.$

will yield $A.\rightarrow A.$

$v \backslash\text{GTSinIncidence}/ e$

or $v \backslash\text{GTSinInc}/ e$

or $v \backslash\text{GTSiI}/ e$

will yield $v \rightarrow e$.

$\$v \backslash\text{GTSinIncidence}/ e\$$

or $\$v \backslash\text{GTSinInc}/ e\$$

or $\$v \backslash \text{GTSiI} / e\$$

will yield $v \nrightarrow e$.

See their [implementations](#) on page 33.

$\backslash \text{GTSinIncidenceRelation}$, $\backslash \text{GTSinIncRel}$, $\backslash \text{GTSiIR}$ These macros will draw a directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.

$\$v \backslash \text{GTSinIncidenceRelation} / e\$$

or $\$v \backslash \text{GTSinIncRel} / e\$$

or $\$v \backslash \text{GTSiIR} / e\$$

will yield $v \rightarrowtail e$.

See their [implementations](#) on page 33.

$\backslash \text{GTSnegatedInIncidence}$, $\backslash \text{GTSnegInInc}$, $\backslash \text{GTSnII}$

These macros will draw a negated directed incidence downward (in(ward) incidence) symbol.

$A. \backslash \text{GTSnegatedInIncidence} / A.$

or $A. \backslash \text{GTSnegInInc} / A.$

or $A. \backslash \text{GTSnII} / A.$

will yield $A. \not\rightarrowtail A.$

$v \backslash \text{GTSnegatedInIncidence} / e$

or $v \backslash \text{GTSnegInInc} / e$

or $v \backslash \text{GTSnII} / e$

will yield $v \not\rightarrowtail e$.

$\$v \backslash \text{GTSnegatedInIncidence} / e\$$

or $\$v \backslash \text{GTSnegInInc} / e\$$

or $\$v \backslash \text{GTSnII} / e\$$

will yield $v \not\rightarrowtail e$.

See their [implementations](#) on page 33.

$\backslash \text{GTSnegatedInIncidenceRelation}$, $\backslash \text{GTSnegInIncRel}$, $\backslash \text{GTSnIIR}$ These macros will draw a negated directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.

$\$v \backslash \text{GTSnegatedInIncidenceRelation} / e\$$

or $\$v \backslash \text{GTSnegInIncRel} / e\$$

or $\$v \backslash \text{GTSnIIR} / e\$$

will yield $v \not\rightarrowtail e$.

See their [implementations](#) on page 34.

2.2.4 Monochrome adjacency macros

$\backslash \text{GTSadjacencyMonochrome}$, $\backslash \text{GTSadjMono}$, $\backslash \text{GTSadjMon}$, $\backslash \text{GTSaM}$

These macros will draw a monochrome adjacency symbol.

$A. \backslash \text{GTSadjacencyMonochrome} / A.$

or $A. \backslash \text{GTSadjMono} / A.$

or $A. \backslash \text{GTSadjMon} / A.$

or $A.\backslash\text{GTSaM}/A.$

will yield $A.\circ A.$

$u \backslash\text{GTSadjacencyMonochrome}/ v$

or $u \backslash\text{GTSadjMono}/ v$

or $u \backslash\text{GTSadjMon}/ v$

or $u \backslash\text{GTSaM}/ v$

will yield $u \circ v$

$\$u \backslash\text{GTSadjacencyMonochrome}/ v\$$

or $\$u \backslash\text{GTSadjMono}/ v\$$

or $\$u \backslash\text{GTSadjMon}/ v\$$

or $\$u \backslash\text{GTSaM}/ v\$$

will yield $u \circ v$

See their [implementations](#) on page 34.

$\backslash\text{GTSadjacencyMonochromeRelation}$, $\backslash\text{GTSadjMonoRel}$, $\backslash\text{GTSadjMonRel}$, $\backslash\text{GTSaMR}$

These macros will draw a monochrome adjacency symbol with relation spacing in math mode.

$\$u \backslash\text{GTSadjacencyMonochromeRelation}/ v\$$

or $\$u \backslash\text{GTSadjMonoRel}/ v\$$

or $\$u \backslash\text{GTSadjMonRel}/ v\$$

or $\$u \backslash\text{GTSaMR}/ v\$$

will yield $u \circ v$

See their [implementations](#) on page 34.

$\backslash\text{GTSunadjacencyMonochrome}$, $\backslash\text{GTSunadjMono}$, $\backslash\text{GTSunadjMon}$, $\backslash\text{GTSuM}$

These macros will draw a monochrome unadjacency symbol.

$A.\backslash\text{GTSunadjacencyMonochrome}/A.$

or $A.\backslash\text{GTSunadjMono}/A.$

or $A.\backslash\text{GTSunadjMon}/A.$

or $A.\backslash\text{GTSuM}/A.$

will yield $A.\circ A.$

$u \backslash\text{GTSunadjacencyMonochrome}/ v$

or $u \backslash\text{GTSunadjMono}/ v$

or $u \backslash\text{GTSunadjMon}/ v$

or $u \backslash\text{GTSuM}/ v$

will yield $u \circ v$

$\$u \backslash\text{GTSunadjacencyMonochrome}/ v\$$

or $\$u \backslash\text{GTSunadjMono}/ v\$$

or $\$u \backslash\text{GTSunadjMon}/ v\$$

or $\$u \backslash\text{GTSuM}/ v\$$

will yield $u \circ v$

See their [implementations](#) on page 34.

\GTSunadjacencyMonochromeRelation, \GTSunadjMonoRel, \GTSunadjMonRel, \GTSuMR

These macros will draw a monochrome unadjacency symbol with relation spacing in math mode.

$\$u\backslash\text{GTSunadjacencyMonochromeRelation}/v\$$

or $\$u\backslash\text{GTSunadjMonoRel}/v\$$

or $\$u\backslash\text{GTSunadjMonRel}/v\$$

or $\$u\backslash\text{GTSuMR}/v\$$

will yield $u \not\sim v$.

See their [implementations](#) on page 34.

\GTSdirectedAdjacencyUpMonochrome, \GTSdirAdjUpMono, \GTSdirAdjUpMon, \GTSdAUM

These macros will draw a monochrome directed adjacency upward symbol.

The operand on the left of the symbol should be considered the source of the arc; the operand on the right of the symbol should be considered the target of the arc.

$A.\backslash\text{GTSdirectedAdjacencyUpMonochrome}/A.$

or $A.\backslash\text{GTSdirAdjUpMono}/A.$

or $A.\backslash\text{GTSdirAdjUpMon}/A.$

or $A.\backslash\text{GTSdAUM}/A.$

will yield $A.\overset{\circ}{\sim}A.$

$u \backslash\text{GTSdirectedAdjacencyUpMonochrome}/ v$

or $u \backslash\text{GTSdirAdjUpMono}/ v$

or $u \backslash\text{GTSdirAdjUpMon}/ v$

or $u \backslash\text{GTSdAUM}/ v$

will yield $u \overset{\circ}{\sim} v$.

$\$u \backslash\text{GTSdirectedAdjacencyUpMonochrome}/ v\$$

or $\$u \backslash\text{GTSdirAdjUpMono}/ v\$$

or $\$u \backslash\text{GTSdirAdjUpMon}/ v\$$

or $\$u \backslash\text{GTSdAUM}/ v\$$

will yield $u \overset{\circ}{\sim} v$.

See their [implementations](#) on page 34.

\GTSdirectedAdjacencyUpMonochromeRelation, \GTSdirAdjUpMonoRel, \GTSdirAdjUpMonRel, \GTSdAUMR These macros will draw a monochrome directed adjacency upward symbol with relation spacing in math mode.

$\$u\backslash\text{GTSdirectedAdjacencyUpMonochromeRelation}/v\$$

or $\$u\backslash\text{GTSdirAdjUpMonoRel}/v\$$

or $\$u\backslash\text{GTSdirAdjUpMonRel}/v\$$

or $\$u\backslash\text{GTSdAUMR}/v\$$

will yield $u \overset{\circ}{\sim} v$.

See their [implementations](#) on page 34.

\GTSnegatedDirectedAdjacencyUpMonochrome, \GTSnegDirAdjUpMono, \GTSnegDirAdjUpMon, \GTSnDAUM

These macros will draw a monochrome negated directed adjacency upward symbol.

`A.\GTSnegatedDirectedAdjacencyUpMonochrome/A.`

or `A.\GTSnegDirAdjUpMono/A.`

or `A.\GTSnegDirAdjUpMon/A.`

or `A.\GTSnDAUM/A.`

will yield $A \overset{\circ}{\circ} A.$

`u \GTSnegatedDirectedAdjacencyUpMonochrome/ v`

or `u \GTSnegDirAdjUpMono/ v`

or `u \GTSnegDirAdjUpMon/ v`

or `u \GTSnDAUM/ v`

will yield $u \overset{\circ}{\circ} v.$

`$u \GTSnegatedDirectedAdjacencyUpMonochrome/ v$`

or `$u \GTSnegDirAdjUpMono/ v$`

or `$u \GTSnegDirAdjUpMon/ v$`

or `$u \GTSnDAUM/ v$`

will yield $u \overset{\circ}{\circ} v.$

See their [implementations](#) on page 35.

`\GTSnegatedDirectedAdjacencyUpMonochromeRelation`, `\GTSnegDirAdjUpMonoRel`, `\GT-SnegDirAdjUpMonRel`, `\GTSnDAUMR` These macros will draw a monochrome negated directed adjacency upward symbol with relation spacing in math mode.

`$u\GTSnegatedDirectedAdjacencyUpMonochromeRelation/v$`

or `$u\GTSnegDirAdjUpMonoRel/v$`

or `$u\GTSnegDirAdjUpMonRel/v$`

or `$u\GTSnDAUMR/v$`

will yield $u \overset{\circ}{\circ} v.$

See their [implementations](#) on page 35.

`\GTSdirectedAdjacencyDownMonochrome`, `\GTSdirAdjDownMono`,
`\GTSdirAdjDownMon`, `\GTSdADM`

These macros will draw a monochrome directed adjacency downward symbol.

The operand on the left of the symbol should be considered the target of the arc; the operand on the right of the symbol should be considered the source of the arc.

`A.\GTSdirectedAdjacencyDownMonochrome/A.`

or `A.\GTSdirAdjDownMono/A.`

or `A.\GTSdirAdjDownMon/A.`

or `A.\GTSdADM/A.`

will yield $A \overset{\circ}{\circ} A.$

`u \GTSdirectedAdjacencyDownMonochrome/ v`

or `u \GTSdirAdjDownMono/ v`

or `u \GTSdirAdjDownMon/ v`

or `u \GTSdADM/ v`

will yield $u \overset{\circ}{\circ} v.$

`$u \GTSdirectedAdjacencyDownMonochrome/ v$`

or `$u \GTSdirAdjDownMono/ v$`

or `$u \GTSdirAdjDownMon/ v$`

or `$u \GTSdADM/ v$`

will yield $u \Downarrow v$.

See their [implementations](#) on page 35.

`\GTSdirectedAdjacencyDownMonochromeRelation`, `\GTSdirAdjDownMonoRel`,
`\GTSdirAdjDownMonRel`, `\GTSdADMR` These macros will draw a monochrome directed adjacency downward symbol with relation spacing in math mode.

`$u\GTSdirectedAdjacencyDownMonochromeRelation/v$`

or `$u\GTSdirAdjDownMonoRel/v$`

or `$u\GTSdirAdjDownMonRel/v$`

or `$u\GTSdADMR/v$`

will yield $u \Downarrow v$.

See their [implementations](#) on page 35.

`\GTSnegatedDirectedAdjacencyDownMonochrome`, `\GTSnegDirAdjDownMono`,
`\GTSnegDirAdjDownMon`, `\GTSnDADM`

These macros will draw a monochrome negated directed adjacency downward symbol.

`A.\GTSnegatedDirectedAdjacencyDownMonochrome/A.`

or `A.\GTSnegDirAdjDownMono/A.`

or `A.\GTSnegDirAdjDownMon/A.`

or `A.\GTSnDADM/A.`

will yield $A \Downarrow A$.

`u \GTSnegatedDirectedAdjacencyDownMonochrome/ v`

or `u \GTSnegDirAdjDownMono/ v`

or `u \GTSnegDirAdjDownMon/ v`

or `u \GTSnDADM/ v`

will yield $u \Downarrow v$.

`$u \GTSnegatedDirectedAdjacencyDownMonochrome/ v$`

or `$u \GTSnegDirAdjDownMono/ v$`

or `$u \GTSnegDirAdjDownMon/ v$`

or `$u \GTSnDADM/ v$`

will yield $u \Downarrow v$.

See their [implementations](#) on page 35.

`\GTSnegatedDirectedAdjacencyDownMonochromeRelation`, `\GTSnegDirAdjDownMonoRel`,
`\GTSnegDirAdjDownMonRel`, `\GTSnDADMR` These macros will draw a monochrome negated directed adjacency downward symbol with relation spacing in math mode.

`$u\GTSnegatedDirectedAdjacencyDownMonochromeRelation/v$`

or `$u\GTSnegDirAdjDownMonoRel/v$`

or `$u\GTSnegDirAdjDownMonRel/v$`

or $\text{\$u\GTSnDADMR/v\$}$

will yield $u \overset{\circ}{\circ} v$.

See their [implementations](#) on page 36.

2.2.5 Monochrome incidence macros

$\backslash\text{GTSincidenceMonochrome}$, $\backslash\text{GTSincMono}$, $\backslash\text{GTSincMon}$, $\backslash\text{GTSiM}$

These macros will draw a monochrome incidence symbol.

The operand on the left of the symbol should be considered the vertex to which the edge/the operand on the right of the symbol is incident.

$\text{A.\GTSincidenceMonochrome/A.}$

or $\text{A.\GTSincMono/A.}$

or $\text{A.\GTSincMon/A.}$

or $\text{A.\GTSiM/A.}$

will yield $A \overset{\circ}{\circ} A$.

$v \backslash\text{GTSincidenceMonochrome/ e}$

or $v \backslash\text{GTSincMono/ e}$

or $v \backslash\text{GTSincMon/ e}$

or $v \backslash\text{GTSiM/ e}$

will yield $v \overset{\circ}{\circ} e$.

$\text{\$v \GTSincidenceMonochrome/ e\$}$

or $\text{\$v \GTSincMono/ e\$}$

or $\text{\$v \GTSincMon/ e\$}$

or $\text{\$v \GTSiM/ e\$}$

will yield $v \overset{\circ}{\circ} e$.

See their [implementations](#) on page 36.

$\backslash\text{GTSincidenceMonochromeRelation}$, $\backslash\text{GTSincMonoRel}$, $\backslash\text{GTSincMonRel}$, $\backslash\text{GTSiMR}$

These macros will draw a monochrome incidence symbol with relation spacing in math mode.

$\text{\$v\GTSincidenceMonochromeRelation/e\$}$

or $\text{\$v\GTSincMonoRel/e\$}$

or $\text{\$v\GTSincMonRel/e\$}$

or $\text{\$v\GTSiMR/e\$}$

will yield $v \overset{\circ}{\circ} e$.

See their [implementations](#) on page 36.

$\backslash\text{GTSnegatedIncidenceMonochrome}$, $\backslash\text{GTSnegIncMono}$, $\backslash\text{GTSnegIncMon}$, $\backslash\text{GTSnIM}$

These macros will draw a monochrome negated incidence symbol.

$\text{A.\GTSnegatedIncidenceMonochrome/A.}$

or $\text{A.\GTSnegIncMono/A.}$

or $\text{A.\GTSnegIncMon/A.}$

or $\text{A.\GTSnIM/A.}$

will yield $A \overset{\circ}{\circ} A$.

$v \backslash\text{GTSnegatedIncidenceMonochrome/ e}$

or $v \backslash\text{GTSnegIncMono/ e}$

or $v \setminus \text{GTSnegIncMon} / e$

or $v \setminus \text{GTSnIM} / e$

will yield $v \not\hookrightarrow e$.

$\$v \setminus \text{GTSnegatedIncidenceMonochrome} / e\$$

or $\$v \setminus \text{GTSnegIncMono} / e\$$

or $\$v \setminus \text{GTSnegIncMon} / e\$$

or $\$v \setminus \text{GTSnIM} / e\$$

will yield $v \not\hookrightarrow e$.

See their [implementations](#) on page 36.

$\setminus \text{GTSnegatedIncidenceMonochromeRelation}$, $\setminus \text{GTSnegIncMonoRel}$, $\setminus \text{GTSnegIncMonRel}$, $\setminus \text{GTSnIMR}$

These macros will draw a monochrome negated incidence symbol with relation spacing in math mode.

$\$v \setminus \text{GTSnegatedIncidenceMonochromeRelation} / e\$$

or $\$v \setminus \text{GTSnegIncMonoRel} / e\$$

or $\$v \setminus \text{GTSnegIncMonRel} / e\$$

or $\$v \setminus \text{GTSnIMR} / e\$$

will yield $v \not\hookrightarrow e$.

See their [implementations](#) on page 36.

$\setminus \text{GTSoutIncidenceMonochrome}$, $\setminus \text{GTSoutIncMono}$, $\setminus \text{GTSoutIncMon}$, $\setminus \text{GTSoIM}$

These macros will draw a monochrome directed incidence upward (out(ward) incidence) symbol.

The operand on the left of the symbol should be considered the vertex to which the arc/the operand on the right of the symbol is incident.

$A. \setminus \text{GTSoutIncidenceMonochrome} / A.$

or $A. \setminus \text{GTSoutIncMono} / A.$

or $A. \setminus \text{GTSoutIncMon} / A.$

or $A. \setminus \text{GTSoIM} / A.$

will yield $A. \uparrow A.$

$v \setminus \text{GTSoutIncidenceMonochrome} / e$

or $v \setminus \text{GTSoutIncMono} / e$

or $v \setminus \text{GTSoutIncMon} / e$

or $v \setminus \text{GTSoIM} / e$

will yield $v \uparrow e$.

$\$v \setminus \text{GTSoutIncidenceMonochrome} / e\$$

or $\$v \setminus \text{GTSoutIncMono} / e\$$

or $\$v \setminus \text{GTSoutIncMon} / e\$$

or $\$v \setminus \text{GTSoIM} / e\$$

will yield $v \uparrow e$.

See their [implementations](#) on page 36.

$\setminus \text{GTSoutIncidenceMonochromeRelation}$, $\setminus \text{GTSoutIncMonoRel}$, $\setminus \text{GTSoutIncMonRel}$,

$\setminus \text{GTSoIMR}$ These macros will draw a monochrome directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

`$v\GTSoutIncidenceMonochromeRelation/e$`

or `$v\GTSoutIncMonoRel/e$`

or `$v\GTSoutIncMonRel/e$`

or `$v\GTSOIMR/e$`

will yield $v \nrightarrow e$.

See their [implementations](#) on page 36.

`\GTSnegatedOutIncidenceMonochrome`, `\GTSnegOutIncMono`, `\GTSnegOutIncMon`,
`\GTSnOIM`

These macros will draw a monochrome negated directed incidence upward (out(ward) incidence) symbol.

`A.\GTSnegatedOutIncidenceMonochrome/A.`

or `A.\GTSnegOutIncMono/A.`

or `A.\GTSnegOutIncMon/A.`

or `A.\GTSnOIM/A.`

will yield $A \nrightarrow A$.

`v \GTSnegatedOutIncidenceMonochrome/ e`

or `v \GTSnegOutIncMono/ e`

or `v \GTSnegOutIncMon/ e`

or `v \GTSnOIM/ e`

will yield $v \nrightarrow e$.

`$v \GTSnegatedOutIncidenceMonochrome/ e$`

or `$v \GTSnegOutIncMono/ e$`

or `$v \GTSnegOutIncMon/ e$`

or `$v \GTSnOIM/ e$`

will yield $v \nrightarrow e$.

See their [implementations](#) on page 37.

`\GTSnegatedOutIncidenceMonochromeRelation`, `\GTSnegOutIncMonoRel`,
`\GTSnegOutIncMonRel`, `\GTSnOIMR`

These macros will draw a monochrome negated directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

`$v\GTSnegatedOutIncidenceMonochromeRelation/e$`

or `$v\GTSnegOutIncMonoRel/e$`

or `$v\GTSnegOutIncMonRel/e$`

or `$v\GTSnOIMR/e$`

will yield $v \nrightarrow e$.

See their [implementations](#) on page 37.

`\GTSinIncidenceMonochrome`, `\GTSinIncMono`, `\GTSinIncMon`, `\GTSiIM`

These macros will draw a monochrome directed incidence downward (in(ward) incidence) symbol.

The operand on the left of the symbol should be considered the vertex to which the arc/the operand on the right of the symbol is incident.

`A.\GTSinIncidenceMonochrome/A.`

or `A.\GTSinIncMono/A.`

or `A.\GTSinIncMon/A.`

or $A.\text{\GTSiIM}/A.$

will yield $A.\text{\GTSiIM}A.$

$v \text{\GTSinIncidenceMonochrome}/ e$

or $v \text{\GTSinIncMono}/ e$

or $v \text{\GTSinIncMon}/ e$

or $v \text{\GTSiIM}/ e$

will yield $v \text{\GTSiIM} e.$

$\$v \text{\GTSinIncidenceMonochrome}/ e\$$

or $\$v \text{\GTSinIncMono}/ e\$$

or $\$v \text{\GTSinIncMon}/ e\$$

or $\$v \text{\GTSiIM}/ e\$$

will yield $v \text{\GTSiIM} e.$

See their [implementations](#) on page 37.

$\text{\GTSinIncidenceMonochromeRelation}$, $\text{\GTSinIncMonoRel}$, $\text{\GTSinIncMonRel}$, $\text{\GTSiIMR}$
These macros will draw a monochrome directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.

$\$v \text{\GTSinIncidenceMonochromeRelation}/ e\$$

or $\$v \text{\GTSinIncMonoRel}/ e\$$

or $\$v \text{\GTSinIncMonRel}/ e\$$

or $\$v \text{\GTSiIMR}/ e\$$

will yield $v \text{\GTSiIM} e.$

See their [implementations](#) on page 37.

$\text{\GTSnegatedInIncidenceMonochrome}$, $\text{\GTSnegInIncMono}$, $\text{\GTSnegInIncMon}$, $\text{\GTSnIIM}$

These macros will draw a monochrome negated directed incidence downward (in(ward) incidence) symbol.

$A.\text{\GTSnegatedInIncidenceMonochrome}/A.$

or $A.\text{\GTSnegInIncMono}/A.$

or $A.\text{\GTSnegInIncMon}/A.$

or $A.\text{\GTSnIIM}/A.$

will yield $A.\text{\GTSnIIM}A.$

$v \text{\GTSnegatedInIncidenceMonochrome}/ e$

or $v \text{\GTSnegInIncMono}/ e$

or $v \text{\GTSnegInIncMon}/ e$

or $v \text{\GTSnIIM}/ e$

will yield $v \text{\GTSnIIM} e.$

$\$v \text{\GTSnegatedInIncidenceMonochrome}/ e\$$

or $\$v \text{\GTSnegInIncMono}/ e\$$

or $\$v \text{\GTSnegInIncMon}/ e\$$

or $\$v \text{\GTSnIIM}/ e\$$

will yield $v \nrightarrow e$.

See their [implementations](#) on page 37.

\GTSnegatedInIncidenceMonochromeRelation, \GTSnegInIncMonoRel, \GTSnegInIncMonRel, \GTSnIIMR These macros will draw a monochrome negated directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.

$\$v\backslash\text{GTSnegatedInIncidenceMonochromeRelation}/e\$$

or $\$v\backslash\text{GTSnegInIncMonoRel}/e\$$

or $\$v\backslash\text{GTSnegInIncMonRel}/e\$$

or $\$v\backslash\text{GTSnIIMR}/e\$$

will yield $v \nrightarrow e$.

See their [implementations](#) on page 37.

2.2.6 Meta-logic macros

\GTSmetaNot, \GTSmN These macros will draw a meta-not or relation-not symbol.

$A.\backslash\text{GTSmetaNot}/A.$

or $A.\backslash\text{GTSmN}/A.$

will yield $A.\nrightarrow A.$

$u\backslash\text{GTSmetaNot}/\backslash\text{GTSdAU}/v$

or $u\backslash\text{GTSmN}/\backslash\text{GTSdAU}/v$

will yield $u \nrightarrow v.$

$\$u\backslash\text{GTSmetaNot}/\backslash\text{GTSdAU}/v\$$

or $\$u\backslash\text{GTSmN}/\backslash\text{GTSdAU}/v\$$

will yield $u \nrightarrow v.$

See their [implementations](#) on page 38.

\GTSmetaAnd, \GTSmA These macros will draw a meta-and or relations-and symbol. This is your duty to check that all relations have same arity. It should be easy as long as you remain in the realm of graphs/2-structures/binary structures. We didn't use Tarski's notation, since square cup has taken the preemptive meaning of disjoint union. Similarly, doublewedge or other wedge symbols have taken various meanings, whilst we want an unambiguous symbol.

Look at the discussion after all logical symbols for less trivial uses and recommendations.

$A.\backslash\text{GTSmetaAnd}/A.$

or $A.\backslash\text{GTSmA}/A.$

will yield $A.\nrightarrow A.$

$u\backslash\text{GTSdAD}/\backslash\text{GTSmetaAnd}/\backslash\text{GTSdAU}/v$

or $u\backslash\text{GTSdAD}/\backslash\text{GTSmA}/\backslash\text{GTSdAU}/v$

will yield $u \nrightarrow v.$

$\$u\backslash\text{GTSdAD}/\backslash\text{GTSmetaAnd}/\backslash\text{GTSdAU}/v\$$

or $\$u\backslash\text{GTSdAD}/\backslash\text{GTSmA}/\backslash\text{GTSdAU}/v\$$

will yield $u \nrightarrow v.$

See their [implementations](#) on page 38.

\GTSmetaAndRelation, \GTSmetaAndRel, \GTSmAR

These macros will draw a meta-and symbol with relation spacing in math mode.

$\$u\backslash\text{GTSdAD}/\backslash\text{GTSmetaAndRelation}/\backslash\text{GTSdAU}/v\$$

or $\$u\backslash\text{GTSdAD}/\backslash\text{GTSmetaAndRel}/\backslash\text{GTSdAU}/v\$$

or $\$u\backslash\text{GTSdAD}/\backslash\text{GTSmAR}/\backslash\text{GTSdAU}/v\$$

will yield $u \nrightarrow v.$

See their [implementations](#) on page 38.

\GTSmetaOr, \GTSmO These macros will draw a meta-or or relations-or symbol. This is your duty to check that all relations have same arity. It should be easy as long as you remain in the realm of graphs/2-structures/binary structures. We didn't use Tarski's notation, since square cup has taken the preemptive meaning of disjoint union. Similarly, doublewedge or other wedge symbols have taken various meanings, whilst we want an unambiguous symbol.

Look at the discussion after all logical symbols for less trivial uses and recommendations.

A.\GTSmetaOr/A.

or **A.\GTSmO/A.**

will yield $A \overset{\text{m}}{\vee} A$.

u \GTSdAD/\GTSmetaOr/\GTSdAU/ v

or **u \GTSdAD/\GTSmO/\GTSdAU/ v**

will yield $u \overset{\text{m}}{\vee} v$.

\$u \GTSdAD/ \GTSmetaOr/ \GTSdAU/ v\$

or **\$u \GTSdAD/ \GTSmO/ \GTSdAU/ v\$**

will yield $u \overset{\text{m}}{\vee} v$.

See their [implementations](#) on page 38.

\GTSmetaOrRelation, \GTSmetaOrRel, \GTSmOR

These macros will draw a meta-or symbol with relation spacing in math mode.

\$u \GTSdAD/\GTSmetaOrRelation/\GTSdAU/ v\$

or **\$u \GTSdAD/\GTSmetaOrRel/\GTSdAU/ v\$**

or **\$u \GTSdAD/\GTSmOR/\GTSdAU/ v\$**

will yield $u \overset{\text{m}}{\vee} v$.

See their [implementations](#) on page 38.

\GTSxmetallogic, \GTSxml Versatile macros for meta-logic symbols that can be given options.

Argument:

[\langle optionsList \rangle] Sets the following options if not empty:

not or **n**,

and or **a**,

or or **o**,

relation or **rel** or **r**.

Of course first three options are incompatible, and the fourth is compatible only with the second and third options.

See their [implementations](#) on page 38.

\GTSx One macro to rule them all.

Versatile macro for all symbols that can be given options, and a symbol type mandatory switch.

Argument:

[\langle optionsList \rangle] Sets the following options if not empty:

- If $\{\langle symbolType \rangle\}$ below is **a**, see **\GTSxa**:
 $\text{mainColor=}\text{color1}$ or $\text{mainC=}\text{color1}$ or $\text{mColor=}\text{color1}$ or $\text{mC=}\text{color1}$,
 $\text{secondColor=}\text{color2}$ or $\text{secondC=}\text{color2}$ or $\text{sColor=}\text{color2}$ or $\text{sC=}\text{color2}$,
 monochrome or mono or mon or m (equivalent to mC=black,sC=black),
 negated or not or **n**,
 up or **u**,
 down or **d**,
 relation or **rel** or **r**.
- If $\{\langle symbolType \rangle\}$ below is **i**, see **\GTSxi**:
 $\text{mainColor=}\text{color1}$ or $\text{mainC=}\text{color1}$ or $\text{mColor=}\text{color1}$ or $\text{mC=}\text{color1}$,
 $\text{secondColor=}\text{color2}$ or $\text{secondC=}\text{color2}$ or $\text{sColor=}\text{color2}$ or $\text{sC=}\text{color2}$,
 monochrome or mono or mon or m (equivalent to mC=black,sC=black),
 negated or not or **n**,
 in or **i**,

out or o,
relation or rel or r.

- If $\{\langle symbolType \rangle\}$ below is **m**, see `\GTSxml1:`
not or **n**,
and or **a**,
or or **o**,
relation or **rel** or **r**.

`{symbolType}` a mandatory switch; it can take value `a` for adjacency, `i` for incidence, `m` for meta-logic. See its [implementation](#) on page 39.

2.3 Good practices

As is customary in algebra and logic, the conjunction/multiplication can be replaced by concatenation, and has higher priority than disjunction. So the following formulas are equivalent; we recommend using the shortest one:

Tournament adjacency:

$$\forall u, v, u \text{ } \begin{array}{c} \textcircled{\text{g}} \textcircled{\text{g}} \\ \textcircled{\text{b}} \textcircled{\text{b}} \end{array} \overset{\text{m}}{\nabla} \begin{array}{c} \textcircled{\text{g}} \textcircled{\text{g}} \\ \textcircled{\text{b}} \textcircled{\text{b}} \end{array} v$$

is preferred over

$$\forall u, v, u \text{ $\otimes$ }^m \text{ $\wedge$ }^m \text{ $\vee$ }^m \text{ $\wedge$ }^m v,$$
$$\text{or } \forall u, v, u \left(\bigotimes_{\otimes}^m \bigotimes \right) \bigvee \left(\bigotimes_{\otimes}^m \bigotimes \right) v,$$

or even $\forall u, v, ((u \circledast v) \wedge (u \circledcirc v)) \vee ((u \circledcirc v) \wedge (u \circledast v))$.

Note the use of macros without Relation suffix above, and adding a single `\mathrel{}` around the composition of all relations:

$$\mathrel{\{\backslash\mathrm{GTSdAD}/\backslash\mathrm{GTSnDAU}/\backslash\mathrm{GTSmO}/\backslash\mathrm{GTSnDAD}/\backslash\mathrm{GTSdAU}/\}}.$$

This is the spacing practice that we recommend, although for very long compositions, it may be quite unreadable, and then spacing everything with `Relation` could/should be preferred.

We also recommend using brackets when the composition reflects all of the adjacencies between two vertices:

Tournament adjacency:

$$\forall u, v, u \left[\begin{array}{c} \textcircled{\circ} \textcircled{\circ} \textcircled{\circ}^{\text{m}} \textcircled{\circ} \textcircled{\circ} \\ \textcircled{\circ} \textcircled{\circ} \nabla \textcircled{\circ} \textcircled{\circ} \end{array} \right] v.$$

Tournament adjacency with maybe some colored edge also, who knows?:

$$\forall u, v, u \text{ --- } \overset{\circ}{\underset{\circ}{\vee}}^m \overset{\circ}{\underset{\circ}{\wedge}} v.$$

Directed graph:

[illegible]

Oriented graph:

$$\forall u, v, u \left[\begin{array}{c} \textcircled{\times} \textcircled{\times} \textcircled{\times} \textcircled{\times} \\ \textcircled{\times} \textcircled{\times} \textcircled{\times} \textcircled{\times} \end{array} \right] v.$$

Finally, we recommend prefix notation without “big” symbol for a sequence of consecutive ors or ands (with parentheses if needed):

$$\exists u, v, u \left[\overset{\text{m}}{\underset{\text{v}}{\nabla}}} \right] v.$$
$$\exists v, e, v \left[\overset{\text{m}}{\underset{\text{V}}{\vee}} \right] e.$$

3 Implementation

Below, we try to avoid repeating each macro description, and we give a hyperlink plus a page number reference of its description, after macro name(s). But if the description is only one sentence, we do repeat it here, because it makes no sense to have to go back and forth in the text for only one sentence.

```

1 \package
2 \RequirePackage{amsmath}
3 \RequirePackage{amssymb}
4 \RequirePackage{graphicx}
5 \RequirePackage{keyval}
6 \RequirePackage{fdsymbol}
7 \RequirePackage{lua-unicode-math}
8 \RequirePackage{xcolor}
9

```

```

10 \def\GTS@mainColor{black}
11 \def\GTS@secondColor{gray}
12 \def\GTS@mainColorBackup{black}
13 \def\GTS@secondColorBackup{gray}
14 \def\GTS@drawSlash{}
15 \def\GTS@drawUpArrow{}
16 \def\GTS@drawDownArrow{}
17

```

\GTS@newcommand See its [description](#) on page 7.

```

18 \@ifdefinable{\GTS@newcommand}{\def\GTS@newcommand#1#2{%
19   \@ifdefinable{#1}{\def#1/{#2}}
20 }}

```

\GTS@newprotectedcommand See its [description](#) on page 7.

```

21 \@ifdefinable{\GTS@newprotectedcommand}{\def\GTS@newprotectedcommand#1#2{%
22   \@ifdefinable{#1}{\protected\def#1/{#2}}
23 }}

```

\GTSsetMainColor See its [description](#) on page 7.

```

24 \newcommand{\GTSsetMainColor}[1]{%
25 \edef\GTS@mainColorTemp{#1}%
26 \edef\GTS@mainColorBackup{\GTS@mainColor}%
27 \edef\GTS@mainColor{\GTS@mainColorTemp}%
28 }

```

\GTSsetSecondColor See its [description](#) on page 7.

```

29 \newcommand{\GTSsetSecondColor}[1]{%
30 \edef\GTS@secondColorTemp{#1}%
31 \edef\GTS@secondColorBackup{\GTS@secondColor}%
32 \edef\GTS@secondColor{\GTS@secondColorTemp}%
33 }

```

\GTS@a See its [description](#) on page 7.

```

34 \newcommand{\GTS@a}[5]{%
35 \if#1\empty\else%
36 \GTSsetMainColor{#1}%
37 \fi%
38 \if#2\empty\else%
39 \GTSsetSecondColor{#2}%
40 \fi%
41 \text{\ensuremath{%
42 \raisebox{-0.32ex}{\scalebox{1.5}[1.5]{%
43 %
44 \raisebox{0.7ex}{\scalebox{0.7}[0.7]{%
45 $\mathcolor{\GTS@secondColor}{\circ}$%
46 }}%
47 \hspace{-0.39ex}%
48 \raisebox{1.05ex}{\scalebox{0.1}[0.1]{%
49 $\mathcolor{\GTS@secondColor}{\bullet}$%
50 }}%
51 \hspace{-0.12ex}%
52 \raisebox{0.11ex}{\scalebox{0.1}[0.73]{%
53 $\mathcolor{\GTS@mainColor}{\smallblacksquare}$%
54 }}%
55 \hspace{-0.40ex}%
56 \raisebox{-0.3ex}{\scalebox{0.7}[0.7]{%
57 $\mathcolor{\GTS@secondColor}{\circ}$%
58 }}%
59 \hspace{-0.39ex}%
60 \raisebox{0.05ex}{\scalebox{0.1}[0.1]{%

```

```

61 $\mathcolor{\GTS@secondColor}{\bullet}$%
62 }}%
63 \hspace{0.27ex}%
if GTS@drawUpArrow empty else
64 \if#4\empty\else%
65 \hspace{-0.65ex}%
66 \raisebox{-0.18ex}{\scalebox{0.5}[0.5]{%
67 \textcolor{\GTS@mainColor}{\textasciicircum}%
68 }}%
69 \fi%
if GTS@drawDownArrow empty else
70 \if#5\empty\else%
71 \hspace{-0.65ex}%
72 \raisebox{1.37ex}{\scalebox{0.5}[-0.5]{%
73 \textcolor{\GTS@mainColor}{\textasciicircum}%
74 }}%
75 \fi%
if GTS@drawSlash empty else
76 \if#3\empty\else%
77 \hspace{-0.65ex}%
78 \raisebox{0.25ex}{\scalebox{0.6}[0.6]{%
79 \textcolor{black}{/}%
80 }}%
81 \fi%
82 %
83 }}%
84 }}%
85 \if#1\empty\else%
86 \GTSsetMainColor{\GTS@mainColorBackup}%
87 \fi%
88 \if#2\empty\else%
89 \GTSsetSecondColor{\GTS@secondColorBackup}%
90 \fi%
91 }

```

\GTS@b See its [description](#) on page 7.

```

92 \newcommand{\GTS@b}[6]{%
93 \if#61%
94 \mathrel{\GTS@a{#1}{#2}{#3}{#4}{#5}}%
95 \else%
96 \GTS@a{#1}{#2}{#3}{#4}{#5}%
97 \fi%
98 }

```

\GTSxadjacency, \GTSxadj, \GTSxa See their [description](#) on page 8.

```

99 \define@key{GTSxa}{mainColor}{\def\GTS@@mainColor{#1}}
100 \define@key{GTSxa}{mainC}{\def\GTS@@mainColor{#1}}
101 \define@key{GTSxa}{mColor}{\def\GTS@@mainColor{#1}}
102 \define@key{GTSxa}{mC}{\def\GTS@@mainColor{#1}}
103 \define@key{GTSxa}{secondColor}{\def\GTS@@secondColor{#1}}
104 \define@key{GTSxa}{secondC}{\def\GTS@@secondColor{#1}}
105 \define@key{GTSxa}{sColor}{\def\GTS@@secondColor{#1}}
106 \define@key{GTSxa}{sC}{\def\GTS@@secondColor{#1}}
107 \define@key{GTSxa}{monochrome}[1]%
108 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
109 \define@key{GTSxa}{mono}[1]%
110 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
111 \define@key{GTSxa}{mon}[1]%
112 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
113 \define@key{GTSxa}{m}[1]%

```

```

114 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
115 \define@key{GTSxa}{negated}[1]{\def\GTS@@drawSlash{1}}
116 \define@key{GTSxa}{not}[1]{\def\GTS@@drawSlash{1}}
117 \define@key{GTSxa}{n}[1]{\def\GTS@@drawSlash{1}}
118 \define@key{GTSxa}{up}[1]{\def\GTS@@drawUpArrow{1}}
119 \define@key{GTSxa}{u}[1]{\def\GTS@@drawUpArrow{1}}
120 \define@key{GTSxa}{down}[1]{\def\GTS@@drawDownArrow{1}}
121 \define@key{GTSxa}{d}[1]{\def\GTS@@drawDownArrow{1}}
122 \define@key{GTSxa}{relation}[1]{\def\GTS@@relation{1}}
123 \define@key{GTSxa}{rel}[1]{\def\GTS@@relation{1}}
124 \define@key{GTSxa}{r}[1]{\def\GTS@@relation{1}}
125
126 \newcommand{\GTSxa}[1][]{\%
127 \def\GTS@@mainColor{}}
128 \def\GTS@@secondColor{}}
129 \def\GTS@@drawSlash{}}
130 \def\GTS@@drawUpArrow{}}
131 \def\GTS@@drawDownArrow{}}
132 \def\GTS@@relation{}}
133 \setkeys{GTSxa}{#1}}
134 \GTS@b{\GTS@@mainColor}{\GTS@@secondColor}{\GTS@@drawSlash}%
135 {\GTS@@drawUpArrow}{\GTS@@drawDownArrow}{\GTS@@relation}%
136 }
137
138 \newcommand{\GTSxadj}[1][]{\GTSxa[#1]}
139
140 \newcommand{\GTSxadjacency}[1][]{\GTSxa[#1]}

```

\GTSadjacency, \GTSadj, \GTSa These macros will draw an adjacency symbol. See their [description](#) and usage examples on page 8.

```

141 \GTS@newcommand{\GTSadjacency}{\GTS@a{}{}{}{}}
142 \GTS@newcommand{\GTSadj}{\GTS@a{}{}{}{}}
143 \GTS@newcommand{\GTSa}{\GTS@a{}{}{}{}}

```

\GTSadjacencyRelation, \GTSadjRel, \GTSaR

These macros will draw an adjacency symbol with relation spacing in math mode. See their [description](#) and usage examples on page 8.

```

144 \GTS@newcommand{\GTSadjacencyRelation}{\mathrel{\GTSa/}}
145 \GTS@newcommand{\GTSadjRel}{\mathrel{\GTSa/}}
146 \GTS@newcommand{\GTSaR}{\mathrel{\GTSa/}}

```

\GTSunadjacency, \GTSunadj, \GTSu These macros will draw an unadjacency symbol. See their [description](#) and usage examples on page 8.

```

147 \GTS@newcommand{\GTSunadjacency}{\GTS@a{}{}{1}{}}
148 \GTS@newcommand{\GTSunadj}{\GTS@a{}{}{1}{}}
149 \GTS@newcommand{\GTSu}{\GTS@a{}{}{1}{}}

```

\GTSunadjacencyRelation, \GTSunadjRel, \GTSuR

These macros will draw an unadjacency symbol with relation spacing in math mode. See their [description](#) and usage examples on page 9.

```

150 \GTS@newcommand{\GTSunadjacencyRelation}{\mathrel{\GTSu/}}
151 \GTS@newcommand{\GTSunadjRel}{\mathrel{\GTSu/}}
152 \GTS@newcommand{\GTSuR}{\mathrel{\GTSu/}}

```

\GTSdirectedAdjacencyUp, \GTSdirAdjUp, \GTSdAU

These macros will draw a directed adjacency upward symbol. See their [description](#) and usage examples on page 9.

```

153 \GTS@newcommand{\GTSdirectedAdjacencyUp}{\GTS@a{}{}{1}{}}
154 \GTS@newcommand{\GTSdirAdjUp}{\GTS@a{}{}{1}{}}
155 \GTS@newcommand{\GTSdAU}{\GTS@a{}{}{1}{}}

```

`\GTSdirectedAdjacencyUpRelation`, `\GTSdirAdjUpRel`, `\GTSdAUR`

These macros will draw a directed adjacency upward symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 9.

```
156 \GTS@newcommand{\GTSdirectedAdjacencyUpRelation}{\mathrel{\GTSdAU/}}
157 \GTS@newcommand{\GTSdirAdjUpRel}{\mathrel{\GTSdAU/}}
158 \GTS@newcommand{\GTSdAUR}{\mathrel{\GTSdAU/}}
```

`\GTSnegatedDirectedAdjacencyUp`, `\GTSnegDirAdjUp`, `\GTSnDAU`

These macros will draw a negated directed adjacency upward symbol.

See their [description](#) and usage examples on page 10.

```
159 \GTS@newcommand{\GTSnegatedDirectedAdjacencyUp}{\GTS@a{}{}{1}{1}{}}
160 \GTS@newcommand{\GTSnegDirAdjUp}{\GTS@a{}{}{1}{1}{}}
161 \GTS@newcommand{\GTSnDAU}{\GTS@a{}{}{1}{1}{}}
```

`\GTSnegatedDirectedAdjacencyUpRelation`, `\GTSnegDirAdjUpRel`, `\GTSnDAUR`

These macros will draw a negated directed adjacency upward symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 10.

```
162 \GTS@newcommand{\GTSnegatedDirectedAdjacencyUpRelation}{%
163 \mathrel{\GTSnDAU/}}%
164 }
165 \GTS@newcommand{\GTSnegDirAdjUpRel}{\mathrel{\GTSnDAU/}}
166 \GTS@newcommand{\GTSnDAUR}{\mathrel{\GTSnDAU/}}
```

`\GTSdirectedAdjacencyDown`, `\GTSdirAdjDown`, `\GTSdAD`

These macros will draw a directed adjacency downward symbol.

See their [description](#) and usage examples on page 10.

```
167 \GTS@newcommand{\GTSdirectedAdjacencyDown}{\GTS@a{}{}{}{1}}
168 \GTS@newcommand{\GTSdirAdjDown}{\GTS@a{}{}{}{1}}
169 \GTS@newcommand{\GTSdAD}{\GTS@a{}{}{}{1}}
```

`\GTSdirectedAdjacencyDownRelation`, `\GTSdirAdjDownRel`, `\GTSdADR`

These macros will draw a directed adjacency downward symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 11.

```
170 \GTS@newcommand{\GTSdirectedAdjacencyDownRelation}{\mathrel{\GTSdAD/}}
171 \GTS@newcommand{\GTSdirAdjDownRel}{\mathrel{\GTSdAD/}}
172 \GTS@newcommand{\GTSdADR}{\mathrel{\GTSdAD/}}
```

`\GTSnegatedDirectedAdjacencyDown`, `\GTSnegDirAdjDown`, `\GTSnDAD`

These macros will draw a negated directed adjacency downward symbol.

See their [description](#) and usage examples on page 11.

```
173 \GTS@newcommand{\GTSnegatedDirectedAdjacencyDown}{\GTS@a{}{}{1}{1}}
174 \GTS@newcommand{\GTSnegDirAdjDown}{\GTS@a{}{}{1}{1}}
175 \GTS@newcommand{\GTSnDAD}{\GTS@a{}{}{1}{1}}
```

`\GTSnegatedDirectedAdjacencyDownRelation`, `\GTSnegDirAdjDownRel`, `\GTSnDADR`

These macros will draw a negated directed adjacency downward symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 11.

```
176 \GTS@newcommand{\GTSnegatedDirectedAdjacencyDownRelation}{%
177 \mathrel{\GTSnDAD/}}%
178 }
179 \GTS@newcommand{\GTSnegDirAdjDownRel}{\mathrel{\GTSnDAD/}}
180 \GTS@newcommand{\GTSnDADR}{\mathrel{\GTSnDAD/}}
```

`\GTS@i` See its [description](#) on page 11.

```
181 \newcommand{\GTS@i}[5]{%
182 \if#1\empty\else%
183 \GTSsetMainColor{#1}%
184 \fi%
```

```

185 \if#2\empty\else%
186 \GTSsetSecondColor{#2}%
187 \fi%
188 \text{\ensuremath{%
189 \raisebox{-0.22ex}{\scalebox{2.05}[2.05]{%
190 %
191 \raisebox{-0.3ex}{\scalebox{0.7}[0.7]{%
192 $\mathcolor{\GTS@secondColor}{\circ}$%
193 }}%
194 \hspace{-0.39ex}%
195 \raisebox{0.05ex}{\scalebox{0.1}[0.1]{%
196 $\mathcolor{\GTS@secondColor}{\bullet}$%
197 }}%
198 \hspace{-0.12ex}%
199 \raisebox{0.11ex}{\scalebox{0.1}[0.73]{%
200 $\mathcolor{\GTS@secondColor}{\smallblacksquare}$%
201 }}%
202 \hspace{-0.18ex}%
203 \raisebox{0.15ex}{\scalebox{0.2}[0.2]{%
204 $\mathcolor{\GTS@mainColor}{\smallblacksquare}$%
205 }}%
206 \hspace{0.2ex}%
if GTS@drawUpArrow empty else
207 \if#4\empty\else%
208 \hspace{-0.65ex}%
209 \raisebox{-0.18ex}{\scalebox{0.5}[0.5]{%
210 \textcolor{\GTS@secondColor}{\textasciicircum}%
211 }}%
212 \fi%
if GTS@drawDownArrow empty else
213 \if#5\empty\else%
214 \hspace{-0.65ex}%
215 \raisebox{1.37ex}{\scalebox{0.5}[-0.5]{%
216 \textcolor{\GTS@secondColor}{\textasciicircum}%
217 }}%
218 \fi%
if GTS@drawSlash empty else
219 \if#3\empty\else%
220 \hspace{-0.65ex}%
221 \raisebox{0.1ex}{\scalebox{0.5}[0.5]{%
222 \textcolor{black}{/}%
223 }}%
224 \fi%
225 %
226 }}%
227 }%
228 \if#1\empty\else%
229 \GTSsetMainColor{\GTS@mainColorBackup}%
230 \fi%
231 \if#2\empty\else%
232 \GTSsetSecondColor{\GTS@secondColorBackup}%
233 \fi%
234 }

\GTS@j See its description on page 12.
235 \newcommand{\GTS@j}[6]{%
236 \if#61%
237 \mathrel{\GTS@i{#1}{#2}{#3}{#4}{#5}}%
238 \else%
239 \GTS@i{#1}{#2}{#3}{#4}{#5}%

```

240 \fi%
241 }
\GTSxincidence, \GTSxinc, \GTSxi See their [description](#) on page 12.

```

242 \define@key{GTSxi}{mainColor}{\def\GTS@@mainColor{#1}}
243 \define@key{GTSxi}{mainC}{\def\GTS@@mainColor{#1}}
244 \define@key{GTSxi}{mColor}{\def\GTS@@mainColor{#1}}
245 \define@key{GTSxi}{mC}{\def\GTS@@mainColor{#1}}
246 \define@key{GTSxi}{secondColor}{\def\GTS@@secondColor{#1}}
247 \define@key{GTSxi}{secondC}{\def\GTS@@secondColor{#1}}
248 \define@key{GTSxi}{sColor}{\def\GTS@@secondColor{#1}}
249 \define@key{GTSxi}{sC}{\def\GTS@@secondColor{#1}}
250 \define@key{GTSxi}{monochrome}[1]%
251 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
252 \define@key{GTSxi}{mono}[1]%
253 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
254 \define@key{GTSxi}{mon}[1]%
255 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
256 \define@key{GTSxi}{m}[1]%
257 {\def\GTS@@mainColor{black}\def\GTS@@secondColor{black}}
258 \define@key{GTSxi}{negated}[1]{\def\GTS@@drawSlash{1}}
259 \define@key{GTSxi}{not}[1]{\def\GTS@@drawSlash{1}}
260 \define@key{GTSxi}{n}[1]{\def\GTS@@drawSlash{1}}
261 \define@key{GTSxi}{out}[1]{\def\GTS@@drawUpArrow{1}}
262 \define@key{GTSxi}{o}[1]{\def\GTS@@drawUpArrow{1}}
263 \define@key{GTSxi}{in}[1]{\def\GTS@@drawDownArrow{1}}
264 \define@key{GTSxi}{i}[1]{\def\GTS@@drawDownArrow{1}}
265 \define@key{GTSxi}{relation}[1]{\def\GTS@@relation{1}}
266 \define@key{GTSxi}{rel}[1]{\def\GTS@@relation{1}}
267 \define@key{GTSxi}{r}[1]{\def\GTS@@relation{1}}
268
269 \newcommand{\GTSxi}[1][{}]{%
270 \def\GTS@@mainColor{}%
271 \def\GTS@@secondColor{}%
272 \def\GTS@@drawSlash{}%
273 \def\GTS@@drawUpArrow{}%
274 \def\GTS@@drawDownArrow{}%
275 \def\GTS@@relation{}%
276 \setkeys{GTSxi}{#1}%
277 \GTS@j{\GTS@@mainColor}{\GTS@@secondColor}{\GTS@@drawSlash}%
278 {\GTS@@drawUpArrow}{\GTS@@drawDownArrow}{\GTS@@relation}%
279 }
280
281 \newcommand{\GTSxinc}[1][{}]{\GTSxi[#1]}
282
283 \newcommand{\GTSxincidence}[1][{}]{\GTSxi[#1]}

```

\GTSincidence, \GTSinc, \GTSi These macros will draw an incidence symbol.
See their [description](#) and usage examples on page 12.

```

284 \GTS@newcommand{\GTSincidence}{\GTS@i{}{}{}{}}
285 \GTS@newcommand{\GTSinc}{\GTS@i{}{}{}{}}
286 \GTS@newcommand{\GTSi}{\GTS@i{}{}{}{}}

```

\GTSincidenceRelation, \GTSincRel, \GTSiR

These macros will draw an incidence symbol with relation spacing in math mode.
See their [description](#) and usage examples on page 12.

```

287 \GTS@newcommand{\GTSincidenceRelation}{\mathrel{\GTSi/}}
288 \GTS@newcommand{\GTSincRel}{\mathrel{\GTSi/}}
289 \GTS@newcommand{\GTSiR}{\mathrel{\GTSi/}}

```

\GTSnegatedIncidence, \GTSnegInc, \GTSnI These macros will draw a negated incidence symbol.
See their [description](#) and usage examples on page 12.

```

290 \GTS@newcommand{\GTSnegatedIncidence}{\GTS@i{}{}{1}{}{}}
291 \GTS@newcommand{\GTSnegInc}{\GTS@i{}{}{1}{}{}}
292 \GTS@newcommand{\GTSnI}{\GTS@i{}{}{1}{}{}}

```

\GTSnegatedIncidenceRelation, \GTSnegIncRel, \GTSnIR

These macros will draw a negated incidence symbol with relation spacing in math mode. See their [description](#) and usage examples on page 13.

```

293 \GTS@newcommand{\GTSnegatedIncidenceRelation}{\mathrel{\GTSnI/}}
294 \GTS@newcommand{\GTSnegIncRel}{\mathrel{\GTSnI/}}
295 \GTS@newcommand{\GTSnIR}{\mathrel{\GTSnI/}}

```

\GTSoutIncidence, \GTSoutInc, \GTSoI

These macros will draw a directed incidence upward (out(ward) incidence) symbol. See their [description](#) and usage examples on page 13.

```

296 \GTS@newcommand{\GTSoutIncidence}{\GTS@i{}{}{1}{}{}}
297 \GTS@newcommand{\GTSoutInc}{\GTS@i{}{}{1}{}{}}
298 \GTS@newcommand{\GTSoI}{\GTS@i{}{}{1}{}{}}

```

\GTSoutIncidenceRelation, \GTSoutIncRel, \GTSoIR These macros will draw a directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 13.

```

299 \GTS@newcommand{\GTSoutIncidenceRelation}{\mathrel{\GTSoI/}}
300 \GTS@newcommand{\GTSoutIncRel}{\mathrel{\GTSoI/}}
301 \GTS@newcommand{\GTSoIR}{\mathrel{\GTSoI/}}

```

\GTSnegatedOutIncidence, \GTSnegOutInc, \GTSnOI

These macros will draw a negated directed incidence upward (out(ward) incidence) symbol. See their [description](#) and usage examples on page 14.

```

302 \GTS@newcommand{\GTSnegatedOutIncidence}{\GTS@i{}{}{1}{1}{}{}}
303 \GTS@newcommand{\GTSnegOutInc}{\GTS@i{}{}{1}{1}{}{}}
304 \GTS@newcommand{\GTSnOI}{\GTS@i{}{}{1}{1}{}{}}

```

\GTSnegatedOutIncidenceRelation, \GTSnegOutIncRel, \GTSnOIR These macros will draw a negated directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 14.

```

305 \GTS@newcommand{\GTSnegatedOutIncidenceRelation}{\mathrel{\GTSnOI/}}
306 \GTS@newcommand{\GTSnegOutIncRel}{\mathrel{\GTSnOI/}}
307 \GTS@newcommand{\GTSnOIR}{\mathrel{\GTSnOI/}}

```

\GTSinIncidence, \GTSinInc, \GTSiI

These macros will draw a directed incidence downward (in(ward) incidence) symbol. See their [description](#) and usage examples on page 14.

```

308 \GTS@newcommand{\GTSinIncidence}{\GTS@i{}{}{}{1}}
309 \GTS@newcommand{\GTSinInc}{\GTS@i{}{}{}{1}}
310 \GTS@newcommand{\GTSiI}{\GTS@i{}{}{}{1}}

```

\GTSinIncidenceRelation, \GTSinIncRel, \GTSiIR These macros will draw a directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 15.

```

311 \GTS@newcommand{\GTSinIncidenceRelation}{\mathrel{\GTSiI/}}
312 \GTS@newcommand{\GTSinIncRel}{\mathrel{\GTSiI/}}
313 \GTS@newcommand{\GTSiIR}{\mathrel{\GTSiI/}}

```

\GTSnegatedInIncidence, \GTSnegInInc, \GTSnII

These macros will draw a negated directed incidence downward (in(ward) incidence) symbol. See their [description](#) and usage examples on page 15.

```

314 \GTS@newcommand{\GTSnegatedInIncidence}{\GTS@i{}{}{1}{}{1}}
315 \GTS@newcommand{\GTSnegInInc}{\GTS@i{}{}{1}{}{1}}
316 \GTS@newcommand{\GTSnII}{\GTS@i{}{}{1}{}{1}}

```

`\GTSnegatedInIncidenceRelation`, `\GTSnegInIncRel`, `\GTSnIIR` These macros will draw a negated directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode. See their [description](#) and usage examples on page 15.

```
317 \GTS@newcommand{\GTSnegatedInIncidenceRelation}{\mathrel{\GTSnII/}}
318 \GTS@newcommand{\GTSnegInIncRel}{\mathrel{\GTSnII/}}
319 \GTS@newcommand{\GTSnIIR}{\mathrel{\GTSnII/}}
```

`\GTSadjacencyMonochrome`, `\GTSadjMono`, `\GTSadjMon`, `\GTSaM`

These macros will draw a monochrome adjacency symbol.

See their [description](#) and usage examples on page 15.

```
320 \GTS@newcommand{\GTSadjacencyMonochrome}{\GTS@a{black}{black}{-}{-}{-}}
321 \GTS@newcommand{\GTSadjMono}{\GTS@a{black}{black}{-}{-}{-}}
322 \GTS@newcommand{\GTSadjMon}{\GTS@a{black}{black}{-}{-}{-}}
323 \GTS@newcommand{\GTSaM}{\GTS@a{black}{black}{-}{-}{-}}
```

`\GTSadjacencyMonochromeRelation`, `\GTSadjMonoRel`, `\GTSadjMonRel`, `\GTSaMR`

These macros will draw a monochrome adjacency symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 16.

```
324 \GTS@newcommand{\GTSadjacencyMonochromeRelation}{\mathrel{\GTSaM/}}
325 \GTS@newcommand{\GTSadjMonoRel}{\mathrel{\GTSaM/}}
326 \GTS@newcommand{\GTSadjMonRel}{\mathrel{\GTSaM/}}
327 \GTS@newcommand{\GTSaMR}{\mathrel{\GTSaM/}}
```

`\GTSunadjacencyMonochrome`, `\GTSunadjMono`, `\GTSunadjMon`, `\GTSuM`

These macros will draw a monochrome unadjacency symbol.

See their [description](#) and usage examples on page 16.

```
328 \GTS@newcommand{\GTSunadjacencyMonochrome}{\GTS@a{black}{black}{1}{-}{-}}
329 \GTS@newcommand{\GTSunadjMono}{\GTS@a{black}{black}{1}{-}{-}}
330 \GTS@newcommand{\GTSunadjMon}{\GTS@a{black}{black}{1}{-}{-}}
331 \GTS@newcommand{\GTSuM}{\GTS@a{black}{black}{1}{-}{-}}
```

`\GTSunadjacencyMonochromeRelation`, `\GTSunadjMonoRel`, `\GTSunadjMonRel`, `\GTSuMR`

These macros will draw a monochrome unadjacency symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 17.

```
332 \GTS@newcommand{\GTSunadjacencyMonochromeRelation}{\mathrel{\GTSuM/}}
333 \GTS@newcommand{\GTSunadjMonoRel}{\mathrel{\GTSuM/}}
334 \GTS@newcommand{\GTSunadjMonRel}{\mathrel{\GTSuM/}}
335 \GTS@newcommand{\GTSuMR}{\mathrel{\GTSuM/}}
```

`\GTSdirectedAdjacencyUpMonochrome`, `\GTSdirAdjUpMono`, `\GTSdirAdjUpMon`, `\GTSdAUM` These macros will draw a monochrome directed adjacency upward symbol.

See their [description](#) and usage examples on page 17.

```
336 \GTS@newcommand{\GTSdirectedAdjacencyUpMonochrome}{%
337 \GTS@a{black}{black}{-}{1}{-}}
338 }
339 \GTS@newcommand{\GTSdirAdjUpMono}{\GTS@a{black}{black}{-}{1}{-}}
340 \GTS@newcommand{\GTSdirAdjUpMon}{\GTS@a{black}{black}{-}{1}{-}}
341 \GTS@newcommand{\GTSdAUM}{\GTS@a{black}{black}{-}{1}{-}}
```

`\GTSdirectedAdjacencyUpMonochromeRelation`, `\GTSdirAdjUpMonoRel`, `\GTSdirAdjUpMonRel`, `\GTSdAUMR`

These macros will draw a monochrome directed adjacency upward symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 17.

```
342 \GTS@newcommand{\GTSdirectedAdjacencyUpMonochromeRelation}{%
343 \mathrel{\GTSdAUM/}}
344 }
345 \GTS@newcommand{\GTSdirAdjUpMonoRel}{\mathrel{\GTSdAUM/}}
```

```

346 \GTS@newcommand{\GTSdirAdjUpMonRel}{\mathrel{\GTSdAUM/}}
347 \GTS@newcommand{\GTSdAUMR}{\mathrel{\GTSdAUM/}}

```

\GTSnegatedDirectedAdjacencyUpMonochrome, \GTSnegDirAdjUpMono, \GTSnegDirAdjUpMon, \GTSnDAUM

These macros will draw a monochrome negated directed adjacency upward symbol. See their [description](#) and usage examples on page 17.

```

348 \GTS@newcommand{\GTSnegatedDirectedAdjacencyUpMonochrome}{%
349 \GTS@a{black}{black}{1}{1}{}}%
350 }
351 \GTS@newcommand{\GTSnegDirAdjUpMono}{\GTS@a{black}{black}{1}{1}{}}
352 \GTS@newcommand{\GTSnegDirAdjUpMon}{\GTS@a{black}{black}{1}{1}{}}
353 \GTS@newcommand{\GTSnDAUM}{\GTS@a{black}{black}{1}{1}{}}

```

\GTSnegatedDirectedAdjacencyUpMonochromeRelation, \GTSnegDirAdjUpMonoRel, \GTSnegDirAdjUpMonRel, \GTSnDAUMR These macros will draw a monochrome negated directed adjacency upward symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 18.

```

354 \GTS@newcommand{\GTSnegatedDirectedAdjacencyUpMonochromeRelation}{%
355 \mathrel{\GTSnDAUM/}}%
356 }
357 \GTS@newcommand{\GTSnegDirAdjUpMonoRel}{\mathrel{\GTSnDAUM/}}
358 \GTS@newcommand{\GTSnegDirAdjUpMonRel}{\mathrel{\GTSnDAUM/}}
359 \GTS@newcommand{\GTSnDAUMR}{\mathrel{\GTSnDAUM/}}

```

\GTSdirectedAdjacencyDownMonochrome, \GTSdirAdjDownMono, \GTSdirAdjDownMon, \GTSdADM

These macros will draw a monochrome directed adjacency downward symbol. See their [description](#) and usage examples on page 18.

```

360 \GTS@newcommand{\GTSdirectedAdjacencyDownMonochrome}{%
361 \GTS@a{black}{black}{-}{-}{1}}%
362 }
363 \GTS@newcommand{\GTSdirAdjDownMono}{\GTS@a{black}{black}{-}{-}{1}}
364 \GTS@newcommand{\GTSdirAdjDownMon}{\GTS@a{black}{black}{-}{-}{1}}
365 \GTS@newcommand{\GTSdADM}{\GTS@a{black}{black}{-}{-}{1}}

```

\GTSdirectedAdjacencyDownMonochromeRelation, \GTSdirAdjDownMonoRel, \GTSdirAdjDownMonRel, \GTSdADMR These macros will draw a monochrome directed adjacency downward symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 19.

```

366 \GTS@newcommand{\GTSdirectedAdjacencyDownMonochromeRelation}{%
367 \mathrel{\GTSdADM/}}%
368 }
369 \GTS@newcommand{\GTSdirAdjDownMonoRel}{\mathrel{\GTSdADM/}}
370 \GTS@newcommand{\GTSdirAdjDownMonRel}{\mathrel{\GTSdADM/}}
371 \GTS@newcommand{\GTSdADMR}{\mathrel{\GTSdADM/}}

```

\GTSnegatedDirectedAdjacencyDownMonochrome, \GTSnegDirAdjDownMono, \GTSnegDirAdjDownMon, \GTSnDADM

These macros will draw a monochrome negated directed adjacency downward symbol. See their [description](#) and usage examples on page 19.

```

372 \GTS@newcommand{\GTSnegatedDirectedAdjacencyDownMonochrome}{%
373 \GTS@a{black}{black}{1}{-}{1}}%
374 }
375 \GTS@newcommand{\GTSnegDirAdjDownMono}{\GTS@a{black}{black}{1}{-}{1}}
376 \GTS@newcommand{\GTSnegDirAdjDownMon}{\GTS@a{black}{black}{1}{-}{1}}
377 \GTS@newcommand{\GTSnDADM}{\GTS@a{black}{black}{1}{-}{1}}

```

\GTSnegatedDirectedAdjacencyDownMonochromeRelation, \GTSnegDirAdjDownMonoRel, \GTSnegDirAdjDownMonRel, \GTSnDADMR These macros

will draw a monochrome negated directed adjacency downward symbol with relation spacing in math mode. See their [description](#) and usage examples on page 19.

```
378 \GTS@newcommand{\GTSnegatedDirectedAdjacencyDownMonochromeRelation}{%
379 \mathrel{\GTSnDADM/}%
380 }
381 \GTS@newcommand{\GTSnegDirAdjDownMonoRel}{\mathrel{\GTSnDADM/}}
382 \GTS@newcommand{\GTSnegDirAdjDownMonRel}{\mathrel{\GTSnDADM/}}
383 \GTS@newcommand{\GTSnDADMR}{\mathrel{\GTSnDADM/}}
```

\GTSincidenceMonochrome, \GTSincMono, \GTSincMon, \GTSiM

These macros will draw a monochrome incidence symbol.

See their [description](#) and usage examples on page 20.

```
384 \GTS@newcommand{\GTSincidenceMonochrome}{\GTS@i{black}{black}{-}{-}{-}}
385 \GTS@newcommand{\GTSincMono}{\GTS@i{black}{black}{-}{-}{-}}
386 \GTS@newcommand{\GTSincMon}{\GTS@i{black}{black}{-}{-}{-}}
387 \GTS@newcommand{\GTSiM}{\GTS@i{black}{black}{-}{-}{-}}
```

\GTSincidenceMonochromeRelation, \GTSincMonoRel, \GTSincMonRel, \GTSiMR

These macros will draw a monochrome incidence symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 20.

```
388 \GTS@newcommand{\GTSincidenceMonochromeRelation}{\mathrel{\GTSiM/}}
389 \GTS@newcommand{\GTSincMonoRel}{\mathrel{\GTSiM/}}
390 \GTS@newcommand{\GTSincMonRel}{\mathrel{\GTSiM/}}
391 \GTS@newcommand{\GTSiMR}{\mathrel{\GTSiM/}}
```

\GTSnegatedIncidenceMonochrome, \GTSnegIncMono, \GTSnegIncMon, \GTSnIM

These macros will draw a monochrome negated incidence symbol.

See their [description](#) and usage examples on page 20.

```
392 \GTS@newcommand{\GTSnegatedIncidenceMonochrome}{%
393 \GTS@i{black}{black}{1}{-}{-}%
394 }
395 \GTS@newcommand{\GTSnegIncMono}{\GTS@i{black}{black}{1}{-}{-}}
396 \GTS@newcommand{\GTSnegIncMon}{\GTS@i{black}{black}{1}{-}{-}}
397 \GTS@newcommand{\GTSnIM}{\GTS@i{black}{black}{1}{-}{-}}
```

\GTSnegatedIncidenceMonochromeRelation, \GTSnegIncMonoRel, \GTSnegIncMonRel, \GTSnIMR

These macros will draw a monochrome negated incidence symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 21.

```
398 \GTS@newcommand{\GTSnegatedIncidenceMonochromeRelation}{\mathrel{\GTSnIM/}}
399 \GTS@newcommand{\GTSnegIncMonoRel}{\mathrel{\GTSnIM/}}
400 \GTS@newcommand{\GTSnegIncMonRel}{\mathrel{\GTSnIM/}}
401 \GTS@newcommand{\GTSnIMR}{\mathrel{\GTSnIM/}}
```

\GTSoutIncidenceMonochrome, \GTSoutIncMono, \GTSoutIncMon, \GTSoIM

These macros will draw a monochrome directed incidence upward (out(ward) incidence) symbol.

See their [description](#) and usage examples on page 21.

```
402 \GTS@newcommand{\GTSoutIncidenceMonochrome}{\GTS@i{black}{black}{-}{1}{-}}
403 \GTS@newcommand{\GTSoutIncMono}{\GTS@i{black}{black}{-}{1}{-}}
404 \GTS@newcommand{\GTSoutIncMon}{\GTS@i{black}{black}{-}{1}{-}}
405 \GTS@newcommand{\GTSoIM}{\GTS@i{black}{black}{-}{1}{-}}
```

\GTSoutIncidenceMonochromeRelation, \GTSoutIncMonoRel, \GTSoutIncMonRel,

\GTSoIMR These macros will draw a monochrome directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode.

See their [description](#) and usage examples on page 21.

```
406 \GTS@newcommand{\GTSoutIncidenceMonochromeRelation}{\mathrel{\GTSoIM/}}
407 \GTS@newcommand{\GTSoutIncMonoRel}{\mathrel{\GTSoIM/}}
408 \GTS@newcommand{\GTSoutIncMonRel}{\mathrel{\GTSoIM/}}
409 \GTS@newcommand{\GTSoIMR}{\mathrel{\GTSoIM/}}
```

\GTSnegatedOutIncidenceMonochrome, \GTSnegOutIncMono, \GTSnegOutIncMon, \GTSnOIM

These macros will draw a monochrome negated directed incidence upward (out(ward) incidence) symbol. See their [description](#) and usage examples on page 22.

```
410 \GTS@newcommand{\GTSnegatedOutIncidenceMonochrome}{%
411 \GTS@i{black}{black}{1}{1}{}}%
412 }
413 \GTS@newcommand{\GTSnegOutIncMono}{\GTS@i{black}{black}{1}{1}{}}
414 \GTS@newcommand{\GTSnegOutIncMon}{\GTS@i{black}{black}{1}{1}{}}
415 \GTS@newcommand{\GTSnOIM}{\GTS@i{black}{black}{1}{1}{}}
```

\GTSnegatedOutIncidenceMonochromeRelation, \GTSnegOutIncMonoRel, \GTSnegOutIncMonRel, \GTSnOIMR These macros will draw a monochrome negated directed incidence upward (out(ward) incidence) symbol with relation spacing in math mode. See their [description](#) and usage examples on page 22.

```
416 \GTS@newcommand{\GTSnegatedOutIncidenceMonochromeRelation}{%
417 \mathrel{\GTSnOIM/}}%
418 }
419 \GTS@newcommand{\GTSnegOutIncMonoRel}{\mathrel{\GTSnOIM/}}
420 \GTS@newcommand{\GTSnegOutIncMonRel}{\mathrel{\GTSnOIM/}}
421 \GTS@newcommand{\GTSnOIMR}{\mathrel{\GTSnOIM/}}
```

\GTSinIncidenceMonochrome, \GTSinIncMono, \GTSinIncMon, \GTSiIM

These macros will draw a monochrome directed incidence downward (in(ward) incidence) symbol. See their [description](#) and usage examples on page 22.

```
422 \GTS@newcommand{\GTSinIncidenceMonochrome}{\GTS@i{black}{black}{}}{1}}
423 \GTS@newcommand{\GTSinIncMono}{\GTS@i{black}{black}{}}{1}}
424 \GTS@newcommand{\GTSinIncMon}{\GTS@i{black}{black}{}}{1}}
425 \GTS@newcommand{\GTSiIM}{\GTS@i{black}{black}{}}{1}}
```

\GTSinIncidenceMonochromeRelation, \GTSinIncMonoRel, \GTSinIncMonRel, \GTSiIMR

These macros will draw a monochrome directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode. See their [description](#) and usage examples on page 23.

```
426 \GTS@newcommand{\GTSinIncidenceMonochromeRelation}{\mathrel{\GTSiIM/}}
427 \GTS@newcommand{\GTSinIncMonoRel}{\mathrel{\GTSiIM/}}
428 \GTS@newcommand{\GTSinIncMonRel}{\mathrel{\GTSiIM/}}
429 \GTS@newcommand{\GTSiIMR}{\mathrel{\GTSiIM/}}
```

\GTSnegatedInIncidenceMonochrome, \GTSnegInIncMono, \GTSnegInIncMon, \GTSnIIM

These macros will draw a monochrome negated directed incidence downward (in(ward) incidence) symbol. See their [description](#) and usage examples on page 23.

```
430 \GTS@newcommand{\GTSnegatedInIncidenceMonochrome}{%
431 \GTS@i{black}{black}{1}{1}{}}%
432 }
433 \GTS@newcommand{\GTSnegInIncMono}{\GTS@i{black}{black}{1}{1}{}}
434 \GTS@newcommand{\GTSnegInIncMon}{\GTS@i{black}{black}{1}{1}{}}
435 \GTS@newcommand{\GTSnIIM}{\GTS@i{black}{black}{1}{1}{}}
```

\GTSnegatedInIncidenceMonochromeRelation, \GTSnegInIncMonoRel, \GTSnegInIncMonRel, \GTSnIIMR These macros will draw a monochrome negated directed incidence downward (in(ward) incidence) symbol with relation spacing in math mode. See their [description](#) and usage examples on page 24.

```
436 \GTS@newcommand{\GTSnegatedInIncidenceMonochromeRelation}{%
437 \mathrel{\GTSnIIM/}}%
438 }
439 \GTS@newcommand{\GTSnegInIncMonoRel}{\mathrel{\GTSnIIM/}}
440 \GTS@newcommand{\GTSnegInIncMonRel}{\mathrel{\GTSnIIM/}}
441 \GTS@newcommand{\GTSnIIMR}{\mathrel{\GTSnIIM/}}
```

\GTSMetaNot, \GTSMN These macros will draw a meta-not or relation-not symbol.
See their [description](#) and usage examples on page 24.

```

442 \GTS@newprotectedcommand{\GTSMN}{%
443 \text{\ensuremath{%
444 \raisebox{-0.44ex}{\scalebox{1}[1]{%
445 \raisebox{0ex}{\scalebox{1}[1]{\not$}}}%
446 \hspace{-1.46ex}%
447 \raisebox{1.2ex}{\scalebox{0.7}[0.7]{m}}}%
448 \hspace{0.2ex}%
449 }}}%
450 }}}%
451 }
452 \GTS@newcommand{\GTSMetaNot}{\GTSMN/}

```

\GTSMetaAnd, \GTSMa These macros will draw a meta-and or relations-and symbol.
See their [description](#) and usage examples on page 24.

```

453 \GTS@newprotectedcommand{\GTSMa}{%
454 \text{\ensuremath{%
455 \raisebox{-0.44ex}{\scalebox{0.95}[0.95]{%
456 \raisebox{0ex}{\scalebox{1}[1]{\wedge$}}}%
457 \hspace{-1.46ex}%
458 \raisebox{1.5ex}{\scalebox{0.7}[0.7]{m}}}%
459 }}}%
460 }}}%
461 }
462 \GTS@newcommand{\GTSMetaAnd}{\GTSMa/}

```

\GTSMetaAndRelation, \GTSMetaAndRel, \GTSMAR

These macros will draw a meta-and symbol with relation spacing in math mode.
See their [description](#) and usage examples on page 24.

```

463 \GTS@newcommand{\GTSMetaAndRelation}{\mathrel{\GTSMa/}}
464 \GTS@newcommand{\GTSMetaAndRel}{\mathrel{\GTSMa/}}
465 \GTS@newcommand{\GTSMAR}{\mathrel{\GTSMa/}}

```

\GTSMetaOr, \GTSMO These macros will draw a meta-or or relations-or symbol. This is your duty to check that all relations have same arity. It should be easy as long as you remain in the realm of graphs/2-structures/binary structures ;). We didn't use Tarski's notation, since square cup has taken the preemptive meaning of disjoint union. Similarly, doublevee or other vee symbols have taken various meanings, whilst we want an unambiguous symbol.

See their [description](#) and usage examples on page 25.

```

466 \GTS@newprotectedcommand{\GTSMO}{%
467 \text{\ensuremath{%
468 \raisebox{-0.44ex}{\scalebox{0.95}[0.95]{%
469 \raisebox{0ex}{\scalebox{1}[1]{\vee$}}}%
470 \hspace{-1.46ex}%
471 \raisebox{1.5ex}{\scalebox{0.7}[0.7]{m}}}%
472 }}}%
473 }}}%
474 }
475 \GTS@newcommand{\GTSMetaOr}{\GTSMO/}

```

\GTSMetaOrRelation, \GTSMetaOrRel, \GTSMOR

These macros will draw a meta-or symbol with relation spacing in math mode.
See their [description](#) and usage examples on page 25.

```

476 \GTS@newcommand{\GTSMetaOrRelation}{\mathrel{\GTSMO/}}
477 \GTS@newcommand{\GTSMetaOrRel}{\mathrel{\GTSMO/}}
478 \GTS@newcommand{\GTSMOR}{\mathrel{\GTSMO/}}

```

\GTSxmetallogic, \GTSxml See their [description](#) on page 25.

```

479 \define@key{GTSxml}{not}[1]{\def\GTS@@drawMetaNot{1}}

```

```

480 \define@key{GTSxml}{n}[1]{\def\GTS@@drawMetaNot{1}}
481 \define@key{GTSxml}{and}[1]{\def\GTS@@drawMetaAnd{1}}
482 \define@key{GTSxml}{a}[1]{\def\GTS@@drawMetaAnd{1}}
483 \define@key{GTSxml}{or}[1]{\def\GTS@@drawMetaOr{1}}
484 \define@key{GTSxml}{o}[1]{\def\GTS@@drawMetaOr{1}}
485 \define@key{GTSxml}{relation}[1]{\def\GTS@@relation{1}}
486 \define@key{GTSxml}{rel}[1]{\def\GTS@@relation{1}}
487 \define@key{GTSxml}{r}[1]{\def\GTS@@relation{1}}
488
489 \newcommand{\GTSxml}[1][]{\%
490 \def\GTS@@drawMetaNot{}}
491 \def\GTS@@drawMetaAnd{}
492 \def\GTS@@drawMetaOr{}
493 \def\GTS@@relation{}
494 \setkeys{GTSxml}{#1}%
495 \if\GTS@@drawMetaNot1%
496 \GTSmN/%
497 \else\if\GTS@@drawMetaAnd1%
498 \if\GTS@@relation{1}%
499 \GTSmAR/%
500 \else%
501 \GTSmA/%
502 \fi%
503 \else\if\GTS@@drawMetaOr1%
504 \if\GTS@@relation{1}%
505 \GTSmOR/%
506 \else%
507 \GTSmO/%
508 \fi%
509 \else%
510 Wrong call to \textbackslash{}GTSxml%
511 \fi%
512 \fi%
513 \fi%
514 }
515
516 \newcommand{\GTSxmetallogic}[1][]{\GTSxml[#1]}

```

\GTSx See its [description](#) on page 25.

```

517 \newcommand{\GTSx}[2][]{\%
518 \if#2a%
519 \GTSxa[#1]%
520 \else\if#2i%
521 \GTSxi[#1]%
522 \else\if#2m%
523 \GTSxml[#1]%
524 \else%
525 Wrong call to \textbackslash{}GTSx%
526 \fi%
527 \fi%
528 \fi%
529 }

530 \endinput
531 \</package>

```

4 Acknowledgments

Thank You God! Thank You Father! Thank You Jesus! Thank You Holy-Spirit!

5 FAQ

Question: Why GraphTheorySymbol instead of GraphTheorySymbols? GraphTheorySymbol does contain many symbols.

Answer: Because I followed one common usage on CTAN.

Here is the list of all current packages with the word "symbol" in their name:

actuarialsymbol, adfsymbols, compact-symbols, cookingsymbols, FdSymbol, jpnedumathsymbols, KKsymbols, listofsymbols, losymbol, maths-symbols, mdsymbol, MnSymbol, open-everyday-symbols, qsymbols, SVRsymbols, symbolindex, The Comprehensive LaTeX Symbol List, tikz-cookingsymbols, tikzsymbols.

7 "symbol" plus GraphTheorySymbol 8, 12 "symbols".

"symb" abbreviation, "sym", "sy" and "s" are also quite common;

oPlotSymbl did it its own way ;) XD.

Because of the goal of GraphTheorySymbol, I was mainly looking at packages like FdSymbol, mdsymbol, MnSymbol, and The Comprehensive LaTeX Symbol List before creating my package; hence I followed this apparent majority, instead of listening to my thought that Symbols would be better.

After the package was uploaded to CTAN for a version update, this question came again, but CTAN admins were reluctant to change the package name afterward.

Otherwise, it is a matter of hours to modify and upload GraphTheorySymbols with version 2.0.0 to CTAN.

6 Support

This package is gratis and free. But if you can star it on GitHub, it is a nice encouragement.

7 Change History

v0.1.0 – 2026-08-01		avoid too big left margins, and use	
General: Initial version	1	paragraph command instead	1
v1.0.0 – 2026-08-26		v1.5.2 – 2026-09-14	
General: First public release	1	General: Add A4, USLetter, and Book variants	
v1.1.0 – 2026-08-29		of PDFs.	1
General: Added a memo	1	v1.6.0 – 2026-09-18	
v1.1.1 – 2026-08-30		General: Add verbatim code for compound	
General: Small corrections and improvements	1	adjacency in memo.	1
v1.2.0 – 2026-09-06		v1.6.1 – 2026-09-19	
General: CTAN URL, new macros for same set		General: Rename test(.tex, etc.) to	
of symbols	1	graph-theory-symbol-test(.tex, etc.).	1
v1.2.1 – 2026-09-08		v1.7.0 – 2026-09-21	
General: Smaller tests output	1	General: Add FAQ section. Minors spacing and	
v1.3.0 – 2026-09-08		newpage corrections. Put table of contents	
General: New macros for monochrome symbols	1	and Introduction on their own page. Use	
v1.4.0 – 2026-09-12		tcolorbox for more visible examples.	
General: New macros for symbols for logical		Disclaimer for documentation of macros	
operations on relations	1	with an at sign.	1
v1.5.0 – 2026-09-12		v1.8.0 – 2026-09-28	
General: One macro to rule them all	1	General: Forward and backward hyperlinks	
v1.5.1 – 2026-09-13		between macros descriptions and	
General: Use noprint option of doc package to		implementations.	1

Index

G

\GTS@@drawDownArrow	120, 121, 131, 135, 263, 264, 274, 278
\GTS@@drawMetaAnd	481, 482, 491, 497
\GTS@@drawMetaNot	479, 480, 490, 495
\GTS@@drawMetaOr	483, 484, 492, 503
\GTS@@drawSlash	115, 116, 117, 129, 134, 258, 259, 260, 272, 277

\GTS@@drawUpArrow	118, 119, 130, 135, 261, 262, 273, 278
\GTS@@mainColor	99, 100, 101, 102, 108, 110, 112, 114, 127, 134, 242, 243, 244, 245, 251, 253, 255, 257, 270, 277
\GTS@@relation	122, 123, 124, 132, 135, 265, 266, 267, 275, 278, 485, 486, 487, 493, 498, 504
\GTS@@secondColor	103, 104, 105, 106, 108, 110, 112, 114, 128, 134, 246, 247, 248, 249, 251, 253, 255, 257, 271, 277
\GTS@a	7, 34, 94, 96, 141, 142, 143, 147, 148, 149, 153, 154, 155, 159, 160, 161, 167, 168, 169, 173, 174, 175, 320, 321, 322, 323, 328, 329, 330, 331, 337, 339, 340, 341, 349, 351, 352, 353, 361, 363, 364, 365, 373, 375, 376, 377
\GTS@b	7, 92, 134
\GTS@drawDownArrow	16
\GTS@drawSlash	14
\GTS@drawUpArrow	15
\GTS@i	11, 181, 237, 239, 284, 285, 286, 290, 291, 292, 296, 297, 298, 302, 303, 304, 308, 309, 310, 314, 315, 316, 384, 385, 386, 387, 393, 395, 396, 397, 402, 403, 404, 405, 411, 413, 414, 415, 422, 423, 424, 425, 431, 433, 434, 435
\GTS@j	12, 235, 277
\GTS@mainColor	10, 26, 27, 53, 67, 73, 204
\GTS@mainColorBackup	12, 26, 86, 229
\GTS@mainColorTemp	25, 27
\GTS@newcommand	7, 18, 141, 142, 143, 144, 145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155, 156, 157, 158, 159, 160, 161, 162, 165, 166, 167, 168, 169, 170, 171, 172, 173, 174, 175, 176, 179, 180, 284, 285, 286, 287, 288, 289, 290, 291, 292, 293, 294, 295, 296, 297, 298, 299, 300, 301, 302, 303, 304, 305, 306, 307, 308, 309, 310, 311, 312, 313, 314, 315, 316, 317, 318, 319, 320, 321, 322, 323, 324, 325, 326, 327, 328, 329, 330, 331, 332, 333, 334, 335, 336, 339, 340, 341, 342, 345, 346, 347, 348, 351, 352, 353, 354, 357, 358, 359, 360, 363, 364, 365, 366, 369, 370, 371, 372, 375, 376, 377, 378, 381, 382, 383, 384, 385, 386, 387, 388, 389, 390, 391, 392, 395, 396, 397, 398, 399, 400, 401, 402, 403, 404, 405, 406, 407, 408, 409, 410, 413, 414, 415, 416, 419, 420, 421, 422, 423, 424, 425, 426, 427, 428, 429, 430, 433, 434, 435, 436, 439, 440, 441, 452, 462, 463, 464, 465, 475, 476, 477, 478
\GTS@newprotectedcommand	7, 21, 442, 453, 466
\GTS@secondColor	11, 31, 32, 45, 49, 57, 61, 192, 196, 200, 210, 216
\GTS@secondColorBackup	13, 31, 89, 232
\GTS@secondColorTemp	30, 32
\GTSa	8, 141, 144, 145, 146
\GTSadj	8, 141
\GTSadjacency	8, 141
\GTSadjacencyMonochrome	15, 320
\GTSadjacencyMonochromeRelation	16, 324
\GTSadjacencyRelation	8, 144
\GTSadjMon	15, 320
\GTSadjMono	15, 320
\GTSadjMonoRel	16, 324
\GTSadjMonRel	16, 324
\GTSadjRel	8, 144
\GTSaM	15, 320, 324, 325, 326, 327
\GTSaMR	16, 324
\GTSaR	8, 144
\GTSdAD	10, 167, 170, 171, 172
\GTSdADM	18, 360, 367, 369, 370, 371
\GTSdADMR	19, 366
\GTSdADR	11, 170
\GTSdAU	9, 153, 156, 157, 158
\GTSdAUM	17, 336, 343, 345, 346, 347
\GTSdAUMR	17, 342
\GTSdAUR	9, 156
\GTSdirAdjDown	10, 167

\GTSdirAdjDown\~Mon	18
\GTSdirAdjDownMon	360
\GTSdirAdjDownMono	18, 360
\GTSdirAdjDownMonoRel	19, 366
\GTSdirAdjDownMonRel	19, 366
\GTSdirAdjDownRel	11, 170
\GTSdirAdjUp	9, 153
\GTSdirAdjUpMon	17, 336
\GTSdirAdjUpMono	17, 336
\GTSdirAdjUpMonoRel	17, 342
\GTSdirAdjUpMonRel	17, 342
\GTSdirAdjUpRel	9, 156
\GTSdirectedAdjacencyDown	10, 167
\GTSdirectedAdjacencyDownMonochrome	18, 360
\GTSdirectedAdjacencyDownMonochromeRelation	19, 366
\GTSdirectedAdjacencyDownRelation	11, 170
\GTSdirectedAdjacencyUp	9, 153
\GTSdirectedAdjacencyUpMonochrome	17, 336
\GTSdirectedAdjacencyUpMonochromeRelation	17, 342
\GTSdirectedAdjacencyUpRelation	9, 156
\GTSi	12, 284, 287, 288, 289
\GTSiI	14, 308, 311, 312, 313
\GTSiIM	22, 422, 426, 427, 428, 429
\GTSiIMR	23, 426
\GTSiIR	15, 311
\GTSiM	20, 384, 388, 389, 390, 391
\GTSiMR	20, 388
\GTSinc	12, 284
\GTSincidence	12, 284
\GTSincidenceMonochrome	20, 384
\GTSincidenceMonochromeRelation	20, 388
\GTSincidenceRelation	12, 287
\GTSincMon	20, 384
\GTSincMono	20, 384
\GTSincMonoRel	20, 388
\GTSincMonRel	20, 388
\GTSincRel	12, 287
\GTSinInc	14, 308
\GTSinIncidence	14, 308
\GTSinIncidenceMonochrome	22, 422
\GTSinIncidenceMonochromeRelation	23, 426
\GTSinIncidenceRelation	15, 311
\GTSinIncMon	22, 422
\GTSinIncMono	22, 422
\GTSinIncMonoRel	23, 426
\GTSinIncMonRel	23, 426
\GTSinIncRel	15, 311
\GTSiR	12, 287
\GTSmA	24, 453, 463, 464, 465, 501
\GTSmAR	24, 463, 499
\GTSmetaAnd	24, 453
\GTSmetaAndRel	24, 463
\GTSmetaAndRelation	24, 463
\GTSmetaNot	24, 442
\GTSmetaOr	25, 466
\GTSmetaOrRel	25, 476

\GTSmetaOrRelation	25, <u>476</u>
\GTSmN	24, <u>442</u> , 496
\GTSmO	25, <u>466</u> , 476, 477, 478, 507
\GTSmOR	25, <u>476</u> , 505
\GTSnDAD	11, <u>173</u> , 177, 179, 180
\GTSnDADM	19, <u>372</u> , 379, 381, 382, 383
\GTSnDADMR	19, <u>378</u>
\GTSnDADR	11, <u>176</u>
\GTSnDAU	10, <u>159</u> , 163, 165, 166
\GTSnDAUM	17, <u>348</u> , 355, 357, 358, 359
\GTSnDAUMR	18, <u>354</u>
\GTSnDAUR	10, <u>162</u>
\GTSnegatedDirectedAdjacencyDown	11, <u>173</u>
\GTSnegatedDirectedAdjacencyDownMonochrome	19, <u>372</u>
\GTSnegatedDirectedAdjacencyDownMonochromeRelation	19, <u>378</u>
\GTSnegatedDirectedAdjacencyDownRelation	11, <u>176</u>
\GTSnegatedDirectedAdjacencyUp	10, <u>159</u>
\GTSnegatedDirectedAdjacencyUpMonochrome	17, <u>348</u>
\GTSnegatedDirectedAdjacencyUpMonochromeRelation	18, <u>354</u>
\GTSnegatedDirectedAdjacencyUpRelation	10, <u>162</u>
\GTSnegatedIncidence	12, <u>290</u>
\GTSnegatedIncidenceMonochrome	20, <u>392</u>
\GTSnegatedIncidenceMonochromeRelation	21, <u>398</u>
\GTSnegatedIncidenceRelation	13, <u>293</u>
\GTSnegatedInIncidence	15, <u>314</u>
\GTSnegatedInIncidenceMonochrome	23, <u>430</u>
\GTSnegatedInIncidenceMonochromeRelation	24, <u>436</u>
\GTSnegatedInIncidenceRelation	15, <u>317</u>
\GTSnegatedOutIncidence	14, <u>302</u>
\GTSnegatedOutIncidenceMonochrome	22, <u>410</u>
\GTSnegatedOutIncidenceMonochromeRelation	22, <u>416</u>
\GTSnegatedOutIncidenceRelation	14, <u>305</u>
\GTSnegDirAdjDown	11, <u>173</u>
\GTSnegDirAdjDownMon	19, <u>372</u>
\GTSnegDirAdjDownMono	19, <u>372</u>
\GTSnegDirAdjDownMonoRel	19, <u>378</u>
\GTSnegDirAdjDownMonRel	19, <u>378</u>
\GTSnegDirAdjDownRel	11, <u>176</u>
\GTSnegDirAdjUp	10, <u>159</u>
\GTSnegDirAdjUpMon	17, <u>348</u>
\GTSnegDirAdjUpMono	17, <u>348</u>
\GTSnegDirAdjUpMonoRel	18, <u>354</u>
\GTSnegDirAdjUpMonRel	18, <u>354</u>
\GTSnegDirAdjUpRel	10, <u>162</u>
\GTSnegInc	12, <u>290</u>
\GTSnegIncMon	20, <u>392</u>
\GTSnegIncMono	20, <u>392</u>
\GTSnegIncMonoRel	21, <u>398</u>
\GTSnegIncMonRel	21, <u>398</u>
\GTSnegIncRel	13, <u>293</u>
\GTSnegInInc	15, <u>314</u>
\GTSnegInIncMon	23, <u>430</u>
\GTSnegInIncMono	23, <u>430</u>
\GTSnegInIncMonoRel	24, <u>436</u>
\GTSnegInIncMonRel	24, <u>436</u>
\GTSnegInIncRel	15, <u>317</u>

\GTSnegOutInc	14, <u>302</u>
\GTSnegOutIncMon	22, <u>410</u>
\GTSnegOutIncMono	22, <u>410</u>
\GTSnegOutIncMonoRel	22, <u>416</u>
\GTSnegOutIncMonRel	22, <u>416</u>
\GTSnegOutIncRel	14, <u>305</u>
\GTSnI	12, <u>290</u> , 293, 294, 295
\GTSnII	15, <u>314</u> , 317, 318, 319
\GTSnIIM	23, <u>430</u> , <u>437</u> , 439, 440, 441
\GTSnIIMR	24, <u>436</u>
\GTSnIIR	15, <u>317</u>
\GTSnIM	20, <u>392</u> , 398, 399, 400, 401
\GTSnIMR	21, <u>398</u>
\GTSnIR	13, <u>293</u>
\GTSnOI	14, <u>302</u> , 305, 306, 307
\GTSnOIM	22, <u>410</u> , <u>417</u> , 419, 420, 421
\GTSnOIMR	22, <u>416</u>
\GTSnOIR	14, <u>305</u>
\GTSoI	13, <u>296</u> , 299, 300, 301
\GTSoIM	21, <u>402</u> , <u>406</u> , <u>407</u> , 408, 409
\GTSoIMR	21, <u>406</u>
\GTSoIR	13, <u>299</u>
\GTSoutInc	13, <u>296</u>
\GTSoutIncidence	13, <u>296</u>
\GTSoutIncidenceMonochrome	21, <u>402</u>
\GTSoutIncidenceMonochromeRelation	21, <u>406</u>
\GTSoutIncidenceRelation	13, <u>299</u>
\GTSoutIncMon	21, <u>402</u>
\GTSoutIncMono	21, <u>402</u>
\GTSoutIncMonoRel	21, <u>406</u>
\GTSoutIncMonRel	21, <u>406</u>
\GTSoutIncRel	13, <u>299</u>
\GTSsetMainColor	7, <u>24</u> , 36, 86, 183, 229
\GTSsetSecondColor	7, <u>29</u> , 39, 89, 186, 232
\GTSu	8, <u>147</u> , 150, 151, 152
\GTSuM	16, <u>328</u> , 332, 333, 334, 335
\GTSuMR	17, <u>332</u>
\GTSunadj	8, <u>147</u>
\GTSunadjacency	8, <u>147</u>
\GTSunadjacencyMonochrome	16, <u>328</u>
\GTSunadjacencyMonochromeRelation	17, <u>332</u>
\GTSunadjacencyRelation	9, <u>150</u>
\GTSunadjMon	16, <u>328</u>
\GTSunadjMono	16, <u>328</u>
\GTSunadjMonoRel	17, <u>332</u>
\GTSunadjMonRel	17, <u>332</u>
\GTSunadjRel	9, <u>150</u>
\GTSuR	9, <u>150</u>
\GTSx	25, <u>517</u>
\GTSxa	8, <u>99</u> , 519
\GTSxadj	8, <u>99</u>
\GTSxadjacency	8, <u>99</u>
\GTSxi	12, <u>242</u> , 521
\GTSxinc	12, <u>242</u>
\GTSxincidence	12, <u>242</u>
\GTSxmetallogic	25, <u>479</u>

\GTSxml 25, 479, 523