

LeafOS Version Naming

Release Planes, Evidence, and Recommended Labels

LeafOS

Recommendation

Do not name the current functional agent stack 0.2.2.1. The codebase has moved beyond the 0.2 task spine, but it has not yet earned a stable 0.5 reliable-loop claim.

Recommended functional label: 0.4.0-alpha.1 Provider Spine

For the root package, keep a separate packaging label:

`0.6.0-alpha.1+root-reformat`

Current Version Planes

Plane	Label	Meaning
Root package	<code>0.6.0-root-reformat</code>	Two-surface root packaging and handoff layout. Not proof of complete 0.6 function.
Taskpack docs	<code>0.5.0</code>	LAN/node CLI and distribution documentation label.
Model installer	<code>0.4.0</code>	Plan-first model catalog, resolve/apply/verify workflow.
Hardware monitor	<code>0.1.0</code>	Separate telemetry package.
Graph contract	<code>0.3.0</code>	Graph object, dependency readiness, and graph gate version.
Functional agent stack	<code>0.4.0-alpha.1</code>	Honest current target for provider spine, actions, and patch loop closure.

Why Not 0.2.2.1

- Four-part numbers obscure whether the change is packaging, taskpack, model installer, or graph contract.
- 0.2.x undersells the graph, provider, patch, node, and runtime work already present.
- The project already has explicit stage boundaries; the version should name the stage being promoted.
- Alpha labels are clearer than pretending staged 0.5/0.6 design is already proven.

Promotion Rule

```

captured test or run artifact
> accepted work-order result
> implementation documentation
> roadmap intention
> conceptual proposal

```

No stage should be promoted from prose alone.

Stage Map

Stage	Capability	Promotion evidence
0.2.0	Universal CLI task pipeline	<code>tests/spine.sh</code> completion gate.
0.3.0	Brain graph and dependency model	<code>tests/graph.sh</code> ; graph validation and gate smoke.
0.4.0	Embedded actions, waits, coder patches	Coder action bridge, patch apply boundary, repair nodes, provider lane tests.
0.5.0	Reliable persistent coding loop	Durable journal, checkpoints, source hashes, repair classification, resume evidence.
0.6.0	Replicable local project factory	Templates, project identity, runtime detection, local hosting foundation, stale-base refusal.
0.7.0	Nodal deployment and relays	Multi-node transfer, recovery, deduplication, and bounded queue evidence.

Suggested Labels

Label	Use
0.4.0-alpha.1 Provider Spine	Current functional release candidate for the agent/provider/patch bridge.
0.4.0-alpha.2 Patch Closure	When <code>agent.ask_coder</code> routes through the coder provider and produces validated patches.
0.4.0-beta.1 Repair Gate	When repair-node creation and bounded retry behavior are tested end to end.
0.5.0-alpha.1 Persistent Loop	First implementation of journal, checkpoint, source hash, and resume flow.
0.6.0-alpha.1 Local Factory	First project-template and runtime-capability detection snapshot.

Version String Pattern

```
<functional-stage>-<stability>.<iteration> <short-name>
```

Examples:

```

0.4.0-alpha.1 Provider Spine
0.4.0-alpha.2 Patch Closure
0.5.0-alpha.1 Persistent Loop

```

Root packaging may add build metadata:

```
0.6.0-alpha.1+root-reformat
```