



Team Contest Reference

Team: Marcel Ultras

Lennart Meyling

Maximilian Saal

Devin Zielke

Contents

1 dp	1
1.1 LCS	1
1.2 LIS	2
1.3 TSP	2
1.4 hungarian	2
2 ds	3
2.1 Fenwick-Tree	3
2.2 Range count query	3
2.3 Sorted Set	3
3 graph	4
3.1 Maximum Bipartite Matching	4
3.2 maxflow	4
4 math	5
4.1 FFT	5
4.2 MOD	7
4.3 Fast prime check	7
5 misc	7
5.1 Bootstrap	7
6 more math	8
6.1 Tree	8
6.2 Divisability Explanation	8
6.3 Combinatorics	8
6.4 Polynomial Interpolation	8
6.4.1 Theory	8
6.5 Fibonacci Sequence	8
6.5.1 Binet's formula	8
6.5.2 Generalization	8
6.5.3 Pisano Period	8
6.6 Series	8
6.7 Binomial coefficients	8
6.8 Catalan numbers	8
6.9 Geometry	8
6.10 Number Theory	9
6.11 Convolution	9
6.12 DP Optimization	9

1 dp

1.1 LCS

```

1 def LCS(S1, S2, m, n):
2     L = [[0 for x in range(n + 1)] for x in range(m + 1)]

```

```

3     for i in range(m + 1):
4         for j in range(n + 1):
5             if i == 0 or j == 0:
6                 L[i][j] = 0
7             elif S1[i - 1] == S2[j - 1]:
8                 L[i][j] = L[i - 1][j - 1] + 1
9             else:

```

```

10         L[i][j] = max(L[i - 1][j], L[i][j -
11             1])
12     index = L[m][n]
13     lcs_algo = [""] * (index + 1)
14     lcs_algo[index] = ""
15     i = m
16     j = n
17     while i > 0 and j > 0:
18         if S1[i - 1] == S2[j - 1]:
19             lcs_algo[index - 1] = S1[i - 1]
20             i -= 1
21             j -= 1
22             index -= 1
23         elif L[i - 1][j] > L[i][j - 1]:
24             i -= 1
25         else:
26             j -= 1
27     return lcs_algo

```

MD5: d4c2c050089e656220b23f7d1fd6963f | $\mathcal{O}(n^2)$

1.2 LIS

```

1 def LIS(A, strict=True):
2     from bisect import bisect_left
3     T = []
4     position = []
5
6     for a in A:
7         if len(T) == 0 or (strict and T[-1] < a) or (
8             not strict and T[-1] <= a):
9             position.append(len(T))
10            T.append(a)
11        else:
12            if strict:
13                k = bisect_left(T, a)
14            else:
15                k = bisect_left(T, a + 1)
16            position.append(k)
17            T[k] = a
18
19     res = []
20     t = len(T) - 1
21     for i, p in enumerate(reversed(position)):
22         if t == p:
23             res.append(len(A) - 1 - i)
24             t -= 1
25     res.reverse()
26     return res

```

MD5: 2ac7f6b4312cecab73e02153e1a764e8 | $\mathcal{O}(n \log n)$

1.3 TSP

```

1 M={};Z={}
2 N=frozenset(range(1,len(dist_m)))
3 def dist(ni,N):
4     if not N:
5         Z[(ni,N)]=dist_m[ni][0]
6         return
7     for nj in N:
8         if (nj,N.difference({nj})) not in Z:
9             dist((nj,N.difference({nj})))
10            c=[(nj,dist_m[ni][nj]+Z[(nj,N.difference({nj}))])
11            for nj in N]
12            nmin,min_cost=min(c,key=lambda x:x[1])

```

```

12     M[(ni,N)] = nmin
13     Z[(ni,N)] = min_cost
14 min_dist = dist(0,N)
15 ni = 0
16 solution = [0]
17
18 while N:
19     ni = M[(ni, N)]
20     solution.append(ni)
21     N = N.difference({ni})
22 print(solution)

```

MD5: f546f5dabd450187bd027ac8a9b393c2 | $\mathcal{O}(2n * 2^n)$

1.4 hungarian

```

1 def hungarian(A):
2     inf = 1 << 40
3     n = len(A) + 1
4     m = len(A[0]) + 1
5     P = [0] * m
6     way = [0] * m
7     U = [0] * n
8     V = [0] * n
9     for i in range(1, n):
10        P[0] = i
11        minV = [inf] * m
12        used = [False] * m
13        j0 = 0
14        while P[j0] != 0:
15            i0 = P[j0]
16            j1 = 0
17            used[j0] = True
18            delta = inf
19            for j in range(1, m):
20                if used[j]:
21                    continue
22                if i0 == 0 or j == 0:
23                    cur = -U[i0] - V[j]
24                else:
25                    cur = A[i0 - 1][j - 1] - U[i0] - V[j]
26                if cur < minV[j]:
27                    minV[j] = cur
28                    way[j] = j0
29                if minV[j] < delta:
30                    delta = minV[j]
31                    j1 = j
32            for j in range(m):
33                if used[j]:
34                    U[P[j]] += delta
35                    V[j] -= delta
36            else:
37                minV[j] -= delta
38            j0 = j1
39            P[j0] = P[way[j0]]
40            j0 = way[j0]
41            while j0 != 0:
42                P[j0] = P[way[j0]]
43                j0 = way[j0]
44
45     ret = [-1] * (n - 1)
46     for i in range(1, m):
47         if P[i] != 0:
48             ret[P[i] - 1] = i - 1
49     return -V[0], ret

```

MD5: 482834ccb5fe1dab437f8562dadd046 | $\mathcal{O}(n^3)$

2 ds

2.1 Fenwick-Tree

```

1 class FenwickTree():
2     def __init__(self, n):
3         self.n = n
4         self.data = [0] * n
5     def build(self, arr):
6         for i, a in enumerate(arr):
7             self.data[i] = a
8         for i in range(1, self.n + 1):
9             if i + (i & -i) <= self.n:
10                self.data[i + (i & -i) - 1] += self.
11                    data[i - 1]
12     def add(self, p, x):
13         p += 1
14         while p <= self.n:
15             self.data[p - 1] += x
16             p += p & -p
17     def sum(self, r):
18         s = 0
19         while r:
20             s += self.data[r - 1]
21             r -= r & -r
22         return s
23     def range_sum(self, l, r):
24         #assert 0 <= l <= r <= self.n
25         return self.sum(r) - self.sum(l)

```

MD5: d291e9d6c6b1f3c72f795e0889401184 | $\mathcal{O}(\log n)$

2.2 Range count query

```

1 from bisect import bisect_left
2 from collections import defaultdict
3 class RangeCountQuery:
4     def __init__(self, arr):
5         self.depth = defaultdict(list)
6         for i, e in enumerate(arr):
7             self.depth[e].append(i)
8
9     def count(self, l, r, x):
10        """l <= k < r """
11        a = self.depth[x]
12        s = bisect_left(a, l)
13        t = bisect_left(a, r, s)
14        return t - s

```

MD5: 8f057ba70089cb686d1ba3e3cf770068 | $\mathcal{O}(?)$

2.3 Sorted Set

```

1 from typing import Union
2 class SortedSet:
3     def __init__(self, u: int):
4
5         self.log = (u - 1).bit_length()
6         self.size = 1 << self.log

```

```

self.u = u
self.data = bytearray(self.size << 1)

def add(self, k: int) -> bool:
    k += self.size
    if self.data[k]: return False
    self.data[k] = 1
    while k > 1:
        k >>= 1
        if self.data[k]: break
        self.data[k] = 1
    return True

def discard(self, k: int) -> bool:
    k += self.size
    if self.data[k] == 0: return False
    self.data[k] = 0
    while k > 1:
        if k & 1:
            if self.data[k - 1]: break
        else:
            if self.data[k + 1]: break
        k >>= 1
        self.data[k] = 0
    return True

def __contains__(self, k: int):
    return self.data[k + self.size] == 1

def get_min(self) -> Union[int, None]:
    if self.data[1] == 0: return None
    k = 1
    while k < self.size:
        k <<= 1
        if self.data[k] == 0: k |= 1
    return k - self.size

def get_max(self) -> Union[int, None]:
    if self.data[1] == 0: return None
    k = 1
    while k < self.size:
        k <<= 1
        if self.data[k | 1]: k |= 1
    return k - self.size

def lt(self, k: int) -> Union[int, None]:
    if self.data[1] == 0: return -1
    x = k
    k += self.size
    while k > 1:
        if k & 1 and self.data[k - 1]:
            k >>= 1
            break
        k >>= 1
    k <<= 1
    if self.data[k] == 0: return -1
    while k < self.size:
        k <<= 1
        if self.data[k | 1]: k |= 1
    k -= self.size
    return k if k < x else -1

def le(self, k: int) -> Union[int, None]:
    if self.data[k + self.size]: return k
    return self.lt(k)

def gt(self, k: int) -> Union[int, None]:
    if self.data[1] == 0: return -1
    x = k
    k += self.size
    while k > 1:

```

```

78         if k & 1 == 0 and self.data[k + 1]:
79             k >>= 1
80             break
81         k >>= 1
82         k = k << 1 | 1
83         while k < self.size:
84             k <<= 1
85             if self.data[k] == 0: k |= 1
86         k -= self.size
87         return k if k > x and k < self.u else -1
89
90 def ge(self, k: int) -> Union[int, None]:
91     if self.data[k + self.size]: return k
92     return self.gt(k)

```

MD5: cc50d52e7105d808eee80adf1f66bd0c | $\mathcal{O}(?)$

3 graph

3.1 Maximum Bipartite Matching

```

1 class BipartiteMatching:
2     def __init__(self, n, m):
3         self._n = n
4         self._m = m
5         self._to = [[] for _ in range(n)]
6
7     def add_edge(self, a, b):
8         self._to[a].append(b)
9
10    def solve(self):
11        n, m, to = self._n, self._m, self._to
12        prev = [-1] * n
13        root = [-1] * n
14        p = [-1] * n
15        q = [-1] * m
16        updated = True
17        while updated:
18            updated = False
19            s = []
20            s_front = 0
21            for i in range(n):
22                if p[i] == -1:
23                    root[i] = i
24                    s.append(i)
25            while s_front < len(s):
26                v = s[s_front]
27                s_front += 1
28                if p[root[v]] != -1:
29                    continue
30                for u in to[v]:
31                    if q[u] == -1:
32                        while u != -1:
33                            q[u] = v
34                            p[v], u = u, p[v]
35                            v = prev[v]
36                        updated = True
37                        break
38                u = q[u]
39                if prev[u] != -1:
40                    continue
41                prev[u] = v
42                root[u] = root[v]
43                s.append(u)
44            if updated:
45                for i in range(n):

```

```

46         prev[i] = -1
47         root[i] = -1
48         return [(v, p[v]) for v in range(n) if p[v] != -1]

```

MD5: 6c08e3f2668368058df74bc9b41fc041 | $\mathcal{O}(Fast)$

3.2 maxflow

Finds the greatest flow in a graph. Capacities must be positive.

```

1 from collections import deque
2
3 class MaxFlow():
4     def __init__(self, n):
5         self.n = n
6         self.graph = [[] for _ in range(n)]
7         self.pos = []
8
9     def add_edge(self, fr, to, cap):
10        m = len(self.pos)
11        self.pos.append((fr, len(self.graph[fr])))
12        fr_id = len(self.graph[fr])
13        to_id = len(self.graph[to])
14        if fr == to: to_id += 1
15        self.graph[fr].append((to, to_id, cap))
16        self.graph[to].append((fr, fr_id, 0))
17        return m
18
19    def get_edge(self, idx):
20        to, rev, cap = self.graph[self.pos[idx][0]][
21            self.pos[idx][1]]
22        rev_to, rev_rev, rev_cap = self.graph[to][rev]
23        return rev_to, to, cap + rev_cap, rev_cap
24
25    def edges(self):
26        m = len(self.pos)
27        for i in range(m):
28            yield self.get_edge(i)
29
30    def dfs(self, s, t, up):
31        stack = [t]
32        while stack:
33            v = stack.pop()
34            if v == s:
35                flow = up
36                for v in stack:
37                    to, rev, cap = self.graph[v][self.
38                        iter[v]]
39                    flow = min(flow, self.graph[to][
40                        rev][2])
41                for v in stack:
42                    self.graph[v][self.iter[v]][2] +=
43                        flow
44                    to, rev, cap = self.graph[v][self.
45                        iter[v]]
46                    self.graph[to][rev][2] -= flow
47                return flow
48            lv = self.level[v]
49            for i in range(self.iter[v], len(self.

```

```

50         break
51     else:
52         self.iter[v] = len(self.graph[v])
53         self.level[v] = self.n
54     return 0
55
56 def max_flow(self, s, t):
57     return self.max_flow_with_limit(s, t, 2**63 -
58                                     1)
59
60 def max_flow_with_limit(self, s, t, limit):
61     flow = 0
62     while flow < limit:
63         self.level = [-1] * self.n
64         self.level[s] = 0
65         queue = deque()
66         queue.append(s)
67         while queue:
68             v = queue.popleft()
69             for to, rev, cap in self.graph[v]:
70                 if cap == 0 or self.level[to] >=
71                     0: continue
72                 self.level[to] = self.level[v] + 1
73                 if to == t: break
74                 queue.append(to)
75             if self.level[t] == -1: break
76         self.iter = [0] * self.n
77         while flow < limit:
78             f = self.dfs(s, t, limit - flow)
79             if not f: break
80             flow += f
81     return flow

```

MD5: 6f622fc0f20b6d5813a979b581580661 | $\mathcal{O}(fast)$

4 math

4.1 FFT

```

1
2 import math
3
4
5 class FFT():
6     def primitive_root_constexpr(self, m):
7         if m == 2: return 1
8         if m == 167772161: return 3
9         if m == 469762049: return 3
10        if m == 754974721: return 11
11        if m == 998244353: return 3
12        divs = [0] * 20
13        divs[0] = 2
14        cnt = 1
15        x = (m - 1) // 2
16        while (x % 2 == 0): x //= 2
17        i = 3
18        while (i * i <= x):
19            if (x % i == 0):
20                divs[cnt] = i
21                cnt += 1
22                while (x % i == 0):
23                    x //= i
24            i += 2
25        if x > 1:
26            divs[cnt] = x
27            cnt += 1
28        g = 2

```

```

29 while (1):
30     ok = True
31     for i in range(cnt):
32         if pow(g, (m - 1) // divs[i], m) == 1:
33             ok = False
34             break
35     if ok:
36         return g
37     g += 1
38
39 def bsf(self, x):
40     res = 0
41     while (x % 2 == 0):
42         res += 1
43         x //= 2
44     return res
45
46 rank2 = 0
47 root = []
48 iroot = []
49 rate2 = []
50 irate2 = []
51 rate3 = []
52 irate3 = []
53
54 def __init__(self, MOD):
55     self.mod = MOD
56     self.g = self.primitive_root_constexpr(self.
57         mod)
58     self.rank2 = self.bsf(self.mod - 1)
59     self.root = [0 for i in range(self.rank2 + 1)]
60     self.iroot = [0 for i in range(self.rank2 + 1)
61         ]
62     self.rate2 = [0 for i in range(self.rank2)]
63     self.irate2 = [0 for i in range(self.rank2)]
64     self.rate3 = [0 for i in range(self.rank2 - 1)
65         ]
66     self.irate3 = [0 for i in range(self.rank2 -
67         1)]
68     self.root[self.rank2] = pow(self.g, (self.mod
69         - 1) >> self.rank2, self.mod)
70     self.iroot[self.rank2] = pow(self.root[self.
71         rank2], self.mod - 2, self.mod)
72     for i in range(self.rank2 - 1, -1, -1):
73         self.root[i] = (self.root[i + 1] ** 2) %
74             self.mod
75         self.iroot[i] = (self.iroot[i + 1] ** 2) %
76             self.mod
77     prod = 1;
78     iprod = 1
79     for i in range(self.rank2 - 1):
80         self.rate2[i] = (self.root[i + 2] * prod)
81         % self.mod
82         self.irate2[i] = (self.iroot[i + 2] *
83             iprod) % self.mod
84         prod = (prod * self.iroot[i + 2]) % self.
85             mod
86         iprod = (iprod * self.root[i + 2]) % self.
87             mod
88     prod = 1;
89     iprod = 1
90     for i in range(self.rank2 - 2):
91         self.rate3[i] = (self.root[i + 3] * prod)
92         % self.mod
93         self.irate3[i] = (self.iroot[i + 3] *
94             iprod) % self.mod
95         prod = (prod * self.iroot[i + 3]) % self.
96             mod

```

```

82         iprod = (iprod * self.root[i + 3]) % self.mod
83         mod
84     def butterfly(self, a):
85         n = len(a)
86         h = (n - 1).bit_length()
87
88         LEN = 0
89         while (LEN < h):
90             if (h - LEN == 1):
91                 p = 1 << (h - LEN - 1)
92                 rot = 1
93                 for s in range(1 << LEN):
94                     offset = s << (h - LEN)
95                     for i in range(p):
96                         l = a[i + offset]
97                         r = a[i + offset + p] * rot
98                         a[i + offset] = (l + r) % self.mod
99                         a[i + offset + p] = (l - r) % self.mod
100                     rot *= self.rate2[(~s & ~s).bit_length() - 1]
101                     rot %= self.mod
102                 LEN += 1
103             else:
104                 p = 1 << (h - LEN - 2)
105                 rot = 1
106                 imag = self.root[2]
107                 for s in range(1 << LEN):
108                     rot2 = (rot * rot) % self.mod
109                     rot3 = (rot2 * rot) % self.mod
110                     offset = s << (h - LEN)
111                     for i in range(p):
112                         a0 = a[i + offset]
113                         a1 = a[i + offset + p] * rot
114                         a2 = a[i + offset + 2 * p] * rot2
115                         a3 = a[i + offset + 3 * p] * rot3
116                         a1na3imag = (a1 - a3) % self.mod * imag
117                         a[i + offset] = (a0 + a2 + a1na3imag) % self.mod
118                         a[i + offset + p] = (a0 + a2 - a1 - a3) % self.mod
119                         a[i + offset + 2 * p] = (a0 - a2 + a1na3imag) % self.mod
120                         a[i + offset + 3 * p] = (a0 - a2 - a1na3imag) % self.mod
121                     rot *= self.rate3[(~s & ~s).bit_length() - 1]
122                     rot %= self.mod
123                 LEN += 2
124
125     def butterfly_inv(self, a):
126         n = len(a)
127         h = (n - 1).bit_length()
128         LEN = h
129         while (LEN):
130             if (LEN == 1):
131                 p = 1 << (h - LEN)
132                 irot = 1
133                 for s in range(1 << (LEN - 1)):
134                     offset = s << (h - LEN + 1)
135                     for i in range(p):
136                         l = a[i + offset]
137                         r = a[i + offset + p]
138                         a[i + offset] = (l + r) % self.mod
139                         a[i + offset + p] = (l - r) * irot % self.mod
140                         irot *= self.irate2[(~s & ~s).bit_length() - 1]
141                         irot %= self.mod
142                 LEN -= 1
143             else:
144                 p = 1 << (h - LEN)
145                 irot = 1
146                 iimag = self.iroot[2]
147                 for s in range(1 << (LEN - 2)):
148                     irot2 = (irot * irot) % self.mod
149                     irot3 = (irot * irot2) % self.mod
150                     offset = s << (h - LEN + 2)
151                     for i in range(p):
152                         a0 = a[i + offset]
153                         a1 = a[i + offset + p]
154                         a2 = a[i + offset + 2 * p]
155                         a3 = a[i + offset + 3 * p]
156                         a2na3iimag = (a2 - a3) * iimag % self.mod
157                         a[i + offset] = (a0 + a1 + a2 + a3) % self.mod
158                         a[i + offset + p] = (a0 - a1 + a2na3iimag) * irot % self.mod
159                         a[i + offset + 2 * p] = (a0 + a1 - a2 - a3) * irot2 % self.mod
160                         a[i + offset + 3 * p] = (a0 - a1 - a2na3iimag) * irot3 % self.mod
161                     irot *= self.irate3[(~s & ~s).bit_length() - 1]
162                     irot %= self.mod
163                 LEN -= 2
164
165     def convolution(self, a, b):
166         n = len(a);
167         m = len(b)
168         if not (a) or not (b):
169             return []
170         if min(n, m) <= 40:
171             res = [0] * (n + m - 1)
172             for i in range(n):
173                 for j in range(m):
174                     res[i + j] += a[i] * b[j]
175                     res[i + j] %= self.mod
176             return res
177         z = 1 << ((n + m - 2).bit_length())
178         a = a + [0] * (z - n)
179         b = b + [0] * (z - m)
180         self.butterfly(a)
181         self.butterfly(b)
182         c = [(a[i] * b[i]) % self.mod for i in range(z)]
183         self.butterfly_inv(c)
184         iz = pow(z, self.mod - 2, self.mod)
185         for i in range(n + m - 1):
186             c[i] = (c[i] * iz) % self.mod
187         return c[:n + m - 1]
188
189     def inv_gcd(a, b):
190         a = a % b
191         if a == 0:
192             return (b, 0)

```

```

194 s = b;
195 t = a
196 m0 = 0;
197 m1 = 1
198 while (t):
199     u = s // t
200     s -= t * u
201     m0 -= m1 * u
202     s, t = t, s
203     m0, m1 = m1, m0
204 if m0 < 0:
205     m0 += b // s
206 return (s, m0)
208
209 def crt(r, m):
210     assert len(r) == len(m)
211     n = len(r)
212     r0 = 0;
213     m0 = 1
214     for i in range(n):
215         assert 1 <= m[i]
216         r1 = r[i] % m[i]
217         m1 = m[i]
218         if m0 < m1:
219             r0, r1 = r1, r0
220             m0, m1 = m1, m0
221         if (m0 % m1 == 0):
222             if (r0 % m1 != r1):
223                 return (0, 0)
224             continue
225         g, im = inv_gcd(m0, m1)
226         u1 = m1 // g
227         if ((r1 - r0) % g):
228             return (0, 0)
229         x = (r1 - r0) // g % u1 * im % u1
230         r0 += x * m0
231         m0 *= u1
232         if r0 < 0:
233             r0 += m0
234     return (r0, m0)
236
237 mod0 = 1012924417
238 mod1 = 167772161
239 mod2 = 469762049
240 mod3 = 1224736769
241 mod4 = 998244353
242 ntt0 = FFT(mod0)
243 ntt1 = FFT(mod1)
244 ntt2 = FFT(mod2)
245 ntt3 = FFT(mod3)
246 ntt4 = FFT(mod4)
248
249 def convolution_2pow64(a, b):
250     mod = 1 << 64
251     n = len(a)
252     m = len(b)
253     for i in range(n): a[i]
254     for i in range(m): b[i]
255     x0 = ntt0.convolution(a, b)
256     x1 = ntt1.convolution(a, b)
257     x2 = ntt2.convolution(a, b)
258     x3 = ntt3.convolution(a, b)
259     x4 = ntt4.convolution(a, b)
260     ret = [0 for i in range(n + m - 1)]
261     for i in range(n + m - 1):
262         tmp = crt((x0[i], x1[i], x2[i], x3[i], x4[i]),
263                 (mod0, mod1, mod2, mod3, mod4))
264         ret[i] = tmp[0] % mod

```

```
return ret
```

MD5: 81010ba542ca59077527a18c77f90d2f | $\mathcal{O}(N \log N)$

4.2 MOD

```

1 MOD = 998244353
2
3 fac_arr = [1]
4 finv_arr = [1]
5
6 def enlarge_fac():
7     old_size = len(fac_arr)
8     new_size = old_size * 2
9     for i in range(old_size, new_size + 1):
10         fac_arr.append((fac_arr[-1] * i) % MOD)
11         finv_arr.append(pow(fac_arr[-1], -1, MOD))
12
13 def fac(n):
14     while n >= len(fac_arr): enlarge_fac()
15     return fac_arr[n]
16
17 def finv(n):
18     while n >= len(finv_arr): enlarge_fac()
19     return finv_arr[n]
20
21 def binom(n, k):
22     if k < 0 or k > n: return 0
23     return ((fac(n) * finv(k)) % MOD * finv(n - k)) % MOD

```

MD5: 563f35f15f93d1fa344f70ccb432d791 | $\mathcal{O}(N)$

4.3 Fast prime check

```

1 def is_prime(n):
2     if n == 2: return 1
3     if n == 1 or not n&1: return 0
4     #miller_rabin
5     if n < 1<<30: test_numbers = [2, 7, 61]
6     else: test_numbers = [2, 325, 9375, 28178, 450775,
7         9780504, 1795265022]
8     d = n - 1
9     while ~d&1: d>>=1
10    for a in test_numbers:
11        if n <= a: break
12        t = d
13        y = pow(a, t, n)
14        while t != n-1 and y != 1 and y != n-1:
15            y = y * y % n
16            t <<= 1
17        if y != n-1 and not t&1: return 0
18    return 1

```

MD5: dd31122281a49a705d1930e030221355 | $\mathcal{O}(\log N)$

5 misc

5.1 Bootstrap

Use when desperate

```

1 def bootstrap(f, stack=[]):
2     from types import GeneratorType
3     def wrappedfunc(*args, **kwargs):
4         if stack:
5             return f(*args, **kwargs)
6         else:
7             to = f(*args, **kwargs)
8             while True:
9                 if type(to) is GeneratorType:
10                     stack.append(to)
11                     to = next(to)
12                 else:
13                     stack.pop()
14                     if not stack:
15                         break
16                     to = stack[-1].send(to)
17             return to
18
19 return wrappedfunc

```

MD5: 026c45e94790fbc1d108dfccc34abb77 | $\mathcal{O}(\text{faster})$

6 more math

6.1 Tree

Diameter: BFS from any node, then BFS from last visited node.
Max dist is then the diameter. Center: Middle vertex in second step from above.

6.2 Divisability Explanation

$D \mid M \Leftrightarrow D \mid \text{digit_sum}(M, k, \text{alt})$, refer to table for values of D, k, alt .

6.3 Combinatorics

- Variations (ordered): k out of n objects (permutations for $k = n$)
 - without repetition:

$$M = \{(x_1, \dots, x_k) : 1 \leq x_i \leq n, x_i \neq x_j \text{ if } i \neq j\},$$

$$|M| = \frac{n!}{(n-k)!}$$
 - with repetition:

$$M = \{(x_1, \dots, x_k) : 1 \leq x_i \leq n\}, |M| = n^k$$
- Combinations (unordered): k out of n objects
 - without repetition: $M = \{(x_1, \dots, x_n) : x_i \in \{0, 1\}, x_1 + \dots + x_n = k\}, |M| = \binom{n}{k}$
 - with repetition: $M = \{(x_1, \dots, x_n) : x_i \in \{0, 1, \dots, k\}, x_1 + \dots + x_n = k\}, |M| = \binom{n+k-1}{k}$
- Ordered partition of numbers: $x_1 + \dots + x_k = n$ (i.e. $1+3=3+1=4$ are counted as 2 solutions)
 - #Solutions for $x_i \in \mathbb{N}_0$: $\binom{n+k-1}{k-1}$
 - #Solutions for $x_i \in \mathbb{N}$: $\binom{n-1}{k-1}$
- Unordered partition of numbers: $x_1 + \dots + x_k = n$ (i.e. $1+3=3+1=4$ are counted as 1 solution)

– #Solutions for $x_i \in \mathbb{N}$: $P_{n,k} = P_{n-k,k} + P_{n-1,k-1}$
where $P_{n,1} = P_{n,n} = 1$

- Derangements (permutations without fixed points): $!n = n! \sum_{k=0}^n \frac{(-1)^k}{k!} = \lfloor \frac{n!}{e} + \frac{1}{2} \rfloor$

6.4 Polynomial Interpolation

6.4.1 Theory

Problem: for $\{(x_0, y_0), \dots, (x_n, y_n)\}$ find $p \in \Pi_n$ with $p(x_i) = y_i$ for all $i = 0, \dots, n$.

Solution: $p(x) = \sum_{i=0}^n \gamma_{0,i} \prod_{j=0}^{i-1} (x - x_j)$ where $\gamma_{j,k} = y_j$ for $k = 0$

and $\gamma_{j,k} = \frac{\gamma_{j+1,k-1} - \gamma_{j,k-1}}{x_{j+k} - x_j}$ otherwise.

Efficient evaluation of $p(x)$: $b_n = \gamma_{0,n}$, $b_i = b_{i+1}(x - x_i) + \gamma_{0,i}$ for $i = n-1, \dots, 0$ with $b_0 = p(x)$.

6.5 Fibonacci Sequence

6.5.1 Binet's formula

$$\begin{pmatrix} f_n \\ f_{n+1} \end{pmatrix} = \begin{pmatrix} 0 & 1 \\ 1 & 1 \end{pmatrix}^n \begin{pmatrix} 0 \\ 1 \end{pmatrix} \Rightarrow f_n = \frac{1}{\sqrt{5}}(\phi^n - \tilde{\phi}^n) \text{ where } \phi = \frac{1+\sqrt{5}}{2} \text{ and } \tilde{\phi} = \frac{1-\sqrt{5}}{2}.$$

6.5.2 Generalization

$$g_n = \frac{1}{\sqrt{5}}(g_0(\phi^{n-1} - \tilde{\phi}^{n-1}) + g_1(\phi^n - \tilde{\phi}^n)) = g_0 f_{n-1} + g_1 f_n$$

for all $g_0, g_1 \in \mathbb{N}_0$

6.5.3 Pisano Period

Both $(f_n \bmod k)_{n \in \mathbb{N}_0}$ and $(g_n \bmod k)_{n \in \mathbb{N}_0}$ are periodic.

6.6 Series

$$\sum_{i=1}^n i = \frac{n(n+1)}{2}, \sum_{i=1}^n i^2 = \frac{n(n+1)(2n+1)}{6}, \sum_{i=1}^n i^3 = \frac{n^2(n+1)^2}{4}$$

$$\sum_{i=0}^n c^i = \frac{c^{n+1}-1}{c-1}, c \neq 1, \sum_{i=0}^{\infty} c^i = \frac{1}{1-c}, \sum_{i=1}^n c^i = \frac{c}{1-c}, |c| < 1$$

$$\sum_{i=0}^n i c^i = \frac{nc^{n+2} - (n+1)c^{n+1} + c}{(c-1)^2}, c \neq 1, \sum_{i=0}^{\infty} i c^i = \frac{c}{(1-c)^2}, |c| < 1$$

6.7 Binomial coefficients

$$\binom{n}{k} = \binom{n-1}{k} + \binom{n-1}{k-1}, \quad \binom{n}{m} \binom{m}{k} = \binom{n}{k} \binom{n-k}{m-k},$$

$$\binom{m+n}{r} = \sum_{k=0}^r \binom{m}{k} \binom{n}{r-k} \text{ and in general, } n_1 + \dots + n_p = \sum_{k_1+\dots+k_p=m} \binom{n_1}{k_1} \dots \binom{n_p}{k_p}$$

6.8 Catalan numbers

$$C_n = \frac{1}{n+1} \binom{2n}{n} = \frac{(2n)!}{(n+1)!n!}$$

$$C_0 = 1, C_{n+1} = \sum_{k=0}^n C_k C_{n-k}, C_{n+1} = \frac{4n+2}{n+2} C_n$$

6.9 Geometry

Area of a polygon: $A = \frac{1}{2}(x_1 y_2 - x_2 y_1 + x_2 y_3 - x_3 y_2 + \dots + x_{n-1} y_n - x_n y_{n-1} + x_n y_1 - x_1 y_n)$

6.10 Number Theory

Chinese Remainder Theorem: There exists a number C , such that:

$$C \equiv a_1 \pmod{n_1}, \dots, C \equiv a_k \pmod{n_k}, \text{ggt}(n_i, n_j) = 1, i \neq j$$

Case $k = 2$: $m_1 n_1 + m_2 n_2 = 1$ with EEA.

Solution is $x = a_1 m_2 n_2 + a_2 m_1 n_1$.

General case: iterative application of $k = 2$

Euler's φ -Funktion: $\varphi(n) = n \prod_{p|n} (1 - \frac{1}{p})$, p prime

$$\varphi(p) = p - 1, \varphi(pq) = \varphi(p)\varphi(q), p, q \text{ prime}$$

$$\varphi(p^k) = p^k - p^{k-1}, p, q \text{ prime}, k \geq 1$$

Eulers Theorem: $a^{\varphi(n)} \equiv 1 \pmod{n}$

Fermats Theorem: $a^p \equiv a \pmod{p}$, p prime

6.11 Convolution

$$(f * g)(n) = \sum_{m=-\infty}^{\infty} f(m)g(n-m) = \sum_{m=-\infty}^{\infty} f(n-m)g(m)$$

6.12 DP Optimization

- Convex Hull Optimization:

$$T[i] = \min_{j < i} (T[j] + b[j] \cdot a[i])$$

with the constraints $b[j] \geq b[j+1]$ and $a[j] \leq a[j+1]$.

Solution is convex and thus the optimal j for i will always

be smaller than the one for $i+1$. So we can use a pointer which we increment as long as the solution gets better. Running time is $\mathcal{O}(n)$ as the pointer visits each element no more than once.

- Divide and Conquer Optimization:

$$T[i][j] = \min_{k < j} (T[i-1][k] + C[k][j])$$

with the constraint $A[i][j] \leq A[i][j+1]$ with $A[i][j]$ giving the smallest optimal k . Is dealt with (including code) in misc chapter above.

- Knuth Optimization:

$$T[i][j] = \min_{i < k < j} (T[i][k] + T[k][j]) + C[i][j]$$

with the constraint $A[i][j-1] \leq A[i][j] \leq A[i+1][j]$ which is apparently equal to the following two constraints:

$$C[a][c] + C[b][d] \leq C[a][d] + C[b][c], a \leq b \leq c \leq d$$

$$C[b][c] \leq C[a][d], a \leq b \leq c \leq d$$

With above constraint we get good bounds on k by going calculating T with increasing $j-i$. Also see the code in misc.

Theoretical Computer Science Cheat Sheet

Definitions		Series	
$f(n) = O(g(n))$	iff \exists positive c, n_0 such that $0 \leq f(n) \leq cg(n) \forall n \geq n_0$.	$\sum_{i=1}^n i = \frac{n(n+1)}{2}, \quad \sum_{i=1}^n i^2 = \frac{n(n+1)(2n+1)}{6}, \quad \sum_{i=1}^n i^3 = \frac{n^2(n+1)^2}{4}.$	
$f(n) = \Omega(g(n))$	iff \exists positive c, n_0 such that $f(n) \geq cg(n) \geq 0 \forall n \geq n_0$.	In general:	
$f(n) = \Theta(g(n))$	iff $f(n) = O(g(n))$ and $f(n) = \Omega(g(n))$.	$\sum_{i=1}^n i^m = \frac{1}{m+1} \left[(n+1)^{m+1} - 1 - \sum_{i=1}^n ((i+1)^{m+1} - i^{m+1} - (m+1)i^m) \right]$	
$f(n) = o(g(n))$	iff $\lim_{n \rightarrow \infty} f(n)/g(n) = 0$.	$\sum_{i=1}^{n-1} i^m = \frac{1}{m+1} \sum_{k=0}^m \binom{m+1}{k} B_k n^{m+1-k}.$	
$\lim_{n \rightarrow \infty} a_n = a$	iff $\forall \epsilon > 0, \exists n_0$ such that $ a_n - a < \epsilon, \forall n \geq n_0$.	Geometric series:	
$\sup S$	least $b \in \mathbb{R}$ such that $b \geq s, \forall s \in S$.	$\sum_{i=0}^{\infty} c^i = \frac{c^{n+1} - 1}{c - 1}, \quad c \neq 1, \quad \sum_{i=0}^{\infty} c^i = \frac{1}{1-c}, \quad \sum_{i=1}^{\infty} c^i = \frac{c}{1-c}, \quad c < 1,$	
$\inf S$	greatest $b \in \mathbb{R}$ such that $b \leq s, \forall s \in S$.	$\sum_{i=0}^{\infty} ic^i = \frac{nc^{n+2} - (n+1)c^{n+1} + c}{(c-1)^2}, \quad c \neq 1, \quad \sum_{i=0}^{\infty} ic^i = \frac{c}{(1-c)^2}, \quad c < 1.$	
$\liminf_{n \rightarrow \infty} a_n$	$\lim_{n \rightarrow \infty} \inf \{a_i \mid i \geq n, i \in \mathbb{N}\}.$	Harmonic series:	
$\limsup_{n \rightarrow \infty} a_n$	$\lim_{n \rightarrow \infty} \sup \{a_i \mid i \geq n, i \in \mathbb{N}\}.$	$H_n = \sum_{i=1}^n \frac{1}{i}, \quad \sum_{i=1}^n iH_i = \frac{n(n+1)}{2}H_n - \frac{n(n-1)}{4}.$	
$\binom{n}{k}$	Combinations: Size k sub-sets of a size n set.	$\sum_{i=1}^n H_i = (n+1)H_n - n, \quad \sum_{i=1}^n \binom{i}{m} H_i = \binom{n+1}{m+1} \left(H_{n+1} - \frac{1}{m+1} \right).$	
$[n]_k$	Stirling numbers (1st kind): Arrangements of an n element set into k cycles.	1. $\binom{n}{k} = \frac{n!}{(n-k)!k!}, \quad 2. \sum_{k=0}^n \binom{n}{k} = 2^n, \quad 3. \binom{n}{k} = \binom{n}{n-k},$	
$\{n\}_k$	Stirling numbers (2nd kind): Partitions of an n element set into k non-empty sets.	4. $\binom{n}{k} = \frac{n}{k} \binom{n-1}{k-1}, \quad 5. \binom{n}{k} = \binom{n-1}{k} + \binom{n-1}{k-1},$	
$\langle n \rangle_k$	1st order Eulerian numbers: Permutations $\pi_1 \pi_2 \dots \pi_n$ on $\{1, 2, \dots, n\}$ with k ascents.	6. $\binom{n}{m} \binom{m}{k} = \binom{n}{k} \binom{n-k}{m-k}, \quad 7. \sum_{k=0}^n \binom{r+k}{k} = \binom{r+n+1}{n},$	
$\langle\langle n \rangle\rangle_k$	2nd order Eulerian numbers.	8. $\sum_{k=0}^n \binom{k}{m} = \binom{n+1}{m+1}, \quad 9. \sum_{k=0}^n \binom{r}{k} \binom{s}{n-k} = \binom{r+s}{n},$	
C_n	Catalan Numbers: Binary trees with $n+1$ vertices.	10. $\binom{n}{k} = (-1)^k \binom{k-n-1}{k}, \quad 11. \left\{ \begin{matrix} n \\ 1 \end{matrix} \right\} = \left\{ \begin{matrix} n \\ n \end{matrix} \right\} = 1,$	
14. $\left[\begin{matrix} n \\ 1 \end{matrix} \right] = (n-1)!,$	15. $\left[\begin{matrix} n \\ 2 \end{matrix} \right] = (n-1)!H_{n-1},$	16. $\left[\begin{matrix} n \\ n \end{matrix} \right] = 1,$	17. $\left[\begin{matrix} n \\ k \end{matrix} \right] \geq \left\{ \begin{matrix} n \\ k \end{matrix} \right\},$
18. $\left[\begin{matrix} n \\ k \end{matrix} \right] = (n-1) \left[\begin{matrix} n-1 \\ k \end{matrix} \right] + \left[\begin{matrix} n-1 \\ k-1 \end{matrix} \right],$	19. $\left\{ \begin{matrix} n \\ n-1 \end{matrix} \right\} = \left[\begin{matrix} n \\ n-1 \end{matrix} \right] = \binom{n}{2},$	20. $\sum_{k=0}^n \left[\begin{matrix} n \\ k \end{matrix} \right] = n!,$	21. $C_n = \frac{1}{n+1} \binom{2n}{n},$
22. $\left\langle \begin{matrix} n \\ 0 \end{matrix} \right\rangle = \left\langle \begin{matrix} n \\ n-1 \end{matrix} \right\rangle = 1,$	23. $\left\langle \begin{matrix} n \\ k \end{matrix} \right\rangle = \left\langle \begin{matrix} n \\ n-1-k \end{matrix} \right\rangle,$	24. $\left\langle \begin{matrix} n \\ k \end{matrix} \right\rangle = (k+1) \left\langle \begin{matrix} n-1 \\ k \end{matrix} \right\rangle + (n-k) \left\langle \begin{matrix} n-1 \\ k-1 \end{matrix} \right\rangle,$	
25. $\left\langle \begin{matrix} 0 \\ k \end{matrix} \right\rangle = \begin{cases} 1 & \text{if } k=0, \\ 0 & \text{otherwise} \end{cases}$	26. $\left\langle \begin{matrix} n \\ 1 \end{matrix} \right\rangle = 2^n - n - 1,$	27. $\left\langle \begin{matrix} n \\ 2 \end{matrix} \right\rangle = 3^n - (n+1)2^n + \binom{n+1}{2},$	
28. $x^n = \sum_{k=0}^n \left\langle \begin{matrix} n \\ k \end{matrix} \right\rangle \binom{x+k}{n},$	29. $\left\langle \begin{matrix} n \\ m \end{matrix} \right\rangle = \sum_{k=0}^m \binom{n+1}{k} (m+1-k)^n (-1)^k,$	30. $m! \left\{ \begin{matrix} n \\ m \end{matrix} \right\} = \sum_{k=0}^n \left\langle \begin{matrix} n \\ k \end{matrix} \right\rangle \binom{k}{n-m},$	
31. $\left\langle \begin{matrix} n \\ m \end{matrix} \right\rangle = \sum_{k=0}^n \left\{ \begin{matrix} n \\ k \end{matrix} \right\} \binom{n-k}{m} (-1)^{n-k-m} k!,$	32. $\langle\langle \begin{matrix} n \\ 0 \end{matrix} \rangle\rangle = 1,$	33. $\langle\langle \begin{matrix} n \\ n \end{matrix} \rangle\rangle = 0 \quad \text{for } n \neq 0,$	
34. $\langle\langle \begin{matrix} n \\ k \end{matrix} \rangle\rangle = (k+1) \langle\langle \begin{matrix} n-1 \\ k \end{matrix} \rangle\rangle + (2n-1-k) \langle\langle \begin{matrix} n-1 \\ k-1 \end{matrix} \rangle\rangle,$	35. $\sum_{k=0}^n \langle\langle \begin{matrix} n \\ k \end{matrix} \rangle\rangle = \frac{(2n)^n}{2^n},$	36. $\left\{ \begin{matrix} x \\ x-n \end{matrix} \right\} = \sum_{k=0}^n \langle\langle \begin{matrix} n \\ k \end{matrix} \rangle\rangle \binom{x+n-1-k}{2n},$	37. $\left\{ \begin{matrix} n+1 \\ m+1 \end{matrix} \right\} = \sum_k \binom{n}{k} \left\{ \begin{matrix} k \\ m \end{matrix} \right\} = \sum_{k=0}^n \left\{ \begin{matrix} k \\ m \end{matrix} \right\} (m+1)^{n-k},$

Theoretical Computer Science Cheat Sheet

Identities Cont.

$$\begin{aligned}
38. \quad \begin{bmatrix} n+1 \\ m+1 \end{bmatrix} &= \sum_k \begin{bmatrix} n \\ k \end{bmatrix} \begin{bmatrix} k \\ m \end{bmatrix} = \sum_{k=0}^n \begin{bmatrix} k \\ m \end{bmatrix} n^{\overline{n-k}} = n! \sum_{k=0}^n \frac{1}{k!} \begin{bmatrix} k \\ m \end{bmatrix}, & 39. \quad \begin{bmatrix} x \\ x-n \end{bmatrix} &= \sum_{k=0}^n \left\langle \begin{bmatrix} n \\ k \end{bmatrix} \right\rangle \begin{bmatrix} x+k \\ 2n \end{bmatrix}, \\
40. \quad \left\{ \begin{bmatrix} n \\ m \end{bmatrix} \right\} &= \sum_k \begin{bmatrix} n \\ k \end{bmatrix} \left\{ \begin{bmatrix} k+1 \\ m+1 \end{bmatrix} \right\} (-1)^{n-k}, & 41. \quad \begin{bmatrix} n \\ m \end{bmatrix} &= \sum_k \begin{bmatrix} n+1 \\ k+1 \end{bmatrix} \begin{bmatrix} k \\ m \end{bmatrix} (-1)^{m-k}, \\
42. \quad \left\{ \begin{bmatrix} m+n+1 \\ m \end{bmatrix} \right\} &= \sum_{k=0}^m k \left\{ \begin{bmatrix} n+k \\ k \end{bmatrix} \right\}, & 43. \quad \begin{bmatrix} m+n+1 \\ m \end{bmatrix} &= \sum_{k=0}^m k(n+k) \begin{bmatrix} n+k \\ k \end{bmatrix}, \\
44. \quad \begin{bmatrix} n \\ m \end{bmatrix} &= \sum_k \left\{ \begin{bmatrix} n+1 \\ k+1 \end{bmatrix} \right\} \begin{bmatrix} k \\ m \end{bmatrix} (-1)^{m-k}, & 45. \quad (n-m)! \begin{bmatrix} n \\ m \end{bmatrix} &= \sum_k \begin{bmatrix} n+1 \\ k+1 \end{bmatrix} \left\{ \begin{bmatrix} k \\ m \end{bmatrix} \right\} (-1)^{m-k}, \quad \text{for } n \geq m, \\
46. \quad \left\{ \begin{bmatrix} n \\ n-m \end{bmatrix} \right\} &= \sum_k \begin{bmatrix} m-n \\ m+k \end{bmatrix} \begin{bmatrix} m+n \\ n+k \end{bmatrix} \begin{bmatrix} m+k \\ k \end{bmatrix}, & 47. \quad \begin{bmatrix} n \\ n-m \end{bmatrix} &= \sum_k \begin{bmatrix} m-n \\ m+k \end{bmatrix} \begin{bmatrix} m+n \\ n+k \end{bmatrix} \left\{ \begin{bmatrix} m+k \\ k \end{bmatrix} \right\}, \\
48. \quad \left\{ \begin{bmatrix} n \\ \ell+m \end{bmatrix} \right\} \begin{bmatrix} \ell+m \\ \ell \end{bmatrix} &= \sum_k \left\{ \begin{bmatrix} k \\ \ell \end{bmatrix} \right\} \left\{ \begin{bmatrix} n-k \\ m \end{bmatrix} \right\} \begin{bmatrix} n \\ k \end{bmatrix}, & 49. \quad \begin{bmatrix} n \\ \ell+m \end{bmatrix} \begin{bmatrix} \ell+m \\ \ell \end{bmatrix} &= \sum_k \begin{bmatrix} k \\ \ell \end{bmatrix} \begin{bmatrix} n-k \\ m \end{bmatrix} \begin{bmatrix} n \\ k \end{bmatrix}.
\end{aligned}$$

Trees

Every tree with n vertices has $n-1$ edges.

Kraft inequality: If the depths of the leaves of a binary tree are d_1, \dots, d_n :

$$\sum_{i=1}^n 2^{-d_i} \leq 1,$$

and equality holds only if every internal node has 2 sons.

Recurrences

Master method:

$$T(n) = aT(n/b) + f(n), \quad a \geq 1, b > 1$$

If $\exists \epsilon > 0$ such that $f(n) = O(n^{\log_b a - \epsilon})$ then

$$T(n) = \Theta(n^{\log_b a}).$$

If $f(n) = \Theta(n^{\log_b a})$ then

$$T(n) = \Theta(n^{\log_b a} \log_2 n).$$

If $\exists \epsilon > 0$ such that $f(n) = \Omega(n^{\log_b a + \epsilon})$, and $\exists c < 1$ such that $af(n/b) \leq cf(n)$ for large n , then

$$T(n) = \Theta(f(n)).$$

Substitution (example): Consider the following recurrence

$$T_{i+1} = 2^{2^i} \cdot T_i^2, \quad T_1 = 2.$$

Note that T_i is always a power of two.

Let $t_i = \log_2 T_i$. Then we have

$$t_{i+1} = 2^i + 2t_i, \quad t_1 = 1.$$

Let $u_i = t_i/2^i$. Dividing both sides of the previous equation by 2^{i+1} we get

$$\frac{t_{i+1}}{2^{i+1}} = \frac{2^i}{2^{i+1}} + \frac{t_i}{2^i}.$$

Substituting we find

$$u_{i+1} = \frac{1}{2} + u_i, \quad u_1 = \frac{1}{2},$$

which is simply $u_i = i/2$. So we find that T_i has the closed form $T_i = 2^{i2^{i-1}}$.

Summing factors (example): Consider the following recurrence

$$T(n) = 3T(n/2) + n, \quad T(1) = 1.$$

Rewrite so that all terms involving T are on the left side

$$T(n) - 3T(n/2) = n.$$

Now expand the recurrence, and choose a factor which makes the left side “telescope”

$$1(T(n) - 3T(n/2)) = n$$

$$3(T(n/2) - 3T(n/4)) = n/2$$

$$\vdots \quad \vdots \quad \vdots$$

$$3^{\log_2 n-1}(T(2) - 3T(1)) = 2$$

Let $m = \log_2 n$. Summing the left side we get $T(n) - 3^m T(1) = T(n) - 3^m = T(n) - n^k$ where $k = \log_2 3 \approx 1.58496$.

Summing the right side we get

$$\sum_{i=0}^{m-1} \frac{n}{2^i} 3^i = n \sum_{i=0}^{m-1} \left(\frac{3}{2}\right)^i.$$

Let $c = \frac{3}{2}$. Then we have

$$n \sum_{i=0}^{m-1} c^i = n \left(\frac{c^m - 1}{c - 1} \right)$$

$$= 2n(c^{\log_2 n} - 1)$$

$$= 2n(c^{(k-1)\log_2 n} - 1)$$

$$= 2n^k - 2n,$$

and so $T(n) = 3n^k - 2n$. Full history recurrences can often be changed to limited history ones (example): Consider

$$T_i = 1 + \sum_{j=0}^{i-1} T_j, \quad T_0 = 1.$$

Note that

$$T_{i+1} = 1 + \sum_{j=0}^i T_j.$$

Subtracting we find

$$T_{i+1} - T_i = 1 + \sum_{j=0}^i T_j - 1 - \sum_{j=0}^{i-1} T_j$$

$$= T_i.$$

And so $T_{i+1} = 2T_i = 2^{i+1}$.

Generating functions:

1. Multiply both sides of the equation by x^i .
2. Sum both sides over all i for which the equation is valid.
3. Choose a generating function $G(x)$. Usually $G(x) = \sum_{i=0}^{\infty} x^i g_i$.
3. Rewrite the equation in terms of the generating function $G(x)$.
4. Solve for $G(x)$.
5. The coefficient of x^i in $G(x)$ is g_i .

Example:

$$g_{i+1} = 2g_i + 1, \quad g_0 = 0.$$

Multiply and sum:

$$\sum_{i \geq 0} g_{i+1} x^i = \sum_{i \geq 0} 2g_i x^i + \sum_{i \geq 0} x^i.$$

We choose $G(x) = \sum_{i \geq 0} x^i g_i$. Rewrite in terms of $G(x)$:

$$\frac{G(x) - g_0}{x} = 2G(x) + \sum_{i \geq 0} x^i.$$

Simplify:

$$\frac{G(x)}{x} = 2G(x) + \frac{1}{1-x}.$$

Solve for $G(x)$:

$$G(x) = \frac{x}{(1-x)(1-2x)}.$$

Expand this using partial fractions:

$$\begin{aligned}
G(x) &= x \left(\frac{2}{1-2x} - \frac{1}{1-x} \right) \\
&= x \left(2 \sum_{i \geq 0} 2^i x^i - \sum_{i \geq 0} x^i \right) \\
&= \sum_{i \geq 0} (2^{i+1} - 1) x^{i+1}.
\end{aligned}$$



So $g_i = 2^i - 1$.

Theoretical Computer Science Cheat Sheet

$$\pi \approx 3.14159, \quad e \approx 2.71828, \quad \gamma \approx 0.57721, \quad \phi = \frac{1+\sqrt{5}}{2} \approx 1.61803, \quad \hat{\phi} = \frac{1-\sqrt{5}}{2} \approx -.61803$$

i	2^i	p_i	General	Probability
1	2	2	Bernoulli Numbers ($B_i = 0$, odd $i \neq 1$):	Continuous distributions: If
2	4	3	$B_0 = 1, B_1 = -\frac{1}{2}, B_2 = \frac{1}{6}, B_4 = -\frac{1}{30},$	$\Pr[a < X < b] = \int_a^b p(x) dx,$
3	8	5	$B_6 = \frac{1}{42}, B_8 = -\frac{1}{30}, B_{10} = \frac{5}{66}.$	then p is the probability density function of X . If
4	16	7	Change of base, quadratic formula:	$\Pr[X < a] = P(a),$
5	32	11	$\log_b x = \frac{\log_a x}{\log_a b}, \quad \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}.$	then P is the distribution function of X . If P and p both exist then
6	64	13	Euler's number e :	$P(a) = \int_{-\infty}^a p(x) dx.$
7	128	17	$e = 1 + \frac{1}{2} + \frac{1}{6} + \frac{1}{24} + \frac{1}{120} + \dots$	Expectation: If X is discrete
8	256	19	$\lim_{n \rightarrow \infty} \left(1 + \frac{x}{n}\right)^n = e^x.$	$E[g(X)] = \sum_x g(x) \Pr[X = x].$
9	512	23	$\left(1 + \frac{1}{n}\right)^n < e < \left(1 + \frac{1}{n}\right)^{n+1}.$	If X continuous then
10	1,024	29	$\left(1 + \frac{1}{n}\right)^n = e - \frac{e}{2n} + \frac{11e}{24n^2} - O\left(\frac{1}{n^3}\right).$	$E[g(X)] = \int_{-\infty}^{\infty} g(x)p(x) dx = \int_{-\infty}^{\infty} g(x) dP(x).$
11	2,048	31	Harmonic numbers:	Variance, standard deviation:
12	4,096	37	$1, \frac{3}{2}, \frac{11}{6}, \frac{25}{12}, \frac{137}{60}, \frac{49}{20}, \frac{363}{140}, \frac{761}{280}, \frac{7129}{2520}, \dots$	$\text{VAR}[X] = E[X^2] - E[X]^2,$
13	8,192	41	$\ln n < H_n < \ln n + 1,$	$\sigma = \sqrt{\text{VAR}[X]}.$
14	16,384	43	$H_n = \ln n + \gamma + O\left(\frac{1}{n}\right).$	For events A and B :
15	32,768	47	Factorial, Stirling's approximation:	$\Pr[A \vee B] = \Pr[A] + \Pr[B] - \Pr[A \wedge B]$
16	65,536	53	$1, 2, 6, 24, 120, 720, 5040, 40320, 362880, \dots$	$\Pr[A \wedge B] = \Pr[A] \cdot \Pr[B],$
17	131,072	59	$n! = \sqrt{2\pi n} \left(\frac{n}{e}\right)^n \left(1 + \Theta\left(\frac{1}{n}\right)\right).$	iff A and B are independent.
18	262,144	61	Ackermann's function and inverse:	$\Pr[A B] = \frac{\Pr[A \wedge B]}{\Pr[B]}$
19	524,288	67	$a(i, j) = \begin{cases} 2^j & i = 1 \\ a(i-1, 2) & j = 1 \\ a(i-1, a(i, j-1)) & i, j \geq 2 \end{cases}$	For random variables X and Y :
20	1,048,576	71	$\alpha(i) = \min\{j \mid a(j, j) \geq i\}.$	$E[X \cdot Y] = E[X] \cdot E[Y],$
21	2,097,152	73	Binomial distribution:	if X and Y are independent.
22	4,194,304	79	$\Pr[X = k] = \binom{n}{k} p^k q^{n-k}, \quad q = 1 - p,$	$E[X + Y] = E[X] + E[Y],$
23	8,388,608	83	$E[X] = \sum_{k=1}^n k \binom{n}{k} p^k q^{n-k} = np.$	$E[cX] = c E[X].$
24	16,777,216	89	Poisson distribution:	Bayes' theorem:
25	33,554,432	97	$\Pr[X = k] = \frac{e^{-\lambda} \lambda^k}{k!}, \quad E[X] = \lambda.$	$\Pr[A_i B] = \frac{\Pr[B A_i] \Pr[A_i]}{\sum_{j=1}^n \Pr[A_j] \Pr[B A_j]}.$
26	67,108,864	101	Normal (Gaussian) distribution:	Inclusion-exclusion:
27	134,217,728	103	$p(x) = \frac{1}{\sqrt{2\pi}\sigma} e^{-(x-\mu)^2/2\sigma^2}, \quad E[X] = \mu.$	$\Pr\left[\bigvee_{i=1}^n X_i\right] = \sum_{i=1}^n \Pr[X_i] +$
28	268,435,456	107	The "coupon collector": We are given a random coupon each day, and there are n different types of coupons. The distribution of coupons is uniform. The expected number of days to pass before we to collect all n types is	$\sum_{k=2}^n (-1)^{k+1} \sum_{i_1 < \dots < i_k} \Pr\left[\bigwedge_{j=1}^k X_{i_j}\right].$
29	536,870,912	109	$nH_n.$	Moment inequalities:
30	1,073,741,824	113		$\Pr[X \geq \lambda E[X]] \leq \frac{1}{\lambda},$
31	2,147,483,648	127		$\Pr[X - E[X] \geq \lambda \cdot \sigma] \leq \frac{1}{\lambda^2}.$
32	4,294,967,296	131		Geometric distribution:
Pascal's Triangle				$\Pr[X = k] = pq^{k-1}, \quad q = 1 - p,$
1				$E[X] = \sum_{k=1}^{\infty} kpq^{k-1} = \frac{1}{p}.$
1 1				
1 2 1				
1 3 3 1				
1 4 6 4 1				
1 5 10 10 5 1				
1 6 15 20 15 6 1				
1 7 21 35 35 21 7 1				
1 8 28 56 70 56 28 8 1				
1 9 36 84 126 126 84 36 9 1				
1 10 45 120 210 252 210 120 45 10 1				

Theoretical Computer Science Cheat Sheet

Trigonometry	Matrices	More Trig.																								
<div></div> <p>Pythagorean theorem: $C^2 = A^2 + B^2$.</p> <p>Definitions:</p> $\sin a = A/C, \quad \cos a = B/C,$ $\csc a = C/A, \quad \sec a = C/B,$ $\tan a = \frac{\sin a}{\cos a} = \frac{A}{B}, \quad \cot a = \frac{\cos a}{\sin a} = \frac{B}{A}.$ <p>Area, radius of inscribed circle:</p> $\frac{1}{2}AB, \quad \frac{AB}{A+B+C}.$ <p>Identities:</p> $\sin x = \frac{1}{\csc x}, \quad \cos x = \frac{1}{\sec x},$ $\tan x = \frac{1}{\cot x}, \quad \sin^2 x + \cos^2 x = 1,$ $1 + \tan^2 x = \sec^2 x, \quad 1 + \cot^2 x = \csc^2 x,$ $\sin x = \cos\left(\frac{\pi}{2} - x\right), \quad \sin x = \sin(\pi - x),$ $\cos x = -\cos(\pi - x), \quad \tan x = \cot\left(\frac{\pi}{2} - x\right),$ $\cot x = -\cot(\pi - x), \quad \csc x = \cot\frac{x}{2} - \cot x,$ $\sin(x \pm y) = \sin x \cos y \pm \cos x \sin y,$ $\cos(x \pm y) = \cos x \cos y \mp \sin x \sin y,$ $\tan(x \pm y) = \frac{\tan x \pm \tan y}{1 \mp \tan x \tan y},$ $\cot(x \pm y) = \frac{\cot x \cot y \mp 1}{\cot x \pm \cot y},$ $\sin 2x = 2 \sin x \cos x, \quad \sin 2x = \frac{2 \tan x}{1 + \tan^2 x},$ $\cos 2x = \cos^2 x - \sin^2 x, \quad \cos 2x = 2 \cos^2 x - 1,$ $\cos 2x = 1 - 2 \sin^2 x, \quad \cos 2x = \frac{1 - \tan^2 x}{1 + \tan^2 x},$ $\tan 2x = \frac{2 \tan x}{1 - \tan^2 x}, \quad \cot 2x = \frac{\cot^2 x - 1}{2 \cot x},$ $\sin(x + y) \sin(x - y) = \sin^2 x - \sin^2 y,$ $\cos(x + y) \cos(x - y) = \cos^2 x - \sin^2 y.$ <p>Euler's equation:</p> $e^{ix} = \cos x + i \sin x, \quad e^{i\pi} = -1.$	<p>Multiplication:</p> $C = A \cdot B, \quad c_{i,j} = \sum_{k=1}^n a_{i,k} b_{k,j}.$ <p>Determinants: $\det A \neq 0$ iff A is non-singular.</p> $\det A \cdot B = \det A \cdot \det B,$ $\det A = \sum_{\pi} \prod_{i=1}^n \text{sign}(\pi) a_{i,\pi(i)}.$ <p>2×2 and 3×3 determinant:</p> $\begin{vmatrix} a & b \\ c & d \end{vmatrix} = ad - bc,$ $\begin{vmatrix} a & b & c \\ d & e & f \\ g & h & i \end{vmatrix} = g \begin{vmatrix} a & b \\ d & e \end{vmatrix} - h \begin{vmatrix} a & c \\ d & f \end{vmatrix} + i \begin{vmatrix} a & b \\ d & e \end{vmatrix}$ $= aei + bfg + cdh - ceg - fha - ibd.$ <p>Permanents:</p> $\text{perm } A = \sum_{\pi} \prod_{i=1}^n a_{i,\pi(i)}.$	<div></div> <p>Law of cosines:</p> $c^2 = a^2 + b^2 - 2ab \cos C.$ <p>Area:</p> $A = \frac{1}{2}hc,$ $= \frac{1}{2}ab \sin C,$ $= \frac{c^2 \sin A \sin B}{2 \sin C}.$ <p>Heron's formula:</p> $A = \sqrt{s \cdot s_a \cdot s_b \cdot s_c},$ $s = \frac{1}{2}(a + b + c),$ $s_a = s - a,$ $s_b = s - b,$ $s_c = s - c.$ <p>More identities:</p> $\sin \frac{x}{2} = \sqrt{\frac{1 - \cos x}{2}},$ $\cos \frac{x}{2} = \sqrt{\frac{1 + \cos x}{2}},$ $\tan \frac{x}{2} = \sqrt{\frac{1 - \cos x}{1 + \cos x}},$ $= \frac{1 - \cos x}{\sin x},$ $= \frac{\sin x}{1 + \cos x},$ $\cot \frac{x}{2} = \sqrt{\frac{1 + \cos x}{1 - \cos x}},$ $= \frac{1 + \cos x}{\sin x},$ $= \frac{\sin x}{1 - \cos x},$ $\sin x = \frac{e^{ix} - e^{-ix}}{2i},$ $\cos x = \frac{e^{ix} + e^{-ix}}{2},$ $\tan x = -i \frac{e^{ix} - e^{-ix}}{e^{ix} + e^{-ix}},$ $= -i \frac{e^{2ix} - 1}{e^{2ix} + 1},$ $\sin x = \frac{\sinh ix}{i},$ $\cos x = \cosh ix,$ $\tan x = \frac{\tanh ix}{i}.$																								
<p>v2.01 ©1994 by Steve Seiden sseiden@acm.org http://www.csc.lsu.edu/~seiden</p>	<p>Hyperbolic Functions</p> <p>Definitions:</p> $\sinh x = \frac{e^x - e^{-x}}{2}, \quad \cosh x = \frac{e^x + e^{-x}}{2},$ $\tanh x = \frac{e^x - e^{-x}}{e^x + e^{-x}}, \quad \text{csch } x = \frac{1}{\sinh x},$ $\text{sech } x = \frac{1}{\cosh x}, \quad \coth x = \frac{1}{\tanh x}.$ <p>Identities:</p> $\cosh^2 x - \sinh^2 x = 1, \quad \tanh^2 x + \text{sech}^2 x = 1,$ $\coth^2 x - \text{csch}^2 x = 1, \quad \sinh(-x) = -\sinh x,$ $\cosh(-x) = \cosh x, \quad \tanh(-x) = -\tanh x,$ $\sinh(x + y) = \sinh x \cosh y + \cosh x \sinh y,$ $\cosh(x + y) = \cosh x \cosh y + \sinh x \sinh y,$ $\sinh 2x = 2 \sinh x \cosh x,$ $\cosh 2x = \cosh^2 x + \sinh^2 x,$ $\cosh x + \sinh x = e^x, \quad \cosh x - \sinh x = e^{-x},$ $(\cosh x + \sinh x)^n = \cosh nx + \sinh nx, \quad n \in \mathbb{Z},$ $2 \sinh^2 \frac{x}{2} = \cosh x - 1, \quad 2 \cosh^2 \frac{x}{2} = \cosh x + 1.$ <table><tr><th>θ</th><th>$\sin \theta$</th><th>$\cos \theta$</th><th>$\tan \theta$</th></tr><tr><td>0</td><td>0</td><td>1</td><td>0</td></tr><tr><td>$\frac{\pi}{6}$</td><td>$\frac{1}{2}$</td><td>$\frac{\sqrt{3}}{2}$</td><td>$\frac{\sqrt{3}}{3}$</td></tr><tr><td>$\frac{\pi}{4}$</td><td>$\frac{\sqrt{2}}{2}$</td><td>$\frac{\sqrt{2}}{2}$</td><td>1</td></tr><tr><td>$\frac{\pi}{3}$</td><td>$\frac{\sqrt{3}}{2}$</td><td>$\frac{1}{2}$</td><td>$\sqrt{3}$</td></tr><tr><td>$\frac{\pi}{2}$</td><td>1</td><td>0</td><td>∞</td></tr></table> <p>... in mathematics you don't understand things, you just get used to them. - J. von Neumann</p>	θ	$\sin \theta$	$\cos \theta$	$\tan \theta$	0	0	1	0	$\frac{\pi}{6}$	$\frac{1}{2}$	$\frac{\sqrt{3}}{2}$	$\frac{\sqrt{3}}{3}$	$\frac{\pi}{4}$	$\frac{\sqrt{2}}{2}$	$\frac{\sqrt{2}}{2}$	1	$\frac{\pi}{3}$	$\frac{\sqrt{3}}{2}$	$\frac{1}{2}$	$\sqrt{3}$	$\frac{\pi}{2}$	1	0	∞	
θ	$\sin \theta$	$\cos \theta$	$\tan \theta$																							
0	0	1	0																							
$\frac{\pi}{6}$	$\frac{1}{2}$	$\frac{\sqrt{3}}{2}$	$\frac{\sqrt{3}}{3}$																							
$\frac{\pi}{4}$	$\frac{\sqrt{2}}{2}$	$\frac{\sqrt{2}}{2}$	1																							
$\frac{\pi}{3}$	$\frac{\sqrt{3}}{2}$	$\frac{1}{2}$	$\sqrt{3}$																							
$\frac{\pi}{2}$	1	0	∞																							

Theoretical Computer Science Cheat Sheet

Number Theory

The Chinese remainder theorem: There exists a number C such that:

$$C \equiv r_1 \pmod{m_1}$$

$$\vdots \quad \vdots \quad \vdots$$

$$C \equiv r_n \pmod{m_n}$$

if m_i and m_j are relatively prime for $i \neq j$.

Euler's function: $\phi(x)$ is the number of positive integers less than x relatively prime to x . If $\prod_{i=1}^n p_i^{e_i}$ is the prime factorization of x then

$$\phi(x) = \prod_{i=1}^n p_i^{e_i-1} (p_i - 1).$$

Euler's theorem: If a and b are relatively prime then

$$1 \equiv a^{\phi(b)} \pmod{b}.$$

Fermat's theorem:

$$1 \equiv a^{p-1} \pmod{p}.$$

The Euclidean algorithm: if $a > b$ are integers then

$$\gcd(a, b) = \gcd(a \bmod b, b).$$

If $\prod_{i=1}^n p_i^{e_i}$ is the prime factorization of x then

$$S(x) = \sum_{d|x} d = \prod_{i=1}^n \frac{p_i^{e_i+1} - 1}{p_i - 1}.$$

Perfect Numbers: x is an even perfect number iff $x = 2^{n-1}(2^n - 1)$ and $2^n - 1$ is prime.

Wilson's theorem: n is a prime iff

$$(n-1)! \equiv -1 \pmod{n}.$$

Möbius inversion:

$$\mu(i) = \begin{cases} 1 & \text{if } i = 1. \\ 0 & \text{if } i \text{ is not square-free.} \\ (-1)^r & \text{if } i \text{ is the product of } r \text{ distinct primes.} \end{cases}$$

If

$$G(a) = \sum_{d|a} F(d),$$

then

$$F(a) = \sum_{d|a} \mu(d) G\left(\frac{a}{d}\right).$$

Prime numbers:

$$\begin{aligned} p_n &= n \ln n + n \ln \ln n - n + n \frac{\ln \ln n}{\ln n} \\ &\quad + O\left(\frac{n}{\ln n}\right), \\ \pi(n) &= \frac{n}{\ln n} + \frac{n}{(\ln n)^2} + \frac{2!n}{(\ln n)^3} \\ &\quad + O\left(\frac{n}{(\ln n)^4}\right). \end{aligned}$$

Graph Theory

Definitions:

Loop An edge connecting a vertex to itself.

Directed Each edge has a direction.

Simple Graph with no loops or multi-edges.

Walk A sequence $v_0 e_1 v_1 \dots e_\ell v_\ell$.

Trail A walk with distinct edges.

Path A trail with distinct vertices.

Connected A graph where there exists a path between any two vertices.

Component A maximal connected subgraph.

Tree A connected acyclic graph.

Free tree A tree with no root.

DAG Directed acyclic graph.

Eulerian Graph with a trail visiting each edge exactly once.

Hamiltonian Graph with a cycle visiting each vertex exactly once.

Cut A set of edges whose removal increases the number of components.

Cut-set A minimal cut.

Cut edge A size 1 cut.

k-Connected A graph connected with the removal of any $k-1$ vertices.

k-Tough $\forall S \subseteq V, S \neq \emptyset$ we have $k \cdot c(G-S) \leq |S|$.

k-Regular A graph where all vertices have degree k .

k-Factor A k -regular spanning subgraph.

Matching A set of edges, no two of which are adjacent.

Clique A set of vertices, all of which are adjacent.

Ind. set A set of vertices, none of which are adjacent.

Vertex cover A set of vertices which cover all edges.

Planar graph A graph which can be embedded in the plane.

Plane graph An embedding of a planar graph.

$$\sum_{v \in V} \deg(v) = 2m.$$

If G is planar then $n - m + f = 2$, so

$$f \leq 2n - 4, \quad m \leq 3n - 6.$$

Any planar graph has a vertex with degree ≤ 5 .

Notation:

$E(G)$ Edge set

$V(G)$ Vertex set

$c(G)$ Number of components

$G[S]$ Induced subgraph

$\deg(v)$ Degree of v

$\Delta(G)$ Maximum degree

$\delta(G)$ Minimum degree

$\chi(G)$ Chromatic number

$\chi_E(G)$ Edge chromatic number

G^c Complement graph

K_n Complete graph

K_{n_1, n_2} Complete bipartite graph

$r(k, \ell)$ Ramsey number

Geometry

Projective coordinates: triples (x, y, z) , not all x, y and z zero.

$$(x, y, z) = (cx, cy, cz) \quad \forall c \neq 0.$$

Cartesian Projective

$$(x, y) \quad (x, y, 1)$$

$$y = mx + b \quad (m, -1, b)$$

$$x = c \quad (1, 0, -c)$$

Distance formula, L_p and L_∞ metric:

$$\sqrt{(x_1 - x_0)^2 + (y_1 - y_0)^2},$$


$$[|x_1 - x_0|^p + |y_1 - y_0|^p]^{1/p},$$

$$\lim_{p \rightarrow \infty} [|x_1 - x_0|^p + |y_1 - y_0|^p]^{1/p}.$$

Area of triangle (x_0, y_0) , (x_1, y_1) and (x_2, y_2) :

$$\frac{1}{2} \text{abs} \begin{vmatrix} x_1 - x_0 & y_1 - y_0 \\ x_2 - x_0 & y_2 - y_0 \end{vmatrix}.$$

Angle formed by three points:



$$\cos \theta = \frac{(x_1, y_1) \cdot (x_2, y_2)}{l_1 l_2}.$$

Line through two points (x_0, y_0) and (x_1, y_1) :

$$\begin{vmatrix} x & y & 1 \\ x_0 & y_0 & 1 \\ x_1 & y_1 & 1 \end{vmatrix} = 0.$$

Area of circle, volume of sphere:

$$A = \pi r^2, \quad V = \frac{4}{3} \pi r^3.$$

If I have seen farther than others, it is because I have stood on the shoulders of giants.

– Issac Newton

Theoretical Computer Science Cheat Sheet

 π

Wallis' identity:

$$\pi = 2 \cdot \frac{2 \cdot 2 \cdot 4 \cdot 4 \cdot 6 \cdot 6 \cdots}{1 \cdot 3 \cdot 3 \cdot 5 \cdot 5 \cdot 7 \cdots}$$

Brouncker's continued fraction expansion:

$$\frac{\pi}{4} = 1 + \frac{1^2}{2 + \frac{3^2}{2 + \frac{5^2}{2 + \frac{7^2}{2 + \cdots}}}}$$

Gregory's series:

$$\frac{\pi}{4} = 1 - \frac{1}{3} + \frac{1}{5} - \frac{1}{7} + \frac{1}{9} - \cdots$$

Newton's series:

$$\frac{\pi}{6} = \frac{1}{2} + \frac{1}{2 \cdot 3 \cdot 2^3} + \frac{1 \cdot 3}{2 \cdot 4 \cdot 5 \cdot 2^5} + \cdots$$

Sharp's series:

$$\frac{\pi}{6} = \frac{1}{\sqrt{3}} \left(1 - \frac{1}{3^1 \cdot 3} + \frac{1}{3^2 \cdot 5} - \frac{1}{3^3 \cdot 7} + \cdots \right)$$

Euler's series:

$$\frac{\pi^2}{6} = \frac{1}{1^2} + \frac{1}{2^2} + \frac{1}{3^2} + \frac{1}{4^2} + \frac{1}{5^2} + \cdots$$

$$\frac{\pi^2}{8} = \frac{1}{1^2} + \frac{1}{3^2} + \frac{1}{5^2} + \frac{1}{7^2} + \frac{1}{9^2} + \cdots$$

$$\frac{\pi^2}{12} = \frac{1}{1^2} - \frac{1}{2^2} + \frac{1}{3^2} - \frac{1}{4^2} + \frac{1}{5^2} - \cdots$$

Partial Fractions

Let $N(x)$ and $D(x)$ be polynomial functions of x . We can break down $N(x)/D(x)$ using partial fraction expansion. First, if the degree of N is greater than or equal to the degree of D , divide N by D , obtaining

$$\frac{N(x)}{D(x)} = Q(x) + \frac{N'(x)}{D(x)},$$

where the degree of N' is less than that of D . Second, factor $D(x)$. Use the following rules: For a non-repeated factor:

$$\frac{N(x)}{(x-a)D(x)} = \frac{A}{x-a} + \frac{N'(x)}{D(x)},$$

where

$$A = \left[\frac{N(x)}{D(x)} \right]_{x=a}.$$

For a repeated factor:

$$\frac{N(x)}{(x-a)^m D(x)} = \sum_{k=0}^{m-1} \frac{A_k}{(x-a)^{m-k}} + \frac{N'(x)}{D(x)},$$

where

$$A_k = \frac{1}{k!} \left[\frac{d^k}{dx^k} \left(\frac{N(x)}{D(x)} \right) \right]_{x=a}.$$

The reasonable man adapts himself to the world; the unreasonable persists in trying to adapt the world to himself. Therefore all progress depends on the unreasonable.
– George Bernard Shaw

Calculus

Derivatives:

$$1. \frac{d(cu)}{dx} = c \frac{du}{dx}, \quad 2. \frac{d(u+v)}{dx} = \frac{du}{dx} + \frac{dv}{dx}, \quad 3. \frac{d(uv)}{dx} = u \frac{dv}{dx} + v \frac{du}{dx},$$

$$4. \frac{d(u^n)}{dx} = nu^{n-1} \frac{du}{dx}, \quad 5. \frac{d(u/v)}{dx} = \frac{v \left(\frac{du}{dx} \right) - u \left(\frac{dv}{dx} \right)}{v^2}, \quad 6. \frac{d(e^{cu})}{dx} = ce^{cu} \frac{du}{dx},$$

$$7. \frac{d(c^u)}{dx} = (\ln c) c^u \frac{du}{dx}, \quad 8. \frac{d(\ln u)}{dx} = \frac{1}{u} \frac{du}{dx},$$

$$9. \frac{d(\sin u)}{dx} = \cos u \frac{du}{dx}, \quad 10. \frac{d(\cos u)}{dx} = -\sin u \frac{du}{dx},$$

$$11. \frac{d(\tan u)}{dx} = \sec^2 u \frac{du}{dx}, \quad 12. \frac{d(\cot u)}{dx} = -\csc^2 u \frac{du}{dx},$$

$$13. \frac{d(\sec u)}{dx} = \tan u \sec u \frac{du}{dx}, \quad 14. \frac{d(\csc u)}{dx} = -\cot u \csc u \frac{du}{dx},$$

$$15. \frac{d(\arcsin u)}{dx} = \frac{1}{\sqrt{1-u^2}} \frac{du}{dx}, \quad 16. \frac{d(\arccos u)}{dx} = \frac{-1}{\sqrt{1-u^2}} \frac{du}{dx},$$

$$17. \frac{d(\arctan u)}{dx} = \frac{1}{1+u^2} \frac{du}{dx}, \quad 18. \frac{d(\operatorname{arccot} u)}{dx} = \frac{-1}{1+u^2} \frac{du}{dx},$$

$$19. \frac{d(\operatorname{arcsec} u)}{dx} = \frac{1}{u\sqrt{1-u^2}} \frac{du}{dx}, \quad 20. \frac{d(\operatorname{arccsc} u)}{dx} = \frac{-1}{u\sqrt{1-u^2}} \frac{du}{dx},$$

$$21. \frac{d(\sinh u)}{dx} = \cosh u \frac{du}{dx}, \quad 22. \frac{d(\cosh u)}{dx} = \sinh u \frac{du}{dx},$$

$$23. \frac{d(\tanh u)}{dx} = \operatorname{sech}^2 u \frac{du}{dx}, \quad 24. \frac{d(\coth u)}{dx} = -\operatorname{csch}^2 u \frac{du}{dx},$$

$$25. \frac{d(\operatorname{sech} u)}{dx} = -\operatorname{sech} u \tanh u \frac{du}{dx}, \quad 26. \frac{d(\operatorname{csch} u)}{dx} = -\operatorname{csch} u \coth u \frac{du}{dx},$$

$$27. \frac{d(\operatorname{arcsinh} u)}{dx} = \frac{1}{\sqrt{1+u^2}} \frac{du}{dx}, \quad 28. \frac{d(\operatorname{arccosh} u)}{dx} = \frac{1}{\sqrt{u^2-1}} \frac{du}{dx},$$

$$29. \frac{d(\operatorname{arctanh} u)}{dx} = \frac{1}{1-u^2} \frac{du}{dx}, \quad 30. \frac{d(\operatorname{arccoth} u)}{dx} = \frac{1}{u^2-1} \frac{du}{dx},$$

$$31. \frac{d(\operatorname{arcsech} u)}{dx} = \frac{-1}{u\sqrt{1-u^2}} \frac{du}{dx}, \quad 32. \frac{d(\operatorname{arccsch} u)}{dx} = \frac{-1}{|u|\sqrt{1+u^2}} \frac{du}{dx}.$$

Integrals:

$$1. \int cu \, dx = c \int u \, dx, \quad 2. \int (u+v) \, dx = \int u \, dx + \int v \, dx,$$

$$3. \int x^n \, dx = \frac{1}{n+1} x^{n+1}, \quad n \neq -1, \quad 4. \int \frac{1}{x} \, dx = \ln x, \quad 5. \int e^x \, dx = e^x,$$

$$6. \int \frac{dx}{1+x^2} = \arctan x, \quad 7. \int u \frac{dv}{dx} \, dx = uv - \int v \frac{du}{dx} \, dx,$$

$$8. \int \sin x \, dx = -\cos x, \quad 9. \int \cos x \, dx = \sin x,$$

$$10. \int \tan x \, dx = -\ln |\cos x|, \quad 11. \int \cot x \, dx = \ln |\cos x|,$$

$$12. \int \sec x \, dx = \ln |\sec x + \tan x|, \quad 13. \int \csc x \, dx = \ln |\csc x + \cot x|,$$

$$14. \int \arcsin \frac{x}{a} \, dx = \arcsin \frac{x}{a} + \sqrt{a^2 - x^2}, \quad a > 0,$$

Theoretical Computer Science Cheat Sheet

Calculus Cont.

15. $\int \arccos \frac{x}{a} dx = \arccos \frac{x}{a} - \sqrt{a^2 - x^2}, \quad a > 0,$
16. $\int \arctan \frac{x}{a} dx = x \arctan \frac{x}{a} - \frac{a}{2} \ln(a^2 + x^2), \quad a > 0,$
17. $\int \sin^2(ax) dx = \frac{1}{2a} (ax - \sin(ax) \cos(ax)),$
18. $\int \cos^2(ax) dx = \frac{1}{2a} (ax + \sin(ax) \cos(ax)),$
19. $\int \sec^2 x dx = \tan x,$
20. $\int \csc^2 x dx = -\cot x,$
21. $\int \sin^n x dx = -\frac{\sin^{n-1} x \cos x}{n} + \frac{n-1}{n} \int \sin^{n-2} x dx,$
22. $\int \cos^n x dx = \frac{\cos^{n-1} x \sin x}{n} + \frac{n-1}{n} \int \cos^{n-2} x dx,$
23. $\int \tan^n x dx = \frac{\tan^{n-1} x}{n-1} - \int \tan^{n-2} x dx, \quad n \neq 1,$
24. $\int \cot^n x dx = -\frac{\cot^{n-1} x}{n-1} - \int \cot^{n-2} x dx, \quad n \neq 1,$
25. $\int \sec^n x dx = \frac{\tan x \sec^{n-1} x}{n-1} + \frac{n-2}{n-1} \int \sec^{n-2} x dx, \quad n \neq 1,$
26. $\int \csc^n x dx = -\frac{\cot x \csc^{n-1} x}{n-1} + \frac{n-2}{n-1} \int \csc^{n-2} x dx, \quad n \neq 1,$
27. $\int \sinh x dx = \cosh x,$
28. $\int \cosh x dx = \sinh x,$
29. $\int \tanh x dx = \ln |\cosh x|,$
30. $\int \coth x dx = \ln |\sinh x|,$
31. $\int \operatorname{sech} x dx = \arctan \sinh x,$
32. $\int \operatorname{csch} x dx = \ln \left| \tanh \frac{x}{2} \right|,$
33. $\int \sinh^2 x dx = \frac{1}{4} \sinh(2x) - \frac{1}{2} x,$
34. $\int \cosh^2 x dx = \frac{1}{4} \sinh(2x) + \frac{1}{2} x,$
35. $\int \operatorname{sech}^2 x dx = \tanh x,$
36. $\int \operatorname{arcsinh} \frac{x}{a} dx = x \operatorname{arcsinh} \frac{x}{a} - \sqrt{x^2 + a^2}, \quad a > 0,$
37. $\int \operatorname{arctanh} \frac{x}{a} dx = x \operatorname{arctanh} \frac{x}{a} + \frac{a}{2} \ln |a^2 - x^2|,$
38. $\int \operatorname{arccosh} \frac{x}{a} dx = \begin{cases} x \operatorname{arccosh} \frac{x}{a} - \sqrt{x^2 + a^2}, & \text{if } \operatorname{arccosh} \frac{x}{a} > 0 \text{ and } a > 0, \\ x \operatorname{arccosh} \frac{x}{a} + \sqrt{x^2 + a^2}, & \text{if } \operatorname{arccosh} \frac{x}{a} < 0 \text{ and } a > 0, \end{cases}$
39. $\int \frac{dx}{\sqrt{a^2 + x^2}} = \ln \left(x + \sqrt{a^2 + x^2} \right), \quad a > 0,$
40. $\int \frac{dx}{a^2 + x^2} = \frac{1}{a} \arctan \frac{x}{a}, \quad a > 0,$
41. $\int \sqrt{a^2 - x^2} dx = \frac{x}{2} \sqrt{a^2 - x^2} + \frac{a^2}{2} \arcsin \frac{x}{a}, \quad a > 0,$
42. $\int (a^2 - x^2)^{3/2} dx = \frac{x}{8} (5a^2 - 2x^2) \sqrt{a^2 - x^2} + \frac{3a^4}{8} \arcsin \frac{x}{a}, \quad a > 0,$
43. $\int \frac{dx}{\sqrt{a^2 - x^2}} = \arcsin \frac{x}{a}, \quad a > 0,$
44. $\int \frac{dx}{a^2 - x^2} = \frac{1}{2a} \ln \left| \frac{a+x}{a-x} \right|,$
45. $\int \frac{dx}{(a^2 - x^2)^{3/2}} = \frac{x}{a^2 \sqrt{a^2 - x^2}},$
46. $\int \sqrt{a^2 \pm x^2} dx = \frac{x}{2} \sqrt{a^2 \pm x^2} \pm \frac{a^2}{2} \ln \left| x + \sqrt{a^2 \pm x^2} \right|,$
47. $\int \frac{dx}{\sqrt{x^2 - a^2}} = \ln \left| x + \sqrt{x^2 - a^2} \right|, \quad a > 0,$
48. $\int \frac{dx}{ax^2 + bx} = \frac{1}{a} \ln \left| \frac{x}{a+bx} \right|,$
49. $\int x \sqrt{a+bx} dx = \frac{2(3bx-2a)(a+bx)^{3/2}}{15b^2},$
50. $\int \frac{\sqrt{a+bx}}{x} dx = 2\sqrt{a+bx} + a \int \frac{1}{x\sqrt{a+bx}} dx,$
51. $\int \frac{x}{\sqrt{a+bx}} dx = \frac{1}{\sqrt{2}} \ln \left| \frac{\sqrt{a+bx} - \sqrt{a}}{\sqrt{a+bx} + \sqrt{a}} \right|, \quad a > 0,$
52. $\int \frac{\sqrt{a^2 - x^2}}{x} dx = \sqrt{a^2 - x^2} - a \ln \left| \frac{a + \sqrt{a^2 - x^2}}{x} \right|,$
53. $\int x \sqrt{a^2 - x^2} dx = -\frac{1}{3} (a^2 - x^2)^{3/2},$
54. $\int x^2 \sqrt{a^2 - x^2} dx = \frac{x}{8} (2x^2 - a^2) \sqrt{a^2 - x^2} + \frac{a^4}{8} \arcsin \frac{x}{a}, \quad a > 0,$
55. $\int \frac{dx}{\sqrt{a^2 - x^2}} = -\frac{1}{a} \ln \left| \frac{a + \sqrt{a^2 - x^2}}{x} \right|,$
56. $\int \frac{x dx}{\sqrt{a^2 - x^2}} = -\sqrt{a^2 - x^2},$
57. $\int \frac{x^2 dx}{\sqrt{a^2 - x^2}} = -\frac{x}{2} \sqrt{a^2 - x^2} + \frac{a^2}{2} \arcsin \frac{x}{a}, \quad a > 0,$
58. $\int \frac{\sqrt{a^2 + x^2}}{x} dx = \sqrt{a^2 + x^2} - a \ln \left| \frac{a + \sqrt{a^2 + x^2}}{x} \right|,$
59. $\int \frac{\sqrt{x^2 - a^2}}{x} dx = \sqrt{x^2 - a^2} - a \arccos \frac{a}{|x|}, \quad a > 0,$
60. $\int x \sqrt{x^2 \pm a^2} dx = \frac{1}{3} (x^2 \pm a^2)^{3/2},$
61. $\int \frac{dx}{x \sqrt{x^2 + a^2}} = \frac{1}{a} \ln \left| \frac{x}{a + \sqrt{a^2 + x^2}} \right|,$

Theoretical Computer Science Cheat Sheet

Calculus Cont.

$$\begin{aligned}
62. \int \frac{dx}{x\sqrt{x^2 - a^2}} &= \frac{1}{a} \arccos \frac{a}{|x|}, \quad a > 0, & 63. \int \frac{dx}{x^2\sqrt{x^2 \pm a^2}} &= \mp \frac{\sqrt{x^2 \pm a^2}}{a^2 x}, \\
64. \int \frac{x dx}{\sqrt{x^2 \pm a^2}} &= \sqrt{x^2 \pm a^2}, & 65. \int \frac{\sqrt{x^2 \pm a^2}}{x^4} dx &= \mp \frac{(x^2 + a^2)^{3/2}}{3a^2 x^3}, \\
66. \int \frac{dx}{ax^2 + bx + c} &= \begin{cases} \frac{1}{\sqrt{b^2 - 4ac}} \ln \left| \frac{2ax + b - \sqrt{b^2 - 4ac}}{2ax + b + \sqrt{b^2 - 4ac}} \right|, & \text{if } b^2 > 4ac, \\ \frac{2}{\sqrt{4ac - b^2}} \arctan \frac{2ax + b}{\sqrt{4ac - b^2}}, & \text{if } b^2 < 4ac, \end{cases} \\
67. \int \frac{dx}{\sqrt{ax^2 + bx + c}} &= \begin{cases} \frac{1}{\sqrt{a}} \ln \left| 2ax + b + 2\sqrt{a}\sqrt{ax^2 + bx + c} \right|, & \text{if } a > 0, \\ \frac{1}{\sqrt{-a}} \arcsin \frac{-2ax - b}{\sqrt{b^2 - 4ac}}, & \text{if } a < 0, \end{cases} \\
68. \int \sqrt{ax^2 + bx + c} dx &= \frac{2ax + b}{4a} \sqrt{ax^2 + bx + c} + \frac{4ac - b^2}{8a} \int \frac{dx}{\sqrt{ax^2 + bx + c}}, \\
69. \int \frac{x dx}{\sqrt{ax^2 + bx + c}} &= \frac{\sqrt{ax^2 + bx + c}}{a} - \frac{b}{2a} \int \frac{dx}{\sqrt{ax^2 + bx + c}}, \\
70. \int \frac{dx}{x\sqrt{ax^2 + bx + c}} &= \begin{cases} \frac{-1}{\sqrt{c}} \ln \left| \frac{2\sqrt{c}\sqrt{ax^2 + bx + c} + bx + 2c}{x} \right|, & \text{if } c > 0, \\ \frac{1}{\sqrt{-c}} \arcsin \frac{bx + 2c}{|x|\sqrt{b^2 - 4ac}}, & \text{if } c < 0, \end{cases} \\
71. \int x^3 \sqrt{x^2 + a^2} dx &= \left(\frac{1}{3}x^2 - \frac{2}{15}a^2\right)(x^2 + a^2)^{3/2}, \\
72. \int x^n \sin(ax) dx &= -\frac{1}{a}x^n \cos(ax) + \frac{n}{a} \int x^{n-1} \cos(ax) dx, \\
73. \int x^n \cos(ax) dx &= \frac{1}{a}x^n \sin(ax) - \frac{n}{a} \int x^{n-1} \sin(ax) dx, \\
74. \int x^n e^{ax} dx &= \frac{x^n e^{ax}}{a} - \frac{n}{a} \int x^{n-1} e^{ax} dx, \\
75. \int x^n \ln(ax) dx &= x^{n+1} \left(\frac{\ln(ax)}{n+1} - \frac{1}{(n+1)^2} \right), \\
76. \int x^n (\ln ax)^m dx &= \frac{x^{n+1}}{n+1} (\ln ax)^m - \frac{m}{n+1} \int x^n (\ln ax)^{m-1} dx.
\end{aligned}$$

Finite Calculus

Difference, shift operators:

$$\Delta f(x) = f(x+1) - f(x),$$

$$\mathbb{E} f(x) = f(x+1).$$

Fundamental Theorem:

$$f(x) = \Delta F(x) \Leftrightarrow \sum f(x) \delta x = F(x) + C.$$

$$\sum_a^b f(x) \delta x = \sum_{i=a}^{b-1} f(i).$$

Differences:

$$\Delta(cu) = c\Delta u, \quad \Delta(u+v) = \Delta u + \Delta v,$$

$$\Delta(uv) = u\Delta v + \mathbb{E} v \Delta u,$$

$$\Delta(x^n) = nx^{n-1},$$

$$\Delta(H_x) = x^{-1}, \quad \Delta(2^x) = 2^x,$$

$$\Delta(c^x) = (c-1)c^x, \quad \Delta\binom{x}{m} = \binom{x}{m-1}.$$

Sums:

$$\sum cu \delta x = c \sum u \delta x,$$

$$\sum (u+v) \delta x = \sum u \delta x + \sum v \delta x,$$

$$\sum u \Delta v \delta x = uv - \sum \mathbb{E} v \Delta u \delta x,$$

$$\sum x^n \delta x = \frac{x^{n+1}}{n+1}, \quad \sum x^{-1} \delta x = H_x,$$

$$\sum c^x \delta x = \frac{c^x}{c-1}, \quad \sum \binom{x}{m} \delta x = \binom{x}{m+1}.$$

Falling Factorial Powers:

$$x^{\underline{n}} = x(x-1) \cdots (x-n+1), \quad n > 0,$$

$$x^{\underline{0}} = 1,$$

$$x^{\underline{n}} = \frac{1}{(x+1) \cdots (x+|n|)}, \quad n < 0,$$

$$x^{\overline{n+m}} = x^{\overline{m}}(x-m)^{\underline{n}}.$$

Rising Factorial Powers:

$$x^{\overline{n}} = x(x+1) \cdots (x+n-1), \quad n > 0,$$

$$x^{\overline{0}} = 1,$$

$$x^{\overline{n}} = \frac{1}{(x-1) \cdots (x-|n|)}, \quad n < 0,$$

$$x^{\overline{n+m}} = x^{\overline{m}}(x+m)^{\underline{n}}.$$

Conversion:

$$x^{\underline{n}} = (-1)^n (-x)^{\overline{n}} = (x-n+1)^{\overline{n}}$$

$$= 1/(x+1)^{\overline{-n}},$$

$$x^{\overline{n}} = (-1)^n (-x)^{\underline{n}} = (x+n-1)^{\underline{n}}$$

$$= 1/(x-1)^{\underline{-n}},$$

$$x^n = \sum_{k=1}^n \left\{ \begin{matrix} n \\ k \end{matrix} \right\} x^{\underline{k}} = \sum_{k=1}^n \left\{ \begin{matrix} n \\ k \end{matrix} \right\} (-1)^{n-k} x^{\overline{k}},$$

$$x^{\underline{n}} = \sum_{k=1}^n \left[\begin{matrix} n \\ k \end{matrix} \right] (-1)^{n-k} x^k,$$

$$x^{\overline{n}} = \sum_{k=1}^n \left[\begin{matrix} n \\ k \end{matrix} \right] x^k.$$

$$\begin{aligned}
x^1 &= x^{\underline{1}} &= x^{\overline{1}} \\
x^2 &= x^{\underline{2}} + x^{\underline{1}} &= x^{\overline{2}} - x^{\overline{1}} \\
x^3 &= x^{\underline{3}} + 3x^{\underline{2}} + x^{\underline{1}} &= x^{\overline{3}} - 3x^{\overline{2}} + x^{\overline{1}} \\
x^4 &= x^{\underline{4}} + 6x^{\underline{3}} + 7x^{\underline{2}} + x^{\underline{1}} &= x^{\overline{4}} - 6x^{\overline{3}} + 7x^{\overline{2}} - x^{\overline{1}} \\
x^5 &= x^{\underline{5}} + 15x^{\underline{4}} + 25x^{\underline{3}} + 10x^{\underline{2}} + x^{\underline{1}} &= x^{\overline{5}} - 15x^{\overline{4}} + 25x^{\overline{3}} - 10x^{\overline{2}} + x^{\overline{1}} \\
x^{\overline{1}} &= x^1 &x^{\underline{1}} &= x^1 \\
x^{\overline{2}} &= x^2 + x^1 &x^{\underline{2}} &= x^2 - x^1 \\
x^{\overline{3}} &= x^3 + 3x^2 + 2x^1 &x^{\underline{3}} &= x^3 - 3x^2 + 2x^1 \\
x^{\overline{4}} &= x^4 + 6x^3 + 11x^2 + 6x^1 &x^{\underline{4}} &= x^4 - 6x^3 + 11x^2 - 6x^1 \\
x^{\overline{5}} &= x^5 + 10x^4 + 35x^3 + 50x^2 + 24x^1 &x^{\underline{5}} &= x^5 - 10x^4 + 35x^3 - 50x^2 + 24x^1
\end{aligned}$$

Theoretical Computer Science Cheat Sheet

Series

Taylor's series:

$$f(x) = f(a) + (x-a)f'(a) + \frac{(x-a)^2}{2}f''(a) + \dots = \sum_{i=0}^{\infty} \frac{(x-a)^i}{i!} f^{(i)}(a).$$

Expansions:

$$\begin{aligned} \frac{1}{1-x} &= 1 + x + x^2 + x^3 + x^4 + \dots = \sum_{i=0}^{\infty} x^i, \\ \frac{1}{1-cx} &= 1 + cx + c^2x^2 + c^3x^3 + \dots = \sum_{i=0}^{\infty} c^i x^i, \\ \frac{1}{1-x^n} &= 1 + x^n + x^{2n} + x^{3n} + \dots = \sum_{i=0}^{\infty} x^{ni}, \\ \frac{x}{(1-x)^2} &= x + 2x^2 + 3x^3 + 4x^4 + \dots = \sum_{i=0}^{\infty} ix^i, \\ x^k \frac{d^n}{dx^n} \left(\frac{1}{1-x} \right) &= x + 2^n x^2 + 3^n x^3 + 4^n x^4 + \dots = \sum_{i=0}^{\infty} i^n x^i, \\ e^x &= 1 + x + \frac{1}{2}x^2 + \frac{1}{6}x^3 + \dots = \sum_{i=0}^{\infty} \frac{x^i}{i!}, \\ \ln(1+x) &= x - \frac{1}{2}x^2 + \frac{1}{3}x^3 - \frac{1}{4}x^4 + \dots = \sum_{i=1}^{\infty} (-1)^{i+1} \frac{x^i}{i}, \\ \ln \frac{1}{1-x} &= x + \frac{1}{2}x^2 + \frac{1}{3}x^3 + \frac{1}{4}x^4 + \dots = \sum_{i=1}^{\infty} \frac{x^i}{i}, \\ \sin x &= x - \frac{1}{3!}x^3 + \frac{1}{5!}x^5 - \frac{1}{7!}x^7 + \dots = \sum_{i=0}^{\infty} (-1)^i \frac{x^{2i+1}}{(2i+1)!}, \\ \cos x &= 1 - \frac{1}{2!}x^2 + \frac{1}{4!}x^4 - \frac{1}{6!}x^6 + \dots = \sum_{i=0}^{\infty} (-1)^i \frac{x^{2i}}{(2i)!}, \\ \tan^{-1} x &= x - \frac{1}{3}x^3 + \frac{1}{5}x^5 - \frac{1}{7}x^7 + \dots = \sum_{i=0}^{\infty} (-1)^i \frac{x^{2i+1}}{(2i+1)}, \\ (1+x)^n &= 1 + nx + \frac{n(n-1)}{2}x^2 + \dots = \sum_{i=0}^{\infty} \binom{n}{i} x^i, \\ \frac{1}{(1-x)^{n+1}} &= 1 + (n+1)x + \binom{n+2}{2}x^2 + \dots = \sum_{i=0}^{\infty} \binom{i+n}{i} x^i, \\ \frac{x}{e^x - 1} &= 1 - \frac{1}{2}x + \frac{1}{12}x^2 - \frac{1}{720}x^4 + \dots = \sum_{i=0}^{\infty} \frac{B_i x^i}{i!}, \\ \frac{1}{2x}(1 - \sqrt{1-4x}) &= 1 + x + 2x^2 + 5x^3 + \dots = \sum_{i=0}^{\infty} \frac{1}{i+1} \binom{2i}{i} x^i, \\ \frac{1}{\sqrt{1-4x}} &= 1 + x + 2x^2 + 6x^3 + \dots = \sum_{i=0}^{\infty} \binom{2i}{i} x^i, \\ \frac{1}{\sqrt{1-4x}} \left(\frac{1 - \sqrt{1-4x}}{2x} \right)^n &= 1 + (2+n)x + \binom{4+n}{2}x^2 + \dots = \sum_{i=0}^{\infty} \binom{2i+n}{i} x^i, \\ \frac{1}{1-x} \ln \frac{1}{1-x} &= x + \frac{3}{2}x^2 + \frac{11}{6}x^3 + \frac{25}{12}x^4 + \dots = \sum_{i=1}^{\infty} H_i x^i, \\ \frac{1}{2} \left(\ln \frac{1}{1-x} \right)^2 &= \frac{1}{2}x^2 + \frac{3}{4}x^3 + \frac{11}{24}x^4 + \dots = \sum_{i=2}^{\infty} \frac{H_{i-1} x^i}{i}, \\ \frac{x}{1-x-x^2} &= x + x^2 + 2x^3 + 3x^4 + \dots = \sum_{i=0}^{\infty} F_i x^i, \\ \frac{F_n x}{1 - (F_{n-1} + F_{n+1})x - (-1)^n x^2} &= F_n x + F_{2n} x^2 + F_{3n} x^3 + \dots = \sum_{i=0}^{\infty} F_{ni} x^i. \end{aligned}$$

Ordinary power series:

$$A(x) = \sum_{i=0}^{\infty} a_i x^i.$$

Exponential power series:

$$A(x) = \sum_{i=0}^{\infty} a_i \frac{x^i}{i!}.$$

Dirichlet power series:

$$A(x) = \sum_{i=1}^{\infty} \frac{a_i}{i^x}.$$

Binomial theorem:

$$(x+y)^n = \sum_{k=0}^n \binom{n}{k} x^{n-k} y^k.$$

Difference of like powers:

$$x^n - y^n = (x-y) \sum_{k=0}^{n-1} x^{n-1-k} y^k.$$

For ordinary power series:

$$\alpha A(x) + \beta B(x) = \sum_{i=0}^{\infty} (\alpha a_i + \beta b_i) x^i,$$

$$x^k A(x) = \sum_{i=k}^{\infty} a_{i-k} x^i,$$

$$\frac{A(x) - \sum_{i=0}^{k-1} a_i x^i}{x^k} = \sum_{i=0}^{\infty} a_{i+k} x^i,$$

$$A(cx) = \sum_{i=0}^{\infty} c^i a_i x^i,$$

$$A'(x) = \sum_{i=0}^{\infty} (i+1) a_{i+1} x^i,$$

$$x A'(x) = \sum_{i=1}^{\infty} i a_i x^i,$$

$$\int A(x) dx = \sum_{i=1}^{\infty} \frac{a_{i-1}}{i} x^i,$$

$$\frac{A(x) + A(-x)}{2} = \sum_{i=0}^{\infty} a_{2i} x^{2i},$$

$$\frac{A(x) - A(-x)}{2} = \sum_{i=0}^{\infty} a_{2i+1} x^{2i+1}.$$

Summation: If $b_i = \sum_{j=0}^i a_j$ then

$$B(x) = \frac{1}{1-x} A(x).$$

Convolution:

$$A(x)B(x) = \sum_{i=0}^{\infty} \left(\sum_{j=0}^i a_j b_{i-j} \right) x^i.$$

God made the natural numbers;
all the rest is the work of man.
– Leopold Kronecker

Theoretical Computer Science Cheat Sheet


Series

Expansions:

$$\begin{aligned} \frac{1}{(1-x)^{n+1}} \ln \frac{1}{1-x} &= \sum_{i=0}^{\infty} (H_{n+i} - H_n) \binom{n+i}{i} x^i, \\ x^{\overline{n}} &= \sum_{i=0}^{\infty} \left[\begin{matrix} n \\ i \end{matrix} \right] x^i, \\ \left(\ln \frac{1}{1-x} \right)^n &= \sum_{i=0}^{\infty} \left[\begin{matrix} i \\ n \end{matrix} \right] \frac{n! x^i}{i!}, \\ \tan x &= \sum_{i=1}^{\infty} (-1)^{i-1} \frac{2^{2i} (2^{2i} - 1) B_{2i} x^{2i-1}}{(2i)!}, \\ \frac{1}{\zeta(x)} &= \sum_{i=1}^{\infty} \frac{\mu(i)}{i^x}, \\ \zeta(x) &= \prod_p \frac{1}{1 - p^{-x}}, \\ \zeta^2(x) &= \sum_{i=1}^{\infty} \frac{d(i)}{x^i} \quad \text{where } d(n) = \sum_{d|n} 1, \\ \zeta(x) \zeta(x-1) &= \sum_{i=1}^{\infty} \frac{S(i)}{x^i} \quad \text{where } S(n) = \sum_{d|n} d, \\ \zeta(2n) &= \frac{2^{2n-1} |B_{2n}|}{(2n)!} \pi^{2n}, \quad n \in \mathbb{N}, \\ \frac{x}{\sin x} &= \sum_{i=0}^{\infty} (-1)^{i-1} \frac{(4^i - 2) B_{2i} x^{2i}}{(2i)!}, \\ \left(\frac{1 - \sqrt{1-4x}}{2x} \right)^n &= \sum_{i=0}^{\infty} \frac{n(2i+n-1)!}{i!(n+i)!} x^i, \\ e^x \sin x &= \sum_{i=1}^{\infty} \frac{2^{i/2} \sin \frac{i\pi}{4}}{i!} x^i, \\ \sqrt{\frac{1 - \sqrt{1-x}}{x}} &= \sum_{i=0}^{\infty} \frac{(4i)!}{16^i \sqrt{2} (2i)!(2i+1)!} x^i, \\ \left(\frac{\arcsin x}{x} \right)^2 &= \sum_{i=0}^{\infty} \frac{4^i i!^2}{(i+1)(2i+1)!} x^{2i}. \end{aligned}$$

$$\begin{aligned} \left(\frac{1}{x} \right)^{\overline{-n}} &= \sum_{i=0}^{\infty} \left\{ \begin{matrix} i \\ n \end{matrix} \right\} x^i, \\ (e^x - 1)^n &= \sum_{i=0}^{\infty} \left\{ \begin{matrix} i \\ n \end{matrix} \right\} \frac{n! x^i}{i!}, \\ x \cot x &= \sum_{i=0}^{\infty} \frac{(-4)^i B_{2i} x^{2i}}{(2i)!}, \\ \zeta(x) &= \sum_{i=1}^{\infty} \frac{1}{i^x}, \\ \frac{\zeta(x-1)}{\zeta(x)} &= \sum_{i=1}^{\infty} \frac{\phi(i)}{i^x}, \end{aligned}$$

Escher's Knot



Stieltjes Integration

If G is continuous in the interval $[a, b]$ and F is nondecreasing then

$$\int_a^b G(x) dF(x)$$

exists. If $a \leq b \leq c$ then

$$\int_a^c G(x) dF(x) = \int_a^b G(x) dF(x) + \int_b^c G(x) dF(x).$$

If the integrals involved exist

$$\int_a^b (G(x) + H(x)) dF(x) = \int_a^b G(x) dF(x) + \int_a^b H(x) dF(x),$$

$$\int_a^b G(x) d(F(x) + H(x)) = \int_a^b G(x) dF(x) + \int_a^b G(x) dH(x),$$

$$\int_a^b c \cdot G(x) dF(x) = \int_a^b G(x) d(c \cdot F(x)) = c \int_a^b G(x) dF(x),$$

$$\int_a^b G(x) dF(x) = G(b)F(b) - G(a)F(a) - \int_a^b F(x) dG(x).$$

If the integrals involved exist, and F possesses a derivative F' at every point in $[a, b]$ then

$$\int_a^b G(x) dF(x) = \int_a^b G(x) F'(x) dx.$$

Cramer's Rule

If we have equations:

$$a_{1,1}x_1 + a_{1,2}x_2 + \cdots + a_{1,n}x_n = b_1$$

$$a_{2,1}x_1 + a_{2,2}x_2 + \cdots + a_{2,n}x_n = b_2$$

$$\vdots \quad \quad \quad \vdots$$

$$a_{n,1}x_1 + a_{n,2}x_2 + \cdots + a_{n,n}x_n = b_n$$

Let $A = (a_{i,j})$ and B be the column matrix (b_i) . Then there is a unique solution iff $\det A \neq 0$. Let A_i be A with column i replaced by B . Then

$$x_i = \frac{\det A_i}{\det A}.$$

Improvement makes strait roads, but the crooked roads without Improvement, are roads of Genius.
– William Blake (The Marriage of Heaven and Hell)

00	47	18	76	29	93	85	34	61	52
86	11	57	28	70	39	94	45	02	63
95	80	22	67	38	71	49	56	13	04
59	96	81	33	07	48	72	60	24	15
73	69	90	82	44	17	58	01	35	26
68	74	09	91	83	55	27	12	46	30
37	08	75	19	92	84	66	23	50	41
14	25	36	40	51	62	03	77	88	99
21	32	43	54	65	06	10	89	97	78
42	53	64	05	16	20	31	98	79	87

The Fibonacci number system:
Every integer n has a unique representation

$$n = F_{k_1} + F_{k_2} + \cdots + F_{k_m},$$

where $k_i \geq k_{i+1} + 2$ for all i ,
 $1 \leq i < m$ and $k_m \geq 2$.

Fibonacci Numbers

1, 1, 2, 3, 5, 8, 13, 21, 34, 55, 89, ...

Definitions:

$$F_i = F_{i-1} + F_{i-2}, \quad F_0 = F_1 = 1,$$

$$F_{-i} = (-1)^{i-1} F_i,$$

$$F_i = \frac{1}{\sqrt{5}} \left(\phi^i - \hat{\phi}^i \right),$$

Cassini's identity: for $i > 0$:

$$F_{i+1}F_{i-1} - F_i^2 = (-1)^i.$$

Additive rule:

$$F_{n+k} = F_k F_{n+1} + F_{k-1} F_n,$$

$$F_{2n} = F_n F_{n+1} + F_{n-1} F_n.$$

Calculation by matrices:

$$\begin{pmatrix} F_{n-2} & F_{n-1} \\ F_{n-1} & F_n \end{pmatrix} = \begin{pmatrix} 0 & 1 \\ 1 & 1 \end{pmatrix}^n.$$