

**LOCHAN D**  
**230701505**  
**COMPUTER SCIENCE AND ENGINEERING**

**Ex. No.: 13                      WORKING WITH TRIGGER**

**Date : 12-10-24**

**Initial:**

```
CREATE TABLE orders ( order_id
NUMBER PRIMARY KEY, item_id
NUMBER, quantity NUMBER,
order_date DATE, running_total
NUMBER, user_id NUMBER,
FOREIGN KEY (item_id) REFERENCES items(item_id)
);
```

```
INSERT INTO orders (order_id, item_id, quantity, order_date, running_total, user_id)
VALUES (1, 1, 20, SYSDATE, 20, 101);
INSERT INTO orders (order_id, item_id, quantity, order_date, running_total, user_id)
VALUES (2, 2, 30, SYSDATE, 50, 102);
```

```
CREATE TABLE items ( item_id
NUMBER PRIMARY KEY, item_name
VARCHAR2(50), stock_level
NUMBER, pending_orders NUMBER
DEFAULT 0
);
```

```
INSERT INTO items (item_id, item_name, stock_level, pending_orders)
VALUES (1, 'Item A', 100, 0);
INSERT INTO items (item_id, item_name, stock_level, pending_orders)
VALUES (2, 'Item B', 50, 0);
INSERT INTO items (item_id, item_name, stock_level, pending_orders) VALUES
(3, 'Item C', 150, 0);
```

```
CREATE TABLE audit_log (
log_id NUMBER PRIMARY KEY,
```

```

table_name VARCHAR2(50),
operation VARCHAR2(10),
    change_time TIMESTAMP DEFAULT CURRENT_TIMESTAMP,
user_id NUMBER,    details VARCHAR2(200)
);

CREATE SEQUENCE audit_log_seq
START WITH 1
INCREMENT BY 1;

```

### 1. Program 1

Write a code in PL/SQL to develop a trigger that enforces referential integrity by preventing the deletion of a parent record if child records exist.

```

CREATE OR REPLACE TRIGGER prevent_parent_delete
BEFORE DELETE ON items
FOR EACH ROW DECLARE
    child_count NUMBER;
BEGIN
    SELECT COUNT(*) INTO child_count FROM orders
    WHERE item_id = :OLD.item_id;

    IF child_count > 0 THEN
        RAISE_APPLICATION_ERROR(-20001, 'Cannot delete item; dependent
        orders exist.');
```

```

    END IF;
END; /

```

2. Write a code in PL/SQL to create a trigger that checks for duplicate values in a specific column and raises an exception if found.

```

CREATE OR REPLACE TRIGGER check_for_duplicates
BEFORE INSERT OR UPDATE ON orders
FOR EACH ROW DECLARE
    duplicate_count NUMBER;
BEGIN

```

```

SELECT COUNT(*) INTO duplicate_count FROM orders
WHERE item_id = :NEW.item_id AND order_id != :NEW.order_id;

IF duplicate_count > 0 THEN
    RAISE_APPLICATION_ERROR(-20002, 'Duplicate item entry found in
orders.');
```

END IF;

END; /

**3.** Write a code in PL/SQL to create a trigger that restricts the insertion of new rows if the total of a column's values exceeds a certain threshold.

```

CREATE OR REPLACE TRIGGER restrict_insertion
BEFORE INSERT ON orders
FOR EACH ROW DECLARE
    total_quantity NUMBER;
BEGIN
    SELECT SUM(quantity) INTO total_quantity FROM orders;
    IF (total_quantity + :NEW.quantity) > 500 THEN
        RAISE_APPLICATION_ERROR(-20003, 'Cannot insert order; total
quantity exceeds threshold.');
```

END IF;

END; /

**4.** Write a code in PL/SQL to design a trigger that captures changes made to specific columns and logs them in an audit table.

```

CREATE OR REPLACE TRIGGER log_changes
AFTER UPDATE ON orders
FOR EACH ROW
BEGIN
    INSERT INTO audit_log (log_id, table_name, operation, user_id, details) VALUES
    (audit_log_seq.NEXTVAL, 'orders', 'UPDATE', :NEW.user_id, 'Order ' ||
:NEW.order_id || ' changed from ' || :OLD.quantity || ' to ' || :NEW.quantity ); END;
```

/

5. Write a code in PL/SQL to implement a trigger that records user activity (inserts, updates, deletes) in an audit log for a given set of tables.

```
CREATE OR REPLACE TRIGGER log_user_activity
AFTER INSERT OR DELETE OR UPDATE ON orders
FOR EACH ROW
BEGIN
    INSERT INTO audit_log (log_id, table_name, operation, user_id, details) VALUES
    (audit_log_seq.NEXTVAL, 'orders',
        CASE
            WHEN INSERTING THEN 'INSERT'
            WHEN UPDATING THEN 'UPDATE'
            WHEN DELETING THEN 'DELETE'
        END,
        NVL(:NEW.user_id, :OLD.user_id), 'User action recorded on order ' ||
        NVL(:NEW.order_id, :OLD.order_id));
END; /
```

7. Write a code in PL/SQL to implement a trigger that automatically calculates and updates a running total column for a table whenever new rows are inserted.

```
CREATE OR REPLACE TRIGGER update_running_total
AFTER INSERT ON orders
FOR EACH ROW
BEGIN
    UPDATE orders SET running_total = (SELECT SUM(quantity) FROM orders)
    WHERE order_id = :NEW.order_id;
END; /
```

**8.** Write a code in PL/SQL to create a trigger that validates the availability of items before allowing an order to be placed, considering stock levels and pending orders

```
CREATE OR REPLACE TRIGGER validate_item_availability
```

```
BEFORE INSERT ON orders
```

```
FOR EACH ROW DECLARE
```

```
    available_stock NUMBER;
```

```
BEGIN
```

```
    SELECT stock_level - pending_orders INTO available_stock FROM items
```

```
    WHERE item_id = :NEW.item_id;
```

```
    IF :NEW.quantity > available_stock THEN
```

```
        RAISE_APPLICATION_ERROR(-20004, 'Insufficient stock available for the  
        order.');
```

```
    END IF;
```

```
    UPDATE items SET pending_orders = pending_orders + :NEW.quantity
```

```
    WHERE item_id = :NEW.item_id;
```

```
END; /
```

Result:

The given programs are performed successfully.