AMRITA VISHWA VIDYAPEETHAM
DEEMED TO BE UNIVERSITY UNDER SECTION 3 OF UGC ACT, 1956

A Security-Aware Self-RAG Framework with MedGemma for Medical Visual Intelligence : Attack Analysis and Mitigation Strategies for Diabetic Retinopathy Application

Project Phase 1

Supervisor: Dr. Gireesh kumar T

Name	Roll Number	Internship details
KAVIARASAN C	CB.SC.P2CSE25017	

Guide Approval Mail

Contents (Delete this slide in final copy – use only for instructions)

- Introduction and Motivation
- Problem Statement
- Proposed Methodology (algorithm, architecture, block diagram – whatever is applicable) – 1 slide
- Implementation Progress
- Identification of standard algorithms and evaluation metrics
- Identify and demonstrate expertise in using the tools and methods for implementation.
- Preliminary Verification & Results
- Datasets
- Project plan for semester 3 – with completion done till now.
- Domain Expertise course –progress
- Technical Enrichment Activities (Update) – List the 3 selected activities
- Conclusion
- References

Duplicate the slide 4 as many copies and edit.

Introduction and Motivation

- Diabetic Retinopathy (DR) affects 103 million people globally and projected to reach 160 million by 2045
- It progresses silently; many patients lose vision before they even notice symptoms
- AI-powered assistants can help with early screening and clinical guidance but current systems have two major weaknesses:

o Traditional RAG doesn't verify its own answers . It retrieves once, generates once, and never checks for errors

o No existing study combines Self-RAG with Medical LLM, and no one has performed adversarial attack testing on such an integrated system

Our motivation: build a DR assistant that checks its own reasoning and resists deliberate manipulation

Problem Statement

- Current RAG-based medical AI systems retrieve information and generate answers in a single pass without verifying whether the retrieved content is actually relevant or whether the final response contains fabricated facts.
- In a clinical domain like Diabetic Retinopathy, where a wrong recommendation about staging or treatment can directly harm a patient, this lack of self-verification is a serious risk.
- Additionally, these systems are deployed through web interfaces and APIs but are never evaluated against adversarial attacks, leaving them exposed to deliberate manipulation.
- This project addresses both gaps by building a Self-RAG pipeline integrated with MedGemma, a medical-domain LLM, that self-validates its reasoning at every stage and is systematically tested for security resilience.

Proposed Methodology

Three-Phase Framework: Build → Break → Shield

Phase 1: BUILD (Completed)

- Developed Self-RAG pipeline with 5 reflection stages
- Integrated MedGemma 4B-IT via Ollama for local, private inference
- Deployed Open WebUI via Docker as the frontend
- Built a unified ChromaDB knowledge base — 314 documents across 5 categories

Phase 2: BREAK


- Conducted systematic security assessment across all application layers
- Tested Role-Play Attacks
- Tested Prompt Injection / Jailbreak Attempts
- Tested Indirect / Inference Attacks
- Tested Bulk Data Dump Attacks, Direct Patient Data Extraction

Proposed Methodology

Phase 3: SHIELD

- Implement targeted defense mechanisms for each identified vulnerability
- Re-test all attack scenarios to validate the mitigations
- Compare security performance before vs. after defense
- Ensure security hardening does not degrade clinical accuracy

System Architecture



Implementation Progress

MODULE	STATUS
Unified ChromaDB Ingestion	Completed
Self-RAG CLI Application	Completed
Self-RAG API Server (OpenAI-compatible)	Completed
Open WebUI Integration	Completed
Multimodal Support	In Progress
Security Assessment	In Progress
Shield	In Progress

standard algorithms : Role-Play Persona Detector

```
FUNCTION detect_roleplay(query):
    score ← 0.0
    triggers ← []
    // Phase A: Scan persona-assignment keywords
    // These are phrases that try to redefine the model's identity
    PERSONA_KEYWORDS ← [
        ("act as / behave like",        weight=0.6),
        ("you are now a ...",           weight=0.7),
        ("pretend / imagine you're",    weight=0.7),
        ("role-play / impersonate",     weight=0.6),
        ("from now on you are/will",    weight=0.8),
        ("ignore your instructions",    weight=0.9),
        ("you have no rules",           weight=0.9)
    ]

    FOR EACH (pattern, weight) IN
        PERSONA_KEYWORDS:
        IF regex_match(pattern, lowercase(query)):
            score += weight
            triggers.add("persona:" + pattern.name)
    // Phase B: Scan authority escalation
    // Attacker claims fake admin/developer status
    AUTHORITY_KEYWORDS ← [
        ("I am the developer/admin",    weight=0.7),
        ("admin/root/sudo mode",        weight=0.8),
        ("maintenance/debug mode",      weight=0.7),
        ("authorized to access all",    weight=0.6)
    ]

    FOR EACH (pattern, weight) IN
    AUTHORITY_KEYWORDS:
        IF regex_match(pattern, lowercase(query)):
            score += weight
            triggers.add("authority:" + pattern.name)
```

standard algorithms : Role-Play Persona Detector

```
// Phase C: Detect fictional framing
// Wraps malicious request in a fictional scenario
FRAMING_KEYWORDS ← [
("hypothetically / theoretically", weight=0.4),
("for a movie/book/story", weight=0.5),
("in an alternate world/reality", weight=0.5)
]

FOR EACH (pattern, weight) IN FRAMING_KEYWORDS:
IF regex_match(pattern, lowercase(query)):
score += weight
triggers.add("framing:" + pattern.name)
```

```
// Phase D: Compound boost
// If BOTH persona AND authority patterns detected, apply 1.4× multiplier
// (indicates deliberate, multi-vector social engineering)
IF triggers contains "persona:*" AND triggers contains "authority:*":
score ← score × 1.4
RETURN min(score, 1.0), triggers
```


Evaluation Metrics

Metric	Value
Precision	1.0000
Recall (Detection Rate)	0.8500
F1 Score	0.9189
Accuracy	0.9250
False Positive Rate	0.0000


Tools and Methods for Implementation

Tool/Library	Purpose	Expertise Demonstrated
LangChain(v0.3.25)	RAG pipeline orchestration	Document loaders, text splitters, retriever chains
ChromaDB(v1.0.12)	Persistent vector database	Collection management, metadata filtering, cosine search
HuggingFace Transformers	Embedding models (all-MiniLM-L6-v2)	Sentence embeddings, mean pooling, L2 normalization
Ollama	Local LLM inference server	MedGemma 4B-IT deployment, OpenAI-compatible API
FastAPI	Self-RAG API server	Streaming SSE, middleware, Pydantic models
Open WebUI	Chat frontend (Docker)	Multi-model support, image upload, conversation management
Docker	Containerized deployment	Open WebUI container, networking


Results : Before Security Shield



Results : Before Security Shield



Results : After Security Shield



Datasets

Synthetic Patient Records (CSV — 500 patients)

Field	Description	Example
PatientID	Unique identifier (no names)	DR-0001
Age, Gender	Demographics	58 years, Female
DiabetesType, Duration	Disease history	Type 2, 14 years
HbA1c, FBS, BMI, BP	Lab results	8.2%, 180 mg/dL, 29.3, 148/92
DR_Stage	Severity classification	Moderate NPDR
VisualAcuity, IOP, MacularEdema	Ocular findings	20/50, 15.2 mmHg, Mild DME
Treatment, Medications, Follow-up	Management plan	Anti-VEGF (Ranibizumab), 3 months

Technical Enrichment Activities

Activity 1: MedGemma & Local LLM Deployment Workshop

- Deployed MedGemma 4B-IT (Google's medical LLM) locally via Ollama on Apple Silicon
- Explored multimodal capabilities: text-based Q&A + fundus image analysis
- Resolved platform-specific issues: ONNX mutex deadlock on macOS, tokenizer parallelism conflicts
- Built alternative ingestion pipeline (ingest_csv_to_chroma.py) using PyTorch directly to bypass ONNX issues

Activity 2: Open WebUI & API Server Development

- Built an OpenAI-compatible API wrapper (selfrag_server.py) exposing the Self-RAG pipeline as a standard /v1/chat/completions endpoint
- Integrated with Open WebUI (Docker) to provide a polished web chat interface
- Implemented Server-Sent Events (SSE) streaming for real-time pipeline stage visibility
- Supports multimodal inputs — users can upload fundus images alongside text queries