

Content model & ACF field definitions

A practical WordPress setup guide and field dictionary for the headless storefront.

Step 2 · Content migration

WordPress + WooCommerce · ACF Free · React on Vercel

10 field groups · 6 custom content types · 1 taxonomy

Includes the companion `Longlife-Digital-ACF-Import.json` package, editor instructions, ownership boundaries and the API contract.

Version 1.0 · September 17, 2026

Prepared from the current project source and integration plan.

Reference contents

1. Scope and ownership
2. Inventory and migration decisions
3. WordPress content structure
4. Page keys and storefront routes
5. Field conventions and validation
6. Page content
7. Site settings
8. Service details
9. Domain and website listing
10. FAQ placement
11. Reusable content block
12. Navigation link
13. Product display extras
14. Search and sharing metadata
15. Asset category display
16. Native fields: avoid duplicate editing
17. Import and first content entry
18. Initial navigation and public endpoints
19. Integration contract and acceptance
20. Sources and document maintenance

Scope and ownership

This reference defines the next content migration for the existing React/Vite/Mantine storefront. It is a schema and import package, not a completed CMS connection. Importing it creates editing structures; it does not populate records, change the React UI or enable checkout.

Owner	Content / responsibility
WordPress + ACF Free	Pages, services, assets, FAQs, reusable content blocks, navigation and public site copy.
Native WordPress fields	Titles, slugs, publication status, long-form content, post excerpts, categories, dates and featured media where supported.
WooCommerce	Product catalog, prices, stock, reviews, coupons, customers and orders. Product extras in this package require a later API mapping.
React on Vercel	Layout, gradients, icons, responsive breakpoints, route handling, interactive state and loading/error behavior.
Firebase / server integration later	Public media integration and protected fulfillment. Purchased file references, credentials, customer data and webhook secrets are excluded from this public import.

Package: 10 field groups, 6 custom post types, one taxonomy and 159 field definitions including structural Group fields. Designed for current ACF Free 6.1+ post-type support and WooCommerce. No Repeater, Flexible Content, Clone, Gallery or Pro Options Pages are used. [1–4]

Inventory and migration decisions

Current source	Target / decision
HomePage.jsx	Structured hero and section copy; related blocks for benefits/statistics; real WooCommerce products and native WordPress posts for collections.
Nav.jsx; HomePage.jsx footer	Public Site Settings + Navigation Links. Service and asset-category dropdowns derive their entries from their content records.
ServicesPage.jsx; Nav.jsx; ContactPage.jsx	One shared Services collection replaces the repeated lists, menu summaries and form service choices.
DomainsPage.jsx	Assets and Asset Categories replace sample listings and hardcoded filters. Verify domain ownership/availability before adding records.
AboutPage.jsx; FAQPage.jsx	Page copy + Content Blocks for story cards; separate FAQ records for questions/answers.
PrivacyPage.jsx; TermsPage.jsx; RefundPage.jsx	Native page editor for full approved policy content; ACF for the effective date and optional callout. Existing January 2024 dates and Payhip statements require review.
constants/data.js BLOG_POSTS; BlogPage.jsx	Native posts, excerpts, dates, categories and images. Full articles and a working article route still need implementation; current Read More controls have no handler.
ContactPage.jsx; DEFAULT_CONTACT; api/chat.js	Consolidate conflicting support emails into one approved Site Settings value. Keep inquiries/subscriber records out of public ACF fields.
NewsletterPopup.jsx; AIChat.jsx; api/chat.js	Move only public interface copy into settings. Subscription delivery, chatbot grounding and server-owned instructions remain implementation work.
ProductPage.jsx; ProductCard.jsx; catalog.js	Reuse WooCommerce data. Add only includes, level, duration, compatibility and public license copy.

Do not automatically migrate sample revenue claims, ratings, customer totals, guarantees, payment methods, coupon promises, domain inventory or dated policies. Populate approved content; keep unsupported statistics and unconfigured promotions absent.

WordPress content structure

Screen / type key	REST collection under /wp-json/wp/v2/	Native content
Pages / page	pages	One entry per route below; title and editor content as applicable.
Posts / post	posts	Articles: title, content, excerpt, date, categories, tags, featured image.
Site Settings lld_settings	lld-settings	Public brand/contact/newsletter/chat copy; one record named Storefront with slug storefront.
Services lld_service	lld-services	One published record per service or package.
Assets lld_asset	lld-assets	Domains now; website listings supported for later migration.
FAQs lld_faq	lld-faqs	Question in title, answer in content.
Content Blocks lld_block	lld-blocks	Reusable trust statements, benefits, story cards and approved statistics.
Navigation Links lld_nav_item	lld-navigation	Public header/footer links and dropdown sources.
Asset Categories / lld_asset_cat	lld-asset-categories	Name, slug, description; attached to Assets.

Custom content types are editable in WordPress and exposed through REST, with WordPress public permalink rendering disabled. Their published content remains public through the API. This setting is not privacy protection. Create exactly one published Site Settings record with slug `storefront`. [2, 5]

Use WordPress Order (`menu_order`) on services, assets, FAQs, blocks and navigation where available. Sort fetched records by `menu_order` then ID in React. Relationship selections have their own explicit order. Fetch all REST pages before sorting; do not assume the first API page is the full collection.

Page keys and storefront routes

Create the following WordPress Pages. Keep WordPress slugs stable and set the matching `lld_page_key`. The homepage record uses slug `home`; its React route remains `/`. WordPress front-page/theme settings do not control the React layout.

Page key	WordPress slug	React route	Current component
home	home	/	HomePage.jsx
shop	products	/products	ShopPage.jsx
about	about	/about	AboutPage.jsx
blog	blog	/blog	BlogPage.jsx
services	services	/services	ServicesPage.jsx
courses	courses	/courses	CoursesPage.jsx
domains	domains	/domains	DomainsPage.jsx
contact	contact	/contact	ContactPage.jsx
faq	faq	/faq	FAQPage.jsx
refund	refund-policy	/refund-policy	RefundPage.jsx
privacy	privacy-policy	/privacy-policy	PrivacyPage.jsx
terms	terms-of-service	/terms-of-service	TermsPage.jsx

The page-key selector controls which structured fields appear; it does not create routes. Uniqueness of page keys and the settings singleton is a publishing convention in this package, not a database constraint. Validate these during migration. Leave duplicate or unfinished entries in Draft.

Field conventions and validation

- API paths in the following tables are relative to the response `acf` object. Group fields nest their children. Field group keys are stable import identifiers; never rename a field name/key after integration without a migration.
- Required means ACF requires the field when its conditional editor controls are visible. Optional blank values omit the corresponding presentation, or use the documented fallback. ACF conditionals affect the editor; React must also respect the page key, pricing mode and block kind.
- Text is plain text. Textarea is plain text unless specified otherwise. WYSIWYG/native editor content must be sanitized by the application before HTML rendering. No raw scripts, HTML icons, CSS snippets or React components belong in text fields.
- Relationship fields return ordered ID arrays; Post Object fields return an ID or an empty value. Resolve only published, accessible records and preserve the chosen order. Do not use WordPress permalink URLs as React navigation destinations.
- The read contract uses `acf_format=light`. Image fields return attachment IDs; retrieve public media details from the WordPress media endpoint. Explicit public image URLs override attachments. Never put private object paths or signed/tokenized delivery URLs in image fields. [2]
- Destination text fields deliberately accept relative storefront paths. The future consumer must allow only local paths and explicitly allowed HTTPS/mailto/tel links, and reject other schemes. ACF Text alone does not validate this rule.
- Defaults are editor conveniences, not migrated or approved content. The import deliberately contains no product/post IDs, actual policy content, real coupon offers, domain inventory or customer statistics.
- All imported field groups have REST visibility enabled and contain public copy only. Conditional hiding, noindex, and publicly_queryable=false do not make a field confidential.

Page content

group_lld_page · Location: post_type = page · Public REST: enabled.

Shared page headings and structured sections. Policy prose lives in the native WordPress editor. Collection cards remain separate records. No CSS or React layout code is stored in these fields.

Label / API path	Type / required	Definition and rules
Storefront page lld_page_key	select Optional	Set this for each storefront content page. Leave empty on WooCommerce Cart, Checkout, My Account and other unrelated pages. Create one published entry per key using the route table. Choices: <code>home</code> = Home; <code>shop</code> = Shop; <code>about</code> = About; <code>blog</code> = Blog; <code>services</code> = Services; <code>courses</code> = Courses; <code>domains</code> = Domains; <code>contact</code> = Contact; <code>faq</code> = Faq; <code>refund</code> = Refund; <code>privacy</code> = Privacy; <code>terms</code> = Terms. Returns: <code>value</code> .
Small heading / badge lld_eyebrow	text Optional	Optional text above the page heading; Home uses this as the hero badge. Max characters: 160.
Display heading lld_heading	text Optional	Optional override of the WordPress page title. Home uses its three hero segments when supplied. Max characters: 160.
Page introduction lld_intro	textarea Optional	Home uses this as the hero paragraph; other pages use it below the heading. Max characters: 1000.

Page closing call to action

Public object: `acf.lld_cta`. Child fields inherit this group's visibility conditions.

Optional presentation value.

Label / API path	Type / required	Definition and rules
Heading lld_cta.heading	text Optional	Max characters: 160.
Description lld_cta.body	textarea Optional	Max characters: 1000.
Button label lld_cta.label	text Optional	Leave both label and destination empty to hide this button. Max characters: 60.
Destination lld_cta.destination	text Optional	A storefront path such as <code>/contact</code> , or a complete HTTPS URL. Never a WordPress page permalink. Max characters: 500.

Homepage sections

Public object: `acf.lld_home`. Child fields inherit this group's visibility conditions.

Show when: `lld_page_key = home`.

Label / API path	Type / required	Definition and rules
Hero opening line <code>lld_home.hero_prefix</code>	text Optional	For example: Beautifully Crafted. Max characters: 160.
Hero highlighted words <code>lld_home.hero_highlight</code>	text Optional	For example: Digital Products. Gradient styling remains in React. Max characters: 160.
Hero closing line <code>lld_home.hero_suffix</code>	text Optional	For example: for Life & Business. Max characters: 160.
Button label <code>lld_home.primary_cta.label</code>	text Optional	Leave both label and destination empty to hide this button. Max characters: 60.
Destination <code>lld_home.primary_cta.destination</code>	text Optional	A storefront path such as /contact, or a complete HTTPS URL. Never a WordPress page permalink. Max characters: 500.
Button label <code>lld_home.secondary_cta.label</code>	text Optional	Leave both label and destination empty to hide this button. Max characters: 60.
Destination <code>lld_home.secondary_cta.destination</code>	text Optional	A storefront path such as /contact, or a complete HTTPS URL. Never a WordPress page permalink. Max characters: 500.
Catalog heading <code>lld_home.catalog_title</code>	text Optional	Default: <code>Explore Our Products</code> . Max characters: 160.
Catalog introduction <code>lld_home.catalog_intro</code>	textarea Optional	Max characters: 1000.
Featured heading <code>lld_home.featured_title</code>	text Optional	Default: <code>Featured Products</code> . Max characters: 160.
Featured introduction <code>lld_home.featured_intro</code>	textarea Optional	Max characters: 1000.
Second collection heading <code>lld_home.more_title</code>	text Optional	Default: <code>More to Explore</code> . Max characters: 160.
Second collection introduction <code>lld_home.more_intro</code>	textarea Optional	Max characters: 1000.
Button label <code>lld_home.collection_cta.label</code>	text Optional	Leave both label and destination empty to hide this button. Max characters: 60.

Label / API path	Type / required	Definition and rules
Destination lld_home.collection_cta.destination	text Optional	A storefront path such as /contact, or a complete HTTPS URL. Never a WordPress page permalink. Max characters: 500.
Sale banner heading lld_home.offer_title	text Optional	Default: <i>Special Offer</i> . Max characters: 160.
Sale banner button label lld_home.offer_button	text Optional	Default: <i>Shop This Deal</i> . Max characters: 60.
Trust strip items lld_home.trust_items	relationship Optional	Select blocks of kind Trust statement; approve delivery/payment claims before publishing. Minimum: 0. Maximum: 8. Records: lld_block. Returns: id.
Additional hero statistics lld_home.hero_stats	relationship Optional	Select approved Statistic blocks. Product count and product review averages are derived from WooCommerce, not manually entered here. Minimum: 0. Maximum: 3. Records: lld_block. Returns: id.
Small heading lld_home.about.eyebrow	text Optional	Default: <i>Who are we?</i> . Max characters: 160.
Heading lld_home.about.heading	text Optional	Max characters: 160.
Body lld_home.about.body	wysiwyg Optional	Optional presentation value.
Benefits lld_home.about.benefits	relationship Optional	Select Benefit blocks in display order. Minimum: 0. Maximum: 8. Records: lld_block. Returns: id.
Statistics lld_home.about.stats	relationship Optional	Select verified Statistic blocks. Hide unverified claims. Minimum: 0. Maximum: 4. Records: lld_block. Returns: id.
Button label lld_home.about.cta.label	text Optional	Leave both label and destination empty to hide this button. Max characters: 60.
Destination lld_home.about.cta.destination	text Optional	A storefront path such as /contact, or a complete HTTPS URL. Never a WordPress page permalink. Max characters: 500.

Label / API path	Type / required	Definition and rules
Heading lld_home.blog.heading	text Optional	Max characters: 160.
Introduction lld_home.blog.intro	textarea Optional	Max characters: 1000.
Featured articles lld_home.blog.posts	relationship Optional	Choose up to three published posts. Empty means the latest three published posts. Minimum: 0. Maximum: 3. Records: post. Returns: id.
Button label lld_home.blog.cta.label	text Optional	Leave both label and destination empty to hide this button. Max characters: 60.
Destination lld_home.blog.cta.destination	text Optional	A storefront path such as /contact, or a complete HTTPS URL. Never a WordPress page permalink. Max characters: 500.

About page

Public object: acf.lld_about. Child fields inherit this group's visibility conditions.

Show when: lld_page_key = about.

Label / API path	Type / required	Definition and rules
Brand introduction lld_about.tagline	textarea Optional	Max characters: 1000.
Mission, offering and promise cards lld_about.sections	relationship Optional	Select Value/story blocks. Native page content can hold additional introductory prose. Minimum: 0. Maximum: 6. Records: lld_block. Returns: id.

Contact page copy

Public object: `acf.lld_contact`. Child fields inherit this group's visibility conditions.

Show when: `lld_page_key = contact`.

Label / API path	Type / required	Definition and rules
Contact information heading <code>lld_contact.information_heading</code>	text Optional	Max characters: 160.
Form heading <code>lld_contact.form_heading</code>	text Optional	Max characters: 160.
Form introduction <code>lld_contact.form_intro</code>	textarea Optional	Max characters: 1000.
Success heading <code>lld_contact.success_heading</code>	text Optional	Max characters: 160.
Success message <code>lld_contact.success_body</code>	textarea Optional	Show only after the future submission API confirms receipt, not on a failed request. Max characters: 1000.

Policy details

Public object: `acf.lld_policy`. Child fields inherit this group's visibility conditions.

Show when: `lld_page_key = privacy` OR `lld_page_key = refund` OR `lld_page_key = terms`.

Label / API path	Type / required	Definition and rules
Policy effective / updated date <code>lld_policy.updated_on</code>	date_picker Required	Date of the approved policy text, not the last incidental WordPress edit. REST light format: <code>Ymd</code> (for example 20260917). Configured standard return format: <code>Y-m-d</code> . Normalize in the content mapper before display.
Optional callout heading <code>lld_policy.callout_heading</code>	text Optional	Max characters: 160.
Optional callout text <code>lld_policy.callout_body</code>	textarea Optional	Max characters: 1000.

Site settings

group_lld_settings · Location: post_type = lld_settings · Public REST: enabled.

One published record with slug storefront. This is a public content record, not an ACF Pro Options Page. Do not put secrets, staff notes or customer records here.

Brand

Public object: `acf.lld_brand`. Child fields inherit this group's visibility conditions.

Optional presentation value.

Label / API path	Type / required	Definition and rules
Brand name <code>lld_brand.name</code>	text Required	Default: Longlife Digital. Max characters: 160.
Legal business name <code>lld_brand.legal_name</code>	text Optional	Default: Longlife Digital LLC. Max characters: 160.
Navigation tagline <code>lld_brand.tagline</code>	text Optional	Max characters: 160.
Public storefront URL <code>lld_brand.website</code>	url Required	Optional presentation value.
WordPress image <code>lld_brand.logo.attachment</code>	image Optional	Optional public preview image; REST value is an attachment ID. Returns: <code>id</code> . Public image: JPG, PNG, WebP or AVIF; max 5 MB. Server image support still applies.
Public image URL <code>lld_brand.logo.public_url</code>	url Optional	Optional HTTPS public image, including a public Firebase preview. If set, this takes precedence over the attachment.
Alternative text <code>lld_brand.logo.alt</code>	text Optional	Describe meaningful images; empty for purely decorative images. Max characters: 160.

Public contact details

Public object: `acf.lld_contact`. Child fields inherit this group's visibility conditions.

Optional presentation value.

Label / API path	Type / required	Definition and rules
Support email <code>lld_contact.email</code>	email Required	Resolve the existing support@lldhome.com versus support@longlifedigital.co mismatch before publishing.
Main social handle <code>lld_contact.social_handle</code>	text Optional	Max characters: 160.
Response-time statement <code>lld_contact.response_note</code>	text Optional	Max characters: 160.
Support hours and timezone <code>lld_contact.hours</code>	textarea Optional	Max characters: 1000.

Social links

Public object: `acf.lld_social`. Child fields inherit this group's visibility conditions.

Optional presentation value.

Label / API path	Type / required	Definition and rules
Instagram <code>lld_social.instagram</code>	url Optional	Optional presentation value.
Facebook <code>lld_social.facebook</code>	url Optional	Optional presentation value.
Tiktok <code>lld_social.tiktok</code>	url Optional	Optional presentation value.
Youtube <code>lld_social.youtube</code>	url Optional	Optional presentation value.
Linkedin <code>lld_social.linkedin</code>	url Optional	Optional presentation value.

Announcement bar

Public object: `acf.lld_announcement`. Child fields inherit this group's visibility conditions.

Optional presentation value.

Label / API path	Type / required	Definition and rules
Show announcement <code>lld_announcement.enabled</code>	true_false Optional	Default: 0.
Message <code>lld_announcement.message</code>	textarea Optional	Public marketing copy. Any advertised offer must match an active WooCommerce coupon. Max characters: 1000.
Displayed coupon code <code>lld_announcement.coupon_code</code>	text Optional	Display only; does not create, enable or validate a coupon. Max characters: 160.
Delivery note <code>lld_announcement.delivery_note</code>	text Optional	Max characters: 160.
Button label <code>lld_announcement.cta.label</code>	text Optional	Leave both label and destination empty to hide this button. Max characters: 60.
Destination <code>lld_announcement.cta.destination</code>	text Optional	A storefront path such as <code>/contact</code> , or a complete HTTPS URL. Never a WordPress page permalink. Max characters: 500.

Footer

Public object: `acf.lld_footer`. Child fields inherit this group's visibility conditions.

Optional presentation value.

Label / API path	Type / required	Definition and rules
Business description <code>lld_footer.description</code>	textarea Optional	Max characters: 1000.
Company links heading <code>lld_footer.company_heading</code>	text Optional	Default: <code>Company</code> . Max characters: 160.
Support links heading <code>lld_footer.support_heading</code>	text Optional	Default: <code>Support</code> . Max characters: 160.
Contact heading <code>lld_footer.contact_heading</code>	text Optional	Default: <code>Contact</code> . Max characters: 160.
Copyright owner <code>lld_footer.copyright_name</code>	text Optional	Year is generated by React; do not enter a fixed year. Max characters: 160.

Newsletter copy

Public object: `acf.lld_newsletter`. Child fields inherit this group's visibility conditions.

Optional presentation value.

Label / API path	Type / required	Definition and rules
Show newsletter signup <code>lld_newsletter.enabled</code>	true_false Optional	Enable in the integrated storefront only once subscription persistence is available. Default: 0.
Section heading <code>lld_newsletter.heading</code>	text Optional	Max characters: 160.
Description <code>lld_newsletter.body</code>	textarea Optional	Max characters: 1000.
Subscribe button label <code>lld_newsletter.button_label</code>	text Optional	Max characters: 60.
Consent wording <code>lld_newsletter.consent_text</code>	textarea Optional	Max characters: 1000.
Confirmed subscription message <code>lld_newsletter.success_message</code>	textarea Optional	Max characters: 1000.
Show newsletter popup <code>lld_newsletter.popup_enabled</code>	true_false Optional	Default: 0.
Popup heading <code>lld_newsletter.popup_heading</code>	text Optional	Max characters: 160.
Popup body <code>lld_newsletter.popup_body</code>	textarea Optional	Max characters: 1000.
Popup delay (seconds) <code>lld_newsletter.popup_delay_seconds</code>	number Optional	Default: 30. Minimum: 0. Maximum: 300. Increment: 1.

Chat public copy

Public object: `acf.lld_chat`. Child fields inherit this group's visibility conditions.

Optional presentation value.

Label / API path	Type / required	Definition and rules
Assistant display name <code>lld_chat.display_name</code>	text Optional	Max characters: 160.
Welcome message <code>lld_chat.welcome</code>	textarea Optional	Max characters: 1000.
Unavailable message <code>lld_chat.unavailable_message</code>	textarea Optional	Max characters: 1000.
Suggested questions <code>lld_chat.suggested_questions</code>	textarea Optional	One question per line; front end caps the list at four. Public copy only, never model instructions or credentials. Max characters: 1000.

Service details

`group_lld_service` · Location: `post_type = lld_service` · Public REST: enabled.

Native title is the service name, excerpt is the card description, content is extended copy, featured image is optional and `menu_order` controls sorting. The same records feed the Services menu and contact form service choices.

Label / API path	Type / required	Definition and rules
Icon <code>lld_icon</code>	text Optional	A short emoji or symbol; no HTML or SVG. Max characters: 12.
Short menu label <code>lld_nav_label</code>	text Optional	Optional; fallback is the service title. Max characters: 60.
Menu description <code>lld_nav_summary</code>	textarea Optional	Max characters: 160.
Pricing display <code>lld_pricing_mode</code>	select Optional	A quoted amount is informational only. Purchasable prices always come from the linked WooCommerce product. Choices: <code>contact</code> = Contact for pricing; <code>estimate</code> = Indicative asking / starting price; <code>product</code> = Linked WooCommerce product. Default: <code>contact</code> . Returns: <code>value</code> .
Indicative amount <code>lld_amount</code>	number Required	Never used to charge a customer. Minimum: 0. Increment: 0.01. Show when: <code>lld_pricing_mode = estimate</code> .
Quote currency <code>lld_currency</code>	select Optional	Initial business currency; expand deliberately if other currencies are supported. Choices: <code>USD</code> = USD. Default: <code>USD</code> . Returns: <code>value</code> . Show when: <code>lld_pricing_mode = estimate</code> .
Price wording <code>lld_billing_period</code>	select Optional	Display wording only; this does not create a subscription. Choices: <code>once</code> = One time; <code>month</code> = Per month; <code>year</code> = Per year. Default: <code>once</code> . Returns: <code>value</code> . Show when: <code>lld_pricing_mode = estimate</code> .
Linked WooCommerce product <code>lld_product</code>	post_object Required	Choose a published product. Resolve its ID through the WooCommerce catalog. Checkout remains a later integration. Records: <code>product</code> . Returns: <code>id</code> . Show when: <code>lld_pricing_mode = product</code> .
Included work / package details <code>lld_package_details</code>	wysiwyg Optional	Optional presentation value.

Service inquiry / consultation button

Public object: `acf.lld_cta`. Child fields inherit this group's visibility conditions.

Optional presentation value.

Label / API path	Type / required	Definition and rules
Button label <code>lld_cta.label</code>	text Optional	Leave both label and destination empty to hide this button. Max characters: 60.
Destination <code>lld_cta.destination</code>	text Optional	A storefront path such as <code>/contact</code> , or a complete HTTPS URL. Never a WordPress page permalink. Max characters: 500.

Domain and website listing

group_lld_asset · Location: post_type = lld_asset · Public REST: enabled.

Native title is the domain or website name; excerpt is the listing summary. Assign Asset Categories for filtering. Initial domain names and asking prices in the React source are samples, not a verified inventory.

Label / API path	Type / required	Definition and rules
Asset type lld_asset_type	select Required	Choices: <code>domain</code> = Domain; <code>website</code> = Ready-to-launch website. Default: <code>domain</code> . Returns: <code>value</code> .
Listing availability lld_availability	select Required	Editorial status only. Future checkout must enforce inventory and transfer eligibility in WooCommerce. Choices: <code>available</code> = Available; <code>reserved</code> = Reserved; <code>sold</code> = Sold. Default: <code>available</code> . Returns: <code>value</code> .
Badge text lld_badge	text Optional	Max characters: 40.
Public website preview lld_demo_url	url Optional	HTTPS public demo only; never registrar credentials or transfer codes. Show when: <code>lld_asset_type</code> = <code>website</code> .
Pricing display lld_pricing_mode	select Optional	A quoted amount is informational only. Purchasable prices always come from the linked WooCommerce product. Choices: <code>contact</code> = Contact for pricing; <code>estimate</code> = Indicative asking / starting price; <code>product</code> = Linked WooCommerce product. Default: <code>contact</code> . Returns: <code>value</code> .
Indicative amount lld_amount	number Required	Never used to charge a customer. Minimum: 0. Increment: 0.01. Show when: <code>lld_pricing_mode</code> = <code>estimate</code> .
Quote currency lld_currency	select Optional	Initial business currency; expand deliberately if other currencies are supported. Choices: <code>USD</code> = USD. Default: <code>USD</code> . Returns: <code>value</code> . Show when: <code>lld_pricing_mode</code> = <code>estimate</code> .
Price wording lld_billing_period	select Optional	Display wording only; this does not create a subscription. Choices: <code>once</code> = One time; <code>month</code> = Per month; <code>year</code> = Per year. Default: <code>once</code> . Returns: <code>value</code> . Show when: <code>lld_pricing_mode</code> = <code>estimate</code> .

Label / API path	Type / required	Definition and rules
Linked WooCommerce product lld_product	post_object Required	Choose a published product. Resolve its ID through the WooCommerce catalog. Checkout remains a later integration. Records: <code>product</code> . Returns: <code>id</code> . Show when: <code>lld_pricing_mode = product</code> .

Inquiry button

Public object: `acf.lld_cta`. Child fields inherit this group's visibility conditions.

Optional presentation value.

Label / API path	Type / required	Definition and rules
Button label lld_cta.label	text Optional	Leave both label and destination empty to hide this button. Max characters: 60.
Destination lld_cta.destination	text Optional	A storefront path such as <code>/contact</code> , or a complete HTTPS URL. Never a WordPress page permalink. Max characters: 500.

FAQ placement

group_lld_faq · Location: post_type = lld_faq · Public REST: enabled.

Native title is the question and native content is the formatted answer. Use menu_order for ordering. Store approved explanations, not application rules or customer messages.

Label / API path	Type / required	Definition and rules
Relevant sections lld_topics	checkbox Optional	General items appear on the FAQ page. Additional placements can be connected later. Choices: <code>general</code> = General; <code>products</code> = Products; <code>services</code> = Services; <code>domains</code> = Domains. Default: <code>['general']</code> . Returns: <code>value</code> .

Reusable content block

group_lld_block · Location: post_type = lld_block · Public REST: enabled.

Native title is the label, excerpt the short description, and content longer story-card text. Homepage/About relationship fields select and order blocks; no ACF Pro Repeater is required.

Label / API path	Type / required	Definition and rules
Block kind lld_kind	select Required	Choices: <code>trust</code> = Trust statement; <code>benefit</code> = Benefit; <code>stat</code> = Statistic; <code>value</code> = Value / story card. Default: <code>benefit</code> . Returns: <code>value</code> .
Icon lld_icon	text Optional	Optional short emoji or symbol. Max characters: 12.
Statistic display value lld_stat_value	text Required	Only approved, supportable marketing figures. Do not duplicate live product counts, prices or product ratings. Max characters: 30. Show when: <code>lld_kind</code> = <code>stat</code> .

Navigation link

`group_lld_navigation` · Location: `post_type = lld_nav_item` · Public REST: enabled.

Native title is the label, excerpt is an optional dropdown description, and `menu_order` controls sibling order. Service/category dropdowns are derived from their records so their names are not copied into multiple lists.

Label / API path	Type / required	Definition and rules
Menu area <code>lld_area</code>	select Required	Choices: <code>header</code> = Header; <code>footer_company</code> = Footer: Company; <code>footer_support</code> = Footer: Support; <code>footer_legal</code> = Footer: Legal. Default: <code>header</code> . Returns: <code>value</code> .
Destination <code>lld_destination</code>	text Required	Storefront path, approved HTTPS URL, mailto: or tel:. Never javascript:, a CMS admin URL or a file download token. Max characters: 500.
Open external link in new tab <code>lld_new_tab</code>	true_false Optional	Default: <code>0</code> .
Optional icon <code>lld_icon</code>	text Optional	Max characters: 12.
Dropdown content <code>lld_children_source</code>	select Optional	Choices: <code>none</code> = No children; <code>manual</code> = Child navigation records; <code>services</code> = Published services; <code>asset_categories</code> = Asset categories. Default: <code>none</code> . Returns: <code>value</code> .
Parent navigation record <code>lld_parent</code>	post_object Optional	Optional. Choose a top-level record in the same menu area with Manual children. One level only; no cycles. Records: <code>lld_nav_item</code> . Returns: <code>id</code> .

Product display extras

group_lld_product · Location: post_type = product · Public REST: enabled.

Optional product metadata only. WooCommerce owns title, description, short description, categories, images, tags, featured status, prices, discounts, ratings, stock and purchasing rules. ACF REST visibility does not automatically add these extras to the WooCommerce Store API.

Label / API path	Type / required	Definition and rules
What is included lld_includes	wysiwyg Optional	Optional additional product section; do not repeat the full WooCommerce description.
Audience / skill level lld_level	text Optional	For example: Beginner or All levels. Optional. Max characters: 160.
Course duration lld_duration	text Optional	Display text only, for example 10 weeks. No enrollment or entitlement logic. Max characters: 160.
Software / format requirements lld_compatibility	textarea Optional	Max characters: 1000.
Public license summary lld_license_summary	textarea Optional	Plain-language display copy; any licensed deliverable is handled separately. Max characters: 1000.

Search and sharing metadata

group_lld_seo · Location: post_type = page OR post_type = post OR post_type = lld_service OR post_type = lld_asset OR post_type = product · Public REST: enabled.

Applies to public pages, posts, services, assets and products. Use this as the initial metadata source; reconcile with any future SEO plugin instead of maintaining two competing sets of fields.

Label / API path	Type / required	Definition and rules
Search title lld_seo_title	text Optional	Optional; fallback is the page or product title plus brand. Max characters: 70.
Search description lld_meta_description	textarea Optional	Optional concise summary; not a ranking guarantee. Max characters: 180.
Request noindex lld_noindex	true_false Optional	An indexing preference only, not access control. The React metadata/prerender integration must apply it. Default: 0.

Social sharing image

Public object: acf.lld_share_image. Child fields inherit this group's visibility conditions.

Public presentation media only. Purchased files and signed download links do not belong here.

Label / API path	Type / required	Definition and rules
WordPress image lld_share_image.attachment	image Optional	Optional public preview image; REST value is an attachment ID. Returns: id. Public image: JPG, PNG, WebP or AVIF; max 5 MB. Server image support still applies.
Public image URL lld_share_image.public_url	url Optional	Optional HTTPS public image, including a public Firebase preview. If set, this takes precedence over the attachment.
Alternative text lld_share_image.alt	text Optional	Describe meaningful images; empty for purely decorative images. Max characters: 160.

Asset category display

group_lld_asset_category · Location: taxonomy = lld_asset_cat · Public REST: enabled.

Native term name and description supply category labels and menu descriptions. Native slug identifies each filter. Initial categories: Premium, Brandable, Local, AI-related, Marketing and Real Estate.

Label / API path	Type / required	Definition and rules
Category icon lld_icon	text Optional	Optional short emoji or symbol. Max characters: 12.
Category display order lld_order	number Optional	Default: 0. Minimum: 0. Increment: 1.

Native fields: avoid duplicate editing

Content	Use native WordPress / WooCommerce	ACF additions
Articles	Title, content, excerpt, published date, categories/tags and featured image. Native sticky flag or Home selected-post list for curation.	SEO overrides only. Derive reading time from content if added later.
FAQs	Title = question; content = answer; Order = display order.	Topic placement only.
Policy pages	Title and full approved text in the page editor.	Policy date, callout and shared page/SEO metadata.
Products / courses	Catalog text, price/sale dates/currency, stock, sold-individually rules, categories, tags, images, reviews and featured flag.	Includes, level, duration, compatibility and license summary only.
Services / assets	Title, excerpt, extended content, optional featured media, publication status and Order.	Offer-specific display details and optional WooCommerce product relationship.
Site links	Native record title and excerpt supply link label and description.	Destination, area, parent/source and new-tab choice.

For service/asset entries using a linked WooCommerce product, resolve price and purchasing eligibility from that product. Editorial quote fields and monthly wording do not implement payments, subscriptions, stock locks or ownership transfers.

Import and first content entry

- **1. Import the package.** In staging WordPress, open **ACF** → **Tools** → **Import Field Groups** (the import screen may also mention post types/taxonomies). Select `Longlife-Digital-ACF-Import.json` and click Import JSON. The file contains all 17 structures, with types before field groups. ACF can identify mixed exports by their keys. [3, 4]
- **2. Confirm the structures.** Expect six custom post types, Asset Categories, and ten Longlife Digital field groups. The import adds definitions only; no Pages, service records or settings values are created.
- **3. Create shared settings.** Under Site Settings, add a record titled Storefront with slug `storefront`. Set the confirmed support email and public website URL. Populate brand/social/footer copy. Enable announcements and signup copy only as their corresponding features are ready.
- **4. Create the pages.** Use the route table. On each page select its Storefront page key. Add approved title/introduction and applicable sections. Use the native editor for policy text. Publish only content intended for the public staging feed.
- **5. Populate collections.** Add approved services, FAQ records, content blocks, verified assets/categories and full blog posts. Add the navigation records below. Then select those records in the Home/About relationships.
- **6. Check REST output.** Open the sample public endpoints on the next page and confirm the `acf` object exists. Draft/private content requires authenticated preview work and will not be shown by the planned public content feed.
- **7. Connect React.** The storefront still needs content API services, mapping, loading states and component changes. This package does not activate those connections automatically.

Re-importing uses the same stable ACF keys and updates these definitions. Export any locally edited Longlife Digital groups first if you want to retain those changes; use this generator as the maintained source of truth. Import behavior has been checked against ACF's documented format and source; live import into your WordPress site has not been performed.

Initial navigation and public endpoints

Area	Label	Destination / children
Header	Home	/
Header	Services	/services · children_source=services
Header	Courses	/courses
Header	Domains	/domains · children_source=asset_categories
Header	Digital Products	/products
Header	About	/about
Header	Contact	/contact
Footer: Company	About / Blog / Shop	/about / /blog / /products; one record per link
Footer: Support	FAQ / Refund Policy / Privacy Policy / Terms / Contact	/faq / /refund-policy / /privacy-policy / /terms-of-service / /contact; one record per link
Footer: Legal	Refund Policy / Privacy Policy / Terms	Same policy routes; separate records allow their own order.

Use the existing staging origin with these read-only paths. Namespace paths below are examples, not credentials. [2, 5]

Purpose	GET path
Homepage content	/wp-json/wp/v2/pages?slug=home&acf_format=light
Public shared settings	/wp-json/wp/v2/lld-settings?slug=storefront&acf_format=light
Services / FAQs / blocks	/wp-json/wp/v2/lld-services?per_page=100 /wp-json/wp/v2/lld-faqs?per_page=100 /wp-json/wp/v2/lld-blocks?per_page=100
Assets / categories / navigation	/wp-json/wp/v2/lld-assets?per_page=100 /wp-json/wp/v2/lld-asset-categories?per_page=100 /wp-json/wp/v2/lld-navigation?per_page=100
Articles	/wp-json/wp/v2/posts?per_page=3&_embed
Existing product catalog	/wp-json/wc/store/v1/products · Different API namespace; product extras need a Store API extension/allowlisted backend mapping. [6]

Integration contract and acceptance

- Build a same-origin read-only content endpoint alongside /api/catalog, allowlisting resources and query parameters. Use TanStack Query for separate content queries with background refresh, cached success data, first-load skeletons and error/empty states.
- Fetch pages by stable slug; confirm page keys agree. Read one storefront settings record. Keep settings missing/error states distinct from intentionally empty optional fields; do not quietly insert old sample claims.
- Normalize ACF light-format scalar/ID values, resolve public media/relationships, follow pagination headers, sanitize HTML and validate link schemes. Never trust ACF required-field/UI settings as server authorization.
- Convert native WordPress links to approved storefront routes. Implement /blog/:slug and any desired service/asset detail routes before rendering links to them; these routes are not present in the current app.
- Map only the named public product extras into the WooCommerce Store API or a verified allowlisted backend response. ACF Show in REST API alone does not extend /wc/store/v1/products. Never expose arbitrary product meta or private download data. [6]
- Apply SEO fields to actual document metadata and sharing/prerender output. WordPress field entry alone does not change React page metadata. Configure staging noindex separately; noindex does not protect drafts.
- Editorial checks: approved support email, real service prices and asset ownership, genuine published articles, active coupon claims, accurate delivery wording, current approved policy dates and substantiated statistics.
- Migration checks: saving public content updates the correct React section; native policy lists/links retain formatting; field absence does not break layouts; hidden/deleted records disappear; keyboard/mobile navigation works; public responses contain no secrets or private fulfillment metadata.

Out of this package: customer accounts, contact/newsletter storage, form delivery, orders/payments/refunds, protected Firebase files, subscriber/customer PII, internal chatbot instructions and automatic domain transfer. Public copy for those features must describe what the implemented system actually supports.

Sources and document maintenance

Project-specific field names, grouping and defaults are design decisions based on the current codebase, not requirements imposed by ACF. References were checked for this edition; the package targets ACF Free with built-in post-type/taxonomy support.

- [1] ACF Free features and download: advancedcustomfields.com/download
- [2] ACF REST integration and response formats: [ACF REST documentation](#)
- [3] ACF import/export overview: [ACF frequently asked questions](#)
- [4] ACF import/post-type/taxonomy implementation: [Official ACF source](#)
- [5] WordPress Pages REST reference: [WordPress Pages API](#)
- [6] WooCommerce Store API extension: [Extending Store API responses](#)
- Local planning basis: docs/Longlife-Digital-CMS-Integration-Plan.md and the source components named in the inventory. This document does not treat source sample content as approved client content.

Maintain definitions in `scripts/generate-acf-reference.py`. Run it to regenerate the import JSON, editable Markdown and print HTML, then run `node scripts/render-acf-reference.mjs` to regenerate the PDF. Stable field names are the contract for the subsequent React integration.

Revision 1.0 — initial field model and import package. No live WordPress configuration or storefront behavior has been changed by generating this reference.