POLYTECHNIQUE MONTRÉAL
affiliée à l'Université de Montréal

A lightweight canonicalization engine in C

WILLIAM ZHANG
Département de Electrical Engineering

Mémoire présenté en vue de l'obtention du diplôme de *Maîtrise ès sciences appliquées*
Electrical Engineering

July 2026

© William Zhang, 2026.

POLYTECHNIQUE MONTRÉAL
affiliée à l'Université de Montréal

Ce mémoire intitulé :

A lightweight canonicalization engine in C

présenté par **William ZHANG**
en vue de l'obtention du diplôme de *Maîtrise ès sciences appliquées*
a été dûment accepté par le jury d'examen constitué de :

Danielle DUBOIS, présidente
Sébastien VIGOT, membre et directeur de recherche
Marie COUTURE, membre et codirectrice de recherche
Jean TREMBLAY, membre
Joseph BROWN, membre externe

DEDICATION

To all the past, present and future CVXPY contributors

ACKNOWLEDGEMENTS

Texte / Text.

RÉSUMÉ

Le résumé est un bref exposé du sujet traité, des objectifs visés, des hypothèses émises, des méthodes expérimentales utilisées et de l'analyse des résultats obtenus. On y présente également les principales conclusions de la recherche ainsi que ses applications éventuelles. En général, un résumé ne dépasse pas trois pages.

Le résumé doit donner une idée exacte du contenu du mémoire ou de la thèse. Ce ne peut pas être une simple énumération des parties du manuscrit. Le but est de présenter de façon précise et concise la nature, l'envergure de la recherche, les sujets traités, les questions de recherche ou les hypothèses soulevées, les méthodes utilisées, les principaux résultats ainsi que les conclusions retenues. Un résumé ne doit jamais comporter de références ou de figures.

ABSTRACT

Written in English, the abstract is a brief summary similar to the previous section (Résumé). However, this section is not a word for word translation of the abstract in French.

The abstract is a brief statement of the subject matter, objectives, research questions or hypotheses, experimental methods and analysis of results. It also presents the main research conclusions and their possible applications. In general, an abstract should not exceed three pages.

The abstract should provide an exact idea of the thesis or dissertation's contents and it cannot be a simple enumeration of the manuscript's parts. The goal is to precisely and concisely present the nature and scope of the research. An abstract should never include references or figures. If the thesis or the dissertation is in English, the résumé (French-language abstract) should come first followed by the abstract.

TABLE OF CONTENTS

DEDICATION iii

ACKNOWLEDGEMENTS iv

RÉSUMÉ v

ABSTRACT vi

LIST OF TABLES ix

LIST OF FIGURES x

LIST OF SYMBOLS AND ACRONYMS xii

CHAPTER 1 INTRODUCTION 1

CHAPTER 2 LITERATURE REVIEW 5
2.1 Canonicalization 6
2.2 Matrix stuffing 10
2.3 Coefficient extraction 12
2.4 Computing derivatives 14
2.5 Sparse matrices 17

CHAPTER 3 A lightweight canonicalization engine 20
3.1 Fundamental data structures 20
3.2 Atom implementations 21
3.3 Problem class and Parameter updates 29
3.4 CVXPY interface 29

CHAPTER 4 Benchmark results 31
4.1 Benchmark Setup 31
4.2 Results across the benchmark suite 32
4.3 Scaling with problem size 33
4.3.1 Parametric least squares 34
4.3.2 Factor-covariance portfolio 35
4.3.3 Energy-storage scheduling 36

CHAPTER 5 CONCLUSION 40

5.1 Summary of Works 40
5.2 Limitations 40
5.3 Future Research 40

REFERENCES 42

LIST OF TABLES

Table 4.1 Cold compilation time: a fresh problem formed and canonicalized from scratch, C engine versus CVXPY's `CPP` backend (22 runnable benchmarks). Ratio = C engine / `CPP`; values below 1 favor the engine. . . 32

Table 4.2 Parametric re-compilation time on a warm cached chain: parameter values are reassigned and the problem data rebuilt (the engine's target regime). Ratio = C engine / `CPP`. 33

LIST OF FIGURES

Figure 1.1 Example of expression tree for the function `log(|Ax-b|)`. 2

Figure 2.1 Users write functions in Python code that are restricted to be from the modeling language. Variables are labeled with a circle, and parameters with a square. 10

Figure 2.2 After the epigraph transformation reduction, the constraints and the objective are affine functions of the variables. 11

Figure 2.3 Matrix stuffing generates a 3D tensor for the constraint map. To depict these 3D tensors here, we leave the parameter values symbolic. Contrast this Figure with Fig. 2.2, which shows the operations being applied at each node. 13

Figure 2.4 Parameter map Q of the augmented objective $[c;\, d]$. The first n rows index the entries of the gradient c (one per post-canonicalization variable: t_1, t_2, and the n-block x); the final row indexes the constant offset d (zero here, since the canonicalized objective has no offset). Columns index the global augmented parameter vector $\tilde{\theta} = (g,\, \mu,\, 1)$. The g columns are zero because the objective does not depend on g, but they are part of $\tilde{\theta}$ globally and the analogous map for the constraints is non-zero in those columns. Multiplying Q by $\tilde{\theta}$ recovers $[c;\, d] = [1,\, \mu,\, 0,\, 0]^T$; the leading three entries match the c vector shown in Fig. 2.3. 14

Figure 2.5 Parameter map for $[A\, b]$ in the running example. The 3D tensor R has one 2D slice per entry of $\tilde{\theta} = (g_1, \ldots, g_m, \mu, 1)$. Block-row order matches Fig. 2.3(b): $x \in \mathbf{R}^n_+$; t_1 row of SOC_1; $Fx - g$ block of SOC_1; t_2 row of SOC_2; x block of SOC_2. Block-columns are the canonical-form variables $(t_1,\, t_2,\, x)$ followed by the b column. Summing $g_i \mathcal{R}[:, :, g_i]$ over i generates the $-g$ entry in b shown at the root of Fig. 2.3(b); the μ slice contributes nothing; the constant slice contributes everything else. 15

Figure 4.1 Parametric least squares, cold-start: full canonicalization from scratch versus problem size n ($m = 3n$). The C engine is $\approx 4\times$ faster across the whole range; both backends scale as $\sim n^{2.1}$. 35

Figure 4.2 Parametric least squares, warm-restart: rebuild after reassigning A and b. With no DPP tensor to reuse, `CPP` pays its full cold-start cost again, while the C engine only re-evaluates values on the cached sparsity pattern—a 10–12× speed-up. 36

Figure 4.3 Parametric least squares, peak process memory (resident-set high-water mark). The backends are within $\sim 30\%$ of each other; both grow as $\sim n^{1.6}$, dominated by the shared interpreter and the dense data matrix A. 37

Figure 4.4 Factor-covariance portfolio, cold-start versus number of assets n ($m = 100$ factors). The engine leads at small n but its advantage shrinks with size—it scales as $\sim n^{1.2}$ against CPP's $\sim n^{0.9}$, reaching near-parity by $n = 8000$. 38

Figure 4.5 Factor-covariance portfolio, warm-restart after reassigning γ and $L_{\max}$. `CPP` re-canonicalizes in essentially its cold-start time; the engine re-extracts on the cached pattern, a stable 12–13× speed-up across the range. 38

Figure 4.6 Factor-covariance portfolio, peak process memory. The backends are within $\sim 15\%$; both grow slowly ($\sim n^{0.35}$), reflecting the low-rank factor structure rather than a dense operator. 39

Figure 4.7 Energy-storage scheduling: scaling of cold-start, warm-restart, and peak memory with horizon length T (*placeholder curves; data pending the size-sweep run*). 39

LIST OF SYMBOLS AND ACRONYMS

AD	Automatic Differentiation
AML	Algebraic Modeling Language
ASA	Affine-Solver-Affine
CSC	Compressed Sparse Column
CSR	Compressed Sparse Row
DAG	Directed Acyclic Graph
DCP	Disciplined Convex Programming
DPP	Disciplined Parameterized Programming
LP	Linear Program
MOI	MathOptInterface
MPS	Mathematical Programming System
NLP	Nonlinear Program
QP	Quadratic Program
SOCP	Second-Order Cone Program
SDP	Semidefinite Program

CHAPTER 1 INTRODUCTION

Domain specific modeling languages for convex optimization such as CVXPY [1] and YALMIP [2] allow users to formulate optimization problems in a natural mathematical syntax. Through a process called *canonicalization*, these high-level problem descriptions are converted to a *standard conic form* used by many general-purpose convex solvers

$$\begin{array}{ll} \text{minimize} & c^T x + d \\ \text{subject to} & b - Ax \in K \end{array} \tag{1.1}$$

where $x \in \mathbf{R}^n$ is the decision variables, and the *problem data* are the matrix $A \in \mathbf{R}^{m \times n}$, the vectors $b \in \mathbf{R}^m$ and $c \in \mathbf{R}^n$, the scalar $d \in \mathbf{R}$ and the non-empty closed convex cone $K \subseteq \mathbf{R}^m$. Almost all of optimization practice can be divided into two groups, *modeling* and *solving*. The modeler's role is to formulate problems based on real-world business or engineering applications. The solver's role is to find an optimal solution given the data of a problem instance. Modeling languages serve as the communication bridge between these two groups. When improvements in solvers are made, modeling languages must adapt to allow users to benefit from them. Conversely, it is through natural formulations that modelers can express their requirements and help motivate solver improvements.

While the time taken to solve an optimization problem is often dominated by the solver, the time taken to *canonicalize* (or *compile*) a problem can also be significant, especially for large problems. In the case of CVXPY, the *compilation time* largely lies in *matrix stuffing*, the final step of canonicalization where symbolic expression trees are converted to explicit numerical matrices. Other modeling languages take different approaches to form the problem data, we review these *coefficient extraction* approaches in §2.3.

Atoms. Modeling languages for convex optimization are built on top of a library of functions which can be used to describe problems. These functions are known as *atoms* in CVXPY since they are the fundamental building blocks of the modeling language [3]. Atoms have known attributes such as curvature, monotonicity, and sign, for example, .

Expression trees. An expression is recursively defined as an atom evaluated at a *subexpression*. The subexpression can either be a variable, a parameter, or another expression. Similarly to atoms, expressions can also be classified by curvature, monotonicity, and sign which are determined by simple *composition rules* [4]. An expression tree whose atoms are

all affine is known as an *affine expression tree*.

Parameterized conic form. The data inputs in a problem instance can either be fixed or varying. In CVXPY, varying data are referred to as *parameters* and fixed data are referred to as *constants*. Parameters are useful for specifying a *family* of problems where the structure is fixed [5]. A *parameterized cone program* extends the conic form in (1.1) by letting the problem data depend on a parameter vector $\theta \in \mathbf{R}^p$:

$$\begin{array}{ll} \text{minimize} & c(\theta)^T x + d(\theta) \\ \text{subject to} & b(\theta) - A(\theta)x \in \mathcal{K}. \end{array} \tag{1.2}$$

When c, d, b and A are *affine with respect to* θ, we can represent the problem data parameter dependence as

$$\begin{bmatrix} c \\ d \end{bmatrix} = Q \cdot \tilde{\theta}, \qquad \text{and} \qquad [A \quad b] = \sum_{i=1}^{p+1} \mathcal{R}[:,:,i] \cdot \tilde{\theta}_i, \tag{1.3}$$

where $Q \in \mathbf{R}^{(n+1)\times(p+1)}$, $\mathcal{R} \in \mathbf{R}^{m\times(n+1)\times(p+1)}$ and $\tilde{\theta} = (\theta, 1) \in \mathbf{R}^{p+1}$. When $A(\theta)$ is sparse, we also require that its structure or *sparsity pattern* must be fixed throughout the different iterations. We refer to Q as the objective *parameter map*, $\mathcal{R}$ as the constraint parameter map, and $\tilde{\theta}$ as the extended parameter vector. The equation for the constraint map is known as a *tensor* product, a generalization of matrix-vector product in higher dimensions. This notation is required to output a constraint matrix from a three dimensional tensor.

Matrix stuffing. Although the original user specified problem formulation may contain nonlinearities, after conversion to standard form, the *canonicalized problem* will only contain affine expressions (with respect to both parameters and variables). Concretely, matrix stuffing refers to the task of forming the constraint parameter map, as the objective parameter map is a scalar special case of it. Once the parameter maps are formed, the parameter depen-




Figure 1.1 Example of expression tree for the function `log(|Ax-b|)`.

dence of the model is *cached* and doesn't rely on the expression tree representation anymore. Subsequent problem instances will only need to update θ and apply the maps to get the new problem data. We review current CVXPY matrix stuffing approaches and give examples of how the parameter maps are formed in §2.2.

Caching versus recompilation. Once a problem is parameterized, there are two broad strategies for handling repeated solves. The default approach in CVXPY, enabled by the DPP composition rules, forms the parameter maps once and *caches* them; subsequent solves merely apply the maps to a new θ. This is fast to re-solve but requires the problem to be DPP-compliant and stores the large three-dimensional tensor $\mathcal{R}$ in memory. The alternative, selected in CVXPY with `ignore_dpp=True`, skips the parameter maps entirely: parameters are treated as ordinary constants and the problem is re-canonicalized from scratch on every solve. This removes the DPP restriction and the tensor, but pays the full matrix-stuffing cost each time. Our method occupies the middle ground: like the `ignore_dpp` path it forms no parameter tensor and imposes no DPP restriction, but it caches the *sparsity pattern* of the problem data once and only refills the numerical values on each solve, recovering the amortized speed of the DPP path.

Contributions. We make the following contributions:

1. We propose an alternative method to matrix stuffing that doesn't rely on forming parameter maps. Instead, we treat matrix stuffing as a sparse Jacobian evaluation which naturally separates the symbolic structure of the Jacobian from its numerical values. This generalizes the `ignore_dpp` path—it applies to the same broad class of problems—while caching the sparsity pattern rather than re-deriving it on every solve.
2. We use the affine atoms from the `SparseDiffengine` package and its Python bindings to implement a canonicalization backend for CVXPY.
3. We benchmark our method against existing approaches and make improvements to CVXPY's codebase.

All code is open source and available at `https://github.com/cvxpy/cvxpy`.

Thesis outline. The rest of this thesis begins with a review of the literature on modeling languages, canonicalization, and matrix stuffing in §2. In §3 we describe a set of relevant affine atoms and their implementation in a sparse differentiation package. In §4 we present

benchmark results comparing our method to existing approaches. Finally, in §5 we summarize our contributions and discuss future improvements to the canonicalization backend.

CHAPTER 2 LITERATURE REVIEW

Solving an optimization problem on a computer requires translating the mathematical formulation into a data format that solvers can process. For linear programs, this means constructing the constraint matrix A, the right-hand side vector b, and the objective coefficients c that define the *standard form*,

$$\begin{aligned} \text{minimize} \quad & c^T x \\ \text{subject to} \quad & Ax \leq b, \\ & x \geq 0. \end{aligned} \tag{2.1}$$

Manual encoding In the early days of linear programming, analysts manually computed and encoded each coefficient onto punch cards. This process was tedious, error-prone and became impractical as linear programming found more and more applications in large-scale industrial problems [6].

MPS format IBM's Mathematical Programming System (MPS) file format, developed in the 1960s, established a standardized file format for representing linear programs [7]. The MPS format uses fixed-width fields designed for 80-column punch cards, with sections for rows, columns, and coefficients. William Orchard-Hays [8] provides a comprehensive history of these early mathematical programming systems, tracing their development from 1952 at RAND Corporation through their widespread adoption on mainframe computers in the late 1960s.

Matrix generators To automate the creation of MPS files, *matrix generators* emerged in the late 1960s; they are procedural programs that compute the problem coefficients through explicit loops and output the results in MPS format [9]. Commercial systems such as `MaGen` [10], `GAMMA` [11], and `DATAFORM` [12] were among the first matrix generators which were used in various domains.

A modern approach Modelers naturally think in terms of sets, indices, and algebraic expressions, not in terms of individual matrix entries. Matrix generators simplified the encoding process but still required modelers to translate their mathematical formulations into procedural code that explicitly constructs the coefficient matrices. This suggests that the gap between the modeler's representation of the problem and the solver's required format

hadn't been resolved yet [6].

Algebraic modeling languages In the late 1970s, *algebraic modeling languages* emerged as formal languages designed to accept problem descriptions that closely mirror standard mathematical notation [13]. By working directly with the modeler's representation, these languages simplify verification, modification, and communication. In the late 1980s and early 1990s, commercial algebraic modeling systems such as GAMS [14], AIMMS [15] and AMPL [16] became widely adopted in both academia and industry (and they are still widely used today).

Embedded modeling languages In the late 2000s and early 2010s, modeling languages emerged that are embedded in general-purpose programming languages (in contrast with standalone systems like AMPL and GAMS). Examples include YALMIP [2] in MATLAB, Pyomo [17, 18] in Python, JuMP [19] in Julia, and CasADi [20] in C++.

Disciplined convex programming In addition, there are domain specific languages that implement *disciplined convex programming* (DCP), a set of composition rules that can automatically verify convexity [3, 4]. These include CVX [21] in MATLAB, CVXPY [1, 22] in Python, and Convex.jl [23] in Julia.

Structure of the chapter The sections on canonicalization and matrix stuffing will be about CVXPY, the Python implementation of DCP. The reasons are twofold: it is the most updated implementation which still has an active community and the work of this thesis aims to be integrated in CVXPY. In section 2.3, we present the embedded modeling language JuMP and one of the original algebraic languages AMPL. In doing so, we also compare the differences with approaches taken in CVXPY. Both modeling languages treat the conic problem data as a form a sparse Jacobian computation so we review approaches on computing derivatives in 2.4. Finally, all modeling languages use sparse matrix formats to store the problem data matrices, they are incredibly useful and we review them in 2.5.

2.1 Canonicalization

CVXPY. CVXPY is a domain-specific language for convex optimization embedded in Python, that was originally developed by Steven Diamond and Stephen Boyd at Stanford University [1]. Akshay Agrawal later redesigned the rewriting system in CVXPY [22], which

enabled support for other disciplined languages [24–26], and the project has since grown through contributions from many others [27].

Functional form. When a user specifies a CVXPY problem, it is usually in a "functional" form

$$\begin{array}{ll} \text{minimize} & f_0(x;\theta) \\ \text{subject to} & f_i(x;\theta) \leq g_i(x;\theta),\ i = 1,\ldots,m_1, \\ & h_i(x;\theta) = j_i(x;\theta),\ i = 1,\ldots,m_2, \end{array} \tag{2.2}$$

with variable $x \in \mathbf{R}^n$ and parameter vector $\theta \in \mathbf{R}^p$ [28]. For a given value of θ we refer to (2.2) as a problem instance, otherwise for general values of θ it defines a problem family. Each function in (2.2) is internally represented as an expression tree.

Disciplined convex programming. When all f_i are convex, all g_i are concave and all h_i and j_i are both affine, the functional form defines a convex optimization problem. To verify that the problem is convex, CVXPY uses the DCP composition rules to classify the curvature of functions. Once all functions are classified, a problem is *DCP-compliant* if its functions satisfy the curvatures of a convex problem. Otherwise, if certain curvatures are incorrect (*i.e.* f_0 is concave) or unknown, CVXPY will raise an error and terminate.

Composition rules. The expression $h(f_1(x), f_2(x), \ldots, f_k(x))$ is convex when h is convex and for each $i \in \{1,\ldots,k\}$ the following holds:

- h is non-decreasing in argument i and f_i is convex, or
- h is non-increasing in argument i and f_i is concave, or
- f_i is affine.

The same results hold for concave functions by swapping convex and concave. Affine expressions require h and all of its arguments to be affine [3].

DPP composition rules. *Disciplined parameterized programming* (DPP) is an extension of DCP which guarantees an affine parameter dependence in the problem data. A problem is *DPP-compliant* if it satisfies the DPP composition rules. The rules essentially disallow products of expressions involving parameters and can be referred to in [26]. DPP-compliance is what makes the parameter maps of §2.2 well defined: because the problem data depend affinely on θ, the dependence can be captured once as the tensor $\mathcal{R}$ and reused across

solves. When a problem violates the DPP rules—or when the user opts out by passing `ignore_dpp=True`—CVXPY abandons this caching and instead treats parameters as ordinary constants, re-canonicalizing the problem from scratch on every solve.

Solver standard form. After a problem is verified to be DPP-compliant, CVXPY will convert the functional form problem to a target solver's standard form. CVXPY supports solvers for quadratic programming (such as OSQP and HiGHS), conic programming (such as ECOS), and conic quadratic programming (such as Mosek and Clarabel). The conic quadratic form is the most general of these, but is not a major generalization of the cone form: any conic quadratic program can be reduced to an equivalent cone program by linearizing the quadratic objective via the second-order cone, at the cost of one extra variable and one extra constraint. We will focus on the conic form throughout the thesis.

Reductions. Canonicalization converts a DPP-compliant model into a cone program via a sequence of reductions [22].

Maximization problems. A first example of a reduction is one which takes a maximization problem and converts it into a minimization problem by flipping the sign of the objective. The reverse transformation simply undoes the sign flipping and has no effect on the actual solution of the problem. In CVXPY, this reduction is conveniently called `FlipObjective`.

Variable bounds. A second example is variable attributes such as numerical bounds or `nonneg`. During canonicalization, CVXPY will also verify if the target solver supports bounds natively. If it does, CVXPY can pass them directly to solvers, otherwise they will get converted into explicit constraints. The reverse transformation for this reduction is to take the dual values corresponding to the explicit constraints ($x \geq 0$) and setting them to be equal to the variable bound's dual values. In CVXPY, this reduction is part of a greater set of general attribute constraints and is called `CvxAttr2Constr`.

Epigraph transformation. Each convex atom has a *canonicalization* that replaces it with an epigraph variable (for concave atoms it is a *hypograph* variable) and auxiliary constraints of the form $f(x, t, \theta) \in \mathcal{K}$ where t is the epigraph variable, f is affine in the variables (x, t) for fixed parameters θ, and $\mathcal{K}$ is a convex cone. This process was presented initially in [29]. One illustrative canonicalization replaces the `norm2` expressions in the objective with a new epigraph variable t_i and imposes the epigraph constraint known as a *second-order* cone

constraint

$$(t_i, z_i) \in \mathcal{K}_{\text{soc}}. \tag{2.3}$$

Nondifferentiability. A subtle benefit of the epigraph transformation is that it removes any need for the user's atoms to be differentiable. The textbook conic standard form [28] is often stated for twice-differentiable functions, but canonicalization never differentiates an atom: each atom is simply replaced by its epigraph variable and a cone constraint. The absolute value $|x|$ is the canonical example—it is nondifferentiable at the origin, yet its epigraph $\{(x,t) : |x| \leq t\}$ is exactly the pair of linear inequalities $-t \leq x \leq t$. Convexity, not smoothness, is what canonicalization requires.

Example of canonicalization. To show a concrete example of canonicalization, we consider a simple fitting with regularization problem

$$\begin{array}{ll} \text{minimize} & \|Fx - g\|_2 + \mu\|x\|_2 \\ \text{subject to} & x \succeq 0 \end{array} \tag{2.4}$$


with variable $x \in \mathbf{R}^n$, fixed problem data $F \in \mathbf{R}^{m\times n}$, and parameters $g \in \mathbf{R}^m$ and $\mu \geq 0$. The problem formulation in CVXPY code is

```
import cvxpy as cp
import numpy as np
F = np.random.randn(m, n)
x = cp.Variable(n)
g = cp.Parameter(m)
mu = cp.Parameter(nonneg=True)
objective = cp.Minimize(cp.norm(F @ x - g) + mu * cp.norm(x))
prob = cp.Problem(objective, [x >= 0])
```


where we also use the numerical computation library `NumPy` [30] for the data arrays. The expression tree representation of the problem is shown in 2.1.

Conic form expression tree. After applying the reductions, the problem has been *canonicalized* to

$$\begin{array}{ll} \text{minimize} & t_1 + \mu t_2 \\ \text{subject to} & x \in \mathbf{R}^n_+ \\ & (t_1, Fx - g) \in \mathcal{K}_{\text{soc},m+1} \\ & (t_2, x) \in \mathcal{K}_{\text{soc},n+1} \end{array} \tag{2.5}$$



(a) Abstract syntax tree of objective



(b) Abstract syntax tree of constraints


Figure 2.1 Users write functions in Python code that are restricted to be from the modeling language. Variables are labeled with a circle, and parameters with a square.

where t_1 and t_2 are new epigraph variables, and the cone $\mathcal{K}$ from 1.1 is the product $\mathbf{R}^n_+ \times \mathcal{K}_{\text{soc},m+1} \times \mathcal{K}_{\text{soc},n+1}$. In the next section, we explain how the symbolic affine expression trees in 2.2 get converted into the parameter maps defined in 1.3.

References. Michael Grant's papers and PhD thesis on CVX and DCP are the standard references on verifying convexity and canonicalization [3, 4, 29]. The paper by Chu et al. [31] gives another perspective of canonicalization through the *relaxed smith form*, it was used extensively to learn the concept initially. The paper by Agrawal et al. [22] on rewriting systems is a great reference for understanding reductions and the core concepts behind CVXPY. Finally, the `CVXPY` documentation and the Mosek modeling cookbook can be used as complementary references for epigraph reformulations and general modeling principles.

2.2 Matrix stuffing

In this section, we explain how to form the parameter maps from a set of affine expression trees. In doing so, we also cover fundamental data structures and design choices of these backends which can later be contrasted with the method proposed in 3. Historically, the implementations of matrix stuffing have been referred to as *canonicalization backends*, and there has been many versions over the years. We will focus on `cvxcore`, one of the original implementations in `C++`, and `SciPy`, an improved Python version which relies on the sparse



(a) Expression tree of the objective

(b) Expression tree of the constraints

Figure 2.2 After the epigraph transformation reduction, the constraints and the objective are affine functions of the variables.

matrix library with the same name.

`Tensor` object. The word *tensor* is borrowed loosely here; we do not require the multilinear machinery of physics or differential geometry. We consider a `Tensor` as a three-dimensional array which represents a sparse linear mapping from a parameter vector to the constraint matrix (as shown in 1.3). The three indices of a `Tensor` are rows for constraints, columns for variables, and parameter offsets for parameters.

Recursive walk. Fundamentally, matrix stuffing is relatively simple; it requires a single depth-first walk of a set of affine expression trees, where each tree represents a potentially vector-valued constraint. Since the process is recursive, every node of an expression tree will have an equivalent `Tensor`, and the final output (the `Tensor` at the root node) will give the constraint parameter map $\mathcal{R}$.

Local vs. Global problem data. All modeling languages for optimization must at least do one thing correctly: abstract away the task of placing *local* tensors (or its equivalent) at the expression level (where typically a single variable appears) towards a *global* tensor at the problem level (where many more variables could be present). In fact, once we are able to compute the local tensor for all expressions of interest, getting the global tensor simply comes down to combining the local tensors and applying appropriate row and column *offsets*.

Column and parameter offsets. Every variable is associated with an offset which indicates its index in the global variable vector. In expressions which involve only a subset

of variables, we must make use of these offsets to correctly place the problem data. We also clarify that a single variable can have multiple entries or values, therefore when we say number of variables, we refer to the number of variable objects not the number of entries of the variable (which we refer to as its *size*).

Row offsets. When an optimization model contains multiple constraints (this refers to constraint objects), we must also be able to correctly place the problem data. The offsets for constraints are used to keep track of the *ordering* of the constraints. They are also used to correctly place the problem data but on a different axis than variables.

`TensorView` object. The fundamental data structure in the backend is a so-called `TensorView`, a nested mapping that indexes a tensor by both variable and parameter offsets at once. This lets the recursive walk accumulate, for each node, the problem-data contribution of every (variable, parameter) pair it touches, which is exactly what the local-to-global assembly requires. We do not dwell on its internals here, since the method we propose in 3 dispenses with this representation entirely.

Tensor Representation.

References.

2.3 Coefficient extraction


`JuMP`. JuMP is an algebraic modeling language embedded in Julia, originally developed in 2012 by Iain Dunning, Joey Huchette, and Miles Lubin at the MIT Operations Research Center [19, 32]. It is now being developed and maintained full-time by Oscar Dowson.

`MathOptInterface`


`CasADi`. [20]

`AMPL`. [16]

References.



(a) Matrix stuffing of the objective



(b) Matrix Stuffing tree

Figure 2.3 Matrix stuffing generates a 3D tensor for the constraint map. To depict these 3D tensors here, we leave the parameter values symbolic. Contrast this Figure with Fig. 2.2, which shows the operations being applied at each node.

$$Q = \begin{array}{c} \\ t_1 \\ t_2 \\ x \\ d \end{array} \begin{array}{c} \begin{array}{ccc} g^T & \mu & 1 \end{array} \\ \begin{bmatrix} 0 \cdots 0 & 0 & 1 \\ 0 \cdots 0 & 1 & 0 \\ 0 \cdots 0 & 0 & 0 \\ 0 \cdots 0 & 0 & 0 \end{bmatrix} \end{array} \qquad \begin{bmatrix} c \\ d \end{bmatrix} = Q\,\tilde{\theta} = \begin{bmatrix} 1 \\ \mu \\ 0 \\ 0 \end{bmatrix}$$

Figure 2.4 Parameter map Q of the augmented objective $[c;\, d]$. The first n rows index the entries of the gradient c (one per post-canonicalization variable: t_1, t_2, and the n-block x); the final row indexes the constant offset d (zero here, since the canonicalized objective has no offset). Columns index the global augmented parameter vector $\tilde{\theta} = (g,\, \mu,\, 1)$. The g columns are zero because the objective does not depend on g, but they are part of $\tilde{\theta}$ globally and the analogous map for the constraints is non-zero in those columns. Multiplying Q by $\tilde{\theta}$ recovers $[c;\, d] = [1,\, \mu,\, 0,\, 0]^T$; the leading three entries match the c vector shown in Fig. 2.3.

2.4 Computing derivatives

Finding the rate of change or the *derivative* of a function at a particular point is a fundamental concept in calculus that was discovered by Leibniz and Newton in the late 1600s. Since then, although the underlying theory has practically remained the same, various methods have been developed to efficiently compute derivatives in different contexts and applications. More recently, the rise of machine learning and deep learning brought renewed interest in this age-old problem through a new application of derivatives in training *neural networks*, it is known as the *backward pass* or *backpropagation* [33, 34]. Some theorists will claim that backpropagation is little more than a clever application of the *chain rule* [35], but the large scale of modern workloads has led to the development of incredible software tools and implementation techniques which are interesting in their own right. This section provides an overview of these new tools and techniques, with a particular emphasis on *algorithmic differentiation* (AD) and its applications to computing sparse Jacobians [36].

Numerical differentiation. Other than computing derivatives by hand, the simplest method is to use *numerical differentiation*, which approximates the derivative of a function at a point by evaluating the function at nearby points using a *finite difference* formula similar to either

$$f'(x) \approx \frac{f(x+h) - f(x)}{h}, \tag{2.6}$$

or

$$f'(x) \approx \frac{f(x+h) - f(x-h)}{2h}, \tag{2.7}$$

$$\mathcal{R}[:,:,g_i] = \begin{bmatrix} 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & -e_i \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \end{bmatrix} \qquad \mathcal{R}[:,:,\mu] = \begin{bmatrix} 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \end{bmatrix}$$

(a) Parameter slices. Each $\mathcal{R}[:,:,g_i]$ $(i = 1, \ldots, m)$ places a single -1 in the b column at the i-th row of the $Fx - g$ block (denoted $-e_i$). $\mathcal{R}[:,:,\mu] = 0$ because μ does not appear in any constraint.

$$\mathcal{R}[:,:,1] = \begin{bmatrix} 0 & 0 & -I & 0 \\ -1 & 0 & 0 & 0 \\ 0 & 0 & -F & 0 \\ 0 & -1 & 0 & 0 \\ 0 & 0 & -I & 0 \end{bmatrix}$$

(b) Constant slice. Holds the fixed structure: $-I$ blocks for the variable bound and SOC_2 rows, -1's for the epigraph variables, and $-F$ for the Fx block.

Figure 2.5 Parameter map for $[A\, b]$ in the running example. The 3D tensor R has one 2D slice per entry of $\tilde{\theta} = (g_1, \ldots, g_m, \mu, 1)$. Block-row order matches Fig. 2.3(b): $x \in \mathbf{R}^n_+$; t_1 row of SOC_1; $Fx - g$ block of SOC_1; t_2 row of SOC_2; x block of SOC_2. Block-columns are the canonical-form variables (t_1, t_2, x) followed by the b column. Summing $g_i\mathcal{R}[:,:,g_i]$ over i generates the $-g$ entry in b shown at the root of Fig. 2.3(b); the μ slice contributes nothing; the constant slice contributes everything else.

where h is a small step size. Although this approach is straightforward to implement and can achieve reasonable accuracy, there are important downsides to consider. First, it requires a linear number of function evaluations with respect to the number of input variables, which is expensive for high-dimensional functions. Second, it can easily lead to *truncation errors* (when h is too large) or *rounding errors* (when h is too small) in the computed derivative if the step size is not carefully chosen [37]. Despite these downsides, numerical differentiation is still widely used in practice, especially for verifying the correctness of derivative computations (also known as a *derivative checker*) [38].

Symbolic differentiation. Mathematical expressions can be manipulated automatically using simple derivative rules of calculus, such as the product and sum rule. This *symbolic* approach to differentiation is used in computer algebra systems such as Mathematica [39] and Maple [40] as well as the SymPy library in Python [41]. Unlike its numerical counterpart, symbolic differentiation tools compute derivatives as closed-form expressions, which can be simplified and evaluated at any arbitrary point. These closed-form expressions are particu-

larly useful for deriving analytic solutions of optimization problems, and can be further used in mathematical proofs and analyses.

However, a naive implementation of symbolic differentiation can easily lead to exponentially large symbolic expressions, which is impractical and inefficient for many problems [36]. Interestingly, when intermediate expressions are stored as *common subexpressions*, and the expression is represented with a *directed acyclic graph* (DAG) instead of a tree, symbolic differentiation performs the same set of operations as *reverse mode differentiation* [42].

Algorithmic differentiation. There is a lot of confusion on the terminology surrounding the various methods for computing derivatives; *automatic differentiation* and *computational differentiation* are often used to describe the field, but we will instead refer to it as *algorithmic differentiation* since it emphasizes the algorithms behind the different implementations rather than a particular method (it is also the convention in the seminal book by Griewank and Walther [36]). Fundamentally, AD is a non-standard interpretation of a computer program: it augments the *evaluation trace* of a function (the sequence of floating point values calculated during the execution) with calculations of its derivatives [43]. This trace can be represented as a *computational graph*, a DAG in which each node corresponds to an elementary operation with known derivatives. Combining the derivatives of these operations throughout the graph using the chain rule gives the derivative of the overall function [36]. The computational graph is the central data structure of AD; the various *modes* of AD correspond to different ways elementary derivatives are accumulated on this graph.

Forward mode AD. The method of propagating tangents forward through the computational graph is known as *forward mode* AD. A single forward pass simultaneously computes the value and derivative of every intermediate variable with respect to a single input variable, giving the sensitivity of all outputs to that input. The cost of a forward pass is a small constant factor of the cost of evaluating the original function, since each elementary operation is augmented with at most a few additional arithmetic operations for the derivatives. However, one downside of forward mode AD is that the number of forward passes scales linearly with the number of input variables, which is impractical for certain functions (which have many input variables and very few output variables).

Reverse mode AD. In contrast to forward mode, *reverse mode* AD propagates adjoints backward through the computational graph. It first requires a forward pass to compute and store the value of every intermediate variable, and it then performs a reverse pass to compute the sensitivities of a single output variable with respect to all input variables. The cost of

a reverse pass is also a small constant factor of the cost of evaluating the original function, but the number of passes required now scales linearly with the number of output variables rather than the number of input variables. This makes reverse mode AD particularly efficient for computing gradients of scalar-valued functions, making it the default method for modern machine learning libraries such as Jax [44], Pytorch [45], and Tensorflow [46].

Advantages of AD. [47].

Jacobian and Hessian computation.

Sparse Jacobian computation. graph coloring, cross-country elimination, vertex elimination, jacobian accumulation, etc. maybe mention graph coloring here?

[48] presents a code generator for operations on sparse data.

[49] presents a similar method for computing sparse Hessians with graph coloring. [50] is a survey of graph coloring methods for computing sparse Jacobians and Hessians.

Differentiation packages. mention ADOL-C and CppAD for C++. mention AMPL and CasADi for optimization. and also mention that they were covered above in the coeff extraction section.

References. The book by Griewank and Walther [36] is a comprehensive reference on the theory and practice of automatic differentiation. The book by Naumann [47] is another great reference that focuses on the implementation of AD in software, with a particular emphasis on the use of operator overloading and source code transformation techniques. [43] is an excellent and relatively up-to-date survey of the various methods for automatic differentiation in machine learning.

2.5 Sparse matrices

Matrices that contain many number of zero entries are known as *sparse matrices*. The simplest sparse matrix data structure is the *coordinate* or *triplet* format. It consists of two integer index arrays `rows` and `cols` and a floating point value array `vals` of length equal to the number of *nonzero entries* in the matrix.

For example, the matrix

$$\begin{bmatrix} 0 & 0 & 3.2 & 0 \\ 4.1 & 1.8 & 0 & 2.2 \\ 0 & 2.8 & 0 & 3.4 \end{bmatrix} \tag{2.8}$$

can be represented in coordinate format as

```
int    rows[] = {0,  1,   1,   1,   2,   2};
int    cols[] = {2,  0,   1,   3,   1,   3};
double vals[] = {3.2, 4.1, 1.8, 2.2, 2.8, 3.4};
```

where we use zero-based indexing and array declaration notation from the C programming language [51]. The coordinate format is the easiest to understand and form, but it is not effective for most operations on sparse matrices; the *compressed sparse row* or CSR format is commonly used instead.

Compressed sparse row format. The CSR format differs from the coordinate format in that it replaces the `rows` array with a row pointer array `idxptr` of length equal to the number of rows plus one. The row pointer array indicates the starting index of each row in the `cols` arrays. For example, the matrix in (2.8) can be represented in CSR format as

```
int  idxptr[] = {0,  1,              4,        6};
int   cols[] = {2,  0,   1,   3,   1,   3};
double vals[] = {3.2, 4.1, 1.8, 2.2, 2.8, 3.4};
```

where we deliberately format `idxptr` to align with the start of each row in the `cols` arrays. The benefits of the CSR format are more than a reduced size of the `idxptr` array compared to the `rows` array. In the CSR format, accessing a row takes constant time and is very *cache-friendly* since the nonzero entries are stored contiguously in memory. For this reason, the CSR format is the default for *iterative methods* to solve sparse linear systems [52].

Compressed sparse column format. However, one downside of the CSR format is that accessing a column is much more difficult; one would need to look at every row to find the nonzero entries in a column. An alternative format is the *compressed sparse column* or CSC format, which swaps the role of the `idxptr` array to refer to column indices instead. In contrast to iterative methods, the CSC format is the preferred format for *direct methods* to solve sparse linear systems [53].

Transpose.

Which format to use?

Other formats. The coordinate, CSR and CSC formats are the most widely used sparse matrix formats, but many others exist for different specialized use cases. The scientific Python sparse library `scipy.sparse` [54] allows users to form other types of sparse matrices such as the list of lists (LIL) matrix, the dictionary of keys (DOK) matrix, and the block-sparse row (BSR) matrix.

Sparse matrix struct in C. A CSR matrix struct in C looks like this.

```
typedef struct CSR_Matrix {
    int *p;      /* row pointers, size m+1 */
    int *i;      /* column indices, size nnz */
    double *x;   /* values, size nnz       */
    int m, n, nnz;
} CSR_Matrix;
```

References. Although the work in this thesis does not necessarily revolve around solving sparse linear systems, a lot of techniques for manipulating sparse matrices we use were inspired by the literature. In particular, the book by Davis [53] was used extensively throughout the development of our methods. The book by Duff [55] is another great reference to learn more about the history and development of sparse matrix algorithms. Another reference is the review article by the "gang of four" (Gill, Murray, Saunders and Wright) from the Systems Optimization Laboratory at Stanford University [56] which provides a high-level overview of various applications of sparse matrix methods in optimization.

CHAPTER 3 A lightweight canonicalization engine

In this chapter we present a minimal implementation of a subset of affine atoms in the `SparseDiffEngine` package, and show how they can be used to compute the sparse constant Jacobian of a set of affine expressions. At this point, we are given a *canonicalized* problem in standard form, after the canonicalization process described in §2.1. The content of this chapter has many similarities to §2.2, since both serve the same purpose of forming the problem data. The structure of the chapter is as follows: in §3.1 we describe basic data structures in the engine which will be used throughout the atom implementations described in §3.2, and finally, in §3.4 we present a high level problem class interface which can easily be used in CVXPY. We also recommend reading §2.5 before reading this chapter, since it covers the basics of sparse matrices and their data structures.

3.1 Fundamental data structures

The main data structure in the engine is the expression struct.

```
typedef struct expr {
    int   d1, d2, size; /* shape (d1 x d2) and size = d1*d2 */
    int   n_vars;       /* total number of variables     */
    int   var_id;       /* offset into u, or NOT_A_VARIABLE */

    struct expr *left;  /* left child (NULL for leaves)  */
    struct expr *right; /* right child (NULL for leaves) */

    double    *value;   /* forward-pass output, size entries */
    CSR_Matrix *jacobian; /* size x n_vars sparse Jacobian */

    forward_fn     forward;
    jacobian_init_fn jacobian_init_impl;
    eval_jacobian_fn eval_jacobian;
} expr;
```

every expression node has a shape (d1 x d2) and a size (d1*d2), and also two pointers to its left and right children. It will also have a pointer to its value, which is the output of the forward pass, and a pointer to its Jacobian, which is a CSR matrix. Every expression must also implement three functions: a forward function, a Jacobian initialization function, and a

Jacobian evaluation function.

Leaf nodes. The two leaf nodes are variables and parameters. They are the fundamental building blocks of the expression tree.

3.2 Atom implementations

We will now show the implementation of atoms in the engine. The semantics of an atom is as follows, it takes one or two expressions as input, and produces an output expression corresponding to the result of the operation. Every atom implementation below will first show the basic CVXPY code, and then show how it is implemented in the engine.

Helpers and definitions. We first import the necessary libraries and define basic variables and constants which will be used throughout the implementation.

```
import cvxpy as cp
import numpy as np
import scipy.sparse as sp

x = cp.Variable(n1)
y = cp.Variable(n2)
a = cp.Parameter(n1)
b = cp.Parameter(n2)
```

Addition. The addition atom (also commonly referred to as `add`) takes two expressions and sums them together elementwise. The CVXPY code is as follows (note that Python's operator overloading for `+` will automatically form an `add` atom).

```
add_expr = cp.add(x, y)
```

In the engine the implementation is as follows.

```
static void forward(expr *node, const double *u)
{   /* forward pass for children */
    node->left->forward(node->left, u);
    node->right->forward(node->right, u);
    for (int i = 0; i < node->size; i++)
    {
        node->value[i] = node->left->value[i] + node->right->value[i];
```

```
    }
}

static void jacobian_init_impl(expr *node)
{
    /* initialize children's jacobians */
    jacobian_init(node->left);
    jacobian_init(node->right);

    /* we never have to store more than the sum of children's nnz */
    int nnz_max = node->left->jacobian->nnz + node->right->jacobian->nnz;
    node->jacobian = new_csr_matrix(node->size, node->n_vars, nnz_max);

    /* fill sparsity pattern */
    sum_csr_alloc();
}

static void eval_jacobian(expr *node)
{
    /* evaluate children's jacobians */
    node->left->eval_jacobian(node->left);
    node->right->eval_jacobian(node->right);

    /* sum children's jacobians */
    sum_csr_fill_values();
}
```

Negation. The negation atom takes a single expression and negates it elementwise.

Transpose. The transpose atom takes a single expression and transposes it. In CVXPY the code is as follows (it can also be written as `x.T`).

```
transpose_expr = cp.transpose(x)
```

```
// Forward pass for transpose atom
static void forward(expr *node, const double *u)
{
    /* forward pass for child */
    node->left->forward(node->left, u);
```

```
    /* local forward pass */
    int d1 = node->d1;
    int d2 = node->d2;
    double *X = node->left->value;
    double *XT = node->value;
    for (int i = 0; i < d1; ++i)
    {
        for (int j = 0; j < d2; ++j)
        {
            XT[j * d1 + i] = X[i * d2 + j];
        }
    }
}
```

explain the Jacobian init and eval for transpose, which is just a permutation of the Jacobian entries.

Horizontal stack. The horizontal stack atom takes two expressions and concatenates them horizontally. In CVXPY the code is as follows, and just like `NumPy`, it requires the input expressions to have the same number of rows.

```
hstack_expr = cp.hstack([x, y])
```

```
static void forward(expr *node, const double *u)
{
    hstack_expr *hnode = (hstack_expr *) node;

    /* children's forward passes */
    for (int i = 0; i < hnode->n_args; i++)
    {
        hnode->args[i]->forward(hnode->args[i], u);
    }

    /* concatenate values horizontally */
    int offset = 0;
    for (int i = 0; i < hnode->n_args; i++)
    {
        expr *child = hnode->args[i];
```

```
        memcpy(node->value + offset, child->value, child->size * sizeof(double
            ));
        offset += child->size;
    }
}

static void eval_jacobian(expr *node)
{
    hstack_expr *hnode = (hstack_expr *) node;
    CSR_Matrix *A = node->jacobian;
    A->nnz = 0;

    for (int i = 0; i < hnode->n_args; i++)
    {
        expr *child = hnode->args[i];
        child->eval_jacobian(child);

        /* copy values */
        memcpy(A->x + A->nnz, child->jacobian->x,
               child->jacobian->nnz * sizeof(double));
        A->nnz += child->jacobian->nnz;
    }
}
```

Vertical stack. The vertical stack atom takes two expressions and concatenates them vertically. In CVXPY the code is as follows, and just like `NumPy`, it requires the input expressions to have the same number of columns.

```
vstack_expr = cp.vstack([x, y])
```

In the engine the implementation uses the transpose and horizontal stack atoms, since we can write `vstack([x, y]) = transpose(hstack(transpose(x), transpose(y)))`.

More generally, we have the following equivalence:

```
vstack([A, B]) == transpose(hstack([transpose(A), transpose(B)]))
```

```
index_expr = x[0:3]
```

```
static void forward(expr *node, const double *u)
```

```
{
    expr *x = node->left;
    index_expr *idx = (index_expr *) node;

    /* child's forward pass */
    x->forward(x, u);

    /* gather selected elements */
    for (int i = 0; i < idx->n_idxs; i++)
    {
        node->value[i] = x->value[idx->indices[i]];
    }
}
```

mention that the Jacobian is a subset of the child's Jacobian, and we can fill it in by copying the relevant rows.

```
sum_expr = cp.sum(x)

static void forward(expr *node, const double *u)
{
    /* child's forward pass */
    x->forward(x, u);
    sum = 0.0;
    end = x->d1 * x->d2;
    /* sum all elements */
    for (i = 0; i < end; i++)
    {
        sum += x->value[i];
    }
    node->value[0] = sum;
}
```

```
elemwise_mult_expr = cp.multiply(x, y)

static void forward(expr *node, const double *u)
```

```
{
    expr *child = node->left;
    vector_mult_expr *vnode = (vector_mult_expr *) node;

    /* call forward for param_source expr tree (this extra logic is needed
       in case the parameter is a broadcast or promote node which needs to
          refresh
       its values) */
    if (vnode->base.needs_parameter_refresh)
    {
        vnode->param_source->forward(vnode->param_source, NULL);
        vnode->base.needs_parameter_refresh = false;
    }

    const double *a = vnode->param_source->value;

    /* child's forward pass */
    child->forward(child, u);

    /* local forward pass: elementwise multiply by a */
    for (int i = 0; i < node->size; i++)
    {
        node->value[i] = a[i] * child->value[i];
    }
}

static void jacobian_init_impl(expr *node)
{
    expr *x = node->left;

    /* initialize child jacobian */
    jacobian_init(x);

    /* same sparsity as child */
    node->jacobian = new_csr_copy_sparsity(x->jacobian);
}

static void eval_jacobian(expr *node)
```

```
{
    expr *x = node->left;
    const double *a = ((vector_mult_expr *) node)->param_source->value;

    /* evaluate x */
    x->eval_jacobian(x);

    /* row-wise scale child's jacobian */
    for (int i = 0; i < node->size; i++)
    {
        for (int j = x->jacobian->p[i]; j < x->jacobian->p[i + 1]; j++)
        {
            node->jacobian->x[j] = a[i] * x->jacobian->x[j];
        }
    }
}
```

Matrix multiplication. The matrix multiplication atom takes a constant (or parameter) matrix $A \in \mathbf{R}^{m \times k}$ and an expression x whose value lies in $\mathbf{R}^k$, and produces $Ax \in \mathbf{R}^m$. Because the canonicalized problem is affine in the variables, one operand of every `matmul` is always data; we take it to be the left operand A and the variable-bearing expression to be the right child.

```
matmul_expr = F @ x
```

The forward pass is an ordinary sparse matrix–vector product.

```
static void forward(expr *node, const double *u)
{
    matmul_expr *mnode = (matmul_expr *) node;
    expr *x = node->right;
    const CSR_Matrix *A = mnode->coeff; /* constant m x k matrix */

    /* child's forward pass */
    x->forward(x, u);

    /* y = A x */
    csr_matvec(A, x->value, node->value);
```

```
}
```

For the Jacobian, note that if x has Jacobian $J_x \in \mathbf{R}^{k \times n_{\text{vars}}}$, then $y = Ax$ has Jacobian $J_y = AJ_x$, a sparse matrix–matrix product. The sparsity pattern of J_y depends only on the patterns of A and J_x, so we compute it once during initialization and reuse it on every solve, filling only its numerical values during evaluation.

```
static void jacobian_init_impl(expr *node)
{
    matmul_expr *mnode = (matmul_expr *) node;
    expr *x = node->right;

    /* initialize child jacobian */
    jacobian_init(x);

    /* symbolic product A * J_x: allocates J_y and fills its sparsity pattern
       */
    node->jacobian = csr_matmat_symbolic(mnode->coeff, x->jacobian);
}

static void eval_jacobian(expr *node)
{
    matmul_expr *mnode = (matmul_expr *) node;
    expr *x = node->right;

    /* evaluate child jacobian */
    x->eval_jacobian(x);

    /* numeric product A * J_x into the pre-allocated pattern */
    csr_matmat_numeric(mnode->coeff, x->jacobian, node->jacobian);
}
```

The split between `csr_matmat_symbolic` and `csr_matmat_numeric` is the heart of the two-phase design: the symbolic product is run once per problem family, while only the numeric product is repeated when parameters change.

3.3 Problem class and Parameter updates

The atoms of the previous section compute the Jacobian of a single expression; a `Problem` ties together the full set of constraint expression trees and assembles their root Jacobians into the global problem data $[A\ b]$ and objective data $[c\ d]$.

At construction time, the problem performs the one-time *initialization* phase. It walks each expression tree once, calling `jacobian_init` bottom-up so that every node allocates its Jacobian and fixes its sparsity pattern. Because the pattern of an affine expression does not depend on the numerical values of its parameters, this walk is performed exactly once for a given problem family. The root Jacobians are then concatenated into the global CSR buffer for A using the constraint row offsets of §2.2, which fixes the sparsity pattern of the problem data as a whole.

Parameter updates. A subsequent *evaluation* phase runs on every solve. Given new parameter values θ, the problem refreshes the leaf parameter values and calls `eval_jacobian` bottom-up, filling in the numerical entries of each pre-allocated Jacobian without touching its sparsity pattern. The forward pass supplies the constant column b, and the updated root Jacobians are copied into the global buffer. A parameter update therefore costs only a forward pass and a numeric Jacobian evaluation—no allocation, no symbolic work, and no graph mutation.

This is precisely the saving that distinguishes our method from the `ignore_dpp` path of §2.1. That path is general—it places no DPP restriction on how parameters enter—but it pays the full cost of re-deriving the symbolic structure on every change of θ. Our two-phase design keeps the same generality while paying that symbolic cost only once, recovering the amortized re-solve speed of the cached DPP path without ever materializing the three-dimensional parameter tensor.

3.4 CVXPY interface

To make the engine usable from CVXPY, we expose the `Problem` class and the atom constructors through a thin set of Python bindings. The engine then acts as a *canonicalization backend*: it occupies the same place in the pipeline as `cvxcore` and the `SciPy` backend of §2.2, consuming the canonicalized affine expression trees produced by the reductions and returning the problem data (A, b, c, d).

Concretely, CVXPY hands the backend its canonicalized expression trees; the binding mirrors each CVXPY atom onto its engine counterpart to build the C expression trees, runs the

initialization phase once, and stores the resulting handle on the problem. On the first solve, and on every subsequent solve with new parameter values, CVXPY calls into the evaluation phase to obtain the updated data, which is then forwarded to the cone solver. Because the binding only forwards pointers to pre-allocated buffers, no problem data is copied between Python and C in the inner loop.

CHAPTER 4 Benchmark results

In this chapter we evaluate the engine of §3 against CVXPY's existing canonicalization path. The central question is the cost of repeatedly forming the problem data for a parameterized problem family, which is exactly the regime our two-phase design targets.

4.1 Benchmark Setup

We benchmark on the public CVXPY benchmark suite [57], 25 real-world problems (linear and quadratic programs, least squares, portfolio models, robust regression, and conic and semidefinite programs) maintained under *airspeed velocity* (`asv`) [58] with seeded, reproducible data. Three problems need the unsupported `kron` atom and are excluded; the remaining 22 run on both backends.

We time *canonicalization* only—the construction of the problem data (A, b, c, P) from the expression tree—and exclude the numerical solve, since that is what the engine changes. Concretely we time `get_problem_data` with the target solver fixed to Clarabel [59]: the `CPP` (`cvxcore`) baseline is the default DPP path, and the C engine is selected with `ignore_dpp`.

```
prob.get_problem_data(solver=cp.CLARABEL)              # CPP baseline (DPP
    tensor)
prob.get_problem_data(solver=cp.CLARABEL, ignore_dpp=True) # our C engine
```

We report two regimes: *cold-start* (a fresh `Problem` built with nothing cached, averaged over 3 builds) and *warm-restart* (parameter values reassigned on a warm cached chain, averaged over 20 re-compiles)—the latter being the regime the engine targets. Alongside these wall-clock times we report *peak memory*, and summarize across the suite with the *geometric mean* of the per-problem engine/`CPP` ratios, the standard scale-free statistic for timings that span orders of magnitude [60].

All measurements run single-threaded on a MacBook Pro (13-inch, M2, 2022): 8-core Apple M2, 24 GB RAM, macOS 26.3, with Python 3.14, CVXPY 1.10 (dev), NumPy 2.4 [30], and SciPy 1.16 [54]. Versions are pinned and the suite and engine are public, so the configuration is reproducible.

4.2 Results across the benchmark suite

Table 4.1 reports cold-start compilation across the 22 runnable benchmarks, and Table 4.2 reports warm-restart re-compilation on the parametric subset. In both, the ratio is C engine/CPP, so a value below 1 means the engine is faster; the final row gives the geometric mean of the per-problem ratios.

Table 4.1 Cold compilation time: a fresh problem formed and canonicalized from scratch, C engine versus CVXPY's `CPP` backend (22 runnable benchmarks). Ratio = C engine / `CPP`; values below 1 favor the engine.

Benchmark	`CPP` (ms)	C engine (ms)	Ratio
Yitzhaki	845	69	**0.08**
Cajas	2154	179	**0.08**
SimpleQP	2882	295	0.10
LeastSquares	2313	263	0.11
HuberRegression	2559	298	0.12
SimpleLP	5656	747	0.13
SlowPruning	1726	283	0.16
SVMWithL1Regularization	2593	411	0.16
TvInpainting	879	164	0.19
SimpleScalarParametrizedLP	1066	223	0.21
SimpleFullyParametrizedLP	463	110	0.24
ParametrizedQP	2645	631	0.24
ConeMatrixStuffing	2589	819	0.32
ParamSmallMatrixStuffing	118	40	0.34
OptimalAdvertising	2202	805	0.37
ParamConeMatrixStuffing	69	27	0.38
SmallMatrixStuffing	1633	627	0.38
CVaR	7128	6224	0.87
FactorCovarianceModel	1157	1117	0.97
Murray	1052	1627	1.55
ConvexPlasticity	81	220	2.63
SemidefiniteProgramming	995	8886	**8.90**
Geometric mean			**0.32**

Reading. In aggregate the engine is about 3× faster on cold builds (geometric-mean ratio 0.32) and near parity on parametric re-compiles (1.18), but the per-problem split is the more informative story. On *cold* compilation the engine wins on the bulk of the LP, QP, portfolio, and conic problems—typically 3–12× faster, since it extracts the problem data directly from

Table 4.2 Parametric re-compilation time on a warm cached chain: parameter values are reassigned and the problem data rebuilt (the engine's target regime). Ratio = C engine / `CPP`.

Benchmark	#par	`CPP` (ms)	C engine (ms)	Ratio
ParamSmallMatrixStuffing	3	2.23	0.65	**0.29**
ParamConeMatrixStuffing	3	1.19	0.40	0.33
SimpleFullyParametrizedLP	1	50.8	36.8	0.72
ParametrizedQP	2	333	309	0.93
SimpleScalarParametrizedLP	1	66.2	67.9	1.03
FactorCovarianceModel	2	21.3	72.2	3.39
SVMWithL1Regularization	1	40.2	150	3.72
ConvexPlasticity	3	43.0	194	4.52
Geometric mean				**1.18**

the expression trees while `CPP` pays the full parameter-tensor build. It loses on `Murray` (1.55×), `ConvexPlasticity` (2.63×), and the `SemidefiniteProgramming` outlier (8.9×), and reaches parity on `FactorCovarianceModel` (0.97×). On *parametric re-compilation* the picture is mixed and use-case dependent: the engine is faster on the matrix-stuffing and fully-parametrized-LP re-solves (0.29–0.72×) and near parity on `ParametrizedQP`, but 3.4–4.5× slower on `FactorCovarianceModel`, `SVM`, and `ConvexPlasticity`, where `CPP`'s cached DPP parameter→data tensor (one sparse matmul per solve) is hard to beat. The largest memory wins come from keeping constants sparse: eliminating an eager $25\,000 \times 25\,000$ dense densification (≈ 5 GB) on `FactorCovarianceModel`, and shrinking the `ConvexPlasticity` Hessian block from 9M to 51k nonzeros by routing a mostly-zero `quad_form` matrix to the sparse binding.

4.3 Scaling with problem size

The cross-suite tables fix the problem size; here we instead sweep it. We deep-dive three parameterized problems—parametric least squares, a factor-covariance portfolio, and an energy-storage scheduling model—and re-measure cold-start time, warm-restart time, and peak memory as the size grows. All three are genuinely parametric, so the warm-restart curve measures the engine's target regime: refilling values on a fixed sparsity pattern as the parameters change. For each panel we plot `CPP` against the C engine on log–log axes.

4.3.1 Parametric least squares

The bread-and-butter case: fit x to noisy observations with the data matrix A and right-hand side b supplied as parameters, so a re-solve only reassigns A and b. The size knobs are the number of observations m and variables n.

```
import cvxpy as cp

A = cp.Parameter((m, n))    # data matrix  (reassigned each solve)
b = cp.Parameter(m)         # observations (reassigned each solve)

x = cp.Variable(n)
objective  = cp.Minimize(cp.sum_squares(A @ x - b))
constraints = [0 <= x, x <= 1]
prob = cp.Problem(objective, constraints)
```

We sweep $n \in \{250, 500, 1000, 2000, 4000\}$ with $m = 3n$ (overdetermined) and measure both backends in the *ignore-DPP* regime: the canonicalization is rebuilt from scratch whenever the parameters change, which is the engine's intended use case. The C engine carries the parameters natively and re-extracts values on a fixed sparsity pattern; the `CPP` baseline substitutes the parameter values (the `EvalParams` reduction) and re-canonicalizes the resulting constant-data problem. We deliberately avoid CPP's DPP parameter-tensor path here: because the data matrix A is itself an $m \times n$ parameter, that tensor has $\Theta(mn)$ entries and its construction dominates everything else—tens of seconds and gigabytes already at $n = 500$—so it is neither representative nor the comparison of interest. Cold-start and warm-restart times are medians over three repetitions; peak memory is the process resident-set high-water mark (`ru_maxrss`), measured in a fresh subprocess per point so that, unlike Python-level `tracemalloc`, it also captures the engine's C-side allocations.

Cold-start (Figure 4.1) favours the engine by roughly 4× across the range (ratio 0.21–0.27), both backends scaling as $\sim n^{2.1}$. The gap widens on warm-restart (Figure 4.2): `CPP` re-canonicalizes in essentially its cold-start time (9.1 s at $n = 4000$), whereas the engine re-extracts on the cached pattern in 863 ms—a 10–12× speed-up that is precisely the non-DPP re-solve regime the engine targets. Peak memory (Figure 4.3) is comparable: both grow as $\sim n^{1.6}$ and are dominated by the dense A, with the engine 2–30% heavier in resident set. Its own internal accounting (the engine's `verbose` "peak memory") grows as $\sim n^{2.0}$, from 14 MB at $n = 250$ to 3.7 GB at $n = 4000$, yet stays below the process RSS throughout.




Figure 4.1 Parametric least squares, cold-start: full canonicalization from scratch versus problem size n ($m = 3n$). The C engine is $\approx 4\times$ faster across the whole range; both backends scale as $\sim n^{2.1}$.

4.3.2 Factor-covariance portfolio

A Markowitz portfolio whose risk is expressed through a low-rank factor model: n assets load on $m \ll n$ factors with covariance Σ, plus idiosyncratic diagonal risk D. The risk-aversion γ and leverage limit $L_{\max}$ are parameters, so re-solving traces the efficient frontier without rebuilding the problem. The size knobs are the number of assets n and factors m.

```
import cvxpy as cp
import numpy as np

# mu: expected returns, F: factor loadings (n x m),
# Sigma: factor covariance (m x m), D: idiosyncratic variances (diagonal).
w = cp.Variable(n)                # portfolio weights
f = cp.Variable(m)                # factor exposures
gamma = cp.Parameter(nonneg=True) # risk aversion (reassigned each solve)
Lmax  = cp.Parameter()            # leverage limit (reassigned each solve)

ret  = mu.T @ w
risk = cp.quad_form(f, Sigma, assume_PSD=True) + cp.sum_squares(np.sqrt(D) @ w
    )
objective  = cp.Maximize(ret - gamma * risk)
constraints = [cp.sum(w) == 1, f == F.T @ w, cp.norm(w, 1) <= Lmax]
prob = cp.Problem(objective, constraints)
```




Figure 4.2 Parametric least squares, warm-restart: rebuild after reassigning A and b. With no DPP tensor to reuse, `CPP` pays its full cold-start cost again, while the C engine only re-evaluates values on the cached sparsity pattern—a 10–12× speed-up.

We hold the factor count fixed at $m = 100$ and sweep the assets $n \in \{500, 1000, 2000, 4000, 8000\}$. As in the least-squares study, both backends run in the *ignore-DPP* rebuild regime—the engine carries $\gamma, L_{\max}$ natively and re-extracts on a fixed sparsity pattern, while `CPP` substitutes their values and re-canonicalizes. (Here the parameters are scalar, so CPP's DPP cache would in fact be feasible; we use the same rebuild regime as before for a consistent comparison.) Times are medians over three repetitions; peak memory is the process resident-set high-water mark measured in a fresh subprocess.

Cold-start (Figure 4.4) again favours the engine, but less decisively than for least squares and with a narrowing margin: from 0.41× at $n = 500$ to 0.88× at $n = 8000$, as the engine's $\sim n^{1.2}$ cold cost catches CPP's $\sim n^{0.9}$. Warm-restart (Figure 4.5) is where the engine dominates: `CPP` pays its full cold-start cost on every re-solve (144 ms at $n = 8000$), while the engine refills the cached pattern in 10.7 ms—a steady 12–13× advantage. Peak memory (Figure 4.6) is close, the engine 4–16% heavier in resident set; both curves are nearly flat because the low-rank model keeps the operator small. The engine's own internal peak (its `verbose` accounting) grows as $\sim n^{0.9}$, from 6 MB at $n = 500$ to 74 MB at $n = 8000$.

4.3.3 Energy-storage scheduling

A simple energy problem: schedule a battery over a horizon of T hours to minimize the cost of grid energy, where the hourly price is the parameter that changes between solves. The state of charge is the running sum of charge minus discharge, and the battery must end




Figure 4.3 Parametric least squares, peak process memory (resident-set high-water mark). The backends are within ∼30% of each other; both grow as $\sim n^{1.6}$, dominated by the shared interpreter and the dense data matrix A.

empty. The size knob is the horizon T.

```
import cvxpy as cp
import numpy as np

price = cp.Parameter(T)          # hourly price (reassigned each solve)
load  = np.random.rand(T)        # fixed demand profile
Q, Pmax = 50.0, 20.0             # capacity and charge/discharge power limit

charge    = cp.Variable(T, nonneg=True)
discharge = cp.Variable(T, nonneg=True)
soc = cp.cumsum(charge - discharge)     # battery state of charge

constraints = [charge <= Pmax, discharge <= Pmax,
               soc >= 0, soc <= Q, soc[T - 1] == 0]
grid = load + charge - discharge        # net energy drawn from the grid
prob = cp.Problem(cp.Minimize(price @ grid), constraints)
```

The cross-suite results (§4.2) and these scaling curves together delineate the operating regime where the engine pays off: cheap from-scratch builds across the suite, and a favorable size trend on problems whose canonicalization cost the engine avoids re-paying.




Figure 4.4 Factor-covariance portfolio, cold-start versus number of assets n ($m = 100$ factors). The engine leads at small n but its advantage shrinks with size—it scales as $\sim n^{1.2}$ against CPP's $\sim n^{0.9}$, reaching near-parity by $n = 8000$.




Figure 4.5 Factor-covariance portfolio, warm-restart after reassigning γ and $L_{\max}$. `CPP` re-canonicalizes in essentially its cold-start time; the engine re-extracts on the cached pattern, a stable 12–13× speed-up across the range.




Figure 4.6 Factor-covariance portfolio, peak process memory. The backends are within $\sim$15%; both grow slowly ($\sim n^{0.35}$), reflecting the low-rank factor structure rather than a dense operator.




Figure 4.7 Energy-storage scheduling: scaling of cold-start, warm-restart, and peak memory with horizon length T (*placeholder curves; data pending the size-sweep run*).

CHAPTER 5 CONCLUSION

5.1 Summary of Works

This thesis reframed CVXPY's matrix stuffing as a *sparse Jacobian evaluation*. Rather than building the three-dimensional parameter tensor of the DPP path (§2.2), we observed that the problem data of a parameterized cone program is an affine function of the variables whose sparsity pattern is fixed across a problem family. This observation separates canonicalization into two phases: a one-time *initialization* that fixes the sparsity pattern, and a per-solve *evaluation* that refills only the numerical values.

We implemented this idea as a lightweight engine in C, the `SparseDiffEngine`, building up a subset of affine atoms—addition, negation, transpose, stacking, indexing, summation, elementwise multiplication, and matrix multiplication—each satisfying a three-function contract of forward pass, Jacobian initialization, and Jacobian evaluation (§3). A `Problem` class assembles the root Jacobians into the global problem data, and a thin set of Python bindings lets the engine act as a canonicalization backend for CVXPY. The result computes the problem sparsity once per family and refills values per solve, so it handles parameterized problems *without* the DPP rule restriction and without materializing the parameter tensor.

5.2 Limitations

The engine is not yet a drop-in replacement for CVXPY's existing backends. Its atom coverage is partial: it implements the affine atoms needed for the problems studied here, but not the full set of CVXPY's standard atoms. It is currently a standalone C library exercised through Python bindings rather than a fully integrated backend, and its execution is single-threaded with no GPU support. Finally, the saving relies on the sparsity pattern being stable across a problem family; problems whose structure changes between solves fall outside the cases the two-phase design is designed to accelerate.

5.3 Future Research

The most immediate direction is to expand the atom library to cover all of CVXPY's standard atoms, making the engine a complete drop-in backend, and to ship it as a Python-importable canonicalization backend selected through CVXPY's usual interface. Beyond coverage, the two-phase design invites exploration of non-DPP parameterizations where the sparsity pat-

tern is nonetheless stable—a class strictly larger than the DPP-compliant problems—and of parallel or GPU-accelerated evaluation, since the per-solve numeric phase is a fixed sequence of sparse kernels over a static structure.

REFERENCES

[1] S. Diamond and S. Boyd, "CVXPY: A Python-embedded modeling language for convex optimization," *Journal of Machine Learning Research*, vol. 17, no. 83, pp. 1–5, 2016.

[2] J. Löfberg, "YALMIP: A toolbox for modeling and optimization in MATLAB," in *2004 IEEE international conference on robotics and automation (IEEE Cat. No. 04CH37508)*. IEEE, 2004, pp. 284–289.

[3] M. Grant, "Disciplined Convex Programming," Ph.D. dissertation, Stanford University, Dec. 2004, ph.D. dissertation. [Online]. Available: https://web.stanford.edu/~boyd/papers/pdf/mcg_thesis.pdf

[4] M. Grant, S. Boyd, and Y. Ye, "Disciplined convex programming," in *Global Optimization: From Theory to Implementation*, L. Liberti and N. Maculan, Eds. New York: Springer, 2006, pp. 155–210.

[5] M. Schaller, G. Banjac, S. Diamond, A. Agrawal, B. Stellato, and S. Boyd, "Embedded code generation with cvxpy," *IEEE Control Systems Letters*, vol. 6, pp. 2653–2658, 2022.

[6] R. Fourer and M. J. Harrison, "A modern approach to computer systems for linear programming," 1978.

[7] *IBM Mathematical Programming System Extended/370 (MPSX/370) Program Reference Manual*, 2nd ed., IBM Corporation, 1976.

[8] W. Orchard-Hays, "History of mathematical programming systems," *Annals of the History of Computing*, vol. 6, no. 3, pp. 296–312, 1984.

[9] I. Marceau and T. W. Mason, "A matrix-generator system for linear programming problems," Center for Advanced Computation, University of Illinois at Urbana-Champaign, Urbana, IL, Tech. Rep. CAC Document No. 4, 1971. [Online]. Available: https://hdl.handle.net/2142/32405

[10] *MaGen Reference Manual*, Haverly Systems, Inc., Denville, NJ, 1977.

[11] *GAMMA 3.4 Programmer Reference*, Sperry Univac Computer Systems, St. Paul, MN, 1977.

[12] *MIPS III DATAFORM User Manual*, Ketron, Inc., Arlington, VA, 1975.

[13] R. Fourer, "Modeling languages versus matrix generators for linear programming," *ACM Trans. Math. Softw.*, vol. 9, no. 2, pp. 143–183, Jun. 1983. [Online]. Available: https://doi.org/10.1145/357456.357457

[14] A. Brooke, D. Kendrick, and A. Meeraus, *GAMS: A User's Guide*. Redwood City, CA: The Scientific Press, 1988.

[15] J. Bisschop, *AIMMS optimization modeling*, 2006.

[16] R. Fourer, D. M. Gay, and B. W. Kernighan, "A modeling language for mathematical programming," *Management Science*, vol. 36, no. 5, pp. 519–554, 1990.

[17] W. E. Hart *et al.*, "Pyomo: modeling and solving mathematical programs in python," *Mathematical Programming Computation*, vol. 3, no. 3, pp. 219–260, 2011.

[18] M. L. Bynum *et al.*, *Pyomo—Optimization Modeling in Python*. Springer, 2021.

[19] I. Dunning, J. Huchette, and M. Lubin, "JuMP: A modeling language for mathematical optimization," *SIAM Review*, vol. 59, no. 2, pp. 295–320, 2017.

[20] J. A. E. Andersson, J. Gillis, G. Horn, J. B. Rawlings, and M. Diehl, "CasADi – A software framework for nonlinear optimization and optimal control," *Mathematical Programming Computation*, vol. 11, no. 1, pp. 1–36, 2019.

[21] I. CVX Research, "CVX: Matlab software for disciplined convex programming, version 2.0," https://cvxr.com/cvx, Aug. 2012.

[22] A. Agrawal, R. Verschueren, S. Diamond, and S. Boyd, "A rewriting system for convex optimization problems," *Journal of Control and Decision*, vol. 5, no. 1, pp. 42–60, 2018.

[23] M. Udell, K. Mohan, D. Zeng, J. Hong, S. Diamond, and S. Boyd, "Convex optimization in Julia," in *2014 first workshop for high performance technical computing in dynamic languages*. IEEE, 2014, pp. 18–28.

[24] A. Agrawal, S. Diamond, and S. Boyd, "Disciplined geometric programming," *Optimization Letters*, vol. 13, pp. 961–976, 2019.

[25] A. Agrawal and S. Boyd, "Disciplined quasiconvex programming," *Optimization Letters*, vol. 14, pp. 1643–1657, 2020.

[26] A. Agrawal, B. Amos, S. Barratt, S. Boyd, S. Diamond, and Z. Kolter, "Differentiable convex optimization layers," in *Advances in Neural Information Processing Systems*, vol. 32, 2019.

[27] D. Cederberg, W. Zhang, P. Nobel, and S. Boyd, "Disciplined nonlinear programming," 2025.

[28] S. Boyd and L. Vandenberghe, *Convex optimization*. Cambridge university press, 2004.

[29] M. Grant and S. Boyd, "Graph Implementations for Nonsmooth Convex Programs," in *Recent Advances in Learning and Control*, ser. Lecture Notes in Control and Information Sciences, V. Blondel, S. Boyd, and H. Kimura, Eds. Springer, London, 2008, vol. 371. [Online]. Available: https://doi.org/10.1007/978-1-84800-155-8_7

[30] C. R. Harris, K. J. Millman, S. J. van der Walt, R. Gommers, P. Virtanen, D. Cournapeau, E. Wieser, J. Taylor, S. Berg, N. J. Smith, R. Kern, M. Picus, S. Hoyer, M. H. van Kerkwijk, M. Brett, A. Haldane, J. F. del Río, M. Wiebe, P. Peterson, P. Gérard-Marchant, K. Sheppard, T. Reddy, W. Weckesser, H. Abbasi, C. Gohlke, and T. E. Oliphant, "Array programming with NumPy," *Nature*, vol. 585, no. 7825, pp. 357–362, Sep. 2020. [Online]. Available: https://doi.org/10.1038/s41586-020-2649-2

[31] E. Chu, N. Parikh, A. Domahidi, and S. Boyd, "Code generation for embedded second-order cone programming," in *2013 European Control Conference (ECC)*, 2013, pp. 1547–1552.

[32] M. Lubin, O. Dowson, J. D. Garcia, J. Huchette, B. Legat, and J. P. Vielma, "Jump 1.0: Recent improvements to a modeling language for mathematical optimization," 2023. [Online]. Available: https://arxiv.org/abs/2206.03866

[33] Y. LeCun, Y. Bengio, and G. Hinton, "Deep learning," *nature*, vol. 521, no. 7553, pp. 436–444, 2015.

[34] L. Bottou, F. E. Curtis, and J. Nocedal, "Optimization methods for large-scale machine learning," *SIAM Review*, vol. 60, no. 2, pp. 223–311, 2018. [Online]. Available: https://epubs.siam.org/doi/10.1137/16M1080173

[35] Y. LeCun, "A theoretical framework for back-propagation," in *Proceedings of the 1988 Connectionist Models Summer School*, vol. 1. CMU, Pittsburgh, Pa, 1988, pp. 21–28.

[36] A. Griewank and A. Walther, *Evaluating Derivatives: Principles and Techniques of Algorithmic Differentiation*, 2nd ed. Philadelphia, PA: Society for Industrial and Applied Mathematics, 2008.

[37] P. C. Chakravarti, "Truncation error in interpolation and numerical differentiation," *Numer. Math.*, vol. 3, no. 1, p. 279–284, Dec. 1961. [Online]. Available: https://doi.org/10.1007/BF01386029

[38] P. Wolfe, "Checking the calculation of gradients," *ACM Trans. Math. Softw.*, vol. 8, no. 4, p. 337–343, Dec. 1982. [Online]. Available: https://doi.org/10.1145/356012.356013

[39] Wolfram Research, Inc., "Mathematica, Version 14.3," 2026, champaign, IL. [Online]. Available: https://www.wolfram.com/mathematica

[40] Maplesoft, a division of Waterloo Maple Inc., "Maple," Waterloo, Ontario. [Online]. Available: https://www.maplesoft.com

[41] A. Meurer, C. P. Smith, M. Paprocki, O. Čertík, S. B. Kirpichev, M. Rocklin, A. Kumar, S. Ivanov, J. K. Moore, S. Singh, T. Rathnayake, S. Vig, B. E. Granger, R. P. Muller, F. Bonazzi, H. Gupta, S. Vats, F. Johansson, F. Pedregosa, M. J. Curry, A. R. Terrel, v. Roučka, A. Saboo, I. Fernando, S. Kulal, R. Cimrman, and A. Scopatz, "Sympy: symbolic computing in python," *PeerJ Computer Science*, vol. 3, p. e103, Jan. 2017. [Online]. Available: https://doi.org/10.7717/peerj-cs.103

[42] S. Laue, "On the equivalence of forward mode automatic differentiation and symbolic differentiation," *ArXiv*, vol. abs/1904.02990, 2019. [Online]. Available: https://api.semanticscholar.org/CorpusID:102350450

[43] A. G. Baydin, B. A. Pearlmutter, A. A. Radul, and J. M. Siskind, "Automatic differentiation in machine learning: a survey," *J. Mach. Learn. Res.*, vol. 18, no. 1, p. 5595–5637, Jan. 2017.

[44] J. Bradbury, R. Frostig, P. Hawkins, M. J. Johnson, Y. Katariya, C. Leary, D. Maclaurin, G. Necula, A. Paszke, J. VanderPlas, S. Wanderman-Milne, and Q. Zhang, "JAX: composable transformations of Python+NumPy programs," 2018. [Online]. Available: http://github.com/jax-ml/jax

[45] A. Paszke, S. Gross, F. Massa, A. Lerer, J. Bradbury, G. Chanan, T. Killeen, Z. Lin, N. Gimelshein, L. Antiga, A. Desmaison, A. Köpf, E. Yang, Z. DeVito, M. Raison, A. Tejani, S. Chilamkurthy, B. Steiner, L. Fang, J. Bai, and S. Chintala, *PyTorch: an imperative style, high-performance deep learning library.* Red Hook, NY, USA: Curran Associates Inc., 2019.

[46] M. Abadi, P. Barham, J. Chen, Z. Chen, A. Davis, J. Dean, M. Devin, S. Ghemawat, G. Irving, M. Isard, M. Kudlur, J. Levenberg, R. Monga, S. Moore, D. G. Murray, B. Steiner, P. Tucker, V. Vasudevan, P. Warden, M. Wicke, Y. Yu, and X. Zheng, "Tensorflow: a system for large-scale machine learning," in *Proceedings of the 12th USENIX*

Conference on Operating Systems Design and Implementation, ser. OSDI'16. USA: USENIX Association, 2016, p. 265–283.

[47] U. Naumann, *The Art of Differentiating Computer Programs: An Introduction to Algorithmic Differentiation*, ser. Software, Environments, and Tools. Philadelphia, PA: SIAM, 2011.

[48] P. Herholz, X. Tang, T. Schneider, S. Kamil, D. Panozzo, and O. Sorkine-Hornung, "Sparsity-specific code optimization using expression trees," *ACM Trans. Graph.*, vol. 41, no. 5, May 2022. [Online]. Available: https://doi.org/10.1145/3520484

[49] A. H. Gebremedhin, A. Tarafdar, A. Pothen, and A. Walther, "Efficient computation of sparse hessians using coloring and automatic differentiation," *INFORMS J. on Computing*, vol. 21, no. 2, p. 209–223, Apr. 2009. [Online]. Available: https://doi.org/10.1287/ijoc.1080.0286

[50] A. H. Gebremedhin, F. Manne, and A. Pothen, "What color is your Jacobian? Graph coloring for computing derivatives," *SIAM Review*, vol. 47, no. 4, pp. 629–705, 2005.

[51] B. W. Kernighan and D. M. Ritchie, *The C Programming Language*, 2nd ed. Prentice Hall, 1988.

[52] Y. Saad, *Iterative Methods for Sparse Linear Systems*, 2nd ed. Philadelphia, PA: Society for Industrial and Applied Mathematics, 2003.

[53] T. A. Davis, *Direct Methods for Sparse Linear Systems*. Philadelphia, PA: Society for Industrial and Applied Mathematics, 2006. [Online]. Available: https://epubs.siam.org/doi/book/10.1137/1.9780898718881

[54] P. Virtanen, R. Gommers, T. E. Oliphant, M. Haberland, T. Reddy, D. Cournapeau, E. Burovski, P. Peterson, W. Weckesser, J. Bright, S. J. van der Walt, M. Brett, J. Wilson, K. J. Millman, N. Mayorov, A. R. J. Nelson, E. Jones, R. Kern, E. Larson, C. J. Carey, İ. Polat, Y. Feng, E. W. Moore, J. VanderPlas, D. Laxalde, J. Perktold, R. Cimrman, I. Henriksen, E. A. Quintero, C. R. Harris, A. M. Archibald, A. H. Ribeiro, F. Pedregosa, P. van Mulbregt, and SciPy 1.0 Contributors, "SciPy 1.0: Fundamental Algorithms for Scientific Computing in Python," *Nature Methods*, vol. 17, pp. 261–272, 2020.

[55] I. S. Duff, A. M. Erisman, and J. K. Reid, *Direct Methods for Sparse Matrices*. Oxford, England: Oxford University Press, 1986.

[56] P. E. Gill, W. Murray, M. A. Saunders, and M. H. Wright, "Sparse matrix methods in optimization," *SIAM Journal on Scientific and Statistical Computing*, vol. 5, no. 3, pp. 562–589, 1984.

[57] CVXPY developers, "CVXPY benchmarks," https://github.com/cvxpy/benchmarks, 2025.

[58] airspeed velocity developers, "airspeed velocity," https://asv.readthedocs.io/, 2025, python benchmarking framework.

[59] P. J. Goulart and Y. Chen, "Clarabel: An interior-point solver for conic programs with quadratic objectives," *arXiv preprint arXiv:2405.12762*, 2024.

[60] D. Cederberg and S. Boyd, "Presolving for GPU-accelerated first-order LP solvers," https://web.stanford.edu/~boyd/papers/pslp.html, 2026, manuscript.