

BOARD CHARACTERISTICS

Copper layer count:	2	Board thickness:	1.6 mm
Board overall dimensions:	80 mm x 70 mm		
Min track/spacing:	7 mils / 7 mils	Min hole diameter:	12.00 mils
Copper finish:	HAL SnPb	Impedance control:	No
Castellated pads:	No	Press-fit pads:	No
Plated board edge:	No	Edge card connectors:	No

Layer Name	Type	Material	Thickness	Color	Epsilon R	Loss Tangent
F.Silkscreen	Top silk screen	Not specified	Not specified	White	1	0
F.Paste	Top solder paste		Not specified		1	0
F.Mask	Top solder mask	Not specified	0.3937 mils	Green	3.3	0
F.Cu	Copper		1.37795 mils		1	0
Dielectric 1	Core	FR4	59.44882 mils	FR4 natural	4.5	0.02
B.Cu	Copper		1.37795 mils		1	0
B.Mask	Bottom solder mask	Not specified	0.3937 mils	Green	3.3	0
B.Paste	Bottom solder paste		Not specified		1	0
B.Silkscreen	Bottom silk screen	Not specified	Not specified	White	1	0



Designed by Logic Reliance for Satview Broadband Ltd

Sheet:

File: pcb_0222.kicad_pcb

Title: UV Floor Sanitization Unit

Size: A4

Date: 2026-08-27

Rev: 20260827

KiCad E.D.A. 10.0.4

Id: 1/1