ChemCritic 文献证据卡

PMC13564410 | 羰基化 | 采集状态 imported_unchecked

标题	Biphasic Solar Reforming of Lignin to Aromatics and CO for In Situ Carbonylation of Organics
作者	Mittal D., Mitra S., Bonvin E., Spring D., Bonke S., Reisner E.
出处	Journal of the American Chemical Society 2026
DOI	10.1021/jacs.6c10525
原文链接	https://pmc.ncbi.nlm.nih.gov/articles/PMC13564410/
许可	https://creativecommons.org/licenses/by/4.0/This article is licensed under CC-BY 4.0

摘要（原文节选）

Lignin is a large-scale, renewable carbon source that remains underutilized due to its complex polymeric structure. Photocatalytic conversion of lignin promises selective bond cleavage to yield functionalized products but is hindered by its strong light absorption. Herein, we report a biphasic photocatalytic system that avoids light competition and enables the generation of both CO and functionalized aromatics from Kraft lignin under visible light at ambient temperature and pressure. This system uses water-disperse ⋯

数据表 · 1（8 行，含数值行 8 行）

One-Pot Cascade Reaction Utilizing Kraft Lignin as a Green CO Source for Aminocarbonylation ,

entry	system	yield (%)
1	LEDs	68
2	solar light	48
3	no QDs	n.d.
4	no [Pd]	n.d.
5	no lignin	n.d.
6	no light	n.d.
7	no biphase	n.d.
8	two-compartments	3

脚注（逐字）：aBiphasic solvent system (1:1, 3 mL) under a N2 atmosphere with aqueous layer containing CdS-AET QDs (1 μ M) and EtOAc layer containing sat. Kraft lignin (3.3 mg mL – 1), iodoanisole (0.1 mmol), octylamine (0.5 mmol), Pd(OAc)2 (20 mol %) and Xantphos (40 mol %) at 25 ° C with 250 rpm orbital shaking fo

正文对应句（逐字）：Unprocessed lignocellulose was then examined for CO generation to show the broad applicability of this reaction to biomass conversion beyond Kraft lignin. The raw lignocellulosic biomass waste samples were ground and refluxed in EtOAc for 1 h to extract lignin, which was reacted in a biphasic config

本卡为 NCBI PMC 开放获取 XML
的逐字摘录（标题、作者、表格行列、脚注、正文句均未改写），用于参照集候选与覆盖面登记；未逐条人工核验，标记 imported_unchecked，不写入判定记录、不参与 ChemCritic 引擎的可比性判定。对外引用一律回到 DOI 原文核对页码与表号。