LS-Reader Tutorial

LS-Reader Tutorial	1
C++	3
API Functions	3
D3P_Parameter	4
DataType	6
How to use	18
Sample1.cpp	18
Sample2.cpp	21
Python	25
API Functions(Recommended)	25
API Functions (Deprecated)	27
D3P_Parameter	31
DataType	34
How to use	45
Sample1.py	45
Sample2.py	48
C	50
API Functions	50
_D3P _Parameter	51
DataType	53
How to use	63
Sample1.c	63
Sample2.c	67

Introduction

This document describes the application functions interface of LS-Reader using C++, Python and C.

The LS-Reader is designed to read LS-DYNA results and it supports C, C++ and Python languages. It supports both Windows(vs2010, vs2015, vs2017, vs2019) and Linux(gcc>=4.1.2). Because of the simplicity of the LS-Reader, using the libraries is very convenient.

C++

API Functions

D3P_Parameter

parameter to call D3plotReader::GetData*, only specific those member variables you are interested, otherwise, ignore this.

```
struct D3P_Parameter
{
       int ist;
       int ipt;
       int ipart;
       int i_rigid_wall;
       int ides;
       int ihv;
       int index_multisolver;
       int id_var_multisolver;
       const char* var_name;
};
1.
       ist: Specify the state number, starting from 0, as follows:
       D3P_Parameter param;
       param.ist = 167;
       param.ipt = 2;
       dr.GetData(D3P_SHELL_STRESS, (char*)shell_stress, param);
2.
       ipt: Specify the integration point, ranging in [0, MAXINT), as follows:
       D3P_Parameter param;
       param.ipt = 0;
3.
       ipart: Specify the index of part, starting from 0, as follows:
       D3P_Parameter param;
       param.ipart = 0;
       . . .
```

4. **i_rigid_wall**: Specify the index of rigid wall, starting from 0, as follows:

```
D3P_Parameter param;
param.i_rigid_wall = 0;
```

5. **ides**: Specify the index of the des data, starting from 0, as follows:

```
D3P_Parameter param;
param.ides = 0;
```

6. **ihv**: Specify the index of history variables, starting from 0, as follows:

```
D3P_Parameter param;
param.ihv = 0;
```

7. **index_multisolver**: Specify the index of the multisolver domain, start from 0 and default is 0 also:

```
D3P_Parameter param;
param.index_multisolver = 0;
```

8. **id_var_multisolver**: Specify the index of the multisolver var, start from 0 and default is 0 also:

```
D3P_Parameter param;
param.id_var_multisolver = 0;
```

9. **var_name**: Specify name of output variables, currently used by DES and CPM data, default is empty

```
D3P_Parameter param;
param.var_name = "Start N";
...
```

DataType

```
struct D3P_Vector
{
      float v[3];
      float X() const { return v[0]; }
      float Y() const { return v[1]; }
      float Z() const { return v[2]; }
      bool operator==(const D3P_Vector& src);
};
struct D3P_VectorDouble
{
      double v[3];
      double X() const { return v[0]; }
      double Y() const { return v[1]; }
      double Z() const { return v[2]; }
      bool operator==(const D3P_VectorDouble& src);
};
struct D3P_Tensor
{
      float t[6];
      float X() const { return t[0]; }
      float Y() const { return t[1]; }
      float Z() const { return t[2]; }
```

```
float XY() const { return t[3]; }
      float YZ() const { return t[4]; }
      float ZX() const { return t[5]; }
      bool operator==(const D3P_Tensor& src);
};
struct D3P_Solid
{
      int conn[10];
      int mat;
      int Mat() const { return mat; }
      int Node(int index) const { return conn[index]; }
      bool operator==(const D3P_Solid& src);
};
struct D3P_Tshell
{
      int conn[10];
      int mat;
      int Mat() const { return mat; }
      int Node(int index) const { return conn[index]; }
      bool operator==(const D3P_Tshell& src);
};
struct D3P_Beam
{
      int conn[2];
```

```
int third;
       int w_int;
       int h_int;
       int mat;
       int Mat() const { return mat; }
       int Node(int index) const { return conn[index]; }
       bool operator==(const D3P_Beam& src);
};
struct D3P_Shell
{
       int conn[4];
       int mat;
       int Mat() const { return mat; }
       int Node(int index) const { return conn[index]; }
       bool operator==(const D3P_Shell& src);
};
struct D3P_Sph
{
       int id;
       unsigned int mat;
       int Mat() const { return mat; }
       int Id() const { return id; }
       bool operator==(const D3P_Sph& src);
};
struct D3P_VAR
```

```
{
   int type;
   char name[8];
      std::string Name() const { return name; }
      int Type() const { return type; }
      bool operator==(const D3P_VAR& src);
};
struct D3P_DES
{
      int id;
      int mat;
      float radius;
      float mass;
      float inertia;
      int Id() const { return id; }
      int Mat() const { return mat; }
      float Radius() const { return radius; }
      float Mass() const { return mass; }
      float Inertia() const { return inertia; }
      bool operator==(const D3P_DES& src);
};
struct D3P_AIRBAG_INFO
{
      int bagid;
      int startn;
      int npart;
      int ngas;
```

int nchamber;

} ;

name D3P_NUM_STATES	conversion	length	
	lint	1	parameters ignore
D3P TIMES	float	D3P NUM STATES	ignore
D3P TITLE	char		ignore
Global			
D3P GLOBAL KINETIC ENERGY	float	1	ist
D3P_GLOBAL_INTERNAL_ENERGY	float	1	ist
D3P_GLOBAL_TOTAL_ENERGY	float	1	ist
D3P_GLOBAL_VELOCITY	D3P_Vector	1	ist
Part			
D3P_NUM_PARTS	int	1	ignore
D3P_PART_IDS	int	D3P_NUM_PARTS	ignore
D3P_PART_NAME	char	80	ipart
D3P_PART_INTERNAL_ENERGY	float	1	ist, ipart
D3P_PART_KINETIC_ENERGY	float	1	ist, ipart
D3P_PART_VELOCITY	D3P_Vector	1	ist, ipart
D3P_PART_MASS	float	1	ist, ipart
D3P_PART_HOURGLASS	float	1	ist, ipart
RIGID WALL			
D3P_NUM_RIGID_WALL	int	1	ignore
D3P_RIGID_WALL_FORCE	float	1	ist, i_rigid_wall
D3P_RIGID_WALL_POSITION	D3P_Vector	1	ist, i_rigid_wall
NODE			
D3P_NUM_NODES	int	1	ignore
D3P_NODE_INITIAL_COORDINATES	D3P_Vector	D3P_NUM_NODES	ignore
D3P_NODE_IDS	int	D3P_NUM_NODES	ignore
D3P_NODE_TEMPERATURE	float	D3P_NUM_NODES	ist
D3P_NODE_COORDINATES	D3P_Vector	D3P_NUM_NODES	ist
D3P_NODE_VELOCITIES	D3P_Vector	D3P_NUM_NODES	ist
D3P_NODE_ACCELERATIONS	D3P_Vector	D3P_NUM_NODES	ist

D3P_NODE_COORDINATES_DOUBLE	D3P_VectorDouble	D3P_NUM_NODES	ist
D3P_NODE_VELOCITIES_DOUBLE	D3P_VectorDouble	D3P_NUM_NODES	ist
D3P_NODE_ACCELERATIONS_DOUBLE	D3P_VectorDouble	D3P_NUM_NODES	ist
SOLID			
D3P_NUM_SOLID	int	1	ignore
D3P_SOLID_MAXINT	int	1	ignore
D3P_SOLID_CONNECTIVITY_MAT	D3P_Solid	D3P_NUM_SOLID	ignore
D3P_SOLID_IDS	int	D3P_NUM_SOLID	ignore
D3P_SOLID_STRESS	D3P_Tensor	D3P_NUM_SOLID	ist, ipt if necessary
D3P_SOLID_EFFECTIVE_PLASTIC_STR AIN	float	D3P_NUM_SOLID	ist, ipt if necessary
D3P_SOLID_STRAIN	D3P_Tensor	D3P_NUM_SOLID	ist, ipt if necessary
D3P_SOLID_HISTORY_VAR	float	D3P_NUM_SOLID	ist, ipt, ihv
TSHELL			
D3P_NUM_TSHELL	int	1	ignore
D3P_TSHELL_MAXINT	int	1	ignore
D3P_TSHELL_CONNECTIVITY_MAT	D3P_Tshell	D3P_NUM_TSHELL	ignore
D3P_TSHELL_IDS	int	D3P_NUM_TSHELL	ignore
D3P_TSHELL_STRESS	D3P_Tensor	D3P_NUM_TSHELL	ist, ipt
D3P_TSHELL_EFFECTIVE_PLASTIC_ST RAIN	float	D3P_NUM_TSHELL	ist, ipt
D3P_TSHELL_STRAIN	D3P_Tensor	D3P_NUM_TSHELL	ist, ipt
			ipt=0:mean
			1:inner
			2:outer
D3P_TSHELL_HISTORY_VAR	float	D3P_NUM_TSHELL	ist, ipt, ihv
BEAM			

D3P_NUM_BEAM	int	1	ignore
D3P_BEAM_MAXINT	int	1	ignore
D3P_BEAM_CONNECTIVITY_THIRD_MAT	D3P_Beam	D3P_NUM_BEAM	ignore
D3P_BEAM_IDS	int	D3P_NUM_BEAM	ignore
D3P_BEAM_AXIAL_FORCE	float	D3P_NUM_BEAM	ist
D3P_BEAM_S_SHEAR_RESULTANT	float	D3P_NUM_BEAM	ist
D3P_BEAM_T_SHEAR_RESULTANT	float	D3P_NUM_BEAM	ist
D3P_BEAM_S_BENDING_MOMENT	float	D3P_NUM_BEAM	ist
D3P_BEAM_T_BENDING_MOMENT	float	D3P_NUM_BEAM	ist
D3P_BEAM_TORSIONAL_RESULTANT	float	D3P_NUM_BEAM	ist
D3P_BEAM_RS_SHEAR_STRESS	float	D3P_NUM_BEAM	ist, ipt
D3P_BEAM_TR_SHEAR_STRESS	float	D3P_NUM_BEAM	ist, ipt
D3P_BEAM_AXIAL_STRESS	float	D3P_NUM_BEAM	ist, ipt
D3P_BEAM_AXIAL_PLASTIC_STRAIN	float	D3P_NUM_BEAM	ist, ipt
D3P_BEAM_AXIAL_STRAIN	float	D3P_NUM_BEAM	ist, ipt
D3P_BEAM_HISTORY_VAR	float	D3P_NUM_BEAM	ist, ipt, ihv
SHELL			
D3P_NUM_SHELL	int	1	ignore
D3P_SHELL_MAXINT	int	1	ignore
D3P_SHELL_CONNECTIVITY_MAT	D3P_She11	D3P_NUM_SHELL	ignore
D3P_SHELL_IDS	int	D3P_NUM_SHELL	ignore
D3P_SHELL_STRESS	D3P_Tensor	D3P_NUM_SHELL	ist, ipt
D3P_SHELL_EFFECTIVE_PLASTIC_STR AIN	float	D3P_NUM_SHELL	ist, ipt
D3P_SHELL_STRAIN	D3P_Tensor	D3P_NUM_SHELL	ist, ipt
			ipt=0:mean
			1:inner
			2:outer
D3P_SHELL_HISTORY_VAR	float	D3P_NUM_SHELL	ist, ipt, ihv

D3P_SHELL_MX	float	D3P_NUM_SHELL	ist
D3P_SHELL_MY	float	D3P_NUM_SHELL	ist
D3P_SHELL_MXY	float	D3P_NUM_SHELL	ist
D3P_SHELL_QX	float	D3P_NUM_SHELL	ist
D3P_SHELL_QY	float	D3P_NUM_SHELL	ist
D3P_SHELL_NX	float	D3P_NUM_SHELL	ist
D3P_SHELL_NY	float	D3P_NUM_SHELL	ist
D3P_SHELL_NXY	float	D3P_NUM_SHELL	ist
DELETION			
D3P_HAS_DELETION	bool	1	ist
D3P_SOLID_DELETION	float	D3P_NUM_SOLID	ist
D3P_TSHELL_DELETION	float	D3P_NUM_TSHELL	ist
D3P_SHELL_DELETION	float	D3P_NUM_SHELL	ist
D3P_BEAM_DELETION	float	D3P_NUM_BEAM	ist
SPH			
D3P_NUM_SPH	int	1	ignore
D3P_SPH_NODE_MAT	D3P_Sph	D3P_NUM_SPH	ignore
D3P_SPH_RADIUS	float	D3P_NUM_SPH	ist
D3P_SPH_PRESSURE	float	D3P_NUM_SPH	ist
D3P_SPH_STRESS	D3P_Tensor	D3P_NUM_SPH	ist
D3P_SPH_PLASTIC_STRAIN	float	D3P_NUM_SPH	ist
D3P_SPH_DENSITY	float	D3P_NUM_SPH	ist
D3P_SPH_INTERNAL_ENERGY	float	D3P_NUM_SPH	ist
D3P_SPH_NUMBER_OF_PARTICLE_NEIG HBORS	int	D3P_NUM_SPH	ist
D3P_SPH_STRAIN	D3P_Tensor	D3P_NUM_SPH	ist
D3P_SPH_MASS	float	D3P_NUM_SPH	ist
DES			
D3P_HAS_DES_DATA	bool	1	ignore

D3P_NUM_DES_DATA	int	1	ignore
D3P_NUM_DES_PART_IN_GEOM	int	1	ides if necessary
D3P_NUM_DES_ELEM_IN_GEOM	int	1	ides if necessary
D3P_NUM_DES_PART_IN_STATE	int	1	ides if necessary
D3P_NUM_DES_ELEM_IN_STATE	int	1	ides if necessary
D3P_NUM_DES_PART_VAR_IN_GEOM	int	1	ides if necessary
D3P_DES_PART_VAR_LIST_IN_GEOM	D3P_VAR	D3P_NUM_DES_PART _VAR_IN_GEOM	ides if necessary
D3P_NUM_DES_ELEM_VAR_IN_GEOM	int	1	ides if necessary
D3P_DES_ELEM_VAR_LIST_IN_GEOM	D3P_VAR	D3P_NUM_DES_ELEM _VAR_IN_GEOM	ides if necessary
D3P_NUM_DES_PART_VAR_IN_STATE	int	1	ides if necessary
D3P_DES_PART_VAR_LIST_IN_STATE	D3P_VAR	D3P_NUM_DES_PART _VAR_IN_STATE	ides if necessary
D3P_NUM_DES_ELEM_VAR_IN_STATE	int	1	ides if necessary
D3P_DES_ELEM_VAR_LIST_IN_STATE	D3P_VAR	D3P_NUM_DES_ELEM _VAR_IN_STATE	ides if necessary
D3P_DES_NODAL_MAT_RADIUS_MASS_I NERTIA	D3P_DES	D3P_NUM_DES_ELEM _IN_GEOM	ides if necessary
D3P_DES_DATA_IN_STATE	int/float/vector/t ensordepends	D3P_NUM_DES_ELEM _IN_STATE	var_name, ist, ides if necessary
CPM			
D3P_HAS_CPM_DATA	bool	1	ignore
D3P_CPM_NUM_AIRBAGS	int	1	ignore
D3P_CPM_NUM_PARTICLES	int	1	ignore
D3P_CPM_NUM_GEOM_VAR	int	1	ignore

D3P_CPM_GEOM_VAR_LIST	D3P_VAR	D3P_CPM_NUM_GEOM _VAR	ignore
D3P_CPM_GEOM_DATA	D3P_VAR	D3P_CPM_NUM_GEOM _VAR	ignore
D3P_CPM_NUM_STATE_VAR	int	1	ignore
D3P_CPM_STATE_VAR_LIST	D3P_VAR	D3P_CPM_NUM_STAT E_VAR	ignore
D3P_CPM_STATE_DATA	int/floatdepend s	D3P_CPM_NUM_PART ICLES	var_name, ist
D3P_CPM_NUM_STATE_GEOM_VAR	int	1	ignore
D3P_CPM_STATE_GEOM_VAR_LIST	D3P_VAR	D3P_CPM_NUM_STAT E_GEOM_VAR	ignore
D3P_CPM_STATE_GEOM_DATA	int/floatdepend s	D3P_CPM_NUM_AIRB AGS	var_name, ist
Multisolver			
D3P_HAS_MS_DATA	bool	1	ignore
D3P_MS_NUM_DOMAINS	int	1	ignore
D3P_MS_DOMAIN_ID	int	1	index_multisol ver
D3P_MS_DOMAIN_NAME	char	80	index_multisol ver
D3P_MS_DOMAIN_VAR_NUM	int	1	index_multisol ver
D3P_MS_DOMAIN_VARS_LIST	int	D3P_MS_DOMAIN_VA R_NUM	index_multisol ver
D3P_MS_VAR_NAME	char	80	id_var_multiso lver
D3P_MS_VAR_IS_VECTOR	bool	1	id_var_multiso lver
D3P_MS_VAR_IS_SCALAR	bool	1	id_var_multiso lver
D3P_MS_VAR_IS_TENSOR	bool	1	id_var_multiso lver
D3P_MS_DOMAIN_VAR_LENGTH	int	1	ist, index_multisol

			ver
D3P_MS_DOMAIN_IS_SOLID	bool	1	ist, index_multisol ver
D3P_MS_DOMAIN_IS_SHELL	bool	1	ist, index_multisol ver
D3P_MS_DOMAIN_IS_BEAM	bool	1	ist, index_multisol ver
D3P_MS_DOMAIN_ELEM_NUM_IN_STATE	int	1	ist, index_multisol ver
D3P_MS_SOLID_CONNECTIVITY_MAT_I N_STATE	D3P_Solid	D3P_MS_DOMAIN_EL EM_NUM_IN_STATE	ist, index_multisol ver
D3P_MS_SHELL_CONNECTIVITY_MAT_I N_STATE	D3P_She11	D3P_MS_DOMAIN_EL EM_NUM_IN_STATE	ist, index_multisol ver
D3P_MS_BEAM_CONNECTIVITY_MAT_IN _STATE	D3P_Beam	D3P_MS_DOMAIN_EL EM_NUM_IN_STATE	ist, index_multisol ver
D3P_MS_DOMAIN_NODE_NUM_IN_STATE	int	1	ist, index_multisol ver
D3P_MS_DOMAIN_COORD_IN_STATE	D3P_Vector	D3P_MS_DOMAIN_NO DE_NUM_IN_STATE	ist, index_multisol ver
D3P_MS_DOMAIN_DATA_IN_STATE	float or D3P_Vector or D3P_Tensor	D3P_MS_DOMAIN_VA R_LENGTH	ist, index_multisol ver,id_var_mul tisolver
D3P_MS_DOMAIN_DATA_IS_ON_STRUCT URE_ELEMENT	bool	1	index_multisol ver
D3P_MS_DOMAIN_DATA_IS_ON_MS_NOD_E	bool	1	index_multisol ver
D3P_MS_DOMAIN_DATA_IS_ON_MS_ELE MENT,	bool	1	index_multisol ver

D3P_MS_DOMAIN_IS_FOLLOW_SURFACE _METHOD	bool	1	index_multisol ver
D3P_MS_DOMAIN_NODE_NUM_ONSURFAC E_IN_STATE	int	1	ist, index_multisol ver
D3P_MS_DOMAIN_SURFACE_IDS_IN_ST ATE	int	D3P_MS_DOMAIN_NO DE_NUM_ONSURFACE _IN_STATE	ist, index_multisol ver

How to use

Sample1.cpp

Purpose: obtain resultant displacement for all the nodes and find maximum value.

ist: last.

```
#include "../config.h"
                               /* define DATA_PATH_1 "d3plot/path" */
#include "../d3plotreader.h"
#include <string.h>
#include <math.h>
#include <iostream>
using namespace std;
int main(){
    string d3plot = DATA_PATH_1;
#ifdef WIN32
   string::size_type pos = d3plot.find('/');
   while(pos != string::npos){
       d3plot.replace(pos, 1, "\\");
       pos = d3plot.find('/');
   }
#else
    string::size_type pos = d3plot.find("\\");
   while(pos != string::npos){
       d3plot.replace(pos, 1, '/');
       pos = d3plot.find("\\");
   }
#endif
```

```
D3plotReader dr(d3plot.c_str());
int num_nodes=0;
dr.GetData(D3P_NUM_NODES, (char*)&num_nodes);
int num_states=0;
dr.GetData(D3P NUM STATES, (char*)&num states);
D3P_Parameter param;
param.ist = num_states-1;
D3P_Vector* node_ini_coor = new D3P_Vector[num_nodes];
dr.GetData(D3P NODE INITIAL COORDINATES, (char*)node ini coor);
D3P_Vector* node_coor = new D3P_Vector[num_nodes];
dr.GetData(D3P_NODE_COORDINATES, (char*)node_coor, param);
/* obtain resultant displacement for all nodes
   and find maximum value.
*/
float* node_res_disp = new float[num_nodes];
float disp_x, disp_y, disp_z, tmp;
for(int i=0; i<num_nodes; i++){</pre>
        disp_x = node_coor[i].X()-node_ini_coor[i].X();
        disp_y = node_coor[i].Y()-node_ini_coor[i].Y();
        disp_z = node_coor[i].Z()-node_ini_coor[i].Z();
        tmp = pow(disp_x, 2) + pow(disp_y, 2) + pow(disp_z, 2);
        node_res_disp[i] = pow(tmp, 0.5);
}
float max = node_res_disp[0];
int index=0;
```

```
for(int i=0; i<num_nodes; i++){
    if(max < node_res_disp[i]){
        max = node_res_disp[i];
        index = i;
    }
}

cout<<"Maximum resultant displacement of nodes is: "<<max <<", index is "<<iindex<<endl;
}</pre>
```

Sample2.cpp

Purpose: extract Variable data for Multisolver.

ist: 2

```
#include "../config.h"
                               /* define DATA_PATH_3 "d3plot/path" */
#include "../d3plotreader.h"
#include <string.h>
#include <math.h>
#include <iostream>
using namespace std;
int main() {
      string d3plot = DATA_PATH_3;
#ifdef WIN32
      string::size_type pos = d3plot.find('/');
      while (pos != string::npos) {
             d3plot.replace(pos, 1, "\\");
             pos = d3plot.find('/');
      }
#else
      string::size_type pos = d3plot.find("\\");
      while (pos != string::npos) {
             d3plot.replace(pos, 1, '/');
             pos = d3plot.find("\\");
      }
#endif
      D3plotReader dr_ms(d3plot.c_str());
```

```
bool has_ms_data = false;
dr_ms.GetData(D3P_HAS_MS_DATA, (char*)&has_ms_data);
if(!has_ms_data)
{
       cout << "No Multisolver Data" << endl;</pre>
       return 0;
}
int num_ms_datasets = 0;
dr_ms.GetData(D3P_MS_NUM_DOMAINS, (char*)&num_ms_datasets);
D3P_Parameter para;
int* domain_var_ids;
for (int dataset = 0; dataset < num_ms_datasets; dataset++)</pre>
{
       para.index_multisolver = dataset;
       int domain_var_num = 0;
       dr_ms.GetData(
              D3P_MS_DOMAIN_ID, (char*)& domain_var_num, para
       );
       domain_var_ids = new int[domain_var_num];
       dr_ms.GetData(
              D3P_MS_DOMAIN_VARS_LIST, (char*)domain_var_ids, para
       );
       para.ist = 2;
       for (int var = 0; var < domain_var_num; var++)</pre>
       {
              para.id_var_multisolver = domain_var_ids[var];
```

```
int sizevar = 0;
dr_ms.GetData(
      D3P_MS_DOMAIN_VAR_LENGTH, (char*)& sizevar, para
);
bool is_scalar = false;
bool is_vector = false;
bool is_tensor = false;
dr_ms.GetData(
      D3P_MS_VAR_IS_SCALAR, (char*)& is_scalar, para
);
dr_ms.GetData(
      D3P_MS_VAR_IS_VECTOR, (char*)& is_vector, para
);
dr_ms.GetData(
      D3P_MS_VAR_IS_TENSOR, (char*)& is_tensor, para
);
if (is_scalar)
{
      float *value = new float[sizevar];
      dr_ms.GetData(
              D3P_MS_DOMAIN_DATA_IN_STATE, (char*)value, para
       );
       cout << "Value type: scalar, value[0]=" << value[0]</pre>
               << endl;
       delete[] value;
}
if (is_vector)
{
```

```
float maxvalue = -1.0e20;
                             D3P_Vector *value = new D3P_Vector[sizevar];
                             dr_ms.GetData(
                                    D3P_MS_DOMAIN_DATA_IN_STATE, (char*)value, para
                             );
                             cout << "Value type: vector, value[0].X()="</pre>
                                     << value[0].X() << endl;</pre>
                             delete[] value;
                      }
                      if (is_tensor)
                      {
                             D3P_Tensor *value = new D3P_Tensor[sizevar];
                             dr_ms.GetData(
                                    D3P_MS_DOMAIN_DATA_IN_STATE, (char*)value, para
                             );
                             cout << "Value type: tensor, value[0].X()"</pre>
                                     << value[0].X() << endl;</pre>
                             delete[] value;
                     }
              }
       }
       delete[] domain_var_ids;
}
```

Python

API Functions(Recommended)

```
class D3plotReader():
    def __init__(self, path):
         pass
    Purpose: Constructor.
    ❖ Input: path: d3plot name.
    ❖ Return: D3plotReader object.
      Example: dr = D3plotReader("d3plot/file/path")
    def get_data(self, type, param):
        pass
    Purpose: Extract data.
    ❖ Input: type: type - enum the data variables' name in d3plot.
                      structure of description which is the advance setting for
            param:
                      getting special data in d3plot.
    * Return: data.
      Example:
            dr = D3plotReader("d3plot/file/path")
            p = D3P_Parameter()
            p.ist = 11
            p.ipt = 0
            shell_stress = dr.get_data(DataType.D3P_SHELL_STRESS, p)
      Or
            dr = D3plotReader("d3plot/file/path")
```

```
shell_stress = dr.get_data(

DataType.D3P_SHELL_STRESS, ist=11, ipt=0
)
```

API Functions (Deprecated)

```
class D3plotReader():
    def init (self, path):
          pass
    ❖ Purpose: Constructor.
    ❖ Input: path: d3plot name.
    ❖ Return: D3plotReader object.
      Example:dr = D3plotReader("d3plot/file/path")
    def GetDataInt(self, type, param):
         pass
      Deprecated. Use the get_data(...) instead.
    ❖ Purpose: Get an integer value.
    ❖ Input: type - enum the data variables' name in d3plot.
             Param - structure of description which is the advance setting for
      getting special data in d3plot.
    ❖ Return: int
    def GetDataFloat(self, type, param):
         pass
      Deprecated. Use the get_data(...) instead.
    ❖ Purpose: Get a float value.
    ❖ Input: type - enum the data variables' name in d3plot.
             param - structure of description which is the advance setting for
      getting special data in d3plot.
    ❖ Return: float.
```

```
def GetDataString(self, type, param):
    pass
  Deprecated. Use the get_data(...) instead.
❖ Purpose: Get a string value.
❖ Input: type - enum the data variables' name in d3plot.
         param - structure of description which is the advance setting for
  getting special data in d3plot.
* Return: string.
def GetDataIntArray(self, type, param):
    pass
  Deprecated. Use the get_data(...) instead.
❖ Purpose: Get a int array.
❖ Input: type - enum the data variables' name in d3plot.
         param - structure of description which is the advance setting for
  getting special data in d3plot.
A Return: int array.
def GetDataFloatArray(self, type, param):
    pass
  Deprecated. Use the get_data(...) instead.
❖ Purpose: Get a float array.
```

❖ Input: type - enum the data variables' name in d3plot.

param - structure of description which is the advance setting for getting special data in d3plot.

❖ Return: float array.

```
def GetDataVectorArray(self, type, param):
    pass
  Deprecated. Use the get_data(...) instead.
Purpose: Get a vector array.
❖ Input: type - enum the data variables' name in d3plot.
         param - structure of description which is the advance setting for
  getting special data in d3plot.
❖ Return: vector array.
def GetDataTensorArray(self, type, param):
    pass
  Deprecated. Use the get_data(...) instead.
❖ Purpose: Get a tensor array.
❖ Input: type - enum the data variables' name in d3plot.
         param - structure of description which is the advance setting for
  getting special data in d3plot.
❖ Return: tensor array.
def GetDataSolidArray(self):
    pass
  Deprecated. Use the get_data(...) instead.
❖ Purpose: Get solid elements array.
❖ Return: solid elements array.
```

def GetDataTshellArray(self):

pass

Deprecated. Use the get_data(...) instead.

- ❖ Purpose: Get tshell elements array.
- ❖ Return: tshell elements array.

def GetDataBeamArray(self):

pass

Deprecated. Use the get_data(...) instead.

- ❖ Purpose: Get beam elements array.
- ❖ Return: beam elements array.

def GetDataShellArray(self):

pass

Deprecated. Use the get_data(...) instead.

- Purpose: Get shell elements array.
- ❖ Return: shell elements array.

def GetDataSphArray(self):

pass

Deprecated. Use the get_data(...) instead.

- ❖ Purpose: Get sph elements array.
- ❖ Return: sph elements array.

D3P_Parameter

parameter to call D3plotReader::get_data*, only specific those member variables you are interested, otherwise, ignore this.

```
class D3P_Parameter:
    def __init__(self):
        self.ist = -1
        self.ipt = -1
        self.ipart = -1
        self.i rigid wall = -1
        self.ides = -1
        self.ihv = -1
        self.index multisolver = -1
        self.id_var_multisolver = -1
        self.var name = ""
1.
      ist: Specify the state number, starting from 0, as follows:
      shell_thickness = dr.get_data(DataType.D3P_SHELL_THICKNESS, ist=11)
      0r
      p = D3P_Parameter()
      p.ist = 11
      shell_thickness = dr.get_data(DataType.D3P_SHELL_THICKNESS, p)
2.
      ipt: Specify the integration point, ranging in [0, MAXINT), as follows:
      shell_stress = dr.get_data(DataType.D3P_SHELL_STRESS, ist=11, ipt=0)
      0r
      p = D3P_Parameter()
      p.ist = 11
      p.ipt = 0
```

```
shell stress = dr.get data(DataType.D3P SHELL STRESS, p)
3.
      ipart: Specify the index of part, starting from 0, as follows:
      part name = dr.get data(DataType.D3P PART NAME, ipart=0)
      0r
      p = D3P_Parameter()
      p.ipart = 0
      part_name = dr.get_data(DataType.D3P_PART_NAME, p)
4.
      i_rigid_wall: Specify the index of rigid wall, starting from 0, as follows:
      r_wall_f = dr.get_data(
             DataType.D3P_RIGID_WALL_FORCE, ist=11, i_rigid_wall=0
      )
      0r
      p = D3P_Parameter()
      p.ist = 11
      p.i_rigid_wall = 0
      r wall f = dr.get data(DataType.D3P RIGID WALL FORCE, p)
5.
      ides: Specify the index of the des data, starting from 0, as follows:
      num des = dr.get data(DataType.D3P NUM DES PART IN GEOM, ides=0)
      0r
      p = D3P_Parameter()
      p.ides = 0
      num_des = dr.get_data(DataType.D3P_NUM_DES_PART_IN_GEOM, p)
6.
      ihv: Specify the index of history variables, starting from 0, as follows:
      solid_hsvar = dr.get_data(
             DataType.D3P_SOLID_HISTORY_VAR, ist=11, ipt=0, ihv=5
      )
      0r
```

```
p = D3P_Parameter()
p.ist = 11
p.ipt = 0
p.ihv = 5
solid_hsvar = dr.get_data(DataType.D3P_SOLID_HISTORY_VAR, p)
```

7. **index_multisolver**: Specify the index of the multisolver domain, start from 0 and default is 0 also:

```
ms_id = dr.get_data(DataType.D3P_MS_DOMAIN_ID, index_multisolver=0)
Or
p = D3P_Parameter()
p.index_multisolver = 0
ms_id = dr.get_data(DataType.D3P_MS_DOMAIN_ID, p)
```

8. **id_var_multisolver**: Specify the index of the multisolver var, start from 0 and default is 0 also:

```
ms_varn = dr.get_data(DataType.D3P_MS_VAR_NAME, id_var_multisolver=0)
Or
p = D3P_Parameter()
p.id_var_multisolver = 0
ms_varn = dr.get_data(DataType.D3P_MS_VAR_NAME, p)
```

9. **var_name**: Specify name of output variables, currently used by DES and CPM data, default is empty

```
cpm_geodt = dr.get_data(DataType.D3P_CPM_GEOM_DATA, var_name='cpm1')
Or
p = D3P_Parameter()
p.var_name = 'cpm1'
cpm_geodt = dr.get_data(DataType.D3P_CPM_GEOM_DATA, p)
```

DataType

```
class D3P_Vector():
    def x(self):
        pass
    def y(self):
        pass
    def z(self):
        pass
class D3P_VectorDouble():
    def x(self):
        pass
    def y(self):
        pass
    def z(self):
        pass
class D3P_Tensor():
    def x(self):
        pass
    def y(self):
        pass
    def z(self):
        pass
    def xy(self):
        pass
```

```
def yz(self):
        pass
    def zx(self):
        pass
class D3P_Solid():
    def node(self, index):
        pass
    def mat(self):
        pass
class D3P_Tshell():
    def node(self, index):
        pass
    def mat(self):
        pass
class D3P_Beam():
    def node(self, index):
        pass
    def mat(self):
        pass
class D3P_Shell():
    def node(self, index):
        pass
    def mat(self):
```

```
pass
class D3P_Sph():
    def id(self):
        pass
    def mat(self):
        pass
class D3P_Var():
    def type(self):
        pass
    def name(self):
        pass
class D3P_Des():
    def id(self):
        pass
    def mat(self):
        pass
    def radius(self):
        pass
    def mass(self):
        pass
    def inertia(self):
        pass
```

name	conversion	length	paramete rs
D3P_NUM_STATES	int	1	ignore
D3P_TIMES	float	D3P_NUM_STATES	ignore
D3P_TITLE	Char		ignore
Global			
D3P_GLOBAL_KINETIC_ENERGY	float	1	ist
D3P_GLOBAL_INTERNAL_ENERGY	float	1	ist
D3P_GLOBAL_TOTAL_ENERGY	float	1	ist
D3P_GLOBAL_VELOCITY	D3P_Vector	1	ist
Part			
D3P_NUM_PARTS	int	1	ignore
D3P_PART_IDS	int	D3P_NUM_PARTS	ignore
D3P_PART_NAME	char	80	ipart
D3P_PART_INTERNAL_ENERGY	float	1	ist, ipart
D3P_PART_KINETIC_ENERGY	float	1	ist, ipart
D3P_PART_VELOCITY	D3P_Vector	1	ist, ipart
D3P_PART_MASS	float	1	ist, ipart
D3P_PART_HOURGLASS	float	1	ist, ipart
RIGID WALL			
D3P_NUM_RIGID_WALL	int	1	ignore
D3P_RIGID_WALL_FORCE	float	1	ist, i_rigid_wal l
D3P_RIGID_WALL_POSITION	D3P_Vector	1	ist, i_rigid_wal l
NODE			
D3P_NUM_NODES	int	1	ignore
D3P_NODE_INITIAL_COORDINATES	D3P_Vector	D3P_NUM_NODES	ignore
D3P_NODE_IDS	int	D3P_NUM_NODES	ignore
D3P_NODE_TEMPERATURE	float	D3P_NUM_NODES	ist
D3P_NODE_COORDINATES	D3P_Vector	D3P_NUM_NODES	ist
D3P_NODE_VELOCITIES	D3P_Vector	D3P_NUM_NODES	ist
D3P_NODE_ACCELERATIONS	D3P_Vector	D3P_NUM_NODES	ist
D3P_NODE_COORDINATES_DOUBLE	D3P_VectorDoub le	D3P_NUM_NODES	ist

D3P_NODE_VELOCITIES_DOUBLE	D3P_VectorDoub le	D3P_NUM_NODES	ist
D3P_NODE_ACCELERATIONS_DOUBLE	D3P_VectorDoub le	D3P_NUM_NODES	ist
SOLID			
D3P_NUM_SOLID	int	1	ignore
D3P_SOLID_MAXINT	int	1	ignore
D3P_SOLID_CONNECTIVITY_MAT	D3P_Solid	D3P_NUM_SOLID	ignore
D3P_SOLID_IDS	int	D3P_NUM_SOLID	ignore
D3P_SOLID_STRESS	D3P_Tensor	D3P_NUM_SOLID	ist, ipt if necessary
D3P_SOLID_EFFECTIVE_PLASTIC_STRA IN	float	D3P_NUM_SOLID	ist, ipt if necessary
D3P_SOLID_STRAIN	D3P_Tensor	D3P_NUM_SOLID	ist, ipt if necessary
D3P_SOLID_HISTORY_VAR	float	D3P_NUM_SOLID	ist, ipt, ihv
TSHELL			
D3P_NUM_TSHELL	int	1	ignore
D3P_TSHELL_MAXINT	int	1	ignore
D3P_TSHELL_CONNECTIVITY_MAT	D3P_Tshell	D3P_NUM_TSHELL	ignore
D3P_TSHELL_IDS	int	D3P_NUM_TSHELL	ignore
D3P_TSHELL_STRESS	D3P_Tensor	D3P_NUM_TSHELL	ist, ipt
D3P_TSHELL_EFFECTIVE_PLASTIC_STR AIN	float	D3P_NUM_TSHELL	ist, ipt
D3P_TSHELL_STRAIN	D3P_Tensor	D3P_NUM_TSHELL	ist, ipt
D3P_TSHELL_HISTORY_VAR	float	D3P_NUM_TSHELL	ist, ipt, ihv
BEAM			
D3P_NUM_BEAM	int	1	ignore
D3P_BEAM_MAXINT	int	1	ignore

D3P_BEAM_CONNECTIVITY_THIRD_MAT	D3P_Beam	D3P_NUM_BEAM	ignore
D3P_BEAM_IDS	int	D3P_NUM_BEAM	ignore
D3P_BEAM_AXIAL_FORCE	float	D3P_NUM_BEAM	ist
D3P_BEAM_S_SHEAR_RESULTANT	float	D3P_NUM_BEAM	ist
D3P_BEAM_T_SHEAR_RESULTANT	float	D3P_NUM_BEAM	ist
D3P_BEAM_S_BENDING_MOMENT	float	D3P_NUM_BEAM	ist
D3P_BEAM_T_BENDING_MOMENT	float	D3P_NUM_BEAM	ist
D3P_BEAM_TORSIONAL_RESULTANT	float	D3P_NUM_BEAM	ist
D3P_BEAM_RS_SHEAR_STRESS	float	D3P_NUM_BEAM	ist, ipt
D3P_BEAM_TR_SHEAR_STRESS	float	D3P_NUM_BEAM	ist, ipt
D3P_BEAM_AXIAL_STRESS	float	D3P_NUM_BEAM	ist, ipt
D3P_BEAM_AXIAL_PLASTIC_STRAIN	float	D3P_NUM_BEAM	ist, ipt
D3P_BEAM_AXIAL_STRAIN	float	D3P_NUM_BEAM	ist, ipt
D3P_BEAM_HISTORY_VAR	float	D3P_NUM_BEAM	ist, ipt, ihv
SHELL			
D3P_NUM_SHELL	int	1	ignore
D3P_SHELL_MAXINT	int	1	ignore
D3P_SHELL_CONNECTIVITY_MAT	D3P_She11	D3P_NUM_SHELL	ignore
D3P_SHELL_IDS	int	D3P_NUM_SHELL	ignore
D3P_SHELL_STRESS	D3P_Tensor	D3P_NUM_SHELL	ist, ipt
D3P_SHELL_EFFECTIVE_PLASTIC_STRA IN	float	D3P_NUM_SHELL	ist, ipt
D3P_SHELL_STRAIN	D3P_Tensor	D3P_NUM_SHELL	ist, ipt
D3P_SHELL_HISTORY_VAR	float	D3P_NUM_SHELL	ist, ipt, ihv
D3P_SHELL_MX	float	D3P_NUM_SHELL	ist
D3P_SHELL_MY	float	D3P_NUM_SHELL	ist
D3P_SHELL_MXY	float	D3P_NUM_SHELL	ist
D3P_SHELL_QX	float	D3P_NUM_SHELL	ist

D3P_SHELL_QY	float	D3P_NUM_SHELL	ist
D3P_SHELL_NX	float	D3P_NUM_SHELL	ist
D3P_SHELL_NY	float	D3P_NUM_SHELL	ist
D3P_SHELL_NXY	float	D3P_NUM_SHELL	ist
DELETION			
D3P_HAS_DELETION	bool	1	ist
D3P_SOLID_DELETION	float	D3P_NUM_SOLID	ist
D3P_TSHELL_DELETION	float	D3P_NUM_TSHELL	ist
D3P_SHELL_DELETION	float	D3P_NUM_SHELL	ist
D3P_BEAM_DELETION	float	D3P_NUM_BEAM	ist
SPH			
D3P_NUM_SPH	int	1	ignore
D3P_SPH_NODE_MAT	D3P_Sph	D3P_NUM_SPH	ignore
D3P_SPH_RADIUS	float	D3P_NUM_SPH	ist
D3P_SPH_PRESSURE	float	D3P_NUM_SPH	ist
D3P_SPH_STRESS	D3P_Tensor	D3P_NUM_SPH	ist
D3P_SPH_PLASTIC_STRAIN	float	D3P_NUM_SPH	ist
D3P_SPH_DENSITY	float	D3P_NUM_SPH	ist
D3P_SPH_INTERNAL_ENERGY	float	D3P_NUM_SPH	ist
D3P_SPH_NUMBER_OF_PARTICLE_NEIGH BORS	int	D3P_NUM_SPH	ist
D3P_SPH_STRAIN	D3P_Tensor	D3P_NUM_SPH	ist
D3P_SPH_MASS	float	D3P_NUM_SPH	ist
DES			
D3P_HAS_DES_DATA	bool	1	ignore
D3P_NUM_DES_DATA	int	1	ignore
D3P_NUM_DES_PART_IN_GEOM	int	1	ides if necessary
D3P_NUM_DES_ELEM_IN_GEOM	int	1	ides if necessary

D3P_NUM_DES_PART_IN_STATE	int	1	ides if
			necessary
D3P_NUM_DES_ELEM_IN_STATE	int	1	ides if
			necessary
D3P_NUM_DES_PART_VAR_IN_GEOM	int	1	ides if necessary
DOD DEG DADE HAD A TOW THE OPEN	Don W	DOD WIN DEG DADE W	
D3P_DES_PART_VAR_LIST_IN_GEOM	D3P_Var	D3P_NUM_DES_PART_VA R_IN_GEOM	ides if necessary
D3P NUM DES ELEM VAR IN GEOM	int	1	ides if
201223_222			necessary
D3P_DES_ELEM_VAR_LIST_IN_GEOM	D3P_Var	D3P_NUM_DES_ELEM_VA	ides if
		R_IN_GEOM	necessary
D3P_NUM_DES_PART_VAR_IN_STATE	int	1	ides if
			necessary
D3P_DES_PART_VAR_LIST_IN_STATE	D3P_Var	D3P_NUM_DES_PART_VA R_IN_STATE	ides if necessary
DOD NAME DEG EVEN AND TAX OWNED			
D3P_NUM_DES_ELEM_VAR_IN_STATE	int	1	ides if necessary
D3P DES ELEM VAR LIST IN STATE	D3P_Var	D3P NUM DES ELEM VA	ides if
DOI _DEG_BBBM_VMN_BIOI_IN_GIMIE	Dol_val	R_IN_STATE	necessary
D3P_DES_NODAL_MAT_RADIUS_MASS_IN	D3P_Des	D3P_NUM_DES_ELEM_IN	ides if
ERTIA		_GEOM	necessary
D3P_DES_DATA_IN_STATE	<pre>int/float/vect or/tensordep</pre>	D3P_NUM_DES_ELEM_IN	var_name,
	ends	_STATE	ist, ides if
			necessary
СРМ			
D3P_HAS_CPM_DATA	bool	1	ignore
D3P_CPM_NUM_AIRBAGS	int	1	ignore
D3P_CPM_NUM_PARTICLES	int	1	ignore
D3P_CPM_NUM_GEOM_VAR	int	1	ignore
D3P_CPM_GEOM_VAR_LIST	D3P_Var	D3P_CPM_NUM_GEOM_VA	ignore
		R	
D3P_CPM_GEOM_DATA	D3P_Var	D3P_CPM_NUM_GEOM_VAR	ignore

D3P_CPM_NUM_STATE_VAR	int	1	ignore
D3P_CPM_STATE_VAR_LIST	D3P_Var	D3P_CPM_NUM_STATE_V AR	ignore
D3P_CPM_STATE_DATA	int/floatde pends	D3P_CPM_NUM_PARTICL ES	var_name,
D3P_CPM_NUM_STATE_GEOM_VAR	int	1	ignore
D3P_CPM_STATE_GEOM_VAR_LIST	D3P_Var	D3P_CPM_NUM_STATE_G EOM_VAR	ignore
D3P_CPM_STATE_GEOM_DATA	int/floatde pends	D3P_CPM_NUM_AIRBAGS	var_name,
Multisolver			
D3P_HAS_MS_DATA	bool	1	ignore
D3P_MS_NUM_DOMAINS	int	1	ignore
D3P_MS_DOMAIN_ID	int	1	index_multi solver
D3P_MS_DOMAIN_NAME	char	80	index_multi solver
D3P_MS_DOMAIN_VAR_NUM	int	1	index_multi solver
D3P_MS_DOMAIN_VARS_LIST	int	D3P_MS_DOMAIN_VAR_N UM	index_multi solver
D3P_MS_VAR_NAME	char	80	id_var_mult isolver
D3P_MS_VAR_IS_VECTOR	bool	1	id_var_mult isolver
D3P_MS_VAR_IS_SCALAR	bool	1	id_var_mult isolver
D3P_MS_VAR_IS_TENSOR	bool	1	id_var_mult isolver
D3P_MS_DOMAIN_VAR_LENGTH	int	1	ist, index_multi solver
D3P_MS_DOMAIN_IS_SOLID	bool	1	ist, index_multi solver

D3P MS DOMAIN IS SHELL	bool	1	ist,
DOI_MO_DOMNIN_IO_DIEDE	5001		index multi
			solver
DOD NO DOWLTY TO DRAW			
D3P_MS_DOMAIN_IS_BEAM	bool	1	ist, index multi
			solver
			Solvei
D3P_MS_DOMAIN_ELEM_NUM_IN_STATE	int	1	ist,
			index_multi
			solver
D3P_MS_SOLID_CONNECTIVITY_MAT_IN	D3P_Solid	D3P MS DOMAIN ELEM	ist,
_STATE	D31_5011u	NUM_IN_STATE	index_multi
			solver
D3P_MS_SHELL_CONNECTIVITY_MAT_IN	D3P_She11	D3P_MS_DOMAIN_ELEM_	ist,
_STATE		NUM_IN_STATE	index_multi solver
			Solvei
D3P_MS_BEAM_CONNECTIVITY_MAT_IN_	D3P_Beam	D3P_MS_DOMAIN_ELEM_	ist,
STATE		NUM_IN_STATE	index_multi
			solver
D3P MS DOMAIN NODE NUM IN STATE	int	1	ist,
			index multi
			solver
DOD MC DOMAIN COORD IN CTATE	DOD W	DOD MC DOMAIN NODE	. ,
D3P_MS_DOMAIN_COORD_IN_STATE	D3P_Vector	D3P_MS_DOMAIN_NODE_ NUM_IN_STATE	ist, index multi
		Nom_IN_OTHIE	solver
D3P_MS_DOMAIN_DATA_IN_STATE	float or	D3P_MS_DOMAIN_VAR_L	ist,
	D3P_Vector or	ENGTH	index_multi
	D3P_Tensor		solver,id_v ar_multisol
			ver
D3P_MS_DOMAIN_DATA_IS_ON_STRUCTU	bool	1	index_multi
RE_ELEMENT			solver
D3P MS DOMAIN DATA IS ON MS NODE	bool	1	index multi
			solver
	1 1	1	
D3P_MS_DOMAIN_DATA_IS_ON_MS_ELEM	bool	1	index_multi solver
ENT,			201vet.
DOD MC DOMAIN IS DOLLOW SUBPLICE	1 1	1	2-1
D3P_MS_DOMAIN_IS_FOLLOW_SURFACE_ METHOD	bool	1	index_multi solver
METHOD			201761
D3P_MS_DOMAIN_NODE_NUM_ONSURFACE	int	1	ist,
_IN_STATE			index_multi

			solver
D3P_MS_DOMAIN_SURFACE_IDS_IN_STA TE	int	D3P_MS_DOMAIN_NODE_ NUM_ONSURFACE_IN_ST ATE	ist, index_multi solver

How to use

Sample1.py

Purpose: obtain resultant displacement for all the nodes and find maximum value.

3D scatterplot(x=shell_nodes_x, y=shell_nodes_y, z=shell_nodes_z, c=resultant displacement of shell nodes)

ist: last.

```
from lsreader import D3plotReader, DataType as dt
import os
import matplotlib.pyplot as plt
from mpl_toolkits import mplot3d
from math import pow
d3plot = os.path.join(os.getcwd(), 'd3plot')
dr = D3plotReader(d3plot)
num states = dr.get data(dt.D3P NUM STATES)
nodes_init_coor = dr.get_data(
   dt.D3P NODE INITIAL COORDINATES, ist=num states-1
)
nodes_coor = dr.get_data(dt.D3P_NODE_COORDINATES, ist=num_states-1)
# obtain resultant displacement for all nodes and find maximum
nodes_res_disp = []
for i in range(nodes_coor.__len__()):
   disp_x = nodes_coor[i].x() - nodes_init_coor[i].x()
   disp_y = nodes_coor[i].y() - nodes_init_coor[i].y()
   disp_z = nodes_coor[i].z() - nodes_init_coor[i].z()
```

```
tmp = pow(disp_x, 2) + pow(disp_y, 2) + pow(disp_z, 2)
   nodes_res_disp.append(pow(tmp, 0.5))
print(
Maximum resultant displacement of nodes is: {0}, index is: {1}
""".format(
   max(nodes res disp), nodes res disp.index(max(nodes res disp))
   )
)
# nodes coordinates of shell elements when ist=last
shells = dr.get_data(dt.D3P_SHELL_CONNECTIVITY_MAT)
nodes_shell = []
for shell in shells:
   nodes_shell.append(shell.node(0))
   nodes_shell.append(shell.node(1))
   nodes_shell.append(shell.node(2))
   nodes_shell.append(shell.node(3))
nodes_shell = list(set(nodes_shell))
nodes_shell.sort()
nodes_x, nodes_y, nodes_z, res = [], [], [], []
for node_shell in nodes_shell:
   nodes_x.append(nodes_coor[node_shell-1].x())
   nodes_y.append(nodes_coor[node_shell-1].y())
   nodes_z.append(nodes_coor[node_shell-1].z())
   res.append(nodes_res_disp[node_shell-1])
```

```
# plotting
fig = plt.figure()
ax = fig.add_subplot(1, 1, 1, projection='3d')
scat = ax.scatter3D(
    nodes_x, nodes_y, nodes_z, c=res, s=15,
)
fig.colorbar(scat, label='Resultant Displacement')
ax.set_zlim3d(-50, 50)
plt.show()
```

Sample2.py

Purpose: extract Variable data for Multisolver.

State: 2

```
import lsreader
from lsreader import D3plotReader
from lsreader import DataType as dt
from lsreader import D3P_Parameter as dp
import os
d3plot = os.path.join(os.getcwd(), 'd3plot')
dr = D3plotReader(d3plot)
has_ms_data = dr.get_data(dt.D3P_HAS_MS_DATA)
if not has_ms_data:
   print("No Multisolver Data")
num ms datasets = dr.get data(dt.D3P MS NUM DOMAINS)
for dataset in range(num_ms_datasets):
   domain_var_ids = dr.get_data(dt.D3P_MS_DOMAIN_VARS_LIST, index_multiso
lver=dataset)
   for var in range(domain_var_ids.__len__()):
        sizevar = dr.get_data(dt.D3P_MS_DOMAIN_VAR_LENGTH, index_multisolv
er=dataset, ist=2)
        is_scalar = dr.get_data(dt.D3P_MS_VAR_IS_SCALAR, id_var_multisolve
r=domain_var_ids[var])
        is_vector = dr.get_data(dt.D3P_MS_VAR_IS_VECTOR, id_var_multisolve
r=domain var ids[var])
```

```
is_tensor = dr.get_data(dt.D3P_MS_VAR_IS_TENSOR, id_var_multisolve
r=domain var ids[var])
       p = dp()
       p.ist=2
       p.index_multisolver = dataset
       p.id_var_multisolver = domain_var_ids[var]
       if is_scalar:
            svalue = dr.get_data(dt.D3P_MS_DOMAIN_DATA_IN_STATE, p)
            print("Value type: scalar, value[0]={}".format(svalue[0]))
       if is_vector:
            vvalue = dr.get_data(dt.D3P_MS_DOMAIN_DATA_IN_STATE, p)
            print(
                   "Value type: vector, value[0].X()={}"
                   .format(vvalue[0].x())
            )
        if is_tensor:
            tvalue = dr.get_data(dt.D3P_MS_DOMAIN_DATA_IN_STATE, p)
            print(
                   "Value type: tensor, value[0].X()={}"
                   .format(tvalue[0].x())
            )
```

C

API Functions

```
char* D3P_Open (const char* filename);
    ❖ Purpose: Open the d3plot file.
    ❖ Input: filename - d3plot name.
    ❖ Return: The pointer to the d3plot.
       D3P_Read (char* handle, enum D3P DataType type, char* value,
int
_D3P_Parameter param);
    ❖ Purpose: Get value of the special data varialbe.
    ❖ Input: handle - the pointer to the d3plot
             type - enum the data variables's name in d3plot.
             value - store the return value.
             param - structure of description which is the advance setting for
             getting special data in d3plot.
    A Return: void.
void D3P_Close(char* handle);
    ❖ Purpose: Close the d3plot file.
    ❖ Input: handle - the pointer to the d3plot
    ❖ Return: void
```

_D3P _Parameter

```
typedef struct _D3P_Parameter_
{
    int ist;
    int ipt;
    int ipart;
    int i_rigid_wall;
    int ides;
    int ihv;
    int index_multisolver;
    int id_var_multisolver;
    const char* var_name;
} _D3P_Parameter;
```

1. **ist**: Specify the state number, starting from 0, as follows:

```
_D3P_Parameter dp;
dp.ist = 11;
dp.ipt = 0;
D3P_Read(handle, D3P_BEAM_AXIAL_STRESS, (char*)beam_axial_stress, dp);
```

2. **ipt**: Specify the integration point, ranging in [0, MAXINT), as follows:

```
_D3P_Parameter dp;
dp.ipt = 0;
...
```

3. **ipart**: Specify the index of part, starting from 0, as follows:

```
_D3P_Parameter dp;
dp.ipart = 0;
...
```

4. **i_rigid_wall**: Specify the index of rigid wall, starting from 0, as follows:

```
_D3P_Parameter dp;
```

```
dp.i_rigid_wall = 0;
```

5. **ides**: Specify the index of the des data, starting from 0, as follows:

```
_D3P_Parameter dp;
dp.ides = 0;
```

6. **ihv**: Specify the index of history variables, starting from 0, as follows:

```
_D3P_Parameter dp;
dp.ihv = 0;
```

7. **index_multisolver**: Specify the index of the multisolver domain, start from 0 and default is 0 also:

```
_D3P_Parameter dp;
dp.index_multisolver = 0;
```

8. **id_var_multisolver**: Specify the index of the multisolver var, start from 0 and default is 0 also:

```
_D3P_Parameter dp;
dp.id_var_multisolver = 0;
```

9. **var_name**: Specify name of output variables, currently used by DES and CPM data, default is empty

```
_D3P_Parameter dp;
dp.var_name = "";
...
```

DataType

```
typedef struct _D3P_Vector_
{
      float v[3];
} _D3P_Vector;
typedef struct D3P_VectorDouble_
{
      double v[3];
} _D3P_VectorDouble;
typedef struct _D3P_Tensor_
{
      float t[6];
} _D3P_Tensor;
typedef struct _D3P_Solid_
{
      int conn[10];
      int mat;
} _D3P_Solid;
typedef struct _D3P_Tshell_
{
      int conn[10];
      int mat;
} _D3P_Tshell;
typedef struct _D3P_Beam_
{
```

```
int conn[2];
      int third;
      int w_int;
      int h_int;
      int mat;
} _D3P_Beam;
typedef struct _D3P_Shell_
{
      int conn[4];
      int mat;
} _D3P_Shell;
typedef struct _D3P_Sph
{
      int id;
      unsigned int mat;
} _D3P_Sph;
typedef struct _D3P_Var_
{
   int type;
   char name[8];
} _D3P_Var;
typedef struct _D3P_Des_
{
      int id;
      int mat;
      float radius;
      float mass;
```

```
float inertia;
} _D3P_Des;

typedef struct _D3P_AirbagInfo_
{
    int bagid;
    int startn;
    int npart;
    int ngas;
    int nchamber;
} _D3P_AirbagInfo;
```

name	conversion	length	parameters
D3P_NUM_STATES	int	1	ignore
D3P_TIMES	float	D3P_NUM_STATES	ignore
D3P_TITLE	Char		ignore
Global			
D3P_GLOBAL_KINETIC_ENERGY	float	1	ist
D3P_GLOBAL_INTERNAL_ENERGY	float	1	ist
D3P_GLOBAL_TOTAL_ENERGY	float	1	ist
D3P_GLOBAL_VELOCITY	_D3P_Vector	1	ist
Part			
D3P_NUM_PARTS	int	1	ignore
D3P_PART_IDS	int	D3P_NUM_PARTS	ignore
D3P_PART_NAME	char	80	ipart
D3P_PART_INTERNAL_ENERGY	float	1	ist, ipart
D3P_PART_KINETIC_ENERGY	float	1	ist, ipart
D3P_PART_VELOCITY	_D3P_Vector	1	ist, ipart
D3P_PART_MASS	float	1	ist, ipart
D3P_PART_HOURGLASS	float	1	ist, ipart
RIGID WALL			
D3P_NUM_RIGID_WALL	int	1	ignore
D3P_RIGID_WALL_FORCE	float	1	ist,
			i_rigid_wall
D3P_RIGID_WALL_POSITION	_D3P_Vector	1	ist,

			i_rigid_wall
NODE			
D3P_NUM_NODES	int	1	ignore
D3P_NODE_INITIAL_COORDINATES	_D3P_Vector	D3P_NUM_NODES	ignore
D3P_NODE_IDS	int	D3P_NUM_NODES	ignore
D3P_NODE_TEMPERATURE	float	D3P_NUM_NODES	ist
D3P_NODE_COORDINATES	_D3P_Vector	D3P_NUM_NODES	ist
D3P_NODE_VELOCITIES	_D3P_Vector	D3P_NUM_NODES	ist
D3P_NODE_ACCELERATIONS	_D3P_Vector	D3P_NUM_NODES	ist
D3P_NODE_COORDINATES_DOUBLE	_D3P_VectorDouble	D3P_NUM_NODES	ist
D3P_NODE_VELOCITIES_DOUBLE	_D3P_VectorDouble	D3P_NUM_NODES	ist
D3P_NODE_ACCELERATIONS_DOUBLE	_D3P_VectorDouble	D3P_NUM_NODES	ist
SOLID			
D3P_NUM_SOLID	int	1	ignore
D3P_SOLID_MAXINT	int	1	ignore
D3P_SOLID_CONNECTIVITY_MAT	_D3P_Solid	D3P_NUM_SOLID	ignore
D3P_SOLID_IDS	int	D3P_NUM_SOLID	ignore
D3P_SOLID_STRESS	_D3P_Tensor	D3P_NUM_SOLID	ist, ipt if necessary
D3P_SOLID_EFFECTIVE_PLASTIC_STR AIN	float	D3P_NUM_SOLID	ist, ipt if necessary
D3P_SOLID_STRAIN	_D3P_Tensor	D3P_NUM_SOLID	ist, ipt if necessary
D3P_SOLID_HISTORY_VAR	float	D3P_NUM_SOLID	ist, ipt, ihv
TSHELL			
D3P_NUM_TSHELL	int	1	ignore
D3P_TSHELL_MAXINT	int	1	ignore
D3P_TSHELL_CONNECTIVITY_MAT	_D3P_Tshe11	D3P_NUM_TSHELL	ignore
D3P_TSHELL_IDS	int	D3P_NUM_TSHELL	ignore

D3P_TSHELL_STRESS	_D3P_Tensor	D3P_NUM_TSHELL	ist, ipt
D3P_TSHELL_EFFECTIVE_PLASTIC_ST RAIN	float	D3P_NUM_TSHELL	ist, ipt
D3P_TSHELL_STRAIN	_D3P_Tensor	D3P_NUM_TSHELL	ist, ipt
D3P_TSHELL_HISTORY_VAR	float	D3P_NUM_TSHELL	ist, ipt, ihv
BEAM			
D3P_NUM_BEAM	int	1	ignore
D3P_BEAM_MAXINT	int	1	ignore
D3P_BEAM_CONNECTIVITY_THIRD_MAT	_D3P_Beam	D3P_NUM_BEAM	ignore
D3P_BEAM_IDS	int	D3P_NUM_BEAM	ignore
D3P_BEAM_AXIAL_FORCE	float	D3P_NUM_BEAM	ist
D3P_BEAM_S_SHEAR_RESULTANT	float	D3P_NUM_BEAM	ist
D3P_BEAM_T_SHEAR_RESULTANT	float	D3P_NUM_BEAM	ist
D3P_BEAM_S_BENDING_MOMENT	float	D3P_NUM_BEAM	ist
D3P_BEAM_T_BENDING_MOMENT	float	D3P_NUM_BEAM	ist
D3P_BEAM_TORSIONAL_RESULTANT	float	D3P_NUM_BEAM	ist
D3P_BEAM_RS_SHEAR_STRESS	float	D3P_NUM_BEAM	ist, ipt
D3P_BEAM_TR_SHEAR_STRESS	float	D3P_NUM_BEAM	ist, ipt
D3P_BEAM_AXIAL_STRESS	float	D3P_NUM_BEAM	ist, ipt
D3P_BEAM_AXIAL_PLASTIC_STRAIN	float	D3P_NUM_BEAM	ist, ipt
D3P_BEAM_AXIAL_STRAIN	float	D3P_NUM_BEAM	ist, ipt
D3P_BEAM_HISTORY_VAR	float	D3P_NUM_BEAM	ist, ipt, ihv
SHELL			
D3P_NUM_SHELL	int	1	ignore
D3P_SHELL_MAXINT	int	1	ignore
D3P_SHELL_CONNECTIVITY_MAT	_D3P_She11	D3P_NUM_SHELL	ignore
D3P_SHELL_IDS	int	D3P_NUM_SHELL	ignore
D3P_SHELL_STRESS	_D3P_Tensor	D3P_NUM_SHELL	ist, ipt

D3P_SHELL_EFFECTIVE_PLASTIC_STR f1c AIN D3P_SHELL_STRAIND3	BP Tensor	D3P_NUM_SHELL	ist, ipt
D3P_SHELL_STRAIND3	RP Tongor		
	or _rensor	D3P_NUM_SHELL	ist, ipt
D3P_SHELL_HISTORY_VAR f10	oat	D3P_NUM_SHELL	ist, ipt, ihv
D3P_SHELL_MX f1c	oat	D3P_NUM_SHELL	ist
D3P_SHELL_MY f1c	oat	D3P_NUM_SHELL	ist
D3P_SHELL_MXY f1c	oat	D3P_NUM_SHELL	ist
D3P_SHELL_QX f1c	oat	D3P_NUM_SHELL	ist
D3P_SHELL_QY f1c	oat	D3P_NUM_SHELL	ist
D3P_SHELL_NX f1c	oat	D3P_NUM_SHELL	ist
D3P_SHELL_NY f1c	oat	D3P_NUM_SHELL	ist
D3P_SHELL_NXY f1c	oat	D3P_NUM_SHELL	ist
DELETION			
D3P_HAS_DELETION boo	ol	1	ist
D3P_SOLID_DELETION f1c	pat	D3P_NUM_SOLID	ist
D3P_TSHELL_DELETION f1c	pat	D3P_NUM_TSHELL	ist
D3P_SHELL_DELETION f10	oat	D3P_NUM_SHELL	ist
D3P_BEAM_DELETION f10	oat	D3P_NUM_BEAM	ist
SPH			
D3P_NUM_SPH int	t	1	ignore
D3P_SPH_NODE_MATD3	BP_Sph	D3P_NUM_SPH	ignore
D3P_SPH_RADIUS flo	oat	D3P_NUM_SPH	ist
D3P_SPH_PRESSURE f10	pat	D3P_NUM_SPH	ist
D3P_SPH_STRESSD3	BP_Tensor	D3P_NUM_SPH	ist
D3P_SPH_PLASTIC_STRAIN flo	pat	D3P_NUM_SPH	ist
D3P_SPH_DENSITY flo	pat	D3P_NUM_SPH	ist
D3P_SPH_INTERNAL_ENERGY f1c	pat	D3P_NUM_SPH	ist
D3P_SPH_NUMBER_OF_PARTICLE_NEIG int		D3P_NUM_SPH	ist
D3P_SPH_STRAIND3	BP_Tensor	D3P_NUM_SPH	ist

D3P_SPH_MASS	float	D3P_NUM_SPH	ist
DES			
D3P_HAS_DES_DATA	bool	1	ignore
D3P_NUM_DES_DATA	int	1	ignore
D3P_NUM_DES_PART_IN_GEOM	int	1	ides if necessary
D3P_NUM_DES_ELEM_IN_GEOM	int	1	ides if necessary
D3P_NUM_DES_PART_IN_STATE	int	1	ides if necessary
D3P_NUM_DES_ELEM_IN_STATE	int	1	ides if necessary
D3P_NUM_DES_PART_VAR_IN_GEOM	int	1	ides if necessary
D3P_DES_PART_VAR_LIST_IN_GEOM	_D3P_Var	D3P_NUM_DES_PART _VAR_IN_GEOM	ides if necessary
D3P_NUM_DES_ELEM_VAR_IN_GEOM	int	1	ides if necessary
D3P_DES_ELEM_VAR_LIST_IN_GEOM	_D3P_Var	D3P_NUM_DES_ELEM _VAR_IN_GEOM	ides if necessary
D3P_NUM_DES_PART_VAR_IN_STATE	int	1	ides if necessary
D3P_DES_PART_VAR_LIST_IN_STATE	_D3P_Var	D3P_NUM_DES_PART _VAR_IN_STATE	ides if necessary
D3P_NUM_DES_ELEM_VAR_IN_STATE	int	1	ides if necessary
D3P_DES_ELEM_VAR_LIST_IN_STATE	_D3P_Var	D3P_NUM_DES_ELEM _VAR_IN_STATE	ides if necessary
D3P_DES_NODAL_MAT_RADIUS_MASS_I NERTIA	_D3P_Des	D3P_NUM_DES_ELEM _IN_GEOM	ides if necessary
D3P_DES_DATA_IN_STATE	int/float/vector/t ensordepends	D3P_NUM_DES_ELEM _IN_STATE	var_name, ist, ides if necessary
CPM			
D3P_HAS_CPM_DATA	bool	1	ignore

D3P_CPM_NUM_AIRBAGS	int	1	ignore
D3P_CPM_NUM_PARTICLES	int	1	ignore
D3P_CPM_NUM_GEOM_VAR	int	1	ignore
D3P_CPM_GEOM_VAR_LIST	_D3P_Var	D3P_CPM_NUM_GEOM _VAR	ignore
D3P_CPM_GEOM_DATA	_D3P_Var	D3P_CPM_NUM_GEOM _VAR	ignore
D3P_CPM_NUM_STATE_VAR	int	1	ignore
D3P_CPM_STATE_VAR_LIST	_D3P_Var	D3P_CPM_NUM_STAT E_VAR	ignore
D3P_CPM_STATE_DATA	int/floatdepend	D3P_CPM_NUM_PART ICLES	var_name, ist
D3P_CPM_NUM_STATE_GEOM_VAR	int	1	ignore
D3P_CPM_STATE_GEOM_VAR_LIST	_D3P_Var	D3P_CPM_NUM_STAT E_GEOM_VAR	ignore
D3P_CPM_STATE_GEOM_DATA	int/floatdepend s	D3P_CPM_NUM_AIRB AGS	var_name, ist
Multisolver			
D3P_HAS_MS_DATA	bool	1	ignore
D3P_MS_NUM_DOMAINS	int	1	ignore
D3P_MS_DOMAIN_ID	int	1	index_multisol ver
D3P_MS_DOMAIN_NAME	char	80	index_multisol ver
D3P_MS_DOMAIN_VAR_NUM	int	1	index_multisol ver
D3P_MS_DOMAIN_VARS_LIST	int	D3P_MS_DOMAIN_VA R_NUM	index_multisol ver
D3P_MS_VAR_NAME	char	80	id_var_multiso lver
D3P_MS_VAR_IS_VECTOR	bool	1	id_var_multiso lver
D3P_MS_VAR_IS_SCALAR	bool	1	id_var_multiso lver

D3P_MS_VAR_IS_TENSOR	bool	1	id_var_multiso
D3P MS DOMAIN VAR LENGTH	int	1	ist,
DSF_MS_DOMAIN_VAK_LENGIN	Int		index_multisol
D3P_MS_DOMAIN_IS_SOLID	bool	1	ist, index_multisol ver
D3P_MS_DOMAIN_IS_SHELL	bool	1	ist, index_multisol ver
D3P_MS_DOMAIN_IS_BEAM	bool	1	ist, index_multisol ver
D3P_MS_DOMAIN_ELEM_NUM_IN_STATE	int	1	ist, index_multisol ver
D3P_MS_SOLID_CONNECTIVITY_MAT_I N_STATE	_D3P_Solid	D3P_MS_DOMAIN_EL EM_NUM_IN_STATE	ist, index_multisol ver
D3P_MS_SHELL_CONNECTIVITY_MAT_I N_STATE	_D3P_Shell	D3P_MS_DOMAIN_EL EM_NUM_IN_STATE	ist, index_multisol ver
D3P_MS_BEAM_CONNECTIVITY_MAT_IN _STATE	_D3P_Beam	D3P_MS_DOMAIN_EL EM_NUM_IN_STATE	ist, index_multisol ver
D3P_MS_DOMAIN_NODE_NUM_IN_STATE	int	1	ist, index_multisol ver
D3P_MS_DOMAIN_COORD_IN_STATE	D3P_Vector	D3P_MS_DOMAIN_NO DE_NUM_IN_STATE	ist, index_multisol ver
D3P_MS_DOMAIN_DATA_IN_STATE	float or D3P_Vector or D3P_Tensor	D3P_MS_DOMAIN_VA R_LENGTH	ist, index_multisol ver,id_var_mul tisolver
D3P_MS_DOMAIN_DATA_IS_ON_STRUCT URE_ELEMENT	bool	1	index_multisol ver
D3P_MS_DOMAIN_DATA_IS_ON_MS_NOD E	bool	1	index_multisol ver

D3P_MS_DOMAIN_DATA_IS_ON_MS_ELE MENT,	bool	1	index_multisol ver
D3P_MS_DOMAIN_IS_FOLLOW_SURFACE _METHOD	bool	1	index_multisol ver
D3P_MS_DOMAIN_NODE_NUM_ONSURFAC E_IN_STATE	int	1	ist, index_multisol ver
D3P_MS_DOMAIN_SURFACE_IDS_IN_ST ATE	int	D3P_MS_DOMAIN_NO DE_NUM_ONSURFACE _IN_STATE	ist, index_multisol ver

How to use

Sample1.c

Purpose: obtain resultant displacement for all the nodes and find maximum value.

3D scatterplot(x=shell_nodes_x, y=shell_nodes_y, z=shell_nodes_z, c=resultant displacement of shell nodes)

ist: last.

```
#include "../config.h" /* define DATA_PATH_1 "d3plot/path" */
#include "../d3plotreaderwrapperc.h"
#include <stdio.h>
#include <stdlib.h>
#include <math.h>
int main() {
       char d3plot[1024] = { 0 };
      char* handle;
       int i;
      int num_nodes = 0;
      int num_states = 0;
      int index = 0;
       _D3P_Vector* node_ini_coor = NULL;
       _D3P_Vector* node_coor = NULL;
      float* node_res_disp = NULL;
      float disp_x, disp_y, disp_z, tmp, max;
       _D3P_Parameter param;
      param.ides = -1;
      param.id_var_multisolver = -1;
       param.ihv = -1;
```

```
param.index_multisolver = -1;
       param.ipart = -1;
       param.ipt = -1;
       param.ist = -1;
       param.i_rigid_wall = -1;
       param.var name = "";
       strcpy(d3plot, DATA_PATH_1);
#ifdef WIN32
       for (i = 0; i < strlen(d3plot); i++) {</pre>
              if (d3plot[i] == '/') {
                     d3plot[i] = '\\';
              }
       }
#else
       for (i = 0; i < strlen(d3plot); i++) {</pre>
              if (d3plot[i] == '\\') {
                     d3plot[i] = '/';
              }
       }
#endif
       handle = D3P_Open(d3plot);
       D3P_Read(handle, D3P_NUM_NODES, (char*)& num_nodes, param);
       D3P_Read(handle, D3P_NUM_STATES, (char*)& num_states, param);
       node_ini_coor = (
              (_D3P_Vector*)malloc(num_nodes * sizeof(_D3P_Vector))
```

```
);
node_coor = (_D3P_Vector*)malloc(num_nodes * sizeof(_D3P_Vector));
D3P_Read(
       handle, D3P_NODE_INITIAL_COORDINATES,
       (char*)node_ini_coor, param
);
param.ist = num_states - 1;
D3P_Read(handle, D3P_NODE_COORDINATES, (char*)node_coor, param);
D3P_Close(handle);
/*
       obtain resultant displacement for all nodes
       and find maximum value.
*/
node_res_disp = (float*)malloc(num_nodes * sizeof(float));
for (i = 0; i < num_nodes; i++) {</pre>
       disp_x = node_coor[i].v[0] - node_ini_coor[i].v[0];
       disp_y = node_coor[i].v[1] - node_ini_coor[i].v[1];
       disp_z = node_coor[i].v[2] - node_ini_coor[i].v[2];
       tmp = pow(disp_x, 2) + pow(disp_y, 2) + pow(disp_z, 2);
       node_res_disp[i] = pow(tmp, 0.5);
}
max = node_res_disp[0];
for (i = 0; i < num_nodes; i++) {</pre>
       if (max < node_res_disp[i]) {</pre>
              max = node_res_disp[i];
              index = i;
       }
```

```
printf(
     "Maximum resultant displacement of nodes is: %f,"
     "index is %d", max, index
);

free(node_ini_coor);
free(node_coor);
free(node_res_disp);
}
```

Sample2.c

Purpose: extract Variable data for Multisolver.

State: 2

```
#include "../config.h" /* define DATA_PATH_3 "d3plot/path" */
#include "../d3plotreaderwrapperc.h"
#include <stdio.h>
#include <stdlib.h>
#include <math.h>
#include <stdbool.h>
int main() {
      char d3plot[1024] = { 0 };
      char* handle_ms = NULL;
      bool has_ms_data = false;
      int num_ms_datasets = 0;
      int* domain_var_ids = NULL;
      int dataset = 0;
      int domain_var_num = 0;
      int var = 0;
      int sizevar = 0;
      int i;
      bool is_scalar = false;
      bool is_vector = false;
      bool is_tensor = false;
      float* fvalue = NULL;
      float maxvalue = -1.0e20;
      _D3P_Vector* vvalue = NULL;
```

_D3P_Tensor* tvalue = NULL;

```
_D3P_Parameter dp;
       dp.ides = -1;
       dp.id_var_multisolver = -1;
       dp.ihv = -1;
       dp.index_multisolver = -1;
       dp.ipart = -1;
       dp.ipt = -1;
       dp.ist = -1;
       dp.i_rigid_wall = -1;
       dp.var_name = "";
       strcpy(d3plot, DATA_PATH_3);
#ifdef WIN32
       for (i = 0; i < strlen(d3plot); i++) {</pre>
              if (d3plot[i] == '/') {
                     d3plot[i] = '\\';
              }
       }
#else
       for (i = 0; i < strlen(d3plot); i++) {</pre>
              if (d3plot[i] == '\\') {
                     d3plot[i] = '/';
              }
       }
#endif
       handle_ms = D3P_Open(d3plot);
       D3P_Read(handle_ms, D3P_HAS_MS_DATA, (char*)& has_ms_data, dp);
       if (!has_ms_data)
```

```
{
       printf("No Multisolver Data\n");
}
D3P_Read(
       handle_ms, D3P_MS_NUM_DOMAINS, (char*)& num_ms_datasets, dp
);
for (dataset; dataset < num_ms_datasets; dataset++)</pre>
{
       dp.index_multisolver = dataset;
       D3P_Read(
              handle_ms, D3P_MS_DOMAIN_ID, (char*)& domain_var_num, dp
       );
       domain_var_ids = (int*)malloc(domain_var_num * sizeof(int));
       D3P_Read(
              handle_ms, D3P_MS_DOMAIN_VARS_LIST,
              (char*)domain_var_ids, dp
       );
       dp.ist = 2;
       var = 0;
       for (var; var < domain_var_num; var++)</pre>
       {
              dp.id_var_multisolver = domain_var_ids[var];
              sizevar = 0;
              D3P_Read(
                     handle_ms, D3P_MS_DOMAIN_VAR_LENGTH,
                     (char*)& sizevar, dp
              );
```

```
D3P_Read(
       handle_ms, D3P_MS_VAR_IS_SCALAR,
       (char*)& is_scalar, dp
);
D3P_Read(
       handle_ms, D3P_MS_VAR_IS_VECTOR,
       (char*)& is_vector, dp
);
D3P_Read(
       handle_ms, D3P_MS_VAR_IS_TENSOR,
       (char*)& is_tensor, dp
);
if (is_scalar)
{
       fvalue = (float*)malloc(sizevar * sizeof(float));
       D3P_Read(
              handle_ms, D3P_MS_DOMAIN_DATA_IN_STATE,
              (char*)fvalue, dp
       );
       printf("Value type: scalar, value[0]=%f\n",
              fvalue[0]
       );
       free(fvalue);
       fvalue = NULL;
}
if (is_vector)
{
       vvalue = (_D3P_Vector*)malloc(
              sizevar * sizeof(_D3P_Vector)
```

```
);
                     D3P_Read(
                            handle_ms, D3P_MS_DOMAIN_DATA_IN_STATE,
                            (char*)vvalue, dp
                     );
                     printf("Value type: vector, value[0].X()=%f\n",
                            vvalue[0].v[0]
                     );
                     free(vvalue);
                     vvalue = NULL;
              }
              if (is_tensor)
              {
                     tvalue = (_D3P_Tensor*)malloc(
                            sizevar * sizeof(_D3P_Tensor)
                     );
                     D3P_Read(
                            handle_ms, D3P_MS_DOMAIN_DATA_IN_STATE,
                            (char*)tvalue, dp
                     );
                     printf("Value type: tensor, value[0].X()=%f\n",
                            tvalue[0].t[0]
                     );
                     free(tvalue);
                     tvalue = NULL;
              }
       }
}
free(domain_var_ids);
domain_var_ids = NULL;
```

```
D3P_Close(handle_ms);
}
```