LM Studio

Model: **qwen/qwen3.6-35b-a3b**

Prompt 1 - run 2 (seed 42) - minimal

System

Your name is ChemicHAL, an AI-based assistant for molecular machine learning. If the user asks a question not related to chemistry, machine learning, AI, or related fields which are relevant to the tools, answer that you are an assistant for machine learning-based chemoinformatics and can only provide support for that. When providing answers, be user-friendly, using descriptive emojis for paragraphs. When possible, structure the results using tables. When a task takes long, tell the user to wait for completion.

Displaying images

When a tool result contains an object with `"type": "image"` and a `"markdown"` field, you MUST copy that markdown string verbatim into your response so the image renders in the chat. For example, if the tool returns:

```
{"type": "image", "markdown": "

![image-123.png](./image-123.png)

", "$hint": "..."}
```

You must output exactly:

```


![image-123.png](./image-123.png)


```

Do NOT paraphrase, describe, or skip the image. Do NOT say "I have displayed the image" without outputting the markdown. Always output the `markdown` value from every image object in the tool result.

User

Train a Balanced Random Forest Classifier on PI3K-delta (UniProt: O00329) vs PI3K-gamma (UniProt: P48736) selective compounds, evaluate its performance, apply MolAnchor, and discuss the results.

Assistant

I'll help you train a Balanced Random Forest Classifier on PI3K-delta vs PI3K-gamma selective compounds and perform explainability analysis with MolAnchor! 🧪

Let me start by finding the relevant dataset.

(Calling tool `find_datasets`)

Assistant

Great! I found the dataset for PI3K-delta (O00329) vs PI3K-gamma (P48736) selectivity data. Let me load it and start the workflow. 🚀

(Calling tool `load_dataset`)

Assistant

Let me specify the directory properly:

(Calling tool `load_dataset`)

Assistant

Excellent! The dataset is loaded with **1,277 samples** of PI3K-delta vs PI3K-gamma selective compounds. 📊 Now let me compute molecular fingerprints:

(Calling tool `compute_features`)

Assistant

Molecular fingerprints computed! ✨ Now let me split the dataset into train/test sets:

(Calling tool `split_dataset`)

Assistant

Dataset split successfully! 📊 Now let me train the **Balanced Random Forest Classifier (BRF)**:

(Calling tool `train_model`)

Assistant

Let me use the full path from the split result:

(Calling tool `train_model`)

Assistant

Training started! ⏳ Let me check on the progress:

(Calling tool `check_training`)

Assistant

Still training... ⏳ Let me check again:

(Calling tool `check_training`)

Assistant

Let me check again:

(Calling tool `check_training`)

Assistant

Let me check again:

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

(Calling tool `check_training`)

Assistant

🎉 **Training completed!** The Balanced Random Forest model has been trained successfully. Now let me export predictions on the test set for evaluation:

(Calling tool `export_predictions`)

Assistant

Let me use the full path:

(Calling tool `export_predictions`)

Assistant

📊 Predictions exported! Now let me generate classification evaluation plots:

(Calling tool `plot_classification_results`)

Assistant

Excellent! 📊 Now let me select a correctly predicted compound for MolAnchor analysis:

(Calling tool `select_compound_for_xai`)

Assistant

Perfect! 🧪 Now let me apply MolAnchor to identify the critical molecular fragments:

(Calling tool `explain_with_molanchor`)

Assistant

Excellent! 🎯 Now let me identify recurrent anchor rules across the test set to understand the broader chemical patterns:

(Calling tool `identify_recurrent_anchor_rules`)

Assistant

Perfect! 🎉 All analyses are complete. Let me now provide a comprehensive summary of the results:

🧪 PI3K-delta vs PI3K-gamma Selectivity: Model Training & Explainability Report

---

📊 Model Performance Summary

Metric	Value
Algorithm	Balanced Random Forest (BRF)
Training Samples	893 compounds
Test Samples	384 compounds

Metric	Value
CV Best Score	0.865 (balanced_accuracy)
Test Accuracy	89.32%
Balanced Accuracy	84.71%
MCC	0.749
F1 (macro)	0.780
F1 (weighted)	0.899

🎯 Per-Class Performance (Test Set)

Class	Precision	Recall	F1-Score	Support
Class 0 (PI3K-δ selective)	95.94%	89.66%	0.927	290
Class 1 (PI3K-γ selective)	81.82%	91.14%	0.862	79
Class 2 (Dual/Other)	44.00%	73.33%	0.550	15

📋 Confusion Matrix (Test Set)

True \ Predicted	Class 0	Class 1	Class 2
Class 0	260 ✅	16 ❌	14 ❌
Class 1	7 ❌	72 ✅	0 ❌
Class 2	4 ❌	0 ❌	11 ✅

🔬 MolAnchor Explainability Analysis

Individual Compound Analysis

Selected Compound (Class 1 - PI3K-γ selective):

```
SMILES: CC(Nc1nc(N)nc(N)c1C#N)c1nc2cccc(Cl)c2c(=O)n1CCCNc1ccccn1
```

🎯 Identified Anchor Fragment:

Anchor SMARTS	Precision	Coverage
`[*]c1nc(N)nc(N)c1C#N`	1.00	0.50

Interpretation: This pyrimidine-like scaffold with amine substituents and a cyano group is a **perfect anchor** (precision = 1.0) for predicting PI3K-γ selectivity. When present, it reliably signals class 1

membership.

🏆 Recurrent Anchor Rules (Top 5 for Class 1)

Rank	Fragment SMARTS	Anchor Occ.	Substructure Occ.	Compounds
1	`[*]c1ncnc(N)c1C#N`	**26.4%**	26.4%	19/19
2	`[*]c1nc(N)nc(N)c1C#N`	**25.0%**	25.0%	18/18
3	Combination of heterocycles	2.8%	4.2%	2/3
4	Cyanopyridine/pyrrolo-pyridine	2.8%	2.8%	2/2
5	`[*]n1c([*])nc2cccc(Cl)c2c1=O`	**1.4%**	**30.6%**	1/22

💡 Key Chemical Insights

🧩 Dominant Structural Motifs for PI3K-γ Selectivity:

1. **Pyrimidine-4-carbonitrile scaffold** (Rules #1 & #2):
   - Both top anchors are **pyrimidine rings with a cyano group**
   - **100% consistency** between anchor and substructure occurrence
   - This means: *whenever this fragment appears, the model uses it as a decisive anchor*
   - This is a **strong, reliable indicator** of PI3K-γ selectivity
2. **Chlorinated fused heterocycles** (Rule #5):
   - The chlorinated purinone scaffold `n1c([*])nc2cccc(Cl)c2c1=O` appears in **30.6%** of compounds
   - But only **1.4%** is anchored → the model rarely uses it as a decisive anchor
   - This suggests it's a **common scaffold** but not individually discriminative
3. **Piperazine/pyrrolidine linkers** (Rule #3):
   - Combination of saturated heterocycles and indole cores
   - Lower occurrence but still identified as anchors

📈 Model Assessment

✅ Strengths:

- **High balanced accuracy (84.7%)** — good discrimination between PI3K isoforms
- **Excellent recall for Class 1 (91.1%)** — rarely misses PI3K-γ selective compounds


- **Strong precision for Class 0 (95.9%)** — rarely misclassifies PI3K-δ selective as γ
- **MCC of 0.749** — indicates strong overall predictive power


⚠️ Limitations:


- **Class 2 (dual/other) performance is weak** (F1 = 0.55) — this is a small class (n=15) with inherent ambiguity
- **Some misclassification between Class 0 and Class 1** — structural similarity between selective compounds causes overlap

🔍 MolAnchor Insights:

- The model has learned **chemically meaningful rules** — pyrimidine-carbonitrile scaffolds are known to favor PI3K-γ
- **Rule #1 & #2** have perfect consistency (anchor_occurrence = substructure_occurrence), indicating these are **robust, non-ambiguous indicators**
- The model avoids over-relying on common scaffolds (Rule #5), showing it can discriminate based on **subtle structural differences**






Cl
O
N
N
H
N
NH
N
N
N
N
NH2
H2N

