

Qurry: A prototype quantum programming language

Lucas Saldyt

Arizona State University

Innovation in near-term quantum programming requires the use of lightweight, transparent abstraction mechanisms. This paper outlines a typeless, dynamic functional quantum programming language, and a surrounding software system which allows for rapid prototyping and evolution of the language. Abstractions are desirable because they allow a programmer to express more computation with less code. Transparency is crucial, especially in quantum computing, because hardware details more strongly affect the types of programs that can be written. To some extent, abstraction and transparency oppose one another. However, carefully crafted abstractions can be lightweight enough to preserve transparency. Qurry achieves lightweight abstractions through hierarchical composition of data and of operations.

1 Introduction

In 1981, Richard Feynman noted that quantum physics appears to be impossible to simulate using a classical computer, but that quantum computers appeared to be perfectly capable of simulating quantum physics [1]. Effectively, quantum computation potentially allows new problems to be computed efficiently: in particular, this includes literal simulations of the physical world, but also abstract algorithms which may receive a superpolynomial change in time complexity.

Stephen Jordan, of Microsoft, keeps a nearly exhaustive list of quantum algorithms and the speedups that they offer [2]. According to this list at time of writing, there are thirty-five distinct quantum algorithms which offer a potential superpolynomial speedup. This famously includes Peter Shor’s factoring and discrete log al-

gorithms, as well as, fundamentally, quantum simulation. [3, 4, 1, 5, 6] Interestingly, many quantum algorithms such as the Deutsch-Jozsa algorithm are matched (at least practically, and sometimes theoretically) by probabilistic algorithms, and even some algorithms with superpolynomial speedups are based on older probabilistic versions. [7] For instance, machine learning does not appear to have superpolynomial improvements at time of writing, but quantum computers can still be applied to it [8]. The most promising application of quantum computing in the near term is in molecular simulation. As the comparisons section will demonstrate, Qurry offers unique programming language features which implementing each of these algorithms significantly easier.

Currently, quantum programming is analogically in a similar stage to classical programming in 1960s and early 1970s. A true high-level quantum programming language is still a desideratum. In the history of classical programming languages, C, while not perfect, filled a major gap that had existed before its time [9], and quantum computing still lacks a similar language. Importantly, C’s evolution was partially driven by the need for a language expressive enough to easily re-code Unix. Quantum languages, of course, are driven by a different motivation, primarily the power that quantum computing adds to the existing classical computing stack. Importantly, quantum programming does not appear to be replacing classical computation, but adding to it. Often quantum computers are used as auxiliary elements to classical computers in hybrid computation [10]. According to the needs of the field, a high-level quantum programming language will likely need to be lightweight, hybridized, and transparent. While myriad other desirable criteria exist, these are certainly among them.

Hybridized instruction languages already exist, and allow one to leverage the power of existing classical computation [11, 12, 13, 14]. However, the ability to program at a higher level of abstrac-

Lucas Saldyt: lsaldyt@asu.edu, <https://github.com/LSaldyt>

tion is desired. It is not that it is particularly hard to write quantum circuits at the gate-level, but simply that existing quantum programming languages often force programmers to write redundant inexpressive code, in the sense that more description is required to get the same level of computation. An obstruction to this is that running circuits on quantum hardware is not trivial, and requires transparency in a given language.

In the design philosophy of C++, Bjarne Stroustrup describes “lightweight abstractions“, which allow users to easily exploit the full power of their computer without having to write hand-optimized assembly code [15]: “The aim [of C++] is to allow a programmer to work at the highest feasible level of abstraction by providing a simple and direct mapping to hardware and zero-overhead abstraction mechanisms“. A zero-overhead abstraction is one which is easier to implement, but performs no differently than code hand-written in a lower-level language (Assembly, in the case of C++, and a quantum circuit language in the case of Qurry).

However, some have argued for the importance of hardware, as in Google’s phrase “hardware aware, not hardware agnostic” [16]. Many aspects of hardware are particularly important, for instance, topology, which will potentially result in a programmer needing to modify a quantum algorithm for it to run on two separate computers. To some extent, this can be handled by existing compilers, but not nearly at the same level as classical compilers are able to do this [17]. Additionally, the error generation of a quantum computer is actually a crucial detail, even though quantum programmers might desire to ignore it. In the current state of quantum computing, many details of hardware cannot yet be ignored. However, it is obvious that *eventual* hardware independence is desirable — Consider the power of Java in the classical computing world. Lightweight abstractions are precisely the scaffold that will catalyze this transition.

Clojure is another inspiration for Qurry.. [18]

1.1 Languages

Qurry is certainly not the first of its kind. Several quantum programming languages exist ([19, 20] TODO Cite more), but this paper will discuss two leading examples: Q# and Quipper.

Summarize and discuss Q# here. TODO.

[21]

Summarize and discuss Quipper here. TODO.

[22] [23]

[24] [25] [26]

1.2 Background

The absolute basics of quantum computing are not nearly as intimidating as they are sometimes made out to be. The main requirement is linear algebra, but exposure to complex numbers and probability are also helpful. For a complete overview, see the beginning chapters of “Quantum Computation and Quantum Information“ [27]. Conventionally, quantum data is represented on qubits. When measured, qubits will be in *either* of two states: $|0\rangle$ or $|1\rangle$. However, more generally, qubits are in a combination of these two states, which is known as a superposition. A particular active qubit’s state is described by two complex numbers, α and β , which are collected in a vector. This is written in the simple equation:

$$|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$$

. However, the state vector α, β is not directly examinable. Instead, when a qubit is measured, one measures $|0\rangle$ with probability $|\alpha|^2$, and $|1\rangle$ with probability $|\beta|^2$, which must sum to 1. For single qubits, a state is evolved in the model simply by multiplying the state vector for a qubit by a 2 by 2 unitary matrix, known as a one-qubit gate. This is written as Av .

For n qubits, the state is simply a complex vector of length 2^n , and a n qubit gate is a 2^n by 2^n matrix:

$$|\psi\rangle = \alpha_i |s_i\rangle \text{ for } s_i \in \{0, 1\}^n, 0 < i < 2^n - 1$$

. Once a given n -qubit quantum state is measured, the outcome is a single bit-string, s_i , with probability $|\alpha_i|^2$. If it is possible to repeat this measurement (by preparing the quantum state multiple times), then a collection of measurements is a multinomial distribution defined by the states s_i and probabilities α_i , but this distribution has 2^n states, and measuring a quantum state only gives a single sample.

Importantly, past a single qubit, quantum states can be entangled. Two states are entangled when the measurement outcome of one qubit is correlated with the measurement outcome of

other qubits. The simplest, most famous example of this is the Bell states, also known as EPR pairs. For instance, in one Bell state, two qubits are either measured both as $|0\rangle$, or both as $|1\rangle$ (even when measured independently), but there is no probability for them to differ. This is the basis for all interesting quantum algorithms.

To summarize, superposition is the fundamental state model for quantum computers, but a given quantum state cannot be measured directly, only sampled once. Then, entanglement allows the correlation of measurements, which is a crucial ingredient in any useful quantum algorithm. Any quantum program is simply a combination of linear operators which affect the superposition. Given an initial state, conventionally the zero vector, a quantum program P operates on the state vector, and then the vector is sampled, by measuring a subset of its qubits. Importantly, a quantum program P is itself a linear operator, potentially further composed of other linear operators. The data in a quantum program, at this level of abstraction, will only ever be a vector of qubits, but at higher levels of abstraction, this vector can be subsectioned into semantic datatypes, no differently than how C++'s fundamental memory model is a sequence of bytes.

At the same time, in hybrid classical-quantum computation, classical control can setup, run, and measure the outcomes of quantum sub-programs. In this way, some quantum program P will be embedded in a hybrid program.

1.3 Circuit Languages

At time of writing, Rigetti pyquil contains the following quantum gates and operations:

Single qubit gates and operations:

- RESET, I, X, Y, Z, H, S, T

Qubit gates taking an angle as the parameter and qubit as the second:

- RX, RY, RZ, PHASE

Swap operators, where each takes two qubits, and PSWAP takes an additional angle as a first argument:

- SWAP, ISWAP, and PSWAP

Controlled operators:

- CZ, CNOT
- CSWAP
- CPHASE00, CPHASE01, CPHASE10, CPHASE

And of course the hybrid measurement instruction, which takes a qubit as the first argument, and a classical register as the second:

- MEASURE

And also contains the following classical operations:

- TRUE, FALSE, NOT, NEG
- AND, OR, MOVE, EXCHANGE, IOR, XOR
- ADD, SUB, MUL, DIV
- EQ, GT, GE, LE, LT
- LOAD
- STORE
- CONVERT

Most importantly, though, QUIL actually already has a notion of higher-level functions, which it calls "Modifiers". These are the following:

- DAGGER
- CONTROLLED

1.4 Classical Probabilistic Languages

Classical probabilistic programming languages are a recent innovation from the MIT cognitive science community [28, 29]. Essentially, they create a way for non-expert programmers to access the power of Bayesian inference. Users can create simple probabilistic models in standard code, and then run them through an expert-created inference backend. Famously, this has resulted in dramatically reduced code complexity, with a famous case where a 50-line probabilistic program could compete with traditional approaches to face recognition [30]. Additionally, classical probabilistic programming has outperformed many other AI techniques [31]. These languages

are successful because they package powerful inference algorithms and intuitive, simple modeling into an understandable framework.

Similar success has also been seen, for instance, with frameworks such as Tensorflow, Keras, or Edward [32].

Qurry is inspired by the effects these languages have had, and in fact there is some overlap between quantum programming and classical probabilistic languages. For instance, quantum bayesian inference has been conceptualized since the 70s-90s [33]. At time of writing, this has been distilled into packages such as Bayesforge [34, 35].

2 Features

Creating abstractions in quantum programming languages comes down to the creation of higher-order functions and higher-order datatypes. Language features that allow the creation and composition of both higher-order functions and higher-order datatypes set Qurry apart from lower-level circuit languages.

2.1 Higher Order Functions

The simplest illustration of a higher order function is trivial, but surprisingly neglected from any existing quantum language: it is the tensor operator ($U^{\otimes n}$), known to functional programmers as the higher-order function, *map*. Many quantum algorithms will begin with a change of basis, effectively a state preparation. Commonly, this is to the Hadamard basis, and is done by applying the Hadamard operator to a block of qubits. In a conventional circuit language, this is done as the following:

```
H 0
H 1
...
H n
```

However, textbooks and papers will write this as $H^{\otimes n}$, and in Qurry, it can be written:

```
(define workspace (block n qubit))
(map H workspace)
```

Implicitly, this example also introduces Qurry’s assignment statement *define*, and its representation for qubit arrays, the *block* command, which takes a size and a type, and allocates space and handles mapping to actual qubit indices. More

impressively, Qurry supports automatic currying of functions:

```
(define initialize_basis (map H))
(define workspace (block n qubit))
(initialize_basis workspace)
```

Of course, Qurry utilizes the two existing higher-order functions defined by QUIL: DAGGER, and more importantly, CONTROLLED. For brevity, Qurry redefines CONTROLLED to CU. Effectively, this allows the creation of arbitrary controlled operators, for instance the redefinition of CNOT:

```
(define custom_cnot (CU X))
(H 0)
(custom_cnot 0 1)
```

Qurry calls functions like CU controlled higher level operators. This list includes:

- CU
- CNU
- Cascade, CascadeU
- ReverseCascade, ReverseCascadeU
- Collect, CollectU
- Expand, ExpandU
- SimU

Interestingly, many of these are defined through composition of simpler gates. For instance, CNU takes a block of control qubits and a block of work qubits, and entangles pairs of control and work qubits, and finally entangles a target qubit, which a unitary is controlled by. Essentially, each of these operators performs some control operations (through a composition of CNOT gates, conventionally), and then performs an arbitrary unitary operation which is controlled by the result of the previous control operations. (This section will contain circuits and more in-depth explanations, but this is currently commented out).

Lastly, Qurry implements lambda expressions, which allow arbitrary re-use and composition of other operators, and natively support currying. Since the λ character is unavailable on most conventional keyboards, lambda expressions are denoted with an *l*, and can be used to create named functions, such as:

```
(define create-bell (l (a b) ((H a) (CNO
```

And of course they support currying:

```
(define partial ((l (a b c) ((X a) (X b) (CNOT a b c))) 0 1))
(partial 2)
```

Obviously, Qurry’s lisp interface will have plenty of parentheses.

2.2 Higher Order Datatypes

Qurry’s memory model is simple: an array of n qubits, and m classical bits. However, in programmer-space, these arrays are cut up and defined using semantic datatypes.

The previous section discussed the *block* type, and the *define* command. The *block* command will automatically select appropriate qubits in the array, and map to these when used.

In terms of datatypes, not much more is needed, except for the *datatype* command, which mimics C++’s *struct* or *class*. For simplicity, elegance, and robustness, Qurry does not implement encapsulation or inheritance, but instead uses public access by default (in the spirit of Python, since after all, Qurry has a Python interface), and relies on composition instead of inheritance. A *datatype* is nothing more than a contiguous collection of other Qurry datatypes, with names for each field. Like *block* objects, *datatypes* automatically map to qubits and bits in Qurry’s memory model. These can be *blocks*, single qubits, single bits, and other defined *datatype* objects, allowing for recursive types. Fields within a datatype are simply accessed with the dot operator:

```
(datatype entanglion
  (a qubit)
  (b qubit))
(define e (entanglion))
(H e.a)
(CNOT e.a e.b)
```


Recursively composed higher-order datatypes, in combination with recursively composed higher-order functions are the foundation for creating a more abstract programming language.

2.3 Other Features

Lastly, Qurry features rudimentary classical features meant to complement the hybrid model used by QUIL.

- cond
- do

3 Comparisons



4 Software Ecosystem

In addition to being a prototype quantum programming language, Qurry defines a software stack surrounding the language, which is intended to make development more pleasant. For instance, this software stack makes it exceptionally easy to add new language features and libraries to Qurry. This allows one to rapidly test new ideas in quantum programming and let the language evolve on its own as opposed to architecting a top-down “perfect” language.

5 Standard Library

Qurry contains mechanisms which enable easy inclusion of qurly code in the form of libraries. As an example, Qurry’s standard library is implemented in this fashion.

Explain how the statistics library can be easily implemented.

At time of writing, Qurry contains the following constructs:

- gaussian

- bernoulli
- multinomial
- uniform

Similarly to in a classical probabilistic programming language, these enable the creation of classical probabilistic states, which can then be used in quantum programs. For instance, it is possible to create a multi-dimensional gaussian distribution, and then entangle an auxillary qubit with the state of the gaussian distribution.

6 Extension

Making additions to Qurry is particularly easy: For instance, the *map* feature is defined using the following python code:

```
from ..compiler.utils import named_uuid

def map(operator, blockname, kernel=None):
    """
    Apply a single-qubit operator to every qubit in a block
    (map H blocka)
    """
    try:
        block = kernel.definitions[blockname]
    except KeyError:
        raise ValueError('The_block_{blockname} does not exist')
    return '\n'.join('{}{}'.format(operator, blockname)
        for i in range(block.start, block.end + 1))
```

7 Statistical Libraries

Since quantum computers are simply special probabilistic computers, Qurry also attempts to create a classical statistical library for high-level modeling. This is particularly useful in the same way that a classical probabilistic programming language is, namely for modeling anything statistical, and especially for bayesian machine learning. For instance, the R. Tucci and H. Dekant's group have shown uses for this through their software, Bayesforge [TODO: Cite]. Qurry includes simple statistical packages for creating states, but no inference engine. [However, Qurry might allow one to interface with Bayesforge]

8 Conclusion

In the creation of a Qurry and its corresponding framework, it is hoped that this will aid the development of quantum algorithms, as algorithm designers will have a new, richer, more abstract vocabulary with which to express themselves. To recap, this goal is approached in the following N ways. By introduction of lightweight abstractions from the C++ school of thought, efficient and transparent programming interfaces are created. Through specialized libraries, Qurry can claim to be a generalized library, while still offering powerful sub-frameworks for specific tasks. With functional programming paradigms, Qurry can move towards higher levels of abstraction as the semantics of quantum programming become better understood. Lastly, by creating a rapid prototyping framework, new language features can be developed in a bottom-up style, which will allow Qurry to be created naturally, instead of artificially.

9 Appendix one

Appendix content

Acknowledgment

The author would like to thank Dr. Will Zeng of Rigetti computing, an organizer of the Unitary Fund, Dr. Ajay Bansal of Arizona State University, PLOS and other funders to the unitary fund, and ASU's FURI program.

References

- [1] Richard Feynman. Simulating physics with computers, May 1981.
- [2] Stephen Jordan. Quantum algorithm zoo.
- [3] Peter W. Shor. Polynomial-time algorithms for prime factorization and discrete logarithms on a quantum computer. *Society for Industrial and Applied Mathematics*.
- [4] Abhinav Kandala, Antonio Mezzacapo, Kristan Temme, Maika Takita, Markus Brink, Jerry M Chow, and Jay M Gambetta. Hardware-efficient variational quantum eigensolver for small molecules and quantum magnets. *Nature*, 549(7671):242, 2017.
- [5] Benjamin P Lanyon, James D Whitfield, Geoff G Gillett, Michael E Goggin, Marcelo P Almeida, Ivan Kassal, Jacob D Biamonte, Masoud Mohseni, Ben J Powell, Marco Barbieri, et al. Towards quantum chemistry on a quantum computer. *Nature chemistry*, 2(2):106, 2010.
- [6] Seth Lloyd. *Programming the universe: a quantum computer scientist takes on the cosmos*. Vintage, 2006.
- [7] David Deutsch and Richard Jozsa. Rapid solution of problems by quantum computation. *Proceedings of the Royal Society of London. Series A: Mathematical and Physical Sciences*, 439(1907):553–558, 1992.
- [8] Jacob Biamonte, Peter Wittek, Nicola Pancotti, Patrick Rebentrost, Nathan Wiebe, and Seth Lloyd. Quantum machine learning. *Nature*, 549(7671):195, 2017.
- [9] Brian W Kernighan and Dennis M Ritchie. *The C programming language*. 2006.
- [10] Will Zeng, Blake Johnson, Robert Smith, Nick Rubin, Matt Reagor, Colm Ryan, and Chad Rigetti. First quantum computers need smart software. *Nature News*, 549(7671):149, 2017.
- [11] Forest: An api for quantum computing in the cloud.
- [12] A python framework for creating, editing, and invoking noisy intermediate scale quantum (nisq) circuits.
- [13] Andrew W Cross, Lev S Bishop, John A Smolin, and Jay M Gambetta. Open quantum assembly language. *arXiv preprint arXiv:1707.03429*, 2017.
- [14] Robert S Smith, Michael J Curtis, and William J Zeng. A practical quantum instruction set architecture. *arXiv preprint arXiv:1608.03355*, 2016.
- [15] Bjarne Stroustrup. Foundations of c++.
- [16] Kevin D. Kissell. Quantum computing at google and in the cloud. FOSDEM: Quantum Computing, 2019.
- [17] Robert S Smith. The rigetti optimizing quil compiler. 2019.
- [18] Rich Hickey. The clojure programming language. In *Proceedings of the 2008 symposium on Dynamic languages*, page 1. ACM, 2008.
- [19] Ryan LaRose. Overview and comparison of gate level quantum software platforms. *Quantum*, 3:130, 2019.
- [20] Bernhard Ömer. A procedural formalism for quantum computing. 1998.
- [21] Krysta M Svore, Alan Geller, Matthias Troyer, John Azariah, Christopher Granade, Bettina Heim, Vadym Kliuchnikov, Mariia Mykhailova, Andres Paz, and Martin Roetteler. Q#: Enabling scalable quantum computing and development with a high-level domain-specific language. *arXiv preprint arXiv:1803.00652*, 2018.
- [22] Peter Selinger and Benoit Valiron. A lambda calculus for quantum computation with classical control. *Mathematical Structures in Computer Science*, 16(3):527–552, 2006.
- [23] Peter Selinger. Towards a quantum programming language. *Mathematical Structures in Computer Science*, 14(4):527–586, 2004.
- [24] Alexander S Green, Peter LeFanu Lumsdaine, Neil J Ross, Peter Selinger, and Benoît Valiron. Quipper: a scalable quantum programming language. 48(6):333–342, 2013.
- [25] Alexander S Green, Peter LeFanu Lumsdaine, Neil J Ross, Peter Selinger, and Benoît Valiron. An introduction to quantum programming in quipper. pages 110–124, 2013.

- [26] Francisco Rios and Peter Selinger. A categorical model for a quantum circuit description language. *arXiv preprint arXiv:1706.02630*, 2017.
- [27] Michael Nielsen and Isaac Chuang. *Quantum Computation and Quantum Information*. 2011.
- [28] Noah Goodman, Vikash Mansinghka, Daniel M Roy, Keith Bonawitz, and Joshua B Tenenbaum. Church: a language for generative models. *arXiv preprint arXiv:1206.3255*, 2012.
- [29] Bob Carpenter, Andrew Gelman, Matthew D Hoffman, Daniel Lee, Ben Goodrich, Michael Betancourt, Marcus Brubaker, Jiqiang Guo, Peter Li, and Allen Riddell. Stan: A probabilistic programming language. *Journal of statistical software*, 76(1), 2017.
- [30] Larry Hardesty. Probabilistic programming does in 50 lines of code what used to take thousands.
- [31] Brenden M Lake, Ruslan Salakhutdinov, and Joshua B Tenenbaum. Human-level concept learning through probabilistic program induction. *Science*, 350(6266):1332–1338, 2015.
- [32] Martín Abadi, Paul Barham, Jianmin Chen, Zhifeng Chen, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Geoffrey Irving, Michael Isard, et al. Tensorflow: A system for large-scale machine learning. In *12th {USENIX} Symposium on Operating Systems Design and Implementation ({OSDI} 16)*, pages 265–283, 2016.
- [33] Robert R Tucci. Quantum bayesian nets. *International Journal of Modern Physics B*, 9(03):295–337, 1995.
- [34] Bayesforge. 2019.
- [35] Marcin Przewięźlikowski, Michał Grabowski, Dariusz Kurzyk, and Katarzyna Rycerz. Support for high-level quantum bayesian inference. In *International Conference on Computational Science*, pages 764–770. Springer, 2019.