




Lancaster
University



Gaussian Processes [Dynamic]



Goal: Find a filter L that

(1) matches with desired spectrum,

(2) is causal, i.e. future only depends on past.

Kalman filtering and smoothing solutions to temporal Gaussian process regression models

Publisher: IEEE


[Cite This](#)

 [PDF](#)

[Jouni Hartikainen](#) ; [Simo Särkkä](#) [All Authors](#)

The filter $(\lambda + \nabla)^{p+1}$ is causal and yields Matérn- $(p + 1/2)$ spectrum.

Example (Matérn-3/2): Solve for $f''(t) + 2\lambda f'(t) + \lambda^2 f(t) = \varepsilon(t)$.





Hartikainen, J. and Särkkä, S. (2010). Kalman filtering and smoothing solutions to temporal Gaussian process regression models, *2010 IEEE international workshop on machine learning for signal processing*, IEEE, pp. 379–384.

Gaussian Processes [Dynamic]

Goal: Find a filter L that

- (1) matches with desired spectrum,
- (2) is causal, i.e. future only depends on past.



Kalman filtering and smoothing solutions to
temporal Gaussian process regression
models

Publisher: IEEE

[Cite This](#)

[PDF](#)

Jouni Hartikainen ; Simo Särkkä [All Authors](#)

The filter $(\lambda + \nabla)^{p+1}$ is causal and yields Matérn- $(p + 1/2)$ spectrum.

Example (Matérn-3/2): Solve for $f''(t) + 2\lambda f'(t) + \lambda^2 f(t) = \varepsilon(t)$.

Gaussian Processes [Dynamic]



$$f''(t) + 2\lambda f'(t) + \lambda^2 f(t) = \varepsilon(t)$$