

Command Line Interface (CLI)

The command line interface, also known as the character user interface (CUI), allows the user to issue commands directly to an application or the operating system. The computer commands are given as one or more lines of text to the program or function to accomplish a specific task or set of tasks. Many advanced Linux users prefer the command line interface (CLI) to interface with the computer. We will explore command line usage when using the BASH shell. In your career as an IT Associate, conducting tasks inside of the command line will become second nature. This course will ensure you are familiar with some of the many commands needed in your job as an IT associate.


Interaction with the operating system is done via programs, which make requests to be serviced by the Kernel through an Application Programming Interface or API. Programs can be either "compiled" into machine instructions that the operating system recognizes, or commands can be given to an interpreter that converts high level requests to machine instruction on the fly. Compiled programs are generally much faster, as all the translation to machine language is completed ahead of time. Interpreted commands are used frequently because of their simple or common language command structure. Many implementations or operating system installs use a text-based interface that employs one of the interpreted languages. This type of user interface is known as a "command line" interface, as the commands to be passed to the interpreter are typically typed into a console or text terminal interface.

```

student@U04:~/Desktop$ neofetch
      .-/+00ssss00+/-.-
      `:+ssssssssssssss+:`
      -+ssssssssssssssyyssss+-
      .ossssssssssssssdMMMnyssso.
      /ssssssssshdmmNNmnyNMMMMhsssss/
      +ssssssssshydMMMMMMNdddyssssss+
      /ssssssshNMMMyhhyyyhNMMMNhsssss/
      .sssssssdMMMNhssssssssshNMMMdssssss.
      +ssssshhhyNMMNysssssssssyNMMMyssssss+
      ossyNMMMNyMMhssssssssssshmmhssssssso
      ossyNMMMNyMMhssssssssssshmmhssssssso
      +ssssshhhyNMMNysssssssssyNMMMyssssss+
      .sssssssdMMMNhssssssssshNMMMdssssss.
      /ssssssshNMMMyhhyyyhNMMMNhsssss/
      +sssssssdnydMMMMMMNdddyssssss+
      /ssssssssshdmmNNNnyNMMMMhsssss/
      .ossssssssssssssdMMMnyssso.
      -+ssssssssssssssyyssss+-
      `:+ssssssssssssss+:`
      .-/+00ssss00+/-.-

student@U04
-----
OS: Ubuntu 20.04.3 LTS x86_64
Host: KVM RHEL-8.2.0 PC (Q35 + ICH9, 2009)
Kernel: 5.11.0-38-generic
Uptime: 1 day, 23 hours, 27 mins
Packages: 1643 (dpkg), 8 (snap)
Shell: bash 5.0.17
Resolution: 1024x768
DE: GNOME
WM: Mutter
WM Theme: Adwaita
Theme: Yaru [GTK2/3]
Icons: Yaru [GTK2/3]
Terminal: gnome-terminal
CPU: Intel (Skylake, IBRS) (2) @ 3.096GHz
GPU: 00:01.0 Red Hat, Inc. QXL paravirtual graphic card
Memory: 809MiB / 3933MiB

  
```



Command Line Interface