

# Python Programming

## Functions



# Introduction

## Outline

Introduction

User Defined Functions

Arguments

Variables Scope

Function as Values

Docstrings

Higher Order Functions

Anonymous Functions

Hands On!

- A `function` is a named sequence of statements that performs some piece of work.
- Later on that function can be called multiple times by using its name.

## User Defined Functions

### Defining a function

A function definition includes its `name`, `parameters` (optional), and `body`:

```
def name ( parameters ):  
    body
```

# User Defined Functions

## Defining a function

A function definition includes its `name`, `parameters` (optional), and `body`:

```
def _name ( parameters ):  
    _body
```

functions.py

```
1 def greeting():  
2     print('Hello!')
```

## User Defined Functions

### Calling a function

A function is called by using its `name` and by providing the required `arguments`:

```
name ( arguments )
```

## User Defined Functions

### Calling a function

A function is called by using its **name** and by providing the required **arguments**:

```
name ( arguments )
```

functions.py

```
1 def greeting():  
2     print('Hello!')  
3  
4 greeting()
```

# User Defined Functions

## Calling a function

A function is called by using its **name** and by providing the required **arguments**:

```
name ( arguments )
```

functions.py

```
1 def greeting():  
2     print('Hello!')  
3  
4 greeting()
```

terminal

```
$ python functions.py  
Hello!
```



# User Defined Functions

## Calling a function

A function is called by using its **name** and by providing the required **arguments**:

```
name ( arguments )
```

Now let's add some **parameters**:

functions.py

```
1 def greeting(name):  
2     print('Hello {}'.format(name))  
3  
4 greeting('students')
```

terminal

```
$ python functions.py  
Hello students !
```

## User Defined Functions

### The `return` statement

Used mainly to `return` a certain result value back to the caller.

functions.py

```
1 def add_two(number):  
2     return number + 2
```

## User Defined Functions

### The `return` statement

Used mainly to `return` a certain result value back to the caller.

functions.py

```
1 def add_two(number):  
2     return number + 2  
3  
4 print(add_two(5))
```

## User Defined Functions

### The `return` statement

Used mainly to `return` a certain result value back to the caller.

functions.py

```
1 def add_two(number):  
2     return number + 2  
3  
4 print(add_two(5))
```

terminal

```
$ python functions.py  
7
```

## User Defined Functions

### The `return` statement

Used mainly to `return` a certain result value back to the caller.

functions.py

```
1 def add_two(number):  
2     return number + 2  
3  
4 for i in range(5):  
5     print('{} -> {}'.format(i, add_two(i)))
```

## User Defined Functions

### The `return` statement

Used mainly to `return` a certain result value back to the caller.

functions.py

```
1 def add_two(number):  
2     return number + 2  
3  
4 for i in range(5):  
5     print('{} -> {}'.format(i, add_two(i)))
```

terminal

```
$ python functions.py  
0 -> 2  
1 -> 3  
2 -> 4  
3 -> 5  
4 -> 6
```

### The `return` statement

- Functions immediately `exit` when a `return` statement is encountered.
- No explicit value needs to be mentioned in the `return` statement.

### The `return` statement

- Functions immediately `exit` when a `return` statement is encountered.
- No explicit value needs to be mentioned in the `return` statement.

negative.py

```
1 def first_negative(numbers):
2     for n in numbers:
3         if n < 0:
4             print(n)
5             return
6     print("No negative number found!")
7
8 first_negative([3, -5, 10, -2])
```



## User Defined Functions

### The `return` statement

- Functions immediately `exit` when a `return` statement is encountered.
- No explicit value needs to be mentioned in the `return` statement.

negative.py

```
1 def first_negative(numbers):
2     for n in numbers:
3         if n < 0:
4             print(n)
5             return
6     print("No negative number found!")
7
8 first_negative([3, -5, 10, -2])
```

terminal

```
$ python negative.py
-5
```

## User Defined Functions

### The `return` statement

- Something is always returned.

negative.py

```
1 def first_negative(numbers):  
2     for n in numbers:  
3         if n < 0:  
4             print(n)  
5             return  
6     print("No negative number found!")  
7  
8 first_negative([3, -5, 10, -2])
```

terminal

```
$ python negative.py  
-5
```

### The `return` statement

- Something is always returned.

negative.py

```
1 def first_negative(numbers):
2     for n in numbers:
3         if n < 0:
4             print(n)
5             return
6     print("No negative number found!")
7
8 print(first_negative([3, -5, 10, -2]))
```

## User Defined Functions

### The `return` statement

- Something is always returned.

negative.py

```
1 def first_negative(numbers):
2     for n in numbers:
3         if n < 0:
4             print(n)
5             return
6     print("No negative number found!")
7
8 print(first_negative([3, -5, 10, -2]))
```

terminal

```
$ python negative.py
-5
None
```

# User Defined Functions

## The `return` statement

- Something is always returned, even if no `return` statement is reached.

negative.py

```
1 def first_negative(numbers):
2     for n in numbers:
3         if n < 0:
4             print(n)
5             return
6     print("No negative number found!")
7
8 print(first_negative([]))
```

## User Defined Functions

### The `return` statement

- Something is always returned, even if no `return` statement is reached.

negative.py

```
1 def first_negative(numbers):
2     for n in numbers:
3         if n < 0:
4             print(n)
5             return
6     print("No negative number found!")
7
8 print(first_negative([]))
```

terminal

```
$ python negative.py
No negative number found!
None
```

### Required

Have to be passed during the function call (precisely in the right order).

functions.py

```
1 def add_two(number):  
2     return number + 2  
3  
4 print(add_two())
```

# Arguments

## Required

Have to be passed during the function call (precisely in the right order).

functions.py

```
1 def add_two(number):  
2     return number + 2  
3  
4 print(add_two())
```

terminal

```
$ python functions.py  
File "functions.py", line 4, in <module>  
    add_two()  
TypeError: add_two() missing 1 required positional argument: 'number'
```



# Arguments

## Default

Have a default value if no argument value is passed during the function call.

functions.py

```
1 def add_value(number, default=2):  
2     return number + default  
3  
4 print(add_value(5))
```

terminal

```
$ python functions.py  
7
```

# Arguments

## Default

Have a default value if no argument value is passed during the function call.

functions.py

```
1 def add_value(number, default=2):  
2     return number + default  
3  
4 print(add_value(5))  
5 print(add_value(5, 5))
```

terminal

```
$ python functions.py  
7  
10
```

## Arguments

### Explicit parameter mentioning

When you want to make sure that the mapping is correct.

functions.py

```
1 def add_value(number, default=2):  
2     return number + default  
3  
4 print(add_value(5, default=2))  
5 print(add_value(number=5, default=2))  
6 print(add_value(default=2, number=5))
```

terminal


```
$ python functions.py  
7  
7  
7
```

Scope refers to the variables visibility, i.e., in which program parts can be seen and used.

Scope refers to the variables visibility, i.e., in which program parts can be seen and used.

Roughly speaking:

- The whole program (module) forms one scope.
- A function definition creates a new (nested) scope.




# Variables Scope

Scope refers to the variables visibility, i.e., in which program parts can be seen and used.

Roughly speaking:

- The whole program (module) forms one scope.
- A function definition creates a new (nested) scope.
- Variables from an outside scope are visible in the inner nested scope, but you cannot (re)-assign a value to them (read only) unless they are declared global.




# Variables Scope

Scope refers to the variables visibility, i.e., in which program parts can be seen and used.

Roughly speaking:

- The whole program (module) forms one scope.
- A function definition creates a new (nested) scope.
- Variables from an outside scope are visible in the inner nested scope, but you cannot (re)-assign a value to them (read only) unless they are declared global.
- Variables inside a nested scope are not visible in the outer scope.



## Variables Scope

scope.py

```
1     g1 = 0
2     if g1 == 0:
3         g2 = 1
4
5     def some_function(p):
6         l = 3
7         print(p)
8         print(l)
9
10    # Calling the function
11    some_function(23)
12
13    print(p, l)
14
15    print(g1, g2)
```



# Variables Scope

scope.py

Module scope

```
1  g1 = 0
2  if g1 == 0:
3      g2 = 1
4
5  def some_function(p):
6      l = 3
7      print(p)
8      print(l)
9
10 # Calling the function
11 some_function(23)
12
13 print(p, l)
14
15 print(g1, g2)
```

# Variables Scope

scope.py

```
1      g1 = 0          # A global variable          Module scope
2      if g1 == 0:
3          g2 = 1
4
5      def some_function(p):
6          l = 3
7          print(p)
8          print(l)
9
10     # Calling the function
11     some_function(23)
12
13     print(p, l)
14
15     print(g1, g2)
```

## Variables Scope

scope.py

```
1      g1 = 0          # A global variable          Module scope
2      if g1 == 0:
3          g2 = 1      # Still a global variable
4
5      def some_function(p):
6          l = 3
7          print(p)
8          print(l)
9
10     # Calling the function
11     some_function(23)
12
13     print(p, l)
14
15     print(g1, g2)
```

# Variables Scope

scope.py

```
1  g1 = 0          # A global variable          Module scope
2  if g1 == 0:
3      g2 = 1      # Still a global variable
4
5  def some_function(p):                          Function scope
6      l = 3
7      print(p)
8      print(l)
9
10 # Calling the function
11 some_function(23)
12
13 print(p, l)
14
15 print(g1, g2)
```

# Variables Scope

scope.py

```
1  g1 = 0          # A global variable          Module scope
2  if g1 == 0:
3      g2 = 1      # Still a global variable
4
5  def some_function(p):                          Function scope
6      l = 3      # A local variable
7      print(p)
8      print(l)
9
10 # Calling the function
11 some_function(23)
12
13 print(p, l)
14
15 print(g1, g2)
```

# Variables Scope

scope.py

```
1  g1 = 0          # A global variable          Module scope
2  if g1 == 0:
3      g2 = 1      # Still a global variable
4
5  def some_function(p):                          Function scope
6      l = 3      # A local variable
7      print(p)
8      print(l)
9
10 # Calling the function
11 some_function(23)
12
13 print(p, l)    # Error: p and l don't exist anymore
14
15 print(g1, g2)
```

# Variables Scope

scope.py

```
1  g1 = 0          # A global variable          Module scope
2  if g1 == 0:
3      g2 = 1      # Still a global variable
4
5  def some_function(p):                          Function scope
6      l = 3      # A local variable
7      print(p)
8      print(l)
9
10 # Calling the function
11 some_function(23)
12
13 print(p, l)    # Error: p and l don't exist anymore
14
15 print(g1, g2) # g1 and g2 still exist
```

# Variables Scope

scope.py

Built-in scope

Module scope

```
1  g1 = 0          # A global variable
2  if g1 == 0:
3      g2 = 1      # Still a global variable
4
5  def some_function(p):
6      l = 3        # A local variable
7      print(p)
8      print(l)
9
10 # Calling the function
11 some_function(23)
12
13 print(p, l)      # Error: p and l don't exist anymore
14
15 print(g1, g2)    # g1 and g2 still exist
```

Function scope



### Hiding variables

If in a new scope a variable is created that already exists in an outer scope, the new variable will hide the outer variable.

## Hiding variables

If in a new scope a variable is created that already exists in an outer scope, the new variable will hide the outer variable.

scope\_hiding.py

```
1  a = 1
2
3  def some_function():
4      a = 2 # Hides the global a variable
5      print(a)
6
7  # Calling the function
8  some_function()
9  print(a)
```

# Variables Scope

## Hiding variables

If in a new scope a variable is created that already exists in an outer scope, the new variable will hide the outer variable.

scope\_hiding.py

```
1 a = 1
2
3 def some_function():
4     a = 2 # Hides the global a variable
5     print(a)
6
7 # Calling the function
8 some_function()
9 print(a)
```

terminal

```
$ python scope_hiding.py
2
1
```

# Variables Scope

## Hiding variables

If in a new scope a variable is created that already exists in an outer scope, the new variable will hide the outer variable.

scope\_hiding.py

```
1  a = 1
2
3  def some_function():
4      a = 2 # Hides the global a variable
5      print(a)
6
7  # Calling the function
8  some_function()
9  print(a)
```

terminal

```
$ python scope_hiding.py
2
1
```

This applies to function parameters as well.

## Variables Scope

### The `global` keyword

Allows a variable to be changed outside of the current scope.

# Variables Scope

## The `global` keyword

Allows a variable to be changed outside of the current scope.

```
global.py
1  a = 1
2
3  def some_function():
4      global a  # a is the global one
5      a = 2
6      print(a)
7
8  # Calling the function
9  some_function()
10 print(a)
```

# Variables Scope

## The `global` keyword

Allows a variable to be changed outside of the current scope.

```
global.py
1  a = 1
2
3  def some_function():
4      global a  # a is the global one
5      a = 2
6      print(a)
7
8  # Calling the function
9  some_function()
10 print(a)
```

terminal

```
$ python global.py
2
2
```

### What about parameters and arguments?

parameters.py

```
1  def some_function(b):  
2      b = 2  
3      print(b)  
4  
5  a = 1  
6  
7  print(a)  
8  
9  # Calling the function  
10 some_function(a)  
11  
12 print(a)
```



## Variables Scope

### What about parameters and arguments?

parameters.py

```
1 def some_function(b):  
2     b = 2  
3     print(b)  
4  
5 a = 1  
6  
7 print(a)  
8  
9 # Calling the function  
10 some_function(a)  
11  
12 print(a)
```

terminal

```
$ python parameters.py  
1  
2  
1
```

## Mutable arguments

mutable\_params.py

```
1 def some_function(a_list):
2     a_list = 13
3     print('a_list:', a_list)
4
5 a = [7, 5]
6
7 print('a before the call:', a)
8
9 # Calling the function
10 some_function(a)
11
12 print('a after the call:', a)
```

# Variables Scope

## Mutable arguments

mutable\_params.py

```
1 def some_function(a_list):
2     a_list = 13
3     print('a_list:', a_list)
4
5 a = [7, 5]
6
7 print('a before the call:', a)
8
9 # Calling the function
10 some_function(a)
11
12 print('a after the call:', a)
```

terminal

```
$ python mutable_params.py
a before the call: [7, 5]
a_list: 13
a after the call: [7, 5]
```

### Mutable arguments

However, element changes to update the argument.

mutable\_params.py

```
1 def some_function(a_list):
2     a_list[1] = 13
3     print('a_list:', a_list)
4
5 a = [7, 5]
6
7 print('a before the call:', a)
8
9 # Calling the function
10 some_function(a)
11
12 print('a after the call:', a)
```

# Variables Scope

## Mutable arguments

However, element changes to update the argument.

mutable\_params.py

```
1 def some_function(a_list):
2     a_list[1] = 13
3     print('a_list:', a_list)
4
5 a = [7, 5]
6
7 print('a before the call:', a)
8
9 # Calling the function
10 some_function(a)
11
12 print('a after the call:', a)
```

terminal

```
$ python mutable_params.py
a before the call: [7, 5]
a_list: [7, 13]
a after the call: [7, 13]
```

## Function as Values

We can pass functions around just like other values, and call them.

function\_values.py

```
1 def add_two(number):
2     return number + 2
3
4 def add_some_other_number(number, other_number=12):
5     return number + other_number
6
7 functions = [add_two, add_some_other_number]
8 for function in functions:
9     print(function(7))
```

## Function as Values

We can pass functions around just like other values, and call them.

function\_values.py

```
1 def add_two(number):
2     return number + 2
3
4 def add_some_other_number(number, other_number=12):
5     return number + other_number
6
7 functions = [add_two, add_some_other_number]
8 for function in functions:
9     print(function(7))
```

terminal

```
$ python function_values.py
9
19
```

## Docstrings

- Regular string values which you start the function definition body with.
- You can access a docstring using the `help()` built-in.

docstrings.py

```
1 def factorial(n):
2     """Compute factorial of n in the obvious way."""
3     if n == 0:
4         return 1
5     else:
6         return factorial(n - 1) * n
7
8 help(factorial)
```



## Docstrings

- Regular string values which you start the function definition body with.
- You can access a docstring using the `help()` built-in.

docstrings.py

```
1 def factorial(n):
2     """Compute factorial of n in the obvious way."""
3     if n == 0:
4         return 1
5     else:
6         return factorial(n - 1) * n
7
8 help(factorial)
```

terminal

```
$ python docstrings.py
Help on function factorial in module __main__:
factorial(n)
Compute factorial of n in the obvious way.
```

## Higher Order Functions

Take a function as an argument.

IPython

```
In [1]: help(map)
Help on class map in module builtins:
class map(object)
|   map(func, *iterables) --> map object
|
|   Make an iterator that computes the function using arguments from
|   each of the iterables. Stops when the shortest iterable is
|   exhausted.

In [2]: list(map(add_two, [1, 2, 3, 4]))
Out[2]: [3, 4, 5, 6]
```

# Anonymous Functions

Can be created with the `lambda` keyword:

```
lambda parameters : expression
```

anonymous.py

```
1 x_times_7 = lambda x: x * 7
2 print(x_times_7(4))
```

# Anonymous Functions

Can be created with the `lambda` keyword:

```
lambda parameters : expression
```

anonymous.py

```
1 x_times_7 = lambda x: x * 7
2 print(x_times_7(4))
```

terminal

```
$ python anonymous.py
28
```

# Anonymous Functions

Can be created with the `lambda` keyword:

```
lambda parameters : expression
```

anonymous.py

```
1 x_times_7 = lambda x: x * 7
2 print(x_times_7(4))
3
4 for i in list(map(lambda x: x+2, range(4))):
5     print(i)
```

# Anonymous Functions

Can be created with the `lambda` keyword:

```
lambda parameters : expression
```

anonymous.py

```
1 x_times_7 = lambda x: x * 7
2 print(x_times_7(4))
3
4 for i in list(map(lambda x: x+2, range(4))):
5     print(i)
```

terminal

```
$ python anonymous.py
28
2
3
4
5
```

You are now able to:

- Create your own user defined functions.
- Call your defined functions with the right arguments.
- Understand variables scope.
- Write docstrings for your functions.
- Use higher order functions.
- Employ anonymous functions.

## Hands On!

1. Write a Python function that returns the maximum of two numbers.
2. Write a Python function that returns the maximum of three numbers. Try to reuse the first maximum of two numbers function.
3. Write a Python function that accepts a list as a parameter. Next, it determines and prints the number of positive and negative numbers.



## Acknowledgements

Martijn Vermaat  
Jeroen Laros  
Jonathan Vis

