

Practical Concurrent and Parallel Programming X

Streams, Parallel Streams and RxJava

Jørgen Staunstrup

- Java Streams
- RxJava

Previously on PCPP:

Distribution (similar tasks to many threads)




Streams:

Pipeline (different tasks to each thread F, G, H, ...)




Supercomputer



DATALOGFORENINGEN | BRIAN VINTER

- Data is often communicated as a stream
- from a file,
- from the internet
- from the user interface
- ...



Java Stream


`x().F().G().H()`



Closely related to: $H(G(F(x)))$

functional programming

Stream example



X is a stream of words: ablaut able ableeze ... zyme

F discards all words with 1 character

G discards all words that are capitalized

H counts number of words

Java (imperative)



```
public static String F(String s) {  
    return s.length() > 1 ? s : null;  
}  
  
public static String G(String s) {  
    if (s==null) return null;  
    return Character.isLowerCase(s.charAt(0)) ? s : null;  
}  
  
public static int H(String s) {  
    return s==null ? 0 : 1;  
}  
...  
while ((line= reader.readLine()) != null) {  
    word= F(line);  
    smallLetters= G(word);  
    count+= H(smallLetters);  
}
```



x().F().G().H()

```
count= readWords(filename) // makes a stream of words
    .filter( w -> w.length()>1 ) // F
    .filter( w -> Character.isLowerCase(w.charAt(0)) ) // G
    .count(); // H
```

```
count= readWords(filename)
    .parallel()
    .filter( w -> w.length()>1 )
    .filter( w -> Character.isLowerCase(w.charAt(0)) )
    .count();
```



x().F().G().H()

```
count= readWords(filename) // makes a stream of words
      .filter( w -> w.length()>1 ) // F
      .filter( w -> Character.isLowerCase(w.charAt(0)) ) // G
      .count(); // H
```

A sequence of stream
method calls is commonly
known as *stream pipeline*

Lambda expressions



The streams are lazy (driven by the terminal operation)

```
count= readWords(filename)  // source
      .filter( w -> w.length()>1 ) // intermediate
      .filter( w -> Character.isLowerCase(w.charAt(0)) )
      .count(); // terminal
```

There are three different types of stream elements:

- *sources* (arrays, collections, IO, generators)
- *intermediate operations* (transforming one stream into another (e.g. filter))
- *terminal operations* (count, sum, forEach, ...)



Provides the data for the stream

Examples of stream sources are:

- Input (files or network)
- The Arrays class has a number of utilities, for example:
`Arrays.stream(arr)`

Other examples of collections?

<https://howtodoinjava.com/java/stream/java-streams-by-examples/>

Intermediate operators



A computation/transformation on *each* element of the string

Examples of intermediate operations are:

- filter – takes a lambda expression lambda returning a boolean, if the boolean is true the element is included in the output stream
- map – transforms each element
- limit(n) – returns a stream of the first n elements
- skip(n) – returns a stream without the first n elements
- distinct – returns a stream without duplicated elements
- sorted - returns a stream with the elements sorted

See Sestoft's Java precisely and the java documentation for a complete list



```
count= readWords(filename) // makes a stream of words
      .filter( w -> w.length()>1 ) // F
      .filter( w -> Character.isLowerCase(w.charAt(0)) ) // G
      .count(); // H
```

Which operation(s) is/are
intermediate?

BufferedReader (file)

· 15



Exercise: 10.2

```
public static void main(String[] args) {  
    String filename = "src/main/resources/english-words.txt";  
    System.out.println( readWords(filename).count());  
}  
  
public static Stream<String> readWords(String filename) {  
    try {  
        BufferedReader reader= new BufferedReader(new FileReader(filename));  
        return ... // TO DO: Implement properly  
    } catch (IOException exn) { return Stream.<String>empty(); }  
}
```

<https://docs.oracle.com/javase/7/docs/api/java/io/BufferedReader.html>

`Stream<String>`

`lines()`

Returns a `Stream`, the elements of which are lines read from this `BufferedReader`

BufferedReader (URL)

· 16



Exercise: 10.2

```
String filename = "https://staunstrups.dk/jst/english-words.txt";  
System.out.println(readWordsFromURL(urlname).count());
```

```
public static Stream<String> readWordsFromURL(String urlname) {  
    try {  
        HttpURLConnection connection=  
            (HttpURLConnection) new URL(urlname).openConnection();  
        BufferedReader reader=  
            new BufferedReader(new InputStreamReader(connection.getInputStream()));  
        return reader.lines();  
    } catch (IOException exn) { return Stream.<String>empty(); }  
}
```

<https://docs.oracle.com/javase/7/docs/api/java/io/BufferedReader.html>

Defining a Java stream



- Using the `Arrays` class
 - `Arrays.stream(array)`
- Most Java collections have a method `stream()` that turns the collection into a stream
- `Stream.of(1,2,3,4)` creates a stream with those elements
- Functional iterators for infinite streams
 - `IntStream nats = IntStream.iterate(0, x->x+1)`
- **`BufferedReader`** (important for exercises)

```
Stream<String>
```

```
lines()
```

Returns a `Stream`, the elements of which are lines read from this `BufferedReader`



Provides the *result* of the stream computation

Examples of terminal operations are:



- min, max, sum, average, count (number streams)
- forEach e.g., `forEach(System.out::println)`
- reduce / collect (introduced shortly)

<https://howtodoinjava.com/java/stream/java-streams-by-examples/>





```
count= readWords(filename)  // makes a stream of words
    .filter( w -> w.length()>1 )  // F
    .filter( w -> Character.isLowerCase(w.charAt(0)) )  // G
    .count();  // H
```

Which operation(s) is/are terminal?



`map (x -> x+2)`



`limit (2)`



Terminal operation reduce



- Reduce all elements of the stream to a single value by applying a function
- **reduce(identity, accumulator)**
 - **identity**: The identity element is both the initial value of the reduction and the default result if there are no elements in the stream.
 - **accumulator**: The accumulator function takes two parameters: a partial result of the reduction and the next element of the stream.
- Example
 - Sum of squares of first 100 natural numbers
 - `IntStream.range(0,100).reduce(0, (a,b) -> a+b*b)`




- Reduce can also be called without identity parameter
- Then it returns an `Optional` value
 - A container object which may or may not contain a non-null value.
 - Needed in case the reduction is performed on an empty stream.
- Example
 - Sum of squares of first 100 natural numbers
 - `IntStream.range(0,100).reduce((a,b) -> a+b*b).orElse(0)`
- There are other built-in reductions: `sum`, `max`, `min`, `average`, etc...

Example with everything so far



· 24





- Here is an example with everything we have seen so far
 - Amount of even numbers in the range 0 to 99

```
IntStream.iterate(0,x->x+1)
    .limit(100)
    .filter(x -> x%2==0)
    .map(x -> 1)
    .reduce(0, (a,b) -> a+b);
```



Streams may or may not have a defined *encounter order*


- **List** and **Arrays** are intrinsically ordered
- **HashSet** is not ordered

An intermediate operation e.g., **sorted** transforms an unordered **Stream** into an ordered **Stream**

<https://docs.oracle.com/javase/8/docs/api/java/util/stream/package-summary.html#Ordering>

Parallel (intermediate)

· 27



```
IntStream.range(0, range)
    .parallel()
    .filter(i -> isPrime(i))
    .count()
```

← ordered

← ?

`IntStream.range` produces an *ordered* stream

`parallel` is an operation in `BaseStream`

OVERVIEW	PACKAGE	CLASS	USE	TREE	DEPRECATED	INDEX	HELP
PREV CLASS	NEXT CLASS	FRAMES	NO FRAMES	ALL CLASSES			
SUMMARY: NESTED FIELD CONSTR METHOD DETAIL: FIELD CONSTR METHOD							
compact1, compact2, compact3 java.util.stream							
Interface BaseStream <T,S extends BaseStream<T,S>>							

parallel()

Returns an equivalent stream that is parallel.

<https://docs.oracle.com/javase/8/docs/api/java/util/stream/BaseStream.html>



- If you try to modify a stream you are operating you will get a `ConcurrentModificationException` at runtime

- So don't do it 😊

- Cannot be detected at compile time. It depends on the programmer.

- From the Java documentation

• Streams enable you to execute possibly-parallel aggregate operations over a variety of data sources, including even non-thread-safe collections such as `ArrayList`. This is possible only if we can prevent interference with the data source during the execution of a stream pipeline. [...] For most data sources, preventing interference means ensuring that the data source is not modified at all during the execution of the stream pipeline.

Example: stream of objects



```
class Employee {
    int id;
    String dept;
    int salary;

    public Employee(int id, String dept, int salary) {
        this.id      = id;
        this.dept    = dept;
        this.salary  = salary;
    }
    public int getId() { return this.id; }
    public String getDept() { return this.dept; }
    public int getSalary() { return this.salary; }
}

static private Stream<Employee> randomEmployees() {
    ...
}
```

- It is a reduction operation that allows to collect the results of a stream into a Java collection or summarize them using complex criteria
- For instance, converting a stream into a list

```
List<Integer> l = randomEmployees()  
    .limit(50)  
    .map(Employee::getId)  
    .collect(Collectors.toList());
```

Terminal operation: collect + groupingBy


· 31



- Group employees by department

```
Map<String,List<Employee>> m = randomEmployees()  
    .limit(50)  
    .collect(Collectors.groupingBy(Employee::getDept));
```

Id: 0 Dept: CS Salary: 151	Id: 1 Dept: BI Salary: 150	Id: 3 Dept: DD Salary: 149	Id: 0 Dept: DD Salary: 10	...
----------------------------------	----------------------------------	----------------------------------	---------------------------------	-----



`collect(Collectors.groupingBy(Employee::getDept))`

CS	Id: 0 Dept: CS Salary: 151	...	
BI	Id: 1 Dept: BI Salary: 150	...	
DD	Id: 3 Dept: DD Salary: 149	Id: 0 Dept: DD Salary: 10	...

Map<String,List<Employee>>

Printing the result



```
randomEmployees ()  
  .limit(50)  
  .collect(Collectors.groupingByConcurrent (Employee::getDept))  
  .forEach((k,v) ->  
    System.out.println(k+":      "+v  
      .stream()  
      .map(Employee::getId)  
      .collect(Collectors.toList())  
    ));
```


- You can create a parallel stream by calling
 - `parallelStream()` on, e.g., a collection, or
 - `parallel()` on a stream

Java Parallel Streams

· 34



- Parallelization of streams is very easy (remember the beginning of the lecture). Disjoint streams (from the original stream) are assigned to distinct threads from a thread pool



- Since execution is parallel the processing of the stream is not guaranteed to in order
- For instance, run this program
 - `IntStream.range(0,10).parallel().forEach(System.out::println);`
- In this case, it may be mitigated with `forEachOrdered`
 - `IntStream.range(0,10).parallel().forEachOrdered(System.out::println);`


Would it be ok if parallel streams work concurrently on the Map resulting from a `groupingBy` operation?

Java Parallel Streams | Grouping

· 38



- In the local reduce operation, each thread creates locally its own “container” (collection or value) for the partial results
- In a final step, a single thread merges the local containers, so no race conditions arise
- However this step is very memory waste full, as it needs to create one container per partition of stream



- A possible solution is to use `groupingByConcurrent`
- This function uses a `ConcurrentHashMap` that all threads can access concurrently.

```
collect(Collectors.groupingByConcurrent(Employee::getDept))
```

Counting primes on Java 8 streams

· 41



Our old standard Java for loop:

Classical efficient
imperative loop

```
int count = 0;
for (int i=0; i<range; i++)
    if (isPrime(i))
        count++;
```

Sequential Java 8 stream:

```
IntStream.range(0, range)
    .filter(i -> isPrime(i))
    .count()
```

Parallel Java 8 stream:

```
IntStream.range(0, range)
    .parallel()
    .filter(i -> isPrime(i))
    .count()
```

PCPP 2019

Counting primes on Java 8 streams

· 42



Our old standard Java for loop:

Classical efficient
imperative loop

```
int count = 0;
for (int i=0; i<range; i++)
    if (isPrime(i))
        count++;
```

Sequential Java 8 stream:

Pure functional
programming ...

```
IntStream.range(0, range)
    .filter(i -> isPrime(i))
    .count()
```

Parallel Java 8 stream:

```
IntStream.range(0, range)
    .parallel()
    .filter(i -> isPrime(i))
    .count()
```

PCPP 2019

Counting primes on Java 8 streams

· 43



Our old standard Java for loop:

Classical efficient
imperative loop

```
int count = 0;
for (int i=0; i<range; i++)
    if (isPrime(i))
        count++;
```

Sequential Java 8 stream:

Pure functional
programming ...

```
IntStream.range(0, range)
    .filter(i -> isPrime(i))
    .count()
```

Parallel Java 8 stream:

... and thus
parallelizable and
thread-safe

```
IntStream.range(0, range)
    .parallel()
    .filter(i -> isPrime(i))
    .count()
```

PCPP 2019

Counting the primes in 2 ... 100.000

Using Mark7

Sequential	4891635.9	ns	21879.73	64
Stream	4953867.6	ns	63873.82	64
ParallelStream	1363886.8	ns	10621.99	256

Intel i7 (4 cores) speed-up: 3.6 x



(input) UI elements (buttons, textfields, ...): **observables**

(output) UI elements (textfields, ...): **observers**

Example: RxJava for Android:

```
Button button; ...
RxView.clicks(button)
    .subscribe(i -> {
        //Perform some work here//
    });
```

https://code.tutsplus.com/tutorials/rxjava-for-android-apps-introducing-rxbinding-and-rxlifecycle--cms-28565?_ga=2.125428746.1281241990.1512099718-1264555618.1502875086




```
Observable.from(letters)
    .map(String::toUpperCase)
    .subscribe(letter -> result += letter);
assertTrue(result.equals("ABCDEFGH"));
```

- *Observable* propagates data from a data source
- An *observer* receives data (via its subscribe method)

from <https://www.baeldung.com/rx-java>

RxJava version of a Stopwatch

48



All three buttons must respond to clicking
When started the display must update every second

⇒ 4 streams

- one for each button
- one for handling the clock ticking

```
timer.subscribe(display) ;  
rxPushStart.subscribe(displaysetRunningTrue) ;  
rxPushStop.subscribe(displaysetRunningFalse) ;  
rxPushStart.subscribe(displaysetAllzero) ;
```



```
const button= document.querySelector("button");
const observer = {
  next: function(value) {
    ... // handle click
  },
  error: function(err) { ... },
  complete: function() { ... }
};

// Create an Observable from event
const observable= Rx.Observable.fromEvent(button, "click");
// Subscribe to begin listening for async result
observable.subscribe(observer);
```

<https://rxjs.dev/guide/overview>

Different types of Observables (2)



50

Observables can be created in many different ways, e.g.

```
String[] letters= {"a", "b", "c", "d", "e", "f", "g"};  
Observable<String> observable= Observable.fromArray(letters);
```

```
List<Integer> list= new ArrayList<>(Arrays.asList(1, 2, 3, 4, 5, 6));  
Observable<Integer> observable= Observable.fromIterable(list);
```

```
Observable<Integer> observable= Observable.range(11, 111);
```

```
Observable<Integer> observable= Observable.just(1, 4, 9, 221);
```

<https://betterprogramming.pub/rxjava-different-ways-of-creating-observables-7ec3204f1e23>



```
Observable<Integer> observable= Observable.range(11, 111).take(10);
```

```
Observable.range(11, 111)  
    .filter(i -> (i%2)==0)  
    .subscribe(System.out::println);
```

<https://github.com/ReactiveX/RxJava/wiki/Alphabetical-List-of-Observable-Operators>

Many subscribers



52


An observable can have several observes

important difference to Java stream !!!


```
rxPush.subscribe(display1) ;  
rxPush.subscribe(display2) ;
```

Backpressure

· 53



An observable may emit items so fast that the consumer can not keep up, this is called *backpressure*



Advice on handling backpressure

<https://medium.com/@srinuraop/rxjava-backpressure-3376130e76c1>

RxJava vs Java stream

54



RxJava

push-based
many subscribers
has rich API
must be added as
dependency

Java Stream

pull-based (terminal operator)
one subscriber
few methods
built into Java

<https://www.reactiveworld.net/2018/04/29/RxJava-vs-Java-Stream.html>

Libraries for many languages: Java, .net, JavaScript, ...

[ReactiveX website](#)

Nice introduction to RxJava: <https://github.com/ReactiveX/RxJava>