## context Ctx\_PartProc\_Trans

- //\* \*\*\*\*\*\*\*\*\*\*\*\*\*\*\*\*\*\*
- // The Event-B model of ARINC 653 Part 1
- // Created by Yongwang Zhao (zhaoyongwang@gmail.com)
- // National Key Laboratory of Software Development Environment (NLSDE)
- // School of Computer and Engineering, Beihang University, Beijing, China
- // \*

## sets PARTITIONS PROCESSES PARTITION MODES PROCESS STATES

## constants PM\_IDLE PM\_NORMAL PM\_WARM\_START

PM\_COLD\_START // partition operating mode, according to ARINC653

PS\_Dormant PS\_Ready PS\_Waiting PS\_Suspend PS\_WaitandSuspend

**PS\_Running** 

## axioms

@axm\_part\_finite finite(PARTITIONS)

@axm\_processes\_finite finite(PROCESSES)

@axm\_partition\_partitionmodes partition(PARTITION\_MODES,{PM\_IDLE},

```
{PM_NORMAL},{PM_COLD_START},{PM_WARM_START})
  @axm_partition_procstates partition(PROCESS_STATES,{PS_Dormant}, {PS_Ready}, {PS_Waiting},
{PS_Suspend}, {PS_WaitandSuspend}, {PS_Running})
  @axm_partition_nums card(PARTITIONS) > 0 ^ card(PARTITIONS) < 256</pre>
```

end