
Dev Guide Book @Adview Android

Contents


- I. Register and configure SDK-KEY
- II.About AdViewSDK_Android-3.4.4
- III. Add SDK
- IV. AndroidManifest.xml text configuration
- V. Acquire ad configurations
- VI. Create banner advertising
- VII. Create interstitial advertising
- VIII. Create opening screen ad
- IX. Create native advertising
- X. Create video advertising
- **XI. Adding Proguard-rules**
- XII. Adding custom ad network
- XIII. Add custom ad platform
- XIV. Contact us

I. Register and configure SDK-KEY


- Visit AdView website http://adview.com and complete the registration process.
- After Login you will land on "My Products" page by default, select "Publish App"
- 3. Select "Android" follow the prompts to complete the relevant information About the application and click on "Next" button at the end where you will be redirected to "APP management" page
- 4. Under "App managemnet" page Click "Next" button at the bottom --> you will get the sole SDK key --> click "Finish" button at the bottom centre of the page and you will be redirected to the below page.




5.Now click on "configure" against your appplication, then you will be redirected to "APP management" page → under the Ad format you want to configure (Banner,interstitial,video,open screen and native) open the switch against Auction ads(AdView Ads) and in case you want to add any custom ad networks (like InMobi, AdMob etc...,) Please refer Adding Custom network for further steps, the cumulative percentage muste be 100%,then click save button. Generally recommended number of platforms is 1-3.




6.For **video ad or native ad**,Please configure in AdView Dash board .Please click **under review or setting** label ,you will get dialog box.In the dialog box For Auction ads ,please click save button in dialog box and click save button in bottom of the page .For other platforms ,please configure those custom adNetworks ids .





7.(Optional) if you wish to show prompt when you click on the ad - Under **app management** --> select **"Edit"** against your app, Switch on "Twice confirmation" button under "Advertising text settings".



Notes:

- 1. we have provided you with Adview Android Unity3d SDK which gives you the freedom to choose your favourite ad network. in order to add custom ad netwroks please refer to this **XIII. Adding custom ad network**.
- If you are fresher, you don't know much about ad platform, which ad platform to choose or which ad platform revenue is stable, we suggest you to use bidding first.
- Bidding and remnant ads need to complement market information at background, if the status is "Under review" you will be receiving test ads. and you will get formal ads only after "pass reviewed" by the AdView team.
- 4. Ads will be shown of only those ad platforms for which the **switch** is on against them.
- 5. Only the "capacity" of those ad platforms for which the switch is on will be valid, the ad newtork with higher proportion will get prior request, for all ad platforms with status as ON, the cumulative should be 100%. Other

- wise the your priority can't be saved.
- 6. For Banner ad, full screen/interstitial, opening screen ,etc, there's a save button at the bottom of the page. You should click the save button every time you modify a ad format, otherwise the modification is invalid.
- 7. **Region optimization:** Region optimization function means mobile phone displays the regional configured ads when it's with in the region, while in foreign country it display foreign configured ads to meet the different demands to the maximum extent. When the region optimization function is closed, it does not distinguish between home and abroad.
- 8. In case you wish to show the same ad format more than once (like 2 banner ads) you need to create a new project (My product page --> publish app) with same credentials to get a new SDK key and the integration process remains same, you need not create a new project if the ad formats are different

II.About AdViewSDK Android-3.4.4

 In the AdViewSDK_Android-3.4.4 package contains all files needed for smooth integration and some of the important fils include AdViewTestDemoEN and libs.

AdViewTestDemoEN

AdViewTestDemoEN project which includes all types of ad format (banner,interstitial,video,native,open screen) sample code with explanation.you can run the application. you can see **test Ads**.


libs

It contains all the .jar file SDK needed for ad platform integration.

(Libinfo.pdf has the ad platform instructions corresponding to each jar.)

III. Add SDK

- 1. In the AdViewSDK_Android-3.4.4 folder contains libs folder ,it contains the SDK for all ad platforms. (Libinfo.pdf has the ad platform instructions corresponding to each jar.)
- Please copy and paste AdViewSDK_Android.jar, google-playservices.jar into your application lib folder.you'll need to integrate the Google Play Services SDK into your app.This is mandatory; without Google Play Services, the SDK cannot function.
- 3. In order to add new ad network please copy the .jar file of that particular ad platform provided by AdView to your lib folder and follow the same for all other ad platforms you would like to integrate. In case of InMobi add the InMobi.jar and Picaso.jar files.Please refer for adding custom ad Network .



IV. AndroidManifest.xml text configuration

4.1 Add permission code

Required permissions should be added.

please refer to AndroidManifest file in the AdViewTestDemoEN project.

```
<uses-permission android:name="android.permission.READ_PHONE_ST
ATE" />
<uses-permissionandroid:name="android.permission.ACCESS_COARSE_
LOCATION"/>
<uses-permissionandroid:name="android.permission.ACCESS_FINE_LO
CATION" />
<uses-permissionandroid:name="android.permission.ACCESS_WIFI_ST
ATE" />
<uses-permissionandroid:name="android.permission.WRITE_EXTERNAL_
STORAGE"/>
<uses-permissionandroid:name="android.permission.READ_EXTERNAL_
STORAGE"/>
```

Note:

- -INTERNET: allow to visit network (required)
- -ACCESS_NETWORK_STATE: allow to visit various status of mobile phone (required)
- -ACCESS_COARSE_LOCATION: allow a procedure to visit CellID or WIFI to get the rough position.
- -ACCESS_FINE_LOCATION: allow a procedure to visit the accurate position (for example, GPS)
- -ACCESS WIFI STATE: allow a procedure to visit WIFI status
- **-WRITE_EXTERNAL_STORAGE:** allow a procedure to visit outside storage device and can cache ads.

-READ_EXTERNAL_STORAGE: allow a procedure to visit outside storage device

4.2 Add Activity declaration

The given code should be added to in AndroidManifest file for AdView, as some platforms need to declare activity to work normal, please refer to **AndroidManifest** file in **AdViewTestDemoEN** project.

Configurations that adview bidding ads should add:

```
<service android:name="com.kyview.DownloadService" />
<activity android:name="com.kyview.AdviewWebView" />
<activity android:name="com.kyview.AdActivity" />
<!-- Adiview bidding video -->
<activity android:name="com.kuaiyou.video.vast.activity.VASTAdActivity"
android:hardwareAccelerated="true"
android:screenOrientation="landscape"/>
```

4.3 Appointed app channel

Please add the below code in the AndroidMainfest file:

```
<meta-data android:name="AdView_CHANNEL" android:value="GFAN">
</meta-data>
```

(You must add the above code, otherwise you application won't be able to pass the review);

Note:

You can refer **AndroidManifest** file in **AdViewTestDemoEN** Project.

V. Acquire ad configurations

Note:

- 1. InitConfiguration serve for the overall procedure, just need to transfer once only.
- 2. The set methods above are optional, not required.
- 3. From 3.2.4 version, SDK supports setting up multiple ad slots (SDK-KEY) in one application. Take 3 ad slots of demo keyset for example, some APP would like to set different ad slots in multiple Activities, thus to statistic the user visit amount of each Activity based on the amount of ad display. If one ad slot can meet the demand of APP, then there's no need to apply multiple ad slots.

```
// Be sure to initialize before requesting ads, otherwise the a
ds cannot be used
// set ad request configured parameter,
//you can use default configuration : InitConfiguration. create
Default(this);
InitConfiguration initConfig = new InitConfiguration.Builder(th
is)
//real-time access to configuration, not required
.setUpdateMode(UpdateMode.EVERYTIME)
// banner switcher can be closed
.setBannerCloseble(BannerSwitcher.CANCLOSED)
//Interstitial Type
.setInstlDisplayType(InitConfiguration.InstlDisplayType.POPUPWI
NDOW_MODE).build();
```

```
//respectively request banner,interstitial,native,
//opening screen ad configuration for one SDK_KEY
AdViewBannerManager.getInstance(this).init(MainActivity.initCon
figuration,new String[]{MainActivity.SDK_KEY});
AdViewInstlManager.getInstance(this).init(MainActivity.initConf
iguration,new String[]{MainActivity.SDK_KEY});
AdViewNativeManager.getInstance(this).init(MainActivity.initCon
figuration,new String[]{MainActivity.SDK_KEY});
AdViewSpreadManager.getInstance(this).init(MainActivity.initCon
figuration,new String[]{MainActivity.SDK_KEY});
AdViewVideoManager.getInstance(this).init(MainActivity.initConf
iguration,new String[]{MainActivity.SDK_KEY});
```

```
// respectively request banner, interstitial, native, opening s
creen ad
//configuration, keyset can be one or more key.
//For Example If you need more than one banner placement while
//initialization this way .
AdViewBannerManager.getInstance(this).init(initConfig,MainActiv
ity.keySet);
AdViewInstlManager.getInstance(this).init(initConfig,MainActivi
ty.keySet);
AdViewNativeManager.getInstance(this).init(initConfig,MainActiv
ity.keySet);
AdViewVideoManager.getInstance(this).init(initConfig,MainActivi
ty.keySet);
```

Note:

You can refer to the code of **MainActivity** in **AdViewTestDemoEN** Project.

VI. Create banner advertising

6.1 Add ads through adding code

Add a banner code to layout file,

```
<FrameLayout
    android:id="@+id/ad_view"
    android:layout_width="match_parent"
    android:layout_height="wrap_content"
    android:gravity="center_horizontal" />
```

Add the following code to your activity:

```
//Initialization for Banner
AdViewBannerManager.getInstance(this).init(initConfiguration,ne
w String[]{SDK_KEY});
```

```
// Gets the currently requested banner View,upload it to y
our own layout.
     FrameLayout layout = (FrameLayout) findViewById(R.id.adLay
out):
        if (layout == null)
            return;
        View view = AdViewBannerManager.getInstance(this).getAd
ViewLayout(this,
                SDK KEY);
        if (null != view) {
            ViewGroup parent = (ViewGroup) view.getParent();
            if (parent != null) {
                parent.removeAllViews();
            }
        }
   // request banner ads after initialization
        AdViewBannerManager.getInstance(this).requestAd(this, S
DK_KEY, this);
        view.setTag(SDK KEY);
        layout.addView(view);
        layout.invalidate();
```

```
// onAdClose Call Back method
@Override
public void onAdClose(String arg0) {
Log.i("AdBannerActivity", "onAdClose");
if (null != layout)
    layout.removeView(layout.findViewWithTag(arg0));
}
```

6.2 Ad Banner events handling

To receive events from ad, you should implement an event listener interface AdViewBannerListener.

After you implement this listener you will get the following methods.

```
public interface AdViewBannerListener{
    /**
    * Use this function when the ad is clicked
    */
    public void onAdClick(String key);

    /**
    * Use this function when the ad is displayed
    */
    public void onAdDisplay(String key);

    /**
    * Use this function when the ad is closed
    */
    public void onAdClose(String key);

    /**
    * Use this function only when the ad is interrupted
    by abnormity or failure
```

```
*/
public void onAdFailed(String key);

/**
  * once ad is Ready while this function will triggered
  */
public void onAdReady(String key);
}
```

Note:

You can refer to the code of **AdBannerActivity** in **AdViewTestDemoEN** Project.

VII. Create interstitial advertising

7.1 create interstitial

Note:

Since interstitial ad has a certain life cycle, Please do not wait too long after the request to call showAd method, so as to avoid invalid advertising.

Add the following code to your activity:

```
// interstitial ad request after initialization, ad request
and display, used alone
   AdViewInstlManager.getInstance(this).requestAd(this,SDK_KEY
);

// After ad request succeed , call the display ad
   AdViewInstlManager.getInstance(this).showAd(this,SDK_KEY);
```

7.2 Ad Interstitial Event Handling

To receive events from ad, you should implement an event listener interface AdViewInstlListener.

After you implement this listener you will get the following methods.

```
public interface AdViewInstlListener {
       /**
        * Use this function when the ad is clicked
        public void onAdClick(String key);
        /**
        * Use this function when the ad is displayed
        public void onAdDisplay(String key);
        /**
        * Use this function when the ad is disappeared
        public void onAdDismiss(String key);
        /**
        * Use this function when the ad is successfully receiv
ed
        */
        public void onAdReceived(String key);
        /**
        * Use this function when the ad is failed
        public void onAdFailed (String key);
   }
```

7.3 Create custom style interstitial

You can customize the popup Intrstitial ad, please refer AdInstlActivity for the entire code .Please refer **AdInstlActivity** in **AdViewTestDemoEN** Project.

```
// You need to set the user-managed mode when initializatio
n, and you must manually call the display
    //after the setting
   InitConfiguration.setInstlControlMode(InstlControlMode.USER
CONTROL);
   // request interstitial ads after initialization
   AdViewInstlManager.getInstance(this).requestAd(this,SDK_KEY
);
   // You need to call it when the ads need to be displayed, t
he return is not null (review) there's an ad to return,
    otherwise it does not get ads.
    // The returned view can be placed in a customcontainer, su
ch as dialog
   AdViewInstlManager.getInstance(this).getInstlView (SDK_KEY)
    // Display report method should be called when successfully
 display (required)
   AdViewInstlManager.getInstance(this).reportImpression(SDK_K
EY);
    // When the ad is clicked, the click event handling method
should be called ,otherwise there will no response(required)
   AdViewInstlManager.getInstance(this).reportClick(SDK KEY);
```

Note:

Please refer to the code of popup Interstitial ad in **AdInstlActivity** in **AdViewTestDemoEN** Project.

VIII. Create opening screen ad

8.1 Create opening screen ad

Add the following code to your activity:

Example We are here used Relative Layout for Opening Screen ad,

```
<RelativeLayout xmlns:android="http://schemas.android.com/a
pk/res/android"
          android:id="@+id/spreadlayout"
          android:layout_width="match_parent"
          android:layout_height="match_parent"
          android:orientation="vertical" >
          </RelativeLayout>
```

Add the following code to your activity:

```
// Set the logo at the bottom of opening screen (not required),
you can also upload local images or images
   AdViewSpreadManager.getInstance(this).setSpreadLogo(R.drawa
ble.spread_logo);
```

```
// Set background color of opening screen( not required)
AdViewSpreadManager.getInstance(this).setSpreadBackgroudColor(
Color.WHITE);

// Request opening screen ads
AdViewSpreadManager.getInstance(this).request(this,SDK_KEY,this,(RelativeLayout) findViewById(R.id.spreadlayout));
```

8.2 Ad Opening screen Event Handling

To receive events from ad, you should implement an event listener interface AdViewSpreadListener.

After you implement this listener you will get the following methods.

```
public interface AdViewSpreadListener {
    * This function is called when the ad is displayed.
    */
    public void onAdDisplay(String key);
    /**
    * This function is called when the ad requestsucceeds.
    public void onAdReceived(String key);
    /**
    * Click to callback .
    public void onAdClick(String key);
    /**
    * This function is called when the ad request failed.
    */
    public void onAdFailed(String key);
    /**
    *This function is called when the ad is closed.
    public void onAdClose(String key);
    /**
    * Custom callback
    */
```

```
public void onAdNotifyCustomCallback(String key,ViewGro
up view,int ruleTime,int delayTime);
}
```

Note:

Please refer to the code of **SpreadScreenActivity** in **AdViewTestDemoEN** Project.

8.3 Custom notification on top of opening screen with countdown options

```
// Skip button will appears on the top after settings
AdViewSpreadManager.getInstance(this).setSpreadNotifyType(t
his, AdSpreadManager.NOTIFY_COUNTER_NUM);

// Defaults, none notification will be displayed
public final static int NOTIFY_COUNTER_NULL = 0;

// Countdown will be shown after settings
public final static int NOTIFY_COUNTER_NUM = 1;

// Skip button will be shown on the top after settings,but
it
will appear only after specified times.
public final static int NOTIFY_COUNTER_TEXT = 2;

// Will call this after settings:onAdNotifyCustomCallback(S
tring key,ViewGroup view,intruleTime,int delayTime)

//interface, you can custom notification styles
public final static int NOTIFY_COUNTER_CUSTOM = 3;
```

Note:

For opening advertising please make sure the exposure time is sufficient, otherwise it will affect the ad revenue.

Please refer to the code of **SpreadScreenActivity** in **AdViewTestDemoEN** Project.

IX. Create native advertising

9.1 create native advertising

Add a RecyclerView to layout file, e.g:

```
<android.support.v7.widget.RecyclerView
    android:id="@+id/list"
    android:layout_width="match_parent"
    android:layout_height="match_parent" />
```

Add the following code to your activity:

```
//Initialized native ads should custom ad layout in advance
, and apply native ad ID at app background
   AdViewNativeManager.getInstance(this).requestAd(this,SDK_KE
Y, 2,this);
```

```
/**
   * Please add this code in the onAdReceived call back.
    * For creating this call back method you can refer 9.2
   */
   // Ad successfully Received
   @Override
   public void onAdRecieved(String arg1, ArrayList arg0) {
        for (int i = 0; i < arg0.size(); i++) {
            Data data = new Data();
            NativeAdInfo nativeAdInfo = (NativeAdInfo) arg0.get
(i);
            data.title = ((NativeAdInfo) arg0.get(i)).getTitle(
);
            data.descript = nativeAdInfo.getDescription();
            data.icon = nativeAdInfo.getIconUrl();
            data.image= nativeAdInfo.getImageUrl();
            data.adInfo = (NativeAdInfo) arg0.get(i);
            ((NativeAdInfo) arg0.get(i)).getIconHeight();
            data.setAd(true):
            data.setType(STREAM AD);
            Log.i("Native info: ", "data.title:" + data.title +
 "\ndata.descript: " + data.descript + "\ndata.icon: "
                    + data.icon + "\ndata.image: " + data.image
 );
            list.add(3, data);
            ((NativeAdInfo) arg0.get(i)).onDisplay(new View(
                    AdNativeActivity.this));
        }
        adAdapter.notifyDataSetChanged();
   }
```

Note:

please refer to the code of **AdNativeActivity** in **AdViewTestDemoEN** Project.

please add DividerItemDecoration ,MyItemClickListener files for Native ad. you can get it from **AdViewTestDemoEN** Project .

9.2 Ad Native Event Handling

To receive events from ad, you should implement an event listener interface AdViewNativeListener.

After you implement this listener you will get the following methods.

```
public interface AdViewNativeListener {
    /**
    * This function is called when the ad request succeed.
    */
    public void onAdReceived(String key, List<NativeAdInfo>
adMaps);

/**
    * This function is called when ad request failed.
    */
    public void onAdReceived(String key);

/**
    * When the ad status changed.
    */
    public void onAdStatusChanged(String key, int status);
}
```

X. Create video advertising

10.1 create video advertising

Add the following code in activity,

```
//Request video ads after initialization. Request and displ
ay ads should be used separately.
   AdViewVideoManager.getInstance(this).requestAd(this,SDK_KEY
,this);

//set video callback interface
   // Call display ad after ad request succeed.
AdViewVideoManager.getInstance(this).playVideo(this,SDK_KEY
);
```

10.2 Ad Video Event Handling

To receive events from ad, you should implement an event listener interface AdViewVideoListener.

After you implement this listener you will get the following methods.

```
public interface AdViewVideoListener{
```

```
/**
     * Play start event notification
    public void onAdPlayStart(String key);
    /**
    * Play end event notification
    */
    public void onAdPlayEnd(String key, Boolean isEnd);
    /**
    * Close event notification
    public void onAdClose(String key);
    /**
    * Ad Ready notification
    public void onAdReady(String s);
    /**
    * Request succeed notification
    public void onAdReceived(String key);
    * Request failed notification
    public void onAdFailed (String key);
}
```

Note:

You can refer to the code of AdVideoActivity in AdViewTestDemoEN Project.

XI. Adding Proguard-rules

If you have a ProGuard configuration file please add the below lines of code in proguard-rules.pro file

```
-keep public class com.kyview.** {*;}
-keep public class com.kuaiyou.** {*;}
```

In case you add other adnetworks (like InMobi, AdMob etc..,) add their proguard rules to proguard-rules.pro file.

For example In case of InMobi add the below lines of code to the proguardrules.pro.

```
-keep class com.google.android.gms.ads.identifier.Advertisi
ngIdClient{
        public *;
    }
    -keep class com.google.android.gms.ads.identifier.Advertisi
ngIdClient$Info{
        public *;
    }
    -keep class com.inmobi.**
{ *; }
    -dontwarn com.inmobi.**
```

XII. Adding custom ad network


AdView has integrated various ad networks (InMobi, AdMob, etc...) where you are given flexibility to add the ad network of your choice and prioritize accordingly, there are various advantages of integrating more than one ad networks to monetize your app, some them include


- --> Good fill rates we suggest to include on an avrage of 3 ad netwroks for good fill rates
- --> More revenue
- --> You can prioritize according to the ad platform performance
 - 1. In your publisher dashboard http://adview.com/user/appreport click on the "App Management" tab --> click "Configure" against your app name

which you want to add custom ad networks, then click on "Add Platform" button (out of China or within China depending on your region) --> you will be redirected to the popup as shown below where you can choose ad netwrok of your choice.

Please select the ad platform to add							
select all							
Ad platform in China							
☐ Wow stick	Posture	Micro Cloud	Easy Media	MadNetwork Chi Road			
Dorman	□ Vpon	AdTouch	Anwar	Curtain one thousand			
AppMedia	Atrium	Baidu	Win Advertisement	☐ One hundred million ZAP			
Aidesiqi	Friends of the Union	_ Fei	US forces	Poly win			
Heat	Momarken	Chang Si (touch)	Pointing	Guang-point			
Tanx Mobile	360 Poly-efficient	More push	Easy integration	Should search			
Zhuo Yi	Jingdong	Hikarion	Hee Mobile Fun	9 Asahi			
Shun fly	European friends	Direct Advertising	Ad exchange	Auction ads			
Custom advertising							
Ad platform out of China							
MillennialMedia	Greystripe	✓ InMobi	□ DOTM	☐ ZestADZ			
Smaato	DoubleClick	Adlantis	MobFox				
Add Cancel							


2.In this example we will be adding InMobi as the custom Ad Netwrok, select InMobi in the popup and click on "Add" button, this will redirect you to the AdView dashboard --> here turn on the switch again InMobi give the priority(%) of your choice then click on "not set" in InMobi row you will get "Configure InMobi" popup with Signup link at the bottom which will redirect you to the below login page, complete the login procedure






Please add the SDK of InMobi--> please refer ${\bf add} \; {\bf sdk}$.


3. After login you will get the the account ID as shown in the below image, click on Add an App.




4.Please add your application (the same application you want to add custom Ad platform in AdView) by filling in the details as asked in below imgae, in case of any proguard rules in the Ad Network integration part just copy and paste them in proguard-rules.pro file in your project.



5.After adding the App to InMobi then click on the application name, where you will be redirected to the below window, please click on the option marked in the below image to get Placement ID.



6.Please copy the placement ID and Account ID which you need to add it in AdView dashobard as shown in the 2nd image



In the same way you can configure different custom Ad Networks to your app (different Ad networks might demand different ID's to be configured)

XII. Add custom ad platform

Sometimes developers would like to add a platform which is not aggregated, Adview provide ways to meet this demand.

There's a "Custom ad platform" in add ad platform. Developer needs to fill in app ID1, this is the name of a function which needs client side to complete. The function of this function is to call the ad platform interface. As for App ID2, just fill in something, otherwise you cannot save it.

Please select the ad platform to add								
select all								
Ad platform in China								
Dorman	Anwar	There are meters	Easy Media	Aidesiqi				
Easy integration	☐ In Cape	MadNetwork Chi Road	Elder	US forces				
Chi tour sinks	Chang Si (touch)	Pointing	Heat	Curtain one thousand				
Baidu	Guang-point	Clouds	Jufu	360 Poly-efficient				
☐ More push	Should search	Midi Midi	Millstone	Zhuo Yi				
Jingdong	Hee Mobile Fun	Hikarion	9 Asahi	Shun fly				
European friends	Direct Advertising	Ad exchange	Auction ads	✓ Custom table plaque				
Ad platform out of China								
☐ MobFox								
Add Cancel								

P	Please select the ad platform to add							
	select all							
	Ad platform in China							
	☐ Dorman	Anwar	There are meters	Easy Media	Aidesiqi			
	Easy integration	☐ In Cape	MadNetwork Chi Road	Elder	US forces			
	Chi tour sinks	Chang Si (touch)	Pointing	Heat	Curtain one thousand			
	Baidu	Guang-point	Clouds	_ Jufu	☐ 360 Poly-efficient			
	More push	Should search	Midi	Millstone	☐ Zhuo Yi			
	Jingdong	Hee Mobile Fun	Hikarion	9 Asahi	Shun fly			
	European friends	Direct Advertising	Ad exchange	Auction ads	Custom table plaque			
	Ad platform out of China							
	☐ MobFox							
		Ad	d	Cancel				

11.1 For Custom platform (Amazon) function implementation

```
// you can visit https://developer.amazon.com/sdk/mobileads
.html
   // Must with: final AdViewAdapter adapter, final String key
these two parameter
   // Otherwise will result in the failure in custom ad
    public void amazon_proc(final AdViewAdapter adapter, final S
tring key){
   // TODO Auto-generated method stub
   AdRegistration.enableLogging(this, true);
   AdRegistration.enableTesting(this, true);
   AdRegistration.setAppKey(this, "sample-app- v1_pub-2");
   // Create an example of amazon in adview
   adView = new AdLayout(this, AdSize.AD_SIZE_320x50);
   //appointed listen interface
    adView.setListener(new AdListener() {
   @Override
    Log.d("AdViewSample", arg1.getAdType().toString()+ " Ad loa
ded successfully.");
    // after the ad request succeed, start the timer and reques
t another ad when time's up.
    adapter.reportImpression(key);
    adapter.rotateDelayedAd(key);
   }
   @Override
   public void onAdExpanded(AdLayout arg0) {
    // TODO Auto-generated method stub
   }
   @Override
    public void onAdCollapsed(AdLayout arg0) {
    // TODO Auto-generated method stub
   }
   @Override
   public void onAdFailedToLoad(AdLayout arg0, AdError arg1) {
    // TODO Auto-generated method stub
    Log.w("AdViewSample","Ad failed to load. Code: "+ arg1.getR
esponseCode() +", Message: "+arg1.getResponseMessage());
   // start to request another ad when failed.
    adapter.rotatePriAd(key);
```

```
}
});
AdViewBannerManager.getInstance(AdBannerActivity.this).addS
ubView(AdViewBannerManager.getInstance(AdBannerActivity.this).
    getAdViewLayout(AdBannerActivity.this,key), adView, key);
AdTargetingOptions adOptions = new AdTargetingOptions();
adView.loadAd(adOptions);
}
```

**You can refer the code in AdViewTestDemoEN project --> BannerActivity for implementation of Amazon ad; **

XIII. Contact us

Users can login Adview, there are service E-mail, service contact number and enterprise QQ customer service at the bottom of the homepage

