

Pitch acceptance: errors by motion direction

20 acceptance cases | 1 kHz linear SMC | 16 s per case

RMS error (mrad)
Each-direction gate: < 20 mrad

PEAK error (mrad)
Each-direction gate: < 60 mrad

Standard3 / DM4310 Nominal	1.96	0.66	1.32	2.81	1.79	1.92
Standard3 / DM4310 Gravity FF x0.8	1.37	2.39	1.80	2.92	4.24	3.47
Standard3 / DM4310 Gravity FF x1.2	4.07	2.79	3.72	6.76	5.87	5.93
Standard3 / DM4310 Unmodeled payload	1.13	2.83	1.71	1.82	3.88	2.56
Standard3 / DM4310 15 deg tilt / correct frame	1.97	0.66	1.32	2.83	1.78	1.91
Standard3 / GM6020 Nominal	1.96	0.66	1.32	2.82	1.79	1.91
Standard3 / GM6020 Gravity FF x0.8	1.37	2.39	1.80	2.92	4.24	3.47
Standard3 / GM6020 Gravity FF x1.2	4.07	2.79	3.72	6.76	5.87	5.93
Standard3 / GM6020 Unmodeled payload	1.13	2.83	1.71	1.82	3.87	2.56
Standard3 / GM6020 15 deg tilt / correct frame	1.97	0.66	1.32	2.82	1.79	1.91
RMUA19 / DM4310 Nominal	3.96	1.32	2.59	5.54	3.36	3.72
RMUA19 / DM4310 Gravity FF x0.8	1.14	3.19	1.04	2.27	5.05	2.49
RMUA19 / DM4310 Gravity FF x1.2	9.26	3.80	5.70	19.24	6.53	7.31
RMUA19 / DM4310 Unmodeled payload	2.11	5.62	3.27	3.54	7.89	4.91
RMUA19 / DM4310 15 deg tilt / correct frame	3.97	1.31	2.59	5.53	3.37	3.71
RMUA19 / GM6020 Nominal	3.96	1.31	2.59	5.53	3.37	3.71
RMUA19 / GM6020 Gravity FF x0.8	1.14	3.19	1.04	2.28	5.04	2.49
RMUA19 / GM6020 Gravity FF x1.2	9.23	3.81	5.70	19.73	6.54	7.30
RMUA19 / GM6020 Unmodeled payload	2.11	5.61	3.27	3.53	7.87	4.90
RMUA19 / GM6020 15 deg tilt / correct frame	3.97	1.31	2.59	5.54	3.37	3.71
	Upward	Downward	Hold	Upward	Downward	Hold



Fraction of each metric's gate (1.0 = threshold)

Synthetic single-axis models. Startup [0,1) excluded from tracking only; up / down / hold each include all 5 s of their phase.
Wrong-frame diagnostics are reported separately. No hardware or soft-limit certification.