Aanlyst : Benjamin Liu

Date : 3/30/2026

Hunt 1 (1/3) - What is the IP address from which the suspicious brute force traffic is seen? (Format: X.X.X.X) *(6 points)*

192.168.1.20 Correct! ✔

```
H1 - Brute Force Detected
Source: winevent-security
```

Filter failed with EventId 4625 (An account failed to log on).




```
> Apr 14, 2021 @ 10:54:02.363760000   @timestamp: Apr 14, 2021 @ 10:54:02.363760000  Event_#attributes_xmlns: http://
  Event_EventData_FailureReason: %%2313  Event_EventData_IpAddress: 192.168.1.20
```

Hunt 1 (2/3) - What is the observed logon type? (Format: Logon Type Name) *(6 points)*

network Correct! ✔

```
> Apr 14, 2021 @ 10:54:02.363760000   @timestamp: Apr 14, 2021 @ 10:54:02.363760000  Event_#attributes_xmlns:
  Event_EventData_FailureReason: %%2313  Event_EventData_IpAddress: 192.1
  Event_EventData_LogonProcessName: NtLmSsp  Event_EventData_LogonType: 3
```

logon type is 3.

AI Mode All Images Videos Forums Shopping Short videos More Tools

ManageEngine
https://www.manageengine.com › products › what-is › l...

Windows logon type 3

Logon type 3 denotes a network logon. A network logon or any other logon can take place only after an interactive logon authentication has taken place. Read more

Hunt 1 (3/3) - What is the time of the first successful logon after the brute force? (Format: Format:DD-MM-YYYY hh:mm:ss) *(6 points)*

14-04-2021 10: 56: 30 Correct! ✔

there are 1804 failed log on attemps. And all of them are from network log on. So keep logon type 3 and filter EventID 4624(An account was successfully logged on)




```
H2 - Windows Defender Bypass
Source: sysmon/winevent-powershell
```

Hunt 2 (1/2) - What is the full command used for bypassing the defender scan on the malicious file? (Format: powershell.exe ... Full Command (Do not include the file path)) *(6 points)*

powershell.exe -inputformat none -outputformat none -NonInteractive -Command Add-MpPreference -ExclusionPath

For detect the command for bypassing the defender scan on the malicious file, I do research and get answers as follow:

- 1. Monitor for Defender Configuration Changes

  Attackers often bypass scans by adding the malicious file or its folder to the **Exclusion List**. You can detect the commands used for this by looking for specific PowerShell activity:

  - **Search for Cmdlets**: Look for `Add-MpPreference` or `Set-MpPreference` with the `-ExclusionPath`, `-ExclusionExtension`, or `-ExclusionProcess` parameters.
  - **Check Windows Event Log**:
    - **Event ID 5007**: Configuration has changed. This log will show if an exclusion was added or a feature like Real-Time Protection was disabled.
    - **Event ID 1116 & 1117**: These show when a threat is detected and what action was taken. If a bypass was successful, you might see a "detected" event followed by no remediation if the user or a script intervened.
  - **PowerShell Script Block Logging (Event ID 4104)**: This is critical for capturing the **full text** of a command, even if it was obfuscated or base64 encoded.
- 3. Review Defender Operational Logs

For deeper forensics on how Defender handled a specific file, check the dedicated operational logs:

  - **Path**: `Applications and Services Logs > Microsoft > Windows > Windows Defender > Operational`.
  - **Offline Scan Logs**: If the bypass involved the offline scanner, logs are stored in `C:\Windows\Microsoft Antimalware\Support` with the naming convention `MPLog-<date>-<time>.log`.
- 4. Detection via Command Line Tools

You can query the current state of Defender to see if any suspicious bypasses (like exclusions) are currently active:

  - **PowerShell**: Run `Get-MpPreference` to see all current exclusions and protection settings.

- **MpCmdRun.exe**: Use the Defender command-line tool located in `%ProgramFiles%\Windows Defender` to run a custom scan and check for skipped paths, which may indicate a hidden exclusion

Hunt 2 (2/2) - What is the filename of the malicious application? (Format: filename.extension)

chroma.exe



H3 - WannaCry KillSwitch Domain
Source: sysmon

Hunt 3 (1/2) - What is the domain name? (Format: domain.tld) *(6 points)*

ayylmaotjhsstasdfasdfasdfasdfasdfasdfas

Correct! ✔





Hunt 3 (2/2) - What is the Execution ProcessID and ThreadID? (Format: pid, tid) *(7 points)*

2724, 4260 Correct! ✔

By clicking one item from the list, we will find more details about the log. we can get the PID and TID.

# Event_System_Execution_#attributes_ProcessID	2,724
# Event_System_Execution_#attributes_ThreadID	4,260

Hunt 4 (1/1) - What is the full path of the exe used for dumping password? (Format: C:\path\to\file.extension) *(7 points)*

C:\Users\nightmare\Desktop\mimi\x64\mim Correct!

filter the log with EventId:1 Or 10. We get 203 items. then we know the duming password shoud be after the event of log successfully at 10:56:30 on 14-04-2021. And we know it may be at the middle or end part of the investigation because it is the stage of actions on objectives.