

错误分类

错误一般可分为两种：

- 语法错误：又称解析错误（语法分析器检查到的错误）
- 异常错误：在运行时检测到的错误（程序的语法是正确的）

处理异常

try ... except ...

- 如果在执行 **try** 子句时没有异常发生，则不会执行 **except** 子句
- 如果 **try** 子句发生了异常，则跳过该子句中剩下的部分，执行 **except** 子句
- 如果 **except** 子句没有指定异常类型，则可以处理 **try** 中的所有异常类型
- 如果 **except** 子句指定了异常类型，则只能处理对应的异常类型（指定多个异常类型时，可以用元组来表示）
- 如果一个异常没有与任何的 **except** 匹配，则报错

```
def div(a, b):  
    try:  
        c = a / b  
        print(f"{a} / {b} = {c}")  
  
    except:  
        print('try中发生异常')
```

```
div(2, 1)  
div(2, 0)  
div('2', 2)
```

```
def div(a, b):  
    try:  
        c = a / b  
        print(f"{a} / {b} = {c}")  
  
    except ZeroDivisionError:  
        print('try中发生了除数为0的异常')  
  
    except TypeError:  
        print('try中发生了类型异常')
```

```
div(2, 1)  
div(2, 0)  
div('2', 2)
```

```
def div(a, b):
    try:
        c = a / b
        print(f"{a} / {b} = {c}")

    except (ZeroDivisionError, TypeError):
        print('try中发生了除数为0的异常或者类型异常')

div(2, 1)
div(2, 0)
div('2', 2)
```

try ... except ... else ...

- else 子句必须放在所有的 except 子句之后
- else 子句将在 try 子句没有发生任何异常的时候执行

```
def div(a, b):
    try:
        c = a / b
        print(f"{a} / {b} = {c}")

    except ZeroDivisionError:
        print('try中发生了除数为0的异常')

    except:
        print('发生了除0以外的异常')

    else:
```

```
print('try中没有异常')
```

```
div(2, 1)
```

```
div(2, 0)
```

```
div('2', 2)
```

try ... except ... as ...

- as 后面为异常实例对象的名称

```
def div(a, b):
```

```
    try:
```

```
        c = a / b
```

```
        print(f"{a} / {b} = {c}")
```

```
    # e: ZeroDivisionError('division by zero')
```

```
    except ZeroDivisionError as e:
```

```
        print(type(e) is ZeroDivisionError)
```

```
        print(e)
```

```
        print(ZeroDivisionError('division by zero'))
```

```
    except Exception as e:
```

```
        print(type(e) is TypeError)
```

```
        print(e)
```

```
div(2, 0)
```

```
div(2, '0')
```

try ... finally ...

- finally 子句将作为 try 语句结束前的最后一项任务被执行
- 不论 try 语句是否产生了异常都会被执行

```
def div(a, b):  
    try:  
        c = a / b  
        print(f"{a} / {b} = {c}")  
  
    finally:  
        print("执行finally子句")  
  
div(2, 0)
```

```
def div(a, b):  
    try:  
        c = a / b  
        print(f"{a} / {b} = {c}")  
  
    except:  
        print('except在发生异常时执行')  
  
    else:  
        print('else在没有异常时执行')  
  
    finally:  
        print('finally在任何情况下都会被执行')
```

```
div(2, 1)
div(2, 0)
```

抛出异常

- `raise` 语句可以主动的抛出异常
- `raise` 后面可以是 异常实例 / 异常类 / 没有内容

```
def div(a, b):
    if b == 0:
        raise ZeroDivisionError('除数为0')

    c = a / b
    print(f"{a} / {b} = {c}")

div(2, 1)
div(2, 0)
```

```
def div(a, b):  
    if b == 0:  
        raise ZeroDivisionError  
  
    c = a / b  
    print(f"{a} / {b} = {c}")  
  
div(2, 1)  
div(2, 0)
```

```
def div(a, b):  
    if b == 0:  
        raise  
  
    c = a / b  
    print(f"{a} / {b} = {c}")  
  
div(2, 1)  
div(2, 0)
```

assert 断言

- `assert` 用于判断一个表达式，在表达式为 `False` 的时候触发 `AssertionError` 异常

- `assert expression` 等价于
`if not expression: raise AssertionError`
- `assert expression [, arguments]`
等价于: `if not expression: raise AssertionError(arguments)`

```
num = int(input("请输入一个整数: "))  
assert num % 2  
print(f'{num}为奇数')
```

```
num = int(input("请输入一个整数: "))  
if not num % 2:  
    raise AssertionError  
print(f'{num}为奇数')
```

```
num = int(input("请输入一个整数: "))  
assert num % 2, f'断言失败, {num}是偶数'  
print(f'{num}为奇数')
```

```
num = int(input("请输入一个整数: "))  
if not num % 2:  
    raise AssertionError(f'断言失败, {num}是偶数')  
print(f'{num}为奇数')
```