

一、OpenManus 环境搭建

NOTE: 可以选择 DSW 服务器，建议镜像选择: pytorch-develop:2.1-gpu-py311-cu118-ubuntu22.04
—> 也可以选择一台普通的 CPU 服务器；

NOTE: 如果选择的环境没有安装 python 环境，需要安装 python 环境，建议直接安装 mini-conda。

NOTE: Python 版本至少 3.11+（建议不要选择 3.12）

▼ 安装 python

Bash

```
wget https://repo.anaconda.com/miniconda/Miniconda3-py311_25.1.1-1-Linux-x86_64.sh
```

```
sh Miniconda3-py311_25.1.1-1-Linux-x86_64.sh
```

安装完成后，退出重新进入

1. 从 github 官网下载对应的源码 OpenManus

Bash

```
git clone https://github.com/FoundationAgents/OpenManus.git
```

```
cd OpenManus
```

```
git tag -l
```

```
git checkout v0.3.0
```

2. 安装依赖环境（实际应用中，可选: 创建一个虚拟环境）

Python

```
pip install -r requirements.txt
```

或者使用uv进行依赖环境安装

```
pip install uv
```

```
uv pip install --system -r requirements.txt
```

3. 修改模型配置，采用 DeepSeek 模型

Bash

复制配置文件

```
cp config/config.example.toml config/config.toml
```

修改模型

```

[llm]
model = "deepseek-chat"          # The LLM model to use
#base_url = "https://api.deepseek.com/v1" # API endpoint URL
base_url = "https://gateway.ai.cloudflare.com/v1/67b8ebfcb6b836e009e1fb540f160fa5/nlp_0913/deepseek/v1" # API endpoint URL
api_key = "sk-xxxx"              # Your API key
max_tokens = 8192                # Maximum number of tokens in the response
temperature = 0.0                # Controls randomness

[llm.vision]
model = "qwen/qwen2.5-vl-32b-instruct:free" # The vision model to use
base_url = "https://openrouter.ai/api" # API endpoint URL for vision model
api_key = "sk-or-v1-xxxx"             # Your API key for vision model
max_tokens = 8192                    # Maximum number of tokens in the response
temperature = 0.0                    # Controls randomness for vision model

# 安装浏览器插件
playwright install
playwright install-deps

=====
(base) root@iZbp15dscmm321tx32xls0Z:~/OpenManus# playwright install
Downloading Chromium 134.0.6998.35 (playwright build v1161) from https://cdn.playwright.dev/dbazure/download/playwright/builds/chromium/1161/chromium-linux.zip
164.9 MiB [=====] 100% 0.0s
Chromium 134.0.6998.35 (playwright build v1161) downloaded to /root/.cache/ms-playwright/chromium-1161
Downloading Chromium Headless Shell 134.0.6998.35 (playwright build v1161) from https://cdn.playwright.dev/dbazure/download/playwright/builds/chromium/1161/chromium-headless-shell-linux.zip
100.9 MiB [=====] 100% 0.0s
Chromium Headless Shell 134.0.6998.35 (playwright build v1161) downloaded to /root/.cache/ms-playwright/chromium_headless_shell-1161
Downloading Firefox 135.0 (playwright build v1475) from https://cdn.playwright.dev/dbazure/download/playwright/builds/firefox/1475/firefox-ubuntu-24.04.zip
90.6 MiB [=====] 100% 0.0s
Firefox 135.0 (playwright build v1475) downloaded to /root/.cache/ms-playwright/firefox-1475
Downloading Webkit 18.4 (playwright build v2140) from https://cdn.playwright.dev/dbazure/download/playwright/builds/webkit/2140/webkit-ubuntu-24.04.zip
92 MiB [=====] 100% 0.0s
Webkit 18.4 (playwright build v2140) downloaded to /root/.cache/ms-playwright/webkit-2140
Downloading FFMPEG playwright build v1011 from https://cdn.playwright.dev/dbazure/download/playwright/builds/ffmpeg/1011/ffmpeg-linux.zip
2.3 MiB [=====] 100% 0.0s
FFMPEG playwright build v1011 downloaded to /root/.cache/ms-playwright/ffmpeg-1011
Playwright Host validation warning:

```

```
|| Host system is missing dependencies to run browsers. ||
|| Please install them with the following command: ||
||
||     playwright install-deps
||
|| Alternatively, use apt:
||     apt-get install libatk1.0-0t64\
||         libatk-bridge2.0-0t64\
||         libcups2t64\
||         libxcomposite1\
||         libxdamage1\
||         libxfixes3\
||         libxrandr2\
||         libgbm1\
||         libpango-1.0-0\
||         libcairo2\
||         libasound2t64\
||         libatspi2.0-0t64
||
|| <3 Playwright Team
```

=====

4. 运行测试

纯文本

```
python main.py
```

```
# 输入内容:
```

```
# 我需要一份10月1日从上海出发的7天北京行程，我的家人和我的总预算为10000元左右，两大两小。我们喜欢历史遗迹和自然风光。我们想看看故宫、长城、博物馆之类的。请提供详细的行程和简单的HTML旅行手册，其中包含地图、景点描述、住宿、饮食和旅行提示等，我们可以在整个旅程中参考。
```

```
# 查询一下最新的MCP相关资料，整理一下最常用的10个MCP，以及它们对应的使用方式
```