

# Components

A React "Component" returns JSX/HTML

- A js function
  - "function-based component" or
  - "functional component"
- Old style is "class-based"
  - We won't be using those
    - Almost no one does: old
  - **Warning:** React docs are years out of date :(
  - See <https://beta.reactjs.org/> instead

# Components are Tags

A React Component can be used as an Element in JSX

- Open/close or self-closing
  - NO: `<Greeting>` (Needs a close somewhere)
  - YES: `<Greeting/>`
  - YES: `<Greeting></Greeting>`
- Element name matches function name
  - MixedCase, not camelCase
  - YES: `<Greeting/>` or `<CatVideos/>`
  - NO: `<greeting/>` or `<catVideos/>`

# HTML Elements in JSX are actually JSX

- Work like actual elements
  - Mostly (But it's good)
- All elements, HTML-based or not, are **consistent**
- All elements can be open/close or be self-closing
- **All elements require a close of some sort in JSX!**
- NO: `<input name="name">`
- YES: `<input name="name"/>`
- YES: `<input name="name"></input>` (but why?)

# Components are not files

OFTEN a `.jsx` file is exactly 1 component

- This is not required by React

## Course Requirements:

- One `.jsx` file === one component
- Filename must match component name
- Component must be MixedCase

Outside of course, then can change

# Components are a single container

Can have any nested elements/components

- MUST have a **single parent container element**
  - YES:

```
function Greeting() {  
  return (<div>Hello<p>World</p></div>);  
}
```

- NO:

```
function Greeting() {  
  return (<div>Hello</div><p>World</p>);  
}
```

- OR be a **fragment**

# Example of single parent container

This works:

```
function CatFacts() {  
  return (  
    <div className="cat-facts">  
      <h1>Cat Facts</h1>  
      <div className="subtitle">Number 3 will shock you</div>  
      <ul>  
        <li>Cats can rotate their ears 180 degrees</li>  
        <li>Felines can purr or roar, but not both</li>  
        <li>Humans domesticated dogs,  
          but cats domesticated humans</li>  
      </ul>  
    </div>  
  );  
}  
  
export default CatFacts;
```

# Example without single parent container

This will give you an error:

```
function CatFacts() {  
  return (  
    <h1>Cat Facts</h1>  
    <div className="subtitle">Number 3 will shock you</div>  
    <ul>  
      <li>Cats can rotate their ears 180 degrees</li>  
      <li>Felines can purr or roar, but not both</li>  
      <li>Humans domesticated dogs,  
        but cats domesticated humans</li>  
    </ul>  
  );  
}  
  
export default CatFacts;
```

# You need to use fragments

"Just put all our of component output in a `<div>`?"

- No
- If the parent container element isn't useful
  - Not semantic
  - Not styled or impacting styling
  - Not listening to events
- Use a **fragment** instead



# How to use a Fragment

```
function Demo() {  
  return (  
    <>  
      <p>  
        These p tags will have no containing  
        element from this component  
      </p>  
      <p>And React will not complain</p>  
    </>  
  );  
}
```

- `<>` and `</>`
- React treats like a containing element
- But no element in output HTML

# imports

Even without React, we want multiple files to organize

- Big files = hard to manage/maintain

CRA includes a **bundler** program

- Lets us use many files in dev
- Outputs to fewer files in prod

Syntax is not browser JS

- Bundler converts

# Importing JSX

Write a `Test.jsx` in `src/`

```
function Test() {  
  return (  
    <p>Hello World</p>  
  );  
}  
export default Test;
```

Top of `App.jsx`:

```
import Test from './Test';
```

Near end of `App.jsx`:

```
<Test/>  
</header>
```

# The parts of importing

- Say what you want to export
- Say what you are importing
  - And from where
- Use what you've imported

We will start with discussing **component imports** first

- Other imports are different rules

# Say what you are exporting

At end of file:

```
export default VARIABLE_NAME;
```

Example:

```
function CatVideo() { /* ... */ }  
export default CatVideo;
```

- Exported default variable should match filename
  - For ease of use, not system requirement
- There are other export options
  - We won't use them yet
- This isn't JS that works in browser
  - Converted by tools that CRA gives us

# Say what you are importing

...and from where

```
import CatVideo from './CatVideo';  
import Component from './Filename';
```

- Can be single or double quotes
- **Component** is the name you will use
  - **Course Requirement:** must match filename
- **Filename** is the filename
  - You need an explicit path (**./**)
  - Can be a different directory
  - Do not need a file extension
    - Will import **.jsx** or **.js**

# Using your imported Component

Use an imported Component in a HTML-like JSX tag:

```
import Test from './Test';

function Demo() {
  return (
    <div className="demo">
      <Test/>
    </div>
  );
}
export default Demo;
```

Any file can import other files

- Gets weird/breaks if you make a circle
  - A uses B, and B uses A
  - Don't do that

# importing CSS

CRA allows you to import CSS files

```
import './App.css';
```

- Makes the CSS available on the HTML page
  - No `<link>` required
- Filename can be anything
  - Does not have to be MixedCase
  - Must have `.css` extension
  - Must have a path (e.g. `./`)



# Organizing your CSS files

- Many options
  - All in `src/index.css`
  - Mostly in css imported by `App.jsx`
  - CSS for each Component
    - Imported in those components?
- React has even more CSS options not seen yet

# Course Requirements for CSS in React

## Course Requirements:

- Any filenames
- import where you want
- MUST have some organization
  - Not all one big file when lots of CSS
- MUST be in imported `.css` files
  - Should feel like CSS in course so far
  - No styled components, CSS modules, etc

# importing images

importing images LOOKS like importing Components:

```
import someImage from './cat-pic.jpg';
```

There are important differences:

- You pick a variable name to import as
- The filename needs to be complete
  - including file extension
  - and path
- Variable holds the path to the image as a string:
  - `<img src={someImage} alt="smug cat"/>`

# **importing JS**

We will cover this more later

- but all components are JS

# Component Props

Components have attribute-like values:

```
<Greeting target="world"/>
```

These are called "props"

- Allow you to pass values to Components
- Allows for flexibility and reuse

```
<Greeting target="class"/>  
<Greeting target="world"/>
```

```
<p>Hello class</p>  
<p>Hello world</p>
```

# Prop values

Unlike HTML, props can hold more than strings

- non-strings must be in `{}`

Unlike HTML, props should ALWAYS have a value

- not there/not there like `disabled` or `checked`

```
<CatList cats={['Jorts', 'Jean', 'Nyancat']}/>
```

```
<ul class="cats">
  <li>Jorts</li>
  <li>Jean</li>
  <li>Nyancat</li>
</ul>
```

# Reading passed props

A Component function is passed an object of all props

```
<CatList cats={['Jorts', 'Jean', 'Nyancat']}/>
```

```
function CatList( props ) {  
  const list = props.cats.map( cat => {  
    return (  
      <li>{cat}</li>  
    );  
  });  
  
  return (  
    <ul className="cats">  
      {list}  
    </ul>  
  );  
}  
export default CatList;
```

# Destructuring props

Common to **destructure** props object to get variables

```
function CatList( { cats } ) {  
  const list = cats.map( cat => {  
    return (  
      <li>{cat}</li>  
    );  
  });  
  
  return (  
    <ul className="cats">  
      {list}  
    </ul>  
  );  
}  
export default CatList;
```



# Error Messages in React are usually helpful

- Check browser console after adding
- `<CatList cats={['Jorts', 'Jean', 'Nyancat']} />`

Warning: Each child in a list should have a unique "key" prop

Check the render method of `CatList`.

See <https://reactjs.org/link/warning-keys>  
for more information

- Actually really helpful!
- Complete with link to learn more!

# Errors vs Warnings

- Technically, that was a **warning**
  - Doesn't stop the program from running
    - May not be *working*
- **Errors** stop a program from running
  - Try not closing a Component/element

Even though a warning doesn't stop the program

- **You should resolve warnings right away**
- It is literally a likely bug
  - Could impact what you're doing now

# What is this warning saying?

- Wants `key` prop on each component in list
  - `key` must have a unique value
- React rewrites HTML when data changes
  - It wants to do so EFFICIENTLY
  - If you give me a list, then later give me list
  - Which added/removed vs changed?
- We need to identify the items of a list
  - And `list` is an array (list) of `<li>` elements

# Can I use the index as the key?

- No
  - Well, Yes, but you shouldn't
- It will silence the warning
- But is actually WORSE
  - If an element is removed
    - Index will not LIE
    - Index does not uniquely identify
      - Index can refer to different elements

**Do not use index for a key prop of a list**

# What DO I use as a key prop?

Use a value uniquely connected to the data in element

- Accurately say "is this the list item as last time"
- Complex records normally have an identifier
  - Ex: NEUID
- Simple records build one from data
  - Might be combination of fields
  - Or just one field:

```
const list = cats.map( cat => {  
  return (  
    <li key={cat}>{cat}</li>  
  );  
});
```

# All About key Prop

- Use when outputting array of elements in JSX
  - Pass `key={}` on each element
  - Use a value that identifies the element
    - Do not pass `index` as `key`

# Events

Components are JS that outputs HTML

- So how do we attach event listeners to HTML?

# "on" Handlers

```
function doMeow() {  
  console.log('meow');  
}  
  
function Meow() {  
  return (  
    <p onClick={doMeow}>Meow</p>  
  );  
}  
  
export default Meow;
```



## But WAIT!

Didn't we say NOT to use "onclick" in HTML?!

**Yes!**

- But this isn't HTML
- It LOOKS like HTML, but isn't
- Differences are subtle but real
  - React will translate it more like `.addEventListener()`

# Comparing

Bad:

```
<p onclick="function() { console.log('meow') }">Meow</p>
```

- Editing JS in HTML
  - All in a string of attribute value
  - Hard to interact with other JS

Good:

```
<p onClick={ () => console.log('meow') }>Meow</p>
```

- Editing JS in JSX (which is just JS)
- No weird scope or variable changes

# Only HTML elements can get events

## Events don't happen to Components

- You can pass props
- No built in behavior, just a name
- Component can apply to returned HTML element
  - Which DOES have built-in behavior

```
function Meow({ onClick }) {  
  return (  
    <p onClick={onClick}>Meow</p>  
  );  
}  
  
export default Meow;
```

# Wait, What?

- Components can be passed props like `onClick`
  - But it is just a name
  - No Behavior
- Component CAN use/pass the passed prop
- Native Elements DO have behavior for `onClick`

```
function Meow({ onClick }) {  
  return (  
    <p onClick={onClick}>Meow</p>  
  );  
}  
  
export default Meow;
```

```
<Meow onClick={ () => console.log('meow') }/>
```

# Summary - Components

Components:

- Functions that return HTML/JSX
  - or class-based component
- Can be nested
- Passed **props**
- Must have a single parent element
  - Or be **fragment**
- Must be named in MixedCase
- FOR THIS COURSE:
  - 1 component per `.jsx` file (must be `.jsx`)
  - Filename matches component name

## Summary - imports/exports

- A component can be exported from a file
- A component can be imported from an export
- A CSS file can be imported
  - Many options on how to organize/approach
  - CSS imports not needed in all components
- An image path can be imported
- All imports need an explicit path

### FOR THIS COURSE:

- CSS classes should be `kebab-case` or BEM
- No styled-components, CSS Modules, etc

# Summary - props

Components have **props** passed in JSX

- Received in `props` object passed to JS function
  - Often **destructured** to named variables
- Props can hold string or non-string values
- Event handler props have no behavior on components
  - But can be passed to HTML elements

# Summary - event handlers

Event handlers go on HTML tags in JSX

- Looks like HTML JS attributes
  - But aren't
- Must be `onEVENT` syntax
  - EVENT is a capitalized event name
  - So `onEVENT` will be camelCase
  - e.g. `onClick`, `onInput`, `onChange`
- Event handler props don't work on components
  - But can be put on HTML elements